

CS2105 Introduction to Computer Networks

Basics

- Circuit switching:**
Call setup required
Circuit-link (guaranteed) performance
Circuit segment idle if not used by call (no sharing)
- Packet switching:**
Share network resources
Resources used on demand
Excessive congestion is possible
Sender breaks message into pkts; receiver reassembles them
- Processing delay:** Check bit errors; determine output link
- Queuing delay:** Waiting in queue for transmission
- Transmission delay:** Time taken to push bits onto link
- Propagation delay:** Time for bits to travel in link
- End-to-end packet delay:** Time for packet to travel from source to destination
- Throughput:** Bits transmittable per unit time for end-to-end communication

Application message Transport segment
Network datagram Link frame

Application Layer

SSH : 23 [TCP]

Common Protocols

App. Protocol	Tpt. Protocol	Port
HTTP	TCP	80 (default)
HTTPS	TCP	443 (default)
DNS	UDP	53
SMTP	TCP	25
DHCP	UDP	67 (svr) 68 (client)
RIP	UDP	520

Hypertext Transfer Protocol

- HTTP 1.0 closes connection after transmitting single object
- HTTP 1.1 uses persistent connection by default (possibly with pipelining)
- HTTP request message:** (terminates with double CRLF)
GET /cs2105/demo.html HTTP/1.1
Host: www.comp.nus.edu.sg
User-Agent: Mozilla/5.0
Connection: close
Cookie: name=value; name2=value2; name3=value3
- HTTP response message:**
HTTP/1.1 200 OK
Date: Thu, 15 Jan 2018 13:02:41 GMT
Content-Type: text/html
Content-Length: 150
Set-Cookie: name=value


data data data...
- Conditional GET:**
If-Modified-Since: Thu, 15 Jan 2018 13:02:41 GMT
Server may reply with 304 Not Modified

Domain Name System

- Mapping between hostname and IP address (and others) are stored as resource records (RR)
- RR format: (name, value, type, ttl)**

type	name	value
A	hostname	IP address
NS	domain (nus.edu.sg)	hostname of authoritative NS
CNAME	alias name	canonical name

- 13 root servers globally that answer NS queries for TLDs
 - Local DNS server caches mapping and acts as proxy**
↳ expires only after TTL
- Dynamic Host Configuration Protocol




- May also provide other network information:
- first-hop router, local DNS server, subnet mask (default gateway)

Transport Layer

TCP vs UDP

- Transmission Control Protocol:**
Reliable transport
Flow control (sender won't overwhelm receiver)
Congestion control (throttle sender in overloaded network)
Does not provide timing, minimum throughput guarantee, security
- User Datagram Protocol:**
Unreliable data transfer
Does not provide reliability, flow control, congestion control, timing, minimum throughput guarantee, security
- Socket:** Interface between application and transport layers
TCP uses a stream socket
UDP uses a datagram socket
- TCP and UDP ports are distinct; port num may be reused
- TCP creates a new socket for each client (using the same server port), but uses client IP and client port to distinguish clients
- Checksum:** 1's complement sum of 16-bit integers = 0b1111111111111111
To compute checksum, remember to invert the sum

- Multiplexing:** When receiving packet from network layer, TCP/UDP must read transport header to decide which socket to deliver the message to (de-multiplexing); when sending messages from application layer, TCP/UDP must combine packets from different messages into the same network interface (multiplexing)
- UDP connectionless de-multiplexing:** decide using destination port only
- TCP connection-oriented de-multiplexing:** decide using (src IP addr, src port, dest IP addr, dest port)



Reliable Data Transfer (Stop & wait protocol)

- rdt 1.0:** Perfectly reliable
- rdt 2.0:** May corrupt packets
Stop-and-wait protocol; receiver sends ACK or NAK back
Fatal flaw if ACK is corrupted, because sender will resend packet and receiver will treat it as new packet
- rdt 2.1:** To fix rdt 2.0, add 1-bit sequence number to each packet; receiver can now detect and discard duplicate packet (but must still send ACK for the duplicate packet)
- rdt 2.2:** Same functionality as rdt 2.1, but is NAK-free; receiver ACKs sequence number of last received packet
- rdt 3.0:** May corrupt packets, may lose packets, may incur arbitrary long packet delay
Sender waits "reasonable" amount of time for ACK, and retransmits if ACK is not received before timeout; sequence number included in both data and ACK just like rdt 2.2

Pipelining

- Go-back-N:**
Sender:
 - Up to N unACKed packets in pipeline
 - k-bit sequence number
 - "sliding window" to keep track of unACKed packets
 - timer for oldest unACKed packet
 - if duplicate ACK of sender then does nothingReceiver:
 - Only ACK packets that arrive in order
 - Discards out of order packets and ACK the last in-order sequence number ("cumulative ACK")

- Selective repeat:**
Receiver individually ACKs all correctly received packets; buffers out-of-order packets as needed
Sender maintains timer for each unACKed packet; if timer expires, retransmit only that unACKed packet

TCP Reliability

- TCP sequence number:** "byte number" of first byte of data in a segment
- TCP acknowledgement number:** sequence number of next byte expected ("cumulative ACK")
- Maximum segment size:** maximum number of data bytes
Maximum packet size: includes header bytes
- TCP delayed ACK:** Wait up to 500ms for second segment; use one ACK for two segments only
- Dynamic TCP timeout:**
SampleRTT := RTT of new packet
EstRTT ← (1 - α) × EstRTT + α × SampleRTT
(typically α = 0.125)
DevRTT ← (1 - β) × DevRTT + β × |SampleRTT - EstRTT|
(typically β = 0.25)
TimeoutInterval ← EstRTT + 4 × DevRTT

- TCP fast retransmission:** If 3 duplicate ACKs (i.e. 4 in total) are received, next segment is treated as lost and thus retransmitted immediately
- Maintains single timer and resends oldest unACKed packet on timeout; timer started only when prev. ACK is received

Network Security

- K_S : session key
 K_A^+ : public key K_A^- : private key 2 keys per user
- Integrity / Authenticity:** Bob can verify Alice is sender
Message authentication code: Send $H(m + K_S) \oplus m$
Digital signature: Send $K_A^-(m) \oplus m$
Digital sign.: Bob can prove to third party Alice is sender
Signed message digest as digital sign: Send $K_A^-(H(m)) \oplus m$
 - Confidentiality:** Send $K_B^+(<\text{everything from above}>)$
 - Hybrid:** Send $K_B^+(K_S) \oplus K_S(m \oplus K_A^-(H(m)))$

Network Layer

IP Addressing

- 172.16.0.0/12 → subnet mask starts with 12 '1's
first: 172.16.0.0 (subnet); last: 172.31.255.255 (broadcast)
- all other addresses are usable
- Valid subnet masks:**

Subnet size	256	128	64	32	16	8	4	2	1
Subnet mask	0	128	192	224	240	248	252	254	255
- Longest prefix match** is used to determine next hop from router forwarding table
- Special IP addresses:**

0.0.0.0/8	Local subnet (non-routable)
127.0.0.0/8	Loopback
255.255.255.255/32	Broadcast (within subnet)
10.0.0.0/8 172.16.0.0/12 192.168.0.0/16	Private
- Routers have one IP address per subnet


Network of Networks

- The Internet is a “network of networks” – a hierarchy of automonous systems (AS)
- **Intra-AS routing:** RIP, OSPF; **Inter-AS routing:** BGP
- “link-state” algorithms – all routers have complete knowledge of network topology and link cost; compute least-cost path using Dijkstra’s algorithm
- “distance vector” algorithms – routers know physically-connected neighbours and link costs to them, and exchange and update “local views” periodically; compute using **Bellman-Ford equation** (*cost = total distance*)
- **Routing Information Protocol (RIP)** implements “distance vector” (DV) algorithm, measuring *hop count*
 - Entries in routing table are aggregated subnet masks (so we are routing to destination subnet)
 - Exchange routing table every 30 secs over **UDP port 520**
 - **If no update for 3 minutes, assume neighbour has failed**

Network Address Translation

- Maintains mapping between (external IP Address, external port) and (destination (LAN) IP address, destination port)

IP Datagram Format



- IP datagram length includes IP header
 - Header checksum only for header bytes; 16-bit 1’s complement sum (just like TCP)
 - Different links have different maximum transfer unit (MTU) (*MTU includes IP header*); routers may fragment IP datagrams
-
- The diagram illustrates IP fragmentation. An original datagram with a single IP header and a large payload is shown. This is then fragmented into three smaller datagrams, each with its own IP header and a portion of the original payload (part 1, part 2, part 3).
- Total data transferred increases due to extra IP headers
 - Destination host will reassemble the packet
 - **Header field changes for fragmentation:** IP datagram length is set to fragment size. More frags. (MF) flag is set for all fragments except the last. Fragment offset is the fragment offset in the original data payload, measured in **8-byte** units. Header checksum is recomputed

Internet Control Message Protocol (ICMP)

- Used to communicate network-level information: error reporting, echo request/reply (ping)
- When TTL for a packet is zero, the packet is discarded and an ICMP message is sent to source address

Link Layer

Required services

- Framing: Encapsulate datagram to frame, add header/trailer

Optional services

- **Link access control:** If multiple nodes share a single link, need to coordinate which nodes can send frames at a certain point in time
- **Reliable delivery:** Often used on error-prone links (e.g. wireless) - **Error detection** - **Error correction**

- Link + physical layer is implemented in hardware in network adapter or on a chip

- **Single bit parity** can detect single-bit errors

- **Two-dimensional bit parity** can detect and correct single-bit errors; can detect two-bit errors

- **Cyclic Redundancy Check (CRC):** Used widely in practice (on Ethernet & Wi-Fi)
 - *D*: data bits (dividend)
 - *G*: generator of $r + 1$ bits, pre-agreed (divisor)
 - *R*: resultant CRC checksum (remainder)Bitwise XOR division is used

Sender computes *R* and sends (*D*, *R*)
Receiver divides (*D*, *R*) by *G* and checks if remainder is zero

Multiple Access Protocols

- Required in **broadcast links**
 - multiple nodes connect to a shared broadcast channel
 - when a node transmits a frame, every other node receives a copy
 - if two nodes transmit simultaneously, frames *collide* and none would be correctly read

- **Categories:**
 - Channel partitioning:** divide channel into smaller “pieces” (e.g. time slots, frequency); each node exclusively allowed to transmit in given piece (unused pieces go idle)
 - Taking turns:** nodes take turns to transmit (but can cooperatively forfeit turn if there is nothing to transmit)
 - Random access:** channel is not divided and collisions are possible; focus on “recovering” from collisions

- **Time division multiple access (TDMA):** Channel partitioning by fixed-length time slot
 - ↳ slot long enough to send one frame
- **Frequency division multiple access (FDMA):** Channel partitioning by frequency band

- **Polling:** Taking turns; master node “invites” slave nodes to transmit in turn (polling overhead; single point of failure of master node)

- **Token passing:** Control token is passed from one node to next sequentially (token overhead; single point of failure (lost token))

- **Slotted ALOHA:** *Transmit frame at start of slot, if collision then retransmit w prob p.*
 - Assumptions:
 - All frames of equal size
 - Time divided into slots of equal length (1 slot = 1 frame)
 - Nodes start to transmit only at the beginning of a slot
 - Operations:
 - Listens to the channel while transmitting (detect collision)
 - If collision, re-transmit frame in each subsequent slot with probability *p* until success

- **Pure (unslotted) ALOHA:** No slots; **transmit immediately**
 - Chance of collision increases
 - ↳ *colliso window doubled*
- **Carrier Sense Multiple Access (CSMA):** *but if collision, wait for one frame time*
 - Sense the channel before transmission; don’t interrupt ongoing transmission
 - Collisions may still occur due to to propagation delay and propagation distance

- **CSMA/CD (Collision Detection):** *2 max(dprop) < dtrans*
 - Abort transmission when collision is detected
 - Minimum frame size is usually specified as collision may not be detected for overly small frames due to propagation delay (*e.g. Ethernet requires minimum frame size of 64 bytes*)

Has “Hidden node problem”: due to propagation distance, collisions at receiver may not be detectable by source

- **CSMA/CA (Collision Avoidance):** Receiver needs to return an acknowledgement if frame is received successfully (*e.g. Wi-Fi*)

MAC Addressing

- 48 bits long
- Permanently assigned to network interface card (NIC)
- Each network node will only process frames that are addressed to its MAC address (or the broadcast address FF-FF-FF-FF-FF-FF)

Address Resolution Protocol (ARP)

- Resolves IP address to MAC address
- Each IP node has an **ARP table** which stores the mapping of IP address to MAC address (and TTL) of other nodes in the same subnet
- If the next hop node is not yet in the ARP table, an ARP query packet (with required IP address) is broadcasted to subnet; node with correct IP address will respond with its MAC address, sent back to source MAC address

Ethernet

- **Topology**
 - Bus:** all nodes can collide with each other
 - Star:** switch in centre, nodes do not collide
- | | | | | | |
|----------|-----------|----------|------|-----------|-----|
| 8 bytes | 6 | 6 | 2 | 46 - 1500 | 4 |
| Preamble | Dest Addr | Src Addr | Type | Payload | CRC |

- **Preamble:** 10101010 10101010 10101010 ... 10101011 Provides bit-level syncing, not part of 64-bit min. frame size
- **Type:** Higher-level protocol; 0x0800 for IPv4
- **Ethernet CSMA/CD algorithm:** ✗
 - 1) If channel idle, start transmitting immediately. Otherwise wait until idle.
 - 2) If collision while transmitting, abort and send jam signal. Then do binary back-off: after m^{th} collision, choose *K* at random from range $[0, 2^m)$, and wait $512 \times K$ bit times, then go back to step 1.

Binary back-off aims to adapt re-transmission attempts to estimated current load

- **Ethernet switch:**
 - Hosts have dedicated connection to switch; switch buffers frames (store-and-forward) and is full duplex (simultaneous bidirectional transfer)
 - **CSMA/CD protocol** is used even though no collisions
 - Maintains switch table – maps MAC address to interface (and TTL); if destination interface is known then frame is forwarded only to that link; if destination is not known then frame is broadcast
 - Switch learns source MAC address when frame is sent through it
 - Nodes do not need to know about the presence of the switch (switch is transparent to nodes)

Network Security

- Principles of Security
 - ① confidentiality
 - ② Integrity
 - ③ Authentication

- Types of Cryptography
 - Symmetric key ($K_A = K_B$)
 - Asymmetric key ($K_A \neq K_B$)

- Encryption [**Confidentiality**]
 - DES (Sym)
 - AES (Sym)
 - RSA (public)*So choose K_s then pass via RSA. Then continue using DES. K_s is called session key.*

- Hash function:
 - If a function $H(.)$ that takes an input *m* and produces fixed-size msg digest (*fingerprint*)*ex SHA-1, MD5* *↳ Cannot get m from hash*

- **Message Integrity**
 - ❖ sender, receiver want to ensure message *not altered* (in transit, or afterwards) *without detection*

- ↳ **Message Authentication Code (MAC)**
 - ❖ The sender and receiver share a “Authentication key” *s*
 - ❖ To ensure Message integrity:
 - ❖ Send ($m, H(m + s)$)

Authentication

- ❖ sender, receiver want to *confirm identity* of each other
- ↳ **Digital Signature** *A → B*
 - use Alice private key to encrypt
 - Then let Bob or anyone else use Alice’s public key to verify
 - can be optimized further by hashing message
- ↳ **Message Authentication Code (MAC)** — *cons: only A and B can verify*