TEST REPORT

Applicant:	ZHEJIANG QIDI TECHNOLOGY CO.,LTD
Address:	No.709 Huaguang Road, Tingtian Street, Wenzhou City, Zhejiang Province
Manufacturer:	ZHEJIANG QIDI TECHNOLOGY CO.,LTD
Address:	No.709 Huaguang Road, Tingtian Street, Wenzhou City, Zhejiang Province
Product Name:	3D printer
Trade Mark:	N/A
Model Number:	Max4, Plus5
Date of Receipt:	Nov. 19, 2025
Test Date:	Nov. 19, 2025 - Dec. 04, 2025
Date of Report:	Dec. 04, 2025
Prepared By:	Shenzhen DL Testing Technology Co., Ltd.
Address:	101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China
Applicable Standards:	EN IEC 62311:2020 EN 50665:2017
Test Result:	Pass
Report Number:	DLE-251119036-1R

Prepared (Engineer):	Ken Tan
Reviewer (Supervisor):	Jack Bu
Approved (Manager):	Jade Yang

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

1. VERSION

Version No.	Date	Description
00	Dec. 04, 2025	Original

2. GENERAL INFORMATION

2.1 Description of Device (EUT)

Product Name:	3D printer
Trade Mark:	N/A
Model Number:	Max4, Plus5
Test Model:	Max4
Model Difference:	All models are same as the samples except model name and appearance color, they have the same structure and circuit.
Power Supply:	100-240V～ 50/60Hz 3.4A Max
Operation Frequency:	802.11b/g/n20:2412~2472 MHz 802.11n40:2422~2462 MHz
Modulation Type:	CCK/OFDM/DBPSK/DAPSK
Antenna Type:	Internal Antenna
Antenna Gain:	2.38dBi
Hardware Version:	1.0
Software Version:	1.0
Firmware:	---

NOTE:

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(2) The EUT's all information provided by client.

3 REQUIREMENT

3.1 GENERAL INFORMATION

EN 62311 Generic standard to demonstrate the compliance of electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (0 Hz–300 GHz) is to demonstrate the compliance of apparatus with the basic restrictions or reference levels on exposure of the general public related to electric, magnetic, electromagnetic fields as well as induced and contact current.

3.2 Limit

Reference levels for electric, magnetic and electromagnetic fields (0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	4 000/f	5 000/f	—
0,025-0,8 kHz	250/f	4/f	5/f	—
0,8-3 kHz	250/f	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	0,73/f	0,92/f	—
1-10 MHz	$87/f^{1/2}$	0,73/f	0,92/f	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375\ f^{1/2}$	$0,0037\ f^{1/2}$	$0,0046\ f^{1/2}$	f/200
2-300 GHz	61	0,16	0,20	10

Notes:

1. *f* as indicated in the frequency range column.

3.3 Test Method

E (V/m) = $(30*P*G)^{0.5}/d$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

3.4 Test Result

EMF Test Data						
Test Mode	Max Output Power (dBm)	Max Output Power (W)	Antenna Gain(dBi)	Electric Field (V/m)	Limit (V/m)	Result
2.4GWIFI	15.21	0.03319	2.38	6.56	61.00	Pass
Note: The max output power(dBm) data is a reference RF report.						

4 EUT PHOTOGRAPHS

Please references EMC report(DLE-251119036-2R).

※※※※※ **END OF REPORT** ※※※※※