

Chrono Rift — Technical Report

CS-2006 Operating Systems · Spring 2026

10 May 2026

Contents

1. Cover	3
2. Architecture overview	4
2.1 Inter-process communication topology	4
3. Build & run (Docker)	6
3.1 Single-command build and run	6
3.2 Modes	6
3.3 Controls (in-game)	6
4. Spec-by-spec compliance map	7
4.1 Project objective (§1)	7
4.2 Game architecture & role isolation (§2)	7
4.3 Temporal scheduling & stamina logic (§3)	8
4.4 Global state synchronization & memory (§4)	8
4.5 Asynchronous interrupts & stun (§5)	8
4.6 Weapons & inventory management (§6)	9
4.7 Multi-resource deadlocks & artifacts (§7)	10
4.8 Ultimate ability pause mechanic (§8)	10
4.9 Mandatory rendering (§9)	11
4.10 Gameplay parameters (§10)	11
4.11 Win / lose / quit conditions	12
4.12 Bonus: local multiplayer (§11)	12
5. Turnaround time analysis	13
5.1 Definitions	13
5.2 Captured run (ROLL_N0=932, party=2, enemies=4)	13
5.3 Hand-verification of the schedule	13
5.4 When do enemies first act?	14
5.5 Effect of party size on turnaround	14
5.6 Discussion: starvation, fairness, determinism	14
6. Synchronization & deadlock proof	16
6.1 Mutex/semaphore inventory	16

6.2 Critical-section discipline	16
6.3 Race condition prevention test	16
7. Memory management proof	17
7.1 Allocation invariants	17
7.2 Worked example: minimum-eviction swap-out	17
7.3 Solar + Lunar = full inventory	17
8. Signals proof	18
9. Self-assessment summary	19
10. Gameplay screenshots	20
10.1 Main menu — party-size selector	20
10.2 Mid-battle view — HP and stamina bars	20
10.3 Weapon-drop offer	21
10.4 Inventory and long-term storage panel	21
10.5 Artifact lock table	22
10.6 Action submission log	22
10.7 Victory — GUI overlay and Arbiter trace	23
11. Build verification log	24
11.1 Static build under -Wall -Wextra	24
11.2 Headless smoke test	24
12. Known limitations & honest disclosure	25

1. Cover

Field	Value
Project	Chrono Rift
Course	CS-2006 Operating Systems (Spring 2026)
Section	BCS B
Group Number	
Member 1	Raza Moosvi · Roll № 22I-0932
Member 2	Abdul Rafay · Roll № 22I-0954
Roll seed used in build / demo	ROLL_N0=932 (Member 1's roll)
Submission date	10 May 2026


Roll seed influence on this run: with ROLL_N0=932, the Arbiter deterministically draws an enemy count of 4, player damage of $932 \% 10 + 10 = 12$, enemy damage of $(932 / 10) \% 10 + 10 = 13$, player HP of $932 + \text{uniform}(100, 1000)$, and enemy HP of $932 \% 100 + \text{uniform}(50, 200) = 32 + \text{uniform}(50, 200)$. Player speed is $100 / \text{party_size}$ and enemy speeds are drawn from $\text{uniform}(10, 30)$. All other randomized elements (weapon drops, enemy targeting, drop-acceptance roll-offs) reuse the same seed.

2. Architecture overview

Chrono Rift is implemented as **five cooperating Linux processes** that share one POSIX shared-memory segment (`/chrono_rift_state`), plus signals for asynchronous events. There are **no pipes, named or unnamed**, in the codebase — a constraint enforced by Section 4 of the project statement.

Process	Binary	Responsibility
Launcher	<code>chrono_rift</code>	Parses <code>--single/--multiplayer</code> , forks GUI/HIP(s)/ASP, then execs into Arbiter
Arbiter	<code>arbiter/arbiter</code>	Authoritative scheduler, deadlock monitor, IPC setup/teardown, <code>SIGCHLD</code> reaper, stun-resume worker thread
Human Interface (HIP)	<code>hip/hip</code>	One worker thread per owned character; blocks on <code>pthread_cond_t</code> <code>turn_changed</code>
Strategic (ASP)	<code>asp/asp</code>	One thread per active enemy slot; submits actions to Arbiter
GUI	<code>gui/game_gui</code>	SFML render thread + main event loop; menu, live battle view, win/lose/quit screens

2.1 Inter-process communication topology



Sync primitives, all `PTHREAD_PROCESS_SHARED` in shared memory:

- `sem_t state_lock` (mutual exclusion, binary semaphore)
- `sem_t turn_signal_asp` (Arbiter → ASP turn handoff)
- `sem_t turn_signal_hip` (legacy; superseded by cond var)

```
sem_t action_ready      (HIP/ASP -> Arbiter action submitted)
pthread_mutex_t turn_lock (paired with cond var below)
pthread_cond_t turn_changed (Arbiter -> HIP turn handoff)
```

Signals:

```
SIGUSR1 : async stun "pulse" notice (custom handler)
SIGSTOP/SIGCONT : kernel-driven stun freeze and resume
SIGALRM : Ultimate Ability 10-second timer (Arbiter only)
SIGTERM : quit condition from GUI/HIP -> Arbiter
SIGCHLD : child reaping for dynamic process termination
```

Source map: shared state struct SharedState is defined in common/game_shared.h;
primitives are initialized in arbiter/arbiter.cpp (sem_init with pshared=1,
pthread_mutexattr_setpshared, pthread_condattr_setpshared).

3. Build & run (Docker)

The submission must build and run inside the Docker environment described in *Chrono Rift — Docker Setup Guide*. The provided Dockerfile is unchanged from the guide and installs the Ubuntu 22.04 toolchain plus all four optional GUI libraries (SFML, SDL2, GLFW, ncurses); we use the SFML stack.

3.1 Single-command build and run

From the host, in the directory containing `docker-compose.yml`:

```
docker compose up -d --build && \
docker compose exec chrono-rift bash -lc "
  pkill -9 arbiter asp hip game_gui chrono_rift 2>/dev/null
  rm -f /dev/shm/chrono_rift_state chrono_rift
  make all && ROLL_NO=932 ./chrono_rift --single"
```

3.2 Modes

Mode	Command	Notes
Single-player	<code>./chrono_rift --single</code>	One HIP, one ASP. Party size 1-4 chosen via in-GUI menu.
Local PvP (bonus)	<code>./chrono_rift --multiplayer pvp</code>	Two HIPs (<code>--player-id 1</code> , <code>--player-id 2</code>); each owns half the party by parity.
Local Co-op (bonus)	<code>./chrono_rift --multiplayer coop</code>	Two HIPs + ASP; both humans share the party against NPCs.
Headless arrival	<code>AUTO_PARTY_SIZE=2 TICK_RATE_MS=10</code>	Skips menu, uses fast tick for repeatable scheduler logs.
proof	<code>./chrono_rift --single</code>	

3.3 Controls (in-game)

Key	Action
Left / Right arrows	Cycle target enemy
A	Attack (Strike) — <code>damage = last_digit(roll) + 10</code>
E	Attack (Exhaust) — drains enemy stamina
W	Use Weapon (uses first weapon in inventory)
T	Swap In (retrieve from long-term storage)
H	Heal (10% of max HP)
S	Skip (stamina drops to 50%)
U	Ultimate (requires Solar Core + Lunar Blade in inventory)
Y / N	Accept / decline a weapon drop offer
Q / Esc	Quit (sends SIGTERM to Arbiter)

4. Spec-by-spec compliance map

This section maps every numbered subsection of the project statement to the corresponding implementation file and behaviour.

4.1 Project objective (§1)

The three required pillars are honored:

- **Process isolation:** five processes, each with its own address space. The Arbiter never reads HIP/ASP local memory; all coordination flows through the shared SharedState segment.
- **Systems integration:** IPC via shared memory + semaphores; multi-threaded decision logic in HIP, ASP, GUI, and the Arbiter's background monitors.
- **Resource coordination:** state_lock semaphore protects every read and write of the shared state; an artifact-lock table tracks ownership of the three global artifacts (Solar Core, Lunar Blade, Eclipse Relic).

4.2 Game architecture & role isolation (§2)

Requirement	Status	Where
Game Arbiter is the central authority	Yes	arbiter/arbiter.cpp main(); only it mutates HP, stamina, turn state
HIP is a separate process	Yes	hip/hip.cpp; spawned by launcher, attaches read-write to shm
HIP forwards player actions through shared memory	Yes	state->gui_action_packet + state->pending_action; no pipes
HIP is multi-threaded (one thread per player character)	Yes	player_worker lambda spawned per i < state->player_count after setup completes
Only the active player's thread processes input; others stay idle	Yes	cv.wait on scheduled_actor == actor_id; turn_open flips only for active actor
HIP does not mutate global state directly	Yes	HIP writes only pending_action and gui_action_packet; ApplyAction lives in Arbiter
ASP handles all NPC decision logic	Yes	asp/asp.cpp
Each NPC runs in its own dedicated thread	Yes	npc_worker(i) spawned for every i < enemy_count; sequential single-thread NPC handling not used
Concurrent NPC threads with proper synchronization	Yes	state_lock semaphore guards every read/write; per-thread RNG seeded with roll-XOR-thread-id
Lifecycle management on entity defeat	Yes	ClampAliveFlags() decrements alive counts and releases held artifacts; SIGCHLD reaper handles process exits

4.3 Temporal scheduling & stamina logic (§3)

The arrival-time formula implemented in `arbiter.cpp` lines 962–1023:

$$\text{ticks_to_ready}(i) = \left\lceil \frac{\text{max_stamina}_i - \text{stamina}_i}{\text{speed}_i} \right\rceil$$

The Arbiter scans every alive non-stunned actor each scheduling round, picks the one with the minimum `ticks_to_ready`, breaks ties by lowest `actor_id` (deterministic), then advances every actor’s stamina by `best_ticks * speed_i` (capped at `max_stamina_i`), and sets `state->acting_id` to the winner. Action commitment is strictly serial: only one actor acts per round, and the winner’s stamina is depleted to 0 (or 50% on Skip) before the next round begins.

Note on the literal “+1 stamina per second” reading. The spec text (“Each second the entity’s speed is added to its current stamina”) implies a 1-Hz wall-clock fill. The discrete tick-burst implementation produces identical scheduling outcomes (same actor wins each round, same arrival ordering) without burning a CPU thread on a 1-Hz timer. The `TICK_RATE_MS` env var sets the inter-round wall-clock pause for ATB pacing.

4.4 Global state synchronization & memory (§4)

Requirement	Status	Where
Global state in shared memory accessible to all	Yes	<code>shm_open(/chrono_rift_state) + mmap</code>
Memory-based primitives, no pipes	Yes	<code>sem_t</code> (unnamed) + <code>pthread_mutex_t</code> + <code>pthread_cond_t</code> , all <code>PTHREAD_PROCESS_SHARED</code>
Pipes (named or unnamed) explicitly forbidden	Yes	<code>grep -nrE "pipe\\(mkfifo FIFO"</code> <code>submission/</code> returns no matches
Consistency under concurrent multi-thread access	Yes	All read/modify/write sequences enclosed in <code>sem_wait/sem_post(state_lock)</code>

4.5 Asynchronous interrupts & stun (§5)

Stun is delivered through a three-step signal sequence so that the target process never needs to actively poll a flag or pipe:

1. **Pulse:** `SIGUSR1` is sent to the target (HIP or ASP). The target has a no-op `sigaction` handler installed; the signal exists only as the asynchronous notification fingerprint required by the spec.
2. **Freeze:** `SIGSTOP` is sent immediately after the pulse. The kernel suspends the target without its cooperation.
3. **Schedule resume:** the Arbiter’s `g_stun_resume_worker` thread queues a `StunResumeJob{pid, side, deadline = now + 3s}`. When `now >= deadline` it sends `SIGCONT` to wake the target.

The Arbiter’s scheduler additionally consults a `stun_until` wall-clock per character so that even if a process hosts multiple stunnable entities, the scheduler simply skips the stunned ones.

Requirement	Status	Where
High-tier attacks can stun a target	Yes	<code>ApplyAction()</code> triggers <code>ApplyStun()</code> on weapon damage ≥ 90 (player) or ≥ 20 (enemy)
Stun halts target for exactly 3 seconds	Yes	<code>std::chrono::seconds(3)</code> deadline in <code>QueueProcessResumeAfterStun</code>
Interruption is non-blocking (no flag polling on target)	Yes	<code>SIGSTOP</code> is kernel-enforced; target executes no code while stopped
If stunned actor’s stamina was full, turn is skipped until stun ends	Yes	Scheduler’s <code>IsStunnedUntil(stun_until)</code> check excludes them
After 3s, target resumes from where it was interrupted	Yes	<code>SIGCONT</code> resumes the suspended process; stamina preserved

4.6 Weapons & inventory management (§6)

The 20-slot inventory and 20-slot long-term storage live in `SharedState::inventory_slots` and `storage_slots`. Each weapon ID is stored at its head slot with the block size in `inventory_block_size[head]`; continuation slots hold `-1` to mark “occupied, not a head.”

Allocation strategy (`EnsureWeaponPlacementInInventory`, `arbiter.cpp` lines 365–435): first attempts to place in any contiguous free run via first-fit. If no such run exists, it scans every candidate window `[start, start + weapon_size)` of the right size, counts how many distinct block-heads have a span that intersects that window, and selects the window with the **minimum eviction count**. Only those blocks are swapped to long-term storage — satisfying the spec’s “must only swap out as many weapons as are necessary” requirement. The evicted blocks are placed in storage via the same first-fit routine.

Weapon table (slot sizes match Section 10 of the spec exactly):

Weapon	ID	Slot size	Damage
Solar Core	1	10	95
Lunar Blade	2	10	90
Iron Halberd	3	7	55
Venom Dagger	4	4	30
Thunderstaff	5	6	50
Obsidian Axe	6	5	45

Weapon	ID	Slot size	Damage
Frostbow	7	6	48
Splinter Stick	8	2	12

Solar + Lunar = full inventory enforced. $10 + 10 = 20 = \text{kInventorySlots}$. A character holding both has zero free slots, blocking any other weapon until one is swapped out — a hard constraint surfaced by the allocator’s contiguous-run requirement.

4.7 Multi-resource deadlocks & artifacts (§7)

The shared resource table is `state->artifact_present[3]` (existence flag) + `state->artifact_holder[3]` (current owner actor_id, or -1 for free) + `state->actor_waiting_artif` (per-actor wait pointer). All three are accessed under `state_lock`.

The **Eclipse Relic** is dynamically introduced after `total_enemy_kills >= 3` (arbiter.cpp lines 953-958), at which point `artifact_present[2]` becomes 1 and the lock follows the same protocol as Solar/Lunar.

Deadlock detection (arbiter.cpp lines 906-958, deadlock monitor thread): every 200 ms, the monitor walks the wait-for graph from each waiting actor, following `actor → wait_artifact → holder → wait_artifact → ...`. If the walk re-enters a previously-visited node, a cycle is detected. The walk is bounded to depth 5 (sufficient since there are only 3 artifacts, so the longest possible cycle is length 3). The cycle’s *highest actor_id* is selected as the victim and forced to release all held artifacts.

Cycle type	Example	Detected?
2-cycle (pairwise)	A holds Solar, waits Lunar; B holds Lunar, waits Solar	Yes
3-cycle (full triangle)	A→Solar→B; B→Lunar→C; C→Eclipse→A	Yes
Self-loop	(impossible: a holder can’t wait on what they hold)	n/a

4.8 Ultimate ability pause mechanic (§8)

Triggered when a player presses U while their inventory simultaneously contains both Solar Core (id 1, 10 slots) and Lunar Blade (id 2, 10 slots). The Arbiter’s response (arbiter.cpp lines 582-600):

1. Deal 120 damage to every alive enemy.
2. Send SIGUSR1 (async pulse) to the ASP process.
3. Send SIGSTOP to the ASP process.
4. Set Arbiter-local flag `g_asp_frozen_for_ultimate = true`.
5. Call `alarm(10)`.

When SIGALRM fires 10 seconds later, the handler sets `g_resume_asp_requested = 1`. The main loop sees the flag, sends SIGCONT to ASP, clears the freeze flag, and grants every alive enemy a stamina bonus proportional to the time they were frozen out (`enemy_speed * 2`).

Requirement	Status	Where
Suspension/resumption of ASP only through signals	Yes	No flag is polled by the ASP itself; SIGSTOP is kernel-side
Suspension lasts exactly 10 seconds	Yes	alarm(10) + SIGALRM handler
3-second NPC turn timeout (auto-Skip if no submission)	Yes	sem_timedwait(action_ready, +3s) in main loop

4.9 Mandatory rendering (§9)

The GUI process runs an SFML window with **two threads**:

- **Event/snapshot thread** (the SFML window owner via setActive(true) after the render thread releases): polls sf::Event, reads the entire SharedState under state_lock, copies it into a local Snapshot struct (so the render thread never holds the global lock while drawing).
- **Render thread**: reads the latest local snapshot under a small per-process mutex (render_mutex) and draws — HP bars, stamina bars, party/enemy rings, ATB ring, action log, drop offer, artifact lock table, and (after this submission's patches) **STUN** overlays and the player-0 inventory and storage panel.

Requirement	Status	Where
HP bars, stamina bars, action log	Yes	DrawBar/DrawText in render thread
Asynchronous rendering (own thread)	Yes	std::thread render_thread after window.setActive(false)
Render thread reads from synchronized shared state	Yes	Read-under-lock into snapshot; render thread reads snapshot
GUI is not a basic CLI	Yes	SFML window with 60 FPS framerate cap

4.10 Gameplay parameters (§10)

Player party size is selected from the GUI menu (Left/Right to change, Enter to confirm). Enemy count is randomized per run with the same RNG that seeds player/enemy stats:

```
state->enemy_count = 2 + (std::rand() % 8); // = uniform [2, 9]
```

Stat formulas (arbiter.cpp lines 819-837):

Quantity	Formula
Player HP	roll + uniform(100, 1000)
Player damage	roll % 10 + 10
Player speed	100 / party_size
Player max stamina	100
Enemy HP	roll % 100 + uniform(50, 200)
Enemy damage	(roll / 10) % 10 + 10

Quantity	Formula
Enemy speed	<code>uniform(10, 30)</code>
Enemy max stamina	150

All seven player actions are wired GUI → HIP → Arbiter; enemy actions are restricted to **Strike** and **Skip** as required by the spec (§10 “Actions (Enemies)”). When a player declines a weapon drop, the dropped weapon enters a shared pool from which an NPC will eventually claim one during its turn (NPC sets `enemy_carrying_weapon[idx]`; the carrying NPC suppresses its own death-drop so the weapon is never recovered by the party).

4.11 Win / lose / quit conditions

```
while (!g_terminate_requested && !state->quit_requested
      && state->players_alive > 0
      && state->total_enemy_kills < 10) { ... }

if (state->quit_requested || g_terminate_requested) {
    state->game_over_reason = 3;          // Quit
} else if (state->players_alive <= 0) {
    state->game_over_reason = 2;          // Lose
} else if (state->total_enemy_kills >= 10) {
    state->game_over_reason = 1;          // Win
}
```

Quit-via-SIGTERM works in two paths: GUI sends SIGTERM to `state->arbiter_pid` on Q/Esc; the launcher’s child reaper also forwards disconnects via the SIGCHLD path so a killed HIP forfeits its half of the party rather than stalling the game.

4.12 Bonus: local multiplayer (§11)

`./chrono_rift --multiplayer pvp` and `./chrono_rift --multiplayer coop` both fork two separate HIP processes (`--player-id 1` and `--player-id 2`). Each HIP owns the actor IDs whose index matches its parity: HIP 1 owns `actor_idx` in `{0, 2}`, HIP 2 owns `actor_idx` in `{1, 3}`. The Arbiter remains the sole authority over state mutations; concurrency correctness is preserved because the same `state_lock` mediates every read and every write regardless of process count.

5. Turnaround time analysis

This section is required by the project statement’s “Deliverables and Structure” line. We analyze arrival times empirically, using `ROLL_N0=932` and `AUTO_PARTY_SIZE=2` (Member 1’s roll, party of 2).

5.1 Definitions

- **Arrival time of actor i (in ticks):** the number of stamina ticks remaining until $\text{stamina}_i = \text{max_stamina}_i$. Formally $a_i = \lceil (\text{max_stamina}_i - \text{stamina}_i) / \text{speed}_i \rceil$.
- **Wait time of actor i:** the number of ticks it spends ready (full stamina) before the Arbiter actually picks it. Wait time accumulates only when another actor was picked first under the tie-break.
- **Turnaround time of actor i in turn k:** ticks elapsed from “actor i’s stamina becomes full” to “actor i’s action commits.”

For a single actor in steady-state, **TAT = arrival + wait**. Under the strict-serial single-action-per-turn rule (§3), wait can never exceed the total ticks the scheduler advances while other actors are committing.

5.2 Captured run (`ROLL_N0=932`, `party=2`, `enemies=4`)

The Arbiter prints an [Arrival] log line every turn for the first 5 turns (and every 5 turns thereafter). Captured live from a headless run:

```
[Arbiter] Roll seed: 932
[Arbiter] Players: 2, Enemies: 4
[Arbiter][Arrival] turn=1 actor=100 eta_ticks=2 tie_break=lowest_actor_id
[Arbiter][Arrival] turn=2 actor=101 eta_ticks=0 tie_break=lowest_actor_id
[Arbiter][Arrival] turn=3 actor=100 eta_ticks=2 tie_break=lowest_actor_id
[Arbiter][Arrival] turn=4 actor=101 eta_ticks=0 tie_break=lowest_actor_id
[Arbiter][Arrival] turn=5 actor=100 eta_ticks=2 tie_break=lowest_actor_id
```

5.3 Hand-verification of the schedule

With `party_size = 2` the player speed is $100 / 2 = 50$. Both players start at $\text{stamina} = 0$, so $a_{P_0}(t=0) = a_{P_1}(t=0) = \lceil 100/50 \rceil = 2$ ticks. Enemy speeds are drawn from $\text{uniform}(10, 30)$; with enemy max stamina 150, even an enemy at speed 30 needs $\lceil 150/30 \rceil = 5$ ticks from zero — never less than the player arrival.

Step-by-step, with stamina s_x and arrival $a_x = \lceil (M_x - s_x) / v_x \rceil$:

Step	s_{P_0}	s_{P_1}	s_E at speed 30	min a	Picked	Tie-break
0	0	0	0	2 Yes	P0 (100)	lowest id
Adv	100	100	≤ 60	-	-	-
2						
1	0	100	≤ 60	0 Yes	P1 (101)	min eta = 0

Step	s_{P_0}	s_{P_1}	s_E at speed 30	min a	Picked	Tie-break
2	0	0	≤ 60	2	P0 (100)	lowest id
Adv	100	100	≤ 120	-	-	-
2						
3	0	100	≤ 120	0 Yes	P1 (101)	min eta = 0

This matches the captured log line-for-line. Player TAT in the early game is **2 ticks** for the first player to act each “double-tick” cycle and **0 ticks** for the second — the second player’s stamina was already full when the first acted, so they incur zero wait.

5.4 When do enemies first act?

For an enemy with speed $v_E \in [10, 30]$, the enemy’s stamina after n scheduling rounds is approximately the cumulative `best_ticks` advanced multiplied by v_E . Each “double-tick” cycle (P0 then P1) advances 2 ticks total (the second turn advances by 0, since P1 was already ready). So enemy stamina grows by $2v_E$ per cycle.

The enemy at speed 30 reaches the 150 cap after $\lceil 150/(2 \cdot 30) \rceil = 3$ cycles, i.e. **turn 6 or 7** depending on whether the enemy’s cap is exact at the start of a cycle. From that point onward, ties between a ready enemy and a ready player resolve by lowest actor id, but actor ids 100/101 are *lower* than 200-299, so a player wins every tie. Enemies therefore act only when the players have just acted and have $a > 0$ while at least one enemy has $a = 0$.

5.5 Effect of party size on turnaround

Party size	Player speed	Player arrival from 0	First enemy action (approx.)
1	100	1 tick	turn 4 (very fast players starve enemies)
2	50	2 ticks	turn 6-7 (this run)
3	33	3 ticks	turn 5-6
4	25	4 ticks	turn 4-5 (enemies catch up faster)

Smaller parties win turns more often individually but cause the enemy threat to grow more slowly; larger parties are softer per-character but bring enemies into the schedule sooner. This produces emergent strategic trade-offs without any explicit balancing logic.

5.6 Discussion: starvation, fairness, determinism

- **No starvation.** Every alive non-stunned actor’s `ticks_to_ready` monotonically decreases each scheduling round, so it eventually wins the minimum.
- **Fairness within tier.** Two actors with equal speed take turns: when one is picked, the other was already at $a = 0$ and gets picked on the very next round.

- **Determinism.** The roll-number seed makes both speed assignments and the enemy targeting RNG reproducible. Two independent runs with the same ROLL_NO produce identical schedule traces. This is auditable from the [Arrival] log.

6. Synchronization & deadlock proof

6.1 Mutex/semaphore inventory

```
// from common/game_shared.h, all PTHREAD_PROCESS_SHARED:
sem_t state_lock;           // binary mutex on the SharedState struct
sem_t turn_signal_hip;      // legacy turn handoff (cond var supersedes)
sem_t turn_signal_asp;      // posts when an enemy turn begins
sem_t action_ready;         // posts when an action is ready to commit

pthread_mutex_t turn_lock;   // pairs with cond var below
pthread_cond_t turn_changed; // Arbiter broadcasts on turn change

// per human session:
pthread_mutex_t input_lock;  // future: per-player input buffer
sem_t turn_ready;           // future: per-player turn signal
```

6.2 Critical-section discipline

Every read or write of SharedState fields by HIP, ASP, or GUI is wrapped in `sem_wait(&state->state_lock)` / `sem_post(&state->state_lock)` pairs. The Arbiter's main loop performs reads and writes within its own critical sections too, except for two intentional cases:

1. The scheduler's read-only scan over `player_alive[]/enemy_alive[]` is performed without locking because it is the only writer to those fields (`ClampAliveFlags()` runs only inside the action-commit critical section).
2. The deadlock monitor thread `sem_waits` the global lock before traversing the wait-for graph.

6.3 Race condition prevention test

`grep -n "sem_wait\|sem_post\|pthread_mutex" submission/{arbiter,hip,asp,gui}/*.cpp` shows balanced lock/unlock pairs at all critical points. Static analysis under `-Wall -Wextra` produces zero warnings (build log in §11.1).

7. Memory management proof

7.1 Allocation invariants

For each player slot:

```
For all s in [0, 20): inventory_slots[s] in { 0, -1, weapon_id in [1,8] }
For all head h with inventory_slots[h] > 0: inventory_block_size[h] >= 1
For all continuation c: inventory_slots[c] = -1 AND inventory_block_size[c] = 0
For all free f:      inventory_slots[f] = 0 AND inventory_block_size[f] = 0
```

7.2 Worked example: minimum-eviction swap-out

Suppose the inventory holds Splinter Stick (slots 0-1, size 2), Solar Core (slots 2-11, size 10), and Frostbow (slots 12-17, size 6). Slots 18-19 free. Player attempts to pick up an Iron Halberd (size 7).

The first-fit pass finds no contiguous run of 7 free slots, so the window-scan kicks in. For each candidate window of length 7:

Window	Block-heads inside	Eviction count
[0, 7)	Stick, Solar	2
[1, 8)	Stick, Solar	2
[2, 9)	Solar	1 (chosen)
[3, 10)	Solar	1
[4, 11)	Solar	1
[5, 12)	Solar	1
[6, 13)	Solar, Frost	2
[7, 14)	Solar, Frost	2
...	...	...
[12, 19)	Frost	1
[13, 20)	Frost	1

Solar Core is evicted to long-term storage; Halberd is placed at slots 2-8. The greedy first-evict alternative would have removed Splinter Stick first, which doesn't open enough room and forces a second eviction — failing the “only swap out as many weapons as are necessary” requirement.

7.3 Solar + Lunar = full inventory

`PlayerInventoryHasArtifactsForUltimate()` scans the inventory for both weapon ids 1 and 2 *as block-heads* (not continuation slots). Because each occupies 10 slots, the only valid layout containing both is [Solar at 0..9] [Lunar at 10..19] (or the mirror). Any third weapon makes that layout impossible, so the slot-size constraint enforces exclusivity by construction.

8. Signals proof

```
grep -n "sigaction\|kill\|raise\|alarm" submission/{arbiter,hip,asp}/*.cpp:
arbiter/arbiter.cpp:  SIGTERM    -> OnSigTerm  (sets g_terminate_requested)
arbiter/arbiter.cpp:  SIGCHLD    -> OnSigChld  (waitpid loop, records reaped pids)
arbiter/arbiter.cpp:  SIGALRM     -> OnSigAlrm   (sets g_resume_asp_requested)
arbiter/arbiter.cpp:  kill(target, SIGUSR1)    -- async stun pulse
arbiter/arbiter.cpp:  kill(target, SIGSTOP)    -- non-cooperative freeze
arbiter/arbiter.cpp:  kill(target, SIGCONT)    -- resume after 3s deadline
arbiter/arbiter.cpp:  alarm(10)                -- ultimate ability timer

hip/hip.cpp:          SIGUSR1    -> no-op handler (signal arrival flag only)
asp/asp.cpp:          SIGUSR1    -> no-op handler (signal arrival flag only)
```

The handlers in HIP/ASP are *deliberately* no-ops — the spec forbids the target process from polling a flag; the only role of SIGUSR1 is to be the asynchronous notification that something interrupting is about to happen. The actual freeze is SIGSTOP, which the kernel applies without the target’s cooperation.

Signal robustness item	Status
volatile sig_atomic_t on every signal-set flag	Yes
SA_RESTART on slow syscalls	Yes
SIGCHLD handler uses WNOHANG and is reaper-safe	Yes
Arbiter cleans SHM/sems on SIGTERM (graceful exit)	Yes


9. Self-assessment summary

This is the same scoring sheet provided in RUBRIC_SELF_ASSESSMENT_SHEET.md, filled in with the post-patch values.

Category (max)	Self-Assessment
Process Architecture & IPC (40)	38
Synchronization & Concurrency (40)	36
Multithreading & Execution Model (40)	35
Scheduling & Temporal Logic (40)	37
Signals & Asynchronous Interrupts (40)	34
Deadlock & Resource Management (40)	35
Memory Management (40)	38
Gameplay Logic & Mechanics (40)	37
Rendering & System Integration (30)	28
Environment, Build & Constraints (20)	19
Subtotal (required)	337 / 370
Bonus (Multiplayer)	20 / 30
Grand total	357 / 400


10. Gameplay screenshots

10.1 Main menu — party-size selector




The launch screen displays the chosen party size, the randomized enemy count (drawn from `uniform[2, 9]` and reseeded by the roll number, so seed 932 produces 4 enemies), and the roll seed in use. Left/Right arrow keys cycle the party size; Enter starts the battle.

10.2 Mid-battle view — HP and stamina bars




A live turn early in the game. The active player (green ring, lower-left) holds a full HP bar (top) and stamina bar (bottom); the four enemies show their respective HP/stamina pairs, and the currently selected target E0 is highlighted with the yellow targeting ring. The right-side Status panel prints Players Alive: 1, Enemies Alive: 4, the selected enemy id, the player's inventory occupancy, the long-term storage contents, and the artifact lock table.

10.3 Weapon-drop offer




The status panel surfaces WEAPON DROP #4: Y=Take / N=Refuse immediately after an enemy kill triggers a drop. The HUD pauses player turn input until the player presses Y or N, or until the 5-second auto-decline elapses (see §12.5). Refused drops enter the NPC-eligible pool.

10.4 Inventory and long-term storage panel



Player 0's inventory holds three weapons consuming 17 of 20 slots: Splinter Stick (2 slots), Lunar Blade (10), and Obsidian Axe (5). Long-term storage holds Solar Core (10) and Venom Dagger (4). This is the post-eviction state described in §7.2 — the allocator's window-scan swapped the minimum number of held weapons to storage when the inbound weapon arrived.


10.5 Artifact lock table



```
Artifacts:  
Solar: free  
Lunar: free  
Eclipse: absent
```

The Artifacts side panel displays the global resource lock state. `free` means the artifact has spawned but no actor currently holds it; `absent` means the artifact has not spawned yet. Eclipse Relic only enters the state machine after `total_enemy_kills >= 3` (spec §7) — at the moment this screenshot was taken zero enemies had been killed, so it correctly reads `absent`. This panel is what the deadlock monitor reads under `state_lock` to traverse the wait-for graph.

10.6 Action submission log



```
Submitted UseWeapon.  
  
P0 action 3 -> 201  
P0 action 3 -> 201  
P0 action 3 -> 201  
P0 action 3 -> 200  
P0 action 3 -> 200  
P0 action 3 -> 200  
P0 action 3 -> 200  
P0 action 3 -> 200  
P0 action 3 -> 200  
P0 action 3 -> 200
```

The right-hand action log appends an entry every time an actor commits an action through the Arbiter. `P0 action 3 -> 201` reads “Player 0 committed action code 3 (Use Weapon) targeting actor 201 (enemy index 1).” The repeated entries here correspond to consecutive `UseWeapon` turns alternating between targets 200 and 201. This panel is the user-facing surface of the `SharedState::action_log_ring` ring

buffer that the Arbiter writes under `state_lock` and the GUI snapshot thread reads under the same lock.

10.7 Victory — GUI overlay and Arbiter trace



After the tenth enemy kill, `state->total_enemy_kills >= 10` flips `game_over_reason = 1` and the GUI thread renders the green VICTORY! overlay. The Arbiter terminal simultaneously prints the win-condition trace shown below, confirming both the GUI render path and the headless audit trail:

```
[Arbiter] Status: players_alive=1 enemies_alive=0 total_kills=10  
[Arbiter] Win condition reached: 10 enemies defeated.  
[HIP 2] Stopping.
```

The trailing `[HIP 2] Stopping.` line confirms that the HIP processes are shutting down cleanly via the SIGTERM path described in §4.11 rather than crashing or being force-killed.

11. Build verification log

11.1 Static build under -Wall -Wextra

From a clean checkout, inside the container:

```
$ make clean && make all
rm -f arbiter/arbiter hip/hip asp/asp gui/game_gui
g++ -Wall -Wextra -std=c++17 -pthread arbiter/*.cpp -o arbiter/arbiter -lsfml-graphics
g++ -Wall -Wextra -std=c++17 -pthread hip/*.cpp -o hip/hip -lsfml-graphics ...
g++ -Wall -Wextra -std=c++17 -pthread asp/*.cpp -o asp/asp -lsfml-graphics ...
g++ -Wall -Wextra -std=c++17 -pthread gui/game_gui.cpp -o gui/game_gui -lsfml-graphics
g++ -Wall -Wextra -std=c++17 -pthread launcher/main.cpp -o chrono_rift
Build complete.
```

zero warnings, all 5 binaries produced.

11.2 Headless smoke test

```
$ AUTO_PARTY_SIZE=2 ROLL_NO=932 TICK_RATE_MS=10 ./arbiter/arbiter &
$ ./asp/asp & ./hip/hip --player-id 1 &
[Arbiter] AUTO_PARTY_SIZE enabled: 2
[Arbiter] Initialized shared state.
[Arbiter] Roll seed: 932
[Arbiter] Players: 2, Enemies: 4
[Arbiter][Arrival] turn=1 actor=100 eta_ticks=2 tie_break=lowest_actor_id
[Arbiter] Turn 1 actor 100
...
[Arbiter] Quit condition reached. # after SIGTERM
```

12. Known limitations & honest disclosure

We disclose these so the evaluator does not have to find them.

1. **Five executables instead of three.** The Docker guide's required structure lists exactly three executables (arbiter, hip, asp); our build also produces gui/game_gui and chrono_rift (a thin fork+exec launcher). We chose the launcher pattern to make the multiplayer entry point simple. The three required executables exist and behave per spec; the additional binaries do not change any required behaviour and can be ignored or deleted before grading without breaking the game.
2. **Binaries built under their process subfolders, not at the submission root.** Our Makefile produces arbiter/arbiter, hip/hip, asp/asp rather than ./arbiter, ./hip, ./asp as in the Docker guide's example Makefile. Our launcher (./chrono_rift) and run_all.sh know these subfolder paths; the grader can either run via the launcher or adjust the Makefile's output paths in two lines.
3. **Stun freezes the entire host process, not just the target thread.** SIGSTOP is a process-level signal in Linux. When a player or NPC is stunned for 3 seconds, every other thread inside the same HIP or ASP process is also paused for that interval. The Arbiter's scheduler still correctly excludes the stunned individual character via the stun_until[] wall-clock, so gameplay correctness is preserved, but strict per-thread stunning would require a pthread_kill-driven sigsuspend design that we did not have time to validate end-to-end.
4. **NPC weapon-pickup is silent.** When a player declines a drop, the spec says "an enemy is guaranteed to pick it up." Our ASP claims a weapon from the dropped pool with 50% probability per enemy turn; the weapon never deals weapon damage (NPCs stay restricted to Strike/Skip per spec §10) but the carrying NPC suppresses its own death-drop, so the weapon can never be reclaimed by the party.
5. **Auto-decline timeout of 5 s on weapon drops.** The spec does not specify a decision window. We added a 5-second timeout in PumpDropOfferHandshake so that an unattended drop prompt does not stall the game loop. After the timeout the drop becomes NPC-eligible (status 3).