Lifesmart Spa Specifications

Spa Model (Seating)	Footprint Dimension	Height	Effective Filter Area	Heater (Watts)	Water Capacity	Dry Weight	Filled Weight	Electrical Requirements
LS100/DX (4 person)	5’10” x 5’1”	32”	50 SQFT	Heat Recovery	205 gal	270 lbs.	2,698 lbs.	110 V, 15-amp GFCI protected circuit
LS200/DX (4 person)	6’5” x 5’6”	29”	25 SQFT	Heat Recovery	220 gal	244 lbs.	2,799 lbs.	110 V, 15-amp GFCI protected circuit
LS350DX/PLUS (5 person)	6’ x 6’9”	34”	50 SQFT	Heat Recovery	315 gal	351 lbs.	3,881 lbs.	110 V, 15-amp GFCI protected circuit
LS450DX (6 person)	6’9” x 6’9”	34”	50 SQFT	Heat Recovery	270 gal	440 lbs.	3,766 lbs.	110 V, 15-amp GFCI protected circuit
LS500 PLUS (5 person)	7’3” x 6’5”	34”	50 SQFT	Heat Recovery	290 gal	423 lbs.	3,743 lbs.	110 V, 15-amp GFCI protected circuit
LS550 PLUS (5 person)	7’3” x 6’5”	34”	50 SQFT	4,000	290 gal	445 lbs.	3,765 lbs.	230 V, 50-amp GFCI protected circuit
LS600DX (7 person)	6’9” x 6’9”	34”	50 SQFT	4,000	290 gal	478 lbs.	4,148 lbs.	230 V, 50-amp GFCI protected circuit
LS700DX (7 person)	6’9” x 6’9”	34”	50 SQFT	4,000	285 gal	583 lbs.	4,210 lbs.	230 V, 50-amp GFCI protected circuit
SERENO (4 person)	6’3” x 6’3”	34”	50 SQFT	1,000 or 4,000	245 gal	406 lbs.	3,171 lbs.	110 V, 15 amp or 230 V, 50-amp GFCI protected circuit
TIERRA (5 person)	7’3” x 6’5”	34”	50 SQFT	4,000	327 gal	426 lbs.	4,058 lbs.	230 V, 50-amp GFCI protected circuit
LEGANZA (6 person)	7’3” x 6’5”	34”	50 SQFT	4,000	290 gal	445 lbs.	3,765 lbs.	230 V, 50-amp GFCI protected circuit
ESTRELLA L (6 person)	7’0” x 7’0”	36”	50 SQFT	4,000	330 gal	796 lbs.	4,737 lbs.	230 V, 50-amp GFCI protected circuit
ESTRELLA NL (7 person)	7’0” x 7’0”	36”	50 SQFT	4,000	360 gal	700 lbs.	4,960	230 V, 50-amp GFCI protected circuit
PLAYA (3 person)	7’0” x 5’5”	29.5”	35 SQFT	4,000	210 gal	663 lbs.	2,958 lbs.	230 V, 50-amp GFCI protected circuit
CARINO (6 person)	7’5” x 7’5”	36”	50 SQFT	4,000	409 gal	893 lbs.	5,433 lbs.	230 V, 50-amp GFCI protected circuit