

# Packaging Software for the Pi

*Packaging and distributing software for the Pi (with a package for WiringPi)*

[Hamish Cunningham](#), January 2014

## Contents

- [1. Introduction: the Good Old Days](#)
- [2. The Problem](#)
- [3. The Platform: GNU, Linux, Debian, Raspbian and Ubuntu](#)
- [3.1. Ubuntu's Personal Package Archives](#)
- [4. Debian Packaging](#)
- [4.1. Creating the debian Directory](#)
- [4.2. Conventions for the Makefile](#)
- [4.3. Creating .deb and .dsc Files](#)
- [5. Case Studies](#)
- [5.1. SimBaMon and BlinkIP](#)
- [5.2. WiringPi](#)
- [6. The End](#)

## 1. Introduction: the Good Old Days

Twenty-odd years ago I worked for a company building accounting and stock control systems for manufacturing businesses. I started as a general gopher, tea-maker and minor bug fixer on big old behemoths written in a language called COBOL — which some people claimed was a "common business-oriented language" but I was sure stood for "computer operators are boring and obviously lobotomised". Customers would phone up and say "we've got a new invoice format, can you change the report printer to fit?", and I would spend a day or two hunched over a stack of continuous paper (the type with perforated edges) with a special measuring ruler figuring out how many spaces to leave between the date and the address, and the like.



copy) over dial-up modem links to push new updates onto machines out on site (and, cheekily, used to get the customer machine to phone us back so that the lengthy upload process would happen on their phone bill, not ours!). Things are a little simpler now: someone invented a thing called the Internet...<sup>2</sup>

The job of packaging and distribution continues to be important, though, and below I'll describe the mechanisms used for the Raspberry Pi's *Raspbian* operating system. I'll give a couple of downloadable examples, including a package for [Gordon Henderson](#)'s excellent [Wiring Pi](#).

## 2. The Problem

Software packaging and distribution has to deal with versions, dependencies and access:

- Different *versions* of programs can incorporate lots of changes, including critical security fixes that need applying in a hurry. Especially on older systems and in low-bandwidth locations, minimising the amount of new download for a changed version is important.
- *Dependencies* between programs are often tied to particular versions — if a facility that one program relies on changes, the program's package data must reflect its need for the old version.
- Access to packages is relatively easy now — most software is distributed as a network download. But what happens if the connection drops half-way through? Or if a million people all want updates on the same day?


These issues have been addressed in various ways; one of the most successful and wide-reaching is the Debian package management system, and this is the one that we'll describe here.

## 3. The Platform: GNU, Linux, Debian, Raspbian and Ubuntu

[Debian](#) is a *distribution* of [GNU Linux](#), which is a Unix-like operating system (like Android, MacOS, Ubuntu, Red Hat and many others).



For the Pi there's a special version of Debian called [Raspbian](#).



Probably the most popular version of Linux at present is [Ubuntu](#), but because of an incompatibility between the Pi's version of its [ARM microprocessor](#) and the Ubuntu build system, we can't use Ubuntu's infrastructure on the Pi, except for programs which are *architecture independent* — a term which we'll explain below when we show how to use Ubuntu Personal Package Archives for Pi software distribution.

### 3.1. Ubuntu's Personal Package Archives

Broadly speaking, computer programming languages come in two sorts: *compiled* or *interpreted*. Compiled languages are translated into machine code (binary instruction sequences) before they can be run. Interpreted languages can be run directly without any translation. This means that programs written in interpreted languages are often *architecture independent* — they can run without change on many different types of computer chips. Several languages popular on the Pi fall into this category, including Shell Script and (with some restrictions) Python.



As we noted earlier, Ubuntu Linux is very popular (and is also derived from Debian). Ubuntu has a great set of infrastructure tools associated with it, including *Personal Package Archives* (PPAs) which simplify the task of building, packaging and distributing software for all the platforms supported by Ubuntu. If we're packaging an architecture-independent program, then, a PPA can be a good way to distribute it. (Several [Pi GATE](#) programs are [distributed like this](#).)

Linux is [open source free software](#), and to make sure everyone gets access to the source of programs in PPAs, Ubuntu only accepts Debian *source packages* as uploads to the archives. This means we have to build both a *source* (.dsc) and a *binary* (.deb) package for each program; the next section describes how we do this.

## 4. Debian Packaging

A lot has been written about packaging, and it's fair to say that it isn't the easiest thing to get started with.<sup>3</sup> We'll take a quick-and-dirty approach here, and give only enough detail for a couple of simple cases:

- scripts and other architecture-independent packages (including *daemons*, which are scripts run at system startup)
- binaries from compiled languages like C (including shared libraries)

In each case the key to the process is to

1. create a `debian` directory in the top-level directory of your software tree, containing data to control the package construction process
2. set up a `Makefile` in the same place which follows certain conventions for installation targets

The rest of this section describes these steps; in [the next section](#) we'll give

example code.

## 4.1. Creating the `debian` Directory

The packaging file tree can be seeded using the `dh_make` program like this:

```
sudo apt-get install devscripts debhelper
dh_make -p=package-name_1.0 --native
```

This creates a set of files in the `debian` directory, many of which are examples or boilerplate which can be ignored. The ones of the set that need editing in our cases are:

- `control`: contains the basic details of the package, its version and dependencies
- `changelog`: describes the changes present in each version
- `copyright`: describes the licence — this should be [an open source licence](#)
- `docs`: lists documentation files, e.g. a `man` page or a `README` for the software itself
- `README`: describes details of the *packaging* of the software, *not* the software itself

There is also a file called `rules` which follows Makefile syntax and which can be used to modify the details of the packaging process. In recent configurations this file uses a lot of implicit rules and doesn't need any changes.

## 4.2. Conventions for the Makefile

Having created our `debian` file tree we then need to create (or adapt) a top-level Makefile so that it:

- has a default target (e.g. `all`) which does any necessary compilation and linking of the software (for scripts this target probably does nothing)
- has an `install` target which adapts to the setting of a `DESTDIR` (*destination directory*) environment variable

The second of these is best accomplished using the `install` program. For example, given a binary called `amazing`, we can install it to `DESTDIR` from our Makefile like this:

```
install -d -m 755      $(DESTDIR)/usr/bin
install -m 755 amazing $(DESTDIR)/usr/bin
```

Here the first command makes sure that the target installation directory (`/usr/bin`) exists; the second copies the binary file and gives it appropriate permissions for an executable program.

It is also convenient to wrap up the commands relating to packaging in

Makefile targets; the next section describes these commands.

## 4.3. Creating .deb and .dsc Files

As noted earlier, the outputs from the packaging process are files of two types:

- .deb files contain binary builds of a program, which is all ready to install on a running instance of Raspbian
- .dsc files contain the source code of a program, ready to be built

We'll create these files using the `debuild` program. In common with several other packaging commands, `debuild` uses various helper programs to do its work. One of the disadvantages of this arrangement is that documentation is often spread across several locations. For example, the manual for `debuild` doesn't describe all of the options that it is parameterised by — some of them are only described by the helper program documentation. A good place to start looking for their meaning is in the documentation for `dpkg-buildpackage` (which in turn calls a whole team of other helpers).

The `debuild` commands that we need are these:

```
debuild -S -Ipackage
debuild -Ipackage
```

The first command builds *only* a .dsc source package (using the `-s` option). The second builds both a .dsc and a .deb. In both cases we ignore the `package` directory (via the `-Ipackage` option) as this is where we'll put the files generated by `debuild`.

We use the source-only build when we're targetting an Ubuntu PPA (see above) — these only accept source packages, building a .deb of their own from the source.

## 5. Case Studies

### 5.1. SimBaMon and BlinkIP

This section gives package file and `Makefile` code examples for the script programs described in our pages on the [SimBaMon simple battery monitor](#) and the [Blink my IP](#) daemons.





Below are summaries of the `debian` files used to build these packages. All of the code [is on GitHub](#), including [the Makefile](#).

---

[The control file](#) (the basic details of the package, its version and dependencies):

```
Source: simbamond
Section: admin
Priority: optional
Maintainer: Hamish Cunningham (http://gate.ac.uk/hamish/) <hamish@gate.ac.uk>
Build-Depends: debhelper (>= 8.0.0), devscripts, gawk
Standards-Version: 3.9.3
Homepage: http://pi.gate.ac.uk/pages/mopi.html#simbamon
Vcs-Git: git://github.com/hamishcunningham/pi-tronics.git
Vcs-Browser: https://github.com/hamishcunningham/pi-tronics/tree/master/simbamon

Package: simbamond
Architecture: all
Depends: bc, ${misc:Depends}
Recommends: gpio
Description: SimBaMon, a Simple Battery Monitor
 SimBaMon is an open source Linux daemon for monitoring battery levels;
...
See http://pi.gate.ac.uk/pages/mopi.html#simbamon
```

---

[The changelog file](#) (the changes present in each version):

```
simbamond (1.3) unstable; urgency=low
 * Snapshot releases in the 1.3+4 series.
 -- Hamish Cunningham (http://gate.ac.uk/hamish/) <hamish@gate.ac.uk> Tue, 17 Sep 2013 11:11:11 +0100

...

simbamond (1.0) unstable; urgency=low
 * Initial Release.
 -- Hamish Cunningham (http://gate.ac.uk/hamish/) <hamish@gate.ac.uk> Wed, 14 Aug 2013 11:11:11 +0100
```

(Use the `dch -i` to add a new entry to `changelog`.)

---

[The copyright file](#) (the licence):



```
Format: http://dep.debian.net/deps/dep5
Upstream-Name: simbamon
Source: https://github.com/hamishcunningham/pi-tronics/tree/master/simbamon

Files: *
Copyright: 2013 Hamish Cunningham <hamish@gate.ac.uk>
License: GPL-3.0+

Files: debian/*
Copyright: 2013 Hamish Cunningham <hamish@gate.ac.uk>
License: GPL-3.0+

License: GPL-3.0+
This program is free software: you can redistribute it and/or modify
...

```

---

[The docs file](#) (listing documentation files):

```
man/simbamond.txt
README.txt

```

---

[The README file](#) (details of the *packaging* of the software):

```
The Debian Package simbamond
-----

```

```
Comments regarding the package:

```

```
- seeded using dh_make -p=simbamond_1.0 --native
- adapted using instructions in the maint-guide package

-- Hamish Cunningham <hamish@gate.ac.uk> Sat, 10 Aug 2013 18:51:23 +0300

```


---

There are a couple more files needed for SimBaMon and BlinkIP that relate to their role as daemons — see `postinst`, `postrm` and the `.default` and `.init` links in [the debian directory](#).

And that's it! With the appropriate Makefile magic, you can now say "make package" and out will pop the files you need to upload to an Ubuntu PPA, and/or contribute to Raspbian, and/or put on a download page for people to install themselves.

## 5.2. WiringPi

A lot of our recent projects have used the excellent [WiringPi library](#) to [talk to the Pi's electronics](#) from software. A small frustration in this process has been the library's lack of integration into Raspbian... So I've written the code needed to do this, and made it available [from GitHub](#). It uses a packaging process exactly like the one described above.



Now we can install WiringPi without having to download or compile it, like this:

```
wget https://raw.githubusercontent.com/hamishcunningham/wiringpi/master/package/2.13/unstable/wiringpi_2.13_armhf.deb
sudo dpkg -i ./wiringpi_2.13_armhf.deb
```

Unlike the script-based examples in the previous section, WiringPi is written in the C programming language and therefore needs to be compiled before use. Gordon Henderson (WiringPi's author) uses a script called `build` to do this; to create a `.deb` I added a [Makefile](#) that copies code from the `build` script and adds an `install` target and packaging targets (like those used in the previous section).

Then I documented the other changes I needed to make (mainly adding the `debian` directory) and sent the details back to Gordon. Hopefully he'll pull them into his Git repository one of these days and start the process of getting WiringPi included in the official Raspbian distribution.

For reference and to give a flavour of the process, below are the details of the changes made to the library.

---

Most of the changes that I needed to make (as opposed to adding new stuff) are in this commit: <https://github.com/hamishcunningham/wiringpi/commit/707cf1bc343e07c9c07eb67c55ed93873c2c67c8>

All the changes needed are as follows:

1. I've added a top-level Makefile which does some of what the build script does (just building and installing the two libraries and the `gpio` command at present). I believe that the build script still works as it used to. The package has to be built on the Pi itself; I tried cross-compiling but didn't get far :-)
2. In the library Makefiles this line assumes that the binary has been written

into DESTDIR, without PREFIX: `@ln -sf $(DESTDIR)$(PREFIX)/lib  
/libwiringPiDev.so.$(VERSION) $(DESTDIR)/lib/libwiringPiDev.so`. This doesn't seem to be the case, however... so I've added a PREFIX. Perhaps I've missed something about how make should be invoked, or...?

3. The package build process requires that DESTDIR is used for everything — so calling "ldconfig" without parameterising it for DESTDIR causes an error. I've changed it to use DESTDIR for now, and also called ldconfig in the .deb's postinst and postrm scripts. This broke the build script's install, so I added this hack to the library Makefiles: `@if [ x$(DESTDIR) = x/usr ];  
then ldconfig; fi`
  4. The devLib/Makefile does a -I., but this doesn't pick up the headers in DESTDIR, so I've changed INCLUDE there to do so (in the same way the gpio/Makefile does).
  5. The gpio build needs the core library to be built first, so I've put both the bare "make" and the "make install" under the top-level "install" target. Probably non-optimal.
  6. I have changed the gpio install to use the "install" command, which doesn't assume that the process is running as root.
  7. The .deb installs into /usr instead of /usr/local; I believe that Debian mandates that the latter is reserved for a "local administrator" or similar. The examples builds still work without change to the -I or -L flags as /usr is included in the default paths, it seems.
  8. I have added a compressed version of the man page, as that seems to be expected. I've also made it install the man page in /usr/share as that's the normal place on Debian. That might want parameterising in "build" if you want it to target other operating systems. Doing "man gpio" works but complains about lacking the .1 file; no idea why :-(
  9. I added an "install from .deb" para to the INSTALL file.
- 

## 6. The End

Here endeth the lesson. Debian packaging is a bit of a black art, but with a little effort (and a lot of copying from our elders and betters!) the results are very powerful, stable and long-lasting solutions to the problems of software distribution and installation. Now it's your turn ;-)

## Footnotes

1. The program is engraved on my soul — it was called SOP-1, for Sales Order Processing, and it had grown and grown far beyond the ability of a neophyte like myself to ever understand. Trial and error was my only weapon, and it was a definite trial with lots of errors.
2. The Internet, of course, mostly runs on Unix-based operating systems, as does your Pi, Android phones, and Apple computers.

3. There are several reasons why packaging is hard. Debian is a distribution of code largely produced by other projects, so the packaging documentation often assumes that we're starting from someone else's systems, whereas in our case that's not true. Its design also dates back to a time where disk space and network bandwidth were very limited and it was important to split systems down into very small chunks stored on different disk partitions, problems that are less acute today. Nevertheless the original designers did such a good job that it's still the best there is. Kudos.