

No.	Time	Source	Destination	Protocol	Length	Info
62	4.674087543	127.0.0.1	127.0.0.1	UDP	56	62680 → 3289 Len=14

Frame 62: 56 bytes on wire (448 bits), 56 bytes captured (448 bits) on interface wlp0s20f3, id 0  
Interface id: 0 (wlp0s20f3)  
Interface name: wlp0s20f3  
Encapsulation type: Ethernet (1)  
Arrival Time: Apr 1, 2025 13:10:11.569994666 EEST  
[Time shift for this packet: 0.000000000 seconds]  
Epoch Time: 1743502211.569994666 seconds  
[Time delta from previous captured frame: 0.567000616 seconds]  
[Time delta from previous displayed frame: 0.567000616 seconds]  
[Time since reference or first frame: 4.674087543 seconds]  
Frame Number: 62  
Frame Length: 56 bytes (448 bits)  
Capture Length: 56 bytes (448 bits)  
[Frame is marked: False]  
[Frame is ignored: False]  
[Protocols in frame: eth:ethertype:ip:udp:data]  
[Coloring Rule Name: UDP]  
[Coloring Rule String: udp]

Ethernet II, Src: IntelCor\_2f:30:5a (44:85:00:2f:30:5a), Dst: Broadcast (ff:ff:ff:ff:ff:ff)  
Destination: Broadcast (ff:ff:ff:ff:ff:ff)  
Address: Broadcast (ff:ff:ff:ff:ff:ff)  
.... 01. .... = LG bit: Locally administered address (this is NOT the factory default)  
.... 01. .... = IG bit: Group address (multicast/broadcast)  
Source: IntelCor\_2f:30:5a (44:85:00:2f:30:5a)  
Address: IntelCor\_2f:30:5a (44:85:00:2f:30:5a)  
.... 00. .... = LG bit: Globally unique address (factory default)  
.... 00. .... = IG bit: Individual address (unicast)  
Type: IPv4 (0x0800)

Internet Protocol Version 4, Src: 127.0.0.1, Dst: 127.0.0.1  
0100 .... = Version: 4  
.... 0101 = Header Length: 20 bytes (5)  
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)  
0000 00.. = Differentiated Services Codepoint: Default (0)  
.... 00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)  
Total Length: 42  
Identification: 0x9b15 (39701)  
Flags: 0x00  
0... .... = Reserved bit: Not set  
.0... .... = Don't fragment: Not set  
..1. .... = More fragments: Set  
...0 0000 0000 0000 = Fragment Offset: 0  
Time to Live: 128  
Protocol: UDP (17)  
Header Checksum: 0x2cda [validation disabled]  
[Header checksum status: Unverified]  
Source Address: 127.0.0.1  
Destination Address: 127.0.0.1

User Datagram Protocol, Src Port: 62680, Dst Port: 3289  
Source Port: 62680  
Destination Port: 3289  
Length: 26  
Checksum: 0xa14b [unverified]  
[Checksum Status: Unverified]  
[Stream index: 5]  
[Timestamps]  
[Time since first frame: 2.877525212 seconds]  
[Time since previous frame: 2.877525212 seconds]  
UDP payload (14 bytes)

Data (18 bytes)  
0000 6A 6C 6F 37 46 35 74 52 34 64 42 68 6A 4A 6A 64 68 48  
Data: 6A6C6F3746357452346442686A4A6A646848  
[Length: 18]