

Algorithms Comprehensive Exam (Fall 2020)

SHORT QUESTIONS (Answer all six questions, each carrying 7 points.)


1. Solve the following recurrences to get their runtime upper bounds:

$$T(n) = T(n-2) + n$$


$$T(n) = T\left(\frac{n}{2}\right) + n$$

$$T(n) = T(n-2) + T\left(\frac{n}{2}\right) + n$$


2. Give the visited vertex order of the following directed graph, starting with vertex s , under (1) breadth-first search and (2) depth-first search, respectively.



3. Follow Prim's Algorithm and Kruskal's Algorithm, respectively to derive the minimum spanning tree (MST) of the following graph. For every algorithm, write down the edge picked in each step. For example, Step 1: $(v1, v2)$.




4. Please use Johnson's Algorithm to reweight the directed graph shown below such that all edge weights are non-negative.




5. The utilization efficiency of a hash table depends heavily on its hashing function(s) employed. Describe with a diagram to illustrate how a multiplication method of hashing works on a machine with the word size of w bits for a hash table with 2^p entries, $p < w$.
6. Show your construction of an optimal Huffman code for the set of 12 frequencies: a:2 b:6 c:5 d:8 e:13 f:21 g:34 h:15 i:27 j:9 k:48 l:26.

LONG QUESTIONS (Answer all four questions, each carrying 15 points.)

1. Follow the Ford-Fulkerson Algorithm to compute the max flow of the flow network given below. Illustrate the corresponding residual network at each step of the Ford-Fulkerson Algorithm. Also, compute the min-cut of the flow network, with each step shown.



2. The following graph denotes a sequence of courses, with their dependencies on other courses shown. A directed edge from vertex u in the graph to vertex v indicates that course u must be taken before course v may start. Please apply DFS (hint: topological sort) to find an ordering of these courses that conforms to the shown dependencies. Illustrate each step.




3. An optimal binary search tree (OBST) for a given set of keys with known access probabilities ensures the minimum expected search cost for key accesses. Given the set of four keys with their access probabilities of $k_1 = 0.16$, $k_2 = 0.13$, $k_3 = 0.2$, $k_4 = 0.08$, respectively, and five non-existing probabilities of $d_0 = 0.12$, $d_1 = 0.1$, $d_2 = 0.06$, $d_3 = 0.11$, $d_4 = 0.04$, construct OBST following dynamic programming with memoization for the given four keys and demonstrate the constructed OBST, which contains all four keys (k_1, k_2, k_3, k_4) and five non-existing dummies (d_0, d_1, d_2, d_3, d_4). (Show your work using the three tables, for expected costs: $e[i, j]$, access weights: $w[i, j]$, and $root[i, j]$, with i in $e[i, j]$ and $w[i, j]$ ranging from 1 to 5, j in $e[i, j]$ and $w[i, j]$ ranging from 0 to 4, and both i and j in $root[i, j]$ ranging from 1 to 4).

```

OPTIMAL-BST( $p, q, n$ )
1  let  $e[1..n+1, 0..n], w[1..n+1, 0..n]$ ,
   and  $root[1..n, 1..n]$  be new tables
2  for  $i = 1$  to  $n+1$ 
3       $e[i, i-1] = q_{i-1}$ 
4       $w[i, i-1] = q_{i-1}$ 
5  for  $l = 1$  to  $n$ 
6      for  $i = 1$  to  $n-l+1$ 
7           $j = i+l-1$ 
8           $e[i, j] = \infty$ 
9           $w[i, j] = w[i, j-1] + p_j + q_j$ 
10         for  $r = i$  to  $j$ 
11              $t = e[i, r-1] + e[r+1, j] + w[i, j]$ 
12             if  $t < e[i, j]$ 
13                  $e[i, j] = t$ 
14                  $root[i, j] = r$ 
15  return  $e$  and  $root$ 

```

4. A Fibonacci min-heap (H) relies on the procedure of CONSOLIDATE to merge trees in the root list upon the operation of extracting the minimum node. For H below, show the final result after extracting $H.min$. (Also, give the result of every key consolidation step till its completion.)



Good Luck!