

Einführung in C++ – Übung 8

Testatgruppe A (Isaak)

Rasmus Diederichsen

7. Dezember 2014

Aufgabe 8.1 Auslagern von Funktionalität in Oberklassen

Die `Renderable`-Klasse kann abstrakt sein, da sie nur eine Methode enthält, die Subklassen überschreiben müssen (sollten), damit etwas passiert. Es ist nicht sinnvoll, die Funktionalität in der Oberklasse zu implementieren, da sich die `render()`-Methoden zwischen `TriangleMesh` und `TexturedMesh` unterscheiden.

Listing 1: `Renderable.hpp`

```
1  /**
2   * @file Renderable.hpp
3   * @author Rasmus Diederichsen (rdiederichse@uos.de)
4   * @version 04.12.2014
5   */
6
7  #ifndef RENDERABLE_KG6LA00J
8
9  #define RENDERABLE_KG6LA00J
10
11 namespace asteroids {
12
13     /**
14      * @class Renderable
15      * @brief Abstract class to represent something which can be
16           rendered on screen.
17     */
18     class Renderable {
19
20         /**
21          * @brief Render this object (pure virtual)
22          */
23         virtual void render () = 0;
24     };
25
26 #endif /* end of include guard: RENDERABLE_KG6LA00J */
```

Das gleiche gilt für `Transformable`, jede Subklasse ist für ihre Bewegung selbst verantwortlich. *Hinweis:* Die Methoden dieser Klasse sind in `TriangleMesh.cpp` implementiert, diese fehlten initial. Auch wurde in allen Klassen die Acquire des Singletons auf Pointer umgestellt.

Listing 2: Transformable.hpp

```

1  #ifndef TRANSFORMABLE_DILCYMZ4
2
3  #define TRANSFORMABLE_DILCYMZ4
4
5  #include "Renderable.hpp"
6  #ifdef __APPLE__
7  #include <OpenGL/gl.h>
8  #else
9  #include <GL/gl.h>
10 #endif
11
12 namespace asteroids
13 {
14     /**
15      * @class Transformable
16      * @brief Abstract base class for <tt>Mesh</tt>es which can be
17      *        moved &
18      *        rotated.
19      */
20     class Transformable : public Renderable
21     {
22     public:
23         /**
24          * @brief Rotate the Transformable
25          * @param axis axis of rotation
26          * @param speed speed of rotation
27          */
28         virtual void rotate(int axis, float speed) = 0;
29
30         /**
31          * @brief Move the Transformable along axis
32          * @param axis axis to move along
33          * @param speed speed of movement
34          */
35         virtual void move(int axis, float speed) = 0;
36
37     protected:
38         /**
39          * @brief Array containing the transformation matrix.
40          */
41         float m_transformation[16];
42
43         /**
44          * @brief Method to compute the transformation matrix.
45          */
46         virtual void computeMatrix() = 0;
47     };
48 }
49

```

```
50 #endif /* end of include guard: TRANSFORMABLE_DILCYMZ4 */
```

Das FixedObject ist leer, also nur ein Markerinterface.

Listing 3: FixedObject.hpp

```
1 #ifndef FIXEDOBJECT_4ST6ZIUC
2
3 #define FIXEDOBJECT_4ST6ZIUC
4
5 #include "Renderable.hpp"
6
7 namespace asteroids {
8
9     /**
10      * @class FixedObject
11      * @brief Represents something which cannot be moved or rotated.
12      */
13     class FixedObject : public Renderable { };
14 }
15
16 #endif /* end of include guard: FIXEDOBJECT_4ST6ZIUC */
```

Aufgabe 8.2 Erweiterungen für neue Dateiformate

Listing 4: TriangleMeshFactory.hpp

```
1 /**
2  * @brief Contains Factory for mesh generation.
3  *
4  * @file TriangleMeshFactory.hpp
5  * @author rdiederichse@uos.de
6  */
7 #ifndef TRIANGLEMESHFACTORY_H
8
9 #define TRIANGLEMESHFACTORY_H
10
11 #include "rendering/TriangleMesh.hpp"
12
13 namespace asteroids
14 {
15     /**
16      * @class TriangleMeshFactory
17      * @brief Singleton Factory class to encapsulate parsing meshes
18      *       from different file
19      *       types.
20      */
21     class TriangleMeshFactory
22     {
23     public:
24         /**
25          * @brief Returns a pointer to a mesh parsed from a given
26          *       file. Format
27          *       is recognized by extension.
28          */
```

```

27         * @param filename The file containing the mesh definition
28         * @return A pointer to the parsed mesh
29         */
30         TriangleMesh* getMesh(const std::string &filename) const;
31
32         /**
33          * @brief Method to acquire the singleton instance
34          * @return The singleton.
35          */
36         static TriangleMeshFactory* instance();
37
38     private:
39         /**
40          * Empty default constructor. Does nothing.
41          */
42         TriangleMeshFactory();
43
44         /**
45          * The singleton instance.
46          */
47         static TriangleMeshFactory* instance_ptr;
48
49         /**
50          * Copy constructor. Does nothing.
51          */
52         TriangleMeshFactory(const TriangleMeshFactory& f) {};
53
54         /**
55          * Assignment operator. Does nothing.
56          */
57         TriangleMeshFactory& operator=(const TriangleMesh& f) {};
58     };
59 } /* namespace asteroids */
60 #endif /* end of include guard: TRIANGLEMESHFACTORY_H */

```

Listing 5: TriangleMeshFactory.cpp

```

1  /**
2   * @brief TriangleMeshFactory implementation.
3   * @file TriangleMeshFactory.cpp
4   * @author rdiederichse@uos.de
5   */
6  #include "io/TriangleMeshFactory.hpp"
7  #include "ReadPLY.hpp"
8  #include "Read3DS.hpp"
9  #include "MeshReader.hpp"
10
11  using std::string;
12
13  namespace asteroids
14  {
15
16      TriangleMeshFactory::TriangleMeshFactory() {}
17      TriangleMeshFactory* TriangleMeshFactory::instance_ptr = NULL;
18
19      TriangleMeshFactory* TriangleMeshFactory::instance()
20      {

```

```

21     if (instance_ptr != NULL) return instance_ptr;
22     else return (instance_ptr = new TriangleMeshFactory);
23 }
24
25 TriangleMesh* TriangleMeshFactory::getMesh(const string &
26     filename) const
27 {
28     unsigned found = filename.find_last_of("/\\");
29     string basePath = filename.substr(0, found+1);
30     TextureFactory::setBasePath(basePath);
31
32     int pos;
33     MeshReader *reader;
34     if ((pos = filename.find(".ply")) == (filename.length() - 4))
35         // .ply extension
36     {
37         reader = new ReadPLY(filename);
38         return reader->getMesh();
39     } else if ((pos = filename.find(".3ds")) == (filename.length()
40         - 4)) // .3ds extension
41     {
42         reader = new Read3DS(filename);
43         return reader->getMesh();
44     } else // error
45     {
46         int i = filename.find_last_of(".");
47         std::cerr << "TriangleMeshFactory_Error: File " <<
48             filename << (i == string::npos ? " without extension"
49             : " of type " + filename.substr(i))
50             << " not readable." << std::endl;
51         return NULL;
52     }
53 }
54
55 } /* namespace asteroids */

```

Listing 6: TextureFactory.hpp

```

1  #ifndef TEXTUREFACTORY_H
2
3  #define TEXTUREFACTORY_H
4
5  #include "rendering/Texture.hpp"
6
7  namespace asteroids
8  {
9      class TextureFactory
10      {
11      public:
12          /**
13           * @brief Returns a pointer to a textured mesh parsed from
14             a given file. Format
15             * is recognized by extension.
16             *
17             * @param filename The file containing the mesh definition
18             *
19             * @return A pointer to the parsed mesh
20             */

```

```

19     Texture* getTexture(const std::string &filename) const;
20
21     /**
22      * @brief Method to acquire the singleton instance
23      * @return The singleton.
24      */
25     static TextureFactory* instance();
26
27     /**
28      * Set the base path relative to which textures will be
29      * loaded.
30      * @param basepath The path relative to which textures are
31      * loaded.
32      */
33     static void setBasePath(std::string basepath);
34
35 private:
36     /**
37      * Empty default constructor. Does nothing.
38      */
39     TextureFactory();
40
41     /**
42      * The singleton instance.
43      */
44     static TextureFactory* instance_ptr;
45
46     /**
47      * Copy constructor. Does nothing.
48      */
49     TextureFactory(const TextureFactory& f) {};
50
51     /**
52      * Assignment operator. Does nothing.
53      */
54     TextureFactory& operator=(const TextureFactory& f) {};
55
56     /**
57      * @brief The base path.
58      */
59     static std::string basepath;
60 };
61 } /* namespace asteroids */
62
63 #endif /* end of include guard: TEXTUREFACTORY_H */

```

Listing 7: TextureFactory.cpp

```

1  /**
2   * @file TextureFactory.cpp
3   * @author Rasmus Diederichsen (rdiederichse@uos.de)
4   * @version 03.12.2014
5   */
6
7  #include "TextureFactory.hpp"
8  #include "BitmapReader.hpp"
9  #include "ReadPPM.hpp"
10 #include "ReadJPG.hpp"

```

```

11 #include "ReadTGA.hpp"
12 #include <iostream>
13 #include <cstdint>
14
15 namespace asteroids
16 {
17
18     TextureFactory::TextureFactory() {}
19     TextureFactory* TextureFactory::instance_ptr = NULL;
20     std::string TextureFactory::basepath = "";
21
22     TextureFactory* TextureFactory::instance()
23     {
24         if (instance_ptr != NULL) return instance_ptr;
25         else return (instance_ptr = new TextureFactory);
26     }
27
28     Texture* TextureFactory::getTexture(const string &filename)
29     {
30         const
31         int pos;
32         BitmapReader *reader;
33         if ((pos = filename.find(".ppm")) == (filename.length() - 4))
34             // .ppm extension
35         {
36             reader = new ReadPPM(basepath + filename);
37             return new Texture(reader->getPixels(), reader->getWidth()
38                 , reader->getHeight());
39         } else if ((pos = filename.find(".jpg")) == (filename.length
40             () - 4)) // .jpg extension
41         {
42             reader = new ReadJPG(basepath + filename);
43             return new Texture(reader->getPixels(), reader->getWidth()
44                 , reader->getHeight());
45         } else if ((pos = filename.find(".tga")) == (filename.length
46             () - 4))
47         {
48             reader = new ReadTGA(basepath + filename);
49             return new Texture(reader->getPixels(), reader->getWidth()
50                 , reader->getHeight());
51         } else // error
52         {
53             int i = filename.find_last_of(".");
54             std::cerr << "TextureFactory␣Error:␣File␣" << filename
55                 << (i == string::npos ? "␣without␣extension" : "␣of␣"
56                     type␣" + filename.substr(i))
57                 << "␣not␣readable.␣" << std::endl;
58             return NULL;
59         }
60     }
61
62     void TextureFactory::setBasePath(string basepath)
63     {
64         TextureFactory::basepath = basepath;
65     }
66 }

```

```
60 } /* namespace asteroids */
```

Listing 8: ReadPPM.hpp

```
1  /**
2   * @file ReadPPM.hpp
3   * @author Rasmus Diederichsen (rdiederichse@uos.de)
4   * @version 02.12.2014
5   */
6
7  #ifndef READPPM_H
8
9  #define READPPM_H
10
11 #include "BitmapReader.hpp"
12 #include <fstream>
13
14 using std::ifstream;
15
16 namespace asteroids
17 {
18     /**
19      * @enum PPMTYPE
20      * @brief Constants for PPM types.
21      */
22     enum PPMTYPE {
23         P3, ///< Ascii file
24         P6, ///< Binary file
25         UNDEF ///< Unknown type (should lead to error)
26     };
27
28     /**
29      * @class ReadPPM
30      * @brief A reader for ppm images.
31      */
32     class ReadPPM : public BitmapReader
33     {
34     private:
35         /**
36          * @brief Reads linewise from a ppm file as long as the
37             current line starts
38          * with a '#'.
39          *
40          * After the method has run, the stream's current line
41             will
42          * be the first non-comment line after the position for
43             which the
44          * method was called.
45          * @param stream The input file stream to read from.
46          * @param buffer Char buffer to place the bytes or chars
47             in.
48          * @param bufsize The length of the buffer.
49          */
49         void readFirstNonCommentLine(ifstream& stream, char*
50             buffer, const int bufsize);
51     };
52 }
```



```

49     * @brief Parses a ppm header. Sets the members <tt>
        m_width</tt>,
50     * <tt>m_height</tt> and reads the magic number.
51     * @param filename The name of the file.
52     * @return The type of the file (binary or ascii). One of
53     * <tt>PPMTYPE</tt>
54     * @see ReadPPM::PPMTYPE
55     */
56     PPMTYPE readHeader(const std::string& filename);
57
58     /**
59     * The position right after the header. Seeking to this
        position and
60     * then reading will read everything except the header.
61     */
62     ifstream::pos_type end_header;
63
64     /**
65     * @brief Read an ascii ppm file.
66     * @param filename The name of the file.
67     */
68     void readP3(const std::string& filename);
69
70     /**
71     * @brief Read a binary ppm file.
72     * @param filename The name of the file.
73     */
74     void readP6(const std::string& filename);
75     public:
76
77     /**
78     * @brief Construct a PPM reader to read from a given file
        .
79     * @param filename The name of the file.
80     */
81     ReadPPM(const std::string& filename);
82
83     /**
84     * @brief Empty destructor. Deallocation of the image
        buffer must be
85     * taken care of by the client.
86     */
87     ~ReadPPM();
88 };
89 } /* namespace asteroids */
90
91 #endif /* end of include guard: READPPM_H */

```

Listing 9: ReadPPM.cpp

```

1  /**
2   * @file ReadPPM.cpp
3   * @author Rasmus Diederichsen (rdiederichse@uos.de)
4   * @version 02.12.2014
5   */
6
7  #include "ReadPPM.hpp"
8  #include <sstream>

```

```

9  #include <iostream>
10
11  using std::cout;
12  using std::cerr;
13  using std::endl;
14  using std::string;
15  using std::stringstream;
16  using std::ifstream;
17  using std::ios;
18
19  namespace asteroids
20  {
21      ReadPPM::ReadPPM(const std::string& filename)
22      {
23          cout << "ReadPPM: reading ppm file " << filename << endl;
24          m_pixels = NULL; // in case shit hits the fan.
25          m_height = m_width = 0;
26          PPMTYPE type = readHeader(filename); // parse header and
                recognise file type
27          // allocate only if needed.
28          if (type != UNDEF) m_pixels = new unsigned char[m_width *
                m_height * 3];
29
30          switch (type)
31          {
32              case P3:
33                  readP3(filename);
34                  break;
35              case P6:
36                  readP6(filename);
37                  break;
38              default:
39                  cerr << "ReadPPM: Error. Unknown PPM format." << endl;
40                  break;
41          }
42      }
43
44      void ReadPPM::readFirstNonCommentLine(ifstream& stream, char*
                buffer, const int bufsize)
45      {
46          do { // read at least one line
47              stream.getline(buffer, bufsize);
48          } while (stream.good() && (buffer[0] == '#')); // continue
                while comment
49          // now we have read the first non-comment line into the
                buffer.
50      }
51
52      PPMTYPE ReadPPM::readHeader(const string& filename)
53      {
54          ifstream file(filename.c_str());
55          if (file.good())
56          {
57              /* ATTENTION. THIS ERRONEOUSLY ASSUMES THAT EVERYTHING IS
                SEPARATED BY
58              NEWLINES, EXCEPT THE DIMENSIONS. NEED TO FIX THIS. */

```

```

59     const int bufsize = 70; // Acc. to spec, lines should not
        be longer
60     char buffer[bufsize]; // buffer to hold the line
61     readFirstNonCommentLine(file, buffer, bufsize); // fill it
62     string magic_number(buffer); // first line must contain
        magic number
63     readFirstNonCommentLine(file, buffer, bufsize);
64     string line(buffer); // next one must contain dimensions
65     stringstream ss(line); ss >> m_width >> m_height; // get
        them out
66     readFirstNonCommentLine(file, buffer, bufsize);
67     file.getline(buffer, bufsize); // skip the max color value
        . Assume it's 255..
68     end_header = file.tellg();
69     file.close();
70
71     cout << "ReadPPM: Parsed header of " << filename << ". "
        width=" << m_width
72         << " height=" << m_height << " magic number is "
73         << magic_number << endl;
74
75     if (magic_number == "P3") return P3;
76     else if (magic_number == "P6") return P6;
77     return UNDEF;
78 }
79
80 void ReadPPM::readP3(const string& filename)
81 {
82     cout << "ReadPPM: Reading ascii file " << filename << endl;
83     ifstream file(filename.c_str());
84     if (file.good())
85     {
86         file.seekg(end_header); // go back to where we left off
87         // the stream splits on whitespace so the chars can be
            read one after
88         // the other without hassle.
89         for(int i = 0; i < m_width * m_height * 3; i++)
90         {
91             int c;
92             file >> c; // we need to map an ascii number symbol (or
                more) to the
93                 // numerical value, not just use the symbols
                    itself
94             m_pixels[i] = (char)c;
95         }
96         file.close();
97     } else { cerr << "ReadPPM: Error, P3 file not good." << endl;
        } // TODO: Detailed error
98 }
99
100 void ReadPPM::readP6(const string& filename)
101 {
102     cout << "ReadPPM: Reading binary file " << filename << endl;
103     ifstream file(filename.c_str(), ios::binary); // open in
        binary mode
104     if (file.good())
105     {

```

```

106         file.seekg(end_header); // go back to where we left off
107         file.read((char *)m_pixels,m_width * m_height * 3); // not
            sure if good. dump whole binary blob into array.
108         file.close();
109     } else { cerr << "ReadPPM:␣Error,␣P6␣file␣not␣good." << endl;
            } // TODO: Detailed error
110 }
111
112 ReadPPM::~ReadPPM() { }
113
114 } /* namespace asteroids */

```