

Java Programming

V P Jayachitra

What is JSF?

- Java Server Faces (JSF) technology is a **front end** framework which makes the creation of user interface components easier by reusing the UI components.
- JSF is designed based on the Model View Controller pattern (MVC) which segregates the presentation, controller and the business logic.
- **UI Components:** Text fields, list boxes, checkboxes, labels, panels, radio buttons, and other elements

Why JSF?

- JavaServer Faces (JSF) is a new standard Java framework for building Web applications.
- **Java** specification for building component-based **user interfaces for web applications**
- JSF offers a clean separation between behavior and presentation for web applications.

JSF Features

- Component Based Framework.
- JSP is based on the Model-View-Controller concept
- Ease and Rapid web Development.
- Default Exception Handling.
- JSF separates the functionality of a component from the display of the component.

Why not JSF?

- JSF forces you to mix Java and xhtml code for the same feature.
- JSF project can be easily become too complex to maintain

JSF program

- JSF provides a standard HTML tag library which are rendered into corresponding html output.
- In order to use these these tags we need to use the following namespaces of URI in html node.
- `<html
xmlns="http://www.w3.org/1999/xhtml"
xmlns:h="http://java.sun.com/jsf/html" >`


JSF tags	HTML tags
h:inputText	<input type="text">
h:outputText	Plain text
h:form	<form>
h:commandButton	<input type=button> value can be "submit", "reset", or "image"
h:inputSecret	<input type="password">
h:inputTextarea	<textarea>
h:inputHidden	<input type="hidden">
h:dataTable	<table>
h:outputLabel	<label>
h:panelGrid	<table> element with <tr> and <td> elements
h:selectOneRadio	<input type="radio">
h:selectBooleanCheckbox	<input type="checkbox">

JSF tags are
similar to
html tags
with minor
variations



@ManagedBean(name="temperatureConvertor")

```
public class TemperatureConvertor {
    private double celsius;
    private double fahrenheit;
    private boolean initial= true;
    public double getCelsius() {
        return celsius; }
    public void setCelsius(double celsius) {
        this.celsius = celsius; }
    public double getFahrenheit() {
        return fahrenheit; }
    public boolean getInitial(){
        return initial; }
    public String reset (){
        initial = true;
        fahrenheit =0;
        celsius = 0;
        return "reset";
    }
    public String celsiusToFahrenheit() { initial
    = false;
    fahrenheit = (celsius *9 / 5) +32;
    return "calculated"; } }
```



```
<html>
<title>Celsius to Fahrenheit Converter</title>
<h:body>
    <h:form>
        <h:outputLabel value="Celsius">
        </h:outputLabel>
        <h:inputText
        value="#{temperatureConvertor.celsius}">
        </h:inputText>
        <h:commandButton action=
        "#{temperatureConvertor.celsiusToFahrenheit}"
        value="Calculate">
        </h:commandButton>
        <h:commandButton action=
        "#{temperatureConvertor.reset}" value="Reset">
        </h:commandButton>
    </h:form>
    <h3> Result </h3>
    <h:outputLabel value="Fahrenheit ">
    </h:outputLabel>
    <h:outputText
    value="#{temperatureConvertor.fahrenheit}" />
    </h:body> </html>
```


JSF-Example code 1

java class and X-html

@ManagedBean(name="hello")

This is the name for the object of HelloWorld class

Later can use in JSF tag to fetch its variables as #{hello.s1}

```
@ManagedBean(name="hello")
public class HelloWorld
{
    private String s1 = "Hello World!!";
}
```

```
<?xml version='1.0' encoding='UTF-8' ?>
<html
xmlns="https://www.w3.org/1999/xhtml"
xmlns:h="https://java.sun.com/jsf/html">
  <h:head>
    <title>Hello World JSF Example</title>
  </h:head>
  <h:body>
    #{hello.s1}
    <br />
    <br />
  </h:body>
</html>
```

Use <h:head> instead of <head>

Access the java class HelloWorld
variable s1 via java object helloWorld
declared using @ManagedBean

Example 2: jdbc connectivity

```
// index.xhtml
html xmlns="http://www.w3.org/1999/xhtml"
xmlns:h="http://xmlns.jcp.org/jsf/html">
<h:head> <title>User Form</title> </h:head>
<h:body>
<h:form>
<h:outputLabel for="username" value="User Name "/>
<h:inputText id="username" value="#{user.userName}"> </h:inputText><br/>
<h:outputLabel for="email" value="Email ID "/>
<h:inputText id="email" value="#{user.email}">
</h:inputText><br/><br/>
<h:commandButton action="#{user.submit()}" value="submit"/>
</h:form>
</h:body>
</html>
```

Example 2: jdbc connectivity

```
// User.java
@ManagedBean(name="user")
public class User {
    String userName;
    String email;
    public String getUser_name() {
        return userName; }
    public void setUser_name(String user_name)
    {
        this.userName = user_name; }
    public String getEmail() {
        return email; }
    public void setEmail(String email) {
        this.email = email;
    }
}
```

```
public boolean save(){
    int result = 0;
    try{
        String url="jdbc:oracle:thin:@localhost:1521:XE";
        String user ="SYSTEM";
        String pwd ="oracle";
        Connection
        con=DriverManager.getConnection(url,user,pwd);
        PreparedStatement stmt = con.prepareStatement(
            "insert into user(name,email) values(?,?)");
        stmt.setString(1, this.getUserName());
        stmt.setString(2, this.getEmail());
        result = stmt.executeUpdate();
    }catch(Exception e){ System.out.println(e); }
    if(result == 1){ return true; }
    else return false;
}

public String submit(){
    if(this.save()){ return "response.xhtml";
    }else return "index.xhtml";
    }
}
```

Example 2: jdbc connectivity

```
// response.xhtml
```

```
<html xmlns="http://www.w3.org/1999/xhtml"
```

```
xmlns:h="http://xmlns.jcp.org/jsf/html">
```

```
<h:head>
```

```
<title>Response Page</title>
```

```
</h:head>
```

```
<h:body>
```

```
<h1><h:outputText value="Hello #{user.userName}"/></h1>
```

```
<h:outputText value="Your Record has been Saved Successfully!"/>
```

```
</h:body>
```

```
</html>
```