

Acme Cloud Platform — API Reference

Version 3.7 | Internal Engineering

1. Authentication

All requests require a Bearer token in the Authorization header. Obtain a token via the `/v2/auth/token` endpoint. Tokens expire after 60 minutes.

2. Accounts

Endpoint: GET `/v2/accounts/{accountId}`

Retrieves account details including subscription status, billing contact, and entitlement summary. Returns 200 on success, ERR-4001 on invalid token, ERR-4404 if account not found.

3. Subscriptions

Endpoint: POST `/v2/accounts/{accountId}/subscriptions`

Creates a new subscription on the account. Required body fields: sku, billingCycle, seats. The sku must reference a valid SKU code (see Pricing & SKU Guide). Returns 201 on success, ERR-4012 if the parent account has an expired entitlement, ERR-4023 if quota is exceeded.

Endpoint: DELETE `/v2/subscriptions/{subscriptionId}`

Cancels an active subscription. Cancellation is effective at the end of the current billing period. Returns 204 on success, ERR-4012 if the subscription is already terminated.

4. Rate Limits

Default rate limit is 100 requests per minute per API key. Enterprise tier (SKU AC-CORE-ENT-ANNUAL) is raised to 1000 requests per minute. Exceeding the rate limit returns ERR-4029.