

Error Code Reference

Version 3.7 | All ERR-XXXX codes returned by the API

Authentication errors (4000-series)

ERR-4001 — Invalid or missing authentication token. The Bearer token in the Authorization header is malformed, expired, or revoked. Resolution: obtain a fresh token via `/v2/auth/token`.

ERR-4003 — Token signature verification failed. The token cannot be validated against the issuer's public key. Often indicates a cross-region misconfiguration.

Authorization errors (4010-series)

ERR-4012 — Subscription entitlement expired. The account associated with this request has a subscription whose entitlement has lapsed. The customer must renew the subscription before the API will accept further write operations on this account. Read-only endpoints continue to work for a 30-day grace period.

ERR-4015 — Insufficient role permissions. The authenticated principal does not have the required role to perform this operation. Required role appears in the response body.

Quota errors (4020-series)

ERR-4023 — Quota exceeded. The account has consumed its allotted seats, storage, or API calls for the current billing period. Customers may upgrade their SKU to raise quotas.

ERR-4029 — Rate limit exceeded. Too many requests in the last minute. Resolution: implement client-side backoff or upgrade to AC-CORE-ENT-ANNUAL for raised limits.

Server errors (5000-series)

ERR-5001 — Internal service error. An unexpected error occurred. Retry with exponential backoff.

ERR-5002 — Database unavailable. The downstream database is unreachable. The platform is in a degraded read-only mode.