Qualifying Dissertation for the Transfer of Status

Theo Wang

November 10, 2026

1 Introduction

2 Literature Review

2.1 Foundations of Probabilistic Programming

From Bayesian Networks to Probabilistic Programming A central tool in Bayesian probabilistic modelling is Bayesian networks [TODO: cite], a graphical representation of a joint distribution. Formally, a Bayesian network over a certain set of variables V is a directed acyclic graph over V, a domain D_x for each variable $x \in V$, and for each variable $v \in V$, a conditional distribution $P(x \mid \mathsf{Parents}(x))$. This data can be seen as a Markov factorisation of a joint distribution

$$P(x_1 ... x_n) = \prod_{x \in V} P(x \mid \mathsf{Parents}(x))$$

Bayesian networks are useful because their graphical structure encodes the conditional independencies between variables (a variable is assumed to only depend on its parents), exploited to make Bayesian inference (computing conditional distributions) more efficient. [TODO: cite again]

For instance consider the scenario where we are trying to model a car, which has fuel with probability 0.8, battery with probability 0.9, and only starts if it has both fuel and battery. Then we can model the joint distribution between fuel, $\mathsf{battery}$ and $\mathsf{carStarts}$ with the following Bayesian network:

[TODO: Draw Bayesian Network]

Probabilistic Programming languages can be seen as a compositional generalisation of Bayesian networks: they provide a compositional syntax for specifying probabilistic models and performing inference on them. Like for Bayesian networks, we can write program represent joint distributions, like in [TODO:]. Unlike Bayesian networks, we can also record observations like $\mathsf{carStarts} = \mathsf{True}$ using the $\mathsf{condition} : \mathbb{B} \to 1$ operation, like in [TODO:], or more general 'soft' conditioning using $\mathsf{score} : \mathbb{R}^+ \to 1$. Finally, general inference algorithms like [TODO:] allows one to sample from the conditional distribution that the program represents.

[TODO: Write program]

Semantics of PPLs The semantics of probabilistic programming languages are generally given in a category $\mathbf{C}$ that 'supports probability theory' with a normalised probability monad Prob. In the discrete case, one considers $\mathbf{Set}$ and the finitely supported distributions monad. Because $\mathbf{Set}$ is cartesian-closed, one can not only interpret first order programs, but also higher order ones like $(X \to \mathsf{Prob}(Y)) \to \mathsf{Prob}(Z)$. In the more general continuous case, one often uses categories like the category of measurable spaces Meas (or subcategories thereof) with the Giry monad $G : \mathsf{Meas} \to \mathsf{Meas}$ [TODO: cite]. Because Meas is famously not cartesian-closed, several works [28, 13] have developed the category of quasi-Borel spaces (QBS) as an alternative in which higher order probabilistic programming is possible. Many extensions to QBS have since been developed, such as ωQBS [TODO: cite], which enables recursion, and quasi-Borel families (QBFs), which enable dependent types [TODO: cite].

Normalised probability monads only allow one to interpret sampling; interpreting conditioning (or scoring in general) will require *unnormalised* probability monads Dist. An unnormalised probability monad should be a super-monad of the normalised counterpart. Without going into too much

detail, there are many possible choices for Dist with different trade-offs. For instance, we can consider $\mathsf{Dist}(X) = \mathsf{Prob}(X \times \mathbb{R}^+)$, which enables general scoring using a writer effect; or indeed the subdistribution monad $\mathsf{Dist}(X) = \mathsf{Prob}(X + 1)$, which only supports (hard) conditioning.

Synthetic Foundations

2.2 Foundations of Causal Modelling

2.2.1 Pearl's Three Rungs of Causality

2.2.2 Semantics of Causality

Causal Models

Causal Structures

2.3 Causal Probabilistic Programming Languages

2.3.1 Summary of our POPL 2027 paper

Contribution 1: semantic foundations of causal programming Our first contribution is to develop a semantic foundation of causal models by taking the analogy with probabilistic programs seriously. In **??**, we reconstruct Pearl's rungs of causality as a hierarchy of simple first order probabilistic programming languages L_1, L_2, L_3. Each language exposes more intension than the previous one using syntactic annotations, and causal inference is performed using program transformations that consume these syntactic annotations: L_1 is a standard first order PPL; L_2 exposes typed holes named *intervention labels*, canonically of type Maybe(A), allowing substituting to optionally perform an intervention; L_3 annotates each let binding with **exo** or **endo**, so that twinning can be formulated as a vectorisation transform. The same idea underlies the intervention-as-program-transformation view of Witty [31, 33], the logical account by Ibeling and Icard [14], and the string-diagrammatic accounts of Jacobs et al. [16] and Lorenz and Tull [20].

What is new is the observation that this simple setting yields a semantic characterisation of Pearl's rungs of causality (**??**). We develop a unified account of contextual equivalences that recovers the full spectrum of causal model equivalences by varying the class of admissible contexts, e.g. Rung 3 (L_3) programs are Rung 3 equivalent ($\equiv_3$) if they behave the same under all twinnings and interventions; Rung 2 equivalent ($\equiv_3^{\mathsf{intv}}$) if under all interventions; Rung 1 equivalent ($\equiv_3^{\mathsf{obs}}$) if they induce the same distribution under no intervention. The subscript 3 marks that we compare L_3 programs throughout; the superscript marks the rung of context tested against (obs, intv, or none for full rung-3 twinning). These equivalences form a strict inclusion hierarchy $\equiv_3 \subsetneq \equiv_3^{\mathsf{intv}} \subsetneq \equiv_3^{\mathsf{obs}}$, an analogue of the causal hierarchy's non-collapse [2], i.e. programs indistinguishable at a lower rung may still differ at a higher one.

In **??** we connect the framework to the theory of SCMs, showing that L_3 extends SCMs conservatively: each SCM can be compiled into L_3, preserving the semantics of intervention and twinning (**??**). Through this compilation, we show that the hierarchy of SCM equivalences developed by Bongers et al. [5] is naturally subsumed by our program equivalences (**??**).

Contribution 2: Typed abstractions and denotational semantics for expressive causal probabilistic programming Our second contribution is the development of L_{HO}, a semantically-founded, expressive, and typed language for higher-order causal probabilistic programming. L_{HO} has a similar programming model to ChiRho [8, 30]: it is expressive as a programming language (higher order, with control flow) and as a causal calculus (rich, higher order interventions, see **??**); we illustrate it with examples such as mediation analysis, which decomposes a causal effect into a direct path and a path through an intermediate variable (**??**). However, unlike ChiRho, it extends the first-order languages in a semantic-preserving way (**??**).

Rung 2: To manage interventions, we track intervention labels using *grading* [21, 17, 9, 10, 26], similarly to the **ImP** construction in [19] or intervention points in [30]. We define a graded reader monad $\mathcal{I}_{[\tau_1 \ldots \tau_n]}(X) \triangleq \prod_i \tau_i \to \mathsf{Meas}(X)$ graded by lists of intervention types $[\tau_1 ... \tau_n]$, where Meas is the unnormalised probability monad. A causal model of type $\mathcal{I}_{[\tau_1 \ldots \tau_n]}(X)$ is an intervenable probabilistic program with n typed intervenable holes, each of type τ_i, and a `do` intervention on the ith hole is simply partial application.

Rung 3: To manage counterfactuals, we first note that we will consider *n-world twinning*, which creates n copies of the original model, because general counterfactual reasoning may require more than 2 copies. We now ask: what is the type of a model under twinning? The twinned version of the car model where only `fuel` is intervenable and `carStarts` is returned has type $\mathcal{I}_{[(\mathrm{Maybe}(\mathbb{B}))^n]}(\mathbb{B}^n)$: an intervenable computation with n intervention labels (one `fuel` intervention label per world), and returning n copies of `carStarts`. The trick is to make each causal model carry its behaviour under twinning, for any world count n. In other words the *twinnable* car model is a world-polymorphic vectorised computation of type $\forall n. \mathcal{I}_{[(\mathrm{Maybe}(\mathbb{B}))^n]}(\mathbb{B}^n)$, where $\forall$ denotes System-F-style polymorphism [25, 12]. Endogenous variables like `carStarts` become n-dimensional vectors, where n is the number of worlds, and compose together using the applicative interface [11]. Twinning is then a simple type application. The corresponding technical setting is the functor category $[\mathbf{Bij}, \mathbf{C}]$, where $\mathbf{C}$ is the semantic model of the underlying PPL, e.g. $\mathbf{C} = \mathbf{Qbs}$ if it is continuous and higher order. Each type A is informally an n-indexed family of $\mathbf{C}$-objects $[\![A]\!](n)$, and each function $A \to B$ is interpreted as an n-indexed family of morphisms $[\![A]\!](n) \to [\![B]\!](n)$, i.e. its behaviour under n-world twinning. This use is similar to names in nominal sets [23].

We derive L_{HO} by denotational and functional programming techniques. In **??**, we develop a denotational semantics for our hierarchy of languages, which we show equivalent to the operational description (**????**). We then turn the categorical abstractions we develop into functional programming abstractions (**??**).

2.3.2 Prior existing causal languages and libraries

Many practical tools like DoWhy (part of the PyWhy ecosystem [24]) are libraries for manipulating SCMs as graphs and thus have limited expressiveness. DoWhy's GCM module nonetheless reaches rung 3, computing sample-level counterfactuals on fitted mechanisms [4]. Among causal PPLs proper, several stop at rung 2. Brulé's Whittemore [6], an early embedded causal DSL, covers rung-2 identification and estimation. Pyro provides a `do` effect handler [3], the design that ChiRho generalises; PyMC's `do` performs graph surgery on the computation graph [1, 15]. Witty et al. [32] treat an intervention as a source transformation that replaces subterms, powerful (shift, variance-scaling, mechanism replacement) but non-compositional. In contrast, our languages only expose simple typed holes, which generalise to the same powerful classes of interventions for free at higher-order (**??**). Rung-3 queries can sometimes be re-encoded on such systems by hand by an identifiability argument [27].

Four systems support rung 3 natively [29, 8, 22, 18]. **OmegaC** [29] obtains rung 2 through a non-standard lazy evaluation strategy: a let-binding evaluates the bound expression e to a closure $\langle \Gamma, e \rangle$ and $\mathsf{do}(x \mapsto e')$ retroactively modifies that closure $\langle \Gamma[x \mapsto e'], e \rangle$, reminiscent of dynamic binding. Rung 3 is enabled by making each program by construction an SCM-like deterministic function of an explicit exogenous noise ω. OmegaC is limited in expressiveness (sampling and building random variables are separate), and only has an operational semantics. We conjecture our formalism can model OmegaC's core denotationally. **MultiVerse** [22] realises Pearl's abduction–action–prediction recipe as an importance-sampling engine, without a formal semantics. **ChiRho** [8, 7], built from effect handlers and tensor broadcasting, is both the system closest to ours, and our initial motivation. Its recent distillation into typed functional abstractions [30] bears clear similarities to L_{HO}: intervention *points* tracked in a reader monad (our *labels* leave open how an intervention is consumed), vectorisation used in an applicative way for twinning. Two differences are key. First, our rungs 2 and 3 are decoupled: interventions never create worlds; twinning alone does. Under ChiRho's multi-world handler, by contrast, each intervention doubles the number of worlds. Second, L_{HO} fixes the number of worlds at twinning time and whether a variable is vectorised (X or $\mathcal{E}(X)$) determines whether it is exogenous or endogenous. In contrast, ChiRho vectorises its values by default (MVal in the typed distillation [30])

and encodes an implicit sharing inference using tensor broadcasting: a random draw is shared wherever broadcasting permits, while sample sites downstream of an intervention will draw fresh noise per world. ChiRho's MVal thus allows finer control over sharing than L_{HO}, but its relation to Pearl's twinning semantics is less clear. Finally, **probabilistic logic programming** also reaches rung 3: Kiesel et al. [18] answer counterfactual queries on ProbLog programs by a transformation proved correct against Pearl's semantics.

2.4 Brief overview of notions of causality

2.4.1 Logical, Diagrammatic, Categorical notions of Causality

2.4.2 "Causality" in other fields

3 Project Proposal

3.1 Summary of the current work done

3.2 Developing the field of Causal PPLs

3.2.1 Putting the language into practice

3.2.2 Expressivity

3.3 Better understanding our categorical constructions

3.3.1 Relation to other constructions

3.3.2 A more synthetic approach?

3.4 Understanding causality using a graph-centered approach

3.5 Understanding relationship with 'causality' as used in other fields

3.5.1 Concurrency

3.5.2 Higher-order processes and quantum causality

References

[1] Oriol Abril-Pla et al. "PyMC: a modern, and comprehensive probabilistic programming framework in Python". In: *PeerJ Computer Science* 9 (2023), e1516. DOI: 10.7717/peerj-cs.1516.

[2] Elias Bareinboim et al. "On Pearl's Hierarchy and the Foundations of Causal Inference". In: *Probabilistic and Causal Inference: The Works of Judea Pearl*. 1st. New York, NY, USA: Association for Computing Machinery, 2022, pp. 507–556.

[3] Eli Bingham et al. "Pyro: Deep Universal Probabilistic Programming". In: *Journal of Machine Learning Research* (2018).

[4] Patrick Blöbaum et al. "DoWhy-GCM: An extension of DoWhy for causal inference in graphical causal models". In: *Journal of Machine Learning Research* 25 (2024). URL: https://jmlr.org/papers/v25/22-1258.html.

[5] Stephan Bongers et al. "Foundations of structural causal models with cycles and latent variables". In: *The Annals of Statistics* 49.5 (Oct. 2021). ISSN: 0090-5364. DOI: 10.1214/21-aos2064. URL: http://dx.doi.org/10.1214/21-AOS2064.

[6] Joshua Brulé. *Whittemore: An embedded domain specific language for causal programming*. 2018. arXiv: 1812.11918 [cs.AI]. URL: https://arxiv.org/abs/1812.11918.

[7] *Causal probabilistic programming without tears - ChiRho documentation*. https://basisresearch.github.io/chirho/tutorial_i.html. Accessed: 2025-10-30.

[8] *ChiRho*. https://basisresearch.github.io/chirho. Accessed: 2025-10-30.

[9] Ulrich Dorsch, Stefan Milius, and Lutz Schröder. "Graded Monads and Graded Logics for the Linear Time–Branching Time Spectrum". In: *CONCUR 2019* (2019).

[10] Soichiro Fujii, Shin-ya Katsumata, and Paul-André Melliès. "Towards a formal theory of graded monads". In: *International Conference on Foundations of Software Science and Computation Structures*. Springer. 2016, pp. 513–530.

[11] Jeremy Gibbons. "APLicative programming with Naperian functors (extended abstract)". In: *Proceedings of the 1st International Workshop on Type-Driven Development*. TyDe 2016. Nara, Japan: Association for Computing Machinery, 2016, pp. 13–14. ISBN: 9781450344357. DOI: 10.1145/2976022.2976023. URL: https://doi.org/10.1145/2976022.2976023.

[12] Jean-Yves Girard. "Interprétation fonctionnelle et élimination des coupures de l'arithmétique d'ordre supérieur". PhD thesis. Université Paris 7, 1972.

[13] Chris Heunen et al. "A convenient category for higher-order probability theory". In: *2017 32nd Annual ACM/IEEE Symposium on Logic in Computer Science (LICS)*. IEEE, June 2017, pp. 1–12. DOI: 10.1109/lics.2017.8005137. URL: http://dx.doi.org/10.1109/LICS.2017.8005137.

[14] Duligur Ibeling and Thomas Icard. "Probabilistic Reasoning across the Causal Hierarchy". In: *CoRR* abs/2001.02889 (2020). arXiv: 2001.02889. URL: http://arxiv.org/abs/2001.02889.

[15] *Interventional distributions and graph mutation with the do-operator — PyMC example gallery*. https://www.pymc.io/projects/examples/en/latest/causal_inference/interventional_distribution.html. Accessed: 2026-07-05.

[16] Bart Jacobs, Aleks Kissinger, and Fabio Zanasi. "Causal inference by string diagram surgery". In: *Foundations of Software Science and Computation Structures: 22nd International Conference, FOSSACS 2019, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2019, Prague, Czech Republic, April 6–11, 2019, Proceedings 22*. Springer. 2019, pp. 313–329.

[17] Shin-ya Katsumata. "Parametric effect monads and semantics of effect systems". In: *SIGPLAN Not.* 49.1 (Jan. 2014), pp. 633–645. ISSN: 0362-1340. DOI: 10.1145/2578855.2535846. URL: https://doi.org/10.1145/2578855.2535846.

[18] Rafael Kiesel, Kilian Rückschloß, and Felix Weitkämper. ""What if?" in probabilistic logic programming". In: *Theory and Practice of Logic Programming* 23.4 (2023).

[19] Jack Liell-Cock and Sam Staton. "Compositional imprecise probability: A solution from graded monads and markov categories". In: *Proceedings of the ACM on Programming Languages* 9.POPL (2025), pp. 1596–1626.

[20] Robin Lorenz and Sean Tull. *Causal models in string diagrams*. 2023. arXiv: 2304.07638 [cs.LO]. URL: https://arxiv.org/abs/2304.07638.

[21] Dominic Orchard, Philip Wadler, and Harley Eades III. "Unifying graded and parameterised monads". In: *Proc. MSFP 2020* (2020).

[22] Yura Perov et al. "Multiverse: causal reasoning using importance sampling in probabilistic programming". In: *Symposium on advances in approximate bayesian inference*. PMLR. 2020, pp. 1–36.

[23] Andrew M. Pitts. *Nominal Sets: Names and Symmetry in Computer Science*. USA: Cambridge University Press, 2013. ISBN: 1107017785.

[24] *PyWhy, An Open Source Ecosystem for Causal Machine Learning*. https://www.pywhy.org/. Accessed: 2025-10-30.

[25] John C. Reynolds. "Towards a theory of type structure". In: *Programming Symposium, Proceedings Colloque Sur La Programmation*. Berlin, Heidelberg: Springer-Verlag, 1974, pp. 408–423. ISBN: 3540068597.

[26] Ralph Sarkis and Fabio Zanasi. *Graded String Diagrams for Imprecise Probability and Causal Intervention*. 2026. arXiv: 2501.18404 [math.CT]. URL: https://arxiv.org/abs/2501.18404.

[27] Ilya Shpitser and Judea Pearl. "What counterfactuals can be tested". In: *Proceedings of the Twenty-Third Conference on Uncertainty in Artificial Intelligence*. UAI'07. Vancouver, BC, Canada: AUAI Press, 2007, pp. 352–359. ISBN: 0974903930.

[28] Sam Staton et al. "Semantics for probabilistic programming: higher-order functions, continuous distributions, and soft constraints". In: *Proceedings of the 31st Annual ACM/IEEE Symposium on Logic in Computer Science*. LICS '16. New York, NY, USA: Association for Computing Machinery, 2016, pp. 525–534. ISBN: 9781450343916. DOI: 10.1145/2933575.2935313. URL: https://doi.org/10.1145/2933575.2935313.

[29] Zenna Tavares et al. "A language for counterfactual generative models". In: *International conference on machine learning*. PMLR. 2021, pp. 10173–10182.

[30] Théo Wang et al. *Typed Abstractions for Causal Probabilistic Programming*. Extended abstract presented at LAFI 2026: Workshop on Languages for Inference, co-located with POPL 2026. Non-archival workshop contribution. Rennes, France, Jan. 2026. URL: https://www.cl.cam.ac.uk/~jdy22/papers/typed-abstractions-for-causal-probabilistic-programming.pdf.

[31] Sam Witty, David Jensen, and Vikash Mansinghka. "SBI: A Simulation-Based Test of Identifiability for Bayesian Causal Inference". In: *arXiv preprint arXiv:2102.11761* (2021).

[32] Sam Witty et al. "Bayesian causal inference via probabilistic program synthesis". In: *CoRR* abs/1910.14124 (2019). arXiv: 1910.14124. URL: http://arxiv.org/abs/1910.14124.

[33] Sam A Witty. "Bayesian Structural Causal Inference with Probabilistic Programming". PhD thesis. University of Massachusetts Amherst, 2023.