```
172.16.25.111
                                                               SSDP
                                                                        179
                                                                              M-SEARCH * HTTP/1.1
   691 18.146632
                                          239.255.255.250
Frame 691: 179 bytes on wire (1432 bits), 179 bytes captured (1432 bits) on interface 0
   Interface id: 0 (\Device\NPF_{6853CBE4-78FA-4F49-A6B7-3D74C86A0839})
       Interface name: \Device\NPF_{6853CBE4-78FA-4F49-A6B7-3D74C86A0839}
   Encapsulation type: Ethernet (1)
   Arrival Time: Feb 21, 2018 21:48:10.244593000 Eastern Standard Time
   [Time shift for this packet: 0.000000000 seconds]
   Epoch Time: 1519267690.244593000 seconds
   [Time delta from previous captured frame: 0.191153000 seconds]
   [Time delta from previous displayed frame: 2.589700000 seconds]
   [Time since reference or first frame: 18.146632000 seconds]
   Frame Number: 691
   Frame Length: 179 bytes (1432 bits)
   Capture Length: 179 bytes (1432 bits)
   [Frame is marked: False]
   [Frame is ignored: False]
   [Protocols in frame: eth:ethertype:ip:udp:ssdp]
   [Coloring Rule Name: UDP]
   [Coloring Rule String: udp]
Ethernet II, Src: RivetNet_e1:f0:cf (9c:b6:d0:e1:f0:cf), Dst: IPv4mcast_7f:ff:fa (01:00:5e:7f:ff:fa)
   Destination: IPv4mcast_7f:ff:fa (01:00:5e:7f:ff:fa)
       Address: IPv4mcast_7f:ff:fa (01:00:5e:7f:ff:fa)
       .... ..0. .... = LG bit: Globally unique address (factory default)
       .... = IG bit: Group address (multicast/broadcast)
   Source: RivetNet_e1:f0:cf (9c:b6:d0:e1:f0:cf)
       Address: RivetNet_e1:f0:cf (9c:b6:d0:e1:f0:cf)
       ......0. .... = LG bit: Globally unique address (factory default)
       .... = IG bit: Individual address (unicast)
   Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 172.16.25.111, Dst: 239.255.255.250
   0100 .... = Version: 4
   .... 0101 = Header Length: 20 bytes (5)
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
       0000 00.. = Differentiated Services Codepoint: Default (0)
       .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
   Total Length: 165
   Identification: 0x64ee (25838)
   Flags: 0x00
       0... = Reserved bit: Not set
       .0.. .... = Don't fragment: Not set
       ..0. .... = More fragments: Not set
   Fragment offset: 0
   Time to live: 4
   Protocol: UDP (17)
   Header checksum: 0x9be0 [validation disabled]
   [Header checksum status: Unverified]
   Source: 172.16.25.111
   Destination: 239.255.255.250
   [Source GeoIP: Unknown]
   [Destination GeoIP: Unknown]
User Datagram Protocol, Src Port: 53915, Dst Port: 1900
   Source Port: 53915
   Destination Port: 1900
   Length: 145
   Checksum: 0x7d2c [unverified]
   [Checksum Status: Unverified]
   [Stream index: 3]
Simple Service Discovery Protocol
   M-SEARCH * HTTP/1.1\r\n
       [Expert Info (Chat/Sequence): M-SEARCH * HTTP/1.1\r\n]
           [M-SEARCH * HTTP/1.1\r\n]
           [Severity level: Chat]
           [Group: Sequence]
       Request Method: M-SEARCH
       Request URI: *
       Request Version: HTTP/1.1
   Host: 239.255.255.250:1900\r\n
   ST: urn:schemas-upnp-org:device:InternetGatewayDevice:1\r\n
   Man: "ssdp:discover"\r\n
   MX: 3\r\n
   \r\n
   [Full request URI: http://239.255.255.250:1900*]
   [HTTP request 2/6]
   [Prev request in frame: 566]
   [Next request in frame: 833]
0010 00 a5 64 ee 00 00 04 11 9b e0 ac 10 19 6f ef ff
                                                     ..d...........
0020 ff fa d2 9b 07 6c 00 91 7d 2c 4d 2d 53 45 41 52
                                                     .....1...},M-SEAR
0030 43 48 20 2a 20 48 54 54 50 2f 31 2e 31 0d 0a 48
                                                    CH * HTTP/1.1..H
0040 6f 73 74 3a 20 32 33 39 2e 32 35 35 2e 32 35 35
                                                     ost: 239.255.255
.250:1900..ST: u
```

0060 72 6e 3a 73 63 68 65 6d 61 73 2d 75 70 6e 70 2d 0070 6f 72 67 3a 64 65 76 69 63 65 3a 49 6e 74 65 72 0080 6e 65 74 47 61 74 65 77 61 79 44 65 76 69 63 65 0090 3a 31 0d 0a 4d 61 6e 3a 20 22 73 73 64 70 3a 64 00a0 69 73 63 6f 76 65 72 22 0d 0a 4d 58 3a 20 33 0d 00b0 0a 0d 0a

rn:schemas-upnporg:device:Inter netGatewayDevice :1..Man: "ssdp:d iscover"..MX: 3.