

Portable Aluminum-Seawater Energy System

Contents

1	Field of the Invention	2
2	Background of the Invention	2
3	Summary of the Invention	2
4	Detailed Description of the Invention	3
4.1	Core Components and Process	3
4.2	System Specifications	4
4.3	Power and Energy Calculations	5
4.3.1	Hydrogen Requirements for 10 kW Output	5
4.3.2	Aluminum Requirements for Hydrogen Production	5
4.3.3	Heat for Desalination	5
4.4	Scientific Basis and Novelty	5
5	Drawings	5
6	Claims	6
7	Abstract	6

1 Field of the Invention

The present invention relates to portable energy and water purification systems, specifically off-grid devices that harness chemical reactions between activated aluminum and seawater to generate hydrogen, heat, electricity, and desalinated water in a sustainable, closed-loop manner.

2 Background of the Invention

Access to clean water and reliable energy remains a critical challenge in off-grid, remote, or disaster-stricken areas. Traditional desalination methods, such as reverse osmosis (RO), often require significant electrical input from fossil fuels or grid power, contributing to carbon emissions and logistical complexities. Hydrogen production typically relies on electrolysis or steam reforming, which are energy-intensive and not feasible in remote settings without infrastructure.

Waste aluminum, abundant from scrap sources, can react with water to produce hydrogen and heat, but the natural oxide layer on aluminum inhibits this reaction, particularly in seawater. Recent advancements, such as activation with gallium-indium alloys or organic compounds like imidazole from coffee grounds, have enabled rapid reactions in saline environments. However, existing systems focus primarily on hydrogen generation and do not integrate desalination or multi-output utilization in a portable format.

The present invention addresses these gaps by providing a self-contained system that uses waste aluminum and seawater to simultaneously produce fresh water, hydrogen fuel, and energy, reducing reliance on external power and enabling circular byproduct recycling. This innovation targets markets including disaster relief, military operations, offshore rigs, islands, ships, and survival applications, with an estimated market potential of \$1.2–3.8 billion at a 13% CAGR.

3 Summary of the Invention

The invention comprises a portable system where activated waste aluminum pellets react with seawater in an exothermic process, generating hydrogen gas, heat, and aluminum hydroxide. The heat is captured via a heat exchanger to drive a turbine-powered reverse osmosis unit for desalination, producing fresh water and brine. Hydrogen is stored and used in a fuel cell for electricity, enabling self-sustaining operation or external power supply. Activation methods include gallium-indium alloys, tin-bismuth coatings, or caffeine/imidazole solutions for cost-effective, environmentally friendly alternatives.

Key features include:

- Off-grid operation using abundant waste materials.
- Dual outputs: ~1,000 liters fresh water/day and hydrogen for ~10 kW fuel cell output.

- Recyclable byproducts and recoverable activators for sustainability.
- Modular design for portability and scalability.

The system overcomes challenges in prior art by integrating heat utilization for desalination, minimizing activation costs through recovery, and ensuring safe byproduct handling.

4 Detailed Description of the Invention

4.1 Core Components and Process

The system is a compact, portable unit (e.g., backpack or cart-sized) consisting of:

- An aluminum pellet reservoir for storing pre-treated waste aluminum (2–4 mm pellets).
- A reaction chamber where seawater is introduced to initiate the aluminum-water reaction.
- A heat exchanger to capture exothermic heat using a working fluid (e.g., isobutane, ammonia, or steam).
- A turbine or expander connected to a reverse osmosis (RO) membrane system for desalination.
- Hydrogen capture and storage modules (e.g., compression tanks at 350–700 bar or liquid storage).
- A fuel cell for converting stored hydrogen to electricity.
- Filtration and settling tanks for byproduct management.

The process operates as follows:

1. **Aluminum Activation:** Waste aluminum pellets are pre-treated to disrupt the oxide layer. Methods include:
 - Application of gallium-indium (Ga-In) eutectic alloy via wiping or cold spray to form sparse “islands” for penetration without clumping.
 - Gallium-free alternatives: Tin-bismuth (Sn-Bi) coatings for micro-galvanic activation, or immersion in caffeine/imidazole solutions (e.g., derived from coffee grounds) to accelerate reactions in seawater.
 - Preparation: Pellets are chopped to 2–4 mm, cleaned with mild NaOH, and activated to achieve high surface area and rapid reaction rates (90–100% hydrogen yield in minutes, as demonstrated in related research).
2. **Reaction Phase:** Activated aluminum reacts with seawater in the chamber:
 - Chemical equation: $2\text{Al} + 6\text{H}_2\text{O} \rightarrow 2\text{Al}(\text{OH})_3 + 3\text{H}_2 + \text{heat}$.

- Outputs: Hydrogen gas (captured via gas separator), thermal energy (~ 139 kJ/g H_2), and aluminum hydroxide sludge.
 - The reaction proceeds efficiently in saline water without prior desalination, though slightly slower than in pure water.
3. **Heat Capture and Desalination:** Exothermic heat is transferred to a working fluid in the heat exchanger, driving an expansion turbine to generate mechanical pressure.
- This pressure powers the RO membrane, forcing seawater through to produce fresh water (permeate) and concentrated brine (reject).
 - Brine can be recycled as reaction feedstock or discharged with environmental safeguards (e.g., diffusion to minimize marine impact).
 - Excess heat can be used for additional processes, such as distillation or space heating.
4. **Hydrogen Storage and Utilization:** Captured hydrogen is compressed or liquefied for storage and fed into a proton exchange membrane (PEM) fuel cell.
- Electricity generated powers the system (e.g., pumps, controls) or external loads.
 - Optional: Integration with metal hydrides for safer, lower-pressure storage.
5. **Byproduct Management and Sustainability:**
- Aluminum hydroxide is filtered and collected; it can be recycled into alum for water treatment, boehmite for semiconductors, or neutralized for safe disposal.
 - Activators like Ga-In are recoverable (up to 99% efficiency) for reuse, reducing costs.
 - The system emits no carbon and uses waste aluminum, promoting circular economy principles.

4.2 System Specifications

- **Capacity:** $\sim 1,000$ liters fresh water/day; hydrogen sufficient for ~ 10 kW continuous fuel cell output.
- **Dimensions:** Portable unit (e.g., 50–100 kg, modular for transport).
- **Capital Cost:** \$10,000–15,000 per unit.
- **Operating Cost:** \$0.30–0.50 per 10 liters, primarily from pellet and activator refills.
- **Business Model:** Low-margin hardware sales; revenue from proprietary pre-treated pellet refills (similar to pod-based systems) and partnerships with scrap dealers for aluminum supply.

4.3 Power and Energy Calculations

The following calculations demonstrate the system's energy balance and scalability. All values are based on standard thermodynamic data and assume a 50% efficient PEM fuel cell.

4.3.1 Hydrogen Requirements for 10 kW Output

4.3.2 Aluminum Requirements for Hydrogen Production

4.3.3 Heat for Desalination

These calculations confirm the system's self-sufficiency, with excess energy for scaling or auxiliary uses.

4.4 Scientific Basis and Novelty

The invention builds on established aluminum activation techniques (e.g., Ga-In penetration or imidazole catalysis) for seawater-compatible hydrogen production, achieving high yields without carbon emissions. Uniqueness lies in the integrated use of reaction heat to drive RO desalination, creating a multi-output system not found in prior art. Challenges such as activator recovery, sludge handling, and efficiency are addressed through recyclable components and optimized designs (e.g., filtration tanks, supercritical CO₂ fluids).

Potential enhancements include solar-assisted startup, safer hydride storage, and brine diffusion for environmental compliance.

5 Drawings

The following drawings illustrate the preferred embodiments of the invention and are referenced in the detailed description:

1. **Figure 1:** Schematic diagram of the portable aluminum-seawater energy system, depicting the reaction chamber, heat exchanger, reverse osmosis unit, hydrogen storage, and fuel cell components.
2. **Figure 2:** Detailed view of the reaction chamber, showing the flow of activated aluminum pellets and seawater, with hydrogen and aluminum hydroxide outputs.

3. **Figure 3:** Diagram of the heat exchanger and turbine system, illustrating the transfer of exothermic heat to the reverse osmosis membrane for desalination.
4. **Figure 4:** Flowchart of the byproduct recycling process, including filtration of aluminum hydroxide and recovery of gallium-indium or alternative activators.

(Note: Actual drawings to be prepared and submitted separately, as per patent office requirements.)

6 Claims

1. A portable energy and desalination system comprising: a reaction chamber for mixing activated waste aluminum pellets with seawater to produce hydrogen, heat, and aluminum hydroxide via an exothermic reaction; a heat exchanger to capture said heat and drive a turbine-powered reverse osmosis membrane for producing desalinated water; a hydrogen storage and fuel cell module for generating electricity; wherein the aluminum is activated using gallium-indium alloy, tin-bismuth coating, or caffeine/imidazole solutions.
2. The system of claim 1, wherein the aluminum pellets are pre-treated to 2–4 mm size and activated with sparse islands of gallium-indium for recoverable, efficient reaction in saline water.
3. The system of claim 1, further comprising byproduct recycling means for converting aluminum hydroxide into alum or boehmite.
4. The system of claim 1, configured to produce at least 1,000 liters of fresh water per day and hydrogen sufficient for 10 kW fuel cell output, operating off-grid with waste aluminum inputs.
5. A method for off-grid water and energy production comprising: activating waste aluminum with a gallium-free agent such as caffeine; reacting said aluminum with seawater to generate hydrogen and heat; utilizing said heat to power reverse osmosis desalination; storing and converting hydrogen to electricity via a fuel cell.
6. The method of claim 5, further including recovering activators and recycling byproducts for sustainability.
7. The system of claim 1, wherein hydrogen storage is achieved via compression at 350–700 bar or liquefaction, with volumes calculated based on production rates of approximately 0.6 kg/hour.

7 Abstract

A portable, off-grid system utilizes waste aluminum pellets activated with a gallium-indium alloy or alternatives such as caffeine or imidazole, reacting with seawater

ter to produce desalinated water, hydrogen fuel, and usable heat or electricity. The exothermic reaction drives a closed-loop distillation and desalination process via a heat exchanger and reverse osmosis membrane, capturing hydrogen for fuel cell use and recycling byproducts for sustainability. The system is designed for remote, disaster relief, military, and maritime applications, providing approximately 1,000 liters of fresh water per day alongside energy outputs, with a business model focused on low-cost units and recurring refills.