



# IMPLEMENTAREA CONCURENTEI IN LIMBAJE DE PROGRAMARE

Concurenta

Threaduri


Memorie Partajata

Ioana Leustean



Part II. Concurrent Haskell  
Cap.7 & 8

<https://hackage.haskell.org/package/base-4.20.0.1/docs/Control-Concurrent.html>



`forkIO :: IO () -> IO ThreadId`

MVar  
mutable variable



## ➤ data MVar a


`newEmptyMVar :: IO (MVar a)` -- `m <- newEmptyMVar`  
-- `m` este o locatie goala

`newMVar :: a -> IO (MVar a)` -- `m <- newMVar v`  
-- `m` este o locatie care contine valoarea `v`

`putMVar :: MVar a -> a -> IO()` -- `putMVar m v`  
-- pune in `m` valoarea `v`  
-- asteapta (blocheaza thread-ul) daca `m` este plina

`takeMVar :: MVar a -> IO a` -- `v <- takeMVar m`  
-- intoarce in `v` valoarea din `m` si **goleste** `m`  
-- asteapta (blocheaza thread-ul) daca `m` este goala

`readMVar :: MVar a -> IO a` -- `v <- readMVar m` citeste atomic continutul lui `m`  
-- intoarce in `v` valoarea din `m` dar aceasta ramane in `m`  
-- asteapta (blocheaza thread-ul) daca `m` este goala



## ➤ Comunicare sincrona

Un thread – **reader**- citeste un fisier text linie cu linie

Liniile sunt trimise, pe rand,  
unui al doilea thread – **writer**- care le afiseaza  
in ordinea trimisa si le numara.

La sfarsit, thread-ul writer trimite thread-ului reader  
numarul de linii si acesta il afiseaza,

[http://rosettacode.org/wiki/Synchronous\\_concurrency](http://rosettacode.org/wiki/Synchronous_concurrency)

```
import Control.Concurrent
import Control.Concurrent.MVar

main = do
    lineVar <- newEmptyMVar
    countVar <- newEmptyMVar
    forkIO $ writer lineVar countVar
    reader lineVar countVar
```



## ➤ Comunicare sincrona

```
import Control.Concurrent
import Control.Concurrent.MVar

main = do
  lineVar <- newEmptyMVar
  countVar <- newEmptyMVar
  forkIO $ writer lineVar countVar
  reader lineVar countVar
```

```
reader lineVar countVar = do
  ls <- fmap lines (readFile "input.txt")
  mapM ((putMVar lineVar) . Just) ls
  putMVar lineVar Nothing
  n <- takeMVar countVar
  print n
```

[http://rosettacode.org/wiki/Synchronous\\_concurrency](http://rosettacode.org/wiki/Synchronous_concurrency)

<https://www.haskell.org/hoogle/>



## ➤ Comunicare sincrona

```
import Control.Concurrent
import Control.Concurrent.MVar

main = do
    lineVar <- newEmptyMVar
    countVar <- newEmptyMVar
    forkIO $ writer lineVar countVar
    reader lineVar countVar
```

```
readFile :: FilePath -> IO String
lines :: String -> [String]
fmap :: Functor f => (a -> b) -> f a -> f b
mapM :: Monad m => (a -> m b) -> [a] -> m [b]
```

```
reader lineVar countVar = do
    ls <- fmap lines (readFile "input.txt")
    mapM ((putMVar lineVar) . Just) ls
    putMVar lineVar Nothing
    n <- takeMVar countVar
    print n
```

```
writer lineVar countVar = loop 0
    where
        loop n = do
            l <- takeMVar lineVar
            case l of
                Just x -> do putStrLn x
                             loop (n+1)
                Nothing -> putMVar countVar n
```

[http://rosettacode.org/wiki/Synchronous\\_concurrency](http://rosettacode.org/wiki/Synchronous_concurrency)

<https://www.haskell.org/hoogle/>



## ➤ Comunicare sincrona

```
import GetURL
import Data.ByteString as B

action x = do
    r <- getURL x
    print (B.length r)
```

Fisierul "inputurl.txt" contine adrese web,  
iar **action** **descarca** paginile respective

```
reader lineVar countVar = do
    ls <- fmap lines (readFile "inputurl.txt")
    mapM ((putMVar lineVar) . Just) ls
    putMVar lineVar Nothing
    n <- takeMVar countVar
    print n

writer lineVar countVar = loop 0
    where
        loop n = do
            l <- takeMVar lineVar
            case l of
                Just x -> do
                    action x
                    loop (n+1)
                Nothing -> putMVar countVar n
```

<https://hackage.haskell.org/package/parconc-examples-0.1/src/GetURL.hs>

<https://www.haskell.org/hoogle/>



“**Concurrent computing** is a form of computing in which several computations are executing during overlapping time periods—*concurrently*—instead of *sequentially* (one completing before the next starts)[...]

*A concurrent system is one where a computation can advance without waiting for all other computations to complete; where more than one computation can advance at the same time.*”

*Operating System Concepts 9th edition, Abraham Silberschatz*

## Exemplu: incarcarea mai multor pagini web

secvential



concurent



```
import Data.ByteString as B
import GetURL
main = do
    m1 <- newEmptyMVar
    forkIO $ do
        r <- getURL "http://..."
        putMVar m1 r

    m2 <- newEmptyMVar
    forkIO $ do
        r <- getURL "http://..."
        putMVar m2 r

    r1 <- takeMVar m1
    r2 <- takeMVar m2

    print (B.length r1, B.length r2)
```

geturl1.hs ©2012, Simon Marlow





➤ Comunicare asincrona

Se creaza un thread separat pentru fiecare actiune si se asteapta rezultatul

```
var <- newEmptyMVar
forkIO $ do
    r <- getURL "http://... "
    putMVar var r
takeMVar var
```

```
a <- async (getURL "http://... ")
wait a
```

```
data Async a = Async (MVar a)
```

```
async :: IO a -> IO (Async a)
```

```
async action = do
```

```
    var <- newEmptyMVar
```

```
    forkIO (do r <- action; putMVar var r)
```

```
    return (Async var)
```

```
wait :: Async a -> IO a
```

```
wait (Async var) = readMVar var
```

**readMVar** nu devine goala dupa citire (multiple-wakeup)  
deci mai multe apeluri **wait** pot fi facute pentru  
aceeasi operatie asincrona



➤ Comunicare asincrona

Se creaza un thread separat pentru fiecare actiune si se asteapta rezultatul

```
data Async a = Async (MVar a)

async :: IO a -> IO (Async a)
async action = do
  var <- newEmptyMVar
  forkIO (do r <- action; putMVar var r)
  return (Async var)

wait :: Async a -> IO a
wait (Async var) = readMVar var
```

```
a <- async action
r <- wait a
```

```
import Data.ByteString as B
import GetURL

main = do
  a1 <- async (getURL "http://..." )
  a2 <- async (getURL "http://..." )
  r1 <- wait a1
  r2 <- wait a2
  print (B.length r1, B.length r2)
```



## ➤ Comunicare asincrona

```
data Async a = Async (MVar a)

async :: IO a -> IO (Async a)
async action = do
  var <- newEmptyMVar
  forkIO (do r <- action; putMVar var r)
  return (Async var)

wait :: Async a -> IO a
wait (Async var) = readMVar var
```

```
a <- async action
r <- wait a
```

```
import Data.ByteString as B
import GetURL
import TimeIt
import Text.Printf

timeDownload :: String -> IO ()
timeDownload url = do
  (page, time) <- timeit $ getURL url
  printf " %s (%d bytes, %.2fs)\n" url (B.length page) time

main = do
  a1 <- async (timeDownload "http://...")
  a2 <- async (timeDownload "http://...")
  wait a1
  wait a2
```



## ➤ Comunicare asincrona

```
import Data.ByteString as B
import GetURL
import Timeit
import Text.Printf

timeDownload :: String -> IO ()
timeDownload url = do
    (page, time) <- timeit $ getURL url
    printf "downloaded: %s (%d bytes, %.2fs)\n" url (B.length page) time

main = do
    a1 <- async (timeDownload "http://...")
    a2 <- async (timeDownload "http://...")
    wait a1
    wait a2
```

vor fi afisate statistici privind timpul de executie

```
*Main> :set +s
*Main> main
downloaded: http://old.uefiscdi.ro/ (74599 bytes, 3.96)
downloaded: http://old.uefiscdi.ro/ (74599 bytes, 4.01)
(4.01 secs, 52,080 bytes)
```



## ➤ Comunicare asincrona

```
import Control.Concurrent
import Text.Printf
import qualified Data.ByteString as B
import GetURL -- parconc-examples
import Timelt  -- parconc-examples

timeDownload :: String -> IO ()
timeDownload url = do
    (page, time) <- timeit $ getURL url
    printf " %s (%d bytes, %.2fs)\n" url (B.length page) time
```

```
sites = ["url1", "url2", ...]
main = do
    as <- mapM (async . timeDownload) sites
    mapM_ wait as
```

```
data Async a = Async (MVar a)

async :: IO a -> IO (Async a)
async action = do
    var <- newEmptyMVar
    forkIO (do r <- action; putMVar var r)
    return (Async var)

wait :: Async a -> IO a
wait (Async var) = readMVar var
```

geturl3.hs ©2012, Simon Marlow



## ➤ Async - comunicare asincrona (folosind MVar)

```
import Control.Concurrent
import Text.Printf
import qualified Data.ByteString as B
import GetURL -- parconc-examples
import Timelt  -- parconc-examples
```

```
timeDownload :: String -> IO ()
timeDownload url = do
    (page, time) <- timeit $ getURL url
    printf " %s (%d bytes, %.2fs)\n" url (B.length page) time
```

```
data Async a = Async (MVar a)

async :: IO a -> IO (Async a)
async action = do
    var <- newEmptyMVar
    forkIO (do r <- action; putMVar var r)
    return (Async var)
```

```
wait :: Async a -> IO a
wait (Async var) = readMVar var
```

```
main = do
    as <- mapM (async . timeDownload) sites -- sites = ["url1", "url2", ...]
    mapM_ wait as
```

**asteapta ca toate actiunile asincrone sa se termine,  
monitorizand fiecare actiune in parte; un alt thread ar putea  
interveni inainte ca toate actiunile sa se termine**

**Cum rezolvam aceasta problema?**



➤ Exemplu: o tranzactie bancara(I)

```
type Account = MVar Int
```

```
deposit :: Account -> Int -> IO() -- depunere  
deposit acc amount = do  
    x <- takeMVar acc  
    putMVar acc (x + amount)
```

```
withdraw :: Account -> Int -> IO() -- retragere  
withdraw acc amount = do  
    x <- takeMVar acc  
    putMVar acc (x - amount)
```

```
showBalance :: Account -> String -> IO() -- sold  
showBalance acc str = do  
    x <- takeMVar acc  
    putMVar acc x  
    putStrLn ("Contul " ++ str ++ ": " ++ (show x))
```



➤ Exemplu: o tranzactie bancara (I)

```
transfer :: Account -> Account -> Int -> IO()
transfer from to amount = do
    withdraw from amount
    deposit to amount
```

data race

un alt thread ar putea observa o stare  
in care banii nu se gasesc in nici un cont

```
import Control.Concurrent
import Control.Monad
```

```
type Account = MVar Int)
```

```
main = do
```

```
    aMVar <- newMVar 1000
```

```
    bMVar <- newMVar 1000
```

```
    forkIO(transfer aMVar bMVar 300)
```

```
    forkIO (transfer bMVar aMVar 500)
```

```
    showBalance aMVar "a"
```

```
    showBalance bMVar "b"
```





➤ Exemplu: o tranzactie bancara (I)

```
transfer :: Account -> Account -> Int -> IO()
transfer from to amount = do
    withdraw from amount
    -- threadDelay (5^6)
    deposit to amount
```

```
transfer :: Account -> Account -> Int -> IO()
transfer from to amount = do
    withdraw from amount
    -- threadDelay (5^6)
    deposit to amount
```

compunerea unor  
operatii corecte  
poate avea ca rezultat o  
operatie eronata

```
main = do
    aMVar <- newMVar 1000
    bMVar <- newMVar 1000
    forkIO(transfer aMVar bMVar 300)
    forkIO (transfer bMVar aMVar 500)

    showBalance aMVar "a"
    showBalance bMVar "b"
```

```
Prelude> :l mybank.hs
[1 of 1] Compiling Main
Ok, modules loaded: Main.
*Main> main
Contul a: 700
Contul b: 500
```

```
*Main> main
Contul a: 1000
Contul b: 800
```



## ➤ Ideea: tranzactiile in baze de date

A **transaction** is a sequence of operations performed as a single logical unit of work. A logical unit of work must exhibit four properties, called the atomicity, consistency, isolation, and durability (**ACID**) properties, to qualify as a transaction.

**Atomicity** - A transaction must be an atomic unit of work; either all of its data modifications are performed, or none of them is performed.

**Consistency** - When completed, a transaction must leave all data in a consistent state.

**Isolation** - Modifications made by concurrent transactions must be isolated from the modifications made by any other concurrent transactions.

**Durability** - After a transaction has completed, its effects are permanently in place in the system. The modifications persist even in the event of a system failure.

<https://technet.microsoft.com/en-us/library/ms190612%28v=sql.105%29.aspx>



## ➤ Atomicitate

- Modalități de sincronizare de nivel scăzut: variabile atomice
  - Atomicitate fără sincronizare. mult mai rapide decât cu locks
  - Java: **AtomicInteger, AtomicBoolean, ...**  
**get(), set(), incrementAndGet(), addAndGet(int d), compareAndSet(int old, int new)**
  - Haskell: **IORef a**  
**newIORef, readIORef, writeIORef, atomicModifyIORef, atomicWriteIORef**
  - Metodele sunt implementate folosind instrucțiuni hardware compare-and-swap
- Modalități de sincronizare de nivel înalt: Software Transactional Memory (STM)
  - sincronizare fără lacate
  - blocuri de instrucțiuni executate atomic



## ➤ Haskell: **variabile atomice**

doua thread-uri care incrementeaza acelasi contor

```
import Control.Concurrent
import Control.Monad
import Data.IORef (newIORef, readIORef, atomicModifyIORef')

data Async a = Async (MVar a)
async :: IO a -> IO (Async a)
wait :: Async a -> IO a

add m = replicateM_ 1000 $ atomicModifyIORef' m (\x -> (x+1, ()))

main = do
    m <- newIORef 0
    a1 <- async (add m)
    a2 <- async (add m)
    r1 <- wait a1
    r2 <- wait a2
    x <- readIORef m
    print x
```

```
data IORef a
newIORef :: a -> IO (IORef a)
readIORef :: IORef a -> IO a
```

```
atomicModifyIORef' :: IORef a -> (a -> (a, b)) -> IO b
```



## ➤ Haskell: **variabile atomice**

doua thread-uri care incrementeaza acelasi contor

```
data IRef a
newIORef :: a -> IO (IORef a)
readIORef :: IORef a -> IO a
atomicModifyIORef' :: IORef a -> (a -> (a, b)) -> IO b
```

```
main = do
  st <- newIORef ""
  a1 <- async $ replicateM 5 $ atomicModifyIORef' st (\s -> s ++ "A")
  a2 <- async $ replicateM 5 $ atomicModifyIORef' st (\s -> s ++ "B")
  a3 <- async $ replicateM 5 $ atomicModifyIORef' st (\s -> s ++ "C")
  r1 <- wait a1
  r2 <- wait a2
  r3 <- wait a3
  x <- readIORef st
  print x
```

```
*Main> main
"AAAAABBBBBBCCCCC"
*Main> main
"AAAAABBBBCCCCCB"
*Main> main
"AAAAABBBBBBCCCCC"
*Main> main
"AAAAABBBBCCCCCB"
*Main> main
"AAAAABBBBCCCCCB"
```



## ► Haskell: MVar

doua thread-uri care incrementeaza acelasi contor

```
import System.Random
act m x = do
  -- t <- getStdRandom (randomR (100, 1000))
  -- threadDelay t
  s <- takeMVar m
  putMVar m (s ++ x)
```

```
main = do
  st <- newMVar ""
  a1 <- async $ replicateM 5 $ act st "A"
  a2 <- async $ replicateM 5 $ act st "B"
  a3 <- async $ replicateM 5 $ act st "C"
  r1 <- wait a1
  r2 <- wait a2
  r3 <- wait a3
  x <- readMVar st
  print x
```

```
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AABBBBBCCCCCAA"
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AAAAABBBBBCCCCC"
*Main>
*Main> main
"AAAAABBBBBCCCCC"
*Main> main
"AAAAABBBBBCCCCCB"
```



## ➤ STM: Tranzactii bancare

```
transfer :: Account -> Account -> Int -> IO()
transfer from to amount = atomically $ do
    withdraw from amount
    deposit to amount
```

```
Prelude> :m Control.Concurrent.STM
Prelude Control.Concurrent.STM> :t atomically
atomically :: STM a -> IO a
```

### atomically

"takes an action as its argument, and performs it atomically. More precisely, it makes two guarantees:

**Atomicity:** the effects of atomically act become visible to another thread all at once. This ensures that no other thread can see a state in which money has been deposited in to but not yet withdrawn from from.

**Isolation:** during a call atomically act, the action act is completely unaffected by other threads. It is as if act takes a snapshot of the state of the world when it begins running, and then executes against that snapshot."

*Simon Peyton Jones, Beautiful Concurrency*



Monada STM  
este asemanatoare monadei IO

```
type Account = TVar Int
```

**TVar**  
variabile tranzactionale

```
deposit :: Account -> Int -> STM ()  
deposit acc amount = do  
  x <- readTVar acc  
  writeTVar acc (x + amount)
```

deposit  
actiune STM

```
withdraw :: Account -> Int -> STM ()  
withdraw acc amount = do  
  x <- readTVar acc  
  writeTVar acc (x - amount)
```

withdraw  
actiune STM

```
transfer :: Account -> Account -> Int -> IO()  
transfer from to amount = atomically $ do  
  withdraw from amount  
  deposit to amount
```

```
Prelude> :m Control.Concurrent.STM  
Prelude Control.Concurrent.STM> :t atomically  
atomically :: STM a -> IO a
```

**atomically** :: STM a -> IO a  
executa atomic o actiune STM





## ➤ Monada STM

```
data STM a
```

```
instance Monad STM
```

```
atomically :: STM a -> IO a
```

```
data TVar a
```

```
newTVar :: a -> STM (TVar a)
```

```
readTVar :: TVar a -> STM a
```

```
writeTVar :: TVar a -> a -> STM ()
```

Operatiile de baza ale monadei STM sunt scrierea si citirea variabilelor tranzactionale.

Variabilele tranzactionale sunt mutabile.  
O variabila TVar **nu** poate fi goala.

Scrierea si citirea variabilelor tranzactionale se face **fara bloca**re.

Actiunile STM au loc **atomic**.

O **tranzactie** este o actiune STM care este executata in monada IO folosind **atomically**



## ➤ Implementarea STM

"One particularly attractive implementation is well established in the database world, namely optimistic execution. When (**atomically act**) is performed, a **thread-local transaction log is allocated, initially empty**. Then the action act is performed, **without taking any locks at all**. While performing act, each call to **writeTVar** writes the address of the **TVar** and its new value into the log; it does not write to the **TVar** itself. Each call to **readTVar** first searches the log (in case the **TVar** was written by an earlier call to **writeTVar**); if no such record is found, the value is read from the **TVar** itself, and the **TVar** and value read are recorded in the log. In the meantime, other threads might be running their own atomic blocks, reading and writing **TVars** like crazy.


**When the action act is finished, the implementation first validates the log and, if validation is successful, commits the log.** The validation step examines each **readTVar** recorded in the log, and checks that the value in the log matches the value currently in the real **TVar**. If so, validation succeeds, and the commit step takes all the writes recorded in the log and writes them into the real **TVars**.

**What if validation fails? Then the transaction has had an inconsistent view of memory. So we abort the transaction, re-initialise the log, and run act all over again"**


*Simon Peyton Jones, Beautiful Concurrency*




1




2




3




4





5



6



7



click pe prezentare

T. Harris, M. Herlihy, S. Marlow, S. Peyton Jones,  
Concurrency unlocked

<https://www.haskell.org/hoogle/>



## ➤ Variabile mutabile: IORef, MVar, TVar

```
import Data.IORef
-- variabile mutabile in monada IO

newIORef :: a -> IO (IORef a)
readIORef :: IORef a -> IO a
writeIORef :: IORef a -> a -> IO ()
```

```
add :: IORef Int -> Int -> IO()
add rref n = do
    val <- readIORef rref
    writeIORef rref

main = do
    rref <- newIORef 0
    add rref 10
    val <- readIORef rref
    print val
```

```
import Control.Concurrent.STM.TVar
-- variabile tranzactionale
-- variabile mutabile in monada STM

newTVar :: a -> STM (TVar a)
readTVar :: TVar a -> STM a
writeTVar :: TVar a -> a -> STM ()
```

```
import Control.Concurrent.MVar
-- variabile de sincronizare
-- variabile mutabile in monada IO

newEmptyMVar :: IO (MVar a)
newMVar :: a -> IO (MVar a)
takeMVar :: MVar a -> IO a    -- blocheaza thread-ul
putMVar :: MVar a -> a -> IO () -- blocheaza thread-ul
```



```
import Control.Concurrent
import Control.Monad
import Control.Concurrent.STM
```

```
type Account = TVar Int
```

```
deposit :: Account -> Int -> STM ()
deposit acc amount = do
    x <- readTVar acc
    writeTVar acc (x + amount)
```

```
withdraw :: Account -> Int -> STM ()
withdraw acc amount = do
    x <- readTVar acc
    writeTVar acc (x - amount)
```

```
showBalance :: Account -> String -> IO()
showBalance acc str = do
    x <- atomically $ readTVar acc
    putStrLn ("Contul " ++ str ++ ": " ++ (show x))
```

mybankstm.hs

```
transfer :: Account -> Account -> Int -> IO()
transfer from to amount = atomically $ do
    withdraw from amount
    deposit to amount
```

**compositionalitate**

```
main = do
    (a,b) <- atomically $ do
        a <- newTVar 1000
        b <- newTVar 1000
        return (a,b)
    forkIO(transfer a b 300)
    forkIO (transfer b a 500)
    showBalance a "a"
    showBalance b "b"
```

```
Prelude> :l mybankstm.hs
[1 of 1] Compiling Main
Ok, modules loaded: Main.
*Main> main
Contul a: 1200
Contul b: 800
```



## ➤ Blocare (blocking)

"Suppose that a thread should *block* if it attempts to overdraw an account (i.e. withdraw more than the current balance). Situations like this are common in concurrent programs: for example, a thread should block if it reads from an empty buffer, or when it waits for an event. We achieve this in STM by adding the single function `retry`, whose type is

`retry :: STM a`

The semantics of `retry` are simple: if a retry action is performed, the current transaction is abandoned and retried at some later time."

```
limitedWithdraw :: Account -> Int -> STM ()
limitedWithdraw acc amount = do
  bal <- readTVar acc
  if amount > 0 && amount > bal
  then retry
  else writeTVar acc (bal - amount)
```

sau

```
check :: Bool -> STM ()
check True  = return ()
check False = retry
```

```
limitedWithdraw :: Account -> Int -> STM ()
limitedWithdraw acc amount = do
  bal <- readTVar acc
  check (amount <= 0 || amount <= bal)
  writeTVar acc (bal - amount)
```

[Simon Peyton Jones, Beautiful Concurrency](#)

<https://www.haskell.org/hoogle/>



## ➤ Alegerea (choice)

"Suppose you want to withdraw money from account A if it has enough money, but if not then withdraw it from account B? For that, we need the ability to choose an alternative action if the first one retries. To support choice, STM Haskell has one further primitive action, called `orElse`, whose type is

```
Prelude Control.Concurrent.STM> :t orElse  
orElse :: STM a -> STM a -> STM a
```

Its semantics are as follows: **the action `(orElse a1 a2)` first performs `a1`;**  
**if `a1` retries (i.e. calls `retry`), it tries `a2` instead;**  
**if `a2` also retries, the whole action retries. "**

```
limitedWithdraw :: Account -> Int -> STM ()  
limitedWithdraw acc amount = do  
  bal <- readTVar acc  
  if amount > 0 && amount > bal  
  then retry  
  else writeTVar acc (bal - amount)
```

*[Simon Peyton Jones, Beautiful Concurrency](#)*

```
limitedWithdraw2 :: Account -> Account -> Int -> STM ()  
limitedWithdraw2 acc1 acc2 amt  
  = orElse (limitedWithdraw acc1 amt) (limitedWithdraw acc2 amt)
```


Exercitiu: Modificati `mybankstm.hs` adaugand `retry` si `orElse`

<https://www.haskell.org/hoogle/>





## ➤ The Dining Philosophers



[http://rosettacode.org/wiki/Dining\\_philosophers](http://rosettacode.org/wiki/Dining_philosophers)

<http://www.tobiasmuehlbauer.com/2011/07/24/stm-haskell-dining-philosophers-problem/>

<http://www-ps.informatik.uni-kiel.de/~fhu/projects/stm.pdf>



<https://www.haskell.org/hoogle/>



"In ancient times, a wealthy philanthropist endowed a College to accommodate five eminent philosophers. Each philosopher had a room in which he could engage in his professional activity of thinking; there was also a common dining room, furnished with a circular table, surrounded by five chairs, each labelled by the name of the philosopher who was to sit in it. The names of the philosophers were PHIL0, PHIL1, PHIL2, PHIL3, PHIL4, and they were disposed in this order anticlockwise around the table. To the left of each philosopher there was laid a golden fork, and in the center stood a large bowl of spaghetti, which was constantly replenished.

A philosopher was expected to spend most of his time thinking; but when he felt hungry, he went to the dining room, sat down in his own chair, picked up his own fork on his left, and plunged it into the spaghetti. But such is the tangled nature of spaghetti that a second fork is required to carry it to the mouth. The philosopher therefore had also to pick up the fork on his right. When we was finished he would put down both his forks, get up from his chair, and continue thinking. Of course, a fork can be used by only one philosopher at a time. If the other philosopher wants it, he just has to wait until the fork is available again."

*C.A.R. Hoare, Communicating Sequential Processes, 2004*  
*(formulate initial de E. Dijkstra)*



➤ Dining Philosophers

Fiecare filozof executa  
la infinit urmatorul ciclu

asteapta sa manance


ia furculita stanga  
ia furculita dreapta

mananca

elibereaza furculita stanga  
elibereaza furculita dreapta

mediteaza

$n$  = numarul de filozofi



## ➤ Probleme

Excludere mutuala - doi filozofi diferiti nu pot folosi aceeași furculita simultan

Coadă circulară – filozofii se așteaptă unul pe celălalt

### Deadlock

Fiecare filozof are o furculiță și așteaptă ca ceilalți vecini să elibereze o furculiță

### Starvation

Un filozof nu mănâncă niciodată  
(ex: unul din vecini nu eliberează furculiță)



Fiecare filozof executa la infinit urmatorul ciclu

-- asteapta sa manance

ia furculita stanga  
ia furculita dreapta

mananca

elibereaza furculita stanga  
elibereaza furculita dreapta


mediteaza

actiuni atomice - elimina  
deadlock

durata finita – elimina  
starvation



- Dining Philosophers – varianta 1  
dinnerSrc1.hs



```
type Fork = TVar Bool          -- True daca furculita este libera

takeFork :: Fork -> STM ()
takeFork s = do
    b <- readTVar s
    if b then writeTVar s False
        else retry  -- asteapta pana se elibereaza furculita

releaseFork :: Fork -> STM ()
releaseFork fork = writeTVar fork True
```



## Un filozof

asteapta sa manance

ia furculita stanga  
ia furculita dreapta

mananca

elibereaza furculita stanga  
elibereaza furculita dreapta

mediteaza

```
import System.Random
type Name = String

runPhilosopher :: (Name, (Fork, Fork)) -> IO ()
runPhilosopher (name, (left, right)) = forever $ do
    putStrLn (name ++ " is hungry.")
    atomically $ do
        takeFork left
        takeFork right
    putStrLn (name ++ " got two forks and is now eating.")
    delay <- randomRIO (1,10)
    threadDelay (delay * 1000000)
    putStrLn (name ++ " is done eating. Going back to thinking.")
    atomically $ do
        releaseFork left
        releaseFork right
    delay <- randomRIO (1, 10)
    threadDelay (delay * 1000000)
```



```
philosophers :: [String]
philosophers = ["Aristotle", "Kant", "Spinoza", "Marx", "Russel"]
```

```
main = do
    forks <- atomically $ do
        sticks <- mapM (const (newTVar True)) [1..5]
        return sticks
```

```
let forkPairs = zip forks ((tail forks) ++ [head forks])
    philosophersWithForks = zip philosophers forkPairs
```

```
putStrLn "Running the philosophers. Press enter to quit."
```

```
mapM_ (forkIO . runPhilosopher) philosophersWithForks
```

```
getLine
```

```
Prelude> :t const
const :: a -> b -> a
Prelude> map (const True) [1..5]
[True,True,True,True,True]
```

```
Prelude> :l dinnersrc1.hs
[1 of 1] Compiling Philosophers      ( dinnersrc1
Ok, modules loaded: Philosophers.
*Philosophers> main
Loading package stm-2.4.2 ... linking ... done.
Running the philosophers. Press enter to quit.
Kant is hungry.
Kant got two forks  and is now eating.
Spinoza is hungry.
Marx is hungry.
Marx got two forks  and is now eating.
Russel is hungry.
Aristotle is hungry.
Marx is done eating. Going back to thinking.
Russel got two forks  and is now eating.
Marx is hungry.
Russel is done eating. Going back to thinking.
Marx got two forks  and is now eating.
Kant is done eating. Going back to thinking.
Aristotle got two forks  and is now eating.
Kant is hungry.
Russel is hungry.
```



## ➤ Implementarea `MVar` folosind `TVar`

o data de tip `MVar` are doua stari:

- goala - nu contine nici o valoare (blocheaza operatia `takeMVar`; permite operatia `putMVar`)
- plina - contine o valoare (permite operatia `takeMVar`; blocheaza operatia `putMVar`)

```
data TMVar a = TMVar (TVar (Maybe a))
```

```
-- Nothing indica faptul ca variabila e goala
```

```
newEmptyTMVar :: STM (TMVar a)
```

```
newEmptyTMVar = do
```

```
    t <- newTVar Nothing
```

```
    return (TMVar t)
```

[Composable Memory Transactions](#)

T. Harris, S. Marlow, S.P. Jones, M. Herlihy  
PPoPP '05

[PCPH, Cap.10, Blocking](#)





➤ TMVar – implementarea MVar folosind TVar

```
takeTMVar :: TMVar a -> STM a
takeTMVar (TMVar t) = do
  m <- readTVar t
  case m of
    Nothing -> retry -- blocare
    Just a -> do
      writeTVar t Nothing
      return a
```

```
putTMVar :: TMVar a -> a -> STM ()
putTMVar (TMVar t) = do
  m <- readTVar t
  case m of
    Just _ -> retry -- blocare
    Nothing -> do
      writeTVar t (Just a)
      return ()
```

*Composable Memory Transactions*  
T. Harris, S. Marlow, S.P. Jones, M. Herlihy  
PPoPP '05  
PCPH, Cap.10, Blocking



## ➤ MVar vs TMVar

```
takeBothMVar :: MVar a -> MVar b -> IO (a,b)
takeBothMVar tv tw = do
    v <- takeMVar tv
    w <- takeMVar tw
    return (v,w)
```

**putMVar tv x**

```
takeBothTMVar :: TMVar a -> TMVar b -> IO (a,b)
takeBothTMVar tv tw = atomically $ do
    v <- takeTMVar tv
    w <- takeTMVar tw
    return (v,w)
```

```
Prelude Control.Concurrent.STM> :t takeTMVar
takeTMVar :: TMVar a -> STM a
```



➤ Dining Philosophers - varianta2  
dinner3.hs

```
type Fork = TMVar Int

newFork :: Int -> STM Fork
newFork i = newTMVar i

takeFork :: Fork -> STM Int
takeFork fork = takeTMVar fork

releaseFork :: Int -> Fork -> STM ()
releaseFork i fork = putTMVar fork i
```

```
forks <- mapM newFork [1..5]
```

```
import System.Random
type Name = String

runPhilosopher :: (Name, (Fork, Fork)) -> IO ()
runPhilosopher (name, (left, right)) = forever $ do
    putStrLn (name ++ " is hungry.")
    (leftv, rightv) <- atomically $ do
        leftv <- takeFork left
        rightv <- takeFork right
        return (leftv, rightv)
    putStrLn (name ++ " got forks" ++ (show leftv) ++ ", " ++
        (show rightv) ++ " and is now eating.")
    delay <- randomRIO (1, 10)
    threadDelay (delay * 1000000)
    putStrLn (name ++ " is done eating. Going back to thinking.")
    atomically $ do
        releaseFork leftv left
        releaseFork rightv right
    delay <- randomRIO (1, 10)
    threadDelay (delay * 1000000)
```



➤ **Async** - comunicare asincrona (folosind **MVar**)

Se creaza un thread separat pentru fiecare actiune si se asteapta rezultatul

```
data Async a = Async (MVar a)

async :: IO a -> IO (Async a)
async action = do
    var <- newEmptyMVar
    forkIO (do r <- action; putMVar var r)
    return (Async var)

wait :: Async a -> IO a
wait (Async var) = readMVar var
```



➤ Async - comunicare asincrona (folosind MVar)

```
import Control.Concurrent
import Text.Printf
import qualified Data.ByteString as B
import GetURL -- parconc-examples
import Timelt -- parconc-examples
```

```
timeDownload :: String -> IO ()
timeDownload url = do
    (page, time) <- timeit $ getURL url
    printf " %s (%d bytes, %.2fs)\n" url (B.length page) time
```

```
main = do
    as <- mapM (async . timeDownload) sites -- sites = ["url1", "url2", ...]
    mapM_ wait as
```

```
data Async a = Async (MVar a)
```

```
async :: IO a -> IO (Async a)
async action = do
    var <- newEmptyMVar
    forkIO (do r <- action; putMVar var r)
    return (Async var)
```

```
wait :: Async a -> IO a
wait (Async var) = readMVar var
```

**asteapta ca toate actiunile asincrone sa se termine,  
monitorizand fiecare actiune in parte; un alt thread ar putea  
interveni inainte ca toate actiunile sa se termine**



## ➤ Async cu TMVar

```
data Async a = Async (TMVar a)

async :: IO a -> IO (Async a)
async action = do
    var <- atomically $ do
        var <- newEmptyTMVar
        return var
    forkIO (do r <- action; (atomically. putTMVar var) r)
    return (Async var)

waitSTM :: Async a -> STM a
waitSTM (Async var) = readTMVar var
```



## ➤ Async cu TMVar

```
data Async a = Async (TMVar a)

async :: IO a -> IO (Async a)
async action = do
    var <- atomically $ do
        var <- newEmptyTMVar
        return var
    forkIO (do r <- action; (atomically. putTMVar var) r)
    return (Async var)

waitSTM :: Async a -> STM a
waitSTM (Async var) = readTMVar var
```

```
waitAll :: [Async a] -> IO ()
waitAll asyncs = atomically $ mapM_ waitSTM asyncs
```

**monitorizeaza terminarea actiunilor global,  
intoarce dupa terminarea tuturor actiunilor din lista**



## ➤ waitAll

```
putStrLn "Running the philosophers."
```

```
as0 <- async $ runPhilosopher 2 (philosophersWithForks !! 0) --Aristotel
```

```
as1 <- async $ runPhilosopher 1 (philosophersWithForks !! 1) -- Kant
```

```
as2 <- async $ runPhilosopher 3 (philosophersWithForks !! 2) -- Spinoza
```

```
waitAll [as0,as1,as2]
```

```
putStrLn "WAIT RETURNED"
```

```
getLine
```

```
runPhilosopher :: Int -> (Name, (Fork, Fork)) -> IO ()
```

```
runPhilosopher n (name, (left, right)) = if (n==0) then return ()
```

```
else do
```

```
    putStrLn (name ++ " is hungry.")
```

```
    ....
```

```
    runPhilosopher (n-1) (name, (left, right))
```

```
Kant is leaving. ←
```

```
Aristotle got two forks and is now eating.
```

```
Aristotle is leaving. ←
```

```
Spinoza got two forks and is now eating.
```

```
Spinoza is done eating. Going back to thinking.
```

```
Spinoza is hungry.
```

```
Spinoza got two forks and is now eating.
```

```
Spinoza is leaving. ←
```

```
WAIT RETURNED
```



➤ Dining Philosophers – varianta in care astept ca fiecare sa manance de n ori

dinnersrc4.hs

```
runPhilosopher n (name, (left, right)) = .....

main = do
    forks <- atomically $ do
        sticks <- mapM (const (newTVar True)) [1..5]
        return sticks

    let forkPairs = zip forks ((tail forks) ++ [head forks])
        philosophersWithForks = zip philosophers forkPairs
        n = 2
    putStrLn "Running the philosophers. "
    as <- mapM (async . (runPhilosopher n)) philosophersWithForks
    waitAll as
    getLine
```

```
Aristotle is done eating. Going back to thinking.
Kant got two forks  and is now eating.
Aristotle is hungry.
Kant is done eating. Going back to thinking.
Aristotle got two forks  and is now eating.
Marx is done eating. Going back to thinking.
Spinoza got two forks  and is now eating.
Kant is hungry.
Spinoza is done eating. Going back to thinking.
Spinoza is hungry.
Spinoza got two forks  and is now eating.
Aristotle is leaving.
Russel got two forks  and is now eating.
Russel is done eating. Going back to thinking.
Marx is hungry.
Spinoza is leaving.
Kant got two forks  and is now eating.
Marx got two forks  and is now eating.
Marx is leaving.
Russel is hungry.
Russel got two forks  and is now eating.
Russel is leaving.
Kant is leaving.
```



➤ Dining Philosophers – varianta in care astept ca fiecare sa manance de n ori

```
runPhilosopher :: Int -> (Name, (Fork, Fork)) -> IO ()
runPhilosopher n (name, (left, right)) = if n == 0
    then return ()
    else do
        putStrLn (name ++ " is hungry.")
        atomically $ do
            takeFork left
            takeFork right
        putStrLn (name ++ " got two forks and is now eating.")
        delay <- randomRIO (1,10)
        threadDelay (delay * 1000000)
        if (n > 1) then putStrLn (name ++ " is done eating. Going back to thinking.")
            else putStrLn (name ++ " is leaving.")
        atomically $ do
            releaseFork left
            releaseFork right
        delay <- randomRIO (1, 10)
        threadDelay (delay * 1000000)
        runPhilosopher (n-1) (name, (left, right))
```



➤ Monada `Either a b`

```
Prelude> let nat x = if (x>=0) then Left x else Right "negativ"
Prelude> :t nat
nat :: (Ord a, Num a) => a -> Either a [Char]
Prelude> :t Left
Left :: a -> Either a b
Prelude> :t Right
Right :: b -> Either a b
```

```
Prelude> :t fmap
fmap :: Functor f => (a -> b) -> f a -> f b
```

```
waitEither :: Async a -> Async b -> IO (Either a b)
waitEither x y = atomically $
    fmap Left (waitSTM x)
    `orElse`
    fmap Right (waitSTM y)
```

[http://chimera.labs.oreilly.com/books/12300000000929/ch10.html#sec\\_stm-async](http://chimera.labs.oreilly.com/books/12300000000929/ch10.html#sec_stm-async)



## ➤ Async cu TMVar

```
data Async a = Async (TMVar a)

async :: IO a -> IO (Async a)
async action = do
    var <- atomically $ do
        var <- newEmptyTMVar
        return var
    forkIO (do r <- action; (atomically. putTMVar var) r)
    return (Async var)

waitSTM :: Async a -> STM a
waitSTM (Async var) = readTMVar var
```

```
waitAny :: [Async a] -> IO a
waitAny asyncs = atomically $ foldr orElse retry $ map waitSTM asyncs
```

**intoarce cand una din actiuni se termina**



## ➤ waitAny

```
putStrLn "Running the philosophers."  
as0 <- async $ runPhilosopher 3 (philosophersWithForks !! 0) -- Aristotel  
as1 <- async $ runPhilosopher 1 (philosophersWithForks !! 1) -- Kant  
as2 <- async $ runPhilosopher 3 (philosophersWithForks !! 2) -- Spinoza  
waitAny [as0,as1,as2]  
putStrLn "WAIT RETURNED"  
getLine
```

```
Kant is leaving. ←  
Aristotle got two forks and is now eating.  
WAIT RETURNED  
Aristotle is done eating. Going back to thinking.  
Spinoza got two forks and is now eating.  
Spinoza is done eating. Going back to thinking.  
Spinoza is hungry.  
Spinoza got two forks and is now eating.  
Spinoza is leaving.  
Aristotle is hungry.  
Aristotle got two forks and is now eating.  
Aristotle is leaving.
```

```
""
```

Programul continua  
pana se efectueaza `getLine`



Pe saptamana viitoare!

