20W LED ALS Flood Lamp

Product Code: FLALS20W Barcode: 600284406 5867

Ambient Light Sensor



Features

- Low energy consumption.
- Cost efficient.
- · Low thermal output.
- Shockproof and vibration proof.
- LED lamps run cool and so minimise deterioration, prolonging the performance and lifespan of your LED flood lamp.
- LED lamps switch ON / OFF instantly with no warm up time (ALS 1 minute) and are also flicker free.
- Leading technology using compact thermal management.
- Quality control throughout the manufacturing process.

Specifications

Specifications				
Supply Voltage	220-240Vac			
Power	20W			
Casing	Black - slim line			
ССТ	5700-6500K			
Light Output	1 560Lm ±10% >=80			
CRI				
Power Factor	>0.95			
Beam Angle	120° TBC			
EMC	SANS215 (CISPR15)			
	IEC61547			
Safety	IEC60598-1			
	IEC60598-2-5			
Surge	IEC61000-4-5 Class 2:			
	Line-Line > 0.5kV			
	Line-GND > 1 kV			
IP protection	65			
Working temperature range	0-40°C			
Ambient light sensor	100-400 lux threshold			
	±50 lux hystersis			
	Avg 1min			

Data based on actual measurements at 230Vac.



Compact >>> Thermal >>> Management






















For all home applications

Example:

- Pool
- Garden
- Driveway
- Braai area
- · Garage work pit



Important Note

It is always recommended that installation be done by a certified electrician.

The Kit Contains



1 x 20W LED flood lamp with Ambient Light Sensor

1 x User Manual



Package Dimensions

Height (mm)	Depth (mm)	Width (mm)	Weight (kg)	QTY
204	52	184	0.84	1



^{*}Lasts for more than 10 years based on 12 hours use per day.