LED Downlight





Product Code: FL42INTC Barcode: 600284406 2552



- More than 50% energy saving compared to CFL down lights.
- Dedicated design to reduce glare.
- Low maintenance cost.
- Easy Installation.
- 3 year warranty.
- LED driver included.





















TECHNICAL INFORMATION

Specifications

Wattage	42W	
Cutout	φ 210mm	
Dimensions	φ 220XH116mm	
Voltage	220V - 240V	
Frequency	50/60Hz	
Fitting colour	White	
Lumens	3800	
Power factor	0.95PF	
Beam angle	90°	
Lifetime	30 000 hours	
Colour rendering index	(CRI) ≥ 80Ra	
Rated	IP20	
Colour Temperature	4000K	

and 8", making installation more convenient.

This aesthetically pleasing downlight is suitable for use in offices, hotels, retail stores, hospitals and airports.

The dedicated design minimises glare, allowing for a lighting environment that is easy on the eyes. This range of downlights has the same cut out as traditional CFL fittings of 2.5", 3", 4", 6"

PACKAGE CONTENTS



1 x LED downlight

PACKAGE DIMENSIONS



122 247 252 1.25	Height	Depth	Width	Weight
	(mm)	(mm)	(mm)	(kg)
122 247 252 1.25	122	247	252	1.25



