

```
In [1]: from keras.datasets import boston_housing  
(train_data, train_targets), (test_data, test_targets) = boston_housing.load_data()
```

Downloading data from https://storage.googleapis.com/tensorflow/tf-keras-datasets/boston_housing.npz (https://storage.googleapis.com/tensorflow/tf-keras-datasets/boston_housing.npz)
57026/57026 [=====] - 0s 0us/step

```
In [2]: train_data.shape
```

```
Out[2]: (404, 13)
```

```
In [3]: test_data.shape
```

```
Out[3]: (102, 13)
```

```
In [4]: train_targets
```

```
Out[4]: array([15.2, 42.3, 50. , 21.1, 17.7, 18.5, 11.3, 15.6, 15.6, 14.4, 12.1,
 17.9, 23.1, 19.9, 15.7,  8.8, 50. , 22.5, 24.1, 27.5, 10.9, 30.8,
 32.9, 24. , 18.5, 13.3, 22.9, 34.7, 16.6, 17.5, 22.3, 16.1, 14.9,
 23.1, 34.9, 25. , 13.9, 13.1, 20.4, 20. , 15.2, 24.7, 22.2, 16.7,
 12.7, 15.6, 18.4, 21. , 30.1, 15.1, 18.7,  9.6, 31.5, 24.8, 19.1,
 22. , 14.5, 11. , 32. , 29.4, 20.3, 24.4, 14.6, 19.5, 14.1, 14.3,
 15.6, 10.5,  6.3, 19.3, 19.3, 13.4, 36.4, 17.8, 13.5, 16.5,  8.3,
 14.3, 16. , 13.4, 28.6, 43.5, 20.2, 22. , 23. , 20.7, 12.5, 48.5,
 14.6, 13.4, 23.7, 50. , 21.7, 39.8, 38.7, 22.2, 34.9, 22.5, 31.1,
 28.7, 46. , 41.7, 21. , 26.6, 15. , 24.4, 13.3, 21.2, 11.7, 21.7,
 19.4, 50. , 22.8, 19.7, 24.7, 36.2, 14.2, 18.9, 18.3, 20.6, 24.6,
 18.2,  8.7, 44. , 10.4, 13.2, 21.2, 37. , 30.7, 22.9, 20. , 19.3,
 31.7, 32. , 23.1, 18.8, 10.9, 50. , 19.6,  5. , 14.4, 19.8, 13.8,
 19.6, 23.9, 24.5, 25. , 19.9, 17.2, 24.6, 13.5, 26.6, 21.4, 11.9,
 22.6, 19.6,  8.5, 23.7, 23.1, 22.4, 20.5, 23.6, 18.4, 35.2, 23.1,
 27.9, 20.6, 23.7, 28. , 13.6, 27.1, 23.6, 20.6, 18.2, 21.7, 17.1,
  8.4, 25.3, 13.8, 22.2, 18.4, 20.7, 31.6, 30.5, 20.3,  8.8, 19.2,
 19.4, 23.1, 23. , 14.8, 48.8, 22.6, 33.4, 21.1, 13.6, 32.2, 13.1,
 23.4, 18.9, 23.9, 11.8, 23.3, 22.8, 19.6, 16.7, 13.4, 22.2, 20.4,
 21.8, 26.4, 14.9, 24.1, 23.8, 12.3, 29.1, 21. , 19.5, 23.3, 23.8,
 17.8, 11.5, 21.7, 19.9, 25. , 33.4, 28.5, 21.4, 24.3, 27.5, 33.1,
 16.2, 23.3, 48.3, 22.9, 22.8, 13.1, 12.7, 22.6, 15. , 15.3, 10.5,
 24. , 18.5, 21.7, 19.5, 33.2, 23.2,  5. , 19.1, 12.7, 22.3, 10.2,
 13.9, 16.3, 17. , 20.1, 29.9, 17.2, 37.3, 45.4, 17.8, 23.2, 29. ,
 22. , 18. , 17.4, 34.6, 20.1, 25. , 15.6, 24.8, 28.2, 21.2, 21.4,
 23.8, 31. , 26.2, 17.4, 37.9, 17.5, 20. ,  8.3, 23.9,  8.4, 13.8,
  7.2, 11.7, 17.1, 21.6, 50. , 16.1, 20.4, 20.6, 21.4, 20.6, 36.5,
  8.5, 24.8, 10.8, 21.9, 17.3, 18.9, 36.2, 14.9, 18.2, 33.3, 21.8,
 19.7, 31.6, 24.8, 19.4, 22.8,  7.5, 44.8, 16.8, 18.7, 50. , 50. ,
 19.5, 20.1, 50. , 17.2, 20.8, 19.3, 41.3, 20.4, 20.5, 13.8, 16.5,
 23.9, 20.6, 31.5, 23.3, 16.8, 14. , 33.8, 36.1, 12.8, 18.3, 18.7,
 19.1, 29. , 30.1, 50. , 50. , 22. , 11.9, 37.6, 50. , 22.7, 20.8,
 23.5, 27.9, 50. , 19.3, 23.9, 22.6, 15.2, 21.7, 19.2, 43.8, 20.3,
 33.2, 19.9, 22.5, 32.7, 22. , 17.1, 19. , 15. , 16.1, 25.1, 23.7,
 28.7, 37.2, 22.6, 16.4, 25. , 29.8, 22.1, 17.4, 18.1, 30.3, 17.5,
 24.7, 12.6, 26.5, 28.7, 13.3, 10.4, 24.4, 23. , 20. , 17.8,  7. ,
 11.8, 24.4, 13.8, 19.4, 25.2, 19.4, 19.4, 29.1])
```

```
In [5]: mean = train_data.mean(axis=0)
train_data -= mean
std = train_data.std(axis=0)
train_data /= std
test_data -= mean
test_data /= std
```

```
In [6]: from keras import models
from keras import layers

def build_model():
    model = models.Sequential()
    model.add(layers.Dense(64, activation='relu',
        input_shape=(train_data.shape[1],)))
    model.add(layers.Dense(64, activation='relu'))
    model.add(layers.Dense(1))
    model.compile(optimizer='rmsprop', loss='mse', metrics=['mae'])
    return model
```

```
In [7]: import numpy as np

k=4
num_val_samples = len(train_data) // k
num_epochs = 100
all_scores = []
```

```
In [8]: for i in range(k):
        print('processing fold #', i)
        val_data = train_data[i * num_val_samples: (i + 1) * num_val_samples]
        val_targets = train_targets[i * num_val_samples: (i + 1) * num_val_samples]

        partial_train_data = np.concatenate(
            [train_data[:i * num_val_samples],
             train_data[(i + 1) * num_val_samples:]],
            axis=0)

        partial_train_targets = np.concatenate(
            [train_targets[:i * num_val_samples],
             train_targets[(i + 1) * num_val_samples:]],
            axis=0)

        model = build_model()
        model.fit(partial_train_data, partial_train_targets,
                  epochs=num_epochs, batch_size=1, verbose=0)
        val_mse, val_mae = model.evaluate(val_data, val_targets, verbose=0)
        all_scores.append(val_mae)
```

```
processing fold # 0
processing fold # 1
processing fold # 2
processing fold # 3
```

```
In [9]: all_scores
```

```
Out[9]: [2.0706627368927, 2.364206552505493, 2.573894739151001, 2.4287617206573486]
```

```
In [10]: np.mean(all_scores)
```

```
Out[10]: 2.3593814373016357
```

```
In [11]: num_epochs = 500
```

```

In [12]: all_mae_histories = []
         for i in range(k):
             print('processing fold #', i)
             val_data = train_data[i * num_val_samples: (i + 1) * num_val_samples]
             val_targets = train_targets[i * num_val_samples: (i + 1) * num_val_samples]

             partial_train_data = np.concatenate(
                 [train_data[:i * num_val_samples],
                  train_data[(i + 1) * num_val_samples:]],
                 axis=0)

             partial_train_targets = np.concatenate(
                 [train_targets[:i * num_val_samples],
                  train_targets[(i + 1) * num_val_samples:]],
                 axis=0)
             model = build_model()
             history = model.fit(partial_train_data, partial_train_targets,
                                 validation_data=(val_data, val_targets),
                                 epochs=num_epochs, batch_size=1, verbose=0)
             mae_history = history.history['val_mae']
             all_mae_histories.append(mae_history)

```

```

processing fold # 0
processing fold # 1
processing fold # 2
processing fold # 3

```


```

In [13]: average_mae_history = [
         np.mean([x[i] for x in all_mae_histories]) for i in range(num_epochs)]

```

```
In [14]: import matplotlib.pyplot as plt
```


```
plt.plot(range(1, len(average_mae_history) + 1), average_mae_history)  
plt.xlabel('Epochs')  
plt.ylabel('Validation MAE')  
plt.show()
```



```
In [15]: def smooth_curve(points, factor=0.9):
    smoothed_points = []
    for point in points:
        if smoothed_points:
            previous = smoothed_points[-1]
            smoothed_points.append(previous * factor + point * (1 - factor))
        else:
            smoothed_points.append(point)
    return smoothed_points

smooth_mae_history = smooth_curve(average_mae_history[10:])

plt.plot(range(1, len(smooth_mae_history) + 1), smooth_mae_history)
plt.xlabel('Epochs')
plt.ylabel('Validation MAE')
plt.show()
```



```
In [16]: model = build_model()
model.fit(train_data, train_targets,
          epochs=80, batch_size=16, verbose=0)
test_mse_score, test_mae_score = model.evaluate(test_data, test_targets)
```

4/4 [=====] - 0s 2ms/step - loss: 19.2415 - mae: 2.6032

```
In [17]: test_mae_score
```

Out[17]: 2.603227138519287

```
In [ ]:
```