校园小动物守护者平台 API 文档 (v2.0)

通用响应格式

所有API响应都遵循统一的格式：

```
{
  "code": 200,
  "message": "success",
  "data": {}
}
```

其中：

- code: 状态码，200表示成功，其他值表示失败
- message: 响应消息
- data: 实际数据内容

动物管理 API

获取动物列表

请求方式: GET
请求地址: `/v2/animals`
请求参数:

- species (可选): 物种筛选条件
- area (可选): 区域筛选条件
- healthStatus (可选): 健康状况筛选条件
- isMissing (可选): 是否走失状态筛选

响应示例:

```
{
  "code": 200,
  "message": "success",
  "data": [
    {
      "id": 1,
      "name": "咪咪",
      "species": "猫",
      "gender": "雌性",
      "isNeutered": true,
      "area": "教学楼A区",
      "appearance": "黑白相间的毛发，左耳有缺口",
      "personality": "亲人，喜欢被抚摸",
      "healthStatus": "健康",
      "dietaryNotes": "偏好鱼类食物",
      "importantNotice": "害怕 loud noises",
      "avatarUrl": "http://example.com/avatar.jpg",
      "isMissing": false,
      "createdTime": "2023-01-01T00:00:00.000+00:00",
```

```
      "lastSeenTime": "2023-01-01T09:30:00.000+00:00",
      "lastSeenLocation": "教学楼A区门口",
      "lastFeedingTime": "2023-01-01T09:00:00.000+00:00"
    }
  ]
}
```

获取动物详情

请求方式: GET
请求地址: `/v2/animals/{id}`
路径参数:

- `id` : 动物ID

响应示例:

```
{
  "code": 200,
  "message": "success",
  "data": {
    "id": 1,
    "name": "咪咪",
    "species": "猫",
    "gender": "雌性",
    "isNeutered": true,
    "area": "教学楼A区",
    "appearance": "黑白相间的毛发，左耳有缺口",
    "personality": "亲人，喜欢被抚摸",
    "healthStatus": "健康",
    "dietaryNotes": "偏好鱼类食物",
    "importantNotice": "害怕 loud noises",
    "avatarUrl": "http://example.com/avatar.jpg",
    "isMissing": false,
    "createdTime": "2023-01-01T00:00:00.000+00:00",
    "lastSeenTime": "2023-01-01T09:30:00.000+00:00",
    "lastSeenLocation": "教学楼A区门口",
    "lastFeedingTime": "2023-01-01T09:00:00.000+00:00"
  }
}
```

创建新动物

请求方式: POST
请求地址: `/v2/animals`
请求体:

```
{
  "name": "咪咪",
  "species": "猫",
  "gender": "雌性",
  "isNeutered": true,
  "area": "教学楼A区",
  "appearance": "黑白相间的毛发，左耳有缺口",
  "personality": "亲人，喜欢被抚摸",
```

```
  "healthStatus": "健康",
  "dietaryNotes": "偏好鱼类食物",
  "importantNotice": "害怕 loud noises",
  "avatarUrl": "http://example.com/avatar.jpg",
  "isMissing": false
}
```

响应示例:

```
{
  "code": 200,
  "message": "Animal created successfully",
  "data": {
    "id": 1,
    "name": "咪咪",
    "species": "猫",
    "gender": "雌性",
    "isNeutered": true,
    "area": "教学楼A区",
    "appearance": "黑白相间的毛发，左耳有缺口",
    "personality": "亲人，喜欢被抚摸",
    "healthStatus": "健康",
    "dietaryNotes": "偏好鱼类食物",
    "importantNotice": "害怕 loud noises",
    "avatarUrl": "http://example.com/avatar.jpg",
    "isMissing": false,
    "createdTime": "2023-01-01T00:00:00.000+00:00",
    "lastSeenTime": null,
    "lastSeenLocation": null,
    "lastFeedingTime": null
  }
}
```

更新动物信息

请求方式: PUT
请求地址: `/v2/animals/{id}`
路径参数:

- id: 动物ID

请求体:

```
{
  "name": "咪咪",
  "species": "猫",
  "gender": "雌性",
  "isNeutered": true,
  "area": "教学楼B区",
  "appearance": "黑白相间的毛发，左耳有缺口",
  "personality": "亲人，喜欢被抚摸",
  "healthStatus": "健康",
  "dietaryNotes": "偏好鱼类食物",
  "importantNotice": "害怕 loud noises",
  "avatarUrl": "http://example.com/avatar.jpg",
```

```
  "isMissing": false
}
```

响应示例:

```
{
  "code": 200,
  "message": "Animal updated successfully",
  "data": {
    "id": 1,
    "name": "咪咪",
    "species": "猫",
    "gender": "雌性",
    "isNeutered": true,
    "area": "教学楼B区",
    "appearance": "黑白相间的毛发，左耳有缺口",
    "personality": "亲人，喜欢被抚摸",
    "healthStatus": "健康",
    "dietaryNotes": "偏好鱼类食物",
    "importantNotice": "害怕 loud noises",
    "avatarUrl": "http://example.com/avatar.jpg",
    "isMissing": false,
    "createdTime": "2023-01-01T00:00:00.000+00:00",
    "lastSeenTime": null,
    "lastSeenLocation": null,
    "lastFeedingTime": null
  }
}
```

喂养记录 API

获取喂养记录列表

请求方式: GET
请求地址: `/v2/feedings`
请求参数:

- location (可选): 地点筛选
- foodType (可选): 食物类型筛选
- `dateFrom` (可选): 起始日期 (格式: YYYY-MM-DD)
- `dateTo` (可选): 结束日期 (格式: YYYY-MM-DD)
- `animalId` (可选): 动物ID筛选

响应示例:

```
{
  "code": 200,
  "message": "success",
  "data": [
    {
      "id": 1,
      "animal": {
        "id": 1,
        "name": "咪咪",
```

```
        "species": "猫",
        "gender": "雌性",
        "isNeutered": true,
        "area": "教学楼A区",
        "appearance": "黑白相间的毛发，左耳有缺口",
        "personality": "亲人，喜欢被抚摸",
        "healthStatus": "健康",
        "dietaryNotes": "偏好鱼类食物",
        "importantNotice": "害怕 loud noises",
        "avatarUrl": "http://example.com/avatar.jpg",
        "isMissing": false,
        "createdTime": "2023-01-01T00:00:00.000+00:00",
        "lastSeenTime": "2023-01-01T09:30:00.000+00:00",
        "lastSeenLocation": "教学楼A区门口",
        "lastFeedingTime": "2023-01-01T09:00:00.000+00:00"
      },
      "animalName": "咪咪",
      "time": "2023-01-01T09:00:00.000+00:00",
      "location": "教学楼A区门口",
      "foodType": "猫粮",
      "brand": "皇家",
      "portion": "适量",
      "providedWater": true,
      "description": "正常进食",
      "imageUrls": "http://example.com/image.jpg",
      "submitter": "张三"
    }
  ]
}
```

创建喂养记录

请求方式: POST
请求地址: `/v2/feedings`
请求体:

```
{
  "animal": {
    "id": 1
  },
  "animalName": "咪咪",
  "time": "2023-01-01T09:00:00.000+00:00",
  "location": "教学楼A区门口",
  "foodType": "猫粮",
  "brand": "皇家",
  "portion": "适量",
  "providedWater": true,
  "description": "正常进食",
  "imageUrls": "http://example.com/image.jpg",
  "submitter": "张三"
}
```

响应示例:

```
{
```

```
  "code": 200,
  "message": "Feeding record created successfully",
  "data": {
    "id": 1,
    "animal": {
      "id": 1,
      "name": "咪咪",
      "species": "猫",
      "gender": "雌性",
      "isNeutered": true,
      "area": "教学楼A区",
      "appearance": "黑白相间的毛发，左耳有缺口",
      "personality": "亲人，喜欢被抚摸",
      "healthStatus": "健康",
      "dietaryNotes": "偏好鱼类食物",
      "importantNotice": "害怕 loud noises",
      "avatarUrl": "http://example.com/avatar.jpg",
      "isMissing": false,
      "createdTime": "2023-01-01T00:00:00.000+00:00",
      "lastSeenTime": "2023-01-01T09:30:00.000+00:00",
      "lastSeenLocation": "教学楼A区门口",
      "lastFeedingTime": "2023-01-01T09:00:00.000+00:00"
    },
    "animalName": "咪咪",
    "time": "2023-01-01T09:00:00.000+00:00",
    "location": "教学楼A区门口",
    "foodType": "猫粮",
    "brand": "皇家",
    "portion": "适量",
    "providedWater": true,
    "description": "正常进食",
    "imageUrls": "http://example.com/image.jpg",
    "submitter": "张三"
  }
}
```

获取喂养统计信息

请求方式: GET
请求地址: `/v2/feedings/statistics`

响应示例:

```
{
  "code": 200,
  "message": "success",
  "data": {
    "totalFeedings": 100,
    "feedingsByLocation": {
      "教学楼A区": 40,
      "图书馆": 30,
      "食堂": 20,
      "宿舍区": 10
    },
    "feedingsByFoodType": {
```

```
      "猫粮": 60,
      "狗粮": 30,
      "鱼肉": 10
    },
    "waterProvidedCount": 80
  }
}
```

目击记录 API

获取目击记录列表

请求方式: GET
请求地址: `/v2/sightings`
请求参数:

- location (可选): 地点筛选
- `dateFrom` (可选): 起始日期 (格式: YYYY-MM-DD)
- `dateTo` (可选): 结束日期 (格式: YYYY-MM-DD)
- species (可选): 物种筛选
- `animalId` (可选): 动物ID筛选

响应示例:

```
{
  "code": 200,
  "message": "success",
  "data": [
    {
      "id": 1,
      "animal": {
        "id": 1,
      },
      "animalName": "咪咪",
      "time": "2023-01-01T09:30:00.000+00:00",
      "location": "教学楼A区门口",
      "description": "正在觅食",
      "imageUrls": "http://example.com/image.jpg",
      "submitter": "李四"
    }
  ]
}
```

获取目击记录详情

请求方式: GET
请求地址: `/v2/sightings/{id}`
路径参数:

- `id` : 目击记录ID

响应示例:

```
{
```

```
  "code": 200,
  "message": "success",
  "data": {
    "id": 1,
    "animal": {
      "id": 1,
    },
    "animalName": "咪咪",
    "time": "2023-01-01T09:30:00.000+00:00",
    "location": "教学楼A区门口",
    "description": "正在觅食",
    "imageUrls": "http://example.com/image.jpg",
    "submitter": "李四"
  }
}
```

创建目击记录

请求方式: POST
请求地址: `/v2/sightings`
请求体:

```
{
  "animal": {
    "id": 1
  },
  "animalName": "咪咪",
  "time": "2023-01-01T09:30:00.000+00:00",
  "location": "教学楼A区门口",
  "description": "正在觅食",
  "imageUrls": "http://example.com/image.jpg",
  "submitter": "李四"
}
```

响应示例:

```
{
  "code": 200,
  "message": "Sighting created successfully",
  "data": {
    "id": 1,
    "animal": {
      "id": 1,
    },
    "animalName": "咪咪",
    "time": "2023-01-01T09:30:00.000+00:00",
    "location": "教学楼A区门口",
    "description": "正在觅食",
    "imageUrls": "http://example.com/image.jpg",
    "submitter": "李四"
  }
}
```

健康记录 API

获取动物的健康记录列表

请求方式: GET
请求地址: `/v2/animals/{animalId}/health-records`
路径参数:

- `animalId` : 动物ID

响应示例:

```
{
  "code": 200,
  "message": "success",
  "data": [
    {
      "id": 1,
      "animal": {
        "id": 1,
      },
      "recordDate": "2023-01-01",
      "status": "健康",
      "description": "体检结果良好",
      "treatment": "无",
      "veterinarian": "王医生",
      "nextCheckup": "2024-01-01",
      "createdAt": "2023-01-01T00:00:00.000+00:00",
      "updatedAt": "2023-01-01T00:00:00.000+00:00"
    }
  ]
}
```

创建动物健康记录

请求方式: POST
请求地址: `/v2/animals/{animalId}/health-records`
路径参数:

- `animalId` : 动物ID

请求体:

```
{
  "recordDate": "2023-01-01",
  "status": "健康",
  "description": "体检结果良好",
  "treatment": "无",
  "veterinarian": "王医生",
  "nextCheckup": "2024-01-01"
}
```

响应示例:

```
{
```

```
  "code": 200,
  "message": "Health record created successfully",
  "data": {
    "id": 1,
    "animal": {
      "id": 1,
    },
    "recordDate": "2023-01-01",
    "status": "健康",
    "description": "体检结果良好",
    "treatment": "无",
    "veterinarian": "王医生",
    "nextCheckup": "2024-01-01",
    "createdAt": "2023-01-01T00:00:00.000+00:00",
    "updatedAt": "2023-01-01T00:00:00.000+00:00"
  }
}
```


数据库表结构

系统包含四个主要数据表：

1. **animals**(动物表)：存储校园内动物的基本信息
2. **sightings**(目击记录表)：记录用户发现动物的时间、地点等信息
3. **feedings**(喂养记录表)：记录动物的喂养情况
4. **health_records**(健康记录表)：记录动物的健康检查和治疗信息

各表之间通过外键建立关联关系，确保数据的一致性和完整性。