The risk maps submitted together with the report provide visual combinations of landslide process scenarios and land use categories. They allow to highlight the places where the risk could be more problematic. Depending on the slope instability processes and the land use, the risk is different. For example, places where deep-seated landslides are located are areas where ground deformations are expected to be the larger (independently from soil creep, which is not discussed here, although highlighted in step 1). Such deformations can be very slow (a few centimetres per year or even less; e.g. Nobile et al., 2019; Dille et al., 2021) and therefore be not at all a problem for agricultural land. On the contrary, building a new road or heavy infrastructures on such areas could create problems (fractures, etc.) as most foundations cannot be deep enough to reach a stable bedrock below the surface of rupture of the landslides. While slow-moving deformations can have pervasive impacts difficult to mitigate, people are not in immediate dangers.

When looking at such documents, we must be aware that further investigations are needed to really assess the problem, not only in terms of landslide process understanding (location, mechanism, deformation rate), but also in terms of vulnerability as well as direct and indirect impacts.

1.2 Proposal of landslide mitigation measures

The goal of the study was to provide a general overview of the potential mitigation measures that could be tested for the areas of the watersheds that have been identified at risk and vulnerable to landslides.
The structure of the study is as follows:

- First, the mitigation measures are detailed;
- Along with criteria for the selection of the mitigation measures, details are provided on measures at the level of the hazard, the vulnerability, and the elements at risk;
- The measures are then discussed in the context of the Catchment Restoration Opportunity Mapping upport System (CROM DSS);
- A high-level Bill of Quantities for specific landslide mitigation measures in the study areas has been provided. The specific measures were developed with the assumption that, should landslides occur in the highest susceptibility zones, they would be shallow landslides that are likely to cause to soil erosion.

Together with the presentation of the mitigation measures, additional figures and appendixes explaining and illustrating key concepts are proposed to ease the understanding of the study. As a last note, a brief focus is provided on gully erosion.

One have to keep in mind that the purpose of this section is not to go beyond the sole role of the literature review. Further research and expertise actions are needed if one want to move towards the implementation of concrete mitigation measures. The measures presented here are therefore not catchment-specific, and to some extent not specific to a type of landslide in particular.