

Chapter 5: Other Relational Languages

- Query-by-Example (QBE)
- Quel
- Datalog

Query-by-Example (QBE)

- Basic Structure
- Queries on One Relation
- Queries on Several Relations
- The Condition Box
- The Result Relation
- Ordering the Display of Tuples
- Aggregate Operations
- Modification of the Database

QBE — Basic Structure

- A graphical query language which is based (roughly) on the domain relational calculus
- Two dimensional syntax – system creates templates of relations that are requested by users
- Queries are expressed “by example”

Skeleton Tables

| <i>branch</i> | <i>branch-name</i> | <i>branch-city</i> | <i>assets</i> |
|---------------|--------------------|--------------------|---------------|
| | | | |

| <i>customer</i> | <i>customer-name</i> | <i>customer-street</i> | <i>customer-city</i> |
|-----------------|----------------------|------------------------|----------------------|
| | | | |

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| | | | |

Skeleton Tables (Cont.)

| <i>borrower</i> | <i>customer-name</i> | <i>loan-number</i> |
|-----------------|----------------------|--------------------|
| | | |

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| | | | |

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| | | |

Queries on One Relation

- Find all loan numbers at the Perryridge branch.

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| | Perryridge | P. _x | |

- _x is a variable (optional)
- P. means print (display)
- duplicates are removed

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| | Perryridge | P.ALL. | |

- duplicates are not removed

Queries on One Relation (Cont.)

- Display full details of all loans

– Method 1:

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|-----------------|
| | P. _x | P. _y | P. _z |

– Method 2: shorthand notation

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| P. | | | |

- Find the loan number of all loans with a loan amount of more than \$700.

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| | | P. | >700 |

Queries on One Relation (Cont.)

- Find the loan numbers of all loans made jointly to Smith and Jones.

| <i>borrower</i> | <i>customer-name</i> | <i>loan-number</i> |
|-----------------|----------------------|--------------------|
| | "Smith" | P. _x |
| | "Jones" | _x |

- Find the loan numbers of all loans made to Smith, Jones or both.

| <i>borrower</i> | <i>customer-name</i> | <i>loan-number</i> |
|-----------------|----------------------|--------------------|
| | "Smith" | P. _x |
| | "Jones" | P. _y |

Queries on Several Relations

- Find the names of all customers who have a loan from the Perryridge branch.

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| | Perryridge | _x | |

| <i>borrower</i> | <i>customer-name</i> | <i>loan-number</i> |
|-----------------|----------------------|--------------------|
| | P._y | _x |

Queries on Several Relations (Cont.)

- Find the names of all customers who have both an account and a loan at the bank.

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| | P._x | |

| <i>borrower</i> | <i>customer-name</i> | <i>loan-number</i> |
|-----------------|----------------------|--------------------|
| | _x | |

Queries on Several Relations (Cont.)

- Find the names of all customers who have an account at the bank, but do not have a loan from the bank.

| <i> depositor </i> | <i> customer-name </i> | <i> account-number </i> |
|--------------------|------------------------|-------------------------|
| | P..x | |

| <i> borrower </i> | <i> customer-name </i> | <i> loan-number </i> |
|-------------------|------------------------|----------------------|
| ¬ | ..x | |

¬ means “there does not exist”

Queries on Several Relations

- Find all customers who have at least two accounts.

| <i> depositor </i> | <i> customer-name </i> | <i> account-number </i> |
|--------------------|------------------------|-------------------------|
| | P..x | ..y |
| | ..x | ¬ ..y |

¬ means “not equal to”

The Condition Box

- Allows the expression of constraints on domain variables that are either inconvenient or impossible to express within the skeleton tables.
- Find all account numbers with a balance between \$1,300 and \$2,000 but not exactly \$1,500.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| | | P. | $_x$ |

| <i>conditions</i> |
|---|
| $_x = (\geq 1300 \text{ and } \leq 2000 \text{ and } \neg 1500)$ |

The Result Relation

- Find the *customer-name*, *account-number*, and *balance* for all customers who have an account at the Perryridge branch.
 - We need to:
 - * Join *depositor* and *account*.
 - * Project *customer-name*, *account-number*, and *balance*.
 - To accomplish this we:
 - * Create a skeleton table, called *result*, with attributes *customer-name*, *account-number*, and *balance*.
 - * Write the query.

The Result Relation (Cont.)

- The resulting query is:

| <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|--------------------|-----------------------|----------------|
| Perryridge | $_y$ | $_z$ |

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| | $_x$ | $_y$ |

| <i>result</i> | <i>customer-name</i> | <i>account-number</i> | <i>balance</i> |
|---------------|----------------------|-----------------------|----------------|
| P. | $_x$ | $_y$ | $_z$ |

Ordering the Display of Tuples

- AO = ascending order; DO = descending order.
When sorting on multiple attributes, the sorting order is specified by including with each sort operator (AO or DO) an integer surrounded by parentheses.
- List all account numbers at the Perryridge branch in ascending alphabetic order with their respective account balances in descending order.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| | Perryridge | P.AO(1). | P.DO(2). |

Aggregate Operations

- The aggregate operators are AVG, MAX, MIN, SUM, and CNT
- The above operators must always be postfixed with "ALL."
(e.g., SUM.ALL. or AVG.ALL..x).
- Find the total balance of all the accounts maintained at the Perryridge branch.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| | Perryridge | | P.SUM.ALL. |

Aggregate Operations (Cont.)

- Find the total number of customers having an account at the bank.

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| | P.CNT.UNQ.ALL. | |

Note: UNQ is used to specify that we want to eliminate duplicates.

Query Examples

- Find the average balance at each branch.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| | P.G. | | P.AVG.ALL._x |

Note:

- The “G” in “P.G” is analogous to SQL’s **group by** construct
- The “ALL” in the “P.AVG.ALL” entry in the *balance* column ensures that all balances are considered
- Find the average account balance at only those branches where the average account balance is more than \$1,200. Add the condition box:

| <i>conditions</i> |
|-------------------|
| AVG.ALL._x > 1200 |

Query Example

- Find all customers who have an account at all branches located in Brooklyn:

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| | P.G._x | -y |

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| | CNT.UNQ.ALL._z | -y | |

| <i>branch</i> | <i>branch-name</i> | <i>branch-city</i> | <i>assets</i> |
|---------------|--------------------|--------------------|---------------|
| | _z | Brooklyn | |
| | _w | Brooklyn | |

Query Example (Cont.)

conditions

CNT.UNQ.ALL._z = CNT.UNQ.ALL._w

- CNT.UNQ.ALL._w specifies the number of distinct branches in Brooklyn.
- CNT.UNQ.ALL._z specifies the number of distinct branches in Brooklyn at which customer x has an account.

Modification of the Database – Deletion

- Deletion of tuples from a relation is expressed by use of a D. command. In the case where we delete information in only some of the columns, null values, specified by –, are inserted.
- Delete customer Smith

| <i>customer</i> | <i>customer-name</i> | <i>customer-street</i> | <i>customer-city</i> |
|-----------------|----------------------|------------------------|----------------------|
| D. | Smith | | |

- Delete the *branch-city* value of the branch whose name is “Perryridge”.

| <i>branch</i> | <i>branch-name</i> | <i>branch-city</i> | <i>assets</i> |
|---------------|--------------------|--------------------|---------------|
| | Perryridge | D. | |

Deletion Query Examples

- Delete all loans with a loan amount between \$1300 and \$1500.

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| D. | | <i>-y</i> | <i>-x</i> |

| <i>borrower</i> | <i>customer-name</i> | <i>loan-number</i> |
|-----------------|----------------------|--------------------|
| D. | | <i>-y</i> |

| <i>conditions</i> |
|----------------------------------|
| <i>-x = (≥ 1300 and ≤ 1500)</i> |

Deletion Query Examples (Cont.)

- Delete all accounts at branches located in Brooklyn.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| D. | <i>-x</i> | <i>-y</i> | |

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| D. | | <i>-y</i> |

| <i>branch</i> | <i>branch-name</i> | <i>branch-city</i> | <i>assets</i> |
|---------------|--------------------|--------------------|---------------|
| | <i>-x</i> | Brooklyn | |

Modification of the Database – Insertion

- Insertion is done by placing the I. operator in the query expression.
- Insert the fact that account A-9732 at the Perryridge branch has a balance of \$700.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| I. | Perryridge | A-9732 | 700 |

- Provide as a gift for all loan customers of the Perryridge branch, a new \$200 savings account for every loan account they have, with the loan number serving as the account number for the new savings account.

(next slide)

Modification of the Database – Insertion (Cont.)

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|----------------|
| I. | Perryridge | _x | 200 |

| <i>depositor</i> | <i>customer-name</i> | <i>account-number</i> |
|------------------|----------------------|-----------------------|
| I. | _y | _x |

| <i>loan</i> | <i>branch-name</i> | <i>loan-number</i> | <i>amount</i> |
|-------------|--------------------|--------------------|---------------|
| | Perryridge | _x | |

| <i>borrower</i> | <i>customer-name</i> | <i>account-number</i> |
|-----------------|----------------------|-----------------------|
| | _y | _x |

Modification of the Database – Updates

- Use the U. operator to change a value in a tuple without changing *all* values in the tuple. QBE does not allow users to update the primary key fields.
- Update the asset value of the of the Perryridge branch to \$10,000,000.

| <i>branch</i> | <i>branch-name</i> | <i>branch-city</i> | <i>assets</i> |
|---------------|--------------------|--------------------|---------------|
| | Perryridge | | U.10000000 |

- Increase all balances by 5 percent.

| <i>account</i> | <i>branch-name</i> | <i>account-number</i> | <i>balance</i> |
|----------------|--------------------|-----------------------|-----------------------|
| U. | | | $_x * 1.05$ $_x$ |

Quel

- Basic Structure
- Simple Queries
- Tuple Variables
- Aggregate Functions
- Modification of the Database
- Set Operations
- Quel and the Tuple Relational Calculus

Quel — Basic Structure

- Introduced as the query language for the Ingres database system, developed at the University of California, Berkeley.
- Basic structure parallels that of the tuple relational calculus.
- Most Quel queries are expressed using three types of clauses: **range of**, **retrieve**, and **where**.
 - Each tuple variable is declared in a **range of** clause.

range of t is r

declares t to be a tuple variable restricted to take on values of tuples in relation r .

- The **retrieve** clause is similar in function to the **select** clause of SQL.
- The **where** clause contains the selection predicate.

Quel Query Structure

- A typical Quel query is of the form:

range of t_1 is r_1

range of t_2 is r_2

\vdots

range of t_m is r_m

retrieve ($t_{i_1}.A_{j_1}, t_{i_2}.A_{j_2}, \dots, t_{i_n}.A_{j_n}$)

where P

- Each t_i is a tuple variable.
- Each r_i is a relation.
- Each A_{j_k} is an attribute.
- The notation $t.A$ denotes the value of tuple variable t on attribute A .

Quel Query Structure (Cont.)

- Quel does not include relational algebra operations like **intersect**, **union**, and **minus**.
- Quel does not allow nested subqueries (unlike SQL).
 - Cannot have a nested **retrieve-where** clause inside a **where** clause.
- These limitations do not reduce the expressive power of Quel, but the user has fewer alternatives for expressing a query.

Simple Queries

- Find the names of all customers having a loan at the bank.

range of t is *borrower*
retrieve (*t.customer-name*)

- To remove duplicates, we must add the keyword **unique** to the **retrieve** clause:

range of t is *borrower*
retrieve unique (*t.customer-name*)

Query Over Several Relations

- Find the names of all customers who have both a loan and an account at the bank.

range of s is *borrower*

range of t is *depositor*

retrieve unique ($s.customer-name$)

where $t.customer-name = s.customer-name$

Tuple Variables

- Certain queries need to have two distinct tuple variables ranging over the same relation.
- Find the name of all customers who live in the same city as Jones does.

range of s is *customer*

range of t is *customer*

retrieve unique ($s.customer-name$)

where $t.customer-name = \text{"Jones"}$ **and**

$s.customer-city = t.customer-city$

Tuple Variables (Cont.)

- When a query requires only one tuple variable ranging over a relation, we can omit the **range of** statement and use the relation name itself as an implicitly declared tuple variable.
- Find the names of all customers who have both a loan and an account at the bank.

retrieve unique (*borrower.customer-name*)
where *depositor.customer-name* = *borrower.customer-name*

Aggregate Functions

- Aggregate functions in Quel compute functions on groups of tuples.
- Grouping is specified as part of each aggregate expression.
- Quel aggregate expressions may take the following forms:

aggregate function (*t.A*)

aggregate function (*t.A where P*)

aggregate function (*t.A by s.B₁, s.B₂, ..., s.B_n where P*)

- *aggregate function* is one of **count**, **sum**, **avg**, **max**, **min**, **countu**, **sumu**, **avgu**, or **any**
- *t* and *s* are tuple variables
- *A*, *B₁*, *B₂*, ..., *B_n* are attributes
- *P* is a predicate similar to the **where** clause in a **retrieve**

Aggregate Functions (Cont.)

- The functions **countu**, **sumu**, and **avgu** are identical to **count**, **sum**, and **avg**, respectively, except that they remove duplicates from their operands.
- An aggregate expression may appear anywhere a constant may appear; for example, in a **where** clause.

Example Queries

- Find the average account balance for all accounts at the Perryridge branch.

range of t is *account*
retrieve avg (*t.balance* **where**
t.branch-name = "Perryridge")

- Find all accounts whose balance is higher than the average balance of Perryridge-branch accounts.

range of u is *account*
range of t is *account*
retrieve (*t.account-number*)
where *t.balance* > **avg** (*u.balance* **where**
u.branch-name = "Perryridge")

Example Queries

- Find all accounts whose balance is higher than the average balance at the branch where the account is held.
 - Compute for each tuple t in *account* the average balance at branch $t.branch\text{-}name$.
 - In order to form these groups of tuples, use the **by** construct in the aggregate expression.

The query is:

```
range of  $u$  is account
range of  $t$  is account
retrieve ( $t.account\text{-}number$ )
where  $t.balance > avg(u.balance \text{ by } t.branch\text{-}name$ 
      where  $u.branch\text{-}name = t.branch\text{-}name$ )
```

Example Query

- Find the names of all customers who have an account at the bank, but do not have a loan from the bank.

```
range of  $t$  is depositor
range of  $u$  is borrower
retrieve unique ( $t.customer\text{-}name$ )
where any ( $u.loan\text{-}number \text{ by } t.customer\text{-}name$ 
          where  $u.customer\text{-}name = t.customer\text{-}name$ ) = 0
```

- The use of a comparison with **any** is analogous to the “there exists” quantifier of the relational calculus.

Example Query

- Find the names of all customers who have an account at all branches located in Brooklyn.
 - First determine the number of branches in Brooklyn.
 - Compare this number with the number of distinct branches in Brooklyn at which each customer has an account.

range of t is *depositor*

range of u is *account*

range of s is *branch*

range of w is *branch*

retrieve unique (*t.customer-name*)

where countu (*s.branch-name by t.customer-name*

where *u.account-number = t.account-number*

and *u.branch-name = s.branch-name*

and *s.branch-city = "Brooklyn") =*

countu (*u.branch-name where u.branch-city = "Brooklyn"*)

Modification of the Database – Deletion

- The form of a Quel deletion is

range of t is r

delete t

where P

- The tuple variable t can be implicitly defined.
- The predicate P can be any valid Quel predicate.
- If the **where** clause is omitted, all tuples in the relation are deleted.

Deletion Query Examples

- Delete all tuples in the *loan* relation.

range of *t* is *loan*
delete *t*

- Delete all Smith's account records.

range of *t* is *depositor*
delete *t*
where *t.customer-name* = "Smith"

- Delete all account records for branches located in Needham.

range of *t* is *account*
range of *u* is *branch*
delete *t*
where *t.branch-name* = *u.branch-name* and
***u.branch-city* = "Needham"**

Modification of the Database – Insertion

- Insertions are expressed in Quel using the **append** command.
- Insert the fact that account A-9732 at the Perryridge branch has a balance of \$700.

append to *account* (*branch-name* = "Perryridge",
***account-number* = A-9732,**
***balance* = 700)**

Insertion Query Example

- Provide as a gift for all loan customers of the Perryridge branch, a new \$200 savings account for every loan account that they have. Let the loan number serve as the account number for the new savings account.

range of t is *loan*

range of s is *borrower*

append to *account* (*branch-name* = *t.branch-name*,
account-number = *t.loan-number*,
balance = 200)

where *t.branch-name* = "Perryridge"

append to *depositor* (*customer-name* = *s.customer-name*,
account-number = *s.loan-number*)

where *t.branch-name* = "Perryridge" **and** *t.loan-number* =
s.loan-number

Modification of the Database – Updates

- Updates are expressed in Quel using the **replace** command.
- Increase all account balances by 5 percent.

range of t is *account*

replace *t* (*balance* = $1.05 * t.balance$)

- Pay 6 percent interest on accounts with balances over \$10,000, and 5 percent on all other accounts.

range of t is *account*

replace *t* (*balance* = $1.06 * balance$)

where *t.balance* > 10000

replace *t* (*balance* = $1.05 * balance$)

where *t.balance* ≤ 10000

Set Operations

- Quel does not include relational algebra operations like **intersect**, **union**, and **minus**.
- To construct queries that require the use of set operations, we must create temporary relations (via the use of regular Quel statements).
- Example: To create a temporary relation *temp* that holds the names of all depositors of the bank, we write

range of *u* is depositor
retrieve into *temp* unique (*u.customer-name*)

- The **into *temp*** clause causes a new relation, *temp*, to be created to hold the result of this query.

Example Queries

- Find the names of all customers who have an account, a loan, or both at the bank.
- Since Quel has no **union** operation, a new relation (called *temp*) must be created that holds the names of all borrowers of the bank.
- We find all borrowers of the bank and insert them in the newly created relation *temp* by using the **append** command.

range of *s* is borrower
append to *temp* unique (*s.customer-name*)

- Complete the query with:

range of *t* is *temp*
retrieve unique (*t.customer-name*)

Example Queries

- Find the names of all customers who have an account at the bank but do not have a loan from the bank.
- Create a temporary relation by writing:
range of u is depositor
retrieve into $temp$ ($u.customer-name$)
- Delete from $temp$ those customers who have a loan.
range of s is borrower
range of t is $temp$
delete t
where $t.customer-name = s.customer-name$
- $temp$ now contains the desired list of customers. We write the following to complete our query.
range of t is $temp$
retrieve unique ($t.customer-name$)

Quel and the Tuple Relational Calculus

The following Quel query

range of t_1 is r_1
range of t_2 is r_2
 .
 .
 .
range of t_m is r_m
retrieve unique ($t_1.A_{j_1}, t_2.A_{j_2}, \dots, t_m.A_{j_m}$)
where P

would be expressed in the tuple relational calculus as:

$$\{t \mid \exists t_1 \in r_1, t_2 \in r_2, \dots, t_m \in r_m ($$

$$t[r_{j_1}.A_{j_1}] = t_1[A_{j_1}] \wedge t[r_{j_2}.A_{j_2}] = t_2[A_{j_2}] \wedge \dots \wedge$$

$$t[r_{j_m}.A_{j_m}] = t_m[A_{j_m}] \wedge P(t_1, t_2, \dots, t_m))\}$$

Quel and TRC (Cont.)

- $t_1 \in r_1 \wedge t_2 \in r_2 \wedge \dots \wedge t_m \in r_m$
Constrains each tuple in t_1, t_2, \dots, t_m to take on values of tuples in the relation over which it ranges.
- $t[r_{i_1}.A_{j_1}] = t_{i_1}[A_{j_1}] \wedge t[r_{i_2}.A_{j_2}] = t_{i_2}[A_{j_2}] \wedge \dots \wedge t[r_{i_n}.A_{j_n}] = t_{i_n}[A_{j_n}]$
Corresponds to the **retrieve** clause of the Quel query.
- $P(t_1, t_2, \dots, t_m)$
The constraint on acceptable values for t_1, t_2, \dots, t_m imposed by the **where** clause in the Quel query.
- Quel achieves the power of the relational algebra by means of the **any** aggregate function and the use of insertion and deletion on temporary relations.

Datalog

- Basic Structure
- Syntax of Datalog Rules
- Semantics of Nonrecursive Datalog
- Safety
- Relational Operations in Datalog
- Recursion in Datalog
- The Power of Recursion

Basic Structure

- Prolog-like logic-based language that allows recursive queries; based on first-order logic.
- A Datalog program consists of a set of *rules* that define views.
- Example: define a view relation *v1* containing account numbers and balances for accounts at the Perryridge branch with a balance of over \$700.

$v1(A, B) :- account(\text{"Perryridge"}, A, B), B > 700.$

- Retrieve the balance of account number "A-217" in the view relation *v1*.

$? v1(\text{"A-217"}, B).$

Example Queries

- Each rule defines a set of tuples that a view relation must contain.
- The set of tuples in a view relation is then defined as the union of all the sets of tuples defined by the rules for the view relation.
- Example:

$interest-rate(A, 0) :- account(N, A, B), B < 2000$

$interest-rate(A, 5) :- account(N, A, B), B \geq 2000$

- Define a view relation *c* that contains the names of all customers who have a deposit but no loan at the bank:

$c(N) :- depositor(N, A), \text{not } is-borrower(N).$

$is-borrower(N) :- borrower(N, L).$

Syntax of Datalog Rules

- A *positive literal* has the form

$$p(t_1, t_2, \dots, t_n)$$

- p is the name of a relation with n attributes
- each t_i is either a constant or variable

- A *negative literal* has the form

$$\text{not } p(t_1, t_2, \dots, t_n)$$

Syntax of Datalog Rules (Cont.)

- *Rules* are built out of literals and have the form:

$$p(t_1, t_2, \dots, t_n) \text{ :- } L_1, L_2, \dots, L_n.$$

- each of the L_i 's is a literal
- head – the literal $p(t_1, t_2, \dots, t_n)$
- body – the rest of the literals

- A *fact* is a rule with an empty body, written in the form:

$$p(v_1, v_2, \dots, v_n).$$

- indicates tuple (v_1, v_2, \dots, v_n) is in relation p

Semantics of a Rule

- A *ground instantiation* of a rule (or simply *instantiation*) is the result of replacing each variable in the rule by some constant.

- Rule defining $v1$

$$v1(A, B) :- \text{account}(\text{"Perryridge"}, A, B), B > 700.$$

- An instantiation of above rule:

$$v1(\text{"A-217"}, 750) :- \text{account}(\text{"Perryridge"}, \text{"A-217"}, 750), \\ 750 > 700.$$

- The body of rule instantiation R' is *satisfied* in a set of facts (database instance) I if

1. For each positive literal $q_i(v_{i,1}, \dots, v_{i,n_i})$ in the body of R' , I contains the fact $q(v_{i,1}, \dots, v_{i,n_i})$.
2. For each negative literal **not** $q_j(v_{j,1}, \dots, v_{j,n_j})$ in the body of R' , I does not contain the fact $q_j(v_{j,1}, \dots, v_{j,n_j})$.

Semantics of a Rule (Cont.)

- We define the set of facts that can be **inferred** from a given set of facts I using rule R as:

$$\text{infer}(R, I) = \{p(t_1, \dots, t_{n_i}) \mid \text{there is an instantiation } R' \text{ of } R \\ \text{where } p(t_1, \dots, t_{n_i}) \text{ is the head of } R', \text{ and} \\ \text{the body of } R' \text{ is satisfied in } I \}$$

- Given a set of rules $\mathcal{R} = \{R_1, R_2, \dots, R_n\}$, we define


$$\text{infer}(\mathcal{R}, I) = \text{infer}(R_1, I) \cup \text{infer}(R_2, I) \cup \dots \cup \text{infer}(R_n, I)$$

Layering of Rules

- Define the interest on each account in Perryridge.

$interest(A, I) :- perryridge-account(A, B),$
 $interest-rate(A, R), I = B * R/100.$
 $perryridge-account(A, B) :- account("Perryridge", A, B).$
 $interest-rate(A, 0) :- account(N, A, B), B < 2000.$
 $interest-rate(A, 5) :- account(N, A, B), B \geq 2000.$

- Layering of the view relations



Layering of Rules (Cont.)

Formally:

- A relation is in layer 1 if all relations used in the bodies of rules defining it are stored in the database.
- A relation is in layer 2 if all relations used in the bodies of rules defining it are either stored in the database, or are in layer 1.
- A relation p is in layer $i + 1$ if
 - it is not in layers $1, 2, \dots, i$
 - all relations used in the bodies of rules defining p are either stored in the database, or are in layers $1, 2, \dots, i$

Semantics of a Program

Let the layers in a given program be $1, 2, \dots, n$. Let \mathcal{R}_i denote the set of all rules defining view relations in layer i .

- Define I_0 = set of facts stored in the database.
- Define $I_{i+1} = I_i \cup \text{infer}(\mathcal{R}_{i+1}, I_i)$
- The set of facts in the view relations defined by the program (also called the *semantics of the program*) is given by the set of facts I_n corresponding to the highest layer n .

Note: Can instead define semantics using view expansion like in relational algebra, but above definition is better for handling extensions such as recursion.

Safety

- It is possible to write rules that generate an infinite number of answers.

$gt(X, Y) :- X > Y$
 $not-in-loan(B, L) :- \text{not } loan(B, L)$

To avoid this possibility Datalog rules must satisfy the following safety conditions.

- Every variable that appears in the head of the rule also appears in a non-arithmetic positive literal in the body of the rule.
- Every variable appearing in a negative literal in the body of the rule also appears in some positive literal in the body of the rule.

Relational Operations in Datalog

- Project out attribute *account-name* from *account*.

$$query(A) :- account(N, A, B).$$

- Cartesian product of relations r_1 and r_2 .

$$query(X_1, X_2, \dots, X_n, Y_1, Y_2, \dots, Y_m) :- \\ r_1(X_1, X_2, \dots, X_n), r_2(Y_1, Y_2, \dots, Y_m).$$

- Union of relations r_1 and r_2 .

$$query(X_1, X_2, \dots, X_n) :- r_1(X_1, X_2, \dots, X_n). \\ query(X_1, X_2, \dots, X_n) :- r_2(X_1, X_2, \dots, X_n).$$

- Set difference of r_1 and r_2 .

$$query(X_1, X_2, \dots, X_n) :- r_1(X_1, X_2, \dots, X_n), \\ \text{not } r_2(X_1, X_2, \dots, X_n).$$

Recursion in Datalog

- Create a view relation *empl* that contains every tuple (X, Y) such that X is directly or indirectly managed by Y .

$$empl(X, Y) :- manager(X, Y). \\ empl(X, Y) :- manager(X, Z), empl(Z, Y).$$

- Find the direct and indirect employees of Jones.

$$? empl(X, \text{"Jones"}).$$

manager

| <i>employee-name</i> | <i>manager-name</i> |
|----------------------|---------------------|
| Alon | Barinsky |
| Barinsky | Estovar |
| Corbin | Duarte |
| Duarte | Jones |
| Estovar | Jones |
| Jones | Klinger |
| Rensal | Klinger |

Semantics of Recursion in Datalog

- The view relations of a recursive program containing a set of rules \mathcal{R} are defined to contain exactly the set of facts I computed by the iterative procedure *Datalog-Fixpoint*

```
procedure Datalog-Fixpoint
     $I$  = set of facts in the database
    repeat
         $Old\_I = I$ 
         $I = I \cup infer(\mathcal{R}, I)$ 
    until  $I = Old\_I$ 
```

- At the end of the procedure, $infer(\mathcal{R}, I) = I$
- I is called a *fixpoint* of the program.
- *Datalog-Fixpoint* computes only true facts so long as no rule in the program has a negative literal.

The Power of Recursion

- Recursive views make it possible to write queries, such as transitive closure queries, that cannot be written without recursion or iteration.
- A view V is said to be **monotonic** if given any two sets of facts I_1 and I_2 such that $I_1 \subseteq I_2$, $E_V(I_1) \subseteq E_V(I_2)$, where E_V is the expression used to define V .
- Procedure *Datalog-Fixpoint* is sound provided the function *infer* is monotonic.
- Relational algebra views defined using only the operators: $\Pi, \sigma, \times, \bowtie, \cup, \cap$ and ρ are monotonic. Views using $-$ are not monotonic.