**TOP LOADING WASHER** 

**ELECTRIC DRYER** 

**GAS DRYER** 

Speed Queen

Coin Operated Washers
and Dryers





# **Speed Queen**<sup>™</sup>

# **SPECIFICATIONS**

Coin Operated Washers and Dryers

TOP LOADING WASHER SWT111		
FEATURES		
Extra large basket volume	71 L (2.5 cu.ft)	
Normal cycle	<b>✓</b>	
Permanent press cycle	<b>✓</b>	
Delicate cycle	V	
Extract speed	640 rpm	
Water temperature selector	<i>V</i>	
Auto balancing system	<i>V</i>	
Bleach dispenser	V	
Fabric softener dispenser	Optional extra	
Top and lid finish	Tuff Guard	
Colour	White	
Tub	Stainless steel	
Self-adjusting rear levelling feet*	<b>✓</b>	
Self-cleaning lint filter	<b>✓</b>	

FEATURES	
Cylinder volume	201 L (7.1 cu.ft)
Normal/delicate cycles	<b>✓</b>
Permanent press cycle	<b>✓</b>
Time dry cycle	<b>✓</b>
Temperature/fabric selector	<b>V</b>
180° side swing reversible door	<b>✓</b>
Upfront lint filter	<b>✓</b>
Colour	White
Self-adjusting levelling feet*	<b>✓</b>
Energy input (electric)	5 Kw
Energy input (gas)	7.31 Kw (25000 BTU/Hr)

<sup>\*</sup>Heights may differ slightly depending on levelling adjustment

#### **TECHNICAL DETAILS**

Width	651mm (25 <sup>5</sup> / <sub>8</sub> ")
Depth	711mm (28")
Height (including control panel)	1086mm (423/4")
Cabinet top height	910mm (35 <sup>7</sup> / <sub>8</sub> ")
Shipping weight	101 Kg (222 Lbs)

Motor - 375W (1/2hp) reversing motor, permanently lubricated with a built in automatic thermal overload protector.

#### **ELECTRICAL REQUIREMENTS**

230V 50Hz 13amp (separately fused 2 wire plus earth).

## **TECHNICAL DETAILS**

Width	683mm (26 <sup>7</sup> / <sub>8</sub> ")
Depth	711mm (28")
Height (including control panel)	1086mm (42³/₄")
Cabinet top height	910mm (35 <sup>7</sup> / <sub>8</sub> ")
Shipping weight	75 Kg (165 Lbs)

Motor - 250W (1/3hp) motor permanently lubricated with a built-in automatic thermal overload protector.

#### **ELECTRICAL REQUIREMENTS**

*Electrically heated model* - 230V 50Hz 30amp (separately fused 2 wire plus earth). 4800W heating element. Optional 2500W (13 amp) at additional cost.

Gas heated model: - 230V 50Hz 13amp (separately fused 2 wire plus earth).

(Other voltages available to special order)

### Distributed by: