@

Huebsch

50 & 75 lb On-Premises Drying Tumblers





Serving the Laundry Industry For Over 90 Years





Because on-premises laundries don't have time to deal with the bassles of maintenance and down time, Huebsch drying tumblers deliver reliable performance and much more. Innovative energy-saving features provide a more economical way to get the job done. With so many user-friendly features like a simple push-to-start button, Huebsch is an easy choice for your laundry facility.

Performance & Efficiency

The name Huebsch is synonymous with top performing drying tumblers. By balancing air flow and heat input, Huebsch can deliver fast drying without wasting energy. Our **fast drying** will save you hours of extra work and our **superior energy efficiency** will give your utility budget a break.

Construction & Features

Huebsch dryers feature an **all belt drive system** with a self adjusting tension idler. The drive system is constructed with metal pulleys and permanently sealed bearings for super quiet operation and low maintenance.



The operating controls are connected to the **modular control panel** by a single plug for reliability and convenient servicing. The wire cover eliminates the need for conduit; making the wiring easy to trace.





Huebsch offers an important new option in fire suppression. Our Combustion Automated Response Equipped (C.A.R.E.TM) system provides an initial response to suppress laundry combustion inside the tumbler cylinder and

can also provide immediate notification to property management. **C.A.R.E.** is an independent sub-system that continually monitors the cylinder temperature as long as power is provided to the unit. If the **C.A.R.E.** system detects an excessive rise in temperature (a load fire) it will spray the load with water and will also provide a "system active" output signal. This output signal may be connected to your property's alarm system, a light, or other security alarm to ensure that even though you may not be on site, **C.A.R.E.** is still monitoring your operation.

Our extra large doors are constructed of top-quality **stainless steel** to stand up to the use in the toughest laundry environments. The large **reversible** door opening provides efficient loading and unloading.





Huebsch tumblers feature a **self-cleaning lint screen** made of fine mesh. Lint is deposited into a large storage area for easy removal. The self-cleaning action maintains maximum air flow and promotes fast, efficient drying.

Optional Features

Huebsch dryers feature many different options:

Narrow width (50 lb models only)

- Bolt-on angle option for narrow width access.
- For clearance through 34 1/2" door opening.

Reversing cylinder (3 phase only)

- Optional reversing cylinder drive helps eliminate tangling during the drying cycle.
- Perfect for drying oversized items such as sheets and table linen.

Bright annealed stainless steel cylinder

• Attractive mirror-like smooth surface reduces fabric abrasion.

To ensure the comfort of your laundry workers, Huebsch models are built with an **automatic** back draft damper. This helps prevent air from entering the user area.

Additional Features

- Galvanized steel cylinder for long life
- Integrated motor overload protection
- Solid steel cap over top of the dryer
- Embossed steel cabinet for easy cleaning
- All major components easily accessible
- High temperature limit control
- Instant electronic ignition
- Superior exterior finish

$m{P}$ utting You in Control

Because different businesses have different requirements, Huebsch offers a variety of controls to meet your needs.

Our **microprocessor control** is state of the art. Computerized models feature four preset automatic drying cycles with an option to further customize four additional automatic drying cycles. A fifth setting (no heat) is also available for items requiring special care.



Our dual digital timer control models enable operators to set drying time (0-60 minutes), cool down time (0-15 minutes) and temperature (High, Medium, Low, No Heat). New features include one touch cycle repeat, automatic extended tumble, and large digital time countdown display.



Unmatched Warranty

At Huebsch, we're so confident that our quality drying tumblers are built to last, we offer a **THREE** year warranty* on the entire machine.


* Parts only, labor not included. See Huebsch Warranty Bond for specifics.




50 & 75 lb On-Premises Drying Tumbler Specifications

HC Models		50 lb		75 lb			
Width - in (mm)		38 5/8" (981)		38 5/8" (981)			
Depth - in (mm)		47" (1194)		53" (1346)			
Height - in (mm)		Gas and Elec: 76 5/8" (1946) Steam: 80" (2032)		46)	Gas and Elec: 76 5/8" (1946) Steam: 80" (2032)		
Cylinder Depth - in (mm)		30" (762)			36" (914)		
Cylinder Diam in (mm)		37" (939)			37" (939)		
Cylinder Vol cu. ft. (liters)		18.67 (528.8)			22.40 (634.4)		
Door Opening - in (mm)		26 7/8" (683)			26 7/8" (683)		
Dry Weight Capacity - lb (kg))	50 (23)		75 (34)			
Airflow - cfm (liters/sec.)		750 (354)		60 Hz Gas and Steam: 920 (434) All Electric and 50 Hz Gas & Steam: 750 (354)			
Water Inlet Size (C.A.R.E.™ System)		(1) 3/4" Hose Connection		(1) 3/4" Hose Connection			
Energy Data		Gas Models: 120,000 Btu/hr (30,240 kcal/hr) Steam Models: At 100 psig (6.9 bar): 5.1 BHP, 178,000 Btu/hr (52.0 kW) At 15 psig (1.0 bar): 3.4 BHP, 119,000 Btu/hr (34.8 kW)			Gas Models: 165,000 Btu/hr (41,580 kcal/hr) Steam Models: At 100 psig (6.9 bar): 6.1 BHP, 210,000 Btu/hr (61.6 kW) At 15 psig (1.0 bar): 4.1 BHP, 141,000 Btu/hr (41.2 kW)		
Electrical		Gas and Steam Models: Gas and Steam Mode					
Specifications		VOLT/FREQ/PH Amps Non-Rev Rev			VOLT/FREQ/PH	Amp Non-Rev	
		120/60/1	9.3	-	120/60/1	13.8	-
		200-208/240/60/1	5.1	-,	200-208/240/60/1	7.6	-
		200-208/240/60/3	2.8	4 4.2	200-208/240/60/3	1	4.3
		200/50/3 440/60/3 (Steam)	3.3	1.9	200/50/3 440/60/3 (Steam)	3.5	2.1
		460-480/60/3	1.4	1.9	460-480/60/3	1.9	2.1
		230-240/50/1	6.3	6.9	230-240/50/1	6.7	7
		230-240/50/3	3.1	4.3	230-240/50/3	3.5	4.9
		380/400-415/50/3	1.6	2	380/400-415/50/3	1.8	2.1
		Electric Models: 30 kW			Electric Models: 30 kW		
		200-208/60/3	89	88	200-208/60/3	89	88
		240/60/3	79	78	240/60/3	79	78
		440/60/3	41	41	440/60/3	41	41
		480/60/3 200/50/3	38 84	38 85	480/60/3 200/50/3	38 84	38 85
		230/50/3	73	75	230/50/3	73	75
		240/50/3	79	78	240/50/3	79	78
		380/50/3	47	48	380/50/3	47	48
		400-415/50/3	43	44	400-415/50/3	43	44
		Electric Model: 21 kW					
		240/50/1	93	95			
Plumbing Connections		Gas: 1/2" - NPT			Gas: 1/2" - NPT		
Not Weight Ib (kg)		Steam: 3/4" - NPT 545 (247)			Steam: 3/4" - NPT 615 (279)		
Net Weight - lb (kg)		602 (273)			677 (307)		
Shipping Weight - lb (kg) Shipping Dimensions - W					41 1/2" (1054)		
in (mm)	-	52 1/8" (1323)			56 3/8" (1433)		
					84 5/8" (2149) (steam)		
					81" (5057) (gas/elec)		
Agency Approvals		Gas Models:			Gas Models:		
		CSA Star, CSA Flame, _C CSA _{us} , CE			CSA Star, CSA Flame, _C CSA _{US} , CE		
		Electric and Steam Models:			Electric and Steam Models:		
		cCSA _{us} , CE			CCSA _{us} , CE		

Roughing in Dimensions





Dimensions	50 lb	75 lb	
A - Height (gas and electric) - in (mm)	76 5/8" (1946)	76 5/8" (1946)	
A - Height (steam) - in (mm)	80" (2032)	80" (2032)	
B - Depth - in (mm)	47" (1194)	53" (1194)	
C - Width - in (mm)	38 5/8" (981)	38 5/8" (981)	
D - Door Opening - in (mm)	26 7/8" (683)	26 7/8" (683)	
E - Door Clearance - in (mm)	28 5/8" (726)	28 5/8" (726)	
F - Exhaust Height - in (mm)	13 3/8" (340)	13 3/8" (340)	
G - Exhaust Vent - in (mm)	8" (203)	8" (203)	

Tumbler models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation refer to Installation, Operation and Maintenance instructions

Due to continuous product improvements, design and specifications subject to change without notice. USA and Canada models are certified by C.S.A. International. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO9001:2000 compliant.

AH06-201

Alliance Laundry Systems Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120