



Certified Penetration Testing Professional

Gobuster Cheat Sheet

Gobuster

Source: <https://github.com>

Gobuster is a Go programming-based directory scanner that allows attackers to perform fast-paced enumeration of hidden files and directories of an application. It is a convenient command-oriented tool used to brute-force URIs in websites, DNS subdomains, names of the virtual hosts on the target server, etc.

The following table lists the various Gobuster commands and their respective operations:

1. [<dns> Mode Options](#)
2. [<dir> Mode Options](#)
3. [<vhost> Mode Options](#)
4. [<dns> Mode Commands](#)
5. [<dir> Mode Commands](#)
6. [<vhost> Mode Commands](#)

1. <dns> Mode Options

Syntax		
<code>gobuster dns [flags]</code>		
Flags		
<code>-d, --domain string</code>		Target domain
<code>-h, --help</code>		Help for DNS
<code>-r, --resolver string</code>		Use custom DNS server
<code>-c, --showcname</code>		Display CNAME records
<code>-i,</code>	<code>--showips</code>	Display IP addresses
	<code>--timeout duration</code>	DNS resolver timeout
	<code>--wildcard</code>	Force continued operation when wildcard found
Global Flags		
<code>-z, --noprogess</code>		Do not display progress
<code>-o, --output string</code>		Output file to write results defaults to stdout
<code>-q, --quiet</code>		Do not print banner and other noise
<code>-t,</code>	<code>--threads int</code>	Number of concurrent threads, default is 10
	<code>--delay duration</code>	Time each thread waits between requests (e.g. 1500ms)
<code>-v, --verbose</code>		Enables verbose output
<code>-w, --wordlist string</code>		Path to wordlist

2. <dir> Mode Options

Syntax	
<code>gobuster dir [flags]</code>	

Flags		
<code>-f, --addslashes</code>		Adds to each request
<code>-c, --cookies string</code>		Cookies to use for the requests
<code>-d, --discover-backup</code>		Search for backup files by appending multiple backup extensions
<code>-e, --expanded</code>		Expanded mode, print full URLs
<code>-x, --extensions string</code>		File extension(s) to search for
<code>-r, --followredirect</code>		Follow redirects
<code>-H, --headers stringArray</code>		Specify HTTP headers, -H 'Header1: val1' -H 'Header2: val2'
<code>-h, --help</code>		Help for dir
<code>-l, --includelength</code>		Include the length of the body in the output
<code>-k, --no-tls-validation</code>		Skip TLS certificate verification
<code>-k, --insecuressl</code>		Skip SSL certificate verification
<code>-n, --nostatus</code>		Do not print status codes
<code>-P, --password string</code>		Password for basic authentication
<code>-p, --proxy string</code>		Proxy to use for requests [http(s)://host:port]
<code>-s, --statuscodes string</code>		Positive status codes
<code>-b,</code>	<code>--statuscodesblacklist string</code>	Negative status codes
	<code>--timeout duration</code>	HTTP Timeout
<code>-u, --url string</code>		Target URL
<code>-a, --useragent string</code>		Set the User-Agent string
<code>-U,</code>	<code>--username string</code>	Username for Basic Auth

	<code>--wildcard</code>	Force continued operation when wildcard found
Global Flags		
<code>-z, --noprogress</code>		Do not display progress
<code>-o, --output string</code>		Output file to write results to (defaults to stdout)
<code>-q, --quiet</code>		Do not print the banner and other noise
<code>-t,</code>	<code>--threads int</code>	Number of concurrent threads, default is 10
	<code>--delay duration</code>	Time each thread waits between requests
<code>-v, --verbose</code>		Verbose output
<code>-w, --wordlist string</code>		Path to the wordlist
<code>--no-color</code>		Disable color output
<code>--no-error</code>		Do not display errors

3. <vhost> Mode Options

Syntax		
<code>gobuster vhost [flags]</code>		
Flags		
<code>-c, --cookies string</code>		Cookies used for requests
<code>-r, --followredirect</code>		Follow redirects
<code>-H, --headers stringArray</code>		Specify HTTP headers, -H 'Header1: val1' -H 'Header2: val2'
<code>-h, --help</code>		Help for vhost
<code>-m, --method string</code>		Use the following HTTP method (default "GET")
<code>-k, --insecuressl</code>		Skip SSL certificate verification

<code>-k, --no-tls-validation</code>		Skip TLS certificate verification
<code>-P,</code>	<code>--password string</code>	Password for basic authentication
	<code>--timeout duration</code>	HTTP Timeout (default 10s)
<code>-u, --url string</code>		Target URL
<code>-a, --useragent string</code>		Set the User-Agent string
<code>-U, --username string</code>		Username for basic authentication
Global Flags		
<code>-z, --noprogess</code>		Do not display progress
<code>-o, --output string</code>		Output file to write results
<code>-q, --quiet</code>		Do not print the banner and other noise
<code>-t,</code>	<code>--threads int</code>	Number of concurrent threads
	<code>--delay duration</code>	Time each thread waits between requests
<code>-v, --verbose</code>		Verbose output
<code>-w, --wordlist string</code>		Path to the wordlist
<code>--no-color</code>		Disable color output
<code>--no-error</code>		Do not display errors

4. <dns> Mode Commands

Command	Description
<code>gobuster dns -d <Target Website> -t 50 -w common-names.txt</code>	Set number of threads to brute-force directories or subdomain names
<code>gobuster dns -d <Target website> -w ~/wordlists/subdomains.txt</code>	Display all the sub-domains
<code>gobuster dns -d <Target website> -w ~/wordlists/subdomains.txt -i</code>	Display IP addresses of the obtained subdomains

<code>gobuster dns -d <Target URL/Domain> -w ~/wordlists/subdomains.txt</code>	Detects wildcard DNS
<code>gobuster dns -d <Target URL/Domain> -w ~/wordlists/subdomains.txt --wildcard</code>	Forces processing of a domain consisting of wildcard entries

5. <dir> Mode Commands

Command	Description
<code>gobuster dir -u <Target URL> -c 'session=123456' -t 50 -w common-files.txt -x .php,.html</code>	Lists out files with specific extensions
<code>gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt</code>	Obtains files or directories
<code>gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt -n</code>	Default options with disabled status code
<code>gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt -v</code>	Display verbose output
<code>gobuster dir -u <Target URL/Domain> -w ~/wordlists/shortlist.txt -l</code>	Display content length
<code>gobuster dir -u <Target website> -w ~/wordlists/shortlist.txt -q -n -e</code>	Disable the output of the result status code with expanded mode looking like 'grep mode'

6. <vhost> Mode Commands

Command	Description
<code>gobuster vhost -u <Target website> -w common-vhosts.txt</code>	Display subdomains/virtual hosts obtained from the custom wordlist