



Certified Penetration Testing Professional

Google Dorks Cheat Sheet

1. [Google Advanced Search Operators](#)
2. [List of The Search Operators](#)
3. [VoIP Footprinting](#)
4. [VPN Footprinting](#)
5. [FTP Servers](#)
6. [Detecting Footholds](#)
7. [Files Containing Usernames](#)
8. [Sensitive Directories](#)
9. [Web Server Detection](#)

1. Google Advanced Search Operators

The following table lists the search operators that work with each Google search service.

Search Service	Search Operators
Web Search	<code>allinanchor:</code> , <code>allintext:</code> , <code>allintitle</code> , <code>allinurl:</code> , <code>cache:</code> , <code>define:</code> , <code>filetype:</code> , <code>inanchor:</code> , <code>intext:</code> , <code>intitle:</code> , <code>inurl:</code> , <code>related:</code> , <code>site:</code>
Image Search	<code>allintitle:</code> , <code>allinurl:</code> , <code>filetype:</code> , <code>inurl:</code> , <code>intitle:</code> , <code>site:</code>
Groups	<code>allintext:</code> , <code>allintitle:</code> , <code>author:</code> , <code>group:</code> , <code>insubject:</code> , <code>intext:</code> , <code>intitle:</code>
Directory	<code>allintext:</code> , <code>allintitle:</code> , <code>allinurl:</code> , <code>ext:</code> , <code>filetype:</code> , <code>intext:</code> , <code>intitle:</code> , <code>inurl:</code>
News	<code>allintext:</code> , <code>allintitle:</code> , <code>allinurl:</code> , <code>intext:</code> , <code>intitle:</code> , <code>inurl:</code> , <code>location:</code> , <code>source:</code>
Product search	<code>allintext:</code> , <code>allintitle:</code>

2. List of The Search Operators

Search Operators	Description
<code>allinanchor:</code>	This operator restricts results to pages containing all query terms specified in the anchor text on links to the page Example: [<code>allinanchor:</code> best museums sydney]
<code>allintext:</code>	This operator restricts results to those containing all the query terms specified in the text of the page Example: [<code>allintext:</code> travel packing list]
<code>allintitle:</code>	This operator restricts results to those containing all the query terms specified in the title Example: [<code>allintitle:</code> detect plagiarism]
<code>allinurl:</code>	This operator restricts results to those containing all the query terms specified in the URL. Example: [<code>allinurl:</code> google faq]
<code>author:</code>	This operator will restrict your Google Groups results to include newsgroup articles specified by the author Example: [<code>children author:john author:doe</code>] or [<code>children author:doe@someaddress.com</code>]

cache:	This operator displays Google's cached version of a web page, instead of the current version of the page. Example: [cache:www.eff.org]
define:	This operator shows definitions from pages on the web for the term that follows. Example: [define: blog]
ext:	This is an undocumented alias for filetype:.
filetype:	This operator restricts the results to pages whose names end in suffix. Example: [web page evaluation checklist filetype:pdf]
group:	This operator restricts your Google Groups results in newsgroup articles from certain groups or subareas. Example: [sleep group:misc.kids.moderated]
inanchor:	This operator restricts the results to pages containing the query terms you specify in the anchor text or links to the page. Example: [restaurants inanchor:gourmet]
info:	This operator will present some information about the corresponding web page Example: [info:gothotel.com]
insubject:	This operator restricts articles in Google Groups to those that contain the terms you specify in the subject. Example: [insubject:"falling asleep"]
intext:	This operator restricts results to documents containing the term in the text. Example: [Hamish Reid intext:pandemonia]
intitle:	This operator restricts results to documents containing the term in the title. Example: [flu shot intitle:help]
inurl:	This operator restricts the results to documents containing that word in the URL. Example: [inurl:print site:www.googleguide.com]
location:	This operator finds information for a specific location. Example: [queen location:canada]

movie:	If you include this operator in your query, Google will find movie-related information. Example: [movie:steve jobs]
related:	This operator will list web pages that are similar to the web page you specify. Example: [related:www.consumerreports.org]
site:	This operator restricts the results to the site or domain you specify. Example: [admissions site:www.lse.ac.uk]
source:	This operator restricts your search to articles from the news source with the ID you specify. Example: [election source:new_york_times]
weather:	If you enter a query with the word weather and a city or location name, if Google recognizes the location, the forecast will appear at the top of the results page. Otherwise, your results will usually include links to sites with the weather conditions and forecast for that location. Example: [weather Sunnyvale CA]

3. VoIP Footprinting

Google Dork	Description
<code>intitle:"Login Page" intext:"Phone Adapter Configuration Utility"</code>	Pages containing login portals
<code>inurl:/voice/advanced/ intitle:Linksys SPA configuration</code>	Finds the Linksys VoIP router configuration page
<code>intitle:"D-Link VoIP Router" "Welcome"</code>	Pages containing D-Link login portals
<code>intitle:asterisk.management.portal web-access</code>	Look for the Asterisk management portal
<code>intitle:"SPA504G Configuration"</code>	Finds Cisco SPA504G Configuration Utility for IP phones
<code>intitle:"Sipura.SPA.Configuration" - .pdf</code>	Finds configuration pages for online VoIP devices
<code>intitle:asterisk.management.portal web-access</code>	Finds the Asterisk web management portal
<code>inurl:8080 intitle:"login" intext:"UserLogin" "English"</code>	Finds VoIP login portals

4. VPN Footprinting

Google Dork	Description
<code>filetype:pcf "cisco" "GroupPwd"</code>	Finds Cisco VPN files with group passwords for remote access
<code>"[main]" "enc_GroupPwd=" ext:txt</code>	Finds Cisco VPN client passwords
<code>"Config" intitle:"Index of" intext:vpn</code>	Finds directory with keys of VPN servers
<code>inurl:/remote/login?lang=en</code>	Finds FortiGate Firewall's SSL-VPN login portal
<code>!Host=*. * intext:enc_UserPassword=* ext:pcf</code>	Look for .pcf files which contains user VPN profiles
<code>filetype:rcf inurl:vpn</code>	Finds Sonicwall Global VPN Client files containing sensitive information and login
<code>filetype:pcf vpn OR Group</code>	Finds publicly accessible profile configuration files (.pcf) used by VPN clients
<code>vpnssl</code>	Retrieves login portals containing VPNSSL companies' access
<code>intitle:"SSL VPN Service" + intext:"Your system administrator provided the following information to help understand and remedy the security conditions:"</code>	Finds Cisco ASA login web pages
<code>site:vpn.*.*/ intitle:"login"</code>	Retrieves pages Containing Login Portals
<code>Index of / *.ovpn</code>	Finds files configuration OpenVPN, some certs, keys
<code>inurl:"/vpn/tmindex.html" vpn</code>	Netscaler & Citrix Gateway VPN login portals
<code>intitle:"inc. vpn 3000 concentrator"</code>	This search will show the login page for Cisco VPN 3000 concentrators
<code>"intitle:Cisco Systems, Inc. VPN 3000 Concentrator"</code>	The Cisco VPN 3000 Concentrator is a remote access VPN

5. FTP Servers

Google Dork	Description
<code>inurl:github.com intext:.ftpconfig -issues</code>	Returns SFTP/FTP server credentials on Github
<code>type:mil inurl:ftp ext:pdf ps</code>	Returns sensitive directories on FTP
<code>intext:pure-ftpd.conf intitle:index of</code>	Returns servers exposing pure-ftpd configuration files
<code>intitle:"Index Of" intext:sftp- config.json</code>	Extracts list of FTP/SFTP passwords from sublime text
<code>inurl:"ftp://www." "Index of /"</code>	Displays various online FTP servers
<code>inurl:~/ftp://193 filetype:(php txt html asp xml cnf sh) ~'/html'</code>	Returns a List of FTP Servers by IP address, mostly Windows NT servers with guest login capabilities
<code>intitle:"index of" share.passwd OR cloud.passwd OR ftp.passwd - public</code>	Dorks containing passwords
<code>-pub -pool intitle:"index of" db.key OR server.key OR ftp.key OR exchange.key OR host.key OR mail.key</code>	This dork will give you a lot of private keys are also known as a secret key.
<code>intitle:"index of" "ftp.log"</code>	It contains FTP LOGS
<code>intitle:"index of" "ws_ftp.log"</code>	Finds sensitive directories
<code>intitle:"index of" inurl:ftp intext:logs</code>	Finds files containing Juicy items
<code>site:ftp.* index of /ftp/backup</code>	View *Backup* files on *FTP* server of various websites
<code>site:ftp://ftp.*.*/login - inurl:https://</code>	Finds Login Portals
<code>intitle:"index of" "ftp.passwd"</code>	Finds files containing password
<code>inurl:ftp://ftp</code>	Detecting FTP sites
<code>inurl:ftp://ftp robots.txt</code>	Finding robots.txt in FTP sites
<code>"/FTPSVC2" intitle:"index of"</code>	Finds Microsoft FTP server logs
<code>inurl:"/cgi-bin/WS_FTP.LOG"</code>	Find field in cgi-bin directory
<code>intitle:ProFTPD Admin - V1.04</code>	Will show you admin page, no login needed

<code>intext:"softperms.txt" ext:TXT</code>	It will generate juicy information that may lead to a parent directory, for best practice filter according to the country
<code>intitle:"Index Of" intext:.ftpconfig</code>	Retrieves FTP/SFTP credentials in. ftpconfig file from Atom text editor
<code>"[FFFTP]" ext:ini</code>	Finds files with FTP logins, server info, and more
<code>inurl:"http://ftp.dlink"</code>	Find lists of FTP directories of D-Link routers
<code>inurl:proftpdpasswd</code>	Dork of proftpd passwords
<code>"[HKEY_CURRENT_USER\Software\sota \FFFTP]" filetype:reg</code>	Finds some files with juicy information about Windows servers
<code>intext:"Powered by net2ftp"</code>	Web based FTP client login page
<code>inurl:"ftp" intext:"user" "username" "userID" "user ID" "logon" "login" intext:"password" "passcode" filetype:xls filetype:xlsx</code>	Retrieves Passwords
<code>intitle:"Index of ftp"</code>	This dork finds open ftps. This is a base dork, where you can add <code>intext:"ssh/"</code> for folder search and <code>intext:"-2015"</code> for dates and years
<code>inurl:ftp inurl:Seagate inurl:Backup inurl:Plus inurl:Drive</code>	Finds open Seagate NAS drives
<code>filetype:xml inurl:/WEB-INF/ inurl:ftp:// -www</code>	Finds sensitive and interesting information under WEB-INF directory via ftp protocol
<code>inurl:ws_ftp.ini "[WS_FTP]" filetype:ini</code>	Finds files containing passwords
<code>inurl:github.com intext:sftp- conf.json +intext:/wp-content/</code>	Find FTP logins and full path disclosures pushed to github
<code>site:github.com inurl:sftp- config.json</code>	Find disclosed FTP login credentials in GitHub repositories
<code>site:github.com inurl:sftp- config.json intext:/wp-content/</code>	Finds disclosed FTP for Wordpress installs, which have been pushed to a public repo on GitHub
<code>filetype:config inurl:web.config inurl:ftp</code>	Finds sensitive information of MySQLServer, "uid, and password" in web.config through ftp

<code>inurl:php intitle:"Cpanel , FTP CraCkeR"</code>	Locates cpanel and ftp cracker
<code>inurl:ftp "password" filetype:xls</code>	This string is used to find many low hanging fruits on FTP sites recently indexed by google
<code>filetype:ini "[FFFTP]" (pass passwd password pwd)</code>	Run the password hash through John etc.
<code>"parent directory" +proftpdpasswd</code>	Usernames and password hashes from web server backups generated by cpanel for ProFTPd. Password hashes can be cracked, granting direct access to FTP accounts. Unix passwd and shadow files can sometimes be found with this query as well.
<code>intitle:"FTP root at"</code>	This dork will return some FTP root directories
<code>intitle:"index of" inurl:ftp (pub incoming)</code>	Adding "inurl:ftp (pub incoming)" to the "index.of" searches help to locate FTP websites
<code>intitle:mywebftp "Please enter your password"</code>	Install it on a remote server and easily connect to your FTP servers through a firewall or a proxy not allowing FTP connections
<code>"index of/" "ws_ftp.ini" "parent directory"</code>	Cleans up the previous entry
<code>filetype:ini wx_ftp</code>	Searches for Total commander FTP passwords (encrypted) in a file called wx_ftp.ini
<code>LeapFTP intitle:"index.of/" sites.ini modified</code>	Finds LeapFTP client configuration file "sites.ini" holds the login credentials for those sites in plain text
<code>"ftp://" "www.eastgame.net"</code>	Finds eastgame.net FTP servers, loads of warez and that sort of thing
<code>filetype:ini ws_ftp pwd</code>	These files can be found with the "index of" keyword or by searching directly for the PWD= value inside the configuration file
<code>filetype:conf inurl:proftpd.conf -sample</code>	Standard FTP configuration file that provides far too many details about how the server is setup, including installation paths, location of log files, generic username and associated group, etc

<code>+htpasswd +WS_FTP.LOG filetype:log</code>	WS_FTP.LOG can be used in many ways to find more information about a server
<code>filetype:url +inurl:"ftp://" +inurl:"@"</code>	These are FTP Bookmarks, some of which contain plaintext login names and passwords
<code>intitle:index.of ws_ftp.ini</code>	ws_ftp.ini is a configuration file for a popular FTP client that stores usernames, (weakly) encoded passwords, sites, and directories that the user can store for later reference

6. Detecting Footholds

Google Dork	Description
<code>intitle:"net2ftp" "powered by net2ftp" inurl:ftp OR intext:login OR inurl:login</code>	net2ftp is a web-based FTP client written in PHP
<code>inurl:"index of" wso</code>	Access to WSO shell infected domains
<code>intitle:"freedom is real - 1945"</code>	Common web shell that sets the HTML title tag to '[freedom is real - 1945]
<code>site:*/wp-admin/install.php intitle:WordPress Installation</code>	Finds files containing Juicy information
<code>intitle:Administration - Installation - MantisBT</code>	Dorks for mantisBT CMS installation
<code>inurl:/phpmyadmin/index.php?db=</code>	Finds phpmyadmin authenticated panel
<code>inurl:"cs.html?url="</code>	Open Redirects
<code>inurl:"urlstatusgo.html?url=" - intext:"Disallowed by URL filter"</code>	Open Redirects
<code>inurl:wp- login.php?action=register</code>	Finds Wordpress sites with registration enabled
<code>inurl:/phpMyAdmin/setup/ index.php?phpMyAdmin=</code>	Finds access sensitive page of phpmyadmin
<code>inurl:"/sidekiq/busy"</code>	Get the sidekiq dashboard that is used to run Ruby systems
<code>intitle:"InfluxDB - Admin Interface" -github</code>	Dork about InfluxDB without password
<code>intitle:"FCKeditor - Connectors Tests"</code>	Finds unauthenticated file upload and directory list

intitle:"FCKeditor - Uploaders Tests"	Finds unauthenticated file upload
intext:"M3R1C4 SHELL BACKDOOR"	Foothold web shell
"index of" /wp-content/uploads/shell.php	Google Dork discovers servers running Wordpress that are infected with web shells
"File Manager - Current disk free"	Google Dork to locate PhpSpy web shells
inurl: "Mister Spy" intext:"Mister Spy & Souheyl Bypass Shell"	Google Dork discovers servers infected with the "Mister Spy" web shell
inurl: "/tiny_mce/plugins/ajaxfilemanager /inc/data.php" inurl: "/tiny_mce/plugins/ajaxfilemanager/ ajax_create_folder.php" -github	Finds tiny_mce vulnerable targets
intitle:Upload inurl:/cgi-bin/filechucker.cgi	AJAX-based web application / file manager - "filechucker" that lets you upload arbitrary files on a website
intitle:"Installing TYPO3 CMS"	Finds the first install wizard of the TYPO3 CMS
inurl:/install/stringnames.txt	DORK is useful to search moodle cms with install folder left on the hosted server
intitle:"Solr Admin" "Solr Query Syntax"	Finds Apache Solr admin panels
ext:jsp intext:"jspspy" intitle:"Jspspy web~shell v1.0"	Find login portals of jspspy webshell
"Sorting Logs:" "Please enter your password" "Powered By" -urlscan -alamy	Finds stealer botnet control panels
intitle:"Authorization" "TF" inurl:"admin.php"	Finds a bunch of unprotected botnet control panels
ext:php intext:"-rwxr-xr-x" site:.in	Discover affected software
intitle:index of intext:@WanaDecryptor@.exe	More information about the Wannacry Ransomware infected Servers
intitle:index of intext:wncry	Dork to find servers affected by Wannacry Ransomware

<code>inurl:"go.cgi?url="</code>	Finds pages which can be exploited to redirect to any site
<code>"WHMCS Auto Xploiter"</code>	Finds WHMCS exploit shell in sites
<code>"El Moujahidin Bypass Shell" ext:php</code>	Simple upload/dir shell
<code>(ext:php) (inurl:/wp-content/uploads/AAPL/loaders/)</code>	Finds a few handy little web shells
<code>inurl:?filesrc=**** ~"Current" ~"asp"</code>	Different uploaded shell names
<code>inurl:/\\filesrc=**** ~"Current" ~":"/" ~"upload"</code>	Finds the extensive list of shell backdoors implemented on websites
<code>"File Manager Version 1.0" "Coded By"</code>	Finds file managers web shells
<code>inurl:"html/js/editor/ckeditor/"</code>	Finds liferay upload file
<code>"You have selected the following files for upload (0 Files)."</code>	Finds file upload pages
<code>intitle:"nstview v2.1:: nst.void.ru" intext:"nsTView v2.1 :: nst.void.ru. Password: Host:"</code>	Web shell
<code>filetype:php intext:Your Email: intext:Your Name: intext:Reply-To: intext:mailer</code>	Results in PHP mailers
<code>intitle:"Hamdida X_Shell Backd00r"</code>	Backdoor
<code>"Fenix Final Version v2.0" filetype:php</code>	Web-Shell
<code>intitle:Automatic cPanel Finder/Cracker 3xplr3 Cyber Army</code>	An exploit to find uploaded cPanel Finder/Cracker script and find cracked cpanel on it
<code>inurl:revslider inurl:temp inurl:update_extract inurl:sym1</code>	Symlinks to files using the revslider vulnerability
<code>intitle:"Shell I" inurl:revslider inurl:error.php inurl:cmd</code>	Find shells inserted using the revslider vulnerability
<code>intext:Developed By Black.Hack3r ext:php</code>	Upload Shell Dorks
<code>ext:aspx intitle:aspxspy</code>	Asp shells
<code>intext:"Sw Bilgi" ext:php</code>	Upload Shell Dork

<code>intext:"Thehacker - Agd_Scorp - BLaSTER - Cr@zy_King - KinSize - JeXToXiC - s3f4 - rx5"</code>	BLaSTER Webshell Footholds
<code>intext:"Please select file to upload:" ext:php</code>	Various file upload forms
<code>inurl:sh3llz/c99/</code>	ind c99 shells uploaded on websites
<code>intitle:SN0X SHELL: WEEEEEEEEEEEEEEEEEEED</code>	Google Dork that brings up ddos shell
<code>ext:asp intext:Smart.Shell 1.0 BY POUy@_53r\3R -</code>	New WebShell
<code>intitle:"WSO 2.4" [Sec. Info], [Files], [Console], [Sql], [Php], [Safe mode], [String tools], [Bruteforce], [Network], [Self remove]</code>	Dork to find uploaded WSO 2.4 shell by hacker
<code>intitle:"=[1n73ct10n privat shell]="</code>	The dork is used to find uploaded 1n73ct10n Shell on website
<code>filetype:php intext:"!C99Shell v. 1.0 beta"</code>	php backdoor: c99 shell
<code>inurl:1337w0rm.php intitle:1337w0rm</code>	Finds websites that have 1337w0rm's CPanel cracker uploaded
<code>Re: intitle:Priv8 SCR</code>	Symlink User configs
<code>Re: inurl:"r00t.php"</code>	Finds websites that were hacked, backdoored and contains their system information
<code>intitle:C0ded By web.sniper</code>	Using this dork, you can find the User and the Domains of the Server
<code>inurl:"amfphp/browser/servicebrowser.swf"</code>	AMFPHP service browser, debug interface. Author: syddd
<code>allintext:"fs-admin.php"</code>	foothold using allintext:"fs-admin.php" shows the world-readable directories of a plug-in that enables Wordpress to be used as a forum
<code>(intitle:"SHOUTcast Administrator") (intext:"U SHOUTcast D.N.A.S. Status")</code>	SHOUTcast is a free-of-charge audio homesteading solution
<code>(intitle:"WordPress ÃfÃçÃâÃ-Ã,Ã° Setup Configuration File") (inurl:"setup-config.php?step=")</code>	Alter setup configuration files.add ?step=1

<code>"index of /" (upload.cfm upload.asp upload.php upload.cgi upload.jsp upload.pl)</code>	Searches for scripts that let you upload files which you can then execute on the server
<code>"Please re-enter your password It must match exactly"</code>	Invision Powerboard registration pages
<code>inurl:"tmtrack.dll?"</code>	Installations of Serena Teamtrack
<code>inurl:polly/CP</code>	Get into admin panel without logging
<code>intitle:MyShell 1.1.0 build 20010923</code>	Execute commands remotely on whichever server it's hosted on
<code>intitle:"YALA: Yet Another LDAP Administrator"</code>	Web-based LDAP administration GUI
<code>intitle:"ERROR: The requested URL could not be retrieved" "While trying to retrieve the URL" "The following error was encountered:"</code>	Squid error messages, most likely from reverse proxy servers
<code>PHPKonsole PHPShell filetype:php -echo</code>	PHPKonsole is a little telnet like that can run commands on the webserver
<code>filetype:php HAXPLORER "Server Files Browser"</code>	The Haxplorer is a web-based file manager which enables the user to browse files on the webserver
<code>(inurl:81/cgi-bin/.cobalt/) (intext:"Welcome to the Cobalt RaQ")</code>	The famous Sun Linux appliance. To replace this page, transfer your new content to the directory /home/sites/home/web"
<code>intitle:"Web Data Administrator - Login"</code>	Web Data Administrator is a utility program implemented in ASP.NET that enables to easily manage SQL Server data
<code>"adding new user" inurl:addnewuser -"there are no domains"</code>	Create an account on a server running Argosoft mail server pro for windows with unlimited disk quota
<code>intitle:"PHP Shell *" "Enable stderr" filetype:php</code>	PHP Shell is a shell wrapped in a PHP script. It's a tool that executes arbitrary shell-commands or browses the filesystem on a remote Webserver
<code>"Powered by PHPFM" filetype:php - username</code>	PHPFM is an open-source file manager written in PHP

<code>+htpasswd +WS_FTP.LOG filetype:log</code>	WS_FTP.LOG can be used in many ways to find more information about a server
<code>intitle:admin intitle:login</code>	Admin Login pages

7. Files Containing Usernames

Google Dork	Description
<code>"username.xlsx" ext:xlsx</code>	Excel files containing a username
<code>inurl:/_layouts/mobile/view.aspx?List=</code>	Access Microsoft SharePoint CMS based domains
<code>"authentication failure; logname=" ext:log</code>	Finds log files for failed logins, containing usernames and login paths
<code>inurl:/profile.php?lookup=1</code>	Find administrator name in most websites and forums
<code>site:extremetracking.com inurl:"login="</code>	The search reveals usernames and links to the sites that are signed up with extremetracking.com
<code>intext:"SteamUserPassphrase=" intext:"SteamAppUser=" -"username" -"user"</code>	This will search for usernames and passwords for steam (www.steampowered.com) taken from the SteamApp.cfg file.
<code>inurl:root.asp?acs=anon</code>	This search jumps right to the main page of Outlook Web Access Public Folders and the Exchange Address Book
<code>filetype:conf inurl:proftpd.conf -sample</code>	Standard FTP configuration file that provides far too many details about how the server is setup, including installation paths, location of log files, generic username and associated group, etc
<code>filetype:log username putty</code>	Record info about the SSH client PUTTY. These files contain usernames, site names, IP addresses, ports and various other information about the SSH server

<code>filetype:reg reg +intext:"internet account manager"</code>	Reveals users' names, pop3 passwords, email addresses, servers connected to and more including IP addresses in some cases
<code>filetype:reg reg HKEY_CURRENT_USER username</code>	Finds registry files from the Windows Operating system
<code>+intext:"webalizer" +intext:"Total Usernames" +intext:"Usage Statistics for"</code>	Webalizer program displays various information but this query displays usernames that have logged into the site
<code>inurl:php inurl:hlstats intext:"Server Username"</code>	This page shows the half-life stat script and reveals username to the system
<code>index.of perform.ini</code>	This file contains information about the mIRC client and may include channel and usernames
<code>"index of" / lck</code>	These lock files often contain usernames of the user that has locked the file
<code>inurl:admin filetype:asp inurl:userlist</code>	Reveals user lists of administrative importance. User lists found using this method can range from benign "message group" lists to system user lists containing passwords
<code>inurl:admin inurl:userlist</code>	Reveals user lists of administrative importance. User lists found using this method can range from benign "message group" lists to system user lists containing passwords
<code>intitle:index.of .bash_history</code>	The file contains what a user typed at a shell command prompt
<code>intitle:index.of .sh_history</code>	Consists of what a user typed at a shell command prompt

8. Sensitive Directories

Google Dork	Description
<code>intitle:"index of" "/Cloudflare-CPanel-7.0.1"</code>	Exposes Cloudflare-Cpanel sensitive files

<code>-pool intitle:"index of" wget-log -pub</code>	Provides good insight into what was downloaded in a system
<code>intitle:"index of" "sms.log"</code>	Contains SMS LOGS
<code>intitle:"index of" "ftp.log"</code>	Contains FTP LOGS
<code>-pub -pool intitle:"index of" vagrantfile -"How to"</code>	The primary function of the Vagrantfile is to describe the type of machine required for a project, and how to configure and provision these machines. It can contain DB passwords, private keys, usernames, etc.
<code>intitle:"index of" .oracle_jre_usage/</code>	Provides version of Java used by the target
<code>-pub -pool intitle:"index of" squirrelmail/</code>	Squirrel mail configuration files and sometimes credentials
<code>intitle:"index of" api_key OR "api key" OR apiKey -pool</code>	API keys
<code>intitle:"index of" domain.key -public</code>	Domains private Keys
<code>intitle:"index of" .zshrc~ OR .zshrc OR .zshenv OR .zshenv~ -pool -public</code>	Z shell (Zsh) juicy info
<code>"key" OR key.jar intitle:"index of" webstart</code>	*Java Web Start* (also known as *JavaWS*, *javaws* or *JAWS*) allows users to start application software for the Java Platform directly from the Internet using a web browser
<code>index of /storage/logs/</code>	Provides informational Logs of the Laravel framework
<code>intitle:index.of "chroot.conf"</code>	Contains sensitive information
<code>intitle:index of "uploads"</code>	The file contains Juicy items
<code>intitle:"index of" "ws_ftp.log"</code>	Sensitive directories
<code>intitle:index.of "htaccess.txt"</code>	Contains htaccess.txt clear text sensitive information
<code>intext:"index of" intext:..bak intext:config</code>	Div backup files
<code>site:* index.of: /android/manifest.xml</code>	Android Files
<code>intitle:index.of "system.db"</code>	Sensitive Directories

<code>intitle:index.of "database.db"</code>	Sensitive Directories
<code>intitle:"Index of" wp-upload</code>	Contains WordPress sensitive information
<code>site:*/logs/default.htm</code>	Sensitive directories
<code>site:* index of: /config</code>	Juicy Files
<code>site:* index of: *.exe</code>	Juicy Files
<code>intitle:"Index of" secret</code>	Secret Folder
<code>intitle:"index of" "/etc/mysql/"</code>	Sensitive directories and files
<code>inurl:/wp-content/uploads/ninja-forms/ intitle:"index of"</code>	WordPress Ninja Forms Plugin, Sensitive file uploads
<code>indexof:backup/web.config</code>	Backup files
<code>intitle:index.of/.htaccess</code>	Sensitive Directories
<code>inurl:/_vti_txt*</code>	Google Dorks for Sensitive Directories
<code>inurl:wp-content intext:backup-db</code>	Gives result of Various backup files/Folders stored in wp-content/uploads directories of various websites It also gives database backups consisting of SQL backup files of various websites who have not secured their sensitive directories
<code>inurl:/scgi-bin*</code>	Google Dork Submission for Apache servers, usually publicly facing directories
<code>inurl: /upload.php intitle:index of</code>	Vulnerable Files
<code>inurl:/database* ext:sql intext:index of -site:github.com</code>	Files Containing Juicy Info
<code>inurl:admin/data* intext:index of</code>	Files Containing Juicy Info
<code>inurl:/admin/ intitle:index.of</code>	Index.of/ Sensitive Directories (i.e */admin/)
<code>intitle:index.of?.login</code>	Used to find user authentication files from the website directory
<code>site:*/wordpress/wordpress.bak/</code>	Sensitive directory
<code>intitle:"index of" /config.ini</code>	Files containing password, sensitive info:
<code>inurl:/wp/wp-admin/</code>	Sensitive directories
<code>intitle:index.of?.database</code>	Used to find sensitive database files (*.sql) from the website directory

<code>intitle:"index of" /content/admin/</code>	<code>intitle:"index of" /content/admin/</code>
<code>intitle:index.of.?.mysql</code>	Used to find sensitive. mysql files
<code>intitle:index.of./.db</code>	Dork to find the database information
<code>intitle:index.of.?.bak</code>	Used to find sensitive .bak files which are backup files, in web applications
<code>intitle:index.of./.sql</code>	SQL files can be downloaded from websites
<code>intitle:"Index of" login.php</code>	Contains sensitive information & sensitive files
<code>intitle:"Index of" wp-config.php</code>	Contains sensitive information & sensitive files
<code>intitle:"index of" sql inurl:./db/</code>	Sensitive database credentials
<code>inurl:/sites/default/private</code>	Contains sensitive files & directories
<code>intitle:"index of" drupal</code>	Contains Drupal Sensitive files and information
<code>intitle:"Index of" inurl:wp-json/oembed</code>	Contains sensitive files, links embedded with WordPress and can be used to find CORS
<code>intitle:"Index of" phpmyadmin</code>	Contains sensitive information
<code>intitle:"Index of" wp-admin</code>	Contains WordPress sensitive information & sensitive files
<code>intitle:index.of.?.sql</code>	Download .sql files from website
<code>inurl: /filemanager/dialog.php</code>	Sensitive directories
<code>intitle:"Index of" wp-content</code>	Contains WordPress sensitive information
<code>intitle:"Index of" wp-config</code>	Contains WordPress sensitive files
<code>intitle:"Index of" portal</code>	Public Portal Directory's
<code>intitle:"Index of" public</code>	Public Folder Directories
<code>"Index of" inurl:config inurl:production</code>	Open Directory listing with words "config" and "production" in the URL
<code>Index of / *.ovpn</code>	Files configuration OpenVPN, some certs, keys
<code>"To Parent Directory" AND "dir"> AND "web.config"</code>	Web Servers with Open Directory Listing containing web.config file
<code>intitle:"index of" intext:"Includes wordpress"</code>	Wordpress based website having sensitive directories

<code>intitle:"index of"</code> <code>intext:"Includes"</code>	Allows access to the sensitive directories using includes file
<code>filetype:svn -gitlab -github</code> <code>inurl:"/.svn"</code>	This potential flaw can be used to download content from the Web server that might otherwise be private
<code>filetype:git -github.com</code> <code>inurl:"/.git"</code>	This potential flaw can be used to download content from the Web server that might otherwise be private
<code>inurl:bc.googleusercontent.com</code> <code>intitle:index of</code>	Dork that enumerates GCP for sensitive directories
<code>intitle:"index of" scada</code>	SCADA Sensitive Directories Expose on Site
<code>"/var/cache/registry/"</code>	CS-Cart admin panel settings information
<code>type:mil inurl:ftp ext:pdf ps</code>	Gives sensitive directories via FTP
<code>allintitle: "index of/admin"</code>	Access some admin login pages and parent directory structure and some vulnerable information like framework used for the web site technology used for building the web site etc
<code>intitle: "index of" "./"</code> <code>"/bitcoin"</code>	Bitcoin Directory Listing
<code>intitle:"index of"</code> <code>".cpanel/caches/config/"</code>	Cpanel Caches Config Directory Listing
<code>intitle: "Index of" intext:log</code>	File Containing Juicy Info - Dorks allow you to view logs. (e.g./log, file/log, ftplogs, server logs)
<code>intitle:"Directory Listing For"</code> <code>"Filename" intext:Tomcat/5.0.28</code>	Access the sensitive directories of any web application using Apache Tomcat/5.0.28
<code>intitle: "index of" "includes"</code>	Access the sensitive directories (includes, wp-includes) using "includes" file
<code>intitle:"index of" "db"</code>	Access the sensitive directories using "db" file
<code>inurl:/uploads/wc-logs/</code>	WooCommerce Classes Paypal Payment Information
<code>inurl:/files/contao</code>	Shows some pdf files used in contao CMS
<code>inurl:typo3conf/l10n/</code>	Directories from typo3 cms exploiting directory listing

<code>intitle:"index of" ".dockerignore"</code>	Access the Sensitive Directories using .dockerignore file
<code>intitle:"index of" "/aws.s3/"</code>	Access the Sensitive Directories of Amazon-Web-Services
<code>intitle:"index of" ".pem"</code>	Access the. pem (Privacy Enhanced Mail) file
<code>intitle:"index of" "/bitcoin/"</code>	Access the Sensitive Directories using bitcoin directories
<code>"description" & "size"</code> <code>intitle:"index of" "owncloud"</code>	Owncloud folders
<code>"Last modified" intitle:"index of"</code> <code>"dropbox"</code>	Dropbox folders
<code>inurl:"/cgi-bin/CVS/"</code>	Find files in cgi-bin directories
<code>"sasl_passwd" smtpd.conf</code> <code>intitle:"index of"</code>	Postfix sensitive files, also passwords
<code>intitle:"index of" "/user" </code> <code>"/users"</code>	Show existing users in the system by simply going to the above-mentioned directories
<code>intitle:"index of" inurl:documents</code> <code>backup</code>	Backup folders containing very juicy info
<code>inurl:"/.Trash" intitle:"index of"</code> <code>~</code>	Juicy info in some *nix Trash bins.
<code>intitle:"index of" \$Recycle.bin</code>	Windows trash bins with a lot of juicy info
<code>intitle:"index of"</code> <code>"/Windows/Recent" </code> <code>"/Windows/History/"</code>	Can access most recently used files and history data
<code>intitle:"index of"</code> <code>"WindowsCookies"</code>	Retrieve cookies from Windows users
<code>intitle:"index of" "Application</code> <code>Data/Microsoft/Credentials"</code>	Retrieve credentials in Windows folder
<code>allinurl:"wp-</code> <code>content/plugins/wordpress-</code> <code>popup/views/admin/"</code>	Dork for finding private directories inside wordpress-popup plugin including admin data which are present in Wordpress websites
<code>allintitle:"Index of /ThinkPHP" </code> <code>inurl: "/ThinkPHP/"</code>	Dork for finding a list of private directories such as library, licence, config files, and more in ThinkPHP framework used for websites

<code>intitle:"index of/" ssh</code>	Obtain -Webserver Version - SSH Version - SSH Keys - SSH Logins - SSH .exe files
<code>intitle:"Index of/" inurl:passport</code>	Find a lot of passports
<code>inurl: "/irj/go/km/" intext:navigation</code>	Extract SAP server documents - Find SAP server - Find server structure - Find usernames and passwords - Find sensitive data - To exploit, go to the site and click on "Navigation user interface" - 1.890 results at the time of writing
<code>inurl: "/irj/go/km/docs/"</code>	Large amounts of information - User data - Sensitive data - Documents - File structure of a server - To exploit, go to the site and click on "Navigation user interface" - You can download the entire SAP server's directory - 86.600 results at the time of writing
<code>inurl: "/webdynpro/resources/sap.com/"</code>	- Discover software installed on servers - Version info - SAP J2EE exploits - Exploit server software - Find adminconsole - Possible SQL Injection: - https://www.exploit-db.com/exploits/43495 - Create new users - 1.670 results at the time of writing

<code>inurl:"ailwm-backups"</code>	Find WordPress backup files and publicly accessible wp-content directories
<code>intitle:"Index of /private/"</code>	Search Private directories also work on Yahoo
<code>index of /etc/certs/</code>	Certificate directories
<code>intitle:"index of /" intext:/backup</code>	Access to different backup files
<code>intitle:'index of' "access_log"</code>	Obtain various Wordpress directories containing access logs
<code>intitle:'index of' "error_log"</code>	Discover various Wordpress directories containing error logs.
<code>intitle:"index of /" authorized_keys</code>	Authorized keys ssh and some rsa file
<code>index of /ckeditor</code>	ckeditor directories
<code>index of kcfinder/</code>	kcfinder directories
<code>inurl:/proc/tty/ index of</code>	Gather information by parent directory to discover vulnerable or credential file
<code>intitle:index of /.sql.gz intext:/backup/</code>	Gather information of database schema and credentials data of MySQL backup
<code>intitle:" - Revision" + "subversion version"</code>	Apache subversion directory listing
<code>Index of /.svn</code>	Finds SVN directory
<code>intitle:"docker" intitle:"index of" config</code>	Finds sensitive directories expose on site
<code>inurl:filebrowser.wcgp?subDir Communicate</code>	Access Public and protected CommunicatePro mail server users' files
<code>inurl:"/wp-json/" -wordpress</code>	Find sites running WordPress CMS and access to the wp-json API endpoint which *might* be vulnerable to content injection
<code>intext:"paytm" intitle:"index of"</code>	Discovers Paytm config files and open directories of Sites
<code>intext:my.cnf intitle:index of</code>	Discovers servers exposing MySQL configuration files
<code>intext:pure-ftpd.conf intitle:index of</code>	Discovers servers exposing pure-ftpd configuration files
<code>inurl:/typo3/typo3conf</code>	Files from TYPO3 CMS installation

<code>intitle:backup+index of</code>	Checks for a public backup folder on the webserver, It might include the sensitive files or database
<code>"index of" "database.sql.zip"</code>	Discovers servers with open directories exposing database backup files
<code>"index of" "database_log"</code>	Discovers servers exposing sensitive SQL log data
<code>"Index of" "database.sql"</code>	Discovers servers with open directories exposing database files
<code>intitle:index.of id_rsa - id_rsa.pub</code>	A simple dork to find SSH private keys indexed by google, Where many of the keys work
<code>inurl:/wp-includes/certificates/</code>	Discover a lot of certificates from websites
<code>intitle:"index of /bins" arm</code>	Find servers infected with Mirai
<code>allintext:'HttpFileServer 2.3k'</code>	Dork about sensitive directory of HFS File Share Server
<code>inurl:'listprojects.spr'</code>	Dork show a list of projects in Codebeamer directory
<code>inurl:"RootFolder=" Allitems "confidential" "classified" "passwords" username</code>	SharePoint directories exposing sensitive information, usernames and sometimes passwords
<code>inurl:revslider</code> <code>inurl:'/revslider+port'</code>	infos and symlinks to revslider folders upload, plugins and settings, server and port
<code>inurl:"paypal" intitle:"index of" backup db access -github</code>	Some juicy information regarding PayPal backups and more
<code>"Powered by Apache Subversion version"</code>	Looking for the SVN source code folder
<code>inurl:"/wp-content/uploads/db-backup"</code>	Searching for the backup directory of WP-DB Backup plugin (WordPress)
<code>index of /node_modules/ -github -stackoverflow</code>	Find several of nodejs folders with important files
<code>intitle:"index.of" inurl:/filemanager/connectors/ intext:uploadtest.html</code>	Open Custom File Uploader specifically in "/FCKeditor/.."
<code>intitle:index.of</code> <code>inurl:/websendmail/</code>	Sites with WebGais – Websendmail

<code>:DIR intitle:index of inurl://whatsapp/</code>	Unconfirmed Websites leaking WhatsApp Databases
<code>intitle:"Index.Of.Applications (Parallels)" -stackoverflow -quora</code>	Dork will give application folder of parallels virtual machines showing what is installed in the virtual machines
<code>intitle:index.of home/000~root~000/</code>	Lists files under Root Directory
<code>intitle:"Index Of" intext:".Trash"</code>	Dorks containing trash folders on Linux/Unix machines
<code>intitle:CV+index of</code>	Search and download CV from web directory
<code>inurl:"apps/backend/config/"</code>	Directories containing Symfony CMS juicy info and files
<code>intext:"Powered by ViewVC" intitle:"ViewVC Repository Listing"</code>	ViewVC Repository Listing
<code>"lv_poweredBy"</code>	Folders with a lot of shared files
<code>intext: "/wp-content/uploads/wpsc/"</code>	Generates juicy information
<code>inurl:"nfs://www." "index of /"</code>	Returns files shared in Network File System (NFS)
<code>intitle:index.of .bashrc</code>	Create own shortcuts using aliases and shell functions. Aliases can be declared in bash files
<code>intext:"index of /userfiles/file/"</code>	Generate juicy information to user files
<code>inurl:/wp-content/plugins/seo-pressor/classes/</code>	Generate juicy information in the parent directory, for best practice filter according to the country
<code>intext:/wp-content/plugins/woocommerce/templates/emails/plain/</code>	Generate juicy information in the parent directory, for best practice filter according to the country
<code>inurl:/sym/root/ intitle:index.of</code>	Probable symbolic links to the root file system of the web server that can be browsable
<code>intext:"Index of /database"</code>	Obtain private database details including SQL and other database elements and contents

<code>intext:"Index of /.git"</code>	Most of the web-applications are maintained using git repositories reveals sensitive information containing data like db-info, logs, configs, main-source code, etc.
<code>intitle:index.of intext:viewvc</code>	List those that are indexed and open for viewing
<code>index of /htdocs</code>	Find unauthorized web-servers, and sensitive info through 'htdocs' folder including xamp servers
<code>intitle:"Index of /" "joomla_update.php"</code>	Finds directories with Joomla logs, often containing juicy info
<code>-inurl:htm -inurl:html intitle:"index of" NIKON</code>	Explore the Images and photos uploaded and saved in Directories from Nikon
<code>-inurl:htm -inurl:html intitle:"index of" 100CANON</code>	Explore the Images and photos uploaded and saved in Directories from Canon
<code>inurl:"/drive/folders/" site:drive.google.com</code>	Google Drive folders
<code>"Index of" inurl:"/\$Recycle.Bin/"</code>	Windows recycle bin
<code>inurl:"folderview?id="</code> <code>site:drive.google.com</code>	Finds people's private folders on Google Drive
<code>powered by h5ai</code>	Browse through files
<code>site:onedrive.live.com shared by</code>	Identifies shared archives in OneDrive
<code>"Powered by AutoIndex PHP Script" ext:php</code>	Sensitive Directories and Files Containing Juicy Info
<code>inurl:admin inurl:uploads</code>	Fishes images and text from upload sites
<code>inurl:/fckeditor/editor/plugins/aj axfilemanager /ajaxfilemanager.php</code>	Refresh, Select All, Delete, Cut, Copy, Paste, New Folder, Upload ← vulnerable exploit in process for upload web shell, Close, Info Sensitive Directories and Files Containing Juicy Info
<code>Hostinger © 2016. All rights reserved inurl:default.php</code>	Hostinger web hosting clients with default Public page, list of Sensitive Directories and list of files in public_html folder
<code>index:"html/js/editor/fckeditor/ed itor/ filemanager/connectors"</code>	name =find liferay file page

<code>inurl:/FCKeditor/editor/filemanager/upload/</code>	Access unprotected files in the FCKeditor without authentication
<code>inurl:pictures intitle:index.of</code>	Access a lot of personal pictures
<code>inurl:.ssh intitle:index.of authorized_keys</code>	SSH Keys
<code>intitle:Index of /__MACOSX ...</code>	MAC OS X. Parent Directory Wordpress information
<code>(intext:"index of /.git") ("parent directory")</code>	This dork will find git repository's which may have sensitive information
<code>intitle: Index of /awstats/data</code>	Awstats Log file's directory can reveal file/directory location
<code>inurl:/server/webapps</code>	Apache Tomcat information disclosure
<code>intitle:index.of.mail</code>	Dork with juicy info
<code>inurl:"wp-content/uploads/private"</code>	Finds directories with juicy data
<code>inurl:pipermail intitle:index.of parent</code>	Finds Pipermail Archives
<code>intitle:index.of inurl:grades site:edu</code>	Finds directories containing grades.
<code>intitle:index.of parent inurl:repos</code>	Retrieve shared repositories
<code>"Desktop" parent intitle:index.of</code>	Find desktops shared on the interwebs
<code>"My Documents" "parent" intitle:index.of</code>	Find "My Documents" folders shared on the interwebs
<code>"sql" "parent" intitle:index.of - injection</code>	Find directories containing SQL Installs and/or SQL databases
<code>inurl:.DS_Store intitle:index.of</code>	Find directories with DS_Store files
<code>inurl:/aspnet_client/system_web/</code>	Find juice directory "ASP"
<code>inurl:.listing intitle:index.of</code>	Find directories with. listing files
<code>mail spool intitle:index.of</code>	Dork for mail spools
<code>private parent intitle:index.of</code>	Dork for all sorts of juicy stuff
<code>inurl:users intitle:index.of</code>	Find user folders containing interesting files
<code>inurl:"default.php" intext:"website" "has been successfully installed on the server!"</code>	Here is a list of files and directories in your public HTML folder, it bypasses the directory-listening restriction

<code>intitle:"Index.of" "attachments"</code>	Find directories with interesting info
<code>intitle:"Index of" "WhatsApp Databases"</code>	Finds db.crypt/.db files of WhatsApp conversations
<code>intitle:"Index of" "WhatsApp Images"</code>	Retrieve WhatsApp Images folder, usually from backups
<code>intitle:"Index of" "DCIM"</code>	Access lot of camera photos dump
<code>intext:index of sym</code>	Retrieve All config file stored in this sym folder
<code>intitle:index.of.pubs</code>	Find sensitive directories
<code>intitle:"Index of" "wwwroot"</code>	Directory of wwwroot Dork
<code>intitle:"index of" inurl:"no-ip.com"</code>	Browse files stored on a personal server(home) using a dynamic DNS service to update server IP. You can replace "no-ip.com" with any other dynamic DNS hosts
<code>inurl:private_files</code>	Find directory private files xD
<code>intitle:"index of" "onetoc2" "one"</code>	View Onenote files stored in the open(*.one). These files can be read easily with Onenote or a compatible viewer, no password, no encryption
<code>inurl:wp-admin/ intext:css/</code>	Finds misconfigured WordPress sites
<code>intitle:"Index of ftp"</code>	Finds open ftps. This is a base dork, where you can add <code>intext:"ssh/"</code> for folder search and <code>intext:"-2015"</code> for dates and years
<code>intitle:index.of.dropbox</code>	Find sensitive directories
<code>intitle:index.of +"Indexed by Apache::Gallery"</code>	Google dork for finding Private pics
<code>intitle:index.of.accounts</code>	Dork for a directory with accounts
<code>inurl:/wp-content/wpbackupup_backups</code>	Sensitive data/site rips/db rips in publicly accessible folders
<code>"Config" intitle:"Index of" intext:vpn</code>	Directory with keys of VPN servers
<code>"jos_users" intitle:"Index of"</code>	Files of the configuration of user Joomla servers
<code>inurl:/cgi-bin/.cgi</code>	Finds open index of /cgi-bin

<code>allinurl:/hide_my_wp=</code>	Show plugin file folder and all file
<code>intitle:"index of" intext:".ds_store"</code>	Mac OSX directories
<code>intitle:"index of" myshare</code>	Gives access to often unconsciously shared documents, programs or sensitive information
<code>inurl:8080 intitle:"Dashboard [Jenkins]"</code>	Access to Jenkins Dashboard
<code>intext:xampp-dav-unsecure:\$apr1\$6O9scpDQ\$JGw2Tjz0jkrqfKh5hhiqD1</code>	Text file but by URL we can travel in paren directory
<code>intitle:index.of intext:.bash_history</code>	Home user's directory path indexed
<code>"index of" inurl:sym</code>	Steal the symlinks of other servers
<code>"index of" inurl:root intitle:symlink</code>	Steal Others Symlink
<code>inurl:ckfinder intext:"ckfinder.html" intitle:"Index of /ckfinder"</code>	Find root directory of CKFinder
<code>inurl:/xampp</code>	Looks for servers with xampp installed
<code>allintext:"WebServerX Server at"</code>	Quick and dirty WebserverX HTTP server google dork
<code>intitle:index.of cisco asa - site:cisco.com</code>	Google search for Pix/Asa images
<code>intitle:index.of ios - site:cisco.com</code>	Google search for Cisco IOS images
<code>intitle:index.of.config</code>	Give information about a web servers configuration
<code>allintitle:"FirstClass Login"</code>	Firstclass directory listings go to <code>http://[target]/[path]/Search</code> type just ' in the search field to get a list of downloadable files, and can search for robots.txt with some folders path or other info for site structure, getting unauthorized access on all files on the target server
<code>inurl:install.pl intext:"Reading path paramaters" -edu</code>	Everything from OS, to the forum software, etc.

"Warning: Installation directory exists at" "Powered by Zen Cart" - demo	Find fresh installations of Zen-Cartsee Full Disclosure forums for details
"Welcome to the directory listing of" "NetworkActiv-Web-Server"	NetworkActiv-Web-Server directory listing
log inurl:linklint filetype:txt - "checking"	Linklint is an Open Source Perl program that checks links on web sites
"Directory Listing for" "Hosted by Xerver"	Directory listing for Xerver web server
intitle:"Folder Listing" "Folder Listing" Name Size Date/Time File Folder	Directory listing for Fastream NETFile Web Server
intitle:"Backup-Management (phpMyBackup v.0.4 beta *)" - johnny.ihackstuff	phpMyBackup is an mySQL backup tool, with features like copying backups to a different server using FTP
intitle:"pictures thumbnails" site:pictures.sprintpcs.com	Reveals photo albums taken by Sprint PCS customers
intitle:index.of WEB-INF	Finds java powered web servers which have indexing enabled on their config directory
intitle:index.of /maildir/new/	Provides mailbox dir. that contains a lot of mails
filetype:ini Desktop.ini intext:mydocs.dll	Finds any web shared windows folder inside my docs
filetype:torrent torrent	Torrent files
"Index of" rar r01 nfo Modified 2004	New Warez Directory Lists
"Web File Browser" "Use regular expression"	Search for a PHP script used to manage files on a server
intitle:"HFS /" +"HttpFileServer"	"The HttpFileServer is a Java-based mechanism for providing web access to a set of files on a server
intitle:upload inurl:upload intext:upload -forum -shop -support -w3c	Reveals server upload portals
intitle:"index of" inurl:ftp (pub incoming)	Adding "inurl:ftp (pub incoming)" to the "index.of" searches help to locate FTP websites
allinurl:"/*/_vti_pvt/" allinurl:"/*/_vti_cnf/"	Frontpage extensions for Unix

<code>intitle:index.of abyss.conf</code>	Reveal the configuration file of the abyss webserver
<code>intitle:"index of" "parent directory" "desktop.ini" site:dyndns.org</code>	Uses desktop.ini to track users with a webserver running on their desktop computers
<code>intext:"Powered By: TotalIndex" intitle:"TotalIndex"</code>	TotalIndex v2.0 is an open-source script that is designed to replace the simple, and boring default index page of a site which lists the files in an indexed folder
<code>"intitle:Index.Of /" stats merchant cgi-* etc</code>	Looks for indexes with the following subdirectories: stats, merchant, online-store, and cgi-local or cgi-bin
<code>inurl:explorer.cfm inurl:(dirpath This_Directory)</code>	Find file manager without authentication
<code>intitle:"index of" intext:"content.ie5"</code>	Indicates the "Local settings" dir in most cases, and browsable server directories in general
<code>index.of.dcim</code>	DCIM directory is the default name for a few brands of digital cameras
<code>intitle:"index of" -inurl:htm -inurl:html mp3</code>	Mp3 files
<code>intitle:"Directory Listing For" intext:Tomcat -int</code>	Google Hackers Guide explains how to find Apache directory indexes, which are the most common found on the Internet
<code>intitle:"webadmin - /*" filetype:php directory filename permission</code>	Webadmin.php is a free simple Web-based file manager. This search finds sites that use this software
<code>intitle:index.of (inurl:fileadmin intitle:fileadmin)</code>	TYPO3 is a free Open Source content management system for enterprise purposes on the web and in intranets, featuring a set of ready-made interfaces, functions, and modules
<code>intitle:"Index of *" inurl:"my shared folder" size modified</code>	These are index pages of "My Shared Folder". Sometimes they contain juicy stuff like mp3's or avi files
<code>intitle:index.of /AlbumArt_</code>	Find directories containing commercial music. AlbumArt_{.*}.jpg are download/create by MS-Windows Media Player in the music directory

<code>intext:"d.aspx?id" inurl:"d.aspx?id"</code>	Shows files that were transmitted. A malicious user could download them from these pages
<code>"index of" / picasa.ini</code>	Picasa is an 'Automated Digital Photo Organizer' recently acquired by Google
<code>intitle:"index of /phpmyadmin" modified</code>	phpMyAdmin is a tool written in PHP intended to handle the administration of MySQL over the Web
<code>filetype:cfg ks intext:rootpw - sample -test -howto</code>	Anaconda is a Linux configuration tool like yast on suse linux. The root password is often encrypted - like md5 or read from the shadow. Sometimes an attacker can also get a cleartext password
<code>intitle:"album permissions" "Users who can modify photos" "EVERYBODY"</code>	Gallery (http://gallery.menalto.com) is software that allows users to create webalbums and upload pictures to it
<code>"Index Of /network" "last modified"</code>	Find directories contain information about network
<code>intitle:intranet inurl:intranet +intext:"human resources"</code>	Access the company's private network and provides employee listings and other sensitive information useful for any social engineering
<code>inurl:/tmp</code>	Reveal temporary files and directories on the webserver
<code>"index of" inurl:recycler</code>	Files in this directory may contain sensitive information
<code>inurl:/pls/sample/admin_/help/</code>	The default installation location of Oracle manuals
<code>inurl:ojspdemos</code>	The directory contains sample Oracle JSP scripts installed on the server
<code>inurl:j2ee/examples/jsp</code>	The directory contains sample JSP scripts which are installed on the server
<code>"index of cgi-bin"</code>	CGI directories contain scripts which can often be exploited by attackers
<code>intitle:"Index of" cfide</code>	The top-level directory of ColdFusion, a powerful web development environment

<code>intitle:"index.of.personal"</code>	The directory has various personal documents and pictures
<code>inurl:backup intitle:index.of inurl:admin</code>	Reveals backup directories and contain various information ranging from source code, SQL tables, user lists, and even passwords
<code>intitle:"Index of c:\Windows"</code>	Indicate that they share the C:\WINDOWS directory, which is the system folder for many Windows installations
<code>"Welcome to phpMyAdmin" "Create new database"</code>	phpMyAdmin is a widely spread web frontend used to maintain SQL databases. The default security mechanism is to leave it up to the admin of the website to put a .htaccess file in the directory of the application
<code>index.of.private</code>	Find directory with some private files
<code>"Index of /backup"</code>	Reveal contents of their backup directories

9. Web Server Detection

Google Dork	Description
<code>intitle:"Welcome to nginx!" intext:"Welcome to nginx on Debian!" intext:"Thank you for"</code>	Finds nginx server welcome page
<code>intitle:"index of" "Served by Sun-ONE"</code>	Finds Sun-ONE web servers
<code>-pub -pool intitle:"index of" "Served by" "Web Server"</code>	Finds LiteSpeed Webservers
<code>intitle:"index of" "server at"</code>	Another way to spot Apache web servers in case the service name is hidden
<code>site:*/server-status intext:"Apache server status for"</code>	Finds files containing Juicy information
<code>inurl:/phpmyadmin/changelog.php -github -gitlab</code>	Finds Phpmyadmin changelog file
<code>inurl:"WebPortal?bankid"</code>	Finds list of banks in ger hosted by the same hoster
<code>intitle:"IIS Windows Server" -inurl:"IIS Windows Server"</code>	Finds IIS windows server

intitle:"Apache2 Ubuntu Default Page: It works"	Finds Apache2 Ubuntu default welcome page.
inurl:/server-status + "Server MPM:"	Finds Apache server-status
inurl:phpinfo.php intext:build 2600	Finds web servers that have been unmaintained for literal decades.
intext:"Brought to you by eVetSites"	List of sites all hosted by eVetSites, hosting platform for veterinarians
inurl:OrganizationChart.cc	Finds all websites using ADSelfService and authorizing guest access to the LDAP directory. Access name, mail, mobile number, function...
intext:"Powered by GetSimple" - site:get-simple.info	Find sites using the GetSimple CMS
inurl:jsmol.php	Moodle sites using Jsmol
intitle:"WAMPSEVER homepage" "Server Configuration" "Apache Version"	Dork for instances of WAMPSEVER homepages
"Powered by BOINC"	Find websites powered by BOINC
"Proudly created with Wix.com"	Find Websites made with WIX
"I have been invoked by servletToJSP"	Find many improperly set up tomcat servlets
intext:" - 2019 Cott Systems, Inc."	Local Government Websites
intitle:Test Page for the Nginx HTTP Server on Fedora	Web server detected
"Powered by vShare"	Find websites that are used to upload files and videos
intext:"Powered by Abyss Web Server"	Machines running Abyss webserver
intitle:livezilla "Server Time"	Dork to locate LiveZilla consoles and version, as well as additional information about the server such as PHP version
intext:"Powered by phpSQLiteCMS" intitle:"phpSQLiteCMS - A simple & lightweight CMS"	phpSQLiteCMS detect
intitle:"Sucuri WebSite Firewall - Access Denied"	Sucuri Firewall detected

<code>"This server is operated by OpenX."</code>	Find websites using the OpenX webserver software
<code>intext:"Powered by Nesta"</code>	Nesta, a Ruby CMS
<code>Coldbox contentbox commandbox "Powered by ContentBox"</code>	Finds ContentBox content management tools and CMS
<code>intext:"Powered by Typesetter"</code>	Typesetter CMS dorks
<code>intext:"Powered by (Quantum Quantum CMS CMS)"</code>	Finds sites using Quantum CMS builder
<code>intext:"Powered by Sentora" - github.com</code>	Finds sites using Sentora CMS
<code>inurl:/_hcms/</code>	Get all sites using Hubspot's Content Management system (CMS)
<code>inurl:tests/mocks intext:autoloader</code>	Identify websites made with codeigniter
<code>intitle:HTTP Server Test Page powered by CentOS</code>	CentOS detected
<code>intitle:"apache tomcat/" "Apache Tomcat examples"</code>	Shows many examples of Server Apache Tomcat
<code>inurl:composer.json codeigniter - site:github.com</code>	Shows RDServer product information
<code>"RDServer Product information" inurl:"/rdagent.jsp"</code>	Shows RDServer Product information
<code>intitle:"apache tomcat/" + "Find additional important configuration information in:"</code>	Apache Tomcat web server detected
<code>intitle:"Apache2 Debian Default Page: It works"</code>	Default Apache2 HTML page
<code>inurl:rvsindex.php & /rvsindex.php?/user/login</code>	Sites running rvsitebuilder CM
<code>intitle:"miniProxy"</code>	Finds this little script: (https://github.com/joshdick/miniProxy) And provides free proxies to be used for browsing or, as it is usable with GET parameters, to use with cURL
<code>intitle:"Axis Happiness Page" "Examining webapp configuration"</code>	Reveals sensitive information including a full path disclosure in Apache Axis
<code>"var miner = new CoinHive" intext:document.domain</code>	Finds sites that run the CoinHive crypto miner

<code>inurl:"server-status" "Server Version: Apache/" "Server Built: " "Server uptime:" "Total accesses" "CPU Usage:"</code>	Shows URL which has Apache server-status file openly accessible
<code>"Application Blocked!" "Google bot"</code>	Retrieves pages with a blacklist or behind FortiGate firewall
<code>inurl:readme.md intext:"Laravel"</code>	Laravel package comes with readme.md and can identify the framework which can be further used for exploiting
<code>inurl:phpmyadmin/themes intext:"pmahomme"</code>	Identify websites that host PHPMyAdmin by detecting exposed theme files
<code>intext:"Welcome to CodeIgniter!"</code>	Identify CodeIgniter applications
<code>inurl:readme.rst intext:"CodeIgniter"</code>	CodeIgniter comes with a default offline readme.rst which most of the installed applications don't remove and get indexed. This can identify the framework and exploit it
<code>intitle:"Index of" "Apache/2.4.7 (Ubuntu) Server"</code>	Find Ubuntu servers and a certain version of Apache
<code>intitle:"Index of /" "Proudly Served by Surftown at"</code>	Finds Surftown HTTP servers
<code>inurl:/pub/ inurl:_ri_</code>	Finds servers using Oracle Responsys
<code>ext:svc inurl:wsdl</code>	Returns Web Services Description Language that will expose web services
<code>inurl:/php/info.php</code>	Php version and information page
<code>intitle:"HFS" "Server Uptime" "Server time"</code>	Finds HttpFileServer with open access
<code>inurl:phpsysinfo/index.php?disp=dynamic</code>	Shows lot of information about servers behind the webpages
<code>intitle:"Apache Status" intext:"Apache Server Status"</code>	Provides Apache Server Status, Server Version, Server Built, Current Time, Restart Time, Parent Server Generation, Server uptime
<code>intext:Apache/2.2.29 (Unix) mod_ssl/2.2.29 intitle:"Index of /"</code>	Finds Server Name and Port
<code>inurl:"/web-console/" intitle:"Administration Console"</code>	Finds Boss Application Server Info

<code>filetype:asmx inurl:(_vti_bin api webservice)</code>	Returns web service
<code>intitle:"BadBlue: the file-sharing web server anyone can use"</code>	Badblue file sharing web server detection
<code>intext:"Target Multicast Group" "beacon"</code>	Provide useful statistics and diagnostic information about a given multicast group's connectivity characteristics
<code>intitle:"Apache Status" "Apache Server Status for"</code>	New Apache server-status dork
<code>inurl:wl.exe inurl:?SS1= intext:"Operating system:" -edu - gov -mil</code>	List server apparently keeps track of many clients, not just Domains and hardware, but Operating systems as well
<code>inurl:nnls_brand.html OR inurl:nnls_nav.html</code>	Novell Nterprise Linux Services detection dork
<code>(intitle:"502 Proxy Error") (intitle:"503 Proxy Error") "The proxy server could not handle the request" -topic - mail -4suite -list - site:geocrawler.co</code>	Enables one web server to provide content from another transparently
<code>intitle:"Welcome To Your WebSTAR Home Page"</code>	This is the default page for the WebSTAR (Macintosh) web server (Headers say --> Server: WebSTAR NetCloak)
<code>intitle:"Document title goes here" intitle:"used by web search tools" " example of a simple Home Page"</code>	Finds IBM Http Server (AS/400)
<code>intitle:"Welcome to the Advanced Extranet Server, ADVX!"</code>	Webserver detection: The Advanced Extranet Server project aims to create an extensible open source web server based on Apache
<code>intitle:"Welcome to Windows Small Business Server 2003"</code>	Another way to find Small Business Server 2003
<code>intitle:"IPC@CHIP Infopage"</code>	Uses the webserver's info page which reveals interesting information
<code>intitle:"Test Page for the Apache HTTP Server on Fedora Core" intext:"Fedora Core Test Page"</code>	Finds Apache 2.0 on Fedore Core Test page
<code>Powered.by.RaidenHTTPD intitle:index.of</code>	Finds RaidenHTTPD (http://www.raidenhttpd.com/en) is a full featured web server software for Windows

<code>(inurl:81-cobalt inurl:cgi-bin/.cobalt)</code>	Finds Cobal RaQ internal pages
<code>intitle:"Resin Default Home Page"</code>	Resin provides a fast-standalone web server and locates those servers based on the title of the default page
<code>intitle:"Welcome To Xitami" -site:xitami.com</code>	The default installation of Xitami web server contains test script which provides a lot of information about the server
<code>intitle:"Welcome to Your New Home Page!" "by the Debian release"</code>	Finds default Apache page on Debian installs
<code>"About Mac OS Personal Web Sharing"</code>	Mac OS Personal Web Sharing allows Mac OS users to share Folders over the Web
<code>"Switch to table format" inurl:table plain</code>	Finds index page of O'Reilly Website Professional
<code>intitle:"Object not found!" intext:"Apache/2.0.* (Linux/SuSE) "</code>	Detects apache web server (2.0.X/SuSE) with its error page
<code>intitle:"Lotus Domino Go Webserver:" "Tuning your webserver" -site:ibm.com</code>	Domino Go Webserver is a scalable high-performance Web server that runs on a broad range of platforms
<code>intitle:"Directory Listing, Index of /*/"</code>	Small HTTP server software for private homepage hosting or big uploads
<code>intitle:"Object not found" netware "apache 1.."</code>	Show NetWare apache webserver as the result
<code>intitle:AnswerBook2 inurl:ab2/ (inurl:8888 inurl:8889)</code>	Indicates Solaris machines and second the web service is vulnerable to a format string attack
<code>intext:"404 Object Not Found" Microsoft-IIS/5.0</code>	Finds IIS 5.0 error pages = IIS 5.0 Server
<code>"powered by" "shoutstats" hourly daily</code>	Produces instant and dynamic usage reports in HTML format, for viewing in a standard browser
<code>intitle:"Shoutcast Administrator"</code>	Finds the administrator page. It can be used to detect unlisted Shoutcast servers
<code>"Novell, Inc" WEBACCESS Username Password "Version *.*" Copyright - inurl:help -guides guide</code>	Find Novell Grouwise Webaccess servers
<code>"AnWeb/1.42h" intitle:index.of</code>	Find Version of a web server
<code>"CERN httpd 3.0B (VAX VMS) "</code>	Find Version of a web server

<code>"JRun Web Server" intitle:index.of</code>	Find Version of a web server
<code>"MaXX/3.1" intitle:index.of</code>	Find Version of a web server
<code>"Microsoft-IIS/* server at" intitle:index.of</code>	Find Version of a web server
<code>"Microsoft-IIS/4.0" intitle:index.of</code>	Find Version of a web server
<code>intitle:"Page rev */*/*" inurl:"admin</code>	Find Red Hat UNIX Administration Pages
<code>HTTP_USER_AGENT=Googlebot</code>	Generic way of grabbing those CGI-spewed environmental var lists
<code>allinurl:".nsconfig" -sample -howto -tutorial</code>	Gives access to Web server's content, CGI scripts, and configuration files are controlled by entries in an access file
<code>inurl:domcfg.nsf</code>	Return a listing of servers running Lotus Domino. These servers have descriptive error messages that can obtain path and OS information
<code>intitle:"300 multiple choices"</code>	Shows sites that have the 300-error code and also reveal a server tag at the bottom of the page that an attacker could use to profile a system
<code>intitle:Snap.Server inurl:Func=</code>	Reveals the existence of a SNAP server
<code>intitle:"Test Page for Apache"</code>	Default web page for Apache 1.2.6 - 1.3.9. used to get information to determine the version of the webserver, or to search Google for vulnerable targets
<code>allintitle:Netscape FastTrack Server Home Page</code>	Finds default installations of Netscape Fasttrack Server
<code>intitle:"Test Page for Apache" "It Worked!"</code>	Default web page for Apache 1.2.6 - 1.3.9. where this information can be used to determine the version of the webserver and vulnerable targets
<code>"seeing this instead" intitle:"test page for apache"</code>	Find default web page for Apache 1.3.11 - 1.3.26
<code>intitle:"Test Page for Apache" "It Worked!" "on this web"</code>	Find default web page for Apache 1.2.6 - 1.3.9

<code>inurl:tech-support inurl:show Cisco</code>	Find Cisco products with an open web interface
<code>intitle:"Apache HTTP Server" intitle:"documentation"</code>	Obtain a set of online documentation when Apache web server is installed