



Certified Penetration Testing Professional

RustScan Cheat Sheet

RustScan

Source: <https://docs.rs>

RustScan is a modern port scanner written in the Rust programming language, designed to be both fast and efficient. It is especially noted for its speed, simplicity, and ability to integrate with other tools like Nmap.

The following tables list the various options and commands associated with RustScan.

Syntax
<code>rustscan [FLAGS] [OPTIONS] <ip> [command]...</code>

Options	
<code>-a</code>	Used to specify the target IP address or URL
<code>-r, --range</code>	Used to specify the range of ports to scan
<code>-T, --timeout</code>	The timeout before a port is assumed to be close
<code>-b, --batch</code>	Increases speed of scanning
<code>-u, --ulimit</code>	Automatically ups the ULIMIT with the value you provided
<code>-o, --output</code>	Specify a file to which the scan results should be written
<code>--no-color</code>	Disabling Color Output

<code>--no-banner</code>	Disabling the RustScan banner
<code>--no-dns</code>	Disabling DNS resolution
<code>--open-only</code>	Printing only open ports
<code>--no-summary</code>	Disabling summary printing
<code>--rate</code>	Specifying the maximum number of packets to be sent per second
<code>--no-closed</code>	Excluding closed ports from the scan results.
<code>-sC -O</code>	These options can be associated with the Nmap network scanner for OS discovery, which can be used in conjunction with RustScan for detailed scanning.
Flags	
<code>-h, --help</code>	Prints help information
<code>-q, --quiet</code>	Quiet mode. Only output the ports.
<code>-V, --version</code>	Prints version information

RustScan Commands

Command	Description
<code>rustscan -a <target_ip> -r <port_range> --tcp</code>	Scan TCP ports on a single IP address
<code>rustscan -a <target_ip> -r <port_range> --udp</code>	Scan UDP ports on a single IP address
<code>rustscan -R <start_ip>-<end_ip> -r <port_range> --tcp</code>	Scan TCP ports over a range of IP addresses
<code>rustscan -a <subnet> -r <port_range> --tcp</code>	Scan TCP ports on a subnet
<code>rustscan -a <target_ip> -r <Port Number></code>	Scan a specific target IP address with a specific port number

<code>rustscan -iL <path_to_file> -r <port_range> --tcp</code>	Scan TCP ports from a list of IPs in a file
<code>rustscan -a <target_ip> --ports-file <path_to_file> --tcp</code>	Scan a specific IP using ports listed in a file
<code>rustscan -a <target_ip> -r <port_range> --tcp --exclude-ports <ports></code>	Exclude certain ports when scanning a specific IP address
<code>rustscan -a <target_ip> -r <port_range> --tcp -o <output_file></code>	Save the results of a scan to a file