



Certified Penetration Testing Professional

SearchSploit Cheat Sheet

SearchSploit

Source: <https://www.exploit-db.com>

SearchSploit is a command-line tool that facilitates the search and utilization of the Exploit Database archives. This tool is particularly useful for attackers who are seeking quick access to a comprehensive repository of publicly available exploits and vulnerability data. Attackers can perform keyword searches, title-specific searches, and even exclude certain terms to fine-tune their search results.

Syntax
<code>searchsploit [options] term1 [term2] ... [termN]</code>

Options	
<code>-h, --help</code>	Displays the help screen with all available options and commands.
<code>-v, --verbose</code>	Enables verbose output for more detailed information.
<code>-t, --title</code>	Searches only in the title of exploits.
<code>-p, --path</code>	Displays the full path to the exploit file.
<code>-j, --json</code>	Outputs the search results in JSON format.
<code>-x, --examine</code>	Opens the selected exploit file with the default editor.
<code>-m, --mirror</code>	Creates a local copy of the exploit database.
<code>-u, --update</code>	Updates the local exploit database to the latest version.
<code>-s, --search</code>	Performs a strict search for the exact term provided.
<code>-e, --exact</code>	Shows only exact matches for the search term.
<code>-c, --case</code>	Case-sensitive search.

<code>-w, --www</code>	Searches Exploit-DB's website instead of the local copy.
<code>--exclude <terms></code>	Excludes results containing the specified terms.
<code>-o, --overflow</code>	Suppresses 'Listing too many entries' warnings.
<code>--colour</code>	Disable color highlighting in search results.
<code>--id</code>	Display the EDB-ID value rather than local path.
<code>--exclude="term"</code>	Remove values from results

SearchSploit Commands

Command	Description
<code>searchsploit afd windows local</code>	Searches for local exploits related to "afd" (Ancillary Function Driver) on Windows systems
<code>searchsploit -t oracle windows</code>	Searches for exploits related to "oracle" and "Windows" in the titles only
<code>searchsploit -p 39446</code>	Displays the full path of the exploit file with the ID 39446
<code>searchsploit -s Apache Struts 2.0.0</code>	Performs a strict search for exploits related to "Apache Struts 2.0.0"
<code>searchsploit linux reverse password</code>	Searches for exploits related to "linux", "reverse", and "password".
<code>searchsploit --cve 2021-44228</code>	Searches for the exploit related to CVE-2021-44228 (Log4Shell vulnerability).
<code>searchsploit linux kernel 3.2 --exclude="(PoC) /dos/"</code>	This command searches for exploits related to "linux kernel 3.2" but excludes results containing "(PoC)" or "/dos/" in their descriptions
<code>searchsploit -j 55555 jq</code>	This command outputs the exploit with ID 55555 in JSON format and pipes it to jq for formatted viewing