



Certified Penetration Testing Professional

ShellGPT Cheat Sheet

ShellGPT

Source: <https://github.com>

ShellGPT is a command-line productivity tool powered by AI large language models (LLM) that offers streamlined generation of shell commands, code snippets, documentation, eliminating the need for external resources (like Google search). ShellGPT is designed to quickly analyze and retrieve information for straightforward requests ranging from technical configurations to general knowledge.

Syntax

Prompt [PROMPT] The prompt to generate completions for.

Options

<code>--help</code>	Show options
<code>--model <TEXT></code>	Large language model to use. [default: gpt-4o]
<code>--temperature <FLOAT RANGE [0.0<=x<=2.0]></code>	Randomness of generated output. [default: 0.0]
<code>--top-p < FLOAT RANGE [0.0<=x<=1.0]></code>	Limits highest probable tokens (words). [default: 1.0]
<code>--md or --no-md</code>	Prettify markdown output. [default: md]
<code>--editor</code>	Open \$EDITOR to provide a prompt. [default: no-editor]
<code>--cache</code>	Cache completion results. [default: cache]
<code>--version</code>	Show version

Assistance Options

<code>--shell or -s</code>	Generate and execute shell commands
----------------------------	-------------------------------------

<code>--interaction</code> or <code>--no-interaction</code>	Interactive mode for <code>--shell</code> option
<code>--describe-shell</code> or <code>-d</code>	Describe a shell command
<code>--code</code> or <code>-c</code>	Generate only code
<code>--functions</code> or <code>--no-functions</code>	Allow function calls
Chat Options	
<code>--chat <TEXT></code>	Follow conversation with id, use "temp" for quick session
<code>--repl <TEXT></code>	Start a REPL (Read-eval-print loop) session
<code>--show-chat <Chat ID></code>	Show all messages from provided chat id
<code>--list-chats</code> or <code>-lc</code>	List all existing chat ids
Role Options	
<code>--role <TEXT></code>	System role for GPT model. [default: None]
<code>--create-role <TEXT></code>	Create role. [default: None]
<code>--show-role <TEXT></code>	Show role. [default: None]
<code>--list-roles</code> or <code>-lr</code>	List roles

ShellGPT Installation
<code>pip install shell-gpt</code>

ShellGPT Commands

sgpt Prompt	Commands Generated
<code>sgpt --shell "<find all json files in current folder>"</code>	<code># -> find . -type f -name "*.json"</code> <code># -> [E]xecute, [D]escribe, [A]bort: e</code>
<code>sgpt -s "update my system"</code>	<code># -> sudo apt update && sudo apt upgrade -y</code> <code># -> [E]xecute, [D]escribe, [A]bort: e</code>
<code>sgpt -s "POST localhost with" <data.json</code>	<code># -> curl -X POST -H "Content-Type: application/json" -d '{"a": 1, "b": 2}' http://localhost</code> <code># -> [E]xecute, [D]escribe, [A]bort: e</code>

sgpt Prompt	Generating code
<pre>sgpt --code "solve fizz buzz problem using python"</pre>	<pre>for i in range(1, 101): if i % 3 == 0 and i % 5 == 0: print("FizzBuzz") elif i % 3 == 0: print("Fizz") elif i % 5 == 0: print("Buzz") else: print(i)</pre>
<pre>sgpt --code "solve classic fizz buzz problem using Python" > fizz_buzz.py</pre>	<pre>python fizz_buzz.py # 1 # 2 # Fizz # 4 # Buzz # ...</pre>
sgpt Prompt	Chat Mode
<pre>sgpt --chat conversation_1 "please remember my favorite number: 4"</pre>	<pre># -> I will remember that your favorite number is 4.</pre>
<pre>sgpt --chat conversation_1 "what would be my favorite number + 4?"</pre>	<pre># -> Your favorite number is 4, so if we add 4 to it, the result would be 8.</pre>
ShellGPT Commands Used for Footprinting	
Footprinting using advanced Google hacking techniques	<pre>sgpt -chat footprint -shell "Use filetype search operator to obtain pdf files on the target website eccouncil.org and store the result in the recon1.txt file"</pre>
VPN Footprinting through Google Hacking Database	<pre>sgpt -chat footprint -shell "Use inurl search operator to obtain the Fortinet VPN login pages"</pre>
Finding a company's top-level Domains (TLDS) and sub-domains	<pre>sgpt -chat footprint -shell "Discover all the subdomains of 'google.com' using dig command."</pre>

Harvesting email lists using theHarvester	<code>sgpt --chat footprint --shell "Use theHarvester to gather email accounts associated with 'microsoft.com', limiting results to 200, and leveraging 'baidu' as a data source"</code>
Footprinting through social networking sites using Sherlock	<code>sgpt --chat footprint --shell "Use Sherlock to gather personal information about 'Sundar Pichai' and save the result in recon2.txt"</code>
DNS lookup using DNSRecon	<code>sgpt --chat footprint --shell "Install and use DNSRecon to perform DNS enumeration on the target domain www.certifiedhacker.com"</code>
Perform tracerouting on a target using traceroute	<code>sgpt --chat footprint --shell "Perform network tracerouting to discover the routers on the path to a target host www.certifiedhacker.com"</code>
Create and run custom Python script to automate footprinting tasks	<code>sgpt --chat footprint --shell "Develop a Python script which will accept domain name microsoft.com as input and execute a series of website footprinting commands, including DNS lookups, WHOIS records retrieval, email enumeration, and more to gather information about the target domain"</code>
ShellGPT Commands Used for Scanning	
Perform network scanning using Hping3 tool	<code>sgpt --chat scan --shell "Use hping3 to perform ICMP scanning on the target IP address 10.10.1.11 and stop after 10 iterations"</code>
Perform ACK scan on target IP address using hping3	<code>sgpt --chat scan --shell "Run a hping3 ACK scan on port 80 of target IP 10.10.1.11"</code>
Perform network scanning of target network and save IP addresses into a file	<code>sgpt --chat scan --shell "Scan the target network 10.10.1.0/24 for active hosts and place only the IP addresses into a file scan1.txt"</code>
Perform an Nmap scan with specific options	<code>sgpt --chat scan --shell "Run a fast but comprehensive nmap scan against scan1.txt with low verbosity and write the results to scan2.txt"</code>
Perform a ping scan using Nmap on the specified IP range	<code>sgpt --chat scan --shell "Use nmap to perform ICMP ECHO ping sweep on the target network 10.10.1.0/24"</code>
Perform port scanning on target IP address	<code>sgpt --chat scan --shell "Use nmap to find open ports on target IP 10.10.1.11"</code>

Perform stealth scan on a target IP address	<code>sgpt --chat scan --shell "Perform stealth scan on target IP 10.10.1.11 and display the results"</code>
Perform XMAS scan on a target IP address	<code>sgpt --chat scan --shell "Perform an XMAS scan on target IP 10.10.1.11"</code>
Perform scan for open services and ports against the list of IP addresses	<code>sgpt --chat scan --shell "Use Nmap to scan for open ports and services against a list of IP addresses in scan1.txt and copy only the port, service and version information with the respective IP address to a new file called scan3.txt"</code>
Discover open ports on a target system using Metasploit	<code>sgpt --chat scan --shell "Use Metasploit to discover open ports on the IP address 10.10.1.22"</code>
Perform scanning using Nmap for MAC details, services running and their versions on a target IP address	<code>sgpt --chat scan --shell "Use Nmap to scan open ports, MAC details, services running on open ports with their versions on target IP 10.10.1.11"</code>
Perform OS discovery using TTL	<code>sgpt --chat scan --shell "Use TTL to identify the operating system running on the target IP address 10.10.1.11"</code>
Perform OS discovery using Nmap script engine	<code>sgpt --chat scan --shell "Use Nmap script engine to perform OS discovery on the target IP addresses in scan1.txt"</code>
Developing the script to automate network scanning process	<code>sgpt --chat scan --shell "Develop a script which will automate network scanning efforts and find out live systems, open ports, running services, service versions, etc. on target IP range 10.10.1.0/24"</code>
Perform scanning using IP address decoy technique	<code>sgpt --chat scan --shell "To evade an IDS/Firewall, use IP address decoy technique to scan the target IP address 10.10.1.22"</code>
ShellGPT Commands Used for Enumeration	
Perform automated NetBIOS enumeration on specified target IPs	<code>sgpt --shell "Perform NetBIOS enumeration on target IP 10.10.1.11"</code>

Perform NetBIOS enumeration on the target IP 10.10.1.11 and display names	<code>sgpt --shell "Get NetBIOS info for IP 10.10.1.11 and display the associated names"</code>
Perform automated NetBIOS enumeration on the specified target IPs using Nmap	<code>sgpt --shell "Enumerate NetBIOS on target IP 10.10.1.22 with nmap"</code>
Perform SNMP enumeration on target IP using SnmpWalk	<code>sgpt --chat enum --shell "Perform SNMP enumeration on target IP 10.10.1.22 using SnmpWalk and display the result here"</code>
Perform SNMP enumeration on target IP using Nmap	<code>sgpt --chat enum --shell "Perform SNMP enumeration on target IP 10.10.1.22 using nmap and display the result here"</code>
Perform SMTP enumeration on the specified target IP	<code>sgpt --chat enum --shell "Perform SMTP enumeration on target IP 10.10.1.19"</code>
Perform SMTP enumeration tasks on the specified target IP using Metasploit	<code>sgpt --shell "Perform SMTP enumeration on target IP 10.10.1.19 with metasploit"</code>
Perform DNS enumeration tasks on the specified target domain	<code>sgpt --chat enum --shell "Use Nmap to perform DNS Enumeration on target domain www.certifiedhacker.com"</code>
Perform DNS cache snooping on the specified target domain using the dig command	<code>sgpt --chat enum --shell "Use dig command to perform DNS cache snooping on target domain www.certifiedhacker.com using recursive method. Use DNS server IP as 162.241.216.11"</code>
Perform DNS cache snooping using non-recursive method	<code>sgpt --chat enum --shell "Use dig command to perform DNS cache snooping on the target domain www.certifiedhacker.com using non-recursive method. Use DNS server IP as 162.241.216.11"</code>
Perform IPsec enumeration on the target IP address	<code>sgpt --shell "Perform IPsec enumeration on target IP 10.10.1.22 with Nmap"</code>
Perform scanning on target IP for open SMB ports using Nmap	<code>sgpt --shell "Scan the target IP 10.10.1.22 for the port using SMB with Nmap"</code>

Create a script to automate the process of network enumeration using various Nmap scans	<code>sgpt --chat enum --shell "Develop and execute a script which will automate various network enumeration tasks on target IP range 10.10.1.0/24"</code>
Perform LDAP enumeration using Nmap script	<code>sgpt --shell "Use nmap script to perform ldap-brute-force on IP 10.10.1.22"</code>
Perform FTP enumeration using Nmap	<code>sgpt --shell "Use Nmap to perform FTP Enumeration on www.certifiedhacker.com"</code>
ShellGPT Commands Used for Vulnerability Analysis	
To launch Nikto vulnerability scan on the target website	<code>sgpt --chat nikto --shell "Launch nikto to execute a scan against the URL www.certifiedhacker.com to identify potential vulnerabilities"</code>
Perform vulnerability scanning using Nikto on the target website and save the results	<code>sgpt --shell "Perform vulnerability scan on target url http://testphp.vulnweb.com with nikto and save the results in output.txt."</code>
Perform vulnerability scan on the target website	<code>sgpt --chat vuln --shell "Perform vulnerability scan on target url http://www.moviescope.com with Nmap"</code>
Perform vulnerability scan on the target website using skipfish	<code>sgpt --chat vuln --shell "Perform a vulnerability scan on target url http://testphp.vulnweb.com with skipfish"</code>
Generate Python script automates network scanning and vulnerability assessment tasks on the IP addresses	<code>Sgpt -chat scancode -code "Create a python script to run a fast but comprehensive Nmap scan on the IP addresses in scan1.txt and then execute vulnerability scanning using nikto against each IP address in scan1.txt"</code>
ShellGPT Commands Used for System Hacking	
Generate a payload using msfvenom tool	<code>sgpt --shell "Use msfvenom to create a TCP payload with lhost=10.10.1.13 and lport=444"</code>
To initialize listener on the given LHOST and LPORT	<code>sgpt --shell "Use msfconsole to start a listener with lhost=10.10.1.13 and lport=444"</code>
Perform SSH-bruteforce attack on the target machine using Hydra	<code>sgpt --shell "Use Hydra to perform SSH-bruteforce on IP address=10.10.1.9 using username.txt and password.txt files available at location /home/attacker/Wordlist"</code>

ShellGPT Commands Used for Steganography	
To perform image steganography using steghide	<code>sgpt --shell "Perform steganography using steghide to hide text 'My swiss account number is 232343435211113' in cover.jpg image file with password as '1234'"</code>
To extract hidden text from the suspicious file using steghide	<code>sgpt --shell "Use steghide to extract hidden text in cover.jpg"</code>
ShellGPT Commands Used for Hacking Web Servers	
Perform directory traversal on target URL using gobuster	<code>sgpt --shell "Perform a directory traversal on target url https://certifiedhacker.com using gobuster"</code>
Perform FTP brute-force attack using hydra	<code>sgpt --shell "Attempt FTP login on target IP 10.10.1.11 with hydra using usernames and passwords file from /home/attacker/Wordlists"</code>
Perform webserver footprinting on target IP address	<code>sgpt --shell "Perform webserver footprinting on target IP 10.10.1.22"</code>
Perform web server footprinting using netcat	<code>sgpt --shell "Perform webserver footprinting on target IP 10.10.1.22 with netcat"</code>
Perform website mirroring using httrack	<code>sgpt --shell "Mirror the target website certifiedhacker.com with httrack on desktop"</code>
ShellGPT Commands Used for Web Application Hacking	
Detect Web Application Firewall	<code>sgpt --shell "Check if the target url www.certifiedhacker.com has web application firewall"</code>
Check for WAF using wafwoof	<code>sgpt --shell "Check if the target url https://www.certifiedhacker.com is protected with web application firewall using wafwoof"</code>
Detect load balancers	<code>sgpt --shell "Use load balancing detector on target domain yahoo.com."</code>
Identify server-side technologies	<code>sgpt --chat HWA --shell "Launch whatweb on the target website www.moviescope.com to perform website footprinting. Run a verbose scan and print the output. Save the results in file whatweb_log.txt."</code>
Identify web application vulnerabilities on a target website	<code>sgpt --shell "Perform the Vulnerability scan on the target url www.moviescope.com"</code>

Perform web application scanning using Nmap	<code>sgpt --shell "Perform the Vulnerability scan on the target url www.moviescope.com using nmap"</code>
Perform a vulnerability scan on web application using Sn1per tool	<code>sgpt --shell "Use Sn1per tool and scan the target url www.moviescope.com for web vulnerabilities and save result in file scan3.txt"</code>
Identify files of a web application	<code>sgpt --shell "Scan the web content of target url www.moviescope.com using Dirb"</code>
Identify directories in target URL using Gobuster	<code>sgpt --shell "Scan the web content of target url www.moviescope.com using Gobuster"</code>
Perform FTP brute-force attack using hydra	<code>sgpt --shell "Attempt FTP login on target IP 10.10.1.11 with hydra using usernames and passwords file from /home/attacker/Wordlists"</code>
Automate web application hacking tasks with custom scripts	<code>sgpt --chat wah --shell "create and run a custom script for web application footprinting and vulnerability scanning. The target url is www.certifiedhacker.com"</code>
Create a custom Python script for web application scanning	<code>sgpt --chat wah --shell "create and run a custom python script for web application footprinting and vulnerability scanning. The target url is www.certifiedhacker.com"</code>
Create a custom Python script for web application scanning	<code>sgpt --chat wah --shell "create and run a custom python script which will run web application footprinting tasks to gather information and then use this information to perform vulnerability scanning on target url is www.certifiedhacker.com"</code>
Perform Web application fuzz testing using Wfuzz tool	<code>sgpt --shell "Fuzz the target url www.moviescope.com using Wfuzz tool"</code>
ShellGPT Commands Used for SQL Injection	
Check for possible SQL injection	<code>sgpt --shell "Check for all possible SQL injection on target url http://testphp.vulnweb.com"</code>
Scan the target website for SQL injection vulnerability and enumerate databases	<code>sgpt --chat sql --shell "Use sqlmap on target url http://www.moviescope.com/viewprofile.aspx?id=1 with cookie value '[cookie value]' and enumerate the DBMS databases"</code>
Enumerate the databases from the target website	<code>sgpt --chat sql --shell "Use sqlmap on target url http://www.moviescope.com/viewprofile.aspx?id=1 with cookie value '[cookie value]' and enumerate the tables pertaining to moviescope database"</code>

Retrieve the complete User_Login table data from the database moviescope	<code>sgpt --chat sql --shell "Use sqlmap on target url http://www.moviescope.com/viewprofile.aspx?id=1 with cookie value '[cookie value]' and retrieve User_Login table contents from moviescope database"</code>
Perform error based SQL injection	<code>Sgpt -shell "Perform error based SQL injection on target url with parameter as http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate the tables in acuart database"</code>
	<code>sgpt -shell "Perform error based SQL injection on target url http://testphp.vulnweb.com/listproducts.php?cat=1 and if vulnerable enumerate the database and enumerate the user table in acuart database"</code>
Perform time-based SQL Injection	<code>sgpt -shell "Check for time-based blind SQL injection on target url with parameter as http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate the database"</code>
	<code>sgpt -shell "Check for time-based blind SQL injection on the target URL http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate tables in the acuart database"</code>
	<code>sgpt -shell "Check for time-based blind SQL injection on the target URL http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate users table in acuart database"</code>
Perform UNION based SQL Injection	<code>sgpt -shell "Check for UNION-based SQL injection on the target URL with parameter as http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate the database"</code>
	<code>sgpt -shell "Check for UNION-based SQL injection on the target URL with parameter as http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate tables in acuart database"</code>
	<code>sgpt -shell "Check for UNION-based SQL injection on the target URL with parameter as http://testphp.vulnweb.com/listproducts.php?cat=1 and enumerate users table in acuart database"</code>

ShellGPT Commands Used for Cryptography	
Calculate MD5 value of the given text	<code>sgpt --shell "Calculate MD5 hash of text 'My Account number is 0234569198'"</code>
Perform multi-layer hashing	<code>sgpt --shell "Calculate MD5 hash of text 'My Account number is 0234569198' and calculate the SHA1 hash value of the MD5 value"</code>
Calculate hash of a file	<code>sgpt --chat hash --shell "Calculate CRC32 hash of the file passwords.txt located at /home/attacker"</code>
Perform basic encryption	<code>sgpt --shell "Encrypt 'Hello World' text using base64 algorithm and save the result to Output.txt file"</code>
Decrypt the encrypted data	<code>sgpt --shell "Decrypt the contents of encrypted Output.txt file located at /home/attacker using base64 algorithm"</code>