



Certified Penetration Testing Professional

Unicornscan Cheat Sheet

Unicornscan

Source: <https://sourceforge.net>

Unicornscan is an information-gathering tool used for scanning a single or multiple host for open ports and other information, it is an asynchronous TCP and UDP port scanner, it is also used for OS detection.

1. [Unicornscan Options](#)
2. [Unicornscan Scanning Options](#)
3. [Unicornscan Commands](#)

1. Unicornscan Options

Syntax	
<code>unicornscan [options] <Target></code>	
Options	
<code>-b, --broken-crc</code>	Set broken crc sums on Transport layer, [Network layer, or both]
<code>-B, --source-port</code>	Set source port or whatever the scan module expects as a number
<code>-c, --proc-duplicates</code>	Process duplicate replies
<code>-d, --delay-type</code>	Set delay type
<code>-D, --no-defpayload</code>	No default Payload, only probe known protocols

-e, --enable-module	Enable modules listed as arguments
-E, --proc-errors	For processing `non-open' responses (ICMP errors, tcp rst...)
-F, --try-frags	--
-G, --payload-group	Payload group (numeric) for tcp/udp type payload selection (default all)
-h, --help	Help
-H, --do-dns	Resolve hostnames during the reporting phase
-i, --interface	String representation of the interface to use
-I, --immediate	Immediate mode, display things as we find them
-j, --ignore-seq	A string representing the intended sequence ignorance level
-l, --logfile	Path to a file where flat text will be dumped that normally would go to the users terminal
-L, --packet-timeout	Numeric value representing the number of seconds to wait before declaring the scan over
-m, --mode	String representation of the desired scanning mode
-M, --module-dir	Path to a directory containing shared object 'modules' for unicornsCan to search
-o, --format	Format of what to display for replies
-p, --ports	Global list of ports to scan
-P, --pcap-filter	Extra pcap filter string for receiver
-q, --coverttness	Coverttness value from 0 to 255
-Q, --quiet	This option is intended to make unicornsCan play the 'quiet game'
-r, --pps	it is a numeric option containing the desired packets per second for the sender to use
-R, --repeats	Repeat packet scan N times
-s, --source-addr	The address to use to override the listeners default interfaces address
-S, --no-shuffle	Do not shuffle ports

-t, --ip-ttl	Set TTL on sent packets as in 62 or 6-16 or r64-128
-T, --ip-tos	Set TOS on sent packets
-u, --debug	Debug mask
-U, --no-openenclosed	Don't say open or closed
-w, --safefile	Write pcap file of received packets
-W, --fingerprint	OS fingerprint 0=cisco(def) 1=openbsd 2=WindowsXP 3=p0fsendsyn 4=FreeBSD 5=nmap 6=linux 7=strangetcp
-v, --verbose	Verbose
-V, --version	Display version
-z, --sniff	Sniff alike
-Z, --drone-str	drone String

2. UnicornsCan Scanning Options

Options	
-mT	SYN scan
-mTsA	ACK scan
-mTsF	Fin scan
-mTs	Null scan
-mTsFPU	Xmas scan
-mTFSRPAU	Full Xmas scan
(-mT) host:1-5	Scan ports 1 through 5
-mTFSRPAUEC	scan with all options

3. UnicornsCan Commands

Command	Description
unicornsCan <host>	Basic UnicornsCan scan
unicornsCan -r200 -mT <target website>:80,443	TCP Scanning
unicornsCan -r300 -mU <Target website>	UDP Scanning

<code>unicornsCan <target ip> -Iv</code>	Scan a host for services & OS(TTL)
<code>unicornsCan -mU -v -I <target ip>/24</code>	Perform a UDP scan on the whole network
<code>unicornsCan <host ip>:5505 -r500 -w huntfor5505.pcap -W1 -s <target ip></code>	Saving to a PCAP file
<code>unicornsCan -mTsA -v -I [IP ADDRESS]</code>	ACK scan
<code>unicornsCan <target website>/24:161,53,123 -mU -r 400</code>	Scan the 256 hosts inside the network that target resides
<code>unicornsCan -mT -R2 -W2 -t5 <target domain>/16:22</code>	TCP syn Scan
<code>unicornsCan -mTs -r 5000 -R 10000 <target ip>:31425</code>	Send to the <Target>destination port 31425 TCP packets
<code>unicornsCan -i eth0 -r 160 -E <target>:20-600</code>	A basic connect scan to find all open ports in a range using unicornsCan
<code>unicornsCan -Iv -r 160 -mT <target IP>:<port_number></code>	unicornsCan full tcp port scan
<code>unicornsCan <target1> <target2></code>	Scan multiple hosts