

# Quant. Comp. HW - 2

Steven MacCoun

Oct. 18, 2005

## 1 Simon's Problem

```
0011001100001110100110000011111110111101100000010000001001110011010100001
110001001000001110111000101001001011001010010010010010001
```

## 2 Modular Exponentiation

Here was my python code:

```
#Modular Exponentiation
import math

def modular_exponentiation(base, exponent, modulus):
    c = 1
    for e_prime in range(1, exponent+1):
        c = (c * base) % modulus
    return c

print modular_exponentiation(1234, 1234*1234, math.pow(10, 10))
```

And the output was:

3102217216.0
--------------

### 3 RSA Misuse

I first tried to solve this as strictly a math problem, but had little success, in large part because I thought that the  $\gcd(e_1, e_2)$  was somehow irrelevant to the problem. However, I noticed that normally the exponents are the same value when performing RSA, so I scoured google to see if there was some well known attack where you have a common modulus with different attacks. Turns out that it is fairly well documented, and Simmons wrote a paper on it a while back.

The basic idea is: Since

$$\gcd(e_1, e_2) = 1$$

, then

$$\exists u, v \text{ s.t. } e_1 * u + e_2 * v = 1$$

You can use this to find M:

$$(M^{e_1} \bmod n)^u (M^{e_2} \bmod n)^v = M^{e_1 * u + e_2 * v} \bmod n = M \bmod n$$

So, to get  $e_2$  and  $e_1$ , I just use the Euclidean algorithm:

### 4 Prime factorization

Problem: Consider  $n=121932632103337941464563328643500519$

(a) How many bits is  $n$ ?

```
print len(str(121932632103337941464563328643500519))
```

Output:

36

(b) Find if  $n$  is prime with program that runs in less than one second.

```
def miller_rabin_pass(a, s, d, n):
    a_to_power = pow(a, d, n)
    if a_to_power == 1:
        return True
```

```

        for i in xrange(s-1):
            if a_to_power == n - 1:
                return True
            a_to_power = (a_to_power * a_to_power) % n
        return a_to_power == n - 1

def miller_rabin(n):
    #compute s and d
    d = n - 1
    s = 0
    while d % 2 == 0:
        d >>= 1
        s += 1

    #Run several miller_rabin passes
    for repeat in xrange(20):
        a = randint(2, n-1)
        if not miller_rabin_pass(a, s, d, n):
            return False

    return True

print miller_rabin(n)

```

- (b)
- (c)
- (d)
- (e)