

# R for Stats

Statistics with R  
Basel R Bootcamp



April 2019

# R is a programming language

From [Wikipedia](#) (emphasis added):

A programming language is a **formal language** that specifies a set of instructions that can be used to produce various kinds of output. Programming languages generally consist of **instructions for a computer**. Programming languages can be used to create programs that **implement specific algorithms**.

## Algorithm

1. Load data
2. Extract variables
3. Run analysis
4. Print result

## Implementation in R


```
data <- read.table(filepath)
variables <- data %>% select(group, variable)
analysis <- lm(variable ~ group, data = variables)
summary(analysis)
```

# Why R?

R steadily **grows in popularity**.

Today, R is one of the **most popular languages for data science** and overall.

In terms of the number of data science jobs, **R beats SAS and Matlab**, and is on par with Python.



# R is so popular because

There are many good reasons to prefer R over superficially more user friendly software such as **Excel** or **SPSS** or more complex programming languages like **C++** or **Python**.

## Pro

1. **It's free**
2. Relatively **easy**
3. **Extensibility** (**CRAN**, packages)
4. **User base** (e.g., **stackoverflow**)
5. **Tidyverse** (dplyr, ggplot, etc.)
6. **RStudio**
7. **Productivity** options: **Latex**, **Markdown**, **GitHub**


## Con

It's slow, but...

**Tidyverse Rcpp**, **BH**: Links R to C++ and high-performance C++ libraries  
**rPython**: Links R to Python  
**RHadoop**: Links R to Hadoop for big data applications.


# R is great for Statistics

...because of high-performance R packages (extensions) **downloaded and used millions of times.**



# Essentials: 11 basic R lessons

1. **Everything is an object**
2. **<- creates/changes objects**
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete



# Essentials: 11 basic R lessons

1. **Everything is an object**
2. **<- creates/changes objects**
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# an object called one_two_three  
one_two_three <- c(1, 2, 3)
```

```
# print object  
one_two_three
```

```
## [1] 1 2 3
```

```
# add 100 to the object's numbers (without <- )  
one_two_three + 100
```

```
## [1] 101 102 103
```

```
# print object (no <-, no change!)  
one_two_three
```

```
## [1] 1 2 3
```

# Essentials: 11 basic R lessons

1. **Everything is an object**
2. **<- creates/changes objects**
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# print object  
one_two_three
```

```
## [1] 1 2 3
```

```
# make change permanent (with <- )  
one_two_three <- one_two_three + 100  
  
# print object (it has changed!)  
one_two_three
```

```
## [1] 101 102 103
```



# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. **Everything happens through functions**
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with `?`
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# function c()
one_two_three <- c(1, 2, 3)
```

```
# function `+`()
one_two_three + 100
```

```
## [1] 101 102 103
```

```
# function print()
one_two_three
```

```
## [1] 1 2 3
```

```
# function mean()
mean(x = one_two_three)
```

```
## [1] 2
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. **Functions have (default) arguments**
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# no argument  
mean()
```

```
## Error in mean.default(): argument "x" is missing, with no
```

```
# one (required) argument  
mean(x = c(1, 2, 3))
```

```
## [1] 2
```

```
# assume a missing value (NA)  
mean(x = c(1, 2, 3, NA))
```

```
## [1] NA
```

```
# changing default to handle NA  
mean(x = c(1, 2, 3, NA), na.rm = TRUE)
```

```
## [1] 2
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. **Functions have (default) arguments**
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# mean with pipe %>%  
c(1, 2, 3) %>% mean()
```

```
## [1] 2
```

```
# mean with pipe %>% and NA  
c(1, 2, 3, NA) %>% mean()
```


```
## [1] NA
```

```
# changing default to handle NA  
c(1, 2, 3, NA) %>% mean(na.rm = TRUE)
```

```
## [1] 2
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. **Functions live in packages**
6. Find help with `?`
7. Data lives in data frames
8. 3 data types + factors
9. `formula` and `data` specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete



# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. **Functions live in packages**
6. Find help with `?`
7. Data lives in data frames
8. 3 data types + factors
9. `formula` and `data` specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

**Install new packages** with `install.packages()`

```
# install package: Only do this once!  
install.packages("tidyverse")
```

**Load existing packages** with `library()`

```
# load package: EVERY TIME you write code  
library(tidyverse)
```

```
— Attaching packages —  
tidyverse 1.2.1 —  
✓ ggplot2 3.1.0      ✓ purrr   0.2.5  
✓ tibble  2.0.1      ✓ dplyr   0.7.6  
✓ tidyr   0.8.1      ✓ stringr 1.3.1  
✓ readr   1.1.1      ✓ forcats 0.3.0  
— Conflicts —  
se_conflicts() —  
✗ dplyr::filter() masks stats::filter()  
✗ dplyr::lag()     masks stats::lag()  
Warning message:  
package ‘tibble’ was built under R version 3.5.2
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. **Find help with ?**
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

## ?mean

mean {base}

R Documentation

### Arithmetic Mean

#### Description

Generic function for the (trimmed) arithmetic mean.

#### Usage

```
mean(x, ...)
```

## Default S3 method:

```
mean(x, trim = 0, na.rm = FALSE, ...)
```

#### Arguments

**x** An R object. Currently there are methods for numeric/logical vectors and [date](#), [date-time](#) and [time interval](#) objects. Complex vectors are allowed for `trim = 0`, only.

**trim** the fraction (0 to 0.5) of observations to be trimmed from each end of `x` before the mean is computed. Values of `trim` outside that range are taken as the nearest endpoint.

**na.rm** a logical value indicating whether NA values should be stripped before the computation proceeds.

**...** further arguments passed to or from other methods.

#### Value

If `trim` is zero (the default), the arithmetic mean of the values in `x` is computed, as a numeric or complex vector of length one. If `x` is not logical (coerced to numeric), numeric (including integer) or complex, `NA_real_` is returned, with a warning.

If `trim` is non-zero, a symmetrically trimmed mean is computed with a fraction of `trim` observations deleted from each end before the mean is computed.

#### References

Becker, R. A., Chambers, J. M. and Wilks, A. R. (1988) *The New S Language*. Wadsworth & Brooks/Cole.

# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. **Find help with ?**
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

?cor

cor {stats}

R Documentation

## Correlation, Variance and Covariance (Matrices)

### Description

`var`, `cov` and `cor` compute the variance of `x` and the covariance or correlation of `x` and `y` if these are vectors. If `x` and `y` are matrices then the covariances (or correlations) between the columns of `x` and the columns of `y` are computed.

`cov2cor` scales a covariance matrix into the corresponding correlation matrix *efficiently*.

### Usage

```
var(x, y = NULL, na.rm = FALSE, use)
```

```
cov(x, y = NULL, use = "everything",  
    method = c("pearson", "kendall", "spearman"))
```

```
cor(x, y = NULL, use = "everything",  
    method = c("pearson", "kendall", "spearman"))
```

```
cov2cor(v)
```

### Arguments

`x` a numeric vector, matrix or data frame.

`y` NULL (default) or a vector, matrix or data frame with compatible dimensions to `x`. The default is equivalent to `y = x` (but more efficient).

`na.rm` logical. Should missing values be removed?


`use` an optional character string giving a method for computing covariances in the presence of missing values. This must be (an abbreviation of) one of the strings "everything", "all.obs", "complete.obs", "na.or.complete", or "pairwise.complete.obs".

`method` a character string indicating which correlation coefficient (or covariance) is to be computed. One of "pearson" (default), "kendall", or "spearman": can be abbreviated.

`v` symmetric numeric matrix, usually positive definite such as a covariance matrix.

# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with `?`
7. **Data lives in data frames**
8. 3 data types + factors
9. `formula` and `data` specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete





# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with `?`
7. Data lives in data frames
8. **3 data types + factors**
9. `formula` and `data` specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

numeric Vector	character Vector	logical Vector
<code>.\$age</code>	<code>.\$sex</code>	<code>.\$sex=="male"</code>
44	"male"	TRUE
65	"female"	FALSE
31	"male"	TRUE
...	...	...

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. **3 data types + factors**
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
print(baselers)
```

```
## # A tibble: 10,000 x 20
##       id sex    age height weight income
##   <dbl> <chr> <dbl>   <dbl>   <dbl>   <dbl>
## 1     1 1 male    44    174.    113.    6300
## 2     2 2 male    65    180.    75.2   10900
## 3     3 3 fema... 31    168.    55.5    5100
## 4     4 4 male    27    209     93.8    4200
## 5     5 5 male    24    177.     NA     4000
## 6     6 6 male    63    187.    67.4   11400
## 7     7 7 male    71    152.    83.3   12000
## 8     8 8 fema... 41    156.    67.8    7600
## 9     9 9 male    43    176.    69.3    8500
## 10    10 10 fema... 31    166.    66.3    6100
## # ... with 9,990 more rows, and 14 more variables
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. **3 data types + factors**
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# select sex variable using $  
baselers$sex
```

```
## [1] "male"    "male"    "female"  "male"    "male"  
## [6] "male"    "male"    "female"  
## [ reached getOption("max.print") -- omitted 9992 entries]
```

```
# select sex variable using %>% select  
baselers %>% select(sex) %>% pull()
```

```
## [1] "male"    "male"    "female"  "male"    "male"  
## [6] "male"    "male"    "female"  
## [ reached getOption("max.print") -- omitted 9992 entries]
```

```
# Possible, but less pretty...  
baselers[['sex']]  
baselers[[2]]
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. **3 data types + factors**
9. formula and data specify a model
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# original sex vector  
baselers$sex
```

```
## [1] "male" "male" "female" "male" "male"  
## [6] "male"  
## [ reached getOption("max.print") -- omitted 9994 entries]
```

```
as.factor(baselers$sex)
```

```
## [1] male male female male male male  
## [ reached getOption("max.print") -- omitted 9994 entries]  
## Levels: female male
```


```
as.factor(baselers$weight)
```

```
## [1] 113.4 75.2 55.5 93.8 <NA> 67.4  
## [ reached getOption("max.print") -- omitted 9994 entries]  
## 719 Levels: 37.9 38.3 39.2 39.6 40.3 ... 125.4
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with `?`
7. Data lives in data frames
8. 3 data types + factors
9. **formula and data specify a model**
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

```
# Run a regression and store result in my_lm
my_lm <- lm(formula = income ~ age + height,
            data = baselers)
```



# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with `?`
7. Data lives in data frames
8. 3 data types + factors
9. **formula and data specify a model**
10. Use RStudio and projects
11. Use editor, shortcuts, auto-complete

**Add variables** using `+`

```
# Include multiple terms with +
my_lm <- lm(formula = income ~ age + height,
            data = baselers)
```

**Include all variables** using `formula = y ~ .`

```
# Use y ~ . to include ALL variables
my_lm <- lm(formula = income ~ .,
            data = baselers)
```

**Subtract variables** using `-`


```
# Remove variables with -
my_lm <- lm(formula = income ~ . - id,
            data = baselers)
```

# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. **Use RStudio and projects**
11. Use editor, shortcuts, auto-complete

## Projects help...

save workspace and history • set project specific options •  
access files • version control • etc.




# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. **Use RStudio and projects**
11. Use editor, shortcuts, auto-complete

## Folder structure


Complement projects by a **folder structure** appropriate for your project.





# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. **Use editor, shortcuts, auto-complete**



The screenshot shows the RStudio interface with two panes: 'Editor' and 'Console'. The Editor pane on the left contains R code for loading packages, reading a CSV file, and performing a linear regression. The Console pane on the right shows the output of the code, including the parsed column specification for the data frame.

```
1 # load packages
2 library(tidyverse)
3
4 # load data
5 baselers <- read_csv('data/baselers.csv')
6
7 # analyze
8 summary(baselers)
9
10 # regression
11 lm(weight ~ sex,
12     data = baselers)
```

```
> # load packages
> library(tidyverse)
>
> # load data
> baselers <- read_csv('_sessions/_data/complete/baselers.csv')
Parsed with column specification:
cols(
  .default = col_integer(),
  sex = col_character(),
  height = col_double(),
  weight = col_double(),
```

Shortcut to **send to console**:

⌘/ctrl + ↵

Shortcut to **rerun chunk**:

⌘/ctrl + ⇧ + p

# Essentials: 11 basic R lessons


1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. **Use editor, shortcuts, auto-complete**

```
# Load packages with library()
library(tidyverse)
library(yarr)
library(lme4)

# import data with
baselers <- read_delim(file = "baselers.txt",
                      delim = '\t')
```


# Essentials: 11 basic R lessons

1. Everything is an object
2. `<-` creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. **Use editor, shortcuts, auto-complete**




# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. **Use editor, shortcuts, auto-complete**



# Essentials: 11 basic R lessons

1. Everything is an object
2. <- creates/changes objects
3. Everything happens through functions
4. Functions have (default) arguments
5. Functions live in packages
6. Find help with ?
7. Data lives in data frames
8. 3 data types + factors
9. formula and data specify a model
10. Use RStudio and projects
11. **Use editor, shortcuts, auto-complete**



Download

# Interactive