

Base URL : <https://www.googleapis.com/books/v1>

Performing Search :

[https://www.googleapis.com/books/v1/volumes?
q=flowers+inauthor:keyes&key=yourAPIKey](https://www.googleapis.com/books/v1/volumes?q=flowers+inauthor:keyes&key=yourAPIKey)

Response :

```
{
  "kind": "books#volumes",
  "items": [
    {
      "kind": "books#volume",
      "id": "_ojXNuzgHRcC",
      "etag": "OTD2tB19qn4",
      "selfLink": "https://www.googleapis.com/books/v1/volumes/_ojXNuzgHRcC",
      "volumeInfo": {
        "title": "Flowers",
        "authors": [
          "Vijaya Khisty Bodach"
        ],
        ...
      }
    }
  ]
}
```

Standard Params :

1. q - *Query String* - space or '+' separated case insensitive terms. '-' for exclusion.

Ex. q = harry+potter OR q = "harry potter"

Special keywords used to search particular fields such as:

inline | inauthor | inpublisher | subject | isbn | lccn | oclc

-
2. startIndex : position at which the result index starts, first index is 0.

-
3. filter : Filter search results based on volume type and availability.

filter = partial | full | free-ebooks | paid-ebooks | ebooks

-
4. langRestrict : Restrict results to specific language. Can be any two letter ISO-639-1 code.

-
5. maxResults : default-10, maximum-40

-
6. orderBy : relevance | newest

-
7. printType : all | books | magazines

-
8. projection : information in each result : full | lite