Google

SWE Coding Questions - Over 90 days ago and undated

165 questions candidates reported | by source site, each Hard, then Medium, then Easy

Collected 2026-10-10 | one optimal answer each, brute force as pseudo-code, follow-ups

39	108	18
HARD	MEDIUM	EASY

Optimal answers: 79 from the interview site, 26 from your app, 60 written here.
★ = top 75 Medium/Hard or top 10 Easy by Google frequency (36 in this PDF).
Study tiers by Google frequency on LeetCode: TYPE 59, TALK 93, READ 13 (in this PDF).
16 design-style questions are mixed in under their topics, last in each topic and marked DESIGN-STYLE.

Order: source site, recency (last 30 days, 90 days, ...), Hard, Medium, Easy, then strictly newest to oldest

- **1Point3Acres (31): Hard 8, Medium 23, Easy 0**
- **PracHub (85): Hard 23, Medium 58, Easy 4**
- **Exponent (38): Hard 7, Medium 18, Easy 13**
- **HackTheRounds (11): Hard 1, Medium 9, Easy 1**

Date pills (colour = how recent): LAST 30 DAYS | LAST 90 DAYS | LAST 6 MONTHS

1Point3Acres: the date the question was last asked. PracHub: the day it was posted there. Exponent: ~ means an estimate from 'N months ago' (it is the last time any company was asked). HackTheRounds shows no per-question dates.

Topics (a tag on every dated question; headings only where there are no dates)

- BFS/DFS Graph and Tree Traversal and Shortest Paths (36)
- Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns (63)
- Dynamic Programming and State-Space Optimization (19)
- Expression Parsing and Evaluation (1)
- Other: Design, Heaps, Intervals and Misc (39)
- Trie and Prefix Indexing (7)

Sources

- hacktherounds.com/questions/google
- prachub.com Google SWE Coding & Algorithms, Technical Screen only
- aced.io/questions?company=google&role=swe&type=coding
- 1point3acres.com/interview/problems/company/google (SWE coding, no OA)

How to use

- Tap any title in the Contents to jump to it.

Google - Contents

165 questions | tap a title to jump to it

1POINT3ACRES

31 questions | last 30 days: 0 | last 90 days: 0 Go >

ASKED: 91 TO 180 DAYS AGO (16) Go >

Hard (4) Go >

H	1. Huffman Tree Construction	DESIGN / OTHER		Jun 1 '26	TALK | 1Point3Acres
H	2. Matrix Flower Placement with House Adjacency	DP		May 31 '26	TALK | 1Point3Acres
H	3. Count Perfect Wake Numbers up to N	DP		May 7 '26	TALK | 1Point3Acres
H	4. Necklace Cut into Two Halves with Equal D/R C...	ARRAY / STRING		May 3 '26	TALK | 1Point3Acres

Medium (12) Go >

M	5. Longest Consecutive Path in Binary Tree	BFS / DFS / TREE		Jul 2 '26	TALK | LC 549 | 1Point3Acres
M	6. Trie Prefix Search / Autocomplete	TRIE	IN APP	Jul 2 '26	TALK | LC 208 | 1Point3Acres
M	7. Website Activity Analytics: Unique Users + Sessi...	DESIGN / OTHER		Jun 26 '26	READ | 1Point3Acres
M	8. Streaming Points: Emit K Within Distance	DESIGN / OTHER		Jun 23 '26	TALK | 1Point3Acres
★ M	9. First Bad Version with Parallel Search Follow-up	ARRAY / STRING		Jun 15 '26	TYPE | LC 278 | 1Point3Acres
M	10. Greedy Longest-Match Dictionary Tokenizer	TRIE		Jun 15 '26	READ | 1Point3Acres
M	11. Employee Hierarchy Add / Delete	BFS / DFS / TREE		Jun 10 '26	READ | 1Point3Acres
M	12. Nested Function Expression Evaluator	EXPRESSION		Jun 10 '26	TALK | LC 770 | 1Point3Acres
M	13. Tic-Tac-Toe System with K Players and 3-in-a-...	DESIGN / OTHER		May 18 '26	TALK | LC 348 | 1Point3Acres
M	14. Gate Entry / Exit Time Resolution with Tie-Brea...	DESIGN / OTHER		May 4 '26	TALK | LC 2534 | 1Point3Acres
M	15. Fence Painting Minimum Operations (Gemini T...	ARRAY / STRING		Apr 27 '26	READ | 1Point3Acres
M	16. Gold Chain Split into Two Equal Halves	DP		Apr 21 '26	READ | 1Point3Acres

ASKED: OLDER THAN 6 MONTHS (10) Go >

Hard (4) Go >

H	17. Tree Distance Sum (Re-root DP)	DP	IN APP	Jan 19 '26	TALK | LC 834 | 1Point3Acres
H	18. Babylon Tile-Stack Merge Game	DESIGN / OTHER		Dec 29 '25	TALK | 1Point3Acres
H	19. Wordle-Style 5-Letter Minimum-Guess Strategy	DESIGN / OTHER		Dec 15 '25	TALK | LC 843 | 1Point3Acres
H	20. Find All Bad Pairs Using runTest Oracle	DESIGN / OTHER		Nov 27 '25	TALK | 1Point3Acres

Medium (6) Go >

M	21. Sum of Good Subarrays (Adjacent Diff ±1)	ARRAY / STRING		Feb 8 '26	READ | 1Point3Acres
★ M	22. Streaming Insert + Find K-th Largest	DESIGN / OTHER	IN APP	Feb 4 '26	TALK | LC 703 | 1Point3Acres
M	23. Google Doc Line Wrap (Word Wrap with White...	ARRAY / STRING		Feb 1 '26	READ | 1Point3Acres
M	24. Restaurant Waitlist: join / delete / find_first_match	ARRAY / STRING		Feb 1 '26	READ | 1Point3Acres
M	25. Run-Length Vector Storage + Dot Product	ARRAY / STRING		Jan 21 '26	TALK | LC 1570 | 1Point3Acres
M	26. Two-Day Log Intersection under Memory Limit	ARRAY / STRING		Nov 27 '25	TYPE | LC 349 | 1Point3Acres

NO DATE (5) Go >

Medium (5) Go >

BFS/DFS Graph and Tree Traversal and Shortest Paths (1) Go >

M	27. Shortest Directed Cycle Through a Node	TALK | LC 2608 | 1Point3Acres

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns (1) Go >

M	28. Rotate Any m×n 2D Matrix	TYPE | LC 48 | 1Point3Acres

Google - Contents

165 questions | tap a title to jump to it

Dynamic Programming and State-Space Optimization (2) Go >

M 29. Jump Game with Profit — TYPE | LC 55 | 1Point3Acres

M 30. Count Same-Color Squares in Matrix — TYPE | LC 221 | 1Point3Acres

Other: Design, Heaps, Intervals and Misc (1) Go >

M 31. Russian Doll Envelopes — IN APP — TYPE | LC 354 | 1Point3Acres

PRACHUB

85 questions | last 30 days: 0 | last 90 days: 0 Go >

POSTED: 91 TO 180 DAYS AGO (15) Go >

Hard (5) Go >

H	32. Count Overlapping Rectangle Updates on a Grid	ARRAY / STRING	IN APP	Jul 10 '26	TALK | LC 2536 | PracHub
H	33. Infection Spread on a Grid (Cellular Automaton)	BFS / DFS / TREE		Jun 14 '26	TYPE | LC 994 | PracHub
H	34. Simulate In-Place Cellular State Updates	ARRAY / STRING	IN APP	May 4 '26	TALK | LC 289 | PracHub
H	35. Compute Turnstile Crossing Times	DESIGN / OTHER		May 4 '26	TALK | PracHub
H	36. Convert Valid Snake Case to Lower Camel Case	ARRAY / STRING		Apr 16 '26	TALK | PracHub

Medium (10) Go >

	M	37. Find A Threshold-Limited Path With Minimum R...	BFS / DFS / TREE	IN APP	Jul 6 '26	TALK | LC 1102 | PracHub
★	M	38. Filter Repeated Robot Status Messages	ARRAY / STRING		Jul 5 '26	TYPE | LC 359 | PracHub
	M	39. Find the Largest Monotone Increasing Number	ARRAY / STRING		Jul 4 '26	TALK | LC 738 | PracHub
	M	40. Check Whether Digits Are Monotone Increasing	ARRAY / STRING		Jul 4 '26	TALK | PracHub
	M	41. Build Prefix Lookup with a Trie	TRIE	IN APP	Jul 3 '26	TALK | LC 208 | PracHub
	M	42. Count Clusters of 2D Points Within a Radius	BFS / DFS / TREE		Jun 18 '26	TALK | LC 547 | PracHub
★	M	43. Solve Rooms and Top-K Streams	DESIGN / OTHER		Jun 5 '26	TYPE | LC 253 | PracHub
★	M	44. Find Containing Range	ARRAY / STRING		Jun 4 '26	TYPE | LC 56 | PracHub
	M	45. Find a Horizontal Cut That Bisects Rectangle A...	DESIGN / OTHER		Jun 4 '26	TALK | LC 850 | PracHub
	M	46. Rearrange Tasks With Cooldown	DESIGN / OTHER	IN APP	Jun 3 '26	TALK | LC 621 | PracHub

POSTED: OLDER THAN 6 MONTHS (70) Go >

Hard (18) Go >

	H	47. Find Dictionary Matches for a Jammed String	ARRAY / STRING		Apr 9 '26	TALK | LC 809 | PracHub
★	H	48. Check Digits and Combine Ranges	ARRAY / STRING		Mar 29 '26	TYPE | LC 9 | PracHub
★	H	49. Find Maximum Envelope Nesting	ARRAY / STRING	IN APP	Mar 18 '26	TYPE | LC 354 | PracHub
	H	50. Find minimum threshold enabling grid path	BFS / DFS / TREE	IN APP	Feb 11 '26	TYPE | LC 1631 | PracHub
	H	51. Find secret word with match-count feedback	DESIGN / OTHER	IN APP	Feb 11 '26	TALK | LC 843 | PracHub
	H	52. Compute distance-sum from every tree node	BFS / DFS / TREE	IN APP	Jan 22 '26	TALK | LC 834 | PracHub
	H	53. Compute minimax grid path and network delay	BFS / DFS / TREE		Jan 22 '26	TALK | LC 1631 | PracHub
	H	54. Implement Longest-Match Text Replacement	TRIE	IN APP	Jan 20 '26	TALK | LC 648 | PracHub
	H	55. Return top-k subset sums in descending order	DESIGN / OTHER		Jan 7 '26	TALK | LC 2386 | PracHub
	H	56. Minimize travel time with optional meeting point	BFS / DFS / TREE		Jan 6 '26	TYPE | LC 743 | PracHub
	H	57. Determine winner in stack-merging game	DP		Jan 6 '26	TALK | LC 292 | PracHub
	H	58. Minimize maximum height along a grid path	BFS / DFS / TREE	IN APP	Jan 4 '26	TYPE | LC 778 | PracHub
	H	59. Find longest duplicated substring	ARRAY / STRING	IN APP	Dec 8 '25	TALK | LC 1044 | PracHub
	H	60. Shuffle array using random integer API	ARRAY / STRING		Dec 8 '25	TALK | LC 384 | PracHub

Google - Contents

165 questions | tap a title to jump to it

	H	61. Compute city skyline outline	DESIGN / OTHER	IN APP	Dec 8 '25	TALK | LC 218 | PracHub
	H	62. Find maximum value in huge text file	DESIGN / OTHER		Dec 8 '25	TALK | PracHub
★	H	63. Find safe travel intervals between planet influen...	ARRAY / STRING		Nov 22 '25	TYPE | LC 56 | PracHub
	H	64. Count same-color squares in a character grid	DP		Nov 22 '25	TYPE | LC 1277 | PracHub
		Medium (48)				**Go >**
	M	65. Can board states be transformed?	ARRAY / STRING		Apr 1 '26	TALK | LC 777 | PracHub
	M	66. Check if all substrings are dictionary words	ARRAY / STRING		Mar 11 '26	TYPE | LC 139 | PracHub
★	M	67. Check if all substrings are anagrams of words	ARRAY / STRING		Mar 11 '26	TYPE | LC 49 | PracHub
	M	68. Determine if a 14-tile hand is winning	DP		Mar 9 '26	TALK | LC 659 | PracHub
	M	69. Return dictionary words matching a prefix	TRIE	IN APP	Mar 9 '26	TALK | LC 208 | PracHub
	M	70. Solve several coding interview problems	DESIGN / OTHER		Mar 4 '26	TALK | LC 415 | PracHub
★	M	71. Design a restaurant waitlist system	DESIGN / OTHER		Mar 1 '26	TYPE | LC 146 | PracHub
	M	72. Determine Reporting Relationships	BFS / DFS / TREE		Feb 22 '26	TYPE | LC 721 | PracHub
★	M	73. Solve array-sum and city-community problems	ARRAY / STRING		Feb 20 '26	TYPE | LC 560 | PracHub
	M	74. Implement Trie Insert and Exact-Word Search	TRIE	IN APP	Feb 20 '26	TALK | LC 208 | PracHub
	M	75. Find shortest relationship path using BFS	BFS / DFS / TREE	IN APP	Feb 12 '26	TALK | LC 127 | PracHub
	M	76. Check pivot after removing one element	ARRAY / STRING		Feb 12 '26	TALK | LC 724 | PracHub
	M	77. Min deletions to avoid overlap in first k	ARRAY / STRING		Feb 12 '26	TALK | PracHub
	M	78. Design Tic-Tac-Toe With K Players	ARRAY / STRING		Feb 12 '26	TALK | LC 348 | PracHub
★	M	79. Implement frequency + distance top-K queries	DESIGN / OTHER		Feb 12 '26	TYPE | LC 347 | PracHub
★	M	80. Compute minimum number of rooms needed	DESIGN / OTHER	IN APP	Feb 12 '26	TYPE | LC 253 | PracHub
	M	81. Min boards to cover roof holes	DESIGN / OTHER		Feb 12 '26	TALK | LC 1326 | PracHub
	M	82. Validate parent array forms a tree	BFS / DFS / TREE	IN APP	Feb 11 '26	TALK | LC 261 | PracHub
	M	83. Determine whether two nodes are related	BFS / DFS / TREE		Jan 22 '26	TALK | LC 1971 | PracHub
	M	84. Solve matrix groups and recipe inventory	BFS / DFS / TREE		Jan 22 '26	TALK | LC 2115 | PracHub
	M	85. Find top/bottom-k words in list or stream	DESIGN / OTHER		Jan 11 '26	TALK | LC 692 | PracHub
	M	86. Compute distance to nearest taxi in grid	BFS / DFS / TREE	IN APP	Jan 10 '26	TALK | LC 542 | PracHub
★	M	87. Find median of merged RLE arrays	ARRAY / STRING		Jan 6 '26	TYPE | LC 4 | PracHub
	M	88. Find longest increasing contiguous subarray	ARRAY / STRING		Jan 6 '26	TALK | LC 674 | PracHub
★	M	89. Maximize sum without choosing adjacent elem...	DP	IN APP	Jan 6 '26	TYPE | LC 198 | PracHub
	M	90. Simulate room assignments for scheduled meet...	DESIGN / OTHER	IN APP	Jan 6 '26	TALK | LC 2402 | PracHub
★	M	91. Design a logger that returns top-K messages	DESIGN / OTHER		Jan 6 '26	TYPE | LC 359 | PracHub
	M	92. Implement iterator merging lists with filtering	DESIGN / OTHER		Jan 6 '26	TALK | LC 281 | PracHub
	M	93. Reconstruct original array from doubled shuffle	ARRAY / STRING		Jan 4 '26	TALK | LC 2007 | PracHub
	M	94. Design set with O(1) random access	ARRAY / STRING	IN APP	Jan 1 '26	TYPE | LC 380 | PracHub
	M	95. Match people to questions using tags and priori...	BFS / DFS / TREE		Dec 27 '25	TALK | LC 1820 | PracHub
	M	96. Maximize 1D deliveries within distance and min...	ARRAY / STRING		Dec 27 '25	TALK | LC 455 | PracHub
★	M	97. Solve chat, grid paths, and car rentals	DESIGN / OTHER		Dec 2 '25	TYPE | LC 692 | PracHub
★	M	98. Add two big integers from digit lists	ARRAY / STRING	IN APP	Nov 24 '25	TYPE | LC 2 | PracHub
	M	99. Find mode in a trinary search tree	BFS / DFS / TREE	IN APP	Nov 16 '25	TALK | LC 501 | PracHub
★	M	100. Find shared objects across two log files	ARRAY / STRING		Nov 5 '25	TYPE | LC 349 | PracHub
	M	101. Minimize calls to find all bad test pairs	ARRAY / STRING		Nov 5 '25	TALK | PracHub

Google - Contents

165 questions | tap a title to jump to it

★ M 102. Compute servers needed for daily recurring jobs — DESIGN / OTHER — IN APP — Nov 5 '25 — TYPE | LC 253 | PracHub

M 103. Choose optimal guesses for green-only Wordle — DESIGN / OTHER — Oct 14 '25 — TALK | LC 843 | PracHub

★ M 104. Compute shortest paths with blocked nodes — BFS / DFS / TREE — Sep 6 '25 — TYPE | LC 743 | PracHub

M 105. Design server allocation for multi-type nodes — DESIGN / OTHER — Sep 6 '25 — READ | LC 1912 | PracHub

M 106. Design an elevator control system — DESIGN / OTHER — Sep 6 '25 — READ | PracHub

★ M 107. Solve tree, graph, sliding-window problems — BFS / DFS / TREE — Aug 4 '25 — TYPE | LC 103 | PracHub

★ M 108. Validate course catalog dependencies — BFS / DFS / TREE — IN APP — Aug 1 '25 — TYPE | LC 207 | PracHub

M 109. Implement zigzag level-order traversal — BFS / DFS / TREE — IN APP — Aug 1 '25 — TALK | LC 103 | PracHub

M 110. Decide string transform with directional tokens... — ARRAY / STRING — Jul 15 '25 — TALK | LC 777 | PracHub

★ M 111. Solve Banana Speed and Interval Merge — ARRAY / STRING — Jan 27 '25 — TYPE | LC 875 | PracHub

★ M 112. Solve Grid and Counting Problems — BFS / DFS / TREE — Jan 25 '25 — TYPE | LC 200 | PracHub

Easy (4) Go >

E 113. Implement string formatting and request tracki... — ARRAY / STRING — Feb 11 '26 — TALK | LC 246 | PracHub

E 114. Implement Batched Undo/Redo Layer — DESIGN / OTHER — Feb 4 '26 — TALK | LC 1472 | PracHub

E 115. Find right-side view of binary tree — BFS / DFS / TREE — IN APP — Nov 1 '25 — TALK | LC 199 | PracHub

E 116. Find k pairs with smallest sums — DESIGN / OTHER — IN APP — Nov 1 '25 — TALK | LC 373 | PracHub

EXPONENT

38 questions | last 30 days: 0 | last 90 days: 0 Go >

ASKED (ROUGH): 91 TO 180 DAYS AGO (8) Go >

Hard (1) Go >

H 117. Edit distance — DP — IN APP — ~Jul '26 — TYPE | LC 127 | Exponent

Medium (2) Go >

M 118. Given the root of a binary tree, return the lengt... — BFS / DFS / TREE — IN APP — ~Jul '26 — TYPE | LC 543 | Exponent

M 119. Write SQL code to publish the Fibonacci series. — DESIGN / OTHER — ~Jun '26 — TALK | Exponent

Easy (5) Go >

★ E 120. Maximum Profit — ARRAY / STRING — ~Jun '26 — TYPE | LC 121 | Exponent

★ E 121. Climbing Stairs — DP — IN APP — ~Jun '26 — TYPE | LC 70 | Exponent

E 122. Reverse a linked list. — DESIGN / OTHER — IN APP — ~Jun '26 — TYPE | LC 206 | Exponent

E 123. Tree Node. — BFS / DFS / TREE — ~May '26 — READ | Exponent

E 124. Sort a binary array in linear time. — ARRAY / STRING — ~May '26 — TYPE | LC 75 | Exponent

ASKED (ROUGH): OLDER THAN 6 MONTHS (30) Go >

Hard (6) Go >

H 125. Given two strings and two allowed operations,... — ARRAY / STRING — ~Apr '26 — TALK | LC 1153 | Exponent

★ H 126. Find the median of two sorted arrays. — ARRAY / STRING — IN APP — ~Feb '26 — TYPE | LC 4 | Exponent

H 127. Implement a function that processes a stream... — ARRAY / STRING — ~Oct '25 — TALK | LC 352 | Exponent

H 128. Implement a decode and encode function of a... — BFS / DFS / TREE — ~Oct '24 — TALK | LC 428 | Exponent

H 129. Given an integer array nums and an integer k,... — ARRAY / STRING — IN APP — ~Oct '24 — TALK | LC 523 | Exponent

★ H 130. Implement a function to justify a list of words... — ARRAY / STRING — IN APP — ~Oct '24 — TYPE | LC 68 | Exponent

Medium (16) Go >

M 131. Given a train schedule with departure city, arri... — BFS / DFS / TREE — ~Apr '26 — TYPE | LC 743 | Exponent

★ M 132. Generate Parentheses — DP — IN APP — ~Apr '26 — TYPE | LC 22 | Exponent

Google - Contents

165 questions | tap a title to jump to it

★	M	133. Find the minimum window substring.	ARRAY / STRING	IN APP	~Mar '26	TYPE | LC 76 | Exponent
★	M	134. Find the longest palindromic subsequence usi...	DP	IN APP	~Mar '26	TYPE | LC 516 | Exponent
	M	135. Coin Change	DP	IN APP	~Mar '26	TYPE | LC 322 | Exponent
	M	136. Given a matrix with a rat, bread, cat, and obst...	BFS / DFS / TREE		~Feb '26	TALK | LC 1102 | Exponent
	M	137. Given an array of strings, return groups of "bu...	ARRAY / STRING	IN APP	~Feb '26	TALK | LC 249 | Exponent
★	M	138. Given a list with response time for each server...	ARRAY / STRING		~Oct '25	TYPE | LC 875 | Exponent
	M	139. Given positions of N kids and M ice cream sell...	ARRAY / STRING		~Oct '25	TALK | LC 475 | Exponent
★	M	140. Sort a nearly sorted (or K sorted) array.	DESIGN / OTHER		~Oct '25	TYPE | LC 215 | Exponent
	M	141. Determine if a given binary tree is a binary se...	BFS / DFS / TREE	IN APP	~Oct '24	TYPE | LC 98 | Exponent
	M	142. Write functions to serialize and deserialize a li...	ARRAY / STRING	IN APP	~Oct '24	TALK | LC 271 | Exponent
	M	143. Explain how to find a target sum in an array.	DP	IN APP	~Oct '24	TALK | LC 494 | Exponent
	M	144. Count the number of ways to split a string.	ARRAY / STRING		~Oct '23	TALK | LC 1573 | Exponent
	M	145. Given a large n-ary tree where the root node c...	BFS / DFS / TREE	IN APP	~Oct '22	TALK | LC 1376 | Exponent
	M	146. Determine if two sentences are similar.	ARRAY / STRING		~Oct '22	TALK | LC 1813 | Exponent

Easy (8) Go >

	E	147. Is this a valid palindrome?	ARRAY / STRING	IN APP	~Apr '26	TYPE | LC 125 | Exponent
	E	148. Return all unique substrings of a given string.	TRIE		~Apr '26	READ | Exponent
	E	149. Find the Duplicates	ARRAY / STRING		~Mar '26	TALK | LC 350 | Exponent
	E	150. Fibonacci Numbers	DP	IN APP	~Jan '26	TYPE | LC 509 | Exponent
	E	151. Given two trees, determine if the pre-order tra...	BFS / DFS / TREE		~Oct '25	TYPE | LC 100 | Exponent
	E	152. Calculate the height of a binary tree.	BFS / DFS / TREE	IN APP	~Oct '24	TYPE | LC 104 | Exponent
	E	153. Reverse a Sentence	ARRAY / STRING	IN APP	~Oct '24	TALK | LC 186 | Exponent
	E	154. Determine if two words are sorted in lexicogra...	ARRAY / STRING	IN APP	~Oct '23	TALK | LC 953 | Exponent

HACKTHEROUNDS

11 questions Go >

HackTheRounds - Hard (1)

Go >

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns (1)

Go >

	H	155. Count of Smaller Numbers After Self		IN APP		TALK | LC 315 | HackTheRounds

HackTheRounds - Medium (9)

Go >

BFS/DFS Graph and Tree Traversal and Shortest Paths (2)

Go >

	M	156. Lowest Common Ancestor of a Binary Tree III		IN APP		TALK | LC 1650 | HackTheRounds
	M	157. Lowest Common Ancestor		IN APP		TALK | LC 236 | HackTheRounds

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns (3)

Go >

★	M	158. Shortest Subarray with K Distinct Integers				TYPE | LC 992 | HackTheRounds
	M	159. Sum of Two Squares in Two Ways				READ | HackTheRounds
	M	160. Hit Counter		IN APP		TALK | LC 362 | HackTheRounds

Dynamic Programming and State-Space Optimization (2)

Go >

	M	161. Trip Expense Settlement		IN APP		TALK | LC 465 | HackTheRounds
	M	162. Reverse Coin Change				TALK | LC 518 | HackTheRounds

Other: Design, Heaps, Intervals and Misc (2)

Go >

★	M	163. Meeting Rooms III Variant				TYPE | LC 253 | HackTheRounds

Google - Contents

165 questions | tap a title to jump to it

M 164. Playlist Shuffle No Adjacent Artists **TALK | LC 767 | HackTheRounds**

HackTheRounds - Easy (1) **Go >**

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns (1) **Go >**

E 165. Parity Alternating Subarray Query **TALK | LC 303 | HackTheRounds**

SIDE NOTE: marked problems that are not in this book

★ The top 75 Medium and Hard problems and the top 10 Easy problems by Google frequency are marked in this book. These 39 are marked too but are not questions here. Do them from your app. Rank is the position in the Medium and Hard list, or E1 to E10 for Easy.

Rank	LC	Problem	Lvl	Freq
3	3	Longest Substring Without Repeating	M	73/69.3
5	42	Trapping Rain Water	H	73.6/55.1
7	128	Longest Consecutive Sequence	M	70.3/58.3
8	15	3Sum	M	72.6/58.3
9	7	Reverse Integer	M	66.3/51.4
15	11	Container With Most Water	M	68.3/41.1
18	410	Split Array Largest Sum	H	57.7/46.9
21	17	Letter Combinations of a Phone Number	M	57.8/51.4
25	239	Sliding Window Maximum	H	54.9/46.9
26	31	Next Permutation	M	61/41.1
30	6	Zigzag Conversion	M	53.5/51.4
31	34	Find First and Last Position	M	53/46.9
32	54	Spiral Matrix	M	59.3/33
34	1944	Number of Visible People in a Queue	H	53.6/41.1
37	33	Search in Rotated Sorted Array	M	57.2/33
38	84	Largest Rectangle in Histogram	H	56.8/33
39	167	Two Sum II	M	49.8/46.9
42	155	Min Stack	M	50.8/41.1
43	19	Remove Nth Node From End of List	M	50.2/41.1
44	424	Longest Repeating Character Replacement	M	53.6/33
47	739	Daily Temperatures	M	47.8/41.1
48	78	Subsets	M	51.7/33
49	39	Combination Sum	M	47.6/41.1
52	16	3Sum Closest	M	50.6/33
53	131	Palindrome Partitioning	M	46/41.1
54	209	Minimum Size Subarray Sum	M	45.2/41.1
57	402	Remove K Digits	M	44.1/0
62	151	Reverse Words in a String	M	46/33
63	312	Burst Balloons	H	41.8/0
67	51	N-Queens	H	58.6/0
75	210	Course Schedule II	M	36.5/33
E1	20	Valid Parentheses	E	67.3/70.9
E3	14	Longest Common Prefix	E	73.6/55.1
E4	88	Merge Sorted Array	E	69.7/55.1
E5	26	Remove Duplicates from Sorted Array	E	65.7/55.1
E7	28	Find the Index of the First Occurrence	E	56.2/61
E8	485	Max Consecutive Ones	E	56/58.3
E9	169	Majority Element	E	66.5/33
E10	242	Valid Anagram	E	57.3/51.4

Freq is LeetCode's frequency for Google: all time / last 30 days.

1POINT3ACRES

31 questions | Hard 8, Medium 23, Easy 0 | asked in the last 30 days: 0, last 90 days: 0 (grouped by recency, newest first) | topics: BFS/DFS and trees first

ASKED: 91 TO 180 DAYS AGO (16)

Hard (4)

HARD | 1Point3Acres | onsite-coding | 1 of 165

Huffman Tree Construction

ASKED 2026-06-01 | 131 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | **NO LEETCODE FREQUENCY** | **PRIORITY 185/224**

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Frequency: Low | Last asked: 2026-06-01 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/huffman-tree-construction

QUESTION

EXAMPLES

```
{"a": 5, "b": 9, "c": 12, "d": 13, "e": 16, "f": 45}
    -> standard Huffman tree with f near the root.
```

APPROACH

Write the heap-based Huffman build from memory in under 15 min.
Drill the encode + decode helpers (DFS to build the code map; tree walk to decode).
Be ready to compare against arithmetic coding (better compression, costlier).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether to return the tree, a code table, or the encoded message, how ties are broken, and what to do with one symbol.

BRUTE FORCE TO SAY OUT LOUD

Repeatedly scan for the two smallest weights. O(n^2).

OPTIMAL IDEA

Min-heap of nodes keyed by (weight, counter). Pop two, merge under a new node with the summed weight, push back, until one node remains. Walk the tree assigning '0' to left and '1' to right. O(n log n). Decode by walking the tree bit by bit. The counter prevents comparing nodes on ties.

DRY-RUN THESE CASES

The CLRS example (total cost 224, 'f' gets a one-bit code). One symbol (code '0'). Equal weights.

LIKELY FOLLOW-UPS

INTERVIEW-DAY PLAN

Canonical codes, decoding, or the two-queue O(n) method on sorted input.

PITFALLS

Comparing tree nodes on equal weights. Forgetting the single symbol case.

HOW TO THINK ABOUT IT

The two rarest symbols belong at the deepest level as siblings, so merge them first, treat the merged node as a new symbol with the combined weight, and repeat. 'Take the two smallest' is the job of a min-heap; tie-breaking with a counter keeps the heap from comparing tree nodes.

Basis: Classic greedy algorithm (CLRS 16.3); related to LeetCode 1167, Minimum Cost to Connect Sticks.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(weights):
    items = list(weights)
    cost = 0
    while len(items) > 1:
        items.sort()
        a, b = items[0], items[1]  # two smallest
        items = items[2:] + [a + b]
        cost += a + b
    return cost
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Finding the two smallest by scanning costs O(n) per merge and n - 1 merges, O(n^2). A min-heap does each merge in O(log n).

OPTIMAL SOLUTION · Min-heap merge of the two lightest nodes

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why is the greedy choice optimal?

Exchange argument: in some optimal tree the two least frequent symbols are siblings at the deepest level (swapping a shallower, more frequent symbol with a deeper, less frequent one never increases cost). Merging them into one symbol reduces the problem to n - 1 symbols with the same optimal-substructure property, so induction closes it.

FOLLOW-UP 2 How do you make the code canonical, and why would you?

Keep only each symbol's code length from the tree, sort symbols by (length, symbol), and assign consecutive binary codes. A decoder then needs just the lengths rather than the whole tree, which is how DEFLATE stores its tables.

FOLLOW-UP 3 Time complexity if symbols arrive already sorted?

Two-queue method: one queue holds the sorted leaves, the other the merged nodes (which are produced in nondecreasing order). Always pop the smaller front of the two queues. That is O(n) after sorting.

FOLLOW-UP 4 Make the codes canonical so only the code lengths need to be stored.

Sort symbols by (code length, symbol) and assign consecutive binary numbers, shifting left when the length grows. A decoder rebuilds the codes from the lengths alone (this is how DEFLATE stores its tables).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


def huffman_lengths(freq):
    # code length of every symbol (depth in the tree)
    if not freq:
        return {}
    if len(freq) == 1:
        # a lone symbol still needs one bit
        return {next(iter(freq)): 1}
    # heap entries: (weight, tie-break, symbols below)
    heap = [(w, i, [s]) for i, (s, w) in
            enumerate(sorted(freq.items()))]
    heapq.heapify(heap)
    depth = {s: 0 for s in freq}
    tie = len(heap)
    while len(heap) > 1:
        # merge the two lightest; everything below goes
        # deeper
        w1, _, a = heapq.heappop(heap)
        w2, _, b = heapq.heappop(heap)
        for s in a + b:
            depth[s] += 1
        heapq.heappush(heap, (w1 + w2, tie, a + b))
        tie += 1
    return depth


# FOLLOW-UP 2, 4: How do you make the code canonical, and
# why would you?
def canonical_codes(lengths):
    # assign consecutive binary numbers by (length,
    # symbol)
    code, prev, out = 0, 0, {}
    for sym, length in sorted(lengths.items(),
                              key=lambda x: (x[1], x[0])):
        # moving to a longer length shifts the code left
        code <<= length - prev
        out[sym] = format(code, f"0{length}b")
        code += 1
        prev = length
    return out


# BASE QUESTION (optimal): Min-heap merge of the two
# lightest nodes
def huffman_codes(freq):
    return canonical_codes(huffman_lengths(freq))


# FOLLOW-UP 3: Time complexity if symbols arrive already
# sorted?
def lengths_two_queues(sorted_items):
    # input already sorted by weight: O(n) with two queues
    from collections import deque
    leaves = deque((w, [s]) for s, w in sorted_items)
    merged = deque()
    depth = {s: 0 for s, _ in sorted_items}

    def pop_smaller():
        # the smaller front of the two queues
        if not merged or (leaves and
                          leaves[0][0] <= merged[0][0]):
            return leaves.popleft()
        return merged.popleft()

    while len(leaves) + len(merged) > 1:
        w1, a = pop_smaller()
        w2, b = pop_smaller()
        for s in a + b:
            depth[s] += 1
        merged.append((w1 + w2, a + b))
    return depth


def decode(bits, codes):
    # read bits until they match a code (prefix-free)
    back = {v: k for k, v in codes.items()}
    out, cur = [], ""
    for b in bits:
        cur += b
        if cur in back:
            out.append(back[cur])
            cur = ""
    return "".join(out)


if __name__ == "__main__":
    freq = {"a": 5, "b": 9, "c": 12,
            "d": 13, "e": 16, "f": 45}
    lengths = huffman_lengths(freq)
    # the most frequent symbol is next to the root
    assert lengths["f"] == 1
    # total cost of the optimal tree
    assert sum(freq[s] * lengths[s] for s in freq) == 224
    codes = huffman_codes(freq)
    # prefix-free: no code starts another code
    for x in codes.values():
        for y in codes.values():
            assert x == y or not y.startswith(x)
    text = "abfadc"
    bits = "".join(codes[ch] for ch in text)
    assert decode(bits, codes) == text
    items = sorted(freq.items(), key=lambda x: x[1])
    two = lengths_two_queues(items)
    assert sum(freq[s] * two[s] for s in freq) == 224
    assert huffman_codes({"x": 3}) == {"x": "0"}
    assert huffman_codes({}) == {}
```

NOTES FROM CANDIDATES

L6 onsite — interviewer expects clean code with a documented tree node, plus a discussion of encoding / decoding correctness.
Common follow-up: how to produce the code table (DFS from root, accumulating bits).
Trade-off discussion: Huffman is optimal for known per-symbol probability but not for adaptive / streaming inputs.

PREPARATION

Write the heap-based Huffman build from memory in under 15 min.
Drill the encode + decode helpers (DFS to build the code map; tree walk to decode).
Be ready to compare against arithmetic coding (better compression, costlier).

HARD | 1Point3Acres | onsite-coding | 2 of 165

Matrix Flower Placement with House Adjacency

ASKED 2026-05-31 | 132 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 186/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: written and tested here for this exact question

Frequency: Low | Last asked: 2026-05-31 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/matrix-flower-placement-with-house-adjacency

QUESTION

EXAMPLES

```
H 0 0 0
H 0 0 0
0 0 0 H
0 0 0 0
```

The task is to fill some 0 cells with F while satisfying both the row/column constraint and each house's adjacency requirement.

APPROACH

Practice N-Queens with row/column sets and a recursive placement order.
Drill grid-neighbor helpers and constraint pruning before writing the full DFS.
Prepare the boolean version first, then generalize to collect all solutions.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether each row and column holds at most one or exactly one flower, whether a house needs at least one or exactly one adjacent flower, whether adjacency is four-way, and whether to return one solution, a boolean, or all.

BRUTE FORCE TO SAY OUT LOUD

Try every subset of empty cells. Exponential.

OPTIMAL IDEA

Row-by-row backtracking like N-Queens: place at most one flower per row, track used columns, and check each house as soon as the row below it is decided (its neighbors are in rows h - 1 to h + 1). Prune at the first failed house. The boolean version stops at the first solution; the all-solutions version continues.

DRY-RUN THESE CASES

No houses, a house with no empty neighbor (impossible), two houses sharing one neighbor, a 1 x 1 grid.

LIKELY FOLLOW-UPS

Exactly-one rule, all solutions, or a faster exact-cover search.

PITFALLS

Checking a house before the next row is decided. Not restoring the cell on backtrack.

HOW TO THINK ABOUT IT

At most one flower per row and column is the N-Queens pattern: decide row by row which column (if any) gets the flower and remember the used columns. The extra rule about houses is local, so check a house as soon as the last row that can affect it is decided, and prune the branch if it fails.

Basis: N-Queens style backtracking (LeetCode 51/52) with extra local constraints. Assumptions stated explicitly: every house must have at least one flower in a 4-neighbour cell; rows and columns hold at most one flower (or exactly one if requested).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    empty = cells_with(grid, 0)
    count = 0
    for k in range(len(empty) + 1):
        for flowers in combinations(empty, k):
            if not one_per_row_and_col(flowers):
                continue
            if houses_covered(grid, flowers):
                count += 1
    return count
```

TIME	SPACE
O(2^cells)	O(cells)

WHY IT IS SLOW

2^cells subsets: exponential. Backtracking row by row with a used-columns set and early house checks prunes almost all of them (still exponential in the worst case).

OPTIMAL SOLUTION · Row-by-row backtracking with used-column set and delayed house checks

TIME	SPACE
exponential worst case, h... exponential worst case, heavily pruned	**O(rows + cols)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What changes between 'at most one' and 'exactly one' flower per row and column?

With 'exactly one' the number of flowers is forced (rows must equal columns) and a row cannot be skipped, which prunes much harder, like N-Queens without the diagonal rule. With 'at most one' you also branch on skipping a row. State which reading you are using before writing code.

FOLLOW-UP 2 How would you speed up the search?

Prune earlier by checking each house as soon as its last neighbour row is decided (done above), order houses by how few candidate cells they have (most-constrained first), and keep bitmasks for used columns. For large grids this becomes a constraint satisfaction or exact-cover problem, so a SAT solver or DLX is the next step. **Cost:** the worst case stays exponential; most-constrained-first ordering and early house checks cut the explored states by orders of magnitude on typical grids.

FOLLOW-UP 3 Exactly one flower per row and column.

Add a flag that forbids skipping a row and requires as many columns as rows (otherwise no solution). The pruning is stronger, since every row must find a column.

FOLLOW-UP 4 Count the solutions instead of listing them.

Keep the same recursion but add one to a counter at the leaf instead of copying the grid; with a bitmask of used columns and memoisation on (row, mask, pending-house state) it can become a DP.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
STEPS = ((1, 0), (-1, 0), (0, 1), (0, -1))


# BASE QUESTION (optimal): Row-by-row backtracking with
# used-column set and delayed ...
def place_flowers(grid, exactly_one=False,
                  find_all=False):
    # 'H' house, '0' empty. At most one F per row and
    # column; every house needs an F on a side.
    R, C = len(grid), len(grid[0])
    cells = [list(row) for row in grid]
    houses = [(r, c) for r in range(R) for c in range(C)
              if cells[r][c] == "H"]
    found = []

    def house_ok(r, c):
        # is some neighbour of this house a flower?
        for dr, dc in STEPS:
            a, b = r + dr, c + dc
            if 0 <= a < R and 0 <= b < C \
                    and cells[a][b] == "F":
                return True
        return False

    def row_houses_ok(r):
        return all(house_ok(hr, hc)
                   for hr, hc in houses if hr == r)

    def solve(r, used):
        # FOLLOW-UP 4: find_all=True lists every solution
        if found and not find_all:
            return
        # rows up to r-1 are decided, so row r-2 is final
        if r >= 2 and not row_houses_ok(r - 2):
            return
        if r == R:
            # FOLLOW-UP 3: exactly_one=True: a flower in
            # every column
            full = len(used) == C
            if row_houses_ok(R - 1) and (full or
                                         not exactly_one):
                found.append(["".join(x) for x in cells])
            return
        # try a flower in every free column of this row
        for c in range(C):
            if c not in used and cells[r][c] == "0":
                cells[r][c] = "F"
                solve(r + 1, used | {c})
                cells[r][c] = "0"
        # or leave the row empty (not allowed for exactly
        # one)
        if not exactly_one:
            solve(r + 1, used)

    solve(0, frozenset())
    if find_all:
        return found
    return found[0] if found else None


# FOLLOW-UP 4: Count the solutions instead of listing
# them.
def count_solutions(grid, exactly_one=False):
    return len(place_flowers(grid, exactly_one, True))


if __name__ == "__main__":
    grid = ["H00", "0H0", "00H"]
    sol = place_flowers(grid)
    assert sol is not None
    # every house has a flower beside it
    for r in range(3):
        for c in range(3):
            if grid[r][c] == "H":
                near = []
                for a, b in STEPS:
                    x, y = r + a, c + b
                    if 0 <= x < 3 and 0 <= y < 3:
                        near.append(sol[x][y])
                assert "F" in near
    # one flower per row and column
    assert all(row.count("F") <= 1 for row in sol)
    for c in range(3):
```

```
    assert [row[c] for row in sol].count("F") <= 1
# a lone house in a 1 x 1 grid cannot be served
assert place_flowers(["H"]) is None
assert count_solutions(["00", "00"], True) == 2
assert place_flowers(["000", "000"], True) is None
```

NOTES FROM CANDIDATES

This is an N-Queens-style DFS / backtracking problem with extra local constraints around houses.
Track occupied rows and columns, then validate the four-neighbor requirement either incrementally or at the leaf.
The two variants differ on at most one vs exactly one flower per row/column; state the assumption before coding.

PREPARATION

Practice N-Queens with row/column sets and a recursive placement order.
Drill grid-neighbor helpers and constraint pruning before writing the full DFS.
Prepare the boolean version first, then generalize to collect all solutions.

HARD | 1Point3Acres | phone-screen, onsite-coding | 3 of 165

Count Perfect Wake Numbers up to N

ASKED 2026-05-07 | 156 DAYS AGO | LAST 6 MONTHS

STUDY: TALK **NO LEETCODE FREQUENCY** **PRIORITY 183/224**

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Frequency: Single report | Last asked: 2026-05-07 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/perfect-wake-number-count

QUESTION

EXAMPLES

```
196   -> perfect (digits 1,9,6 all distinct, no 0, 9
    is not a valley)
23    -> perfect
12463 -> perfect (1<2, 2<4, 4>6? No, 4<6, 6>3 — 6 is
    not a valley because its right neighbor 3 is
    smaller)
1546  -> not perfect (4 is adjacent to 5 and 6, both
    strictly larger)
320   -> not perfect (contains 0)
34321 -> not perfect (digit 3 repeats)
```

APPROACH

Drill digit DP templates: classic digit-DP problems — "count digit one", "non-negative integers without consecutive ones", "numbers at most N given digit set", "numbers with repeated digits" — cover "count integers <= n satisfying digit predicate." Practice bitmask-over-digits + tight-flag state machines. Memorize the standard skeleton: recurse over positions, accept any digit <= n's digit when tight, else any digit 1..9.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the exact definition: no zero digit, all digits distinct, no interior digit smaller than both neighbors. Ask for the range of N and whether to count 1..N inclusive.

BRUTE FORCE TO SAY OUT LOUD

Test every number from 1 to N with a digit check. O(N * d), fine for small N.

OPTIMAL IDEA

Digit DP over positions with state (used-digit mask, last digit, whether the digits have started falling, tight flag). Numbers with fewer digits than N are counted without a tight constraint, and zero is never allowed, so there are no leading-zero cases. Digits must rise then fall, which is exactly the no-valley rule. There is also a closed form of C(9, k) * 2^(k - 1) for k-digit numbers.

DRY-RUN THESE CASES

196, 23, 12463 perfect; 1546, 320, 34321 not perfect. N = 9, N = 10, N a power of ten.

LIKELY FOLLOW-UPS

A range [A, B] (inclusion-exclusion), or different digit rules.

PITFALLS

Forgetting the zero rule. Letting a digit repeat across the tight and free branches.

HOW TO THINK ABOUT IT

Distinct digits with no zero and no valley means the digits go up and then down (they can only change direction once). That structure is both a closed form for each length and a state for a digit DP: position, which digits are used, the last digit, and whether the digits have started falling. The tight flag handles the bound N.

Basis: Digit DP, like LeetCode 1012 (Numbers With Repeated Digits) and 233. Definition from the report: no zero digit, all digits distinct, and no interior digit is a valley (strictly smaller than both neighbours).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def is_perfect(x):
    d = list(map(int, str(x)))
    if 0 in d or len(set(d)) < len(d):
        return False
    for i in range(1, len(d) - 1):
        if d[i] < d[i - 1] and d[i] < d[i + 1]:
            return False  # a valley
    return True
count = 0
for x in range(1, N + 1):
    count += is_perfect(x)
```

TIME	SPACE
O(N * d)	O(1)

WHY IT IS SLOW

O(N * digits): hopeless for N around 10^9. A digit DP counts by position, used digits, last digit and direction in time independent of N's size.

OPTIMAL SOLUTION · Part 1: test a single number

TIME	SPACE
O(d)	O(d)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Part 2: digit DP with tight flag, used-digit mask, last digit and direction

TIME	SPACE
O(d * 2^9 * 9 * 9)	O(2^9 * 9)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why does the DP only need a 'falling' flag instead of the full history?

A valley needs a digit that is lower than the digit before it and then higher than the one after it. Once any digit has decreased, a later increase would create exactly that valley, so the only information to carry is whether we have already gone down. The used mask and last digit cover the other two rules.

FOLLOW-UP 2 How do you count the numbers in a range [A, B]?

Use inclusion-exclusion: count(B) - count(A - 1). The DP is a function of the upper bound only, and it is cheap enough (a few thousand states) to call twice.

FOLLOW-UP 3 What is the closed form without a DP?

Since digits are distinct and unimodal, pick which k digits (from 1..9) appear and the peak is the largest; each of the other k - 1 digits goes either left or right of the peak: 2^(k-1) arrangements per set. So the count of perfect numbers with k digits is C(9, k) * 2^(k-1). Only the 'at most N' bound needs the DP.

FOLLOW-UP 4 Is there a closed form for k-digit numbers?

Pick the k distinct digits from 1..9 (C(9, k) ways); the largest must be the peak, and each of the other k - 1 digits goes either left or right of it in sorted order, so 2^(k-1) arrangements: C(9, k) * 2^(k-1). Only the bound N needs the DP.

FOLLOW-UP 5 Count perfect numbers in a range [A, B].

Compute count(B) - count(A - 1); the DP depends on the upper bound only.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from functools import lru_cache
from math import comb


# BASE QUESTION (optimal): test a single number
def is_perfect(n):
    # distinct digits, no zero, and no valley: no digit is
    # smaller than both of its neighbours
    d = list(map(int, str(n)))
    if 0 in d or len(set(d)) != len(d):
        return False
    return all(not (d[i - 1] > d[i] < d[i + 1])
               for i in range(1, len(d) - 1))


# FOLLOW-UP 4: Is there a closed form for k-digit numbers?
def with_k_digits(k):
    # choose the k digits; the largest is the peak and
    # each
    # other digit goes left or right of it
    return comb(9, k) * 2 ** (k - 1) if k >= 1 else 0


# FOLLOW-UP 2: How do you count the numbers in a range [A,
# B]?
# PART 2: count the perfect numbers up to N
def count_up_to(n):
    if n < 1:
        return 0
    digits = list(map(int, str(n)))
    size = len(digits)
    # all shorter numbers: closed form
    total = sum(with_k_digits(k) for k in range(1, size))

    @lru_cache(None)
    def go(pos, mask, last, falling, tight):
        # count completions of a number of full length
        if pos == size:
            return 1
        out = 0
        limit = digits[pos] if tight else 9
        for d in range(1, limit + 1):
            if mask >> d & 1:
                continue
            fall = falling

            if pos:
                if d > last and falling:
                    # going up after going down: a valley
                    continue
                if d < last:
```

```
                    fall = True
                out += go(pos + 1, mask | 1 << d, d, fall,
                          tight and d == digits[pos])
        return out

    # numbers with the same length as n, not above n
    return total + go(0, 0, 0, False, True)


# FOLLOW-UP 5: Count perfect numbers in a range [A, B].
def count_between(a, b):
    # inclusion-exclusion over the upper bounds
    return count_up_to(b) - count_up_to(a - 1)


if __name__ == "__main__":
    for ok in (196, 23, 12463):
        assert is_perfect(ok)
    for bad in (1546, 320, 34321):
        assert not is_perfect(bad)
    # the DP agrees with checking every number
    for n in (0, 9, 10, 99, 100, 999, 5000, 20000):
        every = range(1, n + 1)
        brute = sum(is_perfect(i) for i in every)
        assert count_up_to(n) == brute
    assert count_between(10, 99) == (
        count_up_to(99) - count_up_to(9))
    # 1-digit and 2-digit counts from the closed form
    assert with_k_digits(1) == 9
    assert with_k_digits(2) == 72
```

NOTES FROM CANDIDATES

Part 1 is a linear scan; Part 2 is digit DP with state (position, mask of used digits, last digit, is_tight against n). Track whether the previous step went up or down to detect a future valley.
Multiple candidates report not finishing Part 2 in the 45-minute window. The interviewer is generally patient and dispenses hints ("think DP" / "think digit DP") when you stall.
Watch out: the "no valley" rule is about interior digits, so the first and last digit are never themselves the valley; they can still create one for their neighbor.
The full prompt is short and recent — expect the follow-up to vary (e.g. count exactly-K-digit Perfect Wake Numbers).

PREPARATION

Drill digit DP templates: classic digit-DP problems — "count digit one", "non-negative integers without consecutive ones", "numbers at most N given digit set", "numbers with repeated digits" — cover "count integers <= n satisfying digit predicate."
Practice bitmask-over-digits + tight-flag state machines.
Memorize the standard skeleton: recurse over positions, accept any digit <= n's digit when tight, else any digit 1..9.

HARD | 1Point3Acres | onsite-coding | 4 of 165

Necklace Cut into Two Halves with Equal D/R Counts

ASKED 2026-05-03 | 160 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 184/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-05-03 | Roles: SWE, MLE

Original: https://www.1point3acres.com/interview/problems/company/google/necklace-cut-equal-counts

QUESTION

EXAMPLES

```
s = "DRDR"    -> cut between index 1 and 2: "DR" +
    "DR".
s = "DDRR"    -> 1-cut not balanced ("DD" vs "RR");
    rotate, two cuts at offsets 1 and 3:
              pieces "DR" and "DR".
```

APPROACH

Practice the running-balance technique on +1/-1 arrays (the contiguous-array and subarray-sums-divisible-by-k families). Drill sliding-window-on-circular-array unrolling (duplicate the string s+s and use a window of length n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the string is circular, whether the two pieces must be contiguous arcs, whether equal counts of each letter or equal strings are needed, and whether one cut or two are allowed.

BRUTE FORCE TO SAY OUT LOUD

Try every pair of cut positions and count letters. O(n^3) or O(n^2) with prefix counts.

OPTIMAL IDEA

Each arc must hold half of the D's and half of the R's, so the total counts of both must be even and each arc has length n / 2. Slide a window of length n / 2 around s + s tracking its D count; the window starting at i and the one starting at i + n / 2 are complementary, and counts change by at most one per step, so some start hits exactly half. O(n).

DRY-RUN THESE CASES

DRDR, DDRR (two cuts needed), an odd D count (impossible), a string of one letter.

LIKELY FOLLOW-UPS

Equal strings instead of equal counts, or three pieces.

PITFALLS

Assuming a linear cut is always enough. Ignoring parity.

HOW TO THINK ABOUT IT

Two arcs of a circle with the same letter counts must each have exactly half the D's and half the R's, so the total counts must be even and each arc has length n / 2. Slide a window of length n / 2 around the circle: the window and its complement have D counts adding to the total, and the count changes by at most one per step, so it must hit half somewhere.

Basis: Circular sliding window / prefix balance (cf. LeetCode 525, Contiguous Array). Assumption: cut the circular necklace at two points into two arcs, each with the same number of D and R.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s):
    n = len(s)
    for i, j in combinations(range(n), 2):
        arc1 = s[i:j]
        arc2 = s[j:] + s[:i]
        d1, d2 = arc1.count("D"), arc2.count("D")
        r1, r2 = arc1.count("R"), arc2.count("R")
        if d1 == d2 and r1 == r2:
            return True
    return False
```

TIME	SPACE
O(n^3)	O(n)

WHY IT IS SLOW

O(n^2) pairs and each recount costs O(n), so O(n^3). Because the arcs must both have length n / 2, one circular window of that length slid around the string finds it in O(n).

OPTIMAL SOLUTION · Fixed-length circular window with the discrete intermediate value argument

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 When is a single cut enough?

A single linear cut works when some prefix has exactly half the D's and half the R's, i.e. a prefix of length n/2 whose D count is d_total / 2. Otherwise rotate: the circular window above finds the start, which is equivalent to two cuts on the circle.

FOLLOW-UP 2 What if the two pieces must be equal strings, not just equal counts?

That is a different question: the necklace must be a square rotation, i.e. some rotation of s is t + t. Check whether s appears inside (s + s)[1:-1] at index n/2, or compare s[i:i + n/2] with the complementary arc using a rolling hash or KMP over s + s. It is a string matching problem, not a counting one.

FOLLOW-UP 3 The two pieces must be equal strings, not just equal counts.

Then the necklace must be a square in some rotation: some rotation of s equals t + t. Test with s in (s + s)[1:-1] restricted to an even-length split, or compare s[i:i + n/2] with s[i + n/2:i + n] using a rolling hash or KMP.

FOLLOW-UP 4 The two pieces must be equal strings, not just have equal counts.

A rotation of the necklace must be of the form t + t. Try every rotation and compare its two halves (O(n^2), or O(n) by searching s in (s + s)[1:-1] and checking the match at an offset of n / 2).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Fixed-length circular window
# with the discrete intermediate ...
def necklace_two_cuts(s):
    n = len(s)
    d_total, r_total = s.count("D"), s.count("R")
    # each piece needs half of both letters
    if n % 2 or d_total % 2 or r_total % 2:
        return None
    half, target = n // 2, d_total // 2
    doubled = s + s
    # slide a window of length n/2 around the circle
    window = doubled[:half].count("D")
    for i in range(n):
        if window == target:
            # cuts at i and i + n/2 give two good halves
            first = doubled[i:i + half]
            second = doubled[i + half:i + n]
            return i, (i + half) % n, first, second
        # move the window one step: add the new, drop the
        # old
        window += (doubled[i + half] == "D")
        window -= (doubled[i] == "D")
    return None


# SINGLE CUT case
def single_cut(s):
    # one cut on the line: a prefix with half of
    # everything
    half = len(s) // 2
    if len(s) % 2:
        return None
    d_prefix = s[:half].count("D")
    return half if d_prefix * 2 == s.count("D") else None


# FOLLOW-UP 2, 3, 4: What if the two pieces must be equal
# strings, not just equal counts?
def equal_string_halves(s):
    # follow-up: the two pieces must be the same string
    n = len(s)
    if n % 2:
        return None
    half, doubled = n // 2, s + s
    for i in range(n):
        if doubled[i:i + half] == doubled[i + half:i + n]:
            return i, (i + half) % n
```

```
    return None


if __name__ == "__main__":
    # DRDR: one cut between the halves works
    assert single_cut("DRDR") == 2
    cuts = necklace_two_cuts("DRDR")
    assert cuts is not None and cuts[2].count("D") == 1
    # DDRR needs two cuts on the circle: DR + DR
    assert single_cut("DDRR") is None
    i, j, a, b = necklace_two_cuts("DDRR")
    assert sorted(a) == sorted(b) == ["D", "R"]
    # odd totals have no answer
    assert necklace_two_cuts("DDR") is None
    assert necklace_two_cuts("DRDRD" + "R") is None
    # equal strings: DRDR is DR + DR, DDRR is not
    assert equal_string_halves("DRDR") is not None
    assert equal_string_halves("DDRR") is None
```

NOTES FROM CANDIDATES

Why 2 cuts always suffice: think of a running balance cnt(D) - cnt(R); over the full string it returns to 0. Any prefix splits the necklace into two arcs whose imbalances sum to 0; if the imbalance at some prefix is already 0, one cut suffices, otherwise a sliding window of length n/2 proves a 2-cut works.
Sliding-window approach: fix one cut at index i, look for j such that the window [i, j) has half the Ds and half the Rs. As i advances, j moves monotonically.
Don't get distracted by the necklace framing; once unwrapped onto a line of length 2n and constrained to half-length windows, the problem is standard.
Verbalize the 2-cut bound out loud before coding — interviewers ask why.

PREPARATION

Practice the running-balance technique on +1/-1 arrays (the contiguous-array and subarray-sums-divisible-by-k families).
Drill sliding-window-on-circular-array unrolling (duplicate the string s+s and use a window of length n).

Medium (12)

MEDIUM | 1Point3Acres | phone-screen | 5 of 165

Longest Consecutive Path in Binary Tree

ASKED 2026-07-02 | 100 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 16.5 | 30 DAYS 0 | PRIORITY 156/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #549 Binary Tree Longest Consecutive Sequence II

ABOUT THIS QUESTION

LeetCode match: LC 549 Binary Tree Longest Consecutive Sequence II (related)

Frequency: Single report | Last asked: 2026-07-02 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/binary-tree-longest-consecutive-path

QUESTION

Given a binary tree, return the length of the longest parent-to-child path whose values increase consecutively by 1. Follow-up: allow the path to extend in any direction through the tree, not only from parent to child.SWEtreedfsrecursionmediumFrequencySingle reportLast asked2026-07-02Stagephone-screen

APPROACH

Write the parent-to-child traversal in under 10 minutes with a global best.
Practice the bidirectional tree follow-up where each node returns two lengths upward.
Dry-run single-node, duplicate-value, and split-branch cases before discussing complexity.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether length counts nodes or edges, whether the path goes only parent to child (base) or can bend through a node (follow-up), and whether the sequence must increase by exactly one.

BRUTE FORCE TO SAY OUT LOUD

From every node walk down both children recording the longest run. O(n^2) on a skewed tree.

OPTIMAL IDEA

Base: DFS passing the current run length; it grows by one when the child is exactly the parent plus one, otherwise it resets to 1; keep the global best. O(n). Follow-up: each node returns the longest increasing and longest decreasing chain going down from it; the best path through a node is inc + dec - 1.

DRY-RUN THESE CASES

A single node, an empty tree, duplicate values, a split branch, a descending chain.

LIKELY FOLLOW-UPS

The any-direction version (above), and an iterative version for very deep trees.

PITFALLS

Counting edges when the interviewer expects nodes. Resetting the run to 0 instead of 1.

HOW TO THINK ABOUT IT

Each node needs to know the longest run that ends at its parent, so pass the current length down and reset it to 1 when the value is not parent + 1. For the bending version each node must report two lengths upward (increasing and decreasing chains going down), and the best path through a node combines one of each.

Basis: LeetCode 298 (parent-to-child) and LeetCode 549 (any direction), Binary Tree Longest Consecutive Sequence I and II.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def walk(node):
    best = 1
    for child in (node.left, node.right):
        if child and child.val == node.val + 1:
            best = max(best, 1 + walk(child))
    return best
answer = 0
for node in all_nodes(root):
    answer = max(answer, walk(node))
```

TIME	SPACE
O(n * h)	O(h)

WHY IT IS SLOW

A node deep in a chain is walked again from every ancestor, O(n * h). Passing the current run length down in one traversal makes it O(n).

OPTIMAL SOLUTION · Top-down DFS carrying the current run

TIME	SPACE
O(n)	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What does the any-direction version return for a single node, or for duplicate values?

A single node is a path of length 1 (0 edges), and an empty tree is 0. Equal values never extend a chain because the step must be exactly +1 or -1, so duplicates reset both counters to 1 at that node.

FOLLOW-UP 2 Can you avoid recursion?

Yes: do an iterative post-order or a BFS that stores (node, run) pairs for the top-down version. The bending version needs child results before the parent, so use an explicit stack with a post-order visit or process nodes in reverse BFS order using a dict from node to (inc, dec). It matters because a chain-shaped tree makes the recursive depth n.

FOLLOW-UP 3 Return the path itself, not only its length.

Carry the current run as a list (or its start node and length) in the traversal and copy it into the best answer when it becomes longer.

FOLLOW-UP 4 The path may go in any direction (LeetCode 549).

Return the pair (longest increasing chain down, longest decreasing chain down) from each node, and update the global best with inc + dec - 1 at the node. Verified against exhaustive path enumeration for small trees.

FOLLOW-UP 5 The values must increase by 1 or decrease by 1 along the path but not mix.

That is exactly the any-direction version: the increasing and decreasing parts meet at the bend; a path cannot zig-zag between increasing and decreasing steps.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


# BASE QUESTION (optimal): Top-down DFS carrying the
# current run
def longest_consecutive(root, want_path=False):
    # parent -> child path whose values go up by exactly 1
    best, best_path = 0, []
    stack = [(root, None, [])] if root else []
    while stack:
        node, parent, run = stack.pop()
        # extend the run or start a new one at this node
        if parent is not None and node.val == parent + 1:
            run = run + [node.val]
        else:
            run = [node.val]
        if len(run) > best:
            best, best_path = len(run), run
        for child in (node.left, node.right):
            if child is not None:
                stack.append((child, node.val, run))
    # FOLLOW-UP 3: want_path=True returns the path itself
    return best_path if want_path else best


# FOLLOW-UP 4: The path may go in any direction (LeetCode
# 549).
def longest_any_direction(root):
    # LeetCode 549: the path may bend at one node
    if root is None:
        return 0
    order, stack = [], [root]
    while stack:
        node = stack.pop()
        order.append(node)
        for child in (node.left, node.right):
            if child is not None:
                stack.append(child)
    # inc[x] / dec[x]: longest chain going down from x
    inc, dec, best = {}, {}, 1
    # children are processed before their parents
```

```
    for node in reversed(order):
        up = down = 1
        for child in (node.left, node.right):
            if child is None:
                continue
            if child.val == node.val + 1:
                up = max(up, inc[child] + 1)
            if child.val == node.val - 1:
                down = max(down, dec[child] + 1)
        inc[node], dec[node] = up, down
        # the bend joins both chains (counted node once)
        best = max(best, up + down - 1)
    return best


if __name__ == "__main__":
    #     1
    #    / \
    #   2   0
    #  /
    # 3
    left = TreeNode(2, TreeNode(3))
    tree = TreeNode(1, left, TreeNode(0))
    assert longest_consecutive(tree) == 3
    assert longest_consecutive(tree, True) == [1, 2, 3]
    # bending: 2 - 1 - 0 or 3 - 2 - 1 - 0 is length 4
    assert longest_any_direction(tree) == 4
    assert longest_consecutive(None) == 0
    assert longest_any_direction(None) == 0
    # duplicates never extend a chain
    dup = TreeNode(5, TreeNode(5), TreeNode(5))
    assert longest_consecutive(dup) == 1
    assert longest_any_direction(dup) == 1
    # a long chain needs no recursion
    chain = TreeNode(0)
    cur = chain
    for i in range(1, 5000):
        cur.left = TreeNode(i)
        cur = cur.left
    assert longest_consecutive(chain) == 5000
```

NOTES FROM CANDIDATES

In the base version, carry the current consecutive length while traversing downward and reset to 1 whenever the child is not exactly parent + 1.
For the any-direction follow-up, track increasing and decreasing chain lengths at each node, then combine through the node when the left/right child values support a consecutive bridge.
Clarify whether the answer is measured in nodes or edges before coding; Google candidates usually state node count.

PREPARATION

Write the parent-to-child traversal in under 10 minutes with a global best.
Practice the bidirectional tree follow-up where each node returns two lengths upward.
Dry-run single-node, duplicate-value, and split-branch cases before discussing complexity.

MEDIUM | IN APP LC 208 | 1Point3Acres | tech-screen, onsite-coding | 6 of 165

Trie Prefix Search / Autocomplete

ASKED 2026-07-02 | 100 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 36 | 30 DAYS 0 | PRIORITY 107/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: your app's interview approach (LeetCode #208)

LeetCode match: LC 208 Implement Trie (Prefix Tree)

Frequency: Medium | Last asked: 2026-07-02 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/trie-prefix-search-autocomplete

QUESTION

LeetCode 208 + 1268. Build a trie from a dictionary and return all words sharing a query prefix. Standard Google onsite coding.

Build a trie from a dictionary / array of words.
Support searchPrefix(prefix) -> list[str]: return all words that start with the query prefix, lexicographically sorted unless ranking is specified.
Some interviewers phrase the query as "a few letters" or "substring"; clarify whether they truly mean arbitrary substring search or the standard prefix/autocomplete contract before coding.
Common follow-ups: deletion, fuzzy match (one-character edit), autocompletion ranking by frequency, and returning only the best K completions.

EXAMPLES

```
Dict ["apple","app","apricot","banana"], prefix "ap"
    -> ["app","apple","apricot"].
```

APPROACH

Write the trie class from memory in under 12 min.
Drill the DFS-collect and the sorted-per-node variants; know which is faster in which scenario.
For frequency-ranking, practice the design-autocomplete variant (per-node top-K updated on insert) as a stretch goal.

HOW TO THINK ABOUT IT

A trie shares prefixes, so walking down the query prefix costs O(length of the prefix) no matter how many words exist. Everything under that node is a completion. For autocomplete you either collect the words below the prefix node with a DFS (visiting children in sorted order gives sorted output) or store the best few words at every node while inserting.

Basis: LeetCode 208, Implement Trie, plus LeetCode 1268, Search Suggestions System (top completions per prefix).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def search_prefix(words, prefix):
    found = []
    for w in words:
        if w.startswith(prefix):
            found.append(w)
    return sorted(found)
```

TIME	SPACE
O(n * L + n log n) per query	**O(output)**

WHY IT IS SLOW

Every query reads the whole dictionary. A trie reaches the prefix in O(length of the prefix) and reads only the completions.

OPTIMAL SOLUTION · Trie with a DFS over sorted children

TIME	SPACE
O(L + output) per query after O(total characters) to build	**O(total characters)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return only the best K completions ranked by frequency.

Store at every node the K best (frequency, word) pairs and update them while inserting; a query then reads one node in O(L + K) and never walks the subtree. The price is more memory and slower inserts, which is the right trade when reads dominate (autocomplete).

FOLLOW-UP 2 Allow one wrong character (fuzzy match).

Walk the trie with a budget of one edit: at each level follow the matching child with the full budget and every other child with the budget reduced to 0. The work grows with the alphabet size times the prefix length, not with the dictionary size.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class Node:
    def __init__(self):
        self.children = {}
        # how often the word ending here was inserted
        self.freq = 0
        # best (negative freq, word) pairs under this node
        self.top = []


# BASE QUESTION (optimal): Trie with a DFS over sorted
# children
class Trie:
    def __init__(self, k=3):
        self.root, self.k = Node(), k

    def insert(self, word, freq=1):
        node = self.root
        path = [node]
        for ch in word:
            node = node.children.setdefault(ch, Node())
            path.append(node)
        node.freq += freq
        # refresh the top-k list on every node of the path
        for n in path:
            n.top = [x for x in n.top if x[1] != word]
            n.top.append((-node.freq, word))
            n.top.sort()
            del n.top[self.k:]

    def find(self, prefix):
        # walk down the prefix; None if it is missing
        node = self.root
        for ch in prefix:
            node = node.children.get(ch)
            if node is None:
                return None
        return node

    def search_prefix(self, prefix):
        # every word with this prefix, in alphabetical
        # order
        node = self.find(prefix)
        out = []
        if node is None:
            return out
        stack = [(node, prefix)]
        while stack:
            n, text = stack.pop()
            if n.freq:
                out.append(text)
            for ch in n.children:
                stack.append((n.children[ch], text + ch))
        return sorted(out)

    def suggest(self, prefix):
        # best k completions, read from one node: O(L + k)
        node = self.find(prefix)
        return [w for _, w in node.top] if node else []

    def fuzzy(self, prefix):
        # words whose first letters differ in at most one
        # place
        out, stack = [], [(self.root, "", 0)]
        while stack:
            n, text, wrong = stack.pop()
            if len(text) == len(prefix):
                out += self.search_below(n, text)
                continue
            for ch, child in n.children.items():
                miss = wrong + (ch != prefix[len(text)])
                if miss <= 1:
                    stack.append((child, text + ch, miss))
        return sorted(out)

    def search_below(self, node, text):
        out, stack = [], [(node, text)]
        while stack:
            n, t = stack.pop()
            if n.freq:
                out.append(t)
            for ch, child in n.children.items():
                stack.append((child, t + ch))
        return out
```

```
if __name__ == "__main__":
    t = Trie(k=2)
    for w in ["apple", "app", "apricot", "banana"]:
        t.insert(w)
    ap = t.search_prefix("ap")
```

```
    assert ap == ["app", "apple", "apricot"]
    assert t.search_prefix("x") == []
    assert t.search_prefix("") == [
        "app", "apple", "apricot", "banana"]
    # frequency ranking: app was typed three more times
    t.insert("app", 3)
    assert t.suggest("ap") == ["app", "apple"]
    assert t.suggest("zzz") == []
    # one wrong letter in the prefix is allowed
    assert "banana" in t.fuzzy("vana")
    assert t.fuzzy("zzzz") == []
```

NOTES FROM CANDIDATES

Standard implementation: each trie node has a children map and an is_end flag.
Two collection patterns at the prefix: (a) DFS from the prefix node and collect all word-end nodes, (b) store the top-K candidates at every node during insert (Google-preferred for autocomplete).
The standard sorted-suggestions follow-up wants 3 suggestions per prefix-length — handle with sorted children or per-node sorted lists.

PREPARATION

Write the trie class from memory in under 12 min.
Drill the DFS-collect and the sorted-per-node variants; know which is faster in which scenario.
For frequency-ranking, practice the design-autocomplete variant (per-node top-K updated on insert) as a stretch goal.

MEDIUM | 1Point3Acres | phone-screen | 7 of 165

Website Activity Analytics: Unique Users + Session Time

ASKED 2026-06-26 | 106 DAYS AGO | LAST 6 MONTHS

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 213/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-06-26 | Roles: DS

Original: https://www.1point3acres.com/interview/problems/company/google/website-activity-analytics-unique-users-session-time

QUESTION

Given website action records with **`user_id`**, timestamp, and activity, compute per-activity unique-user counts and average time spent on the site per user in seconds. The screen paired this Python task with a lighter SQL section and emphasized edge-case discussion over perfect final code.

Input is a collection of user-activity records. Each record contains:

user_id: numeric user identifier
timestamp: timestamp string such as 2024-07-26 10:00:00
activity: action name such as login, view, purchase, or logout

Implement two analytics tasks

Return a mapping from each activity type to the number of unique users who performed that activity.
Calculate the average time spent on the website per user in seconds.

Clarify session semantics before coding. The prompt uses login/logout-style events, but the exact treatment of users without an explicit logout, multiple sessions per user, and out-of-order records must be agreed with the interviewer.

EXAMPLES

```
user_activity = [
    {'user_id': 1, 'timestamp': '2024-07-26
        10:00:00', 'activity': 'login'},
    {'user_id': 2, 'timestamp': '2024-07-26
        10:05:00', 'activity': 'login'},
    {'user_id': 1, 'timestamp': '2024-07-26
        10:10:00', 'activity': 'view'},
    {'user_id': 1, 'timestamp': '2024-07-26
        10:15:00', 'activity': 'purchase'},
    {'user_id': 2, 'timestamp': '2024-07-26
        10:20:00', 'activity': 'view'},
    {'user_id': 3, 'timestamp': '2024-07-26
        10:25:00', 'activity': 'login'},
    {'user_id': 1, 'timestamp': '2024-07-26
        10:30:00', 'activity': 'logout'},
]
```

APPROACH

Practice writing small Python analytics functions in a plain document without IDE help.
Drill grouping records by user and by activity with dictionaries / sets.
Rehearse explaining incomplete edge-case handling and dry-running a small event stream.

HOW TO THINK ABOUT IT

Unique users per activity is a map from activity to a set of user ids. Time on site needs a definition: pair each login with the next logout of the same user, and say what you do for a login without a logout (here: the session ends at that user's last event). Parse timestamps once, sort each user's events by time, and agree on out-of-order rows and repeated logins before coding.

HOW TO THINK ABOUT IT

Basis: Written for this question (a grouping and aggregation task; the SQL half of the screen is the same idea with GROUP BY and COUNT(DISTINCT)).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
for activity in activities:
    users = set()
    for rec in records:
        if rec.activity == activity:
            users.add(rec.user)
    unique[activity] = len(users)
for user in all_users:
    mine = [e for e in records if e.user == user]
    events = sorted(mine)
    spent = 0
    for login, logout in pairs(events):
        spent += logout.time - login.time
    total[user] = spent
average = sum(total.values()) / len(total)
```

TIME	SPACE
O(U * N + A * N)	O(U + A)

WHY IT IS SLOW

Rescans the whole log for every activity and every user. One pass that groups by activity and by user, then sorts each user's events once, is O(N log N).

OPTIMAL SOLUTION · One pass to group, then sessions per user

TIME	SPACE
O(N log N)	O(N)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Users with several sessions, missing logouts or out-of-order rows.

Sort each user's events by time before pairing; a second login before a logout is ignored (or closes the old session, depending on the contract you agree). A login with no logout ends at the user's last event, or is dropped if you decide it is unreliable. Say the choice out loud: the interviewer accepted a strong discussion over perfect code.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict
from datetime import datetime

FORMAT = "%Y-%m-%d %H:%M:%S"


def when(record):
    # timestamp text -> datetime
    return datetime.strptime(record["timestamp"], FORMAT)


# BASE QUESTION (optimal): One pass to group, then
# sessions per user
def unique_users_by_activity(records):
    users = defaultdict(set)
    for r in records:
        # a set counts every user once per activity
        users[r["activity"]].add(r["user_id"])
    return {a: len(u) for a, u in sorted(users.items())}


# BASE QUESTION (optimal): One pass to group, then
# sessions per user
# FOLLOW-UP 1: Users with several sessions, missing
# logouts or out-of-order rows.
def session_seconds(events):
    # events: one user's (time, activity), any order
    total, start = 0, None
    # FOLLOW-UP 1: sorted: rows may arrive out of order
    for t, act in sorted(events):
        if act == "login" and start is None:
            # a second login before a logout is ignored
            start = t
        elif act == "logout" and start is not None:
            total += (t - start).total_seconds()
            start = None
    # a login with no logout ends at the last event seen
    if start is not None:
        last = max(t for t, _ in events)
        total += (last - start).total_seconds()
    return total


# AVERAGE time on the site per user
def average_time_per_user(records):
    events = defaultdict(list)
    for r in records:
        item = (when(r), r["activity"])
        events[r["user_id"]].append(item)
    if not events:
        return 0.0
    # state the denominator: every user who appears
    per_user = events.values()
    total = sum(session_seconds(e) for e in per_user)
    return total / len(events)


if __name__ == "__main__":
    def rec(user, minute, activity):
        stamp = f"2024-07-26 10:{minute:02}:00"
        return {"user_id": user, "activity": activity,
                "timestamp": stamp}

    data = [rec(1, 0, "login"), rec(2, 5, "login"),
            rec(1, 10, "view"), rec(1, 15, "purchase"),
            rec(2, 20, "view"), rec(3, 25, "login"),
            rec(1, 30, "logout")]
    assert unique_users_by_activity(data) == {
        "login": 3, "logout": 1, "purchase": 1, "view": 2}
    # user 1: 1800 s, user 2: 900 s (no logout), user 3: 0
    assert average_time_per_user(data) == 900
    assert average_time_per_user([]) == 0.0
    # out-of-order rows are sorted first
    shuffled = [rec(1, 30, "logout"), rec(1, 0, "login")]
    assert average_time_per_user(shuffled) == 1800
    # two sessions add up
    two = [rec(1, 0, "login"), rec(1, 5, "logout"),
```

```
        rec(1, 10, "login"), rec(1, 20, "logout")]
    assert average_time_per_user(two) == 900
```

NOTES FROM CANDIDATES

SQL in the same screen was described as simple and covered joins / aggregation style work, but the exact SQL prompt did not leak.
The interviewer accepted a strong draft when all edge cases were discussed, even though the final code did not cover every case.
Spend time up front on timestamp parsing, ordering, repeated login/logout events, and users with missing terminal actions.

PREPARATION

Practice writing small Python analytics functions in a plain document without IDE help.
Drill grouping records by user and by activity with dictionaries / sets.
Rehearse explaining incomplete edge-case handling and dry-running a small event stream.

MEDIUM | 1Point3Acres | onsite-coding | 8 of 165

Streaming Points: Emit K Within Distance

ASKED 2026-06-23 | 109 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 195/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-06-23 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/streaming-points-k-within-distance

QUESTION

Process a stream of float positions. Whenever three points satisfy the distance condition, output and remove those three points; a follow-up generalizes from 3 points to K points. The important ambiguity is whether the condition means a span of length **d** or pairwise distance within **d**.SWEdata-structuresorting sliding-windowmediumambiguous-specFrequencySingle reportLast asked2026-06-23Stageonsite-coding

APPROACH

Practice range queries over sorted points with insertion and deletion.
Write the K-generalization in words before coding: identify the local candidate window, test the predicate, then remove exactly the emitted points.
Rehearse explaining float comparison, tie-breaking, and what to do when multiple groups qualify.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the condition means all K points fit in a span of length d or every pair is within d (on a line these are equivalent), whether to emit as soon as a group exists, and how to choose among overlapping groups.

BRUTE FORCE TO SAY OUT LOUD

Keep a list, and after each point sort it and scan for a group. O(n log n) per point.

OPTIMAL IDEA

Keep points in a sorted list (bisect.insort). After inserting x only windows containing x can be new, so look at the K-wide windows of sorted neighbors around its index; if the largest minus the smallest in a window is at most d, emit and remove those K points. O(log n) to locate plus the window size.

DRY-RUN THESE CASES

Exactly d apart, duplicates, points arriving out of order, two overlapping candidate groups, K = 1.

LIKELY FOLLOW-UPS

General K (the same code), 2D points, or a time-based expiration.

PITFALLS

Using epsilon-free float comparison blindly. Checking only the K points directly before x.

HOW TO THINK ABOUT IT

On a line, K points are all within distance d exactly when the largest minus the smallest is at most d, so only K consecutive points in sorted order can form a group. Keep the points sorted and look only where something changed: a window that contains the new point, or the seam left by removed points.

Basis: Written. Assumed rules (confirm them): after each new point, while some K consecutive points (in sorted order) span at most d, emit the lowest such group and remove it; on a line 'all within d' and 'span at most d' are the same condition.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
points = []
def on_point(x):
    points.append(x)
    points.sort()
    emitted = []
    while True:
        group = find_group()
        if group is None:
            return emitted
        emitted.append(group)
        remove(points, group)
def find_group():
    for i in range(len(points) - k + 1):
        if points[i + k - 1] - points[i] <= d:
            return points[i:i + k]
    return None
```

TIME	SPACE
O(n log n) per point	O(n)

WHY IT IS SLOW

Every arrival re-sorts and rescans the whole list, O(n log n). A sorted list with binary search checks only the windows around the new point.

OPTIMAL SOLUTION · Sorted list, check only windows touching the change

TIME	SPACE
O(log n + K) per check, plus list shifting	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if 'within d' means every pair, and points are in 2D?

On a line pairwise distance equals the span, so nothing changes. In 2D it becomes a clique problem: candidates must be neighbours in a spatial grid of cell size d, and you test the K-subset of nearby points; that is much harder, so ask whether the 1D reading is intended.

FOLLOW-UP 2 Floating-point coordinates.

Compare with the exact subtraction hi - lo <= d (not by building a range around the target), and agree on an epsilon policy only if the interviewer wants one. Do not compare floats for equality.

FOLLOW-UP 3 Several groups qualify at once.

Agree on a rule (lowest start, as coded) so output is deterministic, and note that emitting one group can create or destroy others.

FOLLOW-UP 4 The condition is 'every pair within d', not 'span at most d'.

On a line they are the same: the largest pairwise distance is max - min, so checking the span is enough (verified against checking all pairs). In 2D they differ and become a clique problem.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left, insort


# BASE QUESTION (optimal): Sorted list, check only windows
# touching the change
class PointStream:
    def __init__(self, k, d):
        # emit when k points fit in a span of d
        self.k, self.d = k, d
        # all points still waiting, kept sorted
        self.points = []

    def window_start(self, pos):
        # first window of k neighbours that includes pos
        lo = max(0, pos - self.k + 1)
        hi = min(pos, len(self.points) - self.k)
        for i in range(lo, hi + 1):
            last = self.points[i + self.k - 1]
            span = last - self.points[i]
            if span <= self.d:
                return i
        return None

    def add(self, x):
        # insert in order, then emit every window made by
        # x
        insort(self.points, x)
        out, pos = [], bisect_left(self.points, x)
        while True:
            i = self.window_start(pos)
            if i is None:
                return out
            # remove the group so it is emitted only once
            out.append(self.points[i:i + self.k])
            del self.points[i:i + self.k]
            pos = i


# FOLLOW-UP 4: The condition is 'every pair within d', not
# 'span at most d'.
def all_pairs_within(group, d):
    # "every pair within d": on a line this equals the
    # span
    pairs = [(a, b) for a in group for b in group]
    return all(abs(a - b) <= d for a, b in pairs)
```

```
if __name__ == "__main__":
    s = PointStream(3, 1.0)
    assert s.add(0.5) == []
    assert s.add(5.0) == []
    assert s.add(1.0) == []
    # 0.5, 1.0, 1.4 span 0.9 <= 1.0
    out = s.add(1.4)
    assert out == [[0.5, 1.0, 1.4]]
    # the far point is still waiting
    assert s.points == [5.0]
```

```
    # on a line, span and pairwise checks agree
    for group in out:
        assert all_pairs_within(group, 1.0)
        assert max(group) - min(group) <= 1.0
    # k = 2 groups closest neighbours as they appear
    t = PointStream(2, 0.5)
    assert t.add(1.0) == []
    assert t.add(1.4) == [[1.0, 1.4]]
```

NOTES FROM CANDIDATES

A balanced ordered set / TreeSet-style structure is a natural fit because each new point only needs nearby neighbors.
Be careful with floating-point comparison and epsilon policy.
A wrong clarification can lead to checking subset(target, target + d) when the interviewer expects a wider candidate range around the target. Confirm the predicate with a tiny numeric example before coding.

PREPARATION

Practice range queries over sorted points with insertion and deletion.
Write the K-generalization in words before coding: identify the local candidate window, test the predicate, then remove exactly the emitted points.
Rehearse explaining float comparison, tie-breaking, and what to do when multiple groups qualify.

MEDIUM | 1Point3Acres | phone-screen | 9 of 165

★ TOP 75: rank 72 in the Medium and Hard priority list

★ First Bad Version with Parallel Search Follow-up

ASKED 2026-06-15 | 117 DAYS AGO | LAST 6 MONTHS

STUDY: TYPE | **ALL TIME 41.1** | **30 DAYS 33** | **PRIORITY 46/224**

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #278 First Bad Version

LeetCode match: LC 278 First Bad Version

Frequency: Single report | Last asked: 2026-06-15 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/first-bad-version-parallel-search

QUESTION

Phone-screen R1 coding round. The base problem is the standard first-bad-version monotonic search — given an **`isBadVersion(v)`** oracle over versions **`1..n`**, find the first bad version with a single binary search. The graded follow-up requires parallelizing the search: partition the range into buckets and search them concurrently (bucket + binary search), with working code expected.SWEbinary-searchparallelismconcurrencymediumFrequencySingle reportLast asked2026-06-15Stagephone-screen

APPROACH

Write the single-threaded binary search first and verify it on small n.
Then implement the bucketed parallel version with real concurrency primitives (Python concurrent.futures.ThreadPoolExecutor, or Java ExecutorService / CompletableFuture): split [1, n] into k buckets, probe the k boundaries concurrently, pick the bucket where the predicate flips, and binary-search within it. Practice getting this to compile and run in under 20 minutes.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what the oracle is (isBadVersion is monotone), what concurrency primitive to use (ThreadPoolExecutor, Java's ExecutorService), and which metric matters: wall-clock time or total calls.

BRUTE FORCE TO SAY OUT LOUD

Check every version from 1. O(n) calls.

OPTIMAL IDEA

Base: binary search, O(log n) calls. Parallel: each round fires up to k probes concurrently at evenly spaced points, finds the first probe that is bad, and narrows the interval to the gap between it and the previous probe. Each round shrinks the interval by k + 1, so there are about log base (k + 1) of n sequential rounds. Use a thread pool and map the probes in one call.

DRY-RUN THESE CASES

n = 1, the first version bad, the last version bad, n smaller than the number of workers.

LIKELY FOLLOW-UPS

Rate limiting, retries when a probe fails, and caching results.

PITFALLS

Mutating shared state from threads. Assuming more threads always means fewer total calls (they increase it).

HOW TO THINK ABOUT IT

'First bad version' is a boundary in a sorted yes/no sequence, which is binary search. The parallel part is a different trade: instead of one probe per round, send several probes in the same round and keep the gap that contains the boundary. Fewer rounds, more total calls.

HOW TO THINK ABOUT IT

Basis: LeetCode 278, First Bad Version, plus a concurrent k-ary search follow-up.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n):
    for v in range(1, n + 1):
        if is_bad_version(v):
            return v
```

TIME	SPACE
O(n) calls	O(1)

WHY IT IS SLOW

One call per version, O(n) calls; with a billion versions and a slow check that is far too many. The check is monotone, so binary search needs only log2(n) calls, and probing several points in parallel needs fewer rounds.

OPTIMAL SOLUTION · Base problem: binary search

TIME	SPACE
O(log n) calls	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Parallel: probe k points at once, then recurse into the bucket that flips

TIME	SPACE
O(log_{k+1} n) rounds	O(k)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What does parallelism buy you, and what does it cost?

It cuts the number of sequential rounds from log2(n) to log_{k+1}(n), so wall-clock time drops when each probe has high latency. It increases total probes (about k per round instead of 1), so it costs more calls and money. Say which metric you are optimizing before choosing k.

FOLLOW-UP 2 What if the oracle is rate limited or can fail?

Cap the pool size to the rate limit, retry transient failures with backoff (probes are idempotent), and never advance the interval from a probe that errored. Cache results by version so a retry or a later round never repeats a call.

FOLLOW-UP 3 Count how many rounds each approach needs.

Single binary search: log2(n) rounds of one probe each. k workers: about log base (k + 1) of n rounds with k probes each. For n = 10^9, one probe per round needs 30 rounds, while 7 probes per round need 10.

FOLLOW-UP 4 Show how many rounds and calls the parallel search uses.

With k workers each round shrinks the interval by about k + 1, so the number of sequential rounds is about log base (k + 1) of n and the total calls at most k times that. For n = 10^6 and 7 workers that is about 7 rounds and 49 calls, against 20 rounds and 20 calls for the sequential search: fewer rounds, more calls.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from concurrent.futures import ThreadPoolExecutor
from threading import Lock


# BASE QUESTION (optimal): problem: binary search
def first_bad_version(n, is_bad):
    # the base question: binary search on versions 1..n
    lo, hi = 1, n
    while lo < hi:
        mid = lo + (hi - lo) // 2
        if is_bad(mid):
            # the first bad version is mid or earlier
            hi = mid
        else:
            lo = mid + 1
    return lo


# PARALLEL SEARCH helper
def probe_points(lo, hi, workers):
    # evenly spaced versions inside [lo, hi - 1]
    step = max(1, (hi - lo + 1) // (workers + 1))
    pts = {min(hi - 1, lo + step * (i + 1) - 1)
           for i in range(workers)}
    return sorted(pts)


# FOLLOW-UP 1, 3, 4: What does parallelism buy you, and
# what does it cost?
def first_bad_parallel(n, is_bad, workers=4):
    # invariant: the answer is in [lo, hi]
    lo, hi, cache, rounds = 1, n, {}, 0
    with ThreadPoolExecutor(workers) as pool:
        while lo < hi:
            points = probe_points(lo, hi, workers)
            # ask the oracle about new points at the same
            # time
            fresh = [p for p in points if p not in cache]
            answers = pool.map(is_bad, fresh)
            for p, bad in zip(fresh, answers):
                cache[p] = bad
            rounds += 1
            bad_points = [p for p in points if cache[p]]
            if not bad_points:
                # every probe was good: answer is after
```

```
                # them
                lo = points[-1] + 1
            else:
                first = bad_points[0]
                # the answer sits between the last good
                # probe before it and the first bad one
                before = [p for p in points if p < first]
                if before:
                    lo = before[-1] + 1
                hi = first
    return lo, rounds, len(cache)


if __name__ == "__main__":
    calls, lock = [], Lock()

    def oracle(first_bad):
        def is_bad(v):
            with lock:
                calls.append(v)
            return v >= first_bad
        return is_bad

    cases = ((1, 1), (10, 1), (10, 10), (1000, 637))
    for n, bad in cases:
        assert first_bad_version(n, oracle(bad)) == bad
        ans, rounds, used = first_bad_parallel(
            n, oracle(bad), workers=4)
        assert ans == bad
    # fewer rounds than the 20 of a plain binary search
    ans, rounds, used = first_bad_parallel(
        10 ** 6, oracle(123456), workers=7)
    assert ans == 123456 and rounds < 20
    assert used <= 7 * rounds
```

NOTES FROM CANDIDATES

The base is trivial; budget your time for the parallel follow-up and aim to get a complete, compiling version through even if it has minor bugs — finishing the parallel version is what passes this round.
Be explicit about what the parallel design optimizes: wall-clock latency (fire many isBadVersion probes at once) versus total number of calls. Splitting into k buckets and probing each boundary concurrently localizes the transition in one parallel round, then a binary search finishes it.
Common bugs: off-by-one when mapping a bucket index back to an absolute version range; the transition sitting exactly on a bucket boundary; integer overflow in mid if you write (lo + hi) / 2 instead of lo + (hi - lo) // 2.

PREPARATION

Write the single-threaded binary search first and verify it on small n.
Then implement the bucketed parallel version with real concurrency primitives (Python concurrent.futures.ThreadPoolExecutor, or Java ExecutorService / CompletableFuture): split [1, n] into k buckets, probe the k boundaries concurrently, pick the bucket where the predicate flips, and binary-search within it. Practice getting this to compile and run in under 20 minutes.

MEDIUM | 1Point3Acres | phone-screen | 10 of 165

Greedy Longest-Match Dictionary Tokenizer

ASKED 2026-06-15 | 117 DAYS AGO | LAST 6 MONTHS

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 211/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: written and tested here for this exact question

Frequency: Low | Last asked: 2026-06-15 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/tokenize-longest-dict-match-greedy

QUESTION

Phone-screen coding round (R1). Tokenize a text against a dictionary of **`key:id`** entries using greedy longest-match; emit the matched id when a key matches, otherwise output the unmatched character as a literal. One follow-up on changing the tie-breaking / priority rule for which token wins. A second follow-up appears when the dictionary is very large: discuss how to keep the matcher memory- and lookup-efficient at scale.

Input: a text string and a dictionary mapping key (string) -> id.
Sweep the text left-to-right. At each position, find the longest dictionary key that matches a prefix of the remaining text; emit its id. If no key matches at the current position, emit the single character as a literal and advance by one.
Output the concatenation (or list) of ids and literal characters in order.
Follow-up: the interviewer changes the tie-breaking / priority rule for which key wins when multiple match (e.g., not longest but highest-priority by dictionary order). Adapt the data structure so the rule swap is cheap.
Follow-up: the dictionary becomes very large. Discuss how to keep memory and per-position lookup efficient — a compressed / radix trie (or sharding the key space) instead of holding every key in a flat map.

APPROACH

Implement both versions (hashmap-scan and trie-walk) from scratch in under 15 min each. Run them on a small dict like {"the": 1, "theater": 2, "a": 3} against text "theater" to confirm the trie returns id 2 and the hashmap version returns the same.
For the priority-tie follow-up: practice attaching a priority field to terminal nodes and picking the highest-priority terminal seen along the trie walk, not just the deepest. Time complexity should not change.
If asked to stream the input, switch to the Aho-Corasick mental model — the trie augmented with failure links emits all dictionary matches in a single linear pass over the text.

HOW TO THINK ABOUT IT

At each position you want the longest dictionary key that is a prefix of the remaining text. Putting the keys in a trie lets you walk the text character by character from that position and remember the deepest end-of-key node you passed, instead of trying every length. If the tie-break rule changes (priority instead of length), store the priority at the terminal node and keep the best terminal seen.

Basis: Written for this question (longest-prefix matching with a trie, as in LeetCode 208 and the maximal-munch rule of lexers).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def tokenize(text):
    out, i = [], 0
    while i < len(text):
        for size in range(max_key_len, 0, -1):
            key = text[i:i + size]
            if key in dictionary:
                out.append(dictionary[key])
                i += size
                break
        else:
            out.append(text[i])  # literal
            i += 1
    return out
```

TIME	SPACE
O(n * L)	O(dictionary)
lookups, each O(L)	

WHY IT IS SLOW

Every lookup hashes a substring, O(L^2) per position. Walking a trie of the keys one character at a time costs O(L) per position.

OPTIMAL SOLUTION · Trie walk keeping the deepest (or best-priority) terminal

TIME	SPACE
O(n * L)	O(total key length)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The dictionary is huge.

A flat map of every key wastes memory because keys share prefixes. A compressed (radix) trie stores each shared stretch once, or shard the keys by first characters across machines. Lookup stays one pass over the text; only the node layout changes.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Trie walk keeping the deepest
# (or best-priority) terminal
# FOLLOW-UP 1: The dictionary is huge.
class Tokenizer:
    def __init__(self, table, priority=None):
        # table: key -> id. priority(key): lower wins;
        # with
        # None the longest match wins
        self.priority = priority
        self.root = {}
        for key, ident in table.items():
            node = self.root
            for ch in key:
                node = node.setdefault(ch, {})
            # the end of a key stores the key and its id
            node["$"] = (key, ident)

    def better(self, new, old):
        # should the match `new` replace the match `old`?
        if old is None:
            return True
        if self.priority is None:
            # deeper (longer) matches come later: keep
            # them
            return True
        rank = self.priority
        return rank(new[0]) < rank(old[0])

    def longest_at(self, text, i):
        # walk the trie from position i
        node, best, j = self.root, None, i
        while j < len(text) and text[j] in node:
            node = node[text[j]]
            j += 1
            end = node.get("$")
            if end and self.better(end, best):
                best = end
        return best

    def tokenize(self, text):
        out, i = [], 0
        while i < len(text):
            match = self.longest_at(text, i)
            if match is None:
                # no key starts here: keep the character
                out.append(text[i])
                i += 1
            else:
                key, ident = match
                out.append(ident)
                i += len(key)
        return out


# SIMPLER VERSION: one dictionary lookup per length
def tokenize_map(text, table):
    # simpler version: a dictionary lookup per length
    out, i = [], 0
    longest = max(map(len, table), default=0)
    while i < len(text):
        top = min(longest, len(text) - i)
        for size in range(top, 0, -1):
            if text[i:i + size] in table:
                out.append(table[text[i:i + size]])
                i += size
```

```
                break
        else:
            out.append(text[i])
            i += 1
    return out


if __name__ == "__main__":
    table = {"ab": 1, "abc": 2, "c": 3}
    t = Tokenizer(table)
    # abc is longer than ab, so it wins at position 0
    assert t.tokenize("abcab") == [2, 1]
    assert t.tokenize("xyz") == ["x", "y", "z"]
    assert t.tokenize("") == []
    assert tokenize_map("abcab", table) == [2, 1]
    # a single-letter key still applies the longest rule
    assert t.tokenize("cab") == [3, 1]
    # follow-up: priority by dictionary order instead
    order = list(table)
    pri = Tokenizer(table, priority=order.index)
    assert pri.tokenize("abc") == [1, 3]
```

NOTES FROM CANDIDATES

The key:id dictionary format and the literal-passthrough for unmatched characters are confirmed across multiple candidates.
Two natural shapes:

Hashmap of keys + per-position scan up to maxKeyLen. Easy to write, O(n · maxKeyLen) time; O(n · L) if the longest key length L dominates.
Trie of keys + walk the trie one character at a time from each position; remember the deepest reached is_end node and emit it. O(n · L) worst case but does only one pass per starting position and adapts cleanly to the priority-rule follow-up (store priority at each terminal node and keep the best matched terminal along the walk, not necessarily the deepest).

Edge cases to discuss: overlapping keys with different lengths ("ab" vs "abc"), key whose match would consume the rest of the string, empty dictionary, key that is a single character (still apply longest-match, not literal-fallback).
If the follow-up generalizes to "non-overlapping tokenization that maximizes total score", that's the word-break with weights DP variant — flag it as a different problem class rather than patching the greedy.

PREPARATION

Implement both versions (hashmap-scan and trie-walk) from scratch in under 15 min each. Run them on a small dict like {"the": 1, "theater": 2, "a": 3} against text "theater" to confirm the trie returns id 2 and the hashmap version returns the same.
For the priority-tie follow-up: practice attaching a priority field to terminal nodes and picking the highest-priority terminal seen along the trie walk, not just the deepest. Time complexity should not change.
If asked to stream the input, switch to the Aho-Corasick mental model — the trie augmented with failure links emits all dictionary matches in a single linear pass over the text.

MEDIUM | DESIGN-STYLE (skippable) | 1Point3Acres | onsite-coding | 11 of 165

Employee Hierarchy Add / Delete

ASKED 2026-06-10 | 122 DAYS AGO | LAST 6 MONTHS

STUDY: READ | **NO LEETCODE FREQUENCY** | **PRIORITY 223/224**

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-06-10 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/employee-hierarchy-add-delete

QUESTION

Design an employee hierarchy class that supports adding employees under managers and deleting employees by id. Follow-ups cover deleting managers, deleting the CEO, cycle handling, and choosing a replacement manager by seniority.SWEtreehashmapobject-designmediumFrequencySingle reportLast asked2026-06-10Stageonsite-coding

APPROACH

Implement tree mutation operations with parent pointers. Practice deleting an internal node while reconnecting children. Add cycle checks with DFS or parent-chain walking before accepting a new edge.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what happens when a manager is deleted (promote a report, reassign to the grandparent, or reject), what happens when the CEO is deleted, whether adding can create a cycle, and how seniority is defined.

BRUTE FORCE TO SAY OUT LOUD

Store parent pointers only and search the whole tree to find children on every delete. O(n).

OPTIMAL IDEA

Keep id to node, and for each node a parent pointer and a children set. Add: validate the manager exists and the new id is free. Delete: take the children of the removed node and attach them to a replacement (the deleted node's parent, or a chosen successor), update pointers, and remove it from its parent's children. CEO needs a stated policy. Compare candidates by (level descending, insertion order ascending) for the seniority rule.

DRY-RUN THESE CASES

Delete a leaf, a middle manager, the CEO, an unknown id, adding with a missing manager.

LIKELY FOLLOW-UPS

Cycle detection by walking up parent pointers, bulk deletes, or a history of changes.

INTERVIEW-DAY PLAN

PITFALLS

Leaving dangling children references. Not choosing a policy for the root.

HOW TO THINK ABOUT IT

A hierarchy is a tree you update, so store links in both directions (parent per node, children per node). Then every operation touches only the neighbours of one node instead of searching the tree. For each delete case (leaf, middle, root) say the policy first, because the data structure is easy once the rule is fixed.

Basis: Written. Assumed policies (confirm them): deleting a manager hands their reports to that manager's own manager; deleting the CEO is allowed only if exactly one report exists (that report becomes CEO), otherwise it is rejected; ids are unique.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
manager = {}  # employee -> manager
def delete(e):
    reports = [x for x in manager
               if manager[x] == e]
    for x in reports:
        manager[x] = manager[e]
    del manager[e]
```

TIME	SPACE
O(n) per delete	O(n)

WHY IT IS SLOW

Every delete scans all employees, O(n). Keeping a children set per employee makes it O(number of reports).

OPTIMAL SOLUTION · Parent map plus children sets

TIME	SPACE
O(r) per delete where r is the number of reports	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Support moving an employee under another manager and reject cycles.

Walk up from the proposed new manager through manager pointers; if you meet the employee being moved, the move would put a node under its own descendant, so reject it. O(depth).

FOLLOW-UP 2 When a manager leaves, promote the most senior report instead of the grandparent.

Store a hire order (insertion counter) per employee and pick the report with the smallest one: the new manager takes over the other reports. Say how you break ties.

FOLLOW-UP 3 The CEO leaves.

Pick a policy and say it: reject, promote the most senior report (the rest report to them), or leave the company rootless and hold a set of roots. The structure above needs only a promoted root.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Parent map plus children sets
# FOLLOW-UP 1: Support moving an employee under another
# manager and reject cycles.
class Org:
    def __init__(self, ceo):
        self.root = ceo
        self.manager = {ceo: None}
        self.reports = {ceo: set()}
        # hire order, used for "most senior" choices
        self.hired = {ceo: 0}
        self.clock = 1

    def add(self, emp, mgr):
        if emp in self.manager or mgr not in self.manager:
            return False
        self.manager[emp] = mgr
        self.reports[emp] = set()
        self.reports[mgr].add(emp)
        self.hired[emp] = self.clock
        self.clock += 1
        return True

    def senior(self, people):
        # the person hired earliest
        return min(people, key=lambda p: self.hired[p])

    def delete(self, emp, policy="grandparent"):
        if emp not in self.manager:
            return False
        mgr = self.manager[emp]
        kids = set(self.reports[emp])
        # FOLLOW-UP 3: the CEO leaves
        if mgr is None and not kids:
            # the CEO alone: nothing could take over
            return False
        # FOLLOW-UP 2: promote the most senior report
        if policy == "senior" or mgr is None:
            # the most senior report takes the place of
            # emp
            heir = self.senior(kids) if kids else None
        else:
            heir = mgr
        for r in kids:
            if r != heir:
                self.reassign(r, heir)
```

```
        if mgr is None:
            # the promoted report becomes the new CEO
            self.root = heir
            self.manager[heir] = None
```

```
        elif policy == "senior" and heir != mgr:
            self.reassign(heir, mgr)
        if mgr is not None:
            self.reports[mgr].discard(emp)
        del self.manager[emp], self.reports[emp]
        return True

    def reassign(self, emp, new_mgr):
        old = self.manager[emp]
        if old is not None and old in self.reports:
            self.reports[old].discard(emp)
        self.manager[emp] = new_mgr
        self.reports[new_mgr].add(emp)

    # FOLLOW-UP 1: move an employee, reject cycles
    def move(self, emp, new_mgr):
        # walk up from the new manager: meeting emp is a
        # cycle
        node = new_mgr
        while node is not None:
            if node == emp:
                return False
            node = self.manager[node]
        self.reassign(emp, new_mgr)
        return True


if __name__ == "__main__":
    o = Org("ceo")
    for e, m in [("a", "ceo"), ("b", "a"), ("c", "a")]:
        assert o.add(e, m)
    assert not o.add("a", "ceo")
    assert not o.add("x", "nobody")
    # deleting a manager: reports go to the grandparent
    assert o.delete("a")
    assert o.manager["b"] == "ceo"
    assert o.manager["c"] == "ceo"
    # a move that would create a cycle is rejected
    o.add("d", "b")
    assert not o.move("b", "d") and o.move("d", "c")
    # promote the most senior report instead
```

```
    p = Org("ceo")
    for e, m in [("m", "ceo"), ("x", "m"), ("y", "m")]:
        p.add(e, m)
    assert p.delete("m", "senior")
    assert p.manager["x"] == "ceo"
    assert p.manager["y"] == "x"
    # the CEO leaves: the most senior report takes over
    q = Org("ceo")
    q.add("a", "ceo")
    q.add("b", "ceo")
    assert q.delete("ceo")
    assert q.root == "a" and q.manager["b"] == "a"
    assert not Org("solo").delete("solo")
```

NOTES FROM CANDIDATES

Use maps from id to node and id to children; keep parent pointers so deletes do not require a full traversal.
CEO deletion needs an explicit policy: reject, promote a child, or create a new root. State the policy and keep it consistent.
For the seniority follow-up, maintain insertion order on nodes and compare (level desc, insertion_order asc).

PREPARATION

Implement tree mutation operations with parent pointers.
Practice deleting an internal node while reconnecting children.
Add cycle checks with DFS or parent-chain walking before accepting a new edge.

MEDIUM | 1Point3Acres | onsite-coding | 12 of 165

Nested Function Expression Evaluator

ASKED 2026-06-10 | 122 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 5 | 30 DAYS 0 | PRIORITY 174/224

ABOUT THIS QUESTION

Topic: Expression Parsing and Evaluation

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 770 Basic Calculator IV (related)

Frequency: Low | Last asked: 2026-06-10 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/nested-function-expression-evaluator

QUESTION

EXAMPLES

```
add(1, sub(1, 0)) -> 2
add(2, mul(3, pow(4, 5))) -> 3074
```

APPROACH

Write a small tokenizer for identifiers, integers, commas, and parentheses.
Practice a recursive parseExpr() that returns both the value and the next index.
Drill the variable-arity follow-up by collecting arguments until) instead of assuming exactly two.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask which functions exist, whether they take a fixed or variable number of arguments, whether numbers can be negative, how division behaves, and how errors are reported.

BRUTE FORCE TO SAY OUT LOUD

Repeatedly find the innermost call with a regex and replace it with its value. Quick but fragile.

OPTIMAL IDEA

Tokenize into identifiers, integers, commas and parentheses. Write parse(i) returning (value, next index): a number returns itself; a name must be followed by '(', then loop reading arguments until ')', then apply the function. A function table keeps new operators one line each. O(n), recursion depth equals nesting depth.

DRY-RUN THESE CASES

INTERVIEW-DAY PLAN

add(1, sub(1, 0)) is 2. add(2, mul(3, pow(4, 5))) is 3074. A bare number. Variable argument counts. Unknown function names.

LIKELY FOLLOW-UPS

Variables, iterative parsing with two stacks, or division semantics.

PITFALLS

Losing the next index after parsing an argument. Treating '-' in '-5' as an operator.

HOW TO THINK ABOUT IT

An expression with function calls inside function calls has a grammar: expression = number | name '(' expression, expression, ... ')'. Each call can be evaluated only after its arguments, so write a function that parses one expression and reports where it stopped (recursive descent). A tokenizer first, then parse(i) returning (value, next index), keeps the bookkeeping small.

Basis: Recursive descent parsing, in the spirit of LeetCode 224 / 726; closest on LeetCode is 770, Basic Calculator IV.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def evaluate(text):
    while has_call(text):
        call = find_innermost_call(text)
        value = apply(call)  # e.g. add(2, 3)
        text = text.replace(call, str(value))
    return int(text)
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Every replacement rescans and rebuilds the string, O(n) per call and O(n^2) in total, and it cannot report errors well. A tokenizer plus recursive descent reads the text once, O(n).

OPTIMAL SOLUTION · Tokenizer + recursive descent over name(arg, arg, ...)

TIME	SPACE
O(n)	O(depth)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Support variadic functions and variables.

Collect arguments until ')' instead of assuming two (as the code does). For variables, pass an environment dict into parse and treat an identifier that is not followed by '(' as a lookup. Define the error behaviour for undefined names.

FOLLOW-UP 2 How do you make it iterative?

Use two stacks: one of pending function names and one of lists of evaluated arguments. On an identifier push the name and a new list, on a number append to the top list, on ')' pop both, apply the function, and append the result to the new top list. This removes the recursion-depth limit but is easier to get wrong off by one.

FOLLOW-UP 3 What about division?

State the contract: integer or float, truncate toward zero or floor (Python's // floors, which differs for negatives), and divide by zero handling. The implementation above truncates toward zero.

FOLLOW-UP 4 Add variables (an identifier with no parentheses is a lookup).

In parse, check whether the identifier is followed by '('; if not, return env[name]. Decide what an undefined name does (raise, or default to 0).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import math
import re

TOKEN = re.compile(r"-?\d+|[A-Za-z_]\w*|[(),]")


# FOLLOW-UP 3: What about division?
def divide(a, b):
    # integer division that truncates toward zero
    if b == 0:
        raise ZeroDivisionError("division by zero")
    return int(a / b)


OPS = {
    "add": lambda *a: sum(a),
    "sub": lambda a, b: a - b,
    "mul": lambda *a: math.prod(a),
    "pow": lambda a, b: a ** b,
    "div": divide,
    "min": min,
    "max": max,
}


# BASE QUESTION (optimal): Tokenizer + recursive descent
# over name(arg, arg, ...)
def evaluate(expr, env=None):
    env = env or {}
    tokens = TOKEN.findall(expr)

    def parse(i):
        # returns (value, index after this expression)
        tok = tokens[i]
        if re.fullmatch(r"-?\d+", tok):
            return int(tok), i + 1
        # FOLLOW-UP 4: variables come from env
        # a name not followed by "(" is a variable
        if i + 1 >= len(tokens) or tokens[i + 1] != "(":
            if tok not in env:
```

```
                raise ValueError(f"undefined {tok!r}")
            return env[tok], i + 1
        if tok not in OPS:
            raise ValueError(f"unknown function {tok!r}")
        i += 2
```

```
        args = []
        # read arguments until the closing bracket
        while tokens[i] != ")":
            value, i = parse(i)
            args.append(value)
            if tokens[i] == ",":
                i += 1
        return OPS[tok](*args), i + 1

    value, end = parse(0)
    if end != len(tokens):
        raise ValueError("trailing tokens")
    return value


# FOLLOW-UP 2: How do you make it iterative?
def evaluate_iterative(expr):
    # two stacks: function names and their argument lists
    names, args, tokens = [], [[]], TOKEN.findall(expr)
    for tok in tokens:
        if re.fullmatch(r"-?\d+", tok):
            args[-1].append(int(tok))
        elif tok == "(":
            # the name just pushed now owns a new list
            args.append([])
        elif tok == ")":
            result = OPS[names.pop()](*args.pop())
            args[-1].append(result)
        elif tok != ",":
            names.append(tok)
    return args[0][0]


if __name__ == "__main__":
    assert evaluate("add(1, sub(1, 0))") == 2
    assert evaluate("add(2, mul(3, pow(4, 5)))") == 3074
    # variadic functions
    assert evaluate("add(1, 2, 3, 4)") == 10
    assert evaluate("max(3, min(9, 4), 1)") == 4
    # variables come from an environment
    assert evaluate("add(x, mul(x, 2))", {"x": 5}) == 15
    # division truncates toward zero
    assert evaluate("div(-7, 2)") == -3
    for bad in ("foo(1)", "add(1", "add(1) 2", "y"):
        try:
```

```
            evaluate(bad)
            raise AssertionError(bad)
        except (ValueError, IndexError):
            pass
    # the iterative version agrees and has no depth limit
    big = "add(2, mul(3, pow(4, 5)))"
    assert evaluate_iterative(big) == 3074
    deep = "add(1, " * 3000 + "0" + ")" * 3000
    assert evaluate_iterative(deep) == 3000
```

NOTES FROM CANDIDATES

Tokenizer + recursive descent is the cleanest approach: parse operator, consume (, parse comma-separated child expressions, consume), then evaluate.
Iterative parsing works but is easy to make off-by-one errors under interview pressure; one candidate was specifically flagged for minor syntax and bounds issues.
Clarify division behavior for negative values and non-divisible integers.

PREPARATION

Write a small tokenizer for identifiers, integers, commas, and parentheses.
Practice a recursive parseExpr() that returns both the value and the next index.
Drill the variable-arity follow-up by collecting arguments until) instead of assuming exactly two.

MEDIUM | 1Point3Acres | phone-screen, tech-screen | 13 of 165

Tic-Tac-Toe System with K Players and 3-in-a-Row Win

ASKED 2026-05-18 | 145 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 18.1 | 30 DAYS 0 | PRIORITY 153/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 348 Design Tic-Tac-Toe (related)

Frequency: Single report | Last asked: 2026-05-18 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/tic-tac-toe-k-players-three-in-a-row

QUESTION

Design a Tic-Tac-Toe system for **k** players on an **n x n** board. After each move, return the game status; any player wins immediately after forming 3 consecutive marks in a straight line.

Input parameters: k players and an n x n board.
Players take turns placing their marks on empty cells.
A player wins as soon as they form 3 consecutive marks in a straight line, regardless of how large n is.
After each move, return the correct game status, such as Game Over or <player> won.
Discuss implementation details and time complexity before coding.

APPROACH

Implement the classic Tic-Tac-Toe design problem, then generalize from 2 players / 3x3 to k players / n x n.
Practice local directional win checks with boundary guards.
Write tests for corners, edges, duplicate moves, and simultaneous longer lines.

HOW TO THINK ABOUT IT

A move can only create a win through the cell just played, so after each move look only along the four lines through that cell (row, column, both diagonals) and count how far the same player's marks extend in both directions. With a target of 3 that is a handful of cells per move, instead of rescanning the whole board.

Basis: LeetCode 348, Design Tic-Tac-Toe, generalised to k players, an n x n board and a fixed run length of 3.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def status(player):
    for r, c in all_cells(board):
        for dr, dc in DIRECTIONS:
            cells = line_of_3(r, c, dr, dc)
            if all(board[x][y] == player
                   for x, y in cells):
                return "WIN"
    if is_full(board):
        return "DRAW"
    return "PLAYING"
```

TIME	SPACE
O(n^2) per move	O(n^2)

WHY IT IS SLOW

Scans O(n^2) cells per move. Only lines through the cell just played can have changed, so checking four directions around it is O(1).

OPTIMAL SOLUTION · Check the four lines through the new mark

TIME	SPACE
O(1) per move (O(target) when generalised)	O(n^2)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What changes when the winning length is a parameter w?

Replace the constant 3 by w in the run check: the cost per move becomes O(w) because each of the four directions walks at most w - 1 cells each way. The board size does not matter any more, which is the point of checking locally.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
DIRECTIONS = ((0, 1), (1, 0), (1, 1), (1, -1))


# BASE QUESTION (optimal): Check the four lines through
# the new mark
# FOLLOW-UP 1: What changes when the winning length is a
# parameter w?
class TicTacToe:
    def __init__(self, n, k, target=3):
        self.n, self.k, self.target = n, k, target
        self.board = [[0] * n for _ in range(n)]
        self.moves = 0
        self.over = False

    def inside(self, r, c):
        return 0 <= r < self.n and 0 <= c < self.n

    def run_length(self, r, c, dr, dc):
        # marks of the same player in a line through (r,
        # c)
        player, run = self.board[r][c], 1
        for sign in (1, -1):
            a, b = r + sign * dr, c + sign * dc
            while self.inside(a, b) and \
                    self.board[a][b] == player:
                run += 1
                a, b = a + sign * dr, b + sign * dc
        return run

    def move(self, player, r, c):
        # whose turn is it? players go 1, 2, ..., k, 1,
        # ...
        turn = self.moves % self.k + 1
        if self.over or player != turn:
            raise ValueError("not this player's turn")
        if not self.inside(r, c) or self.board[r][c]:
            raise ValueError("illegal cell")
        self.board[r][c] = player
        self.moves += 1
        # only lines through the new mark can have changed
        for dr, dc in DIRECTIONS:
            run = self.run_length(r, c, dr, dc)
            # FOLLOW-UP 1: win with `target` in a row
            if run >= self.target:
                self.over = True
```

```
                return f"player {player} wins"
        if self.moves == self.n * self.n:
            self.over = True
            return "draw"
        return "continue"


if __name__ == "__main__":
    g = TicTacToe(3, 2)
    plan = [(1, 0, 0), (2, 1, 0), (1, 0, 1),
```

```
        (2, 1, 1), (1, 0, 2)]
results = [g.move(p, r, c) for p, r, c in plan]
assert results[:-1] == ["continue"] * 4
assert results[-1] == "player 1 wins"
# three players on a 4 x 4 board: player 2 wins down
h = TicTacToe(4, 3)
seq = [(1, 0, 0), (2, 0, 3), (3, 3, 3), (1, 1, 0),
       (2, 1, 3), (3, 3, 0), (1, 2, 1), (2, 2, 3)]
out = [h.move(p, r, c) for p, r, c in seq]
assert out[-1] == "player 2 wins"
# wrong turn and used cell are rejected
for bad in ((2, 0, 0), (1, 5, 5)):
    try:
        TicTacToe(3, 2).move(*bad)
        raise AssertionError(bad)
    except ValueError:
        pass
# the win length is a parameter: 4 in a row
w = TicTacToe(5, 2, target=4)
for p, r, c in [(1, 0, 0), (2, 1, 0), (1, 0, 1),
                (2, 1, 1), (1, 0, 2), (2, 1, 2)]:
    assert w.move(p, r, c) == "continue"
```

NOTES FROM CANDIDATES

Check four directions through the new mark: horizontal, vertical, main diagonal, anti-diagonal. Count contiguous marks on both sides; win if total reaches 3.
Avoid scanning the whole board after every move unless n is tiny. The local directional check is O(1) for the fixed 3-in-a-row target, or O(target) if generalized.
Clarify invalid moves, turn order, draw state, and whether 3-in-a-row must be exactly 3 or at least 3.

PREPARATION

Implement the classic Tic-Tac-Toe design problem, then generalize from 2 players / 3x3 to k players / n x n.
Practice local directional win checks with boundary guards.
Write tests for corners, edges, duplicate moves, and simultaneous longer lines.

MEDIUM | 1Point3Acres | onsite-coding | 14 of 165

Gate Entry / Exit Time Resolution with Tie-Break Rules

ASKED 2026-05-04 | 159 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 27.4 | 30 DAYS 0 | PRIORITY 130/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 2534 Time Taken to Cross the Door

Frequency: Single report | Last asked: 2026-05-04 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/gate-entry-exit-scheduler

QUESTION

Onsite coding round 2: given an array indexed by person id, each containing **`(timestamp, action in {enter, exit})`**, return per-person the actual time they passed through the gate after applying tie-break rules between simultaneous enters and exits.SWEsimulationalgorithmmediumFrequencySingle reportLast asked2026-05-04Stageonsite-coding

APPROACH

Translate the four priority rules into an explicit state machine (prev_state in {enter, exit, none}) before writing any code.
Practice scheduling problems that pair a per-tick simulation with an event-driven optimization (CPU scheduler, traffic light, calendar conflict resolver).
Stress-test corner cases: same timestamp containing both an enter and an exit for the same person, all-enters or all-exits batches, and very large gaps between two events.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the exact tie-break rules in the four cases (previous second unused, entered, exited, and which wins), whether one person passes per second, and how ties between equal arrival times break (by id).

BRUTE FORCE TO SAY OUT LOUD

Simulate every second between the first and last timestamp. Works, but its cost grows with the size of the timestamps.

OPTIMAL IDEA

Sort people by (time, id) and keep two queues. At each step apply the previous-state rule to choose a queue. When both queues are empty jump to the next arrival time and reset the previous state to idle if at least one second was skipped. Linear after the sort.

DRY-RUN THESE CASES

Same-time enter and exit, an idle gap of exactly one second and of many seconds, all enters, all exits.

LIKELY FOLLOW-UPS

Several gates, priority classes, or answering online.

PITFALLS

Forgetting to reset the state across an idle gap. Letting the clock go backward.

HOW TO THINK ABOUT IT

Write the rule as a small state machine first: the state is what the gate did in the previous second (entered, exited or idle), and the rule picks who goes next from that state. Then replace the second-by-second loop with a loop over people: when nobody is waiting jump the clock forward, and remember that an idle gap resets the state to idle.

HOW TO THINK ABOUT IT

Basis: LeetCode 2534, Time Taken to Cross the Door. Assumption: one person passes per second; if an enter and an exit compete, the door's previous-second use decides (enter if it was an enter, otherwise exit, and exit if the door was idle).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(arrivals):
    t, prev = 0, None
    enter_q, exit_q = deque(), deque()
    while pending(arrivals, enter_q, exit_q):
        add_arrivals(t, arrivals, enter_q,
                     exit_q)
        queue = choose(prev, enter_q, exit_q)
        if queue:
            person = queue.popleft()
            passed[person] = t
            prev = name_of(queue)
        t += 1
    return passed
```

TIME	SPACE
O(T + n)	O(n)
where T is the last timestamp	

WHY IT IS SLOW

It runs through every second between the first and last timestamp, so a timestamp of 10^9 means a billion iterations. Jumping to the next arrival when the queues are empty makes it O(n log n).

OPTIMAL SOLUTION · Event-driven simulation with two queues

TIME	SPACE
O(n log n)	O(n)
for the sort, O(n) simulation	

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why does the optimization need care across an empty gap?

If the door sits idle for even one second the previous state becomes 'none', which favours exits again. Jumping time forward without resetting the state would wrongly keep 'enter' priority from before the gap. Compare t with last_used + 1 to know whether the gap really was idle.

FOLLOW-UP 2 What is the complexity, and what if events come online?

Offline it is O(n log n) for the sort, then O(n) for the simulation, independent of how large the timestamps are. Online, keep the two queues and the previous-state variable and advance the clock on every arrival or tick; the work per person stays O(1).

FOLLOW-UP 3 Timestamps go up to 10^9.

That is why the event-driven loop jumps to the next arrival: its running time is O(n log n) and does not depend on the size of the timestamps. Remember to reset the previous state to idle across a gap.

FOLLOW-UP 4 The tie-break when the gate was idle differs in this version of the question.

Keep the simulation and make the idle winner a parameter: only the line that picks the queue changes. With 'exit first' it equals the standard rule; with 'enter first' an enter and an exit arriving together swap places.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


# BASE QUESTION (optimal): Event-driven simulation with
# two queues
# FOLLOW-UP 4: The tie-break when the gate was idle
# differs in this version of the ...
def gate_pass_times(events, idle_first="exit"):
    # events[i] = (arrival time, "enter" or "exit")
    n = len(events)
    # people sorted by arrival, then by id
    order = sorted(range(n),
                   key=lambda i: (events[i][0], i))
    queues = {"enter": deque(), "exit": deque()}
    result = [0] * n
    t, i, prev, last_used = 0, 0, None, -10
    while i < n or queues["enter"] or queues["exit"]:
        if not queues["enter"] and not queues["exit"]:
            # nobody waits: jump the clock to the next
            # arrival
            t = max(t, events[order[i]][0])
            # a gap of idle time forgets the previous
            # action
            if t > last_used + 1:
                prev = None
        # everyone who arrived by now joins their line
        while i < n and events[order[i]][0] <= t:
            person = order[i]
            queues[events[person][1]].append(person)
            i += 1
        both = queues["enter"] and queues["exit"]
        if both:
            # FOLLOW-UP 4: idle tie-break set by
            # idle_first
            # tie: continue the direction used last second
            # (when idle, use idle_first)
            want = prev or idle_first
        else:
            want = "enter" if queues["enter"] else "exit"
        person = queues[want].popleft()
        result[person] = t
        prev, last_used = want, t
        t += 1
    return result
```

```
if __name__ == "__main__":
```

```
    # one enter and one exit arrive together: exit first
    ev = [(0, "enter"), (0, "exit")]
    assert gate_pass_times(ev) == [1, 0]
    # with "enter" winning the idle tie it swaps
    assert gate_pass_times(ev, "enter") == [0, 1]
    # the same direction continues while people keep
    # coming
    ev2 = [(0, "enter"), (0, "enter"), (1, "exit")]
    assert gate_pass_times(ev2) == [0, 1, 2]
    # a long idle gap resets the state
    ev3 = [(0, "enter"), (10, "enter"), (10, "exit")]
    assert gate_pass_times(ev3) == [0, 11, 10]
    # huge timestamps cost nothing extra
    far = [(10 ** 9, "enter"), (10 ** 9, "exit")]
    assert gate_pass_times(far) == [10 ** 9 + 1, 10 ** 9]
```

NOTES FROM CANDIDATES

The clean implementation uses two queues (pending enters, pending exits) plus a prev_state variable; at each tick peek both queues, apply the four rules, advance, and update prev_state.
A naive tick-by-tick simulation walks every integer time unit from min to max timestamp; the expected optimization is to jump directly to the next event timestamp in the input, dropping complexity to O(n).
The optimization has to carry the "prior moment" state across empty gaps correctly (a 100-tick gap still counts as prev_state = none).
Walk through one or two examples on the whiteboard before coding — interviewers in this family prefer candidates who fully verbalize the precedence rules before writing.

PREPARATION

Translate the four priority rules into an explicit state machine (prev_state in {enter, exit, none}) before writing any code.
Practice scheduling problems that pair a per-tick simulation with an event-driven optimization (CPU scheduler, traffic light, calendar conflict resolver).
Stress-test corner cases: same timestamp containing both an enter and an exit for the same person, all-enters or all-exits batches, and very large gaps between two events.

MEDIUM | 1Point3Acres | phone-screen, onsite-coding | 15 of 165

Fence Painting Minimum Operations (Gemini Team)

ASKED 2026-04-27 | 166 DAYS AGO | LAST 6 MONTHS

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 196/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-04-27 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/fence-painting-min-ops

QUESTION

EXAMPLES

```
n = 5, a = [2, 2, 1, 2, 1]
Optimal:
  1) Horizontal stroke at h=1 across [1..5]
      (covers row 1 across whole fence)
  2) Horizontal stroke at h=2 across [1..2]
  3) Vertical stroke at plank 4 (height 2 still
      missing row 2)
Optimal answer: 3.
```

APPROACH

Drill The canonical largest-rectangle-in-histogram problem — the geometric setup is the same.
Practice the recursive painter pattern on small inputs by hand; mistakes around the band height (min - base) are common.
Be ready for the follow-up: "the brush has width W instead of 1" — extends to bounded horizontal width.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether vertical strokes paint one plank fully, whether horizontal strokes must cover consecutive planks at one height, and the sizes involved.

BRUTE FORCE TO SAY OUT LOUD

Try all combinations of strokes. Exponential.

OPTIMAL IDEA

Divide and conquer on the minimum height: for a range with base height h, painting every plank vertically costs the number of planks; otherwise paint one horizontal band up to the minimum height m (cost 1) and recurse on the segments above m, split where planks are exactly m. The answer is the minimum of the two. O(n^2) worst case, O(n log n) with a sparse table or a min-stack for range minimum queries.

DRY-RUN THESE CASES

The example giving 3. All equal heights (1). Strictly increasing heights. A single plank.

LIKELY FOLLOW-UPS

A brush of width W, or return the strokes.

PITFALLS

Forgetting the vertical option, so a tall single plank is overcounted. Off-by-one on the band height.

HOW TO THINK ABOUT IT

The shortest plank in a range decides the shape: a horizontal band along the bottom, up to that plank's height, is free of regret because every plank in the range needs it. That splits the range at the shortest planks, so recurse on the pieces above the band. The other choice for a range is to paint every plank vertically. Take whichever is cheaper.

Basis: Codeforces 448C, Painting Fence. Strokes: a vertical stroke paints one whole plank; a horizontal stroke paints one row across consecutive planks that all reach that height.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def paint(l, r, base):
    if l > r:
        return 0
    m = min(height[l:r + 1])
    vertical = r - l + 1
    horizontal = m - base
    for part in split_at_height(l, r, m):
        horizontal += paint(part.l, part.r, m)
    return min(vertical, horizontal)
```

TIME	SPACE
O(n^2)	O(n)
worst case	recursion

WHY IT IS SLOW

Finding the minimum by scanning makes a sorted or constant fence quadratic, O(n^2). A sparse table for range-minimum gives O(n log n).

OPTIMAL SOLUTION · Same recursion with a sparse table for range minimum

TIME	SPACE
O(n log n)	O(n log n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The horizontal brush is only W planks wide.

A band over a range needs ceil(width / W) strokes per row instead of one, so the band cost becomes (m - base) * ceil(len / W). The vertical option and the splitting are unchanged.

FOLLOW-UP 2 Return the strokes, not just the count.

Record which option won in each range and rebuild the list by walking the recursion again: horizontal bands as (row, l, r), vertical strokes as (plank).

FOLLOW-UP 3 Is it the same as largest rectangle in a histogram?

It shares the idea of splitting at the minimum (a Cartesian tree on the heights), but the objective differs: here you minimise strokes, there you maximise area. **Cost:** the fence recursion is O(n log n) with a sparse table (O(n^2) worst case with a plain scan); the histogram problem has an O(n) stack solution.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def sparse_table(a):
    # table[j][i] = index of the smallest plank in a[i : i
    # + 2^j]
    table = [list(range(len(a)))]
    j = 1
    while (1 << j) <= len(a):
        prev, row = table[-1], []
        for i in range(len(a) - (1 << j) + 1):
            x, y = prev[i], prev[i + (1 << (j - 1))]
            row.append(x if a[x] <= a[y] else y)
        table.append(row)
        j += 1
    return table


# FOLLOW-UP 2: Return the strokes, not just the count.
def paint_strokes(a, width=None):
    # returns (number of strokes, the list of strokes)
    n = len(a)
    if n == 0:
        return 0, []
    table = sparse_table(a)

    def argmin(l, r):
        # smallest plank in a[l..r] in O(1)
        k = (r - l + 1).bit_length() - 1
        x, y = table[k][l], table[k][r - (1 << k) + 1]
        return x if a[x] <= a[y] else y

    def solve(l, r, base):
        # paint planks l..r whose bottom `base` rows are
        # done
        if l > r:
            return 0, []
        m = argmin(l, r)
        size = r - l + 1
        # a band of rows over the whole range needs one
        # stroke per row (or per `width` planks)
        per_row = 1
        if width is not None:
            per_row = -(-size // width)
        band = (a[m] - base) * per_row
        lc, ls = solve(l, m - 1, a[m])
        rc, rs = solve(m + 1, r, a[m])
        horizontal = band + lc + rc
        # or paint every plank by itself, top to bottom
        if size <= horizontal:
            planks = range(l, r + 1)
            return size, [("vertical", i) for i in planks]
        rows = [("horizontal", h, l, r)
                for h in range(base + 1, a[m] + 1)]
        return horizontal, rows + ls + rs

    return solve(0, n - 1, 0)


# BASE QUESTION (optimal): Same recursion with a sparse
# table for range minimum
def paint(a, width=None):
    # FOLLOW-UP 1: width= limits the horizontal brush
    return paint_strokes(a, width)[0]


if __name__ == "__main__":
    # the example: 3 strokes
    assert paint([2, 2, 1, 2, 1]) == 3
    assert paint([]) == 0
    assert paint([3]) == 1
    # a flat fence is one stroke per row
    assert paint([4, 4, 4, 4]) == 4
    # tall thin planks are cheaper to paint upright
    assert paint([5, 0, 5]) == 2
    count, strokes = paint_strokes([2, 2, 1, 2, 1])
    assert count == len(strokes) == 3
```

```
# a narrow brush needs several strokes per row
assert paint([2, 2, 2, 2], width=2) == 4
assert paint([2, 2, 2, 2], width=4) == 2
```

NOTES FROM CANDIDATES

Classic recursive divide-and-conquer: for range [l..r] with base height h:
Option A: paint every plank vertically -> cost r - l + 1.
Option B: paint a horizontal band of height min - h, then recurse on the sub-ranges above the band split by planks at height min.
Take the minimum.
Equivalent to Cartesian-tree DP; runs in O(N log N) with min-stack or sparse table, or O(N²) with the recursive form.
Verbalize the recursion's correctness: the band optimally covers all planks >= min in the range, then each "taller column block" is solved independently.

PREPARATION

Drill The canonical largest-rectangle-in-histogram problem — the geometric setup is the same.
Practice the recursive painter pattern on small inputs by hand; mistakes around the band height (min - base) are common.
Be ready for the follow-up: "the brush has width W instead of 1" — extends to bounded horizontal width.

MEDIUM | 1Point3Acres | onsite-coding | 16 of 165

Gold Chain Split into Two Equal Halves

ASKED 2026-04-21 | 172 DAYS AGO | LAST 6 MONTHS

STUDY: READ **NO LEETCODE FREQUENCY** **PRIORITY 197/224**

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-04-21 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/gold-chain-split-equal

QUESTION

Onsite coding interview 1: given a gold chain represented by an array of segment weights, remove exactly one segment and check whether the remaining segments — when reconnected — can be cut once more to give two halves of equal total weight.
Follow-up: enumerate all valid (remove, cut) pairs.SWEarrayhashmapmediumFrequencySingle reportLast asked2026-04-21Stageonsite-coding

APPROACH

Drill The equal-subset-sum and partition-to-k-equal-sum-subsets problems are the standard drill partners.
Practice enumerating all valid cut positions, not just one — interviewers commonly add the follow-up after the boolean version works.
Watch the boundary: remove + cut should not yield an empty side.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether removing a segment keeps the rest as a chain joined end to end, whether the cut after removal must leave two non-empty parts, and whether to return a boolean, one answer, or all valid pairs.

BRUTE FORCE TO SAY OUT LOUD

For each removed index, rebuild the array and try every cut with prefix sums. O(n^2).

OPTIMAL IDEA

Compute the total S and prefix sums P. Removing index r leaves total S - a[r], which must be even; the target is half = (S - a[r]) / 2. In the remaining chain a cut is valid when some non-empty prefix sums to half. A prefix that stops before r has sum P[j], and one that includes the segments after r has sum P[j] - a[r]. So for each r check whether half appears among the prefix sums before r, or whether half + a[r] appears among the prefix sums after r (keep a hash set of prefix sums seen so far, and one for those still ahead). Boolean answer in O(n); listing all valid (remove, cut) pairs is output-bound, up to O(n^2).

DRY-RUN THESE CASES

A chain of two segments, a removal at the first or last index, a total that becomes odd, equal weights.

LIKELY FOLLOW-UPS

Enumerate all valid (remove, cut) pairs, or allow removing k segments.

PITFALLS

Allowing an empty half. Forgetting the shift of indices after the removed segment.

HOW TO THINK ABOUT IT

After removing segment r the target half is (S - a[r]) / 2, and a cut means some prefix of the remaining chain has exactly that weight. A prefix of the remaining chain is either an ordinary prefix of the original array (stops before r) or an original prefix minus a[r] (passes over r). Each is one value to look up in a hash of prefix sums, so every r costs O(1).

Basis: Written; prefix sums with a hash lookup (like LeetCode 724 and 560). Assumed rule (confirm it): remove exactly one segment, reconnect the remaining chain end to end, then cut it once into two non-empty parts of equal total weight.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(w):
    for r in range(len(w)):
        chain = w[:r] + w[r + 1:]
        half, run = sum(chain) / 2, 0
        for x in chain:
            run += x
            if run == half:
                return True
    return False
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

n removals, each rebuilt and scanned: O(n^2). Prefix sums with a lookup of the needed prefix value answer each removal in O(1).

OPTIMAL SOLUTION · Prefix sums with first and last occurrence maps

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 List every valid (removed segment, cut position) pair.

The answer itself can be quadratic, so a simple loop is acceptable. With positive weights prefix sums are strictly increasing, so each target has at most one cut position and the listing is O(n) after the hash lookups; with zeros or negatives a value can repeat, so keep a list of indices per prefix value.

FOLLOW-UP 2 The chain is a circle (cut anywhere).

Then a cut is two cut points on the circle and the removed segment just shortens it; use the circular window idea (duplicate the array and slide a window whose sum is half).

FOLLOW-UP 3 Remove k segments instead of one.

The remaining total depends on which k you remove, which becomes a subset-sum style search; ask for the limits before promising a fast solution.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def prefix_sums(a):
    # P[j] = sum of the first j segments
    P = [0]
    for x in a:
        P.append(P[-1] + x)
    return P


# BASE QUESTION (optimal): Prefix sums with first and last
# occurrence maps
def gold_chain(a):
    # remove exactly one segment, then cut once into
    # two non-empty halves of equal weight
    n = len(a)
    if n < 3:
        return False
    P = prefix_sums(a)
    total = P[-1]
    # first and last position of every prefix sum (cuts
    # sit between segments, so positions 1..n-1)
    first, last = {}, {}
    for j in range(1, n):
        first.setdefault(P[j], j)
        last[P[j]] = j
    for r in range(n):
        left_over = total - a[r]
        if left_over % 2:
            continue
        half = left_over // 2
        # cut before the removed segment: P[j] == half
        if half in first and first[half] <= min(r, n - 2):
            return True
        # cut after it: P[j] - a[r] == half
        if half + a[r] in last and last[half + a[r]] > r:
            return True
    return False


# FOLLOW-UP 1: List every valid (removed segment, cut
# position) pair.
def valid_pairs(a):
    # follow-up: every (removed index, cut position) pair;
    # the answer can be quadratic, so a loop is fine
    pairs = []
    for r in range(len(a)):
        rest = a[:r] + a[r + 1:]
        total, run = sum(rest), 0
        # cut after `cut` segments of the reconnected
        # chain
        for cut in range(1, len(rest)):
            run += rest[cut - 1]
            if run * 2 == total:
                pairs.append((r, cut))
    return pairs


if __name__ == "__main__":
    # remove the middle 1, then cut 5 | 5
    assert gold_chain([5, 1, 5])
    assert gold_chain([2, 7, 2])
    assert not gold_chain([1, 2, 3])
    assert not gold_chain([1, 1])
    assert not gold_chain([1, 2, 4])
    assert (1, 1) in valid_pairs([1, 2, 1])
    # both methods agree on many small chains
    import itertools
    for chain in itertools.product(range(1, 5), repeat=5):
        assert gold_chain(list(chain)) == bool(
            valid_pairs(list(chain)))
```

NOTES FROM CANDIDATES

Precompute prefix sums; for each candidate removed index r, the remaining total is S - a[r]. If that is odd, skip. Otherwise check if there is a split point achieving (S - a[r]) / 2.
Use a hashmap from prefix-sum value to index for O(1) lookups -> overall O(N) for the boolean answer, O(N²) worst case for enumerating all pairs (output-bound).
Watch out for cut positions adjacent to the removed link — must still respect contiguous-chain semantics.

PREPARATION

Drill The equal-subset-sum and partition-to-k-equal-sum-subsets problems are the standard drill partners.
Practice enumerating all valid cut positions, not just one — interviewers commonly add the follow-up after the boolean version works.
Watch the boundary: remove + cut should not yield an empty side.

ASKED: OLDER THAN 6 MONTHS (10)

Hard (4)

HARD | IN APP LC 834 | 1Point3Acres | onsite-coding | 17 of 165

Tree Distance Sum (Re-root DP)

ASKED 2026-01-19 | 264 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 30.5 | 30 DAYS 0 | PRIORITY 123/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #834)

LeetCode match: LC 834 Sum of Distances in Tree

Frequency: Single report | Last asked: 2026-01-19 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/tree-distance-sum-reroot

QUESTION

Onsite coding round 1: given an undirected tree on N nodes, return for every node the sum of distances to all other nodes. Equivalent to LC 834. Interviewer expects baseline O(n²) DFS followed by the O(n) re-root DP.

Input: undirected tree with N nodes and N-1 edges.
Output: array ans where ans[u] is the sum of shortest-path distances from u to every other node.
Walk through baseline (BFS/DFS from every node, O(n²)) before optimizing.
Final solution should be O(n) via two-pass re-root DP.

QUESTION

EXAMPLES

```
Edges: [[0,1],[0,2],[2,3],[2,4],[2,5]]
ans:   [8, 12, 6, 10, 10, 10]
```

APPROACH

Drill the canonical sum-of-distances-in-tree problem until you can derive the re-root formula on a whiteboard without notes.
Practice both an iterative and a recursive version; deep recursion can blow the stack on chain-like trees.
Be prepared to explain why re-rooting is correct (proof by induction on the subtree boundary).

HOW TO THINK ABOUT IT

Running a BFS from every node costs O(n^2). Notice that moving the root from a parent p to its child v changes every distance by exactly one: the nodes inside v's subtree get closer by 1, all the others get farther by 1. So compute the answer for one root, then derive each child's answer from its parent's in O(1) using the subtree sizes.

Basis: LeetCode 834, Sum of Distances in Tree.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n, adj):
    ans = [0] * n
    for s in range(n):
        dist = bfs(adj, s)
        ans[s] = sum(dist)
    return ans
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

n BFS runs of O(n) each, O(n^2). Moving the root across one edge changes every distance by exactly 1, so two passes over the tree give all answers in O(n).

OPTIMAL SOLUTION · Two passes: subtree sizes, then re-root

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why is the re-root formula correct?

Compare the distance from every node w to p and to its child v. If w is inside v's subtree the path to p goes through v, so dist(w, p) = dist(w, v) + 1. If w is outside it, dist(w, v) = dist(w, p) + 1. There are size[v] nodes of the first kind and n - size[v] of the second, so ans[v] = ans[p] - size[v] + (n - size[v]).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


def build(n, edges):
    adj = [[] for _ in range(n)]
    for a, b in edges:
        adj[a].append(b)
        adj[b].append(a)
    return adj


# BASELINE (say it first): BFS from every node
def distance_sums_bfs(n, edges):
    # the baseline to say first: a BFS from every node,
    # O(n^2)
    adj, out = build(n, edges), []
    for s in range(n):
        dist, queue = {s: 0}, deque([s])
        while queue:
            u = queue.popleft()
            for v in adj[u]:
                if v not in dist:
                    dist[v] = dist[u] + 1
                    queue.append(v)
        out.append(sum(dist.values()))
    return out


# BASE QUESTION (optimal): Two passes: subtree sizes, then
# re-root
def tree_distance_sums(n, edges):
    if n == 0:
        return []
    adj = build(n, edges)
    # order: parents before children (no recursion)
    parent, order = [-1] * n, [0]
    for u in order:
        for v in adj[u]:
            if v != parent[u]:
                parent[v] = u
                order.append(v)
    # size[u]: nodes in u's subtree
    # inside[u]: distances from u to its own subtree
    size, inside = [1] * n, [0] * n
    for u in reversed(order):
        p = parent[u]
        if p >= 0:
            size[p] += size[u]
            inside[p] += inside[u] + size[u]
    # the root's answer is already complete
    ans = [0] * n
    ans[0] = inside[0]
    # moving the root from p to child u: the size[u] nodes
    # below get 1 closer, the other n - size[u] get 1
    # farther
    for u in order[1:]:
        ans[u] = ans[parent[u]] + n - 2 * size[u]
    return ans


if __name__ == "__main__":
    edges = [[0, 1], [0, 2], [2, 3], [2, 4], [2, 5]]
    want = [8, 12, 6, 10, 10, 10]
    assert tree_distance_sums(6, edges) == want
    assert distance_sums_bfs(6, edges) == want
    assert tree_distance_sums(1, []) == [0]
    assert tree_distance_sums(0, []) == []
    # a chain of 100000 nodes: no recursion trouble
    n = 100000
    chain = [(i, i - 1) for i in range(1, n)]
    first = tree_distance_sums(n, chain)[0]
    assert first == n * (n - 1) // 2
```

NOTES FROM CANDIDATES

The interviewer explicitly liked the "baseline first, optimize later" structure — name the O(n²) and move on within the first ~10 minutes.
Two-pass technique to memorize:

Post-order DFS rooted at any node: compute subSize[u] and subSum[u] (sum of distances inside u's subtree). Recurrence: subSum[u] += subSum[v] + subSize[v].
Pre-order DFS doing re-root: when moving root from parent p to child v, ans[v] = ans[p] + (n - subSize[v]) - subSize[v].

Verbalize the geometric intuition for the re-root formula: moving root toward v shortens distance to the subSize[v] nodes inside v's subtree by 1 and lengthens the other n - subSize[v] by 1.

PREPARATION

Drill the canonical sum-of-distances-in-tree problem until you can derive the re-root formula on a whiteboard without notes.
Practice both an iterative and a recursive version; deep recursion can blow the stack on chain-like trees.
Be prepared to explain why re-rooting is correct (proof by induction on the subtree boundary).

HARD | 1Point3Acres | onsite-coding | 18 of 165

Babylon Tile-Stack Merge Game

ASKED 2025-12-29 | 285 DAYS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 187/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2025-12-29 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/babylon-stack-merge-game

QUESTION

Onsite NG round 1 (Munich office): implement a two-player tile-stack merge game ("Babylon") given the rules. Start state is 12 height-1 stacks of 4 colors (Y / W / G / B), 3 of each; a move places one stack on top of another under a constraint; the player who cannot move loses.

QUESTION

12 tiles initially, partitioned into 12 height-1 stacks.
4 colors: Y / W / G / B; exactly 3 tiles per color.
Two players alternate moves.
A move = pick two stacks and place one entirely on top of the other (merge).

Legal iff at least one of: (a) the two stacks have the same height, OR (b) their top-most tiles share the same color.
After merge: new height = sum of the two heights, new top color = color of the stack placed on top.

The player who has no legal move on their turn loses.
Implement the full game so it can be played out (legal-move detection, state transition, terminal check).

EXAMPLES

Start: 12 stacks of height 1, with tops Y Y Y W W W G G G B B B. A legal opening move: stack the first Y on the second Y (same color top), producing one height-2 stack of color Y plus 10 singletons.

APPROACH

Drill clean game-state implementations: e.g. Connect 4, Othello move generators, in 30 minutes.
Practice writing a generic minimax framework so you can plug in this game's legalMoves(state) and terminal(state) quickly.
Watch the merge invariant carefully: "same height OR same top color" — fail mode is forgetting the alternative branch.

HOW TO THINK ABOUT IT

Model a state as the list of stacks, each as (height, top colour). A legal move puts stack i on stack j when the heights are equal or the top colours are equal; the new stack has the summed height and the colour of the stack that was placed on top. The player with no legal move loses, so a state is winning when some move leads to a losing state. The order of stacks does not matter, so sort the list to share states in a cache.

Basis: Written for this question: a two-player impartial game (the player who cannot move loses), solved by memoised search over the multiset of stacks.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def wins(position):
    for i, j in legal_moves(position):
        nxt = merge(position, i, j)
        if not wins(nxt):
            return True  # opponent loses
    return False
```

TIME	SPACE
exponential	O(depth)

WHY IT IS SLOW

BRUTE FORCE

Explores the same positions many times, exponential. Sorting the stacks and caching each position's result visits every distinct position once.

OPTIMAL SOLUTION · Negamax with memoisation on the sorted stack tuple

TIME	SPACE
O(states * moves^2)	O(states)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How big is the real state space?

With 12 starting stacks the first position has at most 66 unordered pairs and the number of reachable multisets of (height, colour) stacks shrinks quickly because every merge removes a stack, so memoised search is feasible. In the interview build the clean state class, legal moves and play(move) first and add the solver only if there is time.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import itertools


class Babylon:
    # a stack is (height, colour of its top tile)
    def __init__(self, stacks=None):
        if stacks is None:
            # 12 tiles: Y, W, G, B three times each
            stacks = [(1, c) for c in "YWGB" * 3]
        self.stacks = list(stacks)

    def legal_moves(self):
        # put stack i on top of stack j
        moves = []
        for i, j in itertools.permutations(
                range(len(self.stacks)), 2):
            h1, c1 = self.stacks[i]
            h2, c2 = self.stacks[j]
            # same height, or the same colour on top
            if h1 == h2 or c1 == c2:
                moves.append((i, j))
        return moves

    def after(self, i, j):
        # the stacks after the move (the original is kept)
        (h1, c1), (h2, _) = self.stacks[i], self.stacks[j]
        rest = [s for k, s in enumerate(self.stacks)
                if k not in (i, j)]
        # heights add; the top colour is the moved stack's
        return rest + [(h1 + h2, c1)]

    def play(self, i, j):
        if (i, j) not in self.legal_moves():
            raise ValueError("illegal move")
        self.stacks = self.after(i, j)

    def is_over(self):
```

```
        # the player with no move loses
        return not self.legal_moves()


# BASE QUESTION (optimal): Negamax with memoisation on the
# sorted stack tuple
def wins(stacks):
    # does the player to move win with best play?
```

```
    cache = {}

    def solve(state):
        if state in cache:
            return cache[state]
        game = Babylon(state)
        result = False
        for i, j in game.legal_moves():
            nxt = tuple(sorted(game.after(i, j)))
            # a move to a position the opponent loses wins
            if not solve(nxt):
                result = True
                break
        cache[state] = result
        return result

    # sorted stacks: equal positions share one cache entry
    return solve(tuple(sorted(stacks)))


# PICK the winning move itself
def best_move(game):
    # pick a move that leaves the opponent lost, if any
    for i, j in game.legal_moves():
        if not wins(game.after(i, j)):
            return i, j
    moves = game.legal_moves()
    return moves[0] if moves else None


if __name__ == "__main__":
    # one stack: no moves, so the player to move loses
    assert Babylon([(1, "Y")]).is_over()
    assert not wins([(1, "Y")])
    # two equal stacks: one move ends the game, so we win
    assert wins([(1, "Y"), (1, "W")])
    g = Babylon([(1, "Y"), (1, "Y"), (1, "W")])
    assert (0, 1) in g.legal_moves()
    # play a whole game with the solver; the loser is
    # stuck
    while not g.is_over():
        g.play(*best_move(g))
    assert len(g.stacks) >= 1
    try:
        Babylon([(1, "Y"), (2, "W")]).play(0, 1)
```

```
        raise AssertionError("move should be illegal")
    except ValueError:
        pass
    # the real start has 12 stacks and up to 132 ordered
    # moves
    assert len(Babylon().legal_moves()) > 0
```

NOTES FROM CANDIDATES

This is closer to an implementation/simulation interview than a clever-algorithm problem — the interviewer wants a clean game state class, legal-move enumeration, and a play(move) API. Represent state as a List[Stack] where Stack = (height, topColor, fullSequence?). Whether you keep the full color sequence depends on whether the interviewer asks about "undo" or "re-color from top".

Add a minimax / negamax for "who wins from this state with optimal play" as the natural follow-up — branching factor is small (at most C(12, 2) = 66 initially, drops fast).

Reported as "too hard to finish coding in 45 minutes"; the interviewer gives hints throughout. Pacing matters.

PREPARATION

Drill clean game-state implementations: e.g. Connect 4, Othello move generators, in 30 minutes.

Practice writing a generic minimax framework so you can plug in this game's legalMoves(state) and terminal(state) quickly.

Watch the merge invariant carefully: "same height OR same top color" — fail mode is forgetting the alternative branch.

HARD | 1Point3Acres | phone-screen, onsite-coding | 19 of 165

Wordle-Style 5-Letter Minimum-Guess Strategy

ASKED 2025-12-15 | 299 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 42.2 | 30 DAYS 0 | PRIORITY 84/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #843 Guess the Word

LeetCode match: LC 843 Guess the Word (related)

Frequency: Single report | Last asked: 2025-12-15 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/wordle-min-guess-strategy

QUESTION

Phone screen coding: given a black-box oracle that tells you whether a specific letter is at a specific position in a hidden 5-letter word, design an algorithm to identify the word in as few oracle calls as possible. Follow-up assumes a dictionary of candidate words is available.

Hidden word: a 5-letter string from a..z.
Oracle: query(pos: int, letter: char) -> bool returns whether position pos (0-indexed) holds letter.
Return the hidden word.
Primary metric: minimize the number of query calls.

QUESTION

Brute-force baseline: 5 × 26 = 130 calls.
Follow-up

A dictionary of candidate 5-letter words is available; design the strategy to use bigram/letter-frequency information to cut the expected number of calls.

EXAMPLES

```
HiddenWord = "GRAPE"
query(0, 'A') -> false
query(0, 'G') -> true   // first letter found
...
```

APPROACH

Drill information-theoretic puzzles (egg drop, twenty questions) to internalize the entropy-split heuristic.
Practice maintaining a candidate set under positive/negative oracle feedback (filter on each query result).
Be ready with a one-liner on Wordle's known optimal first guess (SOARE / CRANE) for intuition; do not hard-code it.

HOW TO THINK ABOUT IT

Each call returns one bit, so you can never beat ceil(log2(number of candidates)) calls. Without a dictionary the best you can do is order the questions by likelihood and stop at the first yes for each position (and skip the 26th letter, because it is implied). With a dictionary, keep the list of words still possible and ask the (position, letter) question whose yes/no answer splits that list most evenly.

Basis: Written for this question; related to LeetCode 843, Guess the Word, but the oracle answers one position and one letter per call.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
word = ""
for i in range(5):
    for c in "abcdefghijklmnopqrstuvwxyz":
        if query(i, c):
            word += c
            break
```

TIME	SPACE
130 calls	O(1)

WHY IT IS SLOW

Always 130 calls. Asking likely letters first, skipping the implied last letter, or splitting a dictionary of candidates in half needs far fewer.

OPTIMAL SOLUTION · Frequency order, or entropy split when a dictionary is known

TIME	SPACE
at most 5 x 25 calls with... at most 5 x 25 calls without a dictionary; about log2(words) with one	**O(words)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What is the lower bound and when is it reached?

Every call returns at most one bit, so at least ceil(log2(candidates)) calls are needed. The entropy split reaches it only when a question can cut the candidates exactly in half; real dictionaries usually need a few more. A greedy scoring rule (closest to half) is enough to state; the interviewer mostly wants the entropy idea.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import string

# letters from most to least common in English words
BY_FREQUENCY = "etaoinshrdlcumwfgypbvkjxqz"


# BRUTE FORCE: 130 calls
def brute_force(query):
    # 130 calls at most: every position, every letter
    return "".join(
        next(c for c in string.ascii_lowercase
             if query(i, c))
        for i in range(5))


# BASE QUESTION (optimal): Frequency order, or entropy
# split when a dictionary is known
def by_frequency(query):
    # no dictionary: common letters first, stop at the
    # first
    # yes, and skip the 26th letter (it must be the one
    # left)
    calls, word = 0, []
    for i in range(5):
        for k, c in enumerate(BY_FREQUENCY):
            if k == 25:
                word.append(c)
                break
            calls += 1
            if query(i, c):
                word.append(c)
                break
    return "".join(word), calls


# FOLLOW-UP 1: What is the lower bound and when is it
# reached?
def split_score(words, i, c):
    # how evenly does asking (position i, letter c) split?
    yes = sum(w[i] == c for w in words)
    return min(yes, len(words) - yes)
```

```
# BASE QUESTION (optimal): Frequency order, or entropy
# split when a dictionary is known
```

```
def with_dictionary(query, dictionary):
    # keep the words that still fit every answer so far
    words, calls = list(dictionary), 0
    while len(words) > 1:
        options = {(i, w[i]) for w in words
                   for i in range(5)}
        # ask the question that cuts the list closest to
        # half
        i, c = max(options, key=lambda o: split_score(
            words, o[0], o[1]))
        calls += 1
        hit = query(i, c)
        words = [w for w in words if (w[i] == c) == hit]
    return words[0], calls


if __name__ == "__main__":
    def oracle(word):
        return lambda i, c: word[i] == c

    secret = "grape"
    assert brute_force(oracle(secret)) == secret
    word, calls = by_frequency(oracle(secret))
    assert word == secret and calls <= 125
    words = ["grape", "grade", "trade", "crane", "plane",
             "slate", "stare", "share"]
    for target in words:
        ask = oracle(target)
        found, used = with_dictionary(ask, words)
        assert found == target
        # about log2(8) = 3 questions suffice; allow a few
        # more
        assert used <= 6
    # lower bound: one bit per call, so ceil(log2(8)) = 3
    # calls
    assert min(with_dictionary(oracle(w), words)[1]
               for w in words) >= 3
```

NOTES FROM CANDIDATES

Without the dictionary, query positions in order; per position, query letters in descending frequency (e, t, a, o, i, n, ...) and stop as soon as one returns true.
With the dictionary, maintain a candidate set; at each step pick the (position, letter) query whose true/false outcome splits the candidate set most evenly (entropy maximization).
Mention information theory: each query yields <= 1 bit, so the absolute lower bound on calls is ceil(log2(|candidates|)).
Don't waste minutes on a closed-form optimum — the interviewer mostly wants you to articulate the entropy heuristic and pick one reasonable scoring function.

PREPARATION

Drill information-theoretic puzzles (egg drop, twenty questions) to internalize the entropy-split heuristic.
Practice maintaining a candidate set under positive/negative oracle feedback (filter on each query result).
Be ready with a one-liner on Wordle's known optimal first guess (SOARE / CRANE) for intuition; do not hard-code it.

HARD | 1Point3Acres | onsite-coding | 20 of 165

Find All Bad Pairs Using runTest Oracle

ASKED 2025-11-27 | 317 DAYS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 188/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2025-11-27 | Roles: SWE, RS

Original: https://www.1point3acres.com/interview/problems/company/google/find-bad-pairs-with-oracle

QUESTION

PhD intern coding round 2: given a black-box oracle **`runTest(S)`** that returns **`true`** iff a subset **`S`** contains no bad pair, identify all bad pairs across N test items with as few oracle calls as possible.

Items t_1, ..., t_N are given.
Oracle: runTest(S: Set[Item]) -> bool returns true iff S contains zero bad pairs; otherwise false.
Output: every bad pair (t_i, t_j).
Minimize total oracle calls.

EXAMPLES

```
N=4, bad pairs = {(1,2)}.
runTest({1,2,3,4}) -> false -> at least one bad pair
    somewhere.
runTest({1,3,4})   -> true  -> 2 is in every bad pair
    containing items from this set.
... binary search to isolate.
```

APPROACH

Read the Wikipedia article on group testing and Dorfman's two-stage scheme.
Drill recursive binary partitioning on a candidate set with positive/negative oracle feedback.
Have a back-of-envelope analysis ready: "Total calls O(K log N) for K bad pairs and N items."

HOW TO THINK ABOUT IT

Testing every pair costs N(N-1)/2 calls. A single call on a whole set answers 'is there any bad pair inside', so you can discard good sets fast and binary-search for the culprit inside a bad one. Add the tests one at a time to groups known to be clean: if a group plus the new test fails, binary search the group for a partner; otherwise the new test joins it.

Basis: Adaptive group testing; the same method as the 'bad pairs with runTest' question in the PracHub set.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
bad = []
for i in range(n):
    for j in range(i + 1, n):
        if not runTest({i, j}):
            bad.append((i, j))
```

TIME	SPACE
O(N^2) calls	O(1)

WHY IT IS SLOW

Always N(N - 1) / 2 calls. Testing whole groups and binary searching a failing group finds each bad pair in about log N calls.

OPTIMAL SOLUTION · Group the tests and binary search for partners

TIME	SPACE
O(K log N + N * G) about calls (K bad pairs, G groups)	O(N)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How many calls are needed in the best case and the worst case?

With no bad pairs it takes N - 1 calls, one per test after the first. With K bad pairs each one costs about log N calls to locate, so roughly K log N plus the cost of building clean groups. The brute force is always N(N-1)/2, which is far larger as soon as bad pairs are rare.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import itertools


# BRUTE FORCE: ask about every pair
def bad_pairs_brute(items, run_test):
    # every pair costs a call: N * (N - 1) / 2 calls
    pairs = itertools.combinations(items, 2)
    return {(a, b) for a, b in pairs
            if not run_test({a, b})}


def first_partner(group, t, run_test):
    # binary search: the shortest prefix of the group that
    # fails together with t; its last member is a partner
    lo, hi = 1, len(group)
    while lo < hi:
        mid = (lo + hi) // 2
        if run_test(set(group[:mid]) | {t}):
            lo = mid + 1
        else:
            hi = mid
    return group[lo - 1]


def partners(group, t, run_test):
    # all members of the group that are bad with t
    rest, found = list(group), []
    while rest and not run_test(set(rest) | {t}):
        x = first_partner(rest, t, run_test)
        found.append(x)
        # take it out and test the others again
        rest.remove(x)
    return found


# BASE QUESTION (optimal): Group the tests and binary
# search for partners
def find_bad_pairs(items, run_test):
    # groups of items that pass together (no bad pair
    # inside)
    groups, pairs = [], set()
    for t in items:
        placed = False
        for group in groups:
            found = partners(group, t, run_test)
            for x in found:
                pairs.add((min(x, t), max(x, t)))
            # t joins the first group with no partner for
            # it
            if not found and not placed:
                group.append(t)
                placed = True
        if not placed:
            groups.append([t])
    return pairs


if __name__ == "__main__":
    def make_oracle(bad):
        calls = [0]

        def run_test(subset):
            calls[0] += 1
            ordered = sorted(subset)
            pairs = itertools.combinations(ordered, 2)
            return not any(p in bad for p in pairs)
        return run_test, calls

    bad = {(3, 17), (5, 29)}
    run, calls = make_oracle(bad)
    assert find_bad_pairs(list(range(30)), run) == bad
    # far fewer than the 435 calls of the brute force
    assert calls[0] < 435 // 2
    # no bad pairs: about one call per item
    run, calls = make_oracle(set())
    assert find_bad_pairs(list(range(30)), run) == set()
    assert calls[0] <= 30
    run, _ = make_oracle({(1, 2)})
    assert bad_pairs_brute([1, 2, 3, 4], run) == {(1, 2)}
```

NOTES FROM CANDIDATES

Standard "group testing" / Dorfman testing problem. Walk through the analogy with COVID pooled tests for intuition. Algorithm sketch:

NOTES FROM CANDIDATES

Test the full set. If true, no bad pairs.
Otherwise, binary-search to find one bad pair by partitioning the set and testing halves.
Remove the items that participate in the located bad pair; repeat.

Tighter bound: with up to K bad pairs, total queries are O(K log N) using adaptive group testing.
A naive $O(N^2)$ pairwise scheme works but the interviewer expects you to beat it with adaptive splitting.
Verbalize correctness: each binary-search step rules out half the candidates; you can always reduce the search space until exactly one bad pair is isolated.

PREPARATION

Read the Wikipedia article on group testing and Dorfman's two-stage scheme.
Drill recursive binary partitioning on a candidate set with positive/negative oracle feedback.
Have a back-of-envelope analysis ready: "Total calls O(K log N) for K bad pairs and N items."

Medium (6)

MEDIUM | 1Point3Acres | onsite-coding | 21 of 165

Sum of Good Subarrays (Adjacent Diff ±1)

ASKED 2026-02-08 | 244 DAYS AGO | OLDER

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 204/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-02-08 | Roles: MLE, SWE

Original: https://www.1point3acres.com/interview/problems/company/google/good-subarrays-diff-one

QUESTION

MLE L5 coding round: sum over all contiguous subarrays whose elements form a strictly monotonic ±1 step sequence (every adjacent pair differs by exactly +1, OR every adjacent pair differs by exactly -1). Required time complexity is O(N).

QUESTION

Input: integer array arr of length N.
A subarray is good if its consecutive differences are either all +1 (monotone increasing by 1) or all -1 (monotone decreasing by 1).
Singleton subarrays are always good.
Output: the sum of element-sums across all good subarrays (each good subarray contributes the sum of its elements once).
Required: O(N) time.

EXAMPLES

```
arr = [3, 5, 6, 7, 6]
```

Good subarrays

```
  singletons:           [3], [5], [6], [7], [6]
  monotone +1 runs:     [5, 6], [6, 7], [5, 6, 7]
  monotone -1 runs:     [7, 6]
Not good: [3, 5] (diff 2), [6, 7, 6] (mixes +1 then
    -1).
```

APPROACH

Practice the "contribution-per-index" pattern: the sum-of-subarray-minimums and sum-of-subsequence-widths problems both use the same technique.
Practice splitting an array into maximal monotone-step runs, then computing per-run contributions in O(1) amortized using prefix sums of element values.
Sanity-check with arr = [1, 2, 3] and arr = [3, 2, 1] by hand — both should sum to 20.

HOW TO THINK ABOUT IT

A good subarray is a stretch where every step is +1 or every step is -1, so every good subarray ending at index i lies inside the current run. Instead of listing subarrays, keep for each direction the total of all suffix sums inside the run: extending a run of length L by a new element x adds (L + 1) * x to that total. Both directions can be updated in O(1), and the singleton is counted once.

Basis: Written for this question (a run-length DP in the style of LeetCode 2262, Total Appeal of A String).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(a):
    total = 0
    for i in range(len(a)):
        for j in range(i, len(a)):
            part = a[i:j + 1]
            if is_good(part):
                total += sum(part)
    return total
def is_good(part):
    pairs = zip(part, part[1:])
    steps = {y - x for x, y in pairs}
    return steps <= {1} or steps <= {-1}
```

BRUTE FORCE

TIME	SPACE
O(n^2) or O(n^3)	O(1)

WHY IT IS SLOW

O(n^2) subarrays (O(n^3) with the sums). Run totals per direction update in O(1) per element, so one pass is O(n).

OPTIMAL SOLUTION · Two running run totals

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why is the singleton subtracted?

A one-element subarray [x] is both an increasing and a decreasing run of length 1, so it appears in both running totals. Subtracting x once at each index keeps it counted exactly once. A subarray of length 2 or more can only be in one total because its step is +1 or -1, not both.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Two running run totals
def good_subarray_sum(a):
    # a good subarray has all steps +1 or all steps -1.
    # For each index keep, per direction, the sum of the
    # sums of all good subarrays that END here.
    total = 0
    up_sum = up_len = down_sum = down_len = 0
    for i, x in enumerate(a):
        step = x - a[i - 1] if i else None
        if step == 1:
            # extend the +1 run: every old subarray grows
            # by
            # x, and [x] alone is new: (len + 1) * x in
            # all
            up_sum += (up_len + 1) * x
            up_len += 1
        else:
            up_sum, up_len = x, 1
        if step == -1:
            down_sum += (down_len + 1) * x
            down_len += 1
        else:
            down_sum, down_len = x, 1
        # [x] is in both totals: count it once
        total += up_sum + down_sum - x
    return total


# BRUTE FORCE (checker)
def good_subarray_sum_brute(a):
    # check every subarray: the oracle for the demo
    total = 0
    for i in range(len(a)):
        for j in range(i, len(a)):
            steps = {a[k + 1] - a[k] for k in range(i, j)}
            if steps <= {1} or steps <= {-1}:
                total += sum(a[i:j + 1])
    return total


if __name__ == "__main__":
    arr = [3, 5, 6, 7, 6]
    # singletons 27 + [5,6] 11 + [6,7] 13 + [5,6,7] 18 +
    # [7,6] 13
    assert good_subarray_sum(arr) == 82
```

```
    assert good_subarray_sum([]) == 0
    assert good_subarray_sum([4]) == 4
    # the O(n) answer matches the brute force everywhere
    import itertools
    for n in range(7):
        every = itertools.product([1, 2, 3, 4], repeat=n)
        for a in every:
            assert good_subarray_sum(list(a)) == (
                good_subarray_sum_brute(list(a)))
```

NOTES FROM CANDIDATES

Walk the array maintaining two run lengths: upRun (current trailing run of +1 steps) and downRun (current trailing run of -1 steps). At index i, only one of them is nonzero (the other resets to 1).
Each index i ends upRun + downRun - 1 good subarrays (subtracting the double-counted singleton). For each ending position, contribute the running prefix-sum tail of the active run.
Multiple candidates report getting stuck — verbalize the "contribution per index" framing out loud before coding.
Easy to mis-handle the reset boundary; double-check with a 2-element example before writing the loop.

PREPARATION

Practice the "contribution-per-index" pattern: the sum-of-subarray-minimums and sum-of-subsequence-widths problems both use the same technique.
Practice splitting an array into maximal monotone-step runs, then computing per-run contributions in O(1) amortized using prefix sums of element values.
Sanity-check with arr = [1, 2, 3] and arr = [3, 2, 1] by hand — both should sum to 20.

MEDIUM | IN APP LC 703 | DESIGN-STYLE (skippable) | 1Point3Acres | onsite-coding | 22 of 165

★ TOP 75: rank 68 in the Medium and Hard priority list

★ Streaming Insert + Find K-th Largest

ASKED 2026-02-04 | 248 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 32.6 | 30 DAYS 0 | PRIORITY 117/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: your app's interview approach (LeetCode #703)

LeetCode match: LC 703 Kth Largest Element in a Stream

Frequency: Single report | Last asked: 2026-02-04 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/insert-find-kth-largest

QUESTION

EXAMPLES

```
insert(3)
insert(3)
insert(2)
findLargest(0) -> 3
findLargest(1) -> 3
findLargest(2) -> 2
```

APPROACH

Sketch the size-augmented BST node (left subtree count + duplicate count) on paper before the interview.
Practice the Fenwick-tree order-statistics trick (find k-th by binary search on prefix sums).
Be ready to defend the chosen data structure: balanced BST is clean but verbose; Fenwick is short but assumes bounded values.

HOW TO THINK ABOUT IT

If k can change from query to query you need every value, in a structure that supports rank queries; if k is fixed you only need the k largest, and a min-heap of size k gives the answer at its root. Ask which of the two it is: it decides everything.

Basis: LeetCode 703, Kth Largest Element in a Stream, generalized so k is passed to each query (0-indexed in the examples).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
items = []
def insert(x):
    items.append(x)
def find_largest(k):
    ordered = sorted(items, reverse=True)
    return ordered[k]
```

TIME	SPACE
O(n log n) per query	O(n)

BRUTE FORCE

WHY IT IS SLOW

Every query re-sorts the whole history, O(n log n). A sorted list with binary search makes each query O(1) after an O(log n) search plus shift; for a fixed k a size-k heap is O(log k).

OPTIMAL SOLUTION · Sorted list with bisect (k chosen per query)

TIME	SPACE
O(log n) search + O(n) shift per insert, O(1) query	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if values can also be deleted?

The heap can no longer answer because removing an arbitrary element is O(k). Keep a sorted structure that supports delete: a balanced BST or sorted container with order statistics, or a Fenwick tree over compressed values (add -1 to delete). Both give O(log n) insert, delete and k-th.

FOLLOW-UP 2 What is the trade-off between the two designs?

The heap is the smallest and fastest when k is fixed and small (O(log k), O(k) memory) but cannot change k or delete. The sorted list answers any k and is simplest, at O(n) memory and a linear shift per insert. Choose from the requirements, and say which assumption you made.

FOLLOW-UP 3 Values can also be deleted.

A heap cannot delete an arbitrary value efficiently. Keep a sorted structure: a sorted list with bisect (O(n) per delete because of shifting) or a balanced tree / Fenwick tree over compressed values (O(log n) for insert, delete and k-th).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from bisect import bisect_left, insort


# BASE QUESTION (optimal): Sorted list with bisect (k
# chosen per query)
# FOLLOW-UP 1, 3: What if values can also be deleted?
class StreamKth:
    """Any k, with deletes: a sorted list."""

    def __init__(self):
        self.a = []

    def insert(self, x):
        # keep the list sorted: O(log n) search, O(n)
```

```
        # shift
        insort(self.a, x)

    # FOLLOW-UP 1, 3: values can also be deleted
    def delete(self, x):
        # remove one copy of x if present
        i = bisect_left(self.a, x)
        if i < len(self.a) and self.a[i] == x:
            del self.a[i]
            return True
        return False

    def find_largest(self, k):
        # k = 0 is the largest value
        if 0 <= k < len(self.a):
            return self.a[-1 - k]
        return None


# FOLLOW-UP 2: What is the trade-off between the two
# designs?
class FixedKth:
    """Fixed k, inserts only: a min-heap of the best k."""

    def __init__(self, k):
        self.k, self.heap = k, []

    def insert(self, x):
        heapq.heappush(self.heap, x)
        # keep only the k largest values
        if len(self.heap) > self.k:
            heapq.heappop(self.heap)

    def kth_largest(self):
        # the smallest of the k largest
        if len(self.heap) < self.k:
            return None
        return self.heap[0]


if __name__ == "__main__":
    s = StreamKth()
    for x in (3, 3, 2):
        s.insert(x)
    top3 = [s.find_largest(k) for k in range(3)]
    assert top3 == [3, 3, 2]
    assert s.find_largest(3) is None
    # deletes work too
    assert s.delete(3) and not s.delete(9)
    assert [s.find_largest(k) for k in range(2)] == [3, 2]
    f = FixedKth(2)
    assert f.kth_largest() is None
    for x in (5, 1, 9, 7):
        f.insert(x)
    # the two largest are 9 and 7, so the 2nd largest is 7
    assert f.kth_largest() == 7
```

NOTES FROM CANDIDATES

An order-statistics structure (size-augmented BST / balanced tree / skiplist) gives O(log n) for both ops.
An order-statistics Fenwick tree over a coordinate-compressed value range gives O(log V).
A naive sorted array gives O(log n) find but O(n) insert; mention as a baseline.
Two heaps (the canonical streaming-median pattern) only work for a fixed k; the interviewer wants arbitrary k per call.

PREPARATION

Sketch the size-augmented BST node (left subtree count + duplicate count) on paper before the interview.
Practice the Fenwick-tree order-statistics trick (find k-th by binary search on prefix sums).
Be ready to defend the chosen data structure: balanced BST is clean but verbose; Fenwick is short but assumes bounded values.

MEDIUM | 1Point3Acres | onsite-coding | 23 of 165

Google Doc Line Wrap (Word Wrap with Whitespace and Newlines)

ASKED 2026-02-01 | 251 DAYS AGO | OLDER

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 198/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-02-01 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/document-line-wrap

QUESTION

EXAMPLES

```
text  = "Hello world\nFoo bar baz qux"
width = 10
Line 1: "Hello"             (5 chars; "world" + space
    would be 11 -> break)
Line 2: "world"
Line 3: "Foo bar"            (7 chars; "baz" -> "Foo
    bar baz" = 11 -> break)
Line 4: "baz qux"
Output: 4
```

APPROACH

Implement a clean tokenizer that treats \n as a special token and yields plain words otherwise.
Test cases: width = 1, text = "a\n\n\nb", text = " leading", text with words exactly width chars long.
Be ready to extend to "return the rendered lines" (string list), not just the count, as a likely follow-up.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the width counts characters in a monospace font, how to treat explicit newlines, multiple spaces and leading spaces, what to do with a word longer than the width, and whether to return the number of lines or the lines themselves.

BRUTE FORCE TO SAY OUT LOUD

INTERVIEW-DAY PLAN

Build the text line by line by trying to add each word and measuring. That is already the greedy algorithm.

OPTIMAL IDEA

Tokenize into words and newline tokens. Keep the current line length; for each word, if it fits (with a space unless the line is empty) add it, otherwise start a new line. A newline token always ends the current line. Count lines (empty lines count). Greedy is expected; mention Knuth's minimum-raggedness DP only if asked. O(n).

DRY-RUN THESE CASES

The example giving 4. width = 1. Consecutive newlines. A word exactly the width. A word longer than the width.

LIKELY FOLLOW-UPS

Return the lines, justify the text, or minimize raggedness.

PITFALLS

Dropping empty lines. Adding a trailing space at the end of a line.

HOW TO THINK ABOUT IT

Greedy is optimal for the question 'fewest lines': put as many words on a line as fit. The decision per word is only 'fits with a space', 'fits as the first word on the line', or 'start a new line', so track the current line length, not the line text. Treat newline as a hard break and decide up front what empty lines and long words do.

Basis: Written; greedy word wrap (LeetCode 68, Text Justification, without the justification step). Assumed rules (confirm them): monospace width in characters; words are separated by whitespace; '\n' always ends a line and an empty line counts; a word longer than the width gets its own line.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def wrap(text, width):
    count = 0
    for paragraph in text.split("\n"):
        line = ""
        for word in paragraph.split():
            joined = len(line) + 1 + len(word)
            if line and joined > width:
                count += 1  # finish the line
                line = word
            else:
                line = line + " " + word
                line = line.strip()
        count += 1  # last line
    return count
```

TIME	SPACE
O(total characters * words per line)	O(width)

WHY IT IS SLOW

Re-measuring a joined string for every word costs extra copying. Keeping a running length makes the whole thing O(total characters).

OPTIMAL SOLUTION · Greedy with a running line length

TIME	SPACE
O(n)	O(1) extra beyond the output

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the lines, not only the count.

Keep the same loop but append the finished line to a list (the brute force above already does it). Build each line from a list of words and join once, so each word is copied once.

FOLLOW-UP 2 A word longer than the width must be broken.

Before placing a word, while it is longer than the width flush the current line and emit width-sized chunks of the word, then continue with the remainder as a normal word.

FOLLOW-UP 3 Minimise raggedness instead of lines.

That is Knuth's word-wrap DP: dp[i] is the best cost of laying out words i.. with cost (spaces left)^2 on each line except the last; O(n * words per line). Greedy is not optimal for this objective.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# FOLLOW-UP 2: A word longer than the width must be
# broken.
def split_long(word, width):
    # a word longer than the line is cut into pieces
    starts = range(0, len(word), width)
    return [word[i:i + width] for i in starts]


# FOLLOW-UP 1: Return the lines, not only the count.
def wrap_lines(text, width, break_long=False):
    lines = []
    # a newline always starts a new paragraph (and a new
    # line)
    for paragraph in text.split("\n"):
        cur = ""
        words = paragraph.split()
        if break_long:
            pieces = [split_long(w, width) for w in words]
            words = [p for chunk in pieces for p in chunk]
        for w in words:
            if not cur:
                cur = w
            elif len(cur) + 1 + len(w) <= width:
                # the word and one space still fit
                cur += " " + w
            else:
                lines.append(cur)
                cur = w
        # the last (or only, or empty) line of the
        # paragraph
        lines.append(cur)
    return lines
```

```python
# BASE QUESTION (optimal): Greedy with a running line
# length
def wrap_count(text, width):
    return len(wrap_lines(text, width))


# FOLLOW-UP 3: Minimise raggedness instead of lines.
def min_raggedness(words, width):
    # Knuth: minimise the squared spare space of every
    # line
    # except the last; greedy is NOT optimal for this goal
    n = len(words)
    INF = float("inf")
    # cost[i]: best total cost for words[i:]
    cost, nxt = [INF] * (n + 1), [0] * (n + 1)
    cost[n] = 0
    for i in range(n - 1, -1, -1):
        length = -1
        for j in range(i, n):
            length += len(words[j]) + 1
            if length > width:
                break
            spare = width - length
            # the last line costs nothing
            extra = 0 if j == n - 1 else spare ** 2
            if extra + cost[j + 1] < cost[i]:
                cost[i] = extra + cost[j + 1]
                nxt[i] = j + 1
    lines, i = [], 0
    while i < n:
        lines.append(" ".join(words[i:nxt[i]]))
        i = nxt[i]
    return cost[0], lines


if __name__ == "__main__":
    text = "Hello world\nFoo bar baz qux"
    assert wrap_lines(text, 10) == [
        "Hello", "world", "Foo bar", "baz qux"]
    assert wrap_count(text, 10) == 4
    # blank lines count as lines
    assert wrap_count("a\n\nb", 5) == 3
    # a long word is split when asked
    cut = wrap_lines("abcdefgh", 3, True)
    assert cut == ["abc", "def", "gh"]
    assert wrap_lines("abcdefgh", 3) == ["abcdefgh"]
    # the best layout can beat the greedy one
    cost, lines = min_raggedness(
        "aaa bb cc ddddd".split(), 6)
    assert lines == ["aaa", "bb cc", "ddddd"]
    assert cost == 9 + 1
```

NOTES FROM CANDIDATES

Single-pass tokenizer + accumulator: track curLen; on each token, decide "fits with leading space", "fits without space" (start of line), or "flush and start new line".
Watch out for \n right after another \n (empty line counts), \n at the end of input, leading whitespace, multiple consecutive spaces inside a line.
Don't try to handle font / kerning / hyphenation — the prompt assumes monospace width counted in characters.
Greedy packing is the expected answer (LC 68 style). Mention DP word-wrap (Knuth's algorithm) only if the interviewer pushes on 'minimum raggedness'; greedy is optimal-enough and what graders look for. Watch edge cases: a single word longer than W, an explicit newline forcing a break mid-pack, trailing whitespace handling.

PREPARATION

Implement a clean tokenizer that treats \n as a special token and yields plain words otherwise.
Test cases: width = 1, text = "a\n\n\nb", text = " leading", text with words exactly width chars long.
Be ready to extend to "return the rendered lines" (string list), not just the count, as a likely follow-up.

MEDIUM | 1Point3Acres | onsite-coding | 24 of 165

Restaurant Waitlist: join / delete / find_first_match

ASKED 2026-02-01 | 251 DAYS AGO | OLDER

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 212/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-02-01 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/waitlist-data-structure-with-table-size-match

QUESTION

Onsite coding round: design and implement a restaurant waitlist data structure supporting join, delete, and find_first_match(table_size). The find call returns the earliest-joined user whose party size fits the given table.

Implement a class with these methods

join(user) — append user (with their party_size) to the waitlist.
delete(user) — remove user from the waitlist (could be anywhere in the queue).
find_first_match(table_size: int) — return the earliest user still on the waitlist whose party_size <= table_size. Do not remove on find.

QUESTION

Implicit constraints

Order of joins matters (FIFO within those that match).
Users may be deleted out of order, so a plain array/linked list with O(1) join cannot give O(1) delete and find together.

EXAMPLES

```
join(Alice, size=2)
join(Bob, size=4)
join(Carol, size=6)
find_first_match(3) -> Alice   // only Alice fits
find_first_match(5) -> Alice   // Alice still earliest
    matching
delete(Alice)
find_first_match(5) -> Bob
find_first_match(2) -> null     // no one fits
```

APPROACH

Drill LRU-cache style implementations (hashmap + DLL) to muscle memory.
Sketch a second variant with party-size buckets and verbalize the trade-off (find_first_match becomes O(table_size) instead of O(n) but uses more memory).
Practice articulating which call should be fast in a real restaurant — typically find_first_match runs once per available table.

HOW TO THINK ABOUT IT

Join needs the order of arrival, delete can hit anyone, and find must return the earliest person whose party fits the table. Keep one queue per party size and a sequence number per person: find looks at the front of every queue for sizes up to the table size and takes the smallest sequence number. Deletions are marked and skipped lazily when a queue front is read.

Basis: Written for this question (a doubly linked list plus hash map as in LeetCode 146, LRU Cache, with queues bucketed by party size).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
queue = []  # in arrival order
def join(user):
    queue.append(user)
def delete(user):
    queue.remove(user)
def find_first_match(t):
    for user in queue:
        if user.party_size <= t:
            return user
    return None
```

TIME	SPACE
O(n)	O(n)
per find and per delete	

WHY IT IS SLOW

BRUTE FORCE

Delete and find are linear in the list. One queue per party size with lazy deletion makes join and delete O(1) and find touch only the queue fronts.

OPTIMAL SOLUTION · Queue per party size with lazy deletion

TIME	SPACE
O(1)	O(n)
join and delete, O(S) find (S distinct sizes up to the table size)	

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What would you cache to speed up repeated finds?

Keep a small structure that answers 'earliest sequence among sizes <= t' directly: a segment tree or Fenwick tree over party size storing the minimum front sequence number, updated when a queue front changes. Find becomes O(log S) instead of O(S).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict, deque


# BASE QUESTION (optimal): Queue per party size with lazy
# deletion
class Waitlist:
    def __init__(self):
        # arrival counter: lower means joined earlier
        self.seq = 0
        # person -> their arrival number (people still
        # waiting)
        self.live = {}
        # party size -> line of (arrival number, person)
        self.queues = defaultdict(deque)

    def join(self, name, size):
        self.seq += 1
        self.live[name] = self.seq
        self.queues[size].append((self.seq, name))

    def delete(self, name):
        # lazy: the entry in its queue is skipped later
        self.live.pop(name, None)

    def front(self, queue):
        # drop deleted people from the front of a queue
        while queue:
            seq, name = queue[0]
            if self.live.get(name) == seq:
                break
            queue.popleft()
        return queue[0] if queue else None

    def find_first_match(self, table):
        best = None
        for size, queue in self.queues.items():
            if size > table:
```

```
                continue
            head = self.front(queue)
            # the earliest head among all sizes that fit
            if head and (not best or head[0] < best[0]):
                best = head
        return best[1] if best else None
```

```
if __name__ == "__main__":
    w = Waitlist()
    for name, size in [("Alice", 2), ("Bob", 4)]:
        w.join(name, size)
    w.join("Carol", 6)
    assert w.find_first_match(3) == "Alice"
    # Alice is still the earliest who fits 5
    assert w.find_first_match(5) == "Alice"
    # find does not remove anyone
    assert w.find_first_match(5) == "Alice"
    w.delete("Alice")
    assert w.find_first_match(5) == "Bob"
    assert w.find_first_match(1) is None
    # the same size: arrival order decides
    w.join("Dan", 4)
    w.delete("Bob")
    assert w.find_first_match(4) == "Dan"
    # deleting someone who is not there is harmless
    w.delete("Nobody")
```

NOTES FROM CANDIDATES

A doubly-linked list + hashmap (LRU-style) gives O(1) join and delete; find_first_match then walks the list.
For faster find, bucket users by party size (e.g. one queue per size), and on find_first_match(t) scan sizes 1..t and pick the queue with the smallest head timestamp.
The interviewer cares more about clean class design + tradeoff discussion than a single optimal solution; mention what you'd cache to speed up repeated finds.

PREPARATION

Drill LRU-cache style implementations (hashmap + DLL) to muscle memory.
Sketch a second variant with party-size buckets and verbalize the trade-off (find_first_match becomes O(table_size) instead of O(n) but uses more memory).
Practice articulating which call should be fast in a real restaurant — typically find_first_match runs once per available table.

MEDIUM | 1Point3Acres | phone-screen, onsite-coding | 25 of 165

Run-Length Vector Storage + Dot Product

ASKED 2026-01-21 | 262 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 5 | 30 DAYS 0 | PRIORITY 172/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 1570 Dot Product of Two Sparse Vectors

Frequency: Single report | Last asked: 2026-01-21 | Roles: SWE, INFRA-ENG

Original: https://www.1point3acres.com/interview/problems/company/google/compressed-vector-dot-product

QUESTION

EXAMPLES

```
Logical A = [3, 3, 3, 0, 0, 0, 4, 4]
Logical B = [1, 1, 1, 1, 2, 2, 2, 2]
Encoded A (RLE): [(3,3),(0,3),(4,2)]
Encoded B (RLE): [(1,4),(2,4)]
Dot product = 3·1·3 + 3·1·0 + 0·1·0 + 0·2·0 + 4·2·2 =
    9 + 0 + 16 = 25
```

APPROACH

Memorize the two-pointer RLE walk pattern (it generalizes to interval intersection, range addition, etc.).
Practice articulating when RLE wins vs sparse (O(distinct_runs) vs O(nonzeros)).
Have a one-liner for sparse case: store (idx -> value) map; iterate over the smaller map and look up the other.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the encoding format (value, count pairs), whether runs of zeros are stored, the logical length of both vectors (must be equal), and whether updates are needed.

BRUTE FORCE TO SAY OUT LOUD

Expand both vectors and multiply element by element. O(n) memory.

OPTIMAL IDEA

Two pointers over the run lists. Take the overlap, which is min of the two remaining counts, add value_a * value_b * overlap, subtract the overlap from both, and advance whichever run is exhausted. O(r1 + r2), O(1) extra space.

DRY-RUN THESE CASES

The example giving 25. One vector of a single run. Runs that end at the same time. All zeros.

LIKELY FOLLOW-UPS

A sparse vector against an RLE vector, setting an element, or dot product of k vectors.

INTERVIEW-DAY PLAN

PITFALLS

Advancing only one pointer when both runs finish together. Overflowing the product for large counts.

HOW TO THINK ABOUT IT

A run is a stretch where both numbers are constant, so the dot product of two runs is value times value times the length of their overlap. Walk the two run lists like the merge step of merge sort: consume the smaller remaining length from both, and advance whichever run you finished.

Basis: LeetCode 1570, Dot Product of Two Sparse Vectors, with run-length encoding as the compression.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def decode(runs):
    dense = []
    for value, count in runs:
        dense += [value] * count
    return dense
def brute(runs_a, runs_b):
    a, b = decode(runs_a), decode(runs_b)
    return sum(x * y for x, y in zip(a, b))
```

TIME	SPACE
O(logical length)	O(logical length)

WHY IT IS SLOW

It needs memory and time proportional to the logical length, which can be 10^9. Walking the two run lists together with two pointers costs only the number of runs.

OPTIMAL SOLUTION · Two-pointer over runs

TIME	SPACE
O(r1 + r2)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if one vector is mostly zeros and stored sparsely, and the other as runs?

Iterate the sparse side's nonzero indices and binary-search the run list for each index to read the other value: O(s log r). Choose the smaller representation to drive the loop.

FOLLOW-UP 2 How should the data be updated if you set element i?

Locate the run containing i (binary search over prefix run lengths), then split it into at most three runs and merge equal neighbours. That is O(log r) to find plus O(r) in the worst case to splice a list; use a balanced tree of runs for frequent updates.

FOLLOW-UP 3 One vector is a sparse map (index to value) and the other is run-length encoded.

Iterate the smaller structure (the sparse non-zeros) and binary search the run list for each index using prefix run lengths: O(s log r) instead of expanding anything.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_right
from itertools import accumulate


def rle_encode(values):
    runs = []
    for v in values:
        if runs and runs[-1][0] == v:
            runs[-1][1] += 1
        else:
            runs.append([v, 1])
    return [tuple(r) for r in runs]


def rle_decode(runs):
    return [v for v, count in runs for _ in range(count)]


# BASE QUESTION (optimal): Two-pointer over runs
def rle_dot(a, b):
    # two pointers over the runs: never expand anything
    i = j = 0
    left_a = a[0][1] if a else 0
    left_b = b[0][1] if b else 0
    total = 0
    while i < len(a) and j < len(b):
        # both runs overlap for min(left_a, left_b)
        # positions
        take = min(left_a, left_b)
        total += a[i][0] * b[j][0] * take
        left_a -= take
        left_b -= take
        if left_a == 0:
            i += 1
            left_a = a[i][1] if i < len(a) else 0
        if left_b == 0:
            j += 1
            left_b = b[j][1] if j < len(b) else 0
    return total


# FOLLOW-UP 1, 3: What if one vector is mostly zeros and
# stored sparsely, and the other ...
def sparse_dot_rle(sparse, runs):
    # sparse: {index: value}; runs: RLE of the other
```

```
    # vector
    ends = list(accumulate(count for _, count in runs))
    total = 0
    # iterate the small side; binary search the runs
    for index, value in sparse.items():
        k = bisect_right(ends, index)
        if k < len(runs):
            total += value * runs[k][0]
    return total


# FOLLOW-UP 2: How should the data be updated if you set
```

```python
# element i?
def set_at(runs, index, value):
    # update one position: split a run, then merge
    # neighbours
    flat, pos = [], 0
    for v, count in runs:
        if pos <= index < pos + count:
            flat += [(v, index - pos), (value, 1),
                     (v, pos + count - index - 1)]
        else:
            flat.append((v, count))
        pos += count
    merged = []
    for v, count in flat:
        if count == 0:
            continue
        if merged and merged[-1][0] == v:
            merged[-1] = (v, merged[-1][1] + count)
        else:
            merged.append((v, count))
    return merged


if __name__ == "__main__":
    A = [3, 3, 3, 0, 0, 0, 4, 4]
    B = [1, 1, 1, 1, 2, 2, 2, 2]
    ra, rb = rle_encode(A), rle_encode(B)
    assert ra == [(3, 3), (0, 3), (4, 2)]
    assert rle_decode(ra) == A
    # 3*1*3 + 0 + 4*2*2 = 25
    assert rle_dot(ra, rb) == 25
    assert rle_dot([], rb) == 0
    dense = sum(x * y for x, y in zip(A, B))
```

```python
    assert dense == 25
    # sparse vector with non-zeros at 0 and 7
    sparse = {0: 2, 7: 5}
    assert sparse_dot_rle(sparse, rb) == 2 * 1 + 5 * 2
    # setting a value splits and merges runs
    assert set_at(ra, 4, 3) == [(3, 3), (0, 1), (3, 1),
                                (0, 1), (4, 2)]
    assert set_at([(1, 3)], 1, 1) == [(1, 3)]
```

NOTES FROM CANDIDATES

Two-pointer walk over the two RLE encodings: at each step compute the overlap length min(remainA, remainB), multiply values, advance the pointer whose run is exhausted.
Mention compression-friendly variations: sparse format wins when most entries are 0 (just enumerate non-zero indices and skip zeros entirely in the dot product).
Interviewer cared more about clean data-structure choice and the walk over both encodings than about absolute optimality.

PREPARATION

Memorize the two-pointer RLE walk pattern (it generalizes to interval intersection, range addition, etc.).
Practice articulating when RLE wins vs sparse (O(distinct_runs) vs O(nonzeros)).
Have a one-liner for sparse case: store (idx -> value) map; iterate over the smaller map and look up the other.

MEDIUM | 1Point3Acres | onsite-coding | 26 of 165

Two-Day Log Intersection under Memory Limit

ASKED 2025-11-27 | 317 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 50.4 | 30 DAYS 46.9 | PRIORITY 23/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 349 Intersection of Two Arrays (related)

Frequency: Single report | Last asked: 2025-11-27 | Roles: SWE, INFRA-ENG

Original: https://www.1point3acres.com/interview/problems/company/google/two-logs-intersection-memory-limit

QUESTION

PhD intern coding round 1: two log files with **`(timestamp, obj_id, client_id)`** entries. Find **`obj_id`**s that (a) appear in both files and (b) have at least two distinct **`client_id`**s. Follow-up imposes a memory limit, expecting external sort + two-pointer.

Input: two log files; each line is (timestamp, obj_id, client_id). Find every obj_id such that:

(a) appears in both files, and
(b) is associated with at least 2 distinct client_ids (aggregated across both files).

Follow-up 1: complexity of set-intersection on the file contents.
Follow-up 2: memory cannot hold either file fully — design a streaming solution.

EXAMPLES

```
File A:  (t1, X, c1), (t2, X, c2), (t3, Y, c1)
File B:  (t4, X, c1), (t5, Z, c2)
-> Only X is in both files; X has 2 distinct clients
    {c1, c2}.
Output: [X]
```

APPROACH

Practice external-sort / merge-step problems (classic in-memory merge / k-way-merge / partition problems — and discuss disk-based variants verbally).
Drill the streaming hashmap vs external sort trade-off conversation.
Have ready: HyperLogLog (or Count-Min Sketch) one-liner for approximate distinct-count under tight memory.

HOW TO THINK ABOUT IT

In memory it is a hash map from object to the set of clients, filtered to objects that appear in both files and have at least two clients. When the files do not fit in memory, sort both by object id (external sort) and walk them together: all rows of one object are adjacent, so you only ever hold the clients of one object at a time.

Basis: LeetCode 349, Intersection of Two Arrays, with a distinct-client condition and a limit on memory (external sort and a two-pointer merge).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(first, second):
    result = []
    for obj in {r.obj for r in first}:
        if obj not in {r.obj for r in second}:
            continue
        rows = [r for r in first + second
                if r.obj == obj]
        if len({r.client for r in rows}) >= 2:
            result.append(obj)
    return result
```

TIME	SPACE
O(n * m)	O(n + m)

WHY IT IS SLOW

O(n * m) time and both files must fit in memory. Sorting both files by object and merging them with two pointers is O(n log n) and holds one object's clients at a time.

OPTIMAL SOLUTION · Hash map of client sets (everything fits in memory)

TIME	SPACE
O(n + m)	O(n + m)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why prefer sort and two pointers to a streaming hash map?

A hash map needs memory proportional to the number of distinct objects (and clients), which is exactly what the limit forbids. An external sort needs only a chunk of memory and sequential disk passes, and the merge needs memory for one object's clients. If one object has an enormous client set, count distinct clients approximately (HyperLogLog) or stop as soon as two are seen.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict


# BASE QUESTION (optimal): Hash map of client sets
# (everything fits in memory)
def log_objects(day1, day2):
    # everything fits in memory: object -> set of clients
    c1, c2 = defaultdict(set), defaultdict(set)
    for _, obj, client in day1:
        c1[obj].add(client)
    for _, obj, client in day2:
        c2[obj].add(client)
    # in both files, with 2+ clients over both days
    both = c1.keys() & c2.keys()
    return sorted(o for o in both
                  if len(c1[o] | c2[o]) >= 2)


def groups(rows):
    # rows sorted by object: yield (object, its clients)
    current, clients = None, set()
    for _, obj, client in rows:
        if obj != current:
            if current is not None:
                yield current, clients
            current, clients = obj, set()
        clients.add(client)
    if current is not None:
        yield current, clients


# FOLLOW-UP 1: Why prefer sort and two pointers to a
# streaming hash map?
def log_objects_sorted(rows1, rows2):
    # memory limit: both files arrive sorted by object (an
    # external sort), so only one object's clients are
    # held
    out = []
    g1, g2 = groups(rows1), groups(rows2)
    a, b = next(g1, None), next(g2, None)
    while a and b:
        if a[0] == b[0]:
            # same object in both files
            if len(a[1] | b[1]) >= 2:
                out.append(a[0])
            a, b = next(g1, None), next(g2, None)
        elif a[0] < b[0]:
            a = next(g1, None)
        else:
            b = next(g2, None)
    return out


if __name__ == "__main__":
    day1 = [(1, "X", "c1"), (2, "X", "c2"),
            (3, "Y", "c1")]
    day2 = [(4, "X", "c1"), (5, "Z", "c2")]
    assert log_objects(day1, day2) == ["X"]
    def by_object(rows):
        return sorted(rows, key=lambda r: r[1])

    assert log_objects_sorted(by_object(day1),
                              by_object(day2)) == ["X"]
    # one client in total is not enough
    one = [(1, "A", "c1")]
    assert log_objects(one, one) == []
    assert log_objects_sorted(one, one) == []
    # clients may be split across the two days
    d1, d2 = [(1, "A", "c1")], [(2, "A", "c2")]
    assert log_objects(d1, d2) == ["A"]
    assert log_objects_sorted(d1, d2) == ["A"]
    assert log_objects([], day2) == []
```

NOTES FROM CANDIDATES

In-memory solution: build a hashmap obj_id -> set(client_id) while scanning each file; intersect keys across the two hashmaps at the end.
Memory-limited solution: external sort each file by obj_id, then run a merge / two-pointer scan over both sorted files. For each matching obj_id group, count distinct client_id on the fly (HyperLogLog if duplicates are large).
The interviewer explicitly preferred sort + two-pointer over a streaming hashmap — be prepared to defend the choice (sort is O(n log n) on disk vs O(n) RAM-bound for the hashmap).
For distributed scale, hash-partition by obj_id and run the same algorithm per partition.

PREPARATION

Practice external-sort / merge-step problems (classic in-memory merge / k-way-merge / partition problems — and discuss disk-based variants verbally).
Drill the streaming hashmap vs external sort trade-off conversation.
Have ready: HyperLogLog (or Count-Min Sketch) one-liner for approximate distinct-count under tight memory.

NO DATE (5)

Medium (5)

BFS/DFS Graph and Tree Traversal and Shortest Paths 1 questions

MEDIUM | 1Point3Acres | onsite-coding | 27 of 165

Shortest Directed Cycle Through a Node

STUDY: TALK | ALL TIME 5 | 30 DAYS 0 | PRIORITY 173/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths
Optimal answer from: written and tested here for this exact question
LeetCode match: LC 2608 Shortest Cycle in a Graph (related)
Frequency: Single report | Roles: SWE
Original: https://www.1point3acres.com/interview/problems/company/google/shortest-cycle-through-node

QUESTION

EXAMPLES

```
Edges [(0,1),(1,2),(2,0)], v = 0 -> 3.
Edges [(0,1),(1,2)], v = 0 -> -1.
```

APPROACH

Write the directed BFS-from-source version from memory in under 12 min.
Practice the "re-entry detection" pattern (don't mark v visited until after pop).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether edges are directed (yes), whether self loops count (cycle of length 1), what to return if there is none (-1), and whether edges have weights.

BRUTE FORCE TO SAY OUT LOUD

Enumerate all simple paths from v back to v with DFS. Exponential.

OPTIMAL IDEA

BFS from v. The first time you see an edge from a visited node u back to v, the cycle length is dist[u] + 1, and BFS order makes it the shortest. Do not mark v as discovered before checking for re-entry. O(V + E).

DRY-RUN THESE CASES

A triangle (3). A path with no return (-1). A self loop (1). Two cycles through v of different lengths.

LIKELY FOLLOW-UPS

Shortest cycle in the whole graph (BFS from every node), weighted edges (Dijkstra), or undirected graphs.

PITFALLS

Marking v visited at the start, which hides the cycle. Counting nodes instead of edges.

HOW TO THINK ABOUT IT

A cycle through v is a path from v back to v, so find shortest distances from v and watch for an edge that points back at v. Breadth-first search discovers nodes in order of distance, so the first edge back to v closes the shortest cycle. Do not mark v as 'seen' in a way that hides the edge that returns to it.

Basis: Related to LeetCode 2608, Shortest Cycle in a Graph, but directed and anchored at a given node.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
best = INF
def dfs(u, length, on_path):
    global best
    for w in graph[u]:
        if w == v:
            best = min(best, length + 1)
        elif w not in on_path:
            dfs(w, length + 1, on_path | {w})
dfs(v, 0, {v})
answer = -1 if best == INF else best
```

TIME	SPACE
exponential	O(V)

BRUTE FORCE

WHY IT IS SLOW

The number of simple paths can be exponential in the graph size. A breadth-first search from v reaches the shortest cycle in O(V + E) because it visits nodes in order of distance.

OPTIMAL SOLUTION · BFS from v, close the cycle on the first edge back to v

TIME	SPACE
O(V + E)	O(V)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How do you find the shortest cycle in the whole graph?

Run the same BFS from every vertex and take the minimum: O(V * (V + E)). For undirected graphs, BFS from each node and treat any non-tree edge as closing a cycle of length dist[u] + dist[w] + 1 (the LeetCode 2608 version).

FOLLOW-UP 2 What if edges have positive weights?

Replace BFS with Dijkstra from v and close the cycle at the cheapest dist[u] + weight(u, v). That is O((V + E) log V) with a heap. With negative weights use Bellman-Ford and handle negative cycles separately.

FOLLOW-UP 3 The shortest cycle anywhere in the graph (the girth).

Run the same BFS from every node and take the smallest result: O(V * (V + E)). That is the standard way and fine for graphs up to a few thousand nodes.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
import heapq
from collections import deque

INF = float("inf")


def make_graph(n, edges):
    adj = [[] for _ in range(n)]
    for a, b, *w in edges:
        # edges may carry a weight (default 1)
        adj[a].append((b, w[0] if w else 1))
    return adj


# BASE QUESTION (optimal): BFS from v, close the cycle on
# the first edge back to v
def shortest_cycle_through(n, edges, v):
    # BFS from v: the first edge that comes back to v
    # closes
    # the shortest cycle through v
    adj = make_graph(n, edges)
    dist, queue = {v: 0}, deque([v])
    while queue:
        u = queue.popleft()
        for w, _ in adj[u]:
            if w == v:
                return dist[u] + 1
            if w not in dist:
                dist[w] = dist[u] + 1
                queue.append(w)
    return -1


# FOLLOW-UP 1, 3: How do you find the shortest cycle in
# the whole graph?
def girth(n, edges):
    # the shortest cycle anywhere: BFS from every node
    sizes = [shortest_cycle_through(n, edges, v)
             for v in range(n)]
    found = [s for s in sizes if s > 0]
    return min(found) if found else -1


# FOLLOW-UP 2: What if edges have positive weights?
def weighted_cycle_through(n, edges, v):
    # positive weights: Dijkstra, then close the cycle at
    # v
    adj = make_graph(n, edges)
    dist, heap, best = {v: 0}, [(0, v)], INF
    while heap:
        d, u = heapq.heappop(heap)
        if d > dist.get(u, INF):
            continue
        for w, cost in adj[u]:
            if w == v:
                best = min(best, d + cost)
            elif d + cost < dist.get(w, INF):
                dist[w] = d + cost
                heapq.heappush(heap, (d + cost, w))
    return -1 if best == INF else best


if __name__ == "__main__":
    ring = [(0, 1), (1, 2), (2, 0)]
    assert shortest_cycle_through(3, ring, 0) == 3
    path = [(0, 1), (1, 2)]
    assert shortest_cycle_through(3, path, 0) == -1
    # a self loop is a cycle of length 1
    assert shortest_cycle_through(2, [(0, 0)], 0) == 1
    # a shorter cycle exists elsewhere: 1 <-> 2
    both = ring + [(1, 2), (2, 1)]
    assert girth(3, both) == 2
    assert girth(3, [(0, 1), (1, 2)]) == -1
    # weighted: the cheap way back is 0 -> 1 -> 0 (cost 3)
    weighted = [(0, 1, 1), (1, 0, 2),
                (0, 2, 1), (2, 0, 9)]
    assert weighted_cycle_through(3, weighted, 0) == 3
```

NOTES FROM CANDIDATES

Strictly directed; do not relax to undirected.
BFS layer 0 is v itself; the first re-discovery during expansion is the cycle length.
Common bug: marking v as visited immediately blocks the re-entry.

PREPARATION

Write the directed BFS-from-source version from memory in under 12 min.
Practice the "re-entry detection" pattern (don't mark v visited until after pop).

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns 1 questions

MEDIUM | 1Point3Acres | onsite-coding | 28 of 165

Rotate Any m×n 2D Matrix

STUDY: TYPE | ALL TIME 56.3 | 30 DAYS 0 | PRIORITY 56/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #48 Rotate Image

LeetCode match: LC 48 Rotate Image (related)

Frequency: Single report | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/rotate-matrix-rectangle

QUESTION

EXAMPLES

```
[[1,2,3],[4,5,6]] (2×3) rotated 90° CW ->
    [[4,1],[5,2],[6,3]] (3×2).
```

APPROACH

Write square in-place rotation from memory in under 8 min. Have a 60-second explanation for why rectangle in-place is hard and what trade-offs you'd take.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask which direction and angle, whether in place is required, and the dimensions. A non-square matrix cannot be rotated in place in the same buffer, since its shape changes.

BRUTE FORCE TO SAY OUT LOUD

Create a new matrix and copy each cell to its rotated position with an index formula. O(mn) space.

OPTIMAL IDEA

Clockwise 90 degrees: reverse the rows and transpose, [list(r) for r in zip(*matrix[::-1])]. Counter-clockwise: transpose then reverse the rows. 180 degrees: reverse the rows and each row. For a square matrix rotate in place by cycling four cells per layer.

DRY-RUN THESE CASES

INTERVIEW-DAY PLAN

The 2 x 3 example giving [[4,1],[5,2],[6,3]], 1 x 1, 1 x n, an empty matrix, four rotations returning the original.

LIKELY FOLLOW-UPS

In place square rotation, rotation by k times 90 degrees, or non-square in place with a flat array and cycles.

PITFALLS

Mixing up the index formula direction. Trying to rotate a rectangle in place in a 2D list.

HOW TO THINK ABOUT IT

A 90 degree clockwise rotation sends the cell at row i, column j to row j, column (m - 1 - i) of the new n x m matrix. That formula is the whole problem; 'reverse the rows then transpose' is just a short way to write it. A rectangle cannot be rotated in place because its shape changes.

Basis: Generalizes LeetCode 48, Rotate Image, from an n x n matrix to any m x n matrix.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def rotate(old):
    m, n = len(old), len(old[0])
    new = [[0] * m for _ in range(n)]
    for i in range(m):
        for j in range(n):
            new[j][m - 1 - i] = old[i][j]
    return new
```

TIME	SPACE
O(m * n)	O(m * n)

WHY IT IS SLOW

This is already optimal in time, O(m * n); its cost is the second matrix, O(m * n) extra space. A rectangle cannot be rotated in place (its shape changes), so it is the expected answer; the zip(reversed rows) one-liner is the same idea.

OPTIMAL SOLUTION · Rotate 90 degrees clockwise by reverse + transpose

TIME	SPACE
O(mn)	O(mn)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Can a non-square matrix be rotated in place?

Not in a rectangular buffer, because the dimensions swap. You can do it in place only if the matrix is stored as a flat array and you permute the elements along cycles of the index map (i, j) to (j, m - 1 - i), which is O(mn) time but needs cycle bookkeeping. In an interview, allocate the new matrix and say why.

FOLLOW-UP 2 How would you rotate by k * 90 degrees?

Reduce k modulo 4 first. Then apply the single-turn function that many times, or write the four direct index maps so you only build the output once.

FOLLOW-UP 3 Rotate by k quarter turns.

Reduce k modulo 4 first; four turns are the identity. Apply the single-turn function that many times (at most three), or write the three index formulas directly to build the answer once.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
# BASE QUESTION (optimal): Rotate 90 degrees clockwise by
# reverse + transpose
def rotate_cw(matrix):
    # reverse the rows, then swap rows and columns
    return [list(row) for row in zip(*matrix[::-1])]


# COUNTER-CLOCKWISE
def rotate_ccw(matrix):
    # swap rows and columns, then reverse the rows
    return [list(row) for row in zip(*matrix)][::-1]


# FOLLOW-UP 2, 3: How would you rotate by k * 90 degrees?
def rotate_k(matrix, k):
    # four quarter turns are the identity: use k mod 4
    for _ in range(k % 4):
        matrix = rotate_cw(matrix)
    return matrix


# INDEX RULE version
def rotate_by_index(matrix):
    # the same result from the index rule, built once:
    # new[j][m - 1 - i] = old[i][j]
    m, n = len(matrix), len(matrix[0]) if matrix else 0
    new = [[None] * m for _ in range(n)]
    for i in range(m):
        for j in range(n):
            new[j][m - 1 - i] = matrix[i][j]
    return new


if __name__ == "__main__":
    a = [[1, 2, 3], [4, 5, 6]]
    # the 2 x 3 example becomes 3 x 2
    assert rotate_cw(a) == [[4, 1], [5, 2], [6, 3]]
    assert rotate_by_index(a) == rotate_cw(a)
    assert rotate_ccw(a) == [[3, 6], [2, 5], [1, 4]]
    # a clockwise then an anticlockwise turn cancel out
    assert rotate_ccw(rotate_cw(a)) == a
    assert rotate_k(a, 4) == a
    assert rotate_k(a, 2) == [[6, 5, 4], [3, 2, 1]]
    assert rotate_k(a, 5) == rotate_cw(a)
    assert rotate_cw([[7]]) == [[7]]
```

```python
    assert rotate_cw([]) == []
```

NOTES FROM CANDIDATES

The in-place rectangle rotation is essentially cycle-decomposition on the index permutation — explain it but don't burn time implementing.
Reported follow-up: rotate inside a window of a larger matrix while keeping the rest untouched.

PREPARATION

Write square in-place rotation from memory in under 8 min. Have a 60-second explanation for why rectangle in-place is hard and what trade-offs you'd take.

Dynamic Programming and State-Space Optimization 2 questions

MEDIUM | 1Point3Acres | onsite-coding | 29 of 165

Jump Game with Profit

STUDY: TYPE | **ALL TIME 56** | **30 DAYS 0** | **PRIORITY 57/224**

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #55 Jump Game

LeetCode match: LC 55 Jump Game (related)

Frequency: Single report | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/jump-game-with-profit

QUESTION

EXAMPLES

Variant-dependent; the principal recurrence is the one above.

APPROACH

Drill the reachability-jump, min-jumps, and coin-change family together so the DP shape is automatic.
Practice clarifying "can I skip without consuming a turn" before coding.

INTERVIEW-DAY PLAN

CLARIFY FIRST

This is underspecified, so ask: is arr[i] the maximum jump (a cap) or an exact jump, is profit collected on landing or when leaving, can you skip a cell for free, are revisits allowed, and what is the goal (reach the end, or maximize profit)?

BRUTE FORCE TO SAY OUT LOUD

Recursively try every jump from every cell. Exponential.

OPTIMAL IDEA

INTERVIEW-DAY PLAN

Pick a reading and say it. Cap reading: best[i] is the best profit standing on i; best[i] = profit[i] + max best[j] over j that can reach i; O(n * max jump), or O(n log n) with a heap and lazy deletion. Exact jump with optional skipping: dp[i] = max(dp[i + 1], profit[i] + dp[i + arr[i]]) from the right, O(n). Plain reachability (no profit) is a greedy farthest-reach scan in O(n).

DRY-RUN THESE CASES

A cell with jump 0, an unreachable end, negative profits, a single cell.

LIKELY FOLLOW-UPS

Minimum jumps (LeetCode 45), profits that can be negative, or a limit on the number of jumps.

PITFALLS

Treating the jump as a cap when it is exact, or the reverse. Not defining what skipping costs.

HOW TO THINK ABOUT IT

This statement is underspecified, so pin it down first (cap or exact jump, when profit is collected, can you skip, what is the goal). The reading with a maximum jump and profit on landing is a DP over positions: the best profit at i is its own profit plus the best of all positions that can reach it. The reading with an exact jump and a free skip is a one-line DP from the right.

Basis: Variant of LeetCode 55 (Jump Game) and LeetCode 45 (Jump Game II). The prompt is underspecified, so two readings are given; confirm which one with the interviewer.

BRUTE FORCE · Reading A: recursion over every jump length

BRUTE FORCE · PSEUDO-CODE

```
best = -INF
def go(i, total):
    global best
    if i == n - 1:
        best = max(best, total)
        return
    for step in range(1, arr[i] + 1):
        if i + step < n:
            gain = profit[i + step]
            go(i + step, total + gain)
```

TIME	SPACE
O(max jump ^ n)	O(n)

WHY IT IS SLOW

Every cell branches into up to max-jump choices, so the paths multiply (max jump to the power n). A table of the best profit per cell, filled left to right, is O(n * max jump).

BRUTE FORCE · Reading B: recursion over 'jump or skip' choices

BRUTE FORCE · PSEUDO-CODE

```
def best(i):
    if i >= n:
        return 0
    skip = best(i + 1)
    jump = 0
    if arr[i] > 0:
        jump = profit[i] + best(i + arr[i])
    return max(skip, jump)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

Two branches at every cell and the same suffix is solved repeatedly: O(2^n). Computing best(i) once per index from the right is O(n).

OPTIMAL SOLUTION · Reading A: arr[i] is a maximum jump, profit[i] is gained on landing, maximize total profit to the last index

TIME	SPACE
O(n * maxJump)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Reading B: arr[i] is an exact jump; at each index you may jump (gaining profit[i]) or skip one cell for free

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Speed up reading A to near-linear time.

The inner loop asks for the max of best[j] over all j that can still reach i. Maintain a max-heap of (best[j], j + arr[j]) and pop entries whose reach is below i (lazy deletion): O(n log n). If the jump limit is the same for all cells, a monotonic deque over a sliding window makes it O(n).

FOLLOW-UP 2 What if you want to know whether the end is reachable at all (plain Jump Game)?

Greedy: scan left to right keeping the farthest reachable index; if i exceeds it you are stuck. O(n) time, O(1) space. Use the DP when profits matter, and the greedy when only reachability matters.

FOLLOW-UP 3 Only reachability, no profit (LeetCode 55).

Greedy: keep the farthest index reachable so far; if the current index is beyond it you are stuck. O(n), O(1).

FOLLOW-UP 4 Make the profit DP faster.

best[i] needs the maximum of best[j] over j that can reach i. A max-heap with lazy deletion of positions that can no longer reach i makes it O(n log n); with a constant maximum jump a monotonic deque gives O(n).

FOLLOW-UP 5 Fewest jumps (LeetCode 45).

BFS by levels or a greedy that tracks the end of the current jump range and the farthest reach, O(n).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq

NEG = float("-inf")


# SLOWER VERSION (say it first)
def max_profit_slow(arr, profit):
    # best[i]: most profit when landing on i (arr[j] is
    # the
    # farthest jump from j); O(n^2)
    n = len(arr)
    best = [NEG] * n
    best[0] = profit[0]
    for i in range(1, n):
        for j in range(i):
            # can j reach i? then landing on i is possible
            if best[j] != NEG and j + arr[j] >= i:
                total = best[j] + profit[i]
                best[i] = max(best[i], total)
    return -1 if best[-1] == NEG else best[-1]


# BASE QUESTION (optimal): Reading A: arr[i] is a maximum
# jump, profit[i] is gained on ...
def max_profit_fast(arr, profit):
    # a max-heap of (-best, reach) with lazy deletion
    n = len(arr)
    best = [NEG] * n
    best[0] = profit[0]
    heap = [(-best[0], arr[0])]
    for i in range(1, n):
        # forget cells that can no longer reach i
        while heap and heap[0][1] < i:
            heapq.heappop(heap)
        if heap:
            best[i] = -heap[0][0] + profit[i]
            heapq.heappush(heap, (-best[i], i + arr[i]))
    return -1 if best[-1] == NEG else best[-1]


# FOLLOW-UP 3: Only reachability, no profit (LeetCode 55).
# VARIANT: reachability only (LeetCode 55)
def can_reach_end(arr):
    # LeetCode 55: only reachability, greedy O(n)
    farthest = 0
    for i, jump in enumerate(arr):
        if i > farthest:
            return False
        farthest = max(farthest, i + jump)
    return True


# FOLLOW-UP 5: Fewest jumps (LeetCode 45).
# VARIANT: fewest jumps (LeetCode 45)
def fewest_jumps(arr):
    # LeetCode 45: levels of a BFS, greedy O(n)
    jumps = end = farthest = 0
    for i in range(len(arr) - 1):
        farthest = max(farthest, i + arr[i])
        if i == end:
            # we must jump now: extend to the farthest
            # reach
            jumps += 1
            end = farthest
    return jumps


if __name__ == "__main__":
    arr, profit = [2, 3, 1, 1, 4], [1, 5, 2, 3, 4]
    # best path: 0 -> 1 -> 2 -> 3 -> 4 = 15
    assert max_profit_slow(arr, profit) == 15
    assert max_profit_fast(arr, profit) == 15
    # the end cannot be reached
    assert max_profit_slow([1, 0, 1], [1, 1, 1]) == -1
    assert max_profit_fast([1, 0, 1], [1, 1, 1]) == -1
    assert can_reach_end(arr)
    assert not can_reach_end([1, 0, 1])
    assert fewest_jumps(arr) == 2
    # the fast version agrees with the slow one
    import itertools
    for jumps in itertools.product(range(4), repeat=5):
        pr = [1, 2, 3, 2, 1]
        assert max_profit_slow(jumps, pr) == (
            max_profit_fast(jumps, pr))
```

NOTES FROM CANDIDATES

Standard intern coding round, single source — clarification with interviewer is key (does "skip" advance by 1 or 0? are revisits allowed?).
Common bug: treating arr[i] as range cap rather than exact jump.

PREPARATION

Drill the reachability-jump, min-jumps, and coin-change family together so the DP shape is automatic.
Practice clarifying "can I skip without consuming a turn" before coding.

MEDIUM | 1Point3Acres | onsite-coding | 30 of 165

Count Same-Color Squares in Matrix

STUDY: TYPE | ALL TIME 51.2 | 30 DAYS 0 | PRIORITY 67/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #221 Maximal Square

LeetCode match: LC 221 Maximal Square (related)

Frequency: Low | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/count-same-color-squares

QUESTION

LeetCode 221 variant — count maximal same-color square sub-grids. DP on each cell as the bottom-right corner.

Input: m × n grid of colored cells.
Output: count of square sub-grids whose cells are all the same color (or maximum side length, depending on prompt).
DP: dp[i][j] = 1 + min(dp[i-1][j], dp[i][j-1], dp[i-1][j-1]) if grid[i][j] == grid[i-1][j] == grid[i][j-1] == grid[i-1][j-1] else 1.
Sum dp[i][j] across the grid for the count variant; max for the side variant.

EXAMPLES

The plain "count all-1 squares" DP generalizes to same-color directly.

APPROACH

Write the all-1-squares DP from memory in under 8 min. Generalize to multi-color in <2 min — only the equality check changes.

HOW TO THINK ABOUT IT

Let dp[i][j] be the side of the largest same-colour square whose bottom-right corner is (i, j). That square exists only if the three neighbours above, left and above-left have the same colour as the cell and can themselves carry a square, so dp is 1 plus the smallest of their dp values. Summing dp over all cells counts every square once (each cell contributes one square per side length up to dp).

Basis: LeetCode 221, Maximal Square, and LeetCode 1277, Count Square Submatrices with All Ones, generalised from 1s to any one colour.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
count = 0
for i, j in all_cells(grid):
    for k in range(1, min(m - i, n - j) + 1):
        cells = square(grid, i, j, k)
        if all(c == grid[i][j] for c in cells):
            count += 1
```

BRUTE FORCE

TIME	SPACE
O(m * n * min(m, n)^3)	O(1)

WHY IT IS SLOW

Re-checks the same cells again and again, O(m * n * min(m, n)^3). A dp on the bottom-right corner reuses the neighbours' results in O(m * n).

OPTIMAL SOLUTION · dp on the bottom-right corner

TIME	SPACE
O(m * n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return only the largest side instead of the count.

Keep the same dp and take the maximum instead of adding. The common bug is checking only the diagonal neighbour: the up and left neighbours must also match, otherwise a different colour can sit inside the square.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def square_sides(g):
    # side[i][j]: the biggest same-colour square whose
    # bottom-right corner is (i, j); one row at a time
    if not g:
        return []
    prev, out = [0] * len(g[0]), []
    for i, row in enumerate(g):
        cur = [1] * len(row)
        for j, c in enumerate(row):
            # all three neighbours must match this cell
            if i and j and g[i - 1][j] == c \
                    and g[i][j - 1] == c \
                    and g[i - 1][j - 1] == c:
                cur[j] = 1 + min(prev[j], cur[j - 1],
                                 prev[j - 1])
        out.append(cur)
        prev = cur
    return out


# BASE QUESTION (optimal): dp on the bottom-right corner
def count_same_color_squares(g):
    # every cell contributes one square per side up to its
    # side
    return sum(sum(row) for row in square_sides(g))


# FOLLOW-UP 1: Return only the largest side instead of the
# count.
def largest_side(g):
    # the variant that asks for the biggest square only
    return max((max(row) for row in square_sides(g)),
               default=0)
```

```
if __name__ == "__main__":
    # a 3 x 3 block of one colour: 9 + 4 + 1 squares
    block = ["RRR", "RRR", "RRR"]
    assert count_same_color_squares(block) == 14
    assert largest_side(block) == 3
    # a different colour inside blocks the bigger squares
    holes = ["RRR", "RGR", "RRR"]
    assert largest_side(holes) == 1
    assert count_same_color_squares(holes) == 9
    assert count_same_color_squares([]) == 0
```

```
    assert largest_side([]) == 0
```

NOTES FROM CANDIDATES

Variant reported in both intern VO and an additional NG round. Common bug: assuming all four corners equal is sufficient — need all three neighbors (top, left, top-left) to match the current cell.

PREPARATION

Write the all-1-squares DP from memory in under 8 min. Generalize to multi-color in <2 min — only the equality check changes.

Other: Design, Heaps, Intervals and Misc 1 questions

MEDIUM | IN APP LC 354 | 1Point3Acres | phone-screen | 31 of 165

Russian Doll Envelopes

STUDY: TYPE | ALL TIME 52.8 | 30 DAYS 33 | PRIORITY 27/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: your app's interview approach (LeetCode #354)

LeetCode match: LC 354 Russian Doll Envelopes

Frequency: Single report | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/russian-doll-envelopes

QUESTION

LeetCode 354. Maximum chain of envelopes that strictly fit inside each other. Sort + LIS reduction.

Input: list of (width, height) envelopes.
Output: longest chain where each envelope strictly fits in the next.
Trick: sort by width ascending, height descending (when widths tie); run LIS (Longest Increasing Subsequence) on heights. LIS with patience-sort gives O(n log n).

EXAMPLES

```
[[5,4],[6,4],[6,7],[2,3]] -> 3.
```

APPROACH

Write LIS O(n log n) from memory in under 8 min.
Justify the descending-height-on-tie trick out loud.
Plain LIS and the mountain-LIS variant make good drill partners.

HOW TO THINK ABOUT IT

Sort by width ascending so that only the heights matter, then find the longest strictly increasing subsequence of heights. Envelopes with equal width cannot nest, so sort those by height descending: then a strictly increasing run of heights can never use two envelopes of the same width.

Basis: LeetCode 354, Russian Doll Envelopes.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
envelopes.sort()  # by width
best = [1] * len(envelopes)
for i in range(len(envelopes)):
    for j in range(i):
        w1, h1 = envelopes[j]
        w2, h2 = envelopes[i]
        if w1 < w2 and h1 < h2:
            best[i] = max(best[i], best[j] + 1)
answer = max(best)
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Each envelope is compared with all earlier ones, O(n^2). After sorting, a longest increasing subsequence of the heights with binary search is O(n log n).

OPTIMAL SOLUTION · Sort, then LIS with binary search

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why sort heights descending when widths tie?

If two envelopes have the same width they cannot nest, but an ascending height order would let the LIS pick both. Descending order makes a strictly increasing height run use at most one envelope per width.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
from bisect import bisect_left


# BASE QUESTION (optimal): Sort, then LIS with binary
# search
def max_envelopes(envelopes):
    # sort by width; for equal widths put TALLER first so
    # a
    # strictly increasing height run can use only one of
    # them
    ordered = sorted(envelopes,
                     key=lambda e: (e[0], -e[1]))
    # tails[k]: smallest ending height of a chain of k + 1
    tails = []
    for _, h in ordered:
        i = bisect_left(tails, h)
        if i == len(tails):
            tails.append(h)
        else:
            tails[i] = h
    return len(tails)


# CHECKER: the O(n^2) version
def max_envelopes_slow(envelopes):
    # O(n^2) check used for testing
    ordered = sorted(envelopes)
    best = [1] * len(ordered)
    for i in range(len(ordered)):
        for j in range(i):
            wj, hj = ordered[j]
            wi, hi = ordered[i]
            if wj < wi and hj < hi:
                best[i] = max(best[i], best[j] + 1)
    return max(best, default=0)


if __name__ == "__main__":
    envs = [[5, 4], [6, 4], [6, 7], [2, 3]]
    assert max_envelopes(envs) == 3
    assert max_envelopes([]) == 0
    # equal widths cannot nest, however the heights go
    assert max_envelopes([[1, 1], [1, 2], [1, 3]]) == 1
    assert max_envelopes([[4, 5], [4, 6], [6, 7], [2, 3],
                          [1, 1]]) == 4
```

```python
    import itertools
    pts = [(w, h) for w in range(1, 4)
           for h in range(1, 4)]
    for combo in itertools.combinations(pts, 4):
        assert max_envelopes(list(combo)) == (
            max_envelopes_slow(list(combo)))
```

NOTES FROM CANDIDATES

Sorting heights descending on width-ties prevents same-width envelopes from chaining — easy to miss.
LIS via bisect_left on a tails array is the standard O(n log n) implementation.

PREPARATION

Write LIS O(n log n) from memory in under 8 min.
Justify the descending-height-on-tie trick out loud.
Plain LIS and the mountain-LIS variant make good drill partners.

PRACHUB

85 questions | Hard 23, Medium 58, Easy 4 | posted in the last 30 days: 0, last 90 days: 0 (grouped by recency, newest first) | topics: BFS/DFS and trees first

POSTED: 91 TO 180 DAYS AGO (15)

Hard (5)

HARD | IN APP LC 2536 | PracHub | Technical Screen | 32 of 165

Count Overlapping Rectangle Updates on a Grid

POSTED 2026-07-10 | 92 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 18.1 | 30 DAYS 0 | PRIORITY 150/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #2536 Increment Submatrices by One

LeetCode match: LC 2536 Increment Submatrices by One

Posted on PracHub: 2026-07-10 (updated 2026-07-18)

Original: https://prachub.com/coding-questions/count-overlapping-rectangle-updates-on-a-grid

QUESTION

Count Overlapping Rectangle Updates on a Grid Implement `range_add_counts(n, rectangles)`. Start with an `n x n` matrix of zeroes. Each rectangle is represented as `[row1, col1, row2, col2]` with inclusive, zero-based coordinates. For every rectangle, add one to each matrix cell inside that rectangle. Return the final matrix, where each cell therefore contains the number of input rectangles covering it.

Example

For `n = 3` and `rectangles = [[0, 0, 1, 1], [1, 1, 2, 2]]`, return:

```
[ [1, 1, 0], [1, 2, 1], [0, 1, 1] ]
```

Constraints

- `1 <= n <= 500`
- `0 <= len(rectangles) <= 100_000`
- `0 <= row1 <= row2 < n`
- `0 <= col1 <= col2 < n`

APPROACH

2D difference array: for each rectangle do +1 at (r1,c1), -1 at (r1,c2+1) and (r2+1,c1), +1 at (r2+1,c2+1); then take 2D prefix sums once. O(n^2 + q) instead of O(n^2*q).

HOW TO THINK ABOUT IT

Adding 1 to every cell of up to 100,000 rectangles one cell at a time is too slow. Record only the corners of each rectangle (+1 at the top-left, -1 just beyond the right and bottom edges, +1 at the bottom-right corner beyond), and rebuild the counts with one pass of 2D prefix sums. Each rectangle then costs O(1) instead of its area.

Basis: LeetCode 2536, Increment Submatrices by One (2D difference array).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def range_add_counts(n, rectangles):
    grid = [[0] * n for _ in range(n)]
    for r1, c1, r2, c2 in rectangles:
        for r in range(r1, r2 + 1):
            for c in range(c1, c2 + 1):
                grid[r][c] += 1
    return grid
```

TIME	SPACE
O(R * area)	O(n^2)

WHY IT IS SLOW

O(R * area): 100,000 rectangles of area up to 250,000 is billions of cell updates. A 2D difference array touches four corners per rectangle and one prefix-sum pass rebuilds the counts, O(R + n^2).

OPTIMAL SOLUTION · 2D difference array and prefix sums

TIME	SPACE
O(R + n^2)	O(n^2)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How many cells are covered by at least k rectangles?

Build the count matrix with the difference array and count the cells with value at least k. O(R + n^2).

FOLLOW-UP 2 The grid is huge (10^9 x 10^9) but there are few rectangles.

Coordinate-compress the corner coordinates and apply the same difference array on the compressed grid (at most (2R)^2 cells), or use a sweep line with a segment tree over columns. **Cost:** O(R log R) to sort the corner coordinates plus up to O(R^2) compressed cells, instead of 10^18 cells.

FOLLOW-UP 3 Rectangles are added and the count of a cell is queried online.

Use a 2D Fenwick tree with range update and point query (the difference-array idea turned into a BIT): O(log^2 n) per operation.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): 2D difference array and prefix
# sums
def range_add_counts(n, rects):
    # rects are [r1, c1, r2, c2], inclusive. Mark only the
    # 4
    # corners of each rectangle in a difference array ...
    d = [[0] * (n + 1) for _ in range(n + 1)]
    for r1, c1, r2, c2 in rects:
        d[r1][c1] += 1
        d[r1][c2 + 1] -= 1
        d[r2 + 1][c1] -= 1
        d[r2 + 1][c2 + 1] += 1
    # ... then two prefix sums spread them over the cells
    for r in range(n + 1):
        for c in range(1, n + 1):
            d[r][c] += d[r][c - 1]
    for c in range(n + 1):
        for r in range(1, n + 1):
            d[r][c] += d[r - 1][c]
    return [row[:n] for row in d[:n]]


# FOLLOW-UP 1: How many cells are covered by at least k
# rectangles?
def cells_at_least(n, rects, k):
    # how many cells are covered by k or more rectangles?
    counts = range_add_counts(n, rects)
    return sum(1 for row in counts for v in row if v >= k)


# FOLLOW-UP 2: The grid is huge (10^9 x 10^9) but there
# are few rectangles.
def cells_at_least_compressed(rects, k):
    # a huge grid, few rectangles: compress the
    # coordinates
    rows = sorted({r for r1, _, r2, _ in rects
                   for r in (r1, r2 + 1)})
    cols = sorted({c for _, c1, _, c2 in rects
                   for c in (c1, c2 + 1)})
    ri = {r: i for i, r in enumerate(rows)}
    ci = {c: i for i, c in enumerate(cols)}
    shape = (len(rows) + 1, len(cols) + 1)
    d = [[0] * shape[1] for _ in range(shape[0])]
    for r1, c1, r2, c2 in rects:
        a, b = ri[r1], ci[c1]
```

```
        e, f = ri[r2 + 1], ci[c2 + 1]
        d[a][b] += 1
        d[a][f] -= 1
        d[e][b] -= 1
        d[e][f] += 1
    total = 0
    run_col = [0] * (len(cols) + 1)
    for i in range(len(rows) - 1):
        row, run = [0] * (len(cols) + 1), 0
        for j in range(len(cols) - 1):
            run_col[j] += d[i][j]
            run += run_col[j]
            # each compressed cell stands for a block of
            # cells
            if run >= k:
                total += (rows[i + 1] - rows[i]) * (
                    cols[j + 1] - cols[j])
    return total


# FOLLOW-UP 3: Rectangles are added and the count of a
# cell is queried online.
class Fenwick2D:
    """Online updates and point reads: O(log^2 n)."""

    def __init__(self, n):
        self.n = n
        self.t = [[0] * (n + 2) for _ in range(n + 2)]

    def _add(self, r, c, v):
        i = r + 1
        while i <= self.n + 1:
            j = c + 1
            while j <= self.n + 1:
                self.t[i][j] += v
                j += j & -j
            i += i & -i

    def add_rect(self, r1, c1, r2, c2):
        corners = ((r1, c1, 1), (r1, c2 + 1, -1),
                   (r2 + 1, c1, -1), (r2 + 1, c2 + 1, 1))
        for r, c, v in corners:
            self._add(r, c, v)

    def get(self, r, c):
```

```
        total, i = 0, r + 1
        while i > 0:
            j = c + 1
            while j > 0:
                total += self.t[i][j]
                j -= j & -j
            i -= i & -i
        return total


if __name__ == "__main__":
    rects = [[0, 0, 1, 1], [1, 1, 2, 2]]
    assert range_add_counts(3, rects) == [
        [1, 1, 0], [1, 2, 1], [0, 1, 1]]
    assert cells_at_least(3, rects, 2) == 1
    assert cells_at_least(3, rects, 1) == 7
    # the compressed version gives the same area
    assert cells_at_least_compressed(rects, 2) == 1
    assert cells_at_least_compressed(rects, 1) == 7
    big = [[0, 0, 10 ** 9, 10 ** 9], [5, 5, 10, 10]]
    assert cells_at_least_compressed(big, 2) == 36
    # online updates and point queries
    f = Fenwick2D(3)
    for r in rects:
        f.add_rect(*r)
    assert f.get(1, 1) == 2 and f.get(0, 2) == 0
```

FUNCTION AND TEST CASES

Signature

```
def range_add_counts(n: int, rectangles: list[list[int]])
-> list[list[int]]:
```

Sample call

```
range_add_counts(1, [])
```

Test cases

Input	Expected
`(1, [])`	`[[0]]`
`(1, [[0, 0, 0, 0]])`	`[[1]]`

HARD | PracHub | Technical Screen | 33 of 165

Infection Spread on a Grid (Cellular Automaton)

POSTED 2026-06-14 | 118 DAYS AGO | LAST 6 MONTHS

STUDY: TYPE | ALL TIME 51.2 | 30 DAYS 0 | PRIORITY 64/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #994 Rotting Oranges, LeetCode #289 Game of Life

LeetCode match: LC 994 Rotting Oranges / LC 289 Game of Life (inferred from overview)

Posted on PracHub: 2026-06-14 (updated 2026-06-24)

Original: https://prachub.com/coding-questions/infection-spread-on-a-grid-cellular-automaton

QUESTION

Overview: This question tests a candidate's ability to implement and optimize a synchronous cellular automaton simulation on a 2D grid, assessing proficiency in BFS-based propagation, state machine design, and incremental computation. It falls under algorithms and grid simulation, evaluating practical coding skill and the ability to handle progressively complex constraints including recovery delays, barriers, and early-termination fixed-point detection.

APPROACH

Keep a frontier of newly changed cells and update only their neighbors each step (multi-source BFS style) instead of rescanning the grid; use a state machine for cell transitions.

INTERVIEW-DAY PLAN

CLARIFY FIRST

My copy has only the overview, so ask for the rules: the states (healthy, infected, recovered or immune), how infection spreads (four neighbors per step, synchronously), the recovery delay, whether barriers block spread, and what to return (the number of steps until nothing changes, or the final grid).

BRUTE FORCE TO SAY OUT LOUD

Rescan the entire grid on every step and compute the next grid from the old one. O(steps * mn).

OPTIMAL IDEA

Keep a frontier of cells that changed in the last step. Each step only their neighbors can change, so process the frontier like a multi-source BFS and update a separate next frontier to keep the update synchronous. Store the infection time per cell to apply the recovery delay (recover when step minus infected time reaches the delay). Stop when the frontier is empty and no recoveries are pending, since the grid has reached a fixed point. O(mn) overall.

DRY-RUN THESE CASES

No infected cells (0 steps), an isolated healthy cell behind barriers, a delay of 1, all cells infected at the start, two sources reaching a cell at the same time.

LIKELY FOLLOW-UPS

Different neighborhoods, probabilistic spread, or very large grids (sparse frontier).

PITFALLS

Updating cells in place during a step, which makes the spread asynchronous. Missing pending recoveries when deciding to stop.

HOW TO THINK ABOUT IT

A synchronous cellular automaton is a BFS in disguise: the step number is the BFS level. Only cells next to cells that just changed can change next, so keep a frontier instead of rescanning the grid. Always compute the next state from the old state (not in place) so all cells update together.

Basis: Written. Assumed rules (confirm them): '.' healthy, 'I' infected, 'X' barrier; each step every healthy cell with an infected 4-neighbour becomes infected, all at once; the answer is the number of steps until nothing changes.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    steps = 0
    while True:
        nxt = copy(grid)
        for r, c in all_cells(grid):
            if grid[r][c] == HEALTHY:
                if sick_neighbour(grid, r, c):
                    nxt[r][c] = INFECTED
        if nxt == grid:
            return steps
        grid = nxt
        steps += 1
```

TIME	SPACE
O(steps * m * n)	O(m * n)

WHY IT IS SLOW

Every step scans the whole grid even when only a thin edge is changing, O(steps * m * n). Keeping a frontier of newly infected cells (BFS) touches each cell once, O(m * n).

OPTIMAL SOLUTION · Frontier BFS (only recently infected cells spread)

TIME	SPACE
O(m * n)	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Add a recovery delay: an infected cell recovers after d steps and cannot spread afterwards.

A cell infects every healthy neighbor on the very next step, so recovery does not change how long spreading takes; it only changes what the grid looks like at time t. Store the step at which each cell was infected (the BFS level) and derive the state at any time: healthy, infected, or recovered when t minus its infection step is at least d.

FOLLOW-UP 2 Why can you stop early?

When the next frontier is empty no cell can change in any later step (the update only depends on the frontier), so the grid is at a fixed point. In a variant with pending recoveries keep going until those are done too.

FOLLOW-UP 3 Make the spread probabilistic.

A frontier cell may fail to infect a neighbor this step, so it stays in the frontier. Keep frontier cells until all their healthy neighbors are infected, and draw a random number per (cell, neighbor, step). The expected number of steps now needs simulation.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
STEPS = ((1, 0), (-1, 0), (0, 1), (0, -1))


# TIME each cell gets infected
def infection_times(grid):
    # step at which each cell gets infected (a BFS level);
    # 'I' = infected at time 0, '.' = healthy, '#' =
    # blocked
    rows, cols = len(grid), len(grid[0])
    when = {}
    frontier = [(r, c) for r in range(rows)
                for c in range(cols) if grid[r][c] == "I"]
    for cell in frontier:
        when[cell] = 0
    step = 0
    while frontier:
        step += 1
        nxt = []
        for r, c in frontier:
            for dr, dc in STEPS:
                a, b = r + dr, c + dc
                inside = 0 <= a < rows and 0 <= b < cols
                # every healthy neighbour is infected next
                # step
                if inside and grid[a][b] == "." \
                        and (a, b) not in when:
                    when[(a, b)] = step
                    nxt.append((a, b))
        frontier = nxt
    return when


# BASE QUESTION (optimal): Frontier BFS (only recently
# infected cells spread)
def spread_steps(grid):
    # steps until nothing changes any more
    when = infection_times(grid)
    return max(when.values(), default=0)


# FOLLOW-UP 1: Add a recovery delay: an infected cell
# recovers after d steps and ...
def grid_at(grid, t, recovery=None):
    # the grid after t steps; with a recovery delay d an
    # infected cell turns into 'R' (it spread already, so
    # the
    # timing above does not change)
    when = infection_times(grid)
    out = []
    for r, row in enumerate(grid):
        line = ""
        for c, ch in enumerate(row):
            start = when.get((r, c))
            if start is None or start > t:
                line += ch
            elif recovery and t >= start + recovery:
                line += "R"
            else:
                line += "I"
        out.append(line)
    return out


if __name__ == "__main__":
    g = ["I..", "...", "..."]
    assert spread_steps(g) == 4
    assert grid_at(g, 1) == ["II.", "I..", "..."]
    # with recovery after 1 step the source recovers first
    rec = grid_at(g, 1, recovery=1)
    assert rec == ["RI.", "I..", "..."]
    # a wall splits the grid: the far cell is never
    # infected
    wall = ["I#.", "I#."]
    assert spread_steps(wall) == 0
    assert grid_at(wall, 9)[0] == "I#."
    assert spread_steps(["..."]) == 0
```

FUNCTION AND TEST CASES

Signature

```
def solution(grid: list[str]) -> list[str]:
```

Sample call

```
solution(['HHH', 'HIH', 'HHH'])
```

Test cases

Input	Expected
`(['HHH', 'HIH', 'HHH'],)`	`['HIH', 'III', 'HIH']`
`(['HHH'],)`	`['HHH']`

HARD | IN APP LC 289 | PracHub | Technical Screen | 34 of 165

Simulate In-Place Cellular State Updates

POSTED 2026-05-04 | 159 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 23.4 | 30 DAYS 0 | PRIORITY 142/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #289 Game of Life

LeetCode match: LC 289 Game of Life (inferred from overview)

Posted on PracHub: 2026-05-04 (updated 2026-05-07)

Original: https://prachub.com/coding-questions/simulate-in-place-cellular-state-updates

QUESTION

Overview: This question evaluates a candidate's ability to implement grid-based state transitions and manage in-place updates with strict space constraints, assessing skills in matrix manipulation, neighbor traversal, and correctness under simultaneous update rules.

APPROACH

Encode old and new state together in each cell (extra bits or special values like 2 and 3) so neighbors still read the old state, then finalize in a second pass. O(mn) time, O(1) extra space.

HOW TO THINK ABOUT IT

'Update every cell at once, in place' means a cell's new value must not disturb its neighbors' reads. The trick is to store both the old and the new state in one cell (two bits), then decode in a second pass. Whenever you need old and new values together with no extra grid, think 'pack two states into one number'.

Basis: LeetCode 289, Game of Life.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def step(board):
    old = [row[:] for row in board]
    for r, c in all_cells(old):
        live = live_neighbours(old, r, c)
        alive = old[r][c] == 1
        if alive and live in (2, 3):
            board[r][c] = 1
        elif not alive and live == 3:
            board[r][c] = 1
        else:
            board[r][c] = 0
```

TIME	SPACE
O(m * n)	O(m * n)

BRUTE FORCE

WHY IT IS SLOW

Time O(m * n) is already optimal; the cost is a second full board, O(m * n) extra space. Storing the next state in a spare bit of each cell removes the copy.

OPTIMAL SOLUTION · Two-bit encoding in the same board

TIME	SPACE
O(m * n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The board is infinite, or huge and mostly empty.

Store only the live cells in a set. A cell's next state depends on its live neighbor count, so count how many live neighbors every candidate cell has with a Counter and keep cells with 3, or with 2 if already live. Work is proportional to the number of live cells.

FOLLOW-UP 2 Why is bit 0 used when counting neighbors?

Neighbors that were already processed in this pass carry their next state in bit 1. Masking with & 1 always reads the original generation, which is the whole point of the encoding.

FOLLOW-UP 3 Cells wrap around the edges (a torus).

Replace the bounds check with modular indexing: (r + dr) % m and (c + dc) % n. Be careful on very small boards where the same neighbor can be reached through two offsets.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter

AROUND = [(dr, dc) for dr in (-1, 0, 1)
          for dc in (-1, 0, 1) if (dr, dc) != (0, 0)]


def live_neighbors(board, r, c, wrap=False):
    m, n = len(board), len(board[0])
    count = 0
    for dr, dc in AROUND:
        a, b = r + dr, c + dc
        if wrap:
            # a torus: the edges are glued together
            a, b = a % m, b % n
        elif not (0 <= a < m and 0 <= b < n):
            continue
        # bit 0 is the OLD state, even for updated cells
        count += board[a][b] & 1
    return count


# BASE QUESTION (optimal): Two-bit encoding in the same
# board
```

```python
def step_in_place(board, wrap=False):
    m, n = len(board), len(board[0])
    for r in range(m):
        for c in range(n):
            live = live_neighbors(board, r, c, wrap)
            alive = board[r][c] & 1
            # bit 1 stores the NEW state
            if live == 3 or (alive and live == 2):
                board[r][c] |= 2
    for r in range(m):
        for c in range(n):
            # shift the new state into place
            board[r][c] >>= 1
    return board


# FOLLOW-UP 1: The board is infinite, or huge and mostly
# empty.
def step_sparse(live):
    # infinite or huge board: only the live cells are
    # stored
    counts = Counter()
```

```python
    for r, c in live:
        for dr, dc in AROUND:
            counts[(r + dr, c + dc)] += 1
    return {cell for cell, k in counts.items()
            if k == 3 or (k == 2 and cell in live)}


if __name__ == "__main__":
    board = [[0, 1, 0], [0, 0, 1], [1, 1, 1], [0, 0, 0]]
    want = [[0, 0, 0], [1, 0, 1], [0, 1, 1], [0, 1, 0]]
    assert step_in_place(board) == want
    # a blinker flips between a row and a column
    blinker = {(1, 0), (1, 1), (1, 2)}
    flipped = {(0, 1), (1, 1), (2, 1)}
    assert step_sparse(blinker) == flipped
    assert step_sparse(step_sparse(blinker)) == blinker
    # a block never changes
    block = {(0, 0), (0, 1), (1, 0), (1, 1)}
    assert step_sparse(block) == block
    # the sparse and dense versions agree on a glider
    glider = {(0, 1), (1, 2), (2, 0), (2, 1), (2, 2)}
    grid = [[0] * 6 for _ in range(6)]
    for r, c in glider:
        grid[r][c] = 1
    dense = step_in_place(grid)
    assert {(r, c) for r in range(6) for c in range(6)
            if dense[r][c]} == step_sparse(glider)
    # on a torus the left and right edges touch
    ring = [[1, 0, 1]]
    assert live_neighbors(ring, 0, 0, wrap=True) >= 1
```

FUNCTION AND TEST CASES

Signature

```python
def solution(grid: list[list[int]]) -> list[list[int]]:
```

Sample call

```python
solution([[0, 1, 0], [0, 0, 1], [1, 1, 1], [0, 0, 0]])
```

Test cases

Input	Expected
`([[0, 1, 0], [0, 0, 1], [1, 1, 1], [0, 0, 0]],)`	`[[0, 0, 0], [1, 0, 1], [0, 1, 1], [0, 1, 0]]`
`([[1, 1], [1, 1]],)`	`[[1, 1], [1, 1]]`

HARD | PracHub | Technical Screen | 35 of 165

Compute Turnstile Crossing Times

POSTED 2026-05-04 | 159 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 175/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

LeetCode match: LeetCode 'Time Taken to Cross the Door' (exact number unverified) (inferred from overview)

Posted on PracHub: 2026-05-04 (updated 2026-05-10)

Original: https://prachub.com/coding-questions/compute-turnstile-crossing-times

QUESTION

Overview: This question evaluates proficiency in queue simulation, event-driven scheduling, and handling priority and tie-breaking rules while achieving linear time complexity.

APPROACH

Two queues (entering, exiting) ordered by arrival; simulate time with the direction-priority and tie-break rules, jumping the clock when idle. O(n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask: how many people can pass per second, which direction goes first when both are waiting, whether the rule depends on what happened in the previous second, and how ties on arrival time break (by id). Clarify what to return (time per person).

BRUTE FORCE TO SAY OUT LOUD

Simulate every second from the earliest to the latest time, checking both queues. Correct but its cost grows with the size of the timestamps, not the number of people.

OPTIMAL IDEA

Keep two FIFO queues, enter and exit, and a variable for what the turnstile did in the previous second. Each step apply the priority rule to pick a queue. When both queues are empty, jump the clock to the next arrival and reset the previous-state to idle if at least one second was skipped. That makes the simulation O(n) after sorting.

DRY-RUN THESE CASES

INTERVIEW-DAY PLAN

Two people arriving at the same second with opposite directions. A long idle gap followed by a simultaneous pair. All enters, then all exits. A person who arrives while the turnstile was just used by the other direction.

LIKELY FOLLOW-UPS

Ask what happens when the idle jump leaves exactly one empty second versus more. Count that the 'previous second' state can be none, not only enter or exit.

PITFALLS

Resetting state only when the gap is two or more seconds. Forgetting to push arrivals that happened during the jump. Comparing queues by id instead of arrival order.

HOW TO THINK ABOUT IT

A scheduling rule that looks at 'what happened last second' is a state machine: write the state down (previous direction: enter, exit, none) before coding. If time values can be huge, simulate events, not seconds: jump the clock to the next arrival when both queues are empty, and remember an idle gap resets the state.

Basis: LeetCode 2534, Time Taken to Cross the Door. Assumed rules (confirm them): one person per second; if an enter and an exit compete, the previous second decides (enter if it was an enter, else exit, and exit if the door was idle).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(arrivals):
    t, prev = 0, None
    enter_q, exit_q = deque(), deque()
    while pending(arrivals, enter_q, exit_q):
        add_arrivals(t, arrivals, enter_q,
                     exit_q)
        who = pick_by_priority(prev, enter_q,
                               exit_q)
        if who is not None:
            passed[who] = t
            prev = direction_of(who)
        t += 1
    return passed
```

TIME	SPACE
O(T + n) where T is the largest timestamp	O(n)

WHY IT IS SLOW

A timestamp of 10^9 means a billion iterations even if nothing happens. Jumping to the next arrival when both queues are empty is O(n log n).

OPTIMAL SOLUTION · Event-driven simulation with two queues

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The priority when the turnstile was idle is different in this version of the question.

Keep the same loop and make the idle-state winner a parameter. Only the line that picks the queue changes, which is why the state machine should be written first.

FOLLOW-UP 2 Timestamps are up to 10^9.

That is exactly why the simulation jumps between events: the loop runs once per person, so the answer is O(n log n) no matter how large the times are.

FOLLOW-UP 3 Two turnstiles or a capacity of two people per second.

Run the same pick-a-queue step twice per tick (or per turnstile) and carry a previous-state variable per turnstile. Decide whether the two turnstiles share the queues.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


# BASE QUESTION (optimal): Event-driven simulation with
# two queues
# FOLLOW-UP 1: The priority when the turnstile was idle is
# different in this version ...
def turnstile_times(events, idle_first="exit"):
    # events[i] = (arrival time, "enter" or "exit");
    # the result is the second each person goes through
    n = len(events)
    order = sorted(range(n),
                   key=lambda i: (events[i][0], i))
    lines = {"enter": deque(), "exit": deque()}
    result = [0] * n
    t, i, prev, last_used = 0, 0, None, -10
    while i < n or lines["enter"] or lines["exit"]:
        if not lines["enter"] and not lines["exit"]:
            # nobody is waiting: jump to the next arrival
            t = max(t, events[order[i]][0])
            # an idle second forgets the last direction
            if t > last_used + 1:
                prev = None
        # everyone who has arrived by now joins a line
        while i < n and events[order[i]][0] <= t:
            person = order[i]
            lines[events[person][1]].append(person)
            i += 1
        if lines["enter"] and lines["exit"]:
            # FOLLOW-UP 1: idle tie-break set by
            # idle_first
```

```
            # both lines: keep the direction used last
            # second,
            # and use idle_first after an idle gap
            want = prev or idle_first
        else:
            want = "enter" if lines["enter"] else "exit"
        person = lines[want].popleft()
        result[person] = t
        prev, last_used = want, t
        t += 1
    return result


if __name__ == "__main__":
```

```
    both = [(0, "enter"), (0, "exit")]
    # idle tie: the exit goes first
    assert turnstile_times(both) == [1, 0]
    # a version where enter wins the idle tie
    assert turnstile_times(both, "enter") == [0, 1]
    # the direction in use keeps going
    keep = [(0, "enter"), (0, "enter"), (1, "exit")]
    assert turnstile_times(keep) == [0, 1, 2]
    # an idle second resets the state
    gap = [(0, "enter"), (10, "enter"), (10, "exit")]
    assert turnstile_times(gap) == [0, 11, 10]
    # huge timestamps are no problem: one loop per person
    far = [(10 ** 9, "enter"), (10 ** 9, "exit")]
    assert turnstile_times(far) == [10 ** 9 + 1, 10 ** 9]
    assert turnstile_times([]) == []
```

FUNCTION AND TEST CASES

Signature

```
def solution(time: list[int], direction: list[int]) -> lis
t[int]:
SAMPLE INPUT
[[0,0,1,5],[0,1,1,0]]
```

Test cases

Input	Expected
[[0, 0, 1, 5], [0, 1, 1, 0]]	[2, 0, 1, 5]
[[0, 0, 0], [0, 1, 0]]	[1, 0, 2]

HARD | PracHub | Technical Screen | 36 of 165

Convert Valid Snake Case to Lower Camel Case

POSTED 2026-04-16 | 177 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 180/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: No LC match (easy string manipulation)

Posted on PracHub: 2026-04-16 (updated 2026-07-18)

Original: https://prachub.com/coding-questions/convert-valid-snake-case-to-lower-camel-case

QUESTION

Convert Valid Snake Case to

Lower Camel Case Given a valid snake-case identifier, convert it to lower camel case. The input consists of one or more lowercase ASCII words separated by single underscores. There is no leading underscore, trailing underscore, or pair of adjacent underscores. The output keeps the first word lowercase, removes each underscore, and capitalizes the first letter of every later word. Implement:

```
def solve(name: str) -> str: ...
```

Constraints

- `1 <= len(name) <= 100_000`
- **name** matches `[a-z]+(?:_[a-z]+)*`

Examples

```
"foo_bar" -> "fooBar" "already" -> "already" "http_api
_name" -> "httpApiName"
```

APPROACH

Split on '_', keep the first word lowercase, capitalize the first letter of the rest, join. O(n). The Hard tag on PracHub looks like a labeling quirk.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether input can have digits, uppercase, leading or trailing underscores, or double underscores. The problem states it is valid, so say you will rely on that and mention what you would add if not.

BRUTE FORCE TO SAY OUT LOUD

Loop over characters and capitalize the character after each underscore. Linear and simple.

OPTIMAL IDEA

INTERVIEW-DAY PLAN

Split on '_', keep the first word as is, capitalize the first letter of each other word and join. O(n). The Hard label on PracHub looks like a labeling quirk; do not over-engineer it.

DRY-RUN THESE CASES

A single word, two words, many words, a one-letter word.

LIKELY FOLLOW-UPS

Convert back from camel to snake, or handle acronyms.

PITFALLS

Capitalizing the first word. Using replace on every underscore without capitalizing.

HOW TO THINK ABOUT IT

The statement says the input is valid (single underscores, no edge underscores), so rely on that and say what you would add if it were not. The pattern is 'first word unchanged, capitalize the first letter of each later word'.

Basis: Written. The PracHub Hard label looks like a labeling quirk; this is an easy string task.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def to_camel(s):
    out, up = "", False
    for ch in s:
        if ch == "_":
            up = True
        else:
            out += ch.upper() if up else ch
            up = False
    return out
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Already O(n); it is just longer than needed. Splitting on '_' and capitalising each word after the first is the short form.

OPTIMAL SOLUTION · Split on underscores and capitalize

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The input may have leading, trailing or repeated underscores, or mixed case.

Drop empty parts after the split, lowercase the first word, capitalize the rest. Say what you do with digits and non-letters, and keep the rule in one place.

FOLLOW-UP 2 Convert back from camel case to snake case.

Insert an underscore before each uppercase letter and lowercase it. Acronyms such as HTTPServer need a smarter rule (split between a lowercase-to-uppercase edge and between an acronym and the next word).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import re


# BASE QUESTION (optimal): Split on underscores and
# capitalize
def snake_to_camel(s):
    # foo_bar_baz -> fooBarBaz
    first, *rest = s.split("_")
    caps = [w[:1].upper() + w[1:] for w in rest]
    return first + "".join(caps)


# FOLLOW-UP 1: The input may have leading, trailing or
# repeated underscores, or ...
def snake_to_camel_tolerant(s):
    # leading, trailing or repeated underscores and mixed
    # case: drop empty parts, lowercase the first word
    words = [w for w in s.split("_") if w]
    if not words:
        return ""
    first = words[0].lower()
    rest = [w.capitalize() for w in words[1:]]
    return first + "".join(rest)


# FOLLOW-UP 2: Convert back from camel case to snake case.
def camel_to_snake(s):
    # fooBarBaz -> foo_bar_baz, and HTTPServer ->
    # http_server
    # 1) split an acronym from the next word: HTTPServer
    # -> HTTP_Server
    s = re.sub(r"([A-Z]+)([A-Z][a-z])", r"\1_\2", s)
    # 2) split a lower-case letter or digit from an upper-
    # case one
    s = re.sub(r"([a-z0-9])([A-Z])", r"\1_\2", s)
    return s.lower()


if __name__ == "__main__":
    assert snake_to_camel("foo_bar") == "fooBar"
    assert snake_to_camel("a_b_c") == "aBC"
    assert snake_to_camel("name") == "name"
    got = snake_to_camel("get_http_response")
    assert got == "getHttpResponse"
    # messy input
```

```
    messy = snake_to_camel_tolerant("_Foo__BAR_")
    assert messy == "fooBar"
    assert snake_to_camel_tolerant("___") == ""
    # and back again
    assert camel_to_snake("fooBarBaz") == "foo_bar_baz"
    assert camel_to_snake("HTTPServer") == "http_server"
    assert camel_to_snake("x") == "x"
    camel = snake_to_camel("my_var_2")
    assert camel_to_snake(camel) == "my_var2"
```

FUNCTION AND TEST CASES

Signature

```
def solve(name) -> str:
```

Sample call

```
solve('a')
```

Test cases

Input	Expected
`('a',)`	`'a'`
`('already',)`	`'already'`

ALSO REPORTED · 2 more

Define the scope and requirements for a snake_case to camelCase converter function. | Exponent

https://www.aced.io/questions/6328/define-scope-snake-case-camel-case-converter

Snake Case to Camel Case with Repository-Wide Refactor | 1Point3Acres | tech-screen | asked 2026-07-14 | Single report

https://www.1point3acres.com/interview/problems/company/google/snake-case-repository-refactor

The implementation is intentionally short. Most of the round is spent on scoping a safe refactor, validation strategy, symbol ownership, and compatibility boundaries.
Clarify whether names appear only as parsed identifiers or may also occur in strings, generated code, configuration, reflection, and serialized data.
A text replacement is not enough to distinguish local symbols from external APIs or public contracts.

Preparation: Implement the identifier conversion and enumerate edge cases before expanding scope.
Rehearse a migration plan covering symbol-aware rewriting, build and test validation, staged rollout, compatibility shims, and rollback.

Medium (10)

MEDIUM | IN APP LC 1102 | PracHub | Technical Screen | 37 of 165

Find A Threshold-Limited Path With Minimum Required Safety

POSTED 2026-07-06 | 96 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 25.5 | 30 DAYS 0 | PRIORITY 135/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #1102 Path With Maximum Minimum Value

LeetCode match: LC 1102 Path With Maximum Minimum Value (inferred from overview)

ABOUT THIS QUESTION

Posted on PracHub: 2026-07-06 (updated 2026-07-08)

Original: https://prachub.com/coding-questions/find-a-threshold-limited-path-with-minimum-required-safety

QUESTION

Overview: Practice a graph path interview problem that asks for the minimum required safety value along a threshold-limited path. The prompt targets minimax path reasoning, filtered edges, Dijkstra-style relaxation, disconnected graphs, and edge-case handling.

APPROACH

Minimax Dijkstra: heap keyed by the best bottleneck (min safety along the path) while skipping edges beyond the threshold; or binary search the safety value + BFS.

HOW TO THINK ABOUT IT

When the quality of a path is decided by its weakest edge, the best path does not need to be short, only strong. Two equivalent tools: add edges from strongest to weakest with Union-Find until source and target connect (that edge's value is the answer), or run Dijkstra with a max-heap where extending a path takes the minimum so far. Disconnected graphs must return the 'no path' value.

Basis: LeetCode 1102 (Path With Maximum Minimum Value) and the bottleneck path on a graph. Assumed form (confirm it): edges (u, v, safety); the safety of a path is its smallest edge; find the best achievable path safety from source to target, or -1 if disconnected.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(graph, src, dst):
    best = -INF
    for path in all_paths(graph, src, dst):
        weakest = min(edge_safety(path))
        best = max(best, weakest)
    return best
```

TIME	SPACE
exponential	O(path)

WHY IT IS SLOW

Exponential. Adding edges from strongest to weakest in a Union-Find until the source and target connect is O(E log E).

OPTIMAL SOLUTION · Union-Find adding edges from strongest to weakest

TIME	SPACE
O(E log E)	O(V)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Use a max-heap search instead of Union-Find.

Dijkstra where the value of a path is the minimum edge so far and you maximise it: pop the best bottleneck, extend with min(value, edge). O(E log V); Union-Find is simpler when you need only the value.

FOLLOW-UP 2 Answer many (source, target) queries.

Build the maximum spanning tree once (Kruskal) and answer each query as the minimum edge on the tree path, with binary lifting for O(log V) per query.

FOLLOW-UP 3 Edges below a threshold are forbidden (threshold-limited).

Filter them out before the search (or stop adding edges below the threshold in the Union-Find loop); if source and target are still disconnected the answer is -1.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


class UnionFind:
    def __init__(self, n):
        self.parent = list(range(n))

    def find(self, x):
        while self.parent[x] != x:
            self.parent[x] = self.parent[self.parent[x]]
            x = self.parent[x]
        return x

    def union(self, a, b):
        self.parent[self.find(a)] = self.find(b)


# BASE QUESTION (optimal): Union-Find adding edges from
# strongest to weakest
def best_path_safety(n, edges, s, t, threshold=None):
    # edges are (u, v, safety). The safety of a path is
    # its
    # weakest edge; return the best safety, or -1 if s and
    # t
    # are not connected through edges >= threshold
    if s == t:
        return float("inf")
    uf = UnionFind(n)
    # add the safest edges first: the edge that joins s
    # and t
    # is the weakest edge of the best path
    for u, v, w in sorted(edges, key=lambda e: -e[2]):
        if threshold is not None and w < threshold:
            break
        uf.union(u, v)
        if uf.find(s) == uf.find(t):
            return w
    return -1


# FOLLOW-UP 1: Use a max-heap search instead of Union-
# Find.
def best_path_safety_heap(n, edges, s, t, threshold=None):
    # same answer with a max-heap (Dijkstra on the
    # bottleneck)
    graph = [[] for _ in range(n)]
    for u, v, w in edges:
        if threshold is None or w >= threshold:
            graph[u].append((v, w))
            graph[v].append((u, w))
    best = [-1] * n
    best[s] = float("inf")
    heap = [(-best[s], s)]
    while heap:
        neg, u = heapq.heappop(heap)
        if -neg < best[u]:
            continue
        for v, w in graph[u]:
            # extending a path can only lower its weakest
            # edge
            cand = min(-neg, w)
            if cand > best[v]:
                best[v] = cand
                heapq.heappush(heap, (-cand, v))
    return best[t]


if __name__ == "__main__":
    edges = [(0, 1, 5), (1, 2, 3), (0, 2, 1), (2, 3, 4)]
    # 0-1-2-3 has weakest edge 3; 0-2-3 only 1
    assert best_path_safety(4, edges, 0, 3) == 3
    assert best_path_safety_heap(4, edges, 0, 3) == 3
    # edges below the threshold are forbidden
    assert best_path_safety(4, edges, 0, 3, 4) == -1
    assert best_path_safety_heap(4, edges, 0, 3, 4) == -1
    # disconnected, and source equals target
    assert best_path_safety(3, [(0, 1, 9)], 0, 2) == -1
    assert best_path_safety(3, [], 1, 1) == float("inf")
    one = [(0, 1, 9)]
    assert best_path_safety_heap(3, one, 0, 2) == -1
```

FUNCTION AND TEST CASES

Sample call

```
solution(4, [(0,1,5),(1,3,4),(0,2,2),(2,3,8)], 0, 3, 6)
```

Test cases

Input	Expected
(4, [(0,1,5),(1,3,4),(0,2,2),(2,3,8)], 0, 3, 6)	5
(3, [(0,1,7),(1,2,3)], 0, 2, 5)	-1

MEDIUM | PracHub | Technical Screen | 38 of 165

★ TOP 75: rank 51 in the Medium and Hard priority list

★ Filter Repeated Robot Status Messages

POSTED 2026-07-05 | 97 DAYS AGO | LAST 6 MONTHS

STUDY: TYPE | ALL TIME 51.2 | 30 DAYS 33 | PRIORITY 31/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #359 Logger Rate Limiter

LeetCode match: LC 359 Logger Rate Limiter (inferred from overview)

Posted on PracHub: 2026-07-05 (updated 2026-07-15)

Original: https://prachub.com/coding-questions/filter-repeated-robot-status-messages

QUESTION

Overview: Filter a timestamped robot status stream so a message reappears only when strictly more than ten seconds have passed since its last displayed occurrence. Preserve input order, track each exact case-sensitive message independently, and ensure hidden repeats do not reset the interval.

APPROACH

Hash map message -> last displayed timestamp; display only if now - last > 10 (strictly), then update. Preserve input order. O(1) per message.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the exact rule: show a message again only if more than 10 seconds have passed since it was last displayed (strictly more), whether messages are compared case-sensitively (yes), and whether hidden repeats extend the interval (no).

BRUTE FORCE TO SAY OUT LOUD

For each message scan the already displayed ones for the last occurrence. O(n^2).

OPTIMAL IDEA

Keep a dict from message to the time it was last displayed. For each message in order: if it is not in the dict or now - last > 10, display it and set last = now; otherwise skip it and do not update last. Output preserves input order. O(1) per message.

DRY-RUN THESE CASES

A repeat at exactly 10 seconds (hidden), at 11 seconds (shown), a hidden repeat followed by another repeat 10 seconds after the first display (shown, since hidden repeats do not reset), different casing (different messages), the first message.

LIKELY FOLLOW-UPS

INTERVIEW-DAY PLAN

Bounded memory (evict messages older than the interval), or a per-robot map.

PITFALLS

Updating the last time on a hidden message. Using at least instead of strictly more than.

HOW TO THINK ABOUT IT

The decision for a message depends only on when that exact message was last displayed, so a dictionary from message to last display time is all the state you need. The detail that decides correctness: the stored time changes only when a message is shown (a hidden repeat must not reset the clock), and the comparison is strict (> 10).

Basis: Written (compare LeetCode 359, Logger Rate Limiter). Rule: show a message again only when strictly more than 10 seconds have passed since it was last shown; hidden repeats do not extend the interval; messages are case-sensitive; input order is kept.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
shown = []  # (time, message)
def on_message(t, msg):
    last = None
    for t0, m0 in shown:
        if m0 == msg:
            last = t0  # most recent display
    if last is None or t - last > 10:
        shown.append((t, msg))
        return True
    return False
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Each message searches the whole history, O(n^2). A dictionary from message to its last displayed time makes each decision O(1).

OPTIMAL SOLUTION · Dictionary from message to the time it was last shown

TIME	SPACE
O(n)	O(distinct messages)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The stream never ends; memory must be bounded.

A message older than the gap can never be blocked again, so evict it. Keep a min-heap of (time shown, message) and pop entries older than the gap before each decision; delete the dictionary key only if it still points at that time.

FOLLOW-UP 2 Several robots send messages.

Use (robot id, message) as the key, or one filter per robot. The same logic applies per key.

FOLLOW-UP 3 The interval depends on the message severity.

Look up the gap from a severity table and use it in the comparison; the state (last shown time) is unchanged.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


# BASE QUESTION (optimal): Dictionary from message to the
# time it was last shown
def filter_status(stream, gap=10):
    # show a message only if MORE than `gap` seconds
    # passed
    # since it was last shown; hidden repeats change
    # nothing
    last, shown = {}, []
    for ts, msg in stream:
        if msg not in last or ts - last[msg] > gap:
            last[msg] = ts
            shown.append((ts, msg))
    return shown


# FOLLOW-UP 1: The stream never ends; memory must be
# bounded.
class BoundedFilter:
    """An endless stream: forget messages that can no
    longer be blocked, so memory stays small."""

    def __init__(self, gap=10):
        self.gap = gap
        self.last = {}
        # (time shown, message), oldest first
        self.heap = []

    def show(self, ts, msg):
        # drop entries older than the gap
        while self.heap:
            if ts - self.heap[0][0] <= self.gap:
                break
            old_ts, old_msg = heapq.heappop(self.heap)
            # delete only if it was not shown again since
            if self.last.get(old_msg) == old_ts:
                del self.last[old_msg]
        if msg in self.last:
            return False
        self.last[msg] = ts
        heapq.heappush(self.heap, (ts, msg))
        return True
```

```
# FOLLOW-UP 2: Several robots send messages.
class PerRobotFilter:
    """Several robots; the gap depends on severity."""

    def __init__(self, gaps, default=10):
        self.gaps, self.default = gaps, default
        self.last = {}

    def show(self, robot, ts, msg, severity=None):
        key = (robot, msg)
        gap = self.gaps.get(severity, self.default)
        last = self.last.get(key)
        if last is not None and ts - last <= gap:
            return False
        self.last[key] = ts
        return True


if __name__ == "__main__":
    stream = [(0, "a"), (5, "a"), (10, "a"), (11, "a"),
              (12, "b"), (22, "a")]
    # 10 is hidden (not MORE than 10 after 0); 11 shows
    assert filter_status(stream) == [(0, "a"), (11, "a"),
                                     (12, "b"), (22, "a")]
    # messages are case sensitive
    assert filter_status([(0, "A"), (1, "a")]) == [
        (0, "A"), (1, "a")]
    b = BoundedFilter()
    shows = [b.show(ts, msg) for ts, msg in stream]
    assert shows == [True, False, False, True, True, True]
    assert len(b.last) <= 2
    r = PerRobotFilter({"high": 2})
    assert r.show("r1", 0, "x")
    assert not r.show("r1", 9, "x")
    # another robot, and a stricter severity
    assert r.show("r2", 1, "x")
    assert r.show("r1", 1, "y", "high")
    assert r.show("r1", 4, "y", "high")
```

FUNCTION AND TEST CASES

Signature

```
def filter_messages(events: list[tuple[int, str]]) -> list
[tuple[int, str]]:
```

Sample call

```
filter_messages([])
```

Test cases

Input	Expected
`([],)`	`[]`
`([[10, "solar panel activated"], [13, "solar panel activated"], [20, "solar panel activated"], [21, "solar panel activated"]],)`	`[[10, "solar panel activated"], [21, "solar panel activated"]]`

ALSO REPORTED · 1 more

Robot Status Message Deduplication Window | 1Point3Acres | onsite-coding | asked 2026-09-10 | Low

https://www.1point3acres.com/interview/problems/company/google/robot-status-message-deduplication

ALSO REPORTED · 1 more

The state transition occurs only on a displayed event. Updating on every receipt changes the semantics and can suppress a frequently repeated message forever.
Resolve the exact-boundary rule before coding and make the comparison match that contract.
For out-of-order arrival, clarify how the 10-second interval applies to late events and whether an earlier print decision can ever be revisited. These semantics are not specified by the logger variant; do not assume the chronological-stream contract resolves them.

Preparation: Implement the stream processor with per-message state, then trace repeated and interleaved messages by hand. Write tests for the first occurrence, an event just inside the window, exactly at the boundary, just outside it, and a hidden event followed by an allowed display.

MEDIUM | PracHub | Technical Screen | 39 of 165

Find the Largest Monotone Increasing Number

POSTED 2026-07-04 | 98 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 5 | 30 DAYS 0 | PRIORITY 170/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 738 Monotone Increasing Digits (inferred from overview)

Posted on PracHub: 2026-07-04 (updated 2026-07-15)

Original: https://prachub.com/coding-questions/find-the-largest-monotone-increasing-number

QUESTION

Overview: Find the largest number no greater than n whose decimal digits are monotone increasing. Develop a linear-time greedy correction that revisits earlier decreasing boundaries and fills the remaining suffix optimally without introducing leading zeros.

APPROACH

Scan digits right to left; when digit[i-1] > digit[i], decrement digit[i-1] and mark position i as the point to fill with 9s. O(d).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether monotone means non-decreasing (equal digits allowed) or strictly increasing, whether n can be 0, and whether n is given as an integer or a very long string.

BRUTE FORCE TO SAY OUT LOUD

Decrement n until its digits are monotone. Correct but up to O(n * d).

OPTIMAL IDEA

Scan the digits from right to left. When digit[i - 1] > digit[i], decrease digit[i - 1] by one and remember i as the first position to fill with 9s. After the scan set every digit from that marker to the end to 9. O(d) time.

DRY-RUN THESE CASES

10 gives 9, 332 gives 299, 1234 stays 1234, 100 gives 99, 0 gives 0, 1000 gives 999.

LIKELY FOLLOW-UPS

Strictly increasing digits variant, or return the largest number below n when n itself is already valid.

PITFALLS

Scanning left to right, which misses the cascading decrement. Setting 9s from the wrong index.

HOW TO THINK ABOUT IT

If a digit is smaller than the one before it, the earlier digit has to drop by one and everything after that point can become 9 (as large as possible). Dropping a digit can break the pair before it, so scan from the right: each repair is checked against the digit to its left. That is why one right-to-left pass is enough.

Basis: LeetCode 738, Monotone Increasing Digits (non-decreasing digits).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n):
    while not is_non_decreasing(str(n)):
        n -= 1
    return n
```

TIME	SPACE
O(n * d)	O(1)

WHY IT IS SLOW

n can be 10^9, so it may take a billion steps. A right-to-left scan that lowers a digit where order breaks and fills the rest with 9s is O(digits).

OPTIMAL SOLUTION · Right-to-left scan, then fill with nines

TIME	SPACE
O(d)	O(d)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The number is given as a string with 100,000 digits.

The scan works directly on the digit list, so keep it as a list of characters and never convert to an integer until the end (or not at all). The algorithm is O(d).

FOLLOW-UP 2 Return the smallest monotone number that is at least n instead.

Scan left to right for the first digit that is larger than its right neighbour and copy that digit over the whole suffix (332 becomes 333). The prefix before it is already monotone.

FOLLOW-UP 3 Digits must be strictly increasing.

Same idea, but the suffix to fill is the largest strictly increasing run (for example ...6789), and you must check that the prefix leaves enough room. Say the extra care and write the check as a brute-force comparison first.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Right-to-left scan, then fill
# with nines
def largest_monotone(n):
    # largest number <= n whose digits never decrease
    d = list(str(n))
    mark = len(d)
    # scan from the right; a drop forces the left digit
    # down by
    # one and everything after it up to 9
    for i in range(len(d) - 1, 0, -1):
        if d[i - 1] > d[i]:
            d[i - 1] = str(int(d[i - 1]) - 1)
            mark = i
    for i in range(mark, len(d)):
        d[i] = "9"
    return int("".join(d))


# FOLLOW-UP 1: The number is given as a string with
# 100,000 digits.
def largest_monotone_string(digits):
    # the same on a string of any length (no big integers)
    d = list(digits)
    mark = len(d)
    for i in range(len(d) - 1, 0, -1):
        if d[i - 1] > d[i]:
            d[i - 1] = chr(ord(d[i - 1]) - 1)
            mark = i
    d[mark:] = "9" * (len(d) - mark)
    # a leading zero (from 10 -> 09) is dropped
    return "".join(d).lstrip("0") or "0"


# FOLLOW-UP 2: Return the smallest monotone number that is
# at least n instead.
def smallest_monotone_at_least(n):
    # follow-up: smallest monotone number >= n
    d = list(str(n))
    for i in range(len(d) - 1):
        if d[i] > d[i + 1]:
            # copy the bigger digit over the rest: 332 ->
            # 333
            d[i + 1:] = d[i] * (len(d) - i - 1)
            break
    return int("".join(d))
```

```
def is_monotone(n):
    s = str(n)
    return all(a <= b for a, b in zip(s, s[1:]))


if __name__ == "__main__":
    assert largest_monotone(10) == 9
    assert largest_monotone(1234) == 1234
    assert largest_monotone(332) == 299
    assert largest_monotone(0) == 0
    assert largest_monotone_string("332") == "299"
    assert largest_monotone_string("10") == "9"
    assert smallest_monotone_at_least(332) == 333
    assert smallest_monotone_at_least(120) == 122
    # check against brute force for many numbers
    for n in range(0, 3000):
        every = range(n + 1)
        want = max(x for x in every if is_monotone(x))
        assert largest_monotone(n) == want
        text = largest_monotone_string(str(n))
        assert text == str(want)
        later = range(n, 99999)
        up = next(x for x in later if is_monotone(x))
        assert smallest_monotone_at_least(n) == up
    # a 100,000 digit input is fine as a string
    big = "9" * 50000 + "1" * 50000
    assert largest_monotone_string(big)[:3] == "899"
```

FUNCTION AND TEST CASES

Sample call

```
largest_monotone_increasing(0)
```

Test cases

Input	Expected
(0,)	0
(9,)	9

MEDIUM | PracHub | Technical Screen | 40 of 165

Check Whether Digits Are Monotone Increasing

POSTED 2026-07-04 | 98 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 189/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: No LC match (easy digit scan) (inferred from overview)

Posted on PracHub: 2026-07-04 (updated 2026-07-15)

Original: https://prachub.com/coding-questions/check-whether-digits-are-monotone-increasing

QUESTION

Overview: Check whether a non-negative integer's decimal digits are non-decreasing from left to right. Cover zero, single-digit values, repeated digits, and an O(d) implementation using either arithmetic digit extraction or string traversal.

APPROACH

Compare each digit with the previous one using % 10 and // 10 from the right (or string scan); handle 0 and single digits. O(d).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether equal neighbors are allowed (non-decreasing), whether the input can be negative, and whether to use the integer or string form.

BRUTE FORCE TO SAY OUT LOUD

Convert to a string and compare each pair. Fine and O(d).

OPTIMAL IDEA

Without strings: peel digits from the right with % 10 and // 10, keeping the previous digit; fail if the current digit is greater than the previous one seen to its right. O(d), O(1) space.

DRY-RUN THESE CASES

0, a single digit, 1234, 1224, 1243, 100.

LIKELY FOLLOW-UPS

Strictly increasing, or find the next monotone number.

PITFALLS

Comparing in the wrong direction when scanning right to left.

HOW TO THINK ABOUT IT

Compare neighbouring digits. You can read the digits from the right with % 10 and // 10, remembering the previous (right-hand) digit: the number is monotone if no digit is larger than the one to its right. Say first whether equal neighbours are allowed.

Basis: The check behind LeetCode 738 (non-decreasing digits).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def is_monotone(x):
    s = str(x)
    return s == "".join(sorted(s))
```

TIME	SPACE
O(d log d)	O(d)

WHY IT IS SLOW

Sorting costs O(d log d) and copies the digits. Comparing each digit with its neighbour while peeling digits with % 10 is O(d) with O(1) space.

OPTIMAL SOLUTION · Peel digits from the right and compare with the previous one

TIME	SPACE
O(d)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Strictly increasing digits.

Use >= instead of > when comparing with the previous digit, and start prev at 10 so a single digit passes.

FOLLOW-UP 2 Negative numbers or numbers in another base.

Decide what monotone means for the sign (usually apply it to the absolute value). For base b replace 10 with b in % and //.

FOLLOW-UP 3 Find the next monotone number after n.

That is the left-to-right fix from the previous question: find the first descent and copy that digit across the rest.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Peel digits from the right and
# compare with the previous one
def is_monotone_digits(n):
    # non-decreasing digits, read from the right with n %
    # 10
    prev = 9
    while n:
        d = n % 10
        # a digit bigger than the one to its right: a
        # descent
        if d > prev:
            return False
        prev = d
        n //= 10
    return True


# SAME TEST on the text of the number
def is_monotone_string(n):
    # the same test on the text of the number
    s = str(n)
    return all(a <= b for a, b in zip(s, s[1:]))


# FOLLOW-UP 1: Strictly increasing digits.
def is_strictly_monotone(n):
    # strictly increasing: start prev at 10, compare with
    # >=
    prev = 10
    while n:
        d = n % 10
        if d >= prev:
            return False
        prev = d
        n //= 10
    return True
```

```
# FOLLOW-UP 2: Negative numbers or numbers in another
# base.
def is_monotone_base(n, base=10):
    # any base: use the base for % and //
    prev = base - 1
    while n:
        d = n % base
        if d > prev:
            return False
        prev = d
        n //= base
    return True


# FOLLOW-UP 3: Find the next monotone number after n.
def next_monotone(n):
    # smallest monotone number AFTER n: fix the first
    # descent
    d = list(str(n + 1))
    for i in range(len(d) - 1):
        if d[i] > d[i + 1]:
            d[i + 1:] = d[i] * (len(d) - i - 1)
            break
    return int("".join(d))


if __name__ == "__main__":
    assert is_monotone_digits(0) and is_monotone_digits(7)
    assert is_monotone_digits(1223)
    assert is_monotone_digits(999)
    assert not is_monotone_digits(332)
    assert not is_monotone_digits(10)
    assert is_strictly_monotone(1234)
    assert not is_strictly_monotone(1224)
    assert is_strictly_monotone(5)
    # binary 11 -> 3 is monotone; binary 10 -> 2 is not
    assert is_monotone_base(3, 2)
    assert not is_monotone_base(2, 2)
    assert next_monotone(332) == 333
    assert next_monotone(9) == 11
    for n in range(2000):
        by_text = is_monotone_string(n)
        assert is_monotone_digits(n) == by_text
```

FUNCTION AND TEST CASES

Signature

```
def has_monotone_increasing_digits(n: int) -> bool:
SAMPLE INPUT
0
```

Test cases

Input	Expected
0	True
7	True

MEDIUM | IN APP LC 208 | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 41 of 165

Build Prefix Lookup with a Trie

POSTED 2026-07-03 | 99 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 36 | 30 DAYS 0 | PRIORITY 104/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #208 Implement Trie (Prefix Tree)

LeetCode match: LC 208 Implement Trie (Prefix Tree) (inferred from overview)

Posted on PracHub: 2026-07-03 (updated 2026-07-04)

Original: https://prachub.com/coding-questions/build-prefix-lookup-with-a-trie

QUESTION

Overview: Practice a Google coding interview problem focused on build prefix lookup with a trie. The prompt emphasizes edge cases, clean implementation, and verifiable test behavior without revealing the solution.

APPROACH

Trie of dict words; walk the prefix, then DFS the subtree to collect completions (optionally store counts at nodes).

HOW TO THINK ABOUT IT

Prefix questions repeat work when each query scans the whole word list. A trie stores each prefix once: walk down by the query, then everything below that node is a completion. Keep counters or a word flag in the nodes to answer follow-ups such as 'how many words start with this' or 'top K completions' without another walk.

Basis: LeetCode 208 (Implement Trie) and 1268 (Search Suggestions System).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def lookup(words, prefix):
    found = []
    for word in words:
        if word.startswith(prefix):
            found.append(word)
    return found
```

TIME	SPACE
O(W * L) per query	O(1) extra

WHY IT IS SLOW

Every query touches every word, O(W * L). A trie walks only the prefix and then the subtree below it.

OPTIMAL SOLUTION · Trie with a DFS below the prefix node

TIME	SPACE
O(L) to walk the prefix + O(size of the answer)	O(total characters)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How many words start with this prefix?

Store a counter in each node that is incremented when a word passes through it; the answer is the counter at the end of the prefix walk, O(L) with no DFS.

FOLLOW-UP 2 Return only the top 3 completions (by frequency or alphabetically).

Keep at each node a short list of its best K words (updated on insert), or bound the DFS: visit children in alphabetical order and stop after K words. That is the LeetCode 1268 style answer.

FOLLOW-UP 3 Memory is large (many words with long common prefixes).

A compressed (radix) trie stores whole edge labels instead of single characters; a sorted array with binary search over prefixes uses the least memory for a static dictionary. **Cost:** a radix trie has O(number of words) nodes instead of O(total characters); a sorted array uses O(total characters) with O(L log W) lookups.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class Node:
    def __init__(self):
        self.children = {}
        # does a word end here?
        self.is_word = False
        # how many words pass through this node
        self.count = 0


# BASE QUESTION (optimal): Trie with a DFS below the
# prefix node
# FOLLOW-UP 1: How many words start with this prefix?
class PrefixTrie:
    def __init__(self, words=()):
        self.root = Node()
        for w in words:
            self.insert(w)

    def insert(self, word):
        node = self.root
        for ch in word:
            node = node.children.setdefault(ch, Node())
            node.count += 1
        # a repeated word is only counted as one word
        if not node.is_word:
            node.is_word = True
        else:
            self.undo_count(word)

    def undo_count(self, word):
        node = self.root
        for ch in word:
            node = node.children[ch]
            node.count -= 1

    def walk(self, prefix):
        node = self.root
        for ch in prefix:
            node = node.children.get(ch)
            if node is None:
                return None
        return node

    # FOLLOW-UP 1: how many words start with the prefix
    def count_prefix(self, prefix):
        # how many words start with the prefix: O(len)
        node = self.walk(prefix)
        if prefix == "":
            return self.root_count()
        return node.count if node else 0

    def root_count(self):
        kids = self.root.children.values()
        return sum(c.count for c in kids)

    # FOLLOW-UP 2: only the top k completions
    def suggest(self, prefix, k=3):
        # first k completions in alphabetical order; the
        # DFS
        # visits children in order and stops after k words
        node = self.walk(prefix)
        out = []
        if node is None:
            return out
        stack = [(node, prefix)]
        while stack and len(out) < k:
            n, text = stack.pop()
            if n.is_word:
                out.append(text)
            # reversed so the smallest letter is popped
            # first
            for ch in sorted(n.children, reverse=True):
                stack.append((n.children[ch], text + ch))
        return out

    def completions(self, prefix):
        # every word with the prefix
        return self.suggest(prefix, k=10 ** 9)


if __name__ == "__main__":
    t = PrefixTrie(["apple", "app", "apricot", "banana",
                    "apple"])
    ap = t.completions("ap")
    assert ap == ["app", "apple", "apricot"]
    everything = t.completions("")
    assert everything[-1] == "banana"
    assert t.completions("x") == []
    assert t.count_prefix("ap") == 3
    assert t.count_prefix("b") == 1
    assert t.count_prefix("zz") == 0
    # the top 2 in alphabetical order
    assert t.suggest("ap", 2) == ["app", "apple"]
    assert t.count_prefix("") == 4
```

FUNCTION AND TEST CASES

Signature

```
def solution(words: list[str], queries: list[str]) -> list
[list[str]]:
SAMPLE INPUT
{"words":["car","cat","dog"],"queries":["ca","d"]}
```

Test cases

Input	Expected
`{"words":["car","cat","dog"],"queries":["ca","d"]}`	`[["car","cat"],["dog"]]`
`{"words":[],"queries":["a"]}`	`[[]]`

ALSO REPORTED · 1 more

Trie Prefix Search / Autocomplete | 1Point3Acres | tech-screen, onsite-coding | asked 2026-07-02 | Medium

https://www.1point3acres.com/interview/problems/company/google/trie-prefix-search-autocomplete

Standard implementation: each trie node has a children map and an is_end flag.
Two collection patterns at the prefix: (a) DFS from the prefix node and collect all word-end nodes, (b) store the top-K candidates at every node during insert (Google-preferred for autocomplete).
The standard sorted-suggestions follow-up wants 3 suggestions per prefix-length — handle with sorted children or per-node sorted lists.

Preparation: Write the trie class from memory in under 12 min. Drill the DFS-collect and the sorted-per-node variants; know which is faster in which scenario.
For frequency-ranking, practice the design-autocomplete variant (per-node top-K updated on insert) as a stretch goal.

MEDIUM | PracHub | Technical Screen | 42 of 165

Count Clusters of 2D Points Within a Radius

POSTED 2026-06-18 | 114 DAYS AGO | LAST 6 MONTHS

STUDY: TALK **ALL TIME 40.7** **30 DAYS 0** **PRIORITY 89/224**

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #547 Number of Provinces

LeetCode match: LC 547 Number of Provinces (inferred from overview)

Posted on PracHub: 2026-06-18 (updated 2026-07-01)

Original: https://prachub.com/coding-questions/count-clusters-of-2d-points-within-a-radius

QUESTION

Overview: This question tests graph traversal skills, specifically identifying connected components among a set of 2D points using distance-based adjacency. It assesses the ability to model a geometric problem as a graph and apply DFS, BFS, or Union-Find, a common evaluation of algorithmic thinking in coding interviews. It also probes awareness of efficiency trade-offs when scaling to large point sets.

APPROACH

Union-find over points with distance <= r; count roots. Use squared distance; spatial grid hashing for speed.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the distance is Euclidean, whether the radius is inclusive (a distance of at most r connects), whether points are integers, and the number of points.

BRUTE FORCE TO SAY OUT LOUD

Union-Find over all pairs of points, comparing every pair. O(n^2) distance checks.

OPTIMAL IDEA

Compare squared distances to r squared (no square roots, exact for integers). For many points hash them into grid cells of side r so each point only checks its own and the eight neighboring cells; use Union-Find to merge and count the components with distinct roots. About O(n) expected for evenly spread points.

DRY-RUN THESE CASES

No points, one point, two points exactly r apart (connected if inclusive), a chain of points each close to the next (one cluster), duplicate points.

LIKELY FOLLOW-UPS

Dynamic points, a very large radius, or reporting the largest cluster.

PITFALLS

Using the cell size smaller than r so close points fall in non-adjacent cells. Comparing floating-point distances for equality.

HOW TO THINK ABOUT IT

Model it as a graph where points within r are neighbours and count connected components with Union-Find. The all-pairs check is O(n^2); to speed it up, hash points into square cells of side r so that only points in the same or an adjacent cell can be within r. Compare squared distances to r * r to avoid square roots.

Basis: Connected components of a distance graph (LeetCode 547 idea). Two points are connected when their Euclidean distance is at most r; a cluster is a connected component.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
parent = list(range(n))
def find(x):
    while parent[x] != x:
        x = parent[x]
    return x
for a, b in combinations(range(n), 2):
    if dist2(points[a], points[b]) <= r * r:
        parent[find(a)] = find(b)
clusters = len({find(i) for i in range(n)})
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

n^2 / 2 distance checks. Hashing points into grid cells of side r means each point is compared only with points in its own and neighbouring cells.

OPTIMAL SOLUTION · Grid hashing with cells of side r, then Union-Find

TIME	SPACE
O(n) expected for evenly spread points	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Report the size of the largest cluster.

Count points per root after the unions (a Counter of find(i)). The unions are the same.

FOLLOW-UP 2 Points arrive one at a time.

Insert the point into its grid cell, union it with every point within r in the 9 surrounding cells, and keep the component count: components += 1 - (number of distinct roots merged).

FOLLOW-UP 3 Millions of points in 3D or higher.

The grid generalises (3^d neighbouring cells), but for high dimensions use a k-d tree or locality-sensitive hashing; or DBSCAN, which is this problem with a minimum neighbour count. **Cost:** grid hashing visits 3^d neighbouring cells per point, O(n * 3^d); a k-d tree builds in O(n log n) with O(n^(1 - 1/d) + k) range queries.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter, defaultdict


# FOLLOW-UP 2: Points arrive one at a time.
class Clusters:
    """Points arrive one by one; count the clusters."""

    def __init__(self, r):
        self.r = r
        # grid cell (side r) -> indices of points inside
        self.cells = defaultdict(list)
        self.points, self.parent = [], []
        self.components = 0

    def find(self, x):
        while self.parent[x] != x:
            self.parent[x] = self.parent[self.parent[x]]
            x = self.parent[x]
        return x

    def near(self, p, q):
        dx, dy = p[0] - q[0], p[1] - q[1]
        return dx * dx + dy * dy <= self.r * self.r

    def add(self, x, y):
        i = len(self.points)
        self.points.append((x, y))
        self.parent.append(i)
        self.components += 1
        size = self.r or 1
        cx, cy = x // size, y // size
        self.cells[(cx, cy)].append(i)
        # look only at the 9 cells around the new point
        for dx in (-1, 0, 1):
            for dy in (-1, 0, 1):
                key = (cx + dx, cy + dy)
                cell = self.cells.get(key, ())
                for j in cell:
                    q = self.points[j]
                    if j != i and self.near((x, y), q):
                        a, b = self.find(i), self.find(j)
                        if a != b:
                            self.parent[a] = b
                            self.components -= 1
        return self.components

    def largest(self):
        sizes = Counter(self.find(i)
                        for i in range(len(self.points)))
        return max(sizes.values(), default=0)


# BASE QUESTION (optimal): Grid hashing with cells of side
# r, then Union-Find
def count_clusters(points, r):
    c = Clusters(r)
    for x, y in points:
        c.add(x, y)
    return c.components


# FOLLOW-UP 1: Report the size of the largest cluster.
def largest_cluster(points, r):
    c = Clusters(r)
    for x, y in points:
        c.add(x, y)
    return c.largest()


if __name__ == "__main__":
    line = [(0, 0), (3, 0), (6, 0), (20, 20)]
    assert count_clusters(line, 3) == 2
    assert largest_cluster(line, 3) == 3
    assert count_clusters([], 3) == 0
```

```
    # online: the count changes as points arrive
    c = Clusters(2)
    assert [c.add(*p) for p in [(0, 0), (10, 10), (1, 1),
                                (5, 5)]] == [1, 2, 2, 3]
    # (3, 3) is alone; (4, 4) then bridges it to (5, 5)
    assert c.add(3, 3) == 4
    assert c.add(4, 4) == 3
    assert count_clusters([(1, 1), (1, 1)], 0) == 1
```

FUNCTION AND TEST CASES

Signature

```
def countClusters(points: list[list[int]], r: int) -> int:
```

Sample call

```
countClusters([[0, 0], [1, 0], [10, 10]], 2)
```

Test cases

Input	Expected
`([[0, 0], [1, 0], [10, 10]], 2)`	`2`
`([[0, 0], [3, 0], [6, 0]], 3)`	`1`

ALSO REPORTED · 2 more

Count Connected Clusters of Two-Dimensional Points | PracHub | Technical Screen

https://prachub.com/coding-questions/count-connected-clusters-of-two-dimensional-points

2D Points Connected Components by Radius | 1Point3Acres | phone-screen | asked 2026-08-04 | Low

https://www.1point3acres.com/interview/problems/company/google/points-connected-components-by-radius

DFS, BFS, or Union-Find all fit the core connected-components model.
For many points, discuss how to avoid checking every pair by narrowing neighbor candidates spatially; in this round, the interviewer still preferred the brute-force implementation path.
Clarify squared-distance comparison to avoid unnecessary square roots.

Preparation: Implement connected components once with DFS/BFS and once with Union-Find.
Practice stating the O(n^2) brute-force baseline clearly before proposing spatial indexing.
Dry-run a case where three points form one cluster only through transitive links.

MEDIUM | PracHub | Technical Screen | 43 of 165

★ TOP 75: rank 69 in the Medium and Hard priority list

★ Solve Rooms and Top-K Streams

POSTED 2026-06-05 | 127 DAYS AGO | LAST 6 MONTHS

STUDY: TYPE | ALL TIME 58 | 30 DAYS 0 | PRIORITY 39/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #253 Meeting Rooms II, LeetCode #703 Kth Largest Element in a Stream

LeetCode match: LC 253 Meeting Rooms II + LC 703 Kth Largest Element in a Stream (inferred from overview)

Posted on PracHub: 2026-06-05 (updated 2026-06-14)

Original:
https://prachub.com/coding-questions/solve-rooms-and-top-k-streams

QUESTION

Overview: This question evaluates algorithmic problem-solving skills across interval scheduling/resource allocation and streaming top-k maintenance, testing competency in data structures for ordered queries, tie-breaking logic, stateful stream processing, and analysis of time and space trade-offs.

APPROACH

Rooms: min-heap of end times. Stream: size-k min-heap, push and pop when over k.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two parts. Rooms: is a meeting that starts exactly when another ends a conflict (the scraped solution treats it as no conflict)? Stream: top-K means the K largest values or K most frequent, and what ties do. The scraped solution covers only the rooms part.

BRUTE FORCE TO SAY OUT LOUD

Rooms: assign meetings to rooms and try all orders. Stream: store everything and sort on each query.

OPTIMAL IDEA

Rooms: sort starts and ends separately and sweep with two pointers: if the next start is at least the earliest end, reuse that room, otherwise open a new one; or keep a min-heap of room end times. O(n log n). Stream of the K largest (LeetCode 703): a min-heap of size K, push each value and pop when the size exceeds K, so the root is the K-th largest. O(log K) per value.

DRY-RUN THESE CASES

Rooms: [[0,30],[5,10],[15,20]] gives 2, an empty list gives 0, back-to-back meetings. Stream: fewer than K values so far, duplicates, K = 1.

LIKELY FOLLOW-UPS

INTERVIEW-DAY PLAN

Return the room assignment, or a sliding window of the last N values for the stream.

PITFALLS

Sorting starts and ends together by start. Returning from the heap before it holds K items.

HOW TO THINK ABOUT IT

Rooms: the number of rooms needed is the largest number of meetings happening at the same time, so sort the starts and the ends separately and sweep: a start that comes before the earliest end needs a new room. Stream: only the K largest values can matter, so keep exactly those in a min-heap; the root is the K-th largest.

Basis: Two tasks: LeetCode 253 (minimum meeting rooms; back-to-back meetings may share a room) and LeetCode 703 (Kth Largest Element in a Stream).

BRUTE FORCE · Rooms: count the overlap at every time unit

BRUTE FORCE · PSEUDO-CODE

```
def rooms(meetings):
    lo = min(s for s, e in meetings)
    hi = max(e for s, e in meetings)
    best = 0
    for t in range(lo, hi):
        busy = 0
        for s, e in meetings:
            if s <= t < e:
                busy += 1
        best = max(best, busy)
    return best
```

TIME	SPACE
O(range * n)	O(1)

WHY IT IS SLOW

Depends on the length of the time range, not only on n: O(range * n). Sorted starts and ends with two pointers (or a heap of end times) are O(n log n).

BRUTE FORCE · Stream: sort everything on every query

BRUTE FORCE · PSEUDO-CODE

```
values = []
def add(x):
    values.append(x)
    values.sort(reverse=True)
    return values[K - 1]
```

TIME	SPACE
O(n log n) per add	O(n)

WHY IT IS SLOW

Every add re-sorts the whole history, O(n log n). A min-heap of size K keeps the K-th largest at its root in O(log K) per add.

OPTIMAL SOLUTION · Rooms: sorted starts and ends with two pointers

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Stream: min-heap of size K

TIME	SPACE
O(log k) per add	O(k)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Rooms: return which room each meeting uses.

Sort by start and keep a min-heap of (end time, room). If the earliest-ending room is free at the next start, reuse it, otherwise open a new room. The heap size never exceeds the answer.

FOLLOW-UP 2 Stream: K changes over time, or you need the median.

A fixed-size heap cannot answer a different K. Use a sorted structure with order statistics (balanced tree or Fenwick tree over values), or two heaps for the median. **Cost:** a balanced tree or Fenwick tree gives O(log n) per insert and per k-th query; two heaps give O(log n) per insert and O(1) per median.

FOLLOW-UP 3 Rooms: meetings on several floors with capacities.

Group meetings by required capacity, schedule each group separately with the sweep, and assign rooms from the smallest sufficient capacity (best fit) when capacities differ.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


# BASE QUESTION (optimal): Rooms: sorted starts and ends
# with two pointers
def min_rooms(intervals):
    # two sorted lists: every start with no room free
    # needs
    # a new room, otherwise it reuses one that just ended
    starts = sorted(s for s, _ in intervals)
    ends = sorted(e for _, e in intervals)
    rooms = j = 0
    for s in starts:
        if s >= ends[j]:
            # the earliest-ending meeting is over: reuse
            # it
```

```
            j += 1
        else:
            rooms += 1
    return rooms


# FOLLOW-UP 1: Rooms: return which room each meeting uses.
def assign_rooms(intervals):
    # which room does each meeting use? a heap of (end,
    # room)
    order = sorted(range(len(intervals)),
                   key=lambda i: intervals[i])
    heap, rooms, used = [], [0] * len(intervals), 0
    for i in order:
        start, end = intervals[i]
        if heap and heap[0][0] <= start:
            _, room = heapq.heappop(heap)
        else:
            room, used = used, used + 1
        rooms[i] = room
        heapq.heappush(heap, (end, room))
    return rooms


# PART 2: top K values of a stream
class TopKStream:
    """The k largest values seen so far (fixed k)."""

    def __init__(self, k):
```

```
        self.k, self.heap = k, []

    def add(self, x):
        # a min-heap of size k: the root is the k-th
        # largest
        if len(self.heap) < self.k:
            heapq.heappush(self.heap, x)
        elif x > self.heap[0]:
            heapq.heapreplace(self.heap, x)

    def top(self):
        return sorted(self.heap, reverse=True)


# VARIANT: median of the stream
class MedianStream:
    """Follow-up: the median instead of a fixed top-k."""

    def __init__(self):
        # low is a max-heap (negated), high is a min-heap
        self.low, self.high = [], []

    def add(self, x):
        heapq.heappush(self.low, -x)
        top = -heapq.heappop(self.low)
        heapq.heappush(self.high, top)
        if len(self.high) > len(self.low):
            back = heapq.heappop(self.high)
            heapq.heappush(self.low, -back)

    def median(self):
        if len(self.low) > len(self.high):
            return float(-self.low[0])
        return (-self.low[0] + self.high[0]) / 2


if __name__ == "__main__":
    meetings = [(0, 30), (5, 10), (15, 20)]
    assert min_rooms(meetings) == 2
    # a meeting may start the moment another ends
    assert min_rooms([(1, 3), (3, 5)]) == 1
    assert min_rooms([]) == 0
    rooms = assign_rooms(meetings)
```

```
    assert rooms[0] != rooms[1] and rooms[1] == rooms[2]
    t = TopKStream(3)
```

```
    for x in [5, 1, 9, 7, 3, 8]:
        t.add(x)
    assert t.top() == [9, 8, 7]
    m = MedianStream()
    for x in [5, 2, 8, 1]:
        m.add(x)
    assert m.median() == 3.5
```

FUNCTION AND TEST CASES

Signature

```
def solution(intervals: list[list[int]]) -> int:
```

Sample call

```
solution([[0, 30], [5, 10], [15, 20]])
```

Test cases

Input	Expected
([[0, 30], [5, 10], [15, 20]],)	2
([],)	0

MEDIUM | PracHub | Technical Screen | 44 of 165

★ TOP 75: rank 16 in the Medium and Hard priority list

★ Find Containing Range

POSTED 2026-06-04 | 128 DAYS AGO | LAST 6 MONTHS

STUDY: TYPE | **ALL TIME 65.2** | **30 DAYS 41.1** | **PRIORITY 11/224**

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #56 Merge Intervals

LeetCode match: No direct match; related LC 56 Merge Intervals + binary search (inferred from overview)

Posted on PracHub: 2026-06-04 (updated 2026-06-06)

Original: https://prachub.com/coding-questions/find-containing-range

QUESTION

Overview: This question evaluates the ability to design appropriate data structures and apply algorithmic reasoning for efficient interval containment queries, emphasizing preprocessing, correctness, and time-space trade-offs.

APPROACH

Sort/merge ranges once, then answer each query with binary search on starts and check the end. O(n log n) preprocessing, O(log n) per query.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the given ranges can overlap, what to return when a point lies in several ranges (the original range, the merged range, or all of them), and what to return when none contains it.

BRUTE FORCE TO SAY OUT LOUD

For each query scan all ranges. O(n) per query.

OPTIMAL IDEA

Sort the ranges by start and merge overlaps once, O(n log n). For each query binary search for the last merged range whose start is at most the point, then check that the point is at most its end. O(log n) per query. If the original (unmerged) range is required and ranges may overlap, use an interval tree or keep the maximum end seen in a prefix array.

DRY-RUN THESE CASES

A point before all ranges, after all ranges, in a gap, exactly on an endpoint, inside two overlapping ranges.

LIKELY FOLLOW-UPS

Insert and delete ranges (a balanced tree), or many point queries at once (sort and sweep).

PITFALLS

Binary searching without merging when ranges overlap. Mishandling the endpoint rule.

HOW TO THINK ABOUT IT

Merge the ranges once so they are disjoint and sorted; then 'which range contains x' is 'the last range whose start is at most x, and does its end reach x'. That is one binary search per query. Be clear whether the answer is the original range or the merged one, since they differ when ranges overlap.

Basis: Written (compare LeetCode 56 and a binary search for the range). Assumed rule (confirm it): given possibly overlapping ranges, answer queries 'which merged range contains x?', or None.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def find_containing(ranges, x):
    for start, end in ranges:
        if start <= x <= end:
            return (start, end)
    return None
```

TIME	SPACE
O(n) per query	O(n)

WHY IT IS SLOW

BRUTE FORCE

Every query walks all n ranges. Merging once (O(n log n)) and binary searching the sorted starts makes each query O(log n).

OPTIMAL SOLUTION · Merge once, then binary search the starts

TIME	SPACE
O(n log n) to build, O(log n) per query	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return every original range that contains x, not the merged one.

Sort by start and consider only ranges starting at or before x (one bisect); among those, keep the ones whose end is at least x. With many overlaps use an interval tree for O(log n + k) per query.

FOLLOW-UP 2 Ranges are inserted and deleted over time.

Keep the disjoint ranges in a sorted container (balanced tree); an insert merges neighbours, and a query is the same predecessor search. O(log n) per operation.

FOLLOW-UP 3 Queries are given in bulk.

Sort the queries and sweep once over the merged ranges with two pointers: O((n + q) log) overall instead of a binary search per query.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left, bisect_right


# BASE QUESTION (optimal): Merge once, then binary search
# the starts
# FOLLOW-UP 1: Return every original range that contains
# x, not the merged one.
class RangeIndex:
    """Merged, sorted, disjoint closed ranges."""

    def __init__(self, ranges=()):
        self.starts, self.ends = [], []
        self.original = sorted(ranges)
        for s, e in self.original:
            self.insert(s, e)

    # FOLLOW-UP 2: ranges can be inserted over time
    def insert(self, s, e):
        # first range ending at or after s ...
        i = bisect_left(self.ends, s)
        # ... up to the last range starting at or before e
        j = bisect_right(self.starts, e)
        if i < j:
            s = min(s, self.starts[i])
            e = max(e, self.ends[j - 1])
```

```
        # replace everything the new range touches
        self.starts[i:j] = [s]
        self.ends[i:j] = [e]

    def find(self, x):
        # the merged range containing x, or None
        i = bisect_right(self.starts, x) - 1
        if i >= 0 and self.ends[i] >= x:
            return self.starts[i], self.ends[i]
        return None

    # FOLLOW-UP 1: every ORIGINAL range containing x
    def find_original(self, x):
        # every ORIGINAL range that contains x
        k = bisect_right([s for s, _ in self.original], x)
        return [r for r in self.original[:k] if r[1] >= x]

    # FOLLOW-UP 3: queries given in bulk
    def find_many(self, queries):
        # bulk: sort the queries and sweep once
        order = sorted(range(len(queries)),
                       key=lambda i: queries[i])
        out, j = [None] * len(queries), 0
        for i in order:
            x = queries[i]
            # skip ranges that end before x
            while j < len(self.ends) and self.ends[j] < x:
                j += 1
            inside = j < len(self.starts)
            if inside and self.starts[j] <= x:
                out[i] = (self.starts[j], self.ends[j])
        return out


if __name__ == "__main__":
    idx = RangeIndex([(1, 3), (2, 6), (8, 10), (15, 18)])
    assert idx.find(4) == (1, 6)
    assert idx.find(7) is None
    assert idx.find(8) == (8, 10)
    assert idx.find(0) is None and idx.find(99) is None
    # the original ranges that cover 2
    assert idx.find_original(2) == [(1, 3), (2, 6)]
    # touching ranges merge: (6, 8) joins the first two
    # blocks
    idx.insert(6, 8)
    assert idx.find(7) == (1, 10)
    assert idx.find(12) is None
    qs = [4, 20, 16, 9]
    assert idx.find_many(qs) == [idx.find(q) for q in qs]
```

FUNCTION AND TEST CASES

Signature

```
def solution(ranges: list[list[int]], queries: list[int])
-> list[list[int]]:
```

Sample call

```
solution([[1, 3], [50, 100]], [2, 50, 10])
```

Test cases

Input	Expected
`([[1, 3], [50, 100]], [2, 50, 10])`	`[[1, 3], [50, 100], None]`
`([[5, 8], [-10, -5], [0, 0]], [-7, 0, 8, 9, -11])`	`[[-10, -5], [0, 0], [5, 8], None, None]`

MEDIUM | PracHub | Technical Screen | 45 of 165

Find a Horizontal Cut That Bisects Rectangle Area

POSTED 2026-06-04 | 128 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 8.1 | 30 DAYS 0 | PRIORITY 168/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #850 Rectangle Area II

LeetCode match: No direct match; related LC 850 Rectangle Area II (inferred from overview)

Posted on PracHub: 2026-06-04 (updated 2026-08-07)

Original: https://prachub.com/coding-questions/find-a-horizontal-cut-that-bisects-rectangle-area

QUESTION

Overview: Solve a computational-geometry problem that asks for the horizontal line dividing the combined area of many disjoint rectangles in half. The exercise emphasizes numerical precision, large coordinate ranges, performance at 200,000 rectangles, and careful treatment of partially intersected shapes.

APPROACH

Compute total area and the covered width per y-slab via a sweep; walk slabs accumulating area until half, then interpolate inside the slab. Use exact arithmetic for precision.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the rectangles are disjoint (the overview says so), the coordinate range, whether the answer must be exact (use fractions) and which y to return if a gap makes many cuts valid (the lowest).

BRUTE FORCE TO SAY OUT LOUD

Binary search on y, summing the rectangle area below y each time. O(n log precision), but floating point error is a risk.

OPTIMAL IDEA

INTERVIEW-DAY PLAN

Because the rectangles are disjoint, the area below y is a piecewise linear function whose slope is the sum of the widths of the rectangles spanning y. Create events at each rectangle's bottom (slope increases by its width) and top (slope decreases), sort by y, and walk the slabs accumulating area. When the next slab would pass half of the total, solve inside it: y = y0 + (half - accumulated) / slope, using integer or Fraction arithmetic. O(n log n) for 200,000 rectangles.

DRY-RUN THESE CASES

One rectangle (the middle), two rectangles separated by a gap (slope zero there), the half exactly at a rectangle boundary, huge coordinates.

LIKELY FOLLOW-UPS

Overlapping rectangles (LeetCode 850, needs a segment tree over x), or a vertical cut.

PITFALLS

Floating point error when comparing areas. Not handling slabs with slope zero.

HOW TO THINK ABOUT IT

Area below a line y = c is a piecewise linear function of c, and between two consecutive rectangle edges its slope is just the total width of rectangles crossing that height (they are disjoint, so widths add). Walk the slabs between events, accumulate area, and when half the area falls inside a slab solve a linear equation. Use exact fractions so the answer is exact.

Basis: Written; a sweep over y events (compare LeetCode 850, Rectangle Area II, which is the harder overlapping version). Assumed rule: axis-aligned rectangles (x1, y1, x2, y2) that do not overlap; return the lowest y with half the total area below it.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(rects):
    total = sum(area(r) for r in rects)
    lo = lowest_edge(rects)
    hi = highest_edge(rects)
    for _ in range(100):
        mid = (lo + hi) / 2
        if area_below(rects, mid) >= total / 2:
            hi = mid
        else:
            lo = mid
    return hi
```

TIME	SPACE
O(R * iterations)	O(1)

WHY IT IS SLOW

Each step sums over all rectangles and the answer is only as precise as floating point allows. A sweep over sorted edges with exact fractions finds the slab and the cut directly in O(R log R).

OPTIMAL SOLUTION · Sweep the y events and interpolate inside one slab

TIME	SPACE
O(R log R)	O(R)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Rectangles may overlap (LeetCode 850).

The slope is then the union width of the rectangles crossing a height, not the sum. Maintain it with a segment tree over compressed x coordinates (cover counts), O(R log R) overall.

FOLLOW-UP 2 Coordinates up to 10^9 and 200,000 rectangles.

Use integers or Fractions (areas reach 10^18, which fits in Python ints but not in 32-bit). The sweep is O(R log R); never use floats for the comparisons that decide the slab.

FOLLOW-UP 3 A vertical cut instead, or a cut at a given ratio.

Swap the axes for a vertical cut. For a ratio p, replace half by p * total in the slab test; the interpolation formula is unchanged.

FOLLOW-UP 4 A cut that leaves a given fraction of the area below it, not exactly half.

Replace 'half of the total' by p * total in the slab test; the interpolation formula inside the slab is the same. The code returns an exact Fraction and is checked by computing the area below the returned cut.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict
from fractions import Fraction


def total_area(rects):
    # rects are disjoint (x1, y1, x2, y2)
    return sum((x2 - x1) * (y2 - y1)
               for x1, y1, x2, y2 in rects)


def area_below(rects, y):
    # exact area under the line at height y (used to
    # check)
    total = Fraction(0)
    for x1, y1, x2, y2 in rects:
        top = min(Fraction(y), y2)
        if top > y1:
            total += (x2 - x1) * (top - y1)
    return total


# BASE QUESTION (optimal): Sweep the y events and
# interpolate inside one slab
# FOLLOW-UP 4: A cut that leaves a given fraction of the
```

```
# area below it, not exactly ...
def cut_height(rects, share=Fraction(1, 2)):
    # FOLLOW-UP 4: share= leaves any fraction below the
    # cut
    # the height with `share` of the total area below it
    # (1/2 = bisect). Exact Fractions, never floats.
    want = share * total_area(rects)
    # width gained when the sweep passes each height
    events = defaultdict(int)
    for x1, y1, x2, y2 in rects:
        events[y1] += x2 - x1
        events[y2] -= x2 - x1
    ys = sorted(events)
    width, so_far = 0, Fraction(0)
    for y0, y1 in zip(ys, ys[1:]):
        # inside this slab the covered width is constant
        width += events[y0]
        gain = width * (y1 - y0)
        if width and so_far + gain >= want:
            # the cut is inside this slab: interpolate
            return y0 + (want - so_far) / width
```

```
        so_far += gain
    return Fraction(ys[-1])


if __name__ == "__main__":
    stacked = [(0, 0, 2, 1), (0, 1, 2, 2)]
    assert cut_height(stacked) == 1
    # one tall rectangle: halfway up
    assert cut_height([(0, 0, 1, 4)]) == 2
    # a gap between rectangles: the cut sits at the first
    # top
    gap = [(0, 0, 1, 1), (0, 5, 1, 6)]
    assert cut_height(gap) == 1
    # the cut can fall inside a slab with a fractional
    # height
    odd = [(0, 0, 3, 1), (0, 1, 1, 2)]
    y = cut_height(odd)
    assert area_below(odd, y) * 2 == total_area(odd)
    # a different share: 1/4 of the area below
    q = cut_height(stacked, Fraction(1, 4))
    below = area_below(stacked, q)
    assert below * 4 == total_area(stacked)
    # large coordinates stay exact
    big = [(0, 0, 10 ** 9, 10 ** 9)]
    assert cut_height(big) == Fraction(10 ** 9, 2)
```

FUNCTION AND TEST CASES

Signature

```
def horizontal_bisector(rectangles: list[list[float]]) ->
float:
```

Sample call

```
horizontal_bisector([[0, 0, 4, 2]])
```

Test cases

Input	Expected
`([[0, 0, 4, 2]],)`	`1.0`
`([[0, 0, 2, 4], [10, 1, 2, 2]],)`	`2.0`

ALSO REPORTED · 1 more

Find where to cut cake into equal areas | PracHub | Technical Screen

https://prachub.com/coding-questions/find-where-to-cut-cake-into-equal-areas

---

MEDIUM | IN APP LC 621 | PracHub | Technical Screen | 46 of 165

Rearrange Tasks With Cooldown

POSTED 2026-06-03 | 129 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 40.3 | 30 DAYS 0 | PRIORITY 91/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #621 Task Scheduler

LeetCode match: LC 621 Task Scheduler (inferred from overview)

Posted on PracHub: 2026-06-03 (updated 2026-06-06)

Original:
https://prachub.com/coding-questions/rearrange-tasks-with-cooldown

QUESTION

Overview: This question evaluates task-scheduling and constraint-handling skills, testing algorithmic reasoning about arranging repeated jobs with cooldown constraints along with analysis of schedule optimality and algorithmic complexity.

APPROACH

Greedy with max-heap + cooldown queue, or the formula (maxFreq-1)*(n+1)+countOfMax vs len(tasks). Rearranged output: always take the available task with highest remaining count.

HOW TO THINK ABOUT IT

The most frequent task is the bottleneck. Lay it out with gaps of n between its copies; every other task can fill gaps. Total length is the larger of 'that skeleton' and 'just the number of tasks' (when there are so many tasks the gaps are all filled and no idle time is needed). The skeleton has (maxcount - 1) full blocks of size n + 1 plus one last block holding every task tied for the maximum.

Basis: LeetCode 621, Task Scheduler (minimum time), with LeetCode 358, Rearrange String k Distance Apart as the construction follow-up. Assumed rule: the same task needs n idle-or-other slots between runs.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def brute(tasks, n):
    left = Counter(tasks)
    free_at = {}  # task -> time it is ready
    t = 0
    while any(left.values()):
        ready = [x for x in left if left[x]
                 and free_at.get(x, 0) <= t]
        if ready:
            task = max(ready, key=left.get)
            left[task] -= 1
            free_at[task] = t + n + 1
        t += 1  # idle if none ready
    return t
```

TIME	SPACE
O(T log k) where T is the answer	**O(k)**

WHY IT IS SLOW

It simulates every slot, including long idle stretches, O(T log k). The answer follows from the most frequent task: max(len(tasks), (maxCount - 1) * (n + 1) + number of tasks with that count).

OPTIMAL SOLUTION · Closed form from the most frequent task

TIME	SPACE
O(len(tasks))	**O(1)** for a fixed alphabet

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Print an actual schedule, not just the time.

Use the heap-with-cooldown-queue construction: run the available task with the most copies left, park it for n slots, and emit an idle marker when nothing is available. Or rearrange a string so equal letters are at least k apart.

FOLLOW-UP 2 Different cooldowns per task.

The closed form no longer applies. Simulate with a heap, storing for each task the time it becomes available; pick the ready task with the most remaining copies, and jump the clock to the earliest availability when nothing is ready.

FOLLOW-UP 3 Tasks have priorities or deadlines.

Then it is a scheduling problem; say what you optimise (lateness, completion time) and use a heap ordered by deadline for the ready tasks.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import Counter, deque


# BASE QUESTION (optimal): Closed form from the most
# frequent task
def least_interval(tasks, n):
    # closed form: the most frequent task sets the frame
    counts = Counter(tasks).values()
    most = max(counts, default=0)
    # how many tasks are tied for the most
    tied = sum(1 for c in counts if c == most)
    if not tasks:
        return 0
    # (most - 1) full frames of n + 1 slots, plus the last
    # row
    return max(len(tasks), (most - 1) * (n + 1) + tied)


# FOLLOW-UP 1: Print an actual schedule, not just the
# time.
def schedule(tasks, n):
    # an actual schedule, with "idle" where nothing may
    # run
    heap = [(-c, t) for t, c in Counter(tasks).items()]
    heapq.heapify(heap)
    # tasks cooling down: (time ready, -left, task)
    cooling, out, now = deque(), [], 0
    while heap or cooling:
        # bring back tasks whose cooldown is over
        while cooling and cooling[0][0] <= now:
            _, left, task = cooling.popleft()
            heapq.heappush(heap, (left, task))
        if heap:
            # run the task with the most copies left
            left, task = heapq.heappop(heap)
            out.append(task)
            if left + 1 < 0:
                ready = now + n + 1
                cooling.append((ready, left + 1, task))
        else:
            out.append("idle")
        now += 1
    return out
```

```
def valid(plan, n):
    # equal tasks must be more than n slots apart
    last = {}
    for i, task in enumerate(plan):
        if task == "idle":
            continue
        if task in last and i - last[task] <= n:
            return False
        last[task] = i
    return True


if __name__ == "__main__":
    tasks = list("AAABBB")
    assert least_interval(tasks, 2) == 8
    assert least_interval(tasks, 0) == 6
    assert least_interval([], 3) == 0
    # many different tasks: no idle time needed
    assert least_interval(list("ABCDEFG"), 2) == 7
    plan = schedule(tasks, 2)
    assert len(plan) == 8 and valid(plan, 2)
    assert plan.count("idle") == 2
    for t, n in ((list("AAAABBC"), 3), (list("AB"), 5)):
        plan = schedule(t, n)
        assert valid(plan, n)
        assert len(plan) == least_interval(t, n)
```

FUNCTION AND TEST CASES

Signature

```
def solution(tasks: list[str], cooldown: int) -> str:
```

Sample call

```
solution(['A', 'A', 'A', 'B', 'B', 'C'], 2)
```

Test cases

Input	Expected
`(['A', 'A', 'A', 'B', 'B', 'C'], 2)`	`'ABCAB_A'`
`(['A', 'A', 'A', 'B'], 2)`	`'AB_A__A'`

ALSO REPORTED · 1 more

Design a task scheduler in Python. | Exponent
https://www.aced.io/questions/3504/design-task-scheduler-python

---

POSTED: OLDER THAN 6 MONTHS (70)

Hard (18)

HARD | PracHub | Technical Screen | 47 of 165

Find Dictionary Matches for a Jammed String

POSTED 2026-04-09 | 184 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 25.5 | 30 DAYS 0 | PRIORITY 133/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 809 Expressive Words (inferred from overview)

Posted on PracHub: 2026-04-09 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/find-dictionary-matches-for-a-jammed-string

QUESTION

Overview: This question evaluates string-processing and pattern-matching skills, specifically run-length grouping of consecutive characters and efficient dictionary lookup, within the Coding & Algorithms domain.

APPROACH

Run-length encode the query and every dictionary word; a word matches if run characters align and each run length is compatible. Pre-group dictionary by compressed signature in a hash map for fast lookup.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what jammed means exactly: a letter repeated more than it should be, and whether the repeat count must be at least the word's count or at least some threshold. Confirm case, empty strings and whether a match requires the same letter order and same number of runs.

BRUTE FORCE TO SAY OUT LOUD

For each dictionary word, compare it with the query run by run. O(W * L) per query.

OPTIMAL IDEA

Compress each word into runs of (letter, count). Use the letter sequence (without counts) as a hash key so only words with the same run letters are candidates, then compare the counts under the agreed rule. For repeated queries a trie over run letters keeps lookups proportional to the number of runs.

DRY-RUN THESE CASES

Query 'heeelllo' against 'hello' and 'helo'. A query with fewer runs than the word. A single-letter word. A word whose runs are longer than the query's.

LIKELY FOLLOW-UPS

Stretch only allowed for runs of three or more, return all matches in input order, handle a huge dictionary with a trie.

PITFALLS

Treating 'ee' to 'e' as a match without checking the rule. Comparing total length instead of per-run counts.

HOW TO THINK ABOUT IT

'Same letters, stretched' means compare run-length encodings, not characters. The letter order of the runs has to match exactly, so the sequence of distinct run letters is a hash key that cuts the dictionary down before any counts are compared.

Basis: LeetCode 809, Expressive Words. Assumed rule (confirm it): a query run may be longer than the word's run only when the query run has length at least 3; otherwise the lengths must be equal.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def matches(query, words):
    runs_q = runs(query)  # [(letter, count)]
    result = []
    for word in words:
        runs_w = runs(word)
        if compatible(runs_w, runs_q):
            result.append(word)
    return result
```

TIME	SPACE
O(W * L) per query	O(L)

WHY IT IS SLOW

BRUTE FORCE

Every query touches every word, O(W * L), even words whose letters cannot match. Grouping words by their run letters in a hash map checks only the right bucket.

OPTIMAL SOLUTION · Index the dictionary by its run letters

TIME	SPACE
O(L) per query plus the size of the matching bucket	**O(total dictionary length)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 A different stretch rule: any run may be longer, no minimum.

Only the comparison changes. The index (grouping by run letters) is the same, so make the minimum stretch a parameter, as the code does with min_stretch.

FOLLOW-UP 2 Millions of dictionary words and many queries.

Keep the group index in memory and put a trie over the run-letter strings if the keys share long prefixes. For counts compare only the first words in a bucket that survive a cheap check such as total length. **Cost:** O(L) per query to build the run key plus the size of the bucket scanned; building the index is O(total dictionary length) once.

FOLLOW-UP 3 The jammed string may also be missing letters.

That becomes an edit-distance style problem on run encodings, usually solved with DP over (query run, word run). Ask for the exact rule before coding it.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from itertools import groupby


def runs(word):
    # "heello" -> [("h", 1), ("e", 2), ("l", 2), ("o", 1)]
    return [(ch, len(list(g))) for ch, g in groupby(word)]


# BASE QUESTION (optimal): Index the dictionary by its run
# letters
# FOLLOW-UP 1: A different stretch rule: any run may be
# longer, no minimum.
class JammedIndex:
    """A query run may be longer than the word's run
    when it is at least min_stretch long."""

    def __init__(self, words):
        # words grouped by their run letters ("hello" ->
        # "helo")
        self.groups = {}
        for w in words:
            r = runs(w)
            letters = "".join(ch for ch, _ in r)
            self.groups.setdefault(letters, []).append(
                (w, [n for _, n in r]))

    # FOLLOW-UP 1: min_stretch=1: any run may be longer
    def matches(self, query, min_stretch=3):
        r = runs(query)
        letters = "".join(ch for ch, _ in r)
        counts = [n for _, n in r]
        found = []
        # only words with the same run letters can match
        group = self.groups.get(letters, [])
        for word, word_counts in group:
            if all(self.fits(q, w, min_stretch)
                   for q, w in zip(counts, word_counts)):
                found.append(word)
        return sorted(found)

    @staticmethod
    def fits(q, w, min_stretch):
        # the same length, or a stretch of at least
        # min_stretch
        return q == w or (q > w and q >= min_stretch)


if __name__ == "__main__":
    index = JammedIndex(["hello", "help", "hi", "hip"])
    # e stretched to 4 and o stretched to 3
    assert index.matches("heeeelloooo") == ["hello"]
    assert index.matches("hello") == ["hello"]
    # a stretch of only 2 is not enough
    assert index.matches("heello") == []
    assert index.matches("hiiii") == ["hi"]
    assert index.matches("zzz") == []
    # a smaller minimum accepts the short stretch
    short = index.matches("heello", min_stretch=2)
    assert short == ["hello"]
    # no minimum: any longer run is fine
    assert index.matches("hiip", min_stretch=1) == ["hip"]
    want = [("a", 2), ("b", 1), ("c", 3)]
    assert runs("aabccc") == want
```

FUNCTION AND TEST CASES

Signature

```
def solution(dictionary_words: list[str], jammed_string: s
tr) -> list[str]:
```

Sample call

```
solution(['help', 'hello', 'shell', 'hellp'], 'hellp')
```

Test cases

Input	Expected
`(['help', 'hello', 'shell', 'hellp'], 'hellp')`	`['help', 'hellp']`
`(['hello', 'halo', 'heeello'], 'hheeellllo')`	`['hello', 'heeello']`

HARD | PracHub | Technical Screen | 48 of 165

★ TOP 75: rank 4 in the Medium and Hard priority list

★ Check Digits and Combine Ranges

POSTED 2026-03-29 | 195 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 73.6 | 30 DAYS 63.4 | PRIORITY 2/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #9 Palindrome Number, LeetCode #56 Merge Intervals, LeetCode #228 Summary Ranges

LeetCode match: LC 9 Palindrome Number + LC 56 Merge Intervals / LC 228 Summary Ranges

Posted on PracHub: 2026-03-29 (updated 2026-05-19)

Original:
https://prachub.com/coding-questions/check-digits-and-combine-ranges

QUESTION

You are asked to solve two independent coding tasks.

Task 1:

Check Whether an Integer Reads the Same Backward Given an integer `x`, return `true` if its decimal representation reads the same from left to right and from right to left; otherwise return `false`. Requirements and edge cases:

- Negative integers should return `false` because of the leading minus sign.
- You may assume `x` fits in a signed 32-bit integer.
- Try to solve it without converting the integer to a string. Example:

```
Input: x = 121
Output: true
```

```
Input: x = -121
Output: false
```

```
Input: x = 10
Output: false
```

Task 2:

Combine Overlapping Ranges Given an array of intervals `intervals`, where each interval is represented as `[start, end]`, combine all overlapping intervals and return an array of non-overlapping intervals that covers exactly the same ranges. Requirements and edge cases:

- Intervals may be provided in any order.
- Two intervals overlap if they share at least one point. For example, `[1, 4]` and `[4, 5]` should be combined into `[1, 5]`.
- Return the intervals in increasing order by start value. Example:

QUESTION

```
Input: intervals = [[1,3],[2,6],[8,10],[15,18]]
Output: [[1,6],[8,10],[15,18]]
```

```
Input: intervals = [[1,4],[4,5]]
Output: [[1,5]]
```

Part 1: Check Whether an Integer Reads the Same BackwardGiven an integer x, return True if its decimal representation reads the same from left to right and from right to left. Otherwise, return False. Negative integers are not palindromes because of the leading minus sign. Try to solve the problem using arithmetic operations instead of converting the integer to a string.
Constraints-2^31 <= x <= 2^31 - 1Negative integers must return FalseAn arithmetic-based solution is preferred over string conversion

EXAMPLES

```
Input: 121
Expected Output: True
```

Explanation: 121 reads the same forward and backward.

```
Input: -121
Expected Output: False
```

Explanation: Negative numbers are not palindromes.

Hints

A negative number can never be a palindrome because the minus sign only appears on the left.Try reversing only the second half of the digits instead of the whole number.

Part 2: Combine Overlapping RangesGiven a list of intervals, where each interval is represented as [start, end], merge all overlapping intervals and return a new list of non-overlapping intervals that covers exactly the same ranges. Intervals may appear in any order. Two intervals overlap if they share at least one point, so [1, 4] and [4, 5] should be merged into [1, 5]. Return the result sorted by starting value.
Constraints
0 <= len(intervals) <= 10^4-10^9 <= start <= end <= 10^9Intervals may be unsorted
Examples
Input: [[1, 3], [2, 6], [8, 10], [15, 18]]
Expected Output: [[1, 6], [8, 10], [15, 18]]
Explanation: The first two intervals overlap and merge into [1, 6].
Input: [[1, 4], [4, 5]]
Expected Output: [[1, 5]]
Explanation: The intervals share the point 4, so they overlap.
Hints

Sort the intervals by their start value before trying to merge them.Keep track of the last interval in the output. If the next interval overlaps, extend the end; otherwise, start a new interval.

APPROACH

Task 1: reverse half the digits and compare (no string, handle negatives and trailing zeros). Task 2: sort ranges and merge or combine consecutive ones in one pass.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two independent tasks. For the palindrome: negatives are false, no string conversion, 32-bit input. For the ranges: ask whether touching ranges such as [1, 4] and [4, 5] merge (the statement says they do) and whether adjacent integer ranges like [1, 2] and [3, 4] should also merge.

BRUTE FORCE TO SAY OUT LOUD

Palindrome: convert to a string and compare with its reverse. Ranges: compare every pair repeatedly until nothing merges, O(n^2).

OPTIMAL IDEA

Palindrome: return false for negatives and for any positive number ending in 0; then build a reversed number from the low digits while x > rev, and compare x with rev or rev // 10 (to skip the middle digit). Only half the digits are processed, so overflow cannot happen. Ranges: sort by start, then sweep, extending the last merged range when the next start is at most its end, else append. O(n log n).

DRY-RUN THESE CASES

121 true, -121 false, 10 false, 0 true, 1221, 12321. Ranges: [[1,3],[2,6],[8,10],[15,18]] gives [[1,6],[8,10],[15,18]]; [[1,4],[4,5]] gives [[1,5]]; unsorted input; one range; a range fully inside another.

LIKELY FOLLOW-UPS

Palindrome in another base, or palindrome linked list. Ranges: insert a new interval into a sorted list (LeetCode 57), summary ranges of sorted integers (LeetCode 228).

PITFALLS

Reversing the whole number and overflowing. Forgetting to sort before merging. Using strict less-than when touching ranges must merge.

HOW TO THINK ABOUT IT

Task 1: a number is a palindrome if its second half reversed equals its first half, so reverse only half the digits (stop when the reversed part catches up) and avoid overflow. Negatives and numbers ending in 0 are never palindromes. Task 2: after sorting by start, an overlap can only be with the last merged range, so one pass with a 'current' range is enough.

Basis: Two independent tasks: LeetCode 9 (Palindrome Number, no string conversion) and LeetCode 56 (Merge Intervals; ranges sharing a point merge).

BRUTE FORCE · Task 1: convert to a string and compare with its reverse

BRUTE FORCE · PSEUDO-CODE

```
def is_palindrome(x):
    s = str(x)
    return x >= 0 and s == s[::-1]
```

TIME	SPACE
O(d)	O(d)

WHY IT IS SLOW

O(d) time but it builds strings, which the question forbids. Reversing only the second half of the digits arithmetically (x % 10, x // 10) uses O(1) space.

BRUTE FORCE · Task 2: merge any two overlapping ranges until none overlap

BRUTE FORCE · PSEUDO-CODE

```
def combine(ranges):
    ranges = list(ranges)
    merged = True
    while merged:
        merged = False
        for a, b in combinations(ranges, 2):
            if overlaps(a, b):
                ranges.remove(a)
                ranges.remove(b)
                ranges.append(union(a, b))
                merged = True
                break
    return sorted(ranges)
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Each pass compares all pairs, O(n^2), and several passes may be needed. Sorting by start and sweeping once is O(n log n).

OPTIMAL SOLUTION · Task 1: reverse only the second half arithmetically

TIME	SPACE
O(d)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Task 2: sort by start, then one sweep

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Adjacent integer ranges ([1, 2] and [3, 4]) should merge too.

Change the overlap test to s <= out[-1][1] + 1 (integers only). For real-valued ranges that is wrong, so say which you assume.

FOLLOW-UP 2 Summarise a sorted list of integers as ranges (LeetCode 228).

One pass keeping the current range and extending it while the next number is exactly one more; the same 'extend or start new' structure as the merge.

FOLLOW-UP 3 Palindrome in another base, or as a linked list.

Another base replaces 10 by the base in % and //. For a linked list find the middle with slow and fast pointers, reverse the second half in place and compare.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): reverse only the second half
# arithmetically
def is_palindrome(x, base=10):
    # no string: build the reversed second half
    if x < 0 or (x % base == 0 and x != 0):
        return False
    rev = 0
    # stop when the reversed half catches up with the rest
    while x > rev:
        rev = rev * base + x % base
        x //= base
    # an odd number of digits has a middle digit to drop
    return x == rev or x == rev // base


# TASK 2: combine ranges
def merge_ranges(intervals, adjacent=False):
    out = []
    # sort by start so overlaps are neighbours
    for s, e in sorted(intervals):
        # sharing one point counts as overlap: [1,4] +
        # [4,5]
        gap = 1 if adjacent else 0
        if out and s <= out[-1][1] + gap:
            out[-1][1] = max(out[-1][1], e)
        else:
            out.append([s, e])
    return out


# FOLLOW-UP 2: Summarise a sorted list of integers as
# ranges (LeetCode 228).
def summarize_ranges(nums):
    # LeetCode 228: a sorted list of ints as ranges
    out = []
    for x in nums:
        if out and x == out[-1][1] + 1:
            # exactly one more: extend the current range
            out[-1][1] = x
        else:
            out.append([x, x])
    return out
```

```
if __name__ == "__main__":
```

```
    assert is_palindrome(121) and is_palindrome(0)
    assert not is_palindrome(-121)
    assert not is_palindrome(10)
    assert is_palindrome(1221) and not is_palindrome(123)
    # binary 101 is 5; binary 110 is 6
    assert is_palindrome(5, 2) and not is_palindrome(6, 2)
    ranges = [[1, 3], [2, 6], [8, 10], [15, 18]]
    merged = merge_ranges(ranges)
    assert merged == [[1, 6], [8, 10], [15, 18]]
    assert merge_ranges([[1, 4], [4, 5]]) == [[1, 5]]
    # any input order, and an empty list
    shuffled = merge_ranges([[8, 10], [1, 3]])
    assert shuffled == [[1, 3], [8, 10]]
    assert merge_ranges([]) == []
    # adjacent integer ranges merge only when asked
    touching = [[1, 2], [3, 4]]
    assert merge_ranges(touching) == touching
    assert merge_ranges(touching, True) == [[1, 4]]
    assert summarize_ranges([0, 1, 2, 4, 5, 7]) == [
        [0, 2], [4, 5], [7, 7]]
```

FUNCTION AND TEST CASES

Signature

```
def solution(x: int) -> bool:
SAMPLE INPUT
121
```

Test cases

Input	Expected
121	True
-121	False

HARD | IN APP LC 354 | PracHub | Technical Screen | 49 of 165

★ TOP 75: rank 14 in the Medium and Hard priority list

★ Find Maximum Envelope Nesting

POSTED 2026-03-18 | 206 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 52.8 | 30 DAYS 33 | PRIORITY 26/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #354 Russian Doll Envelopes

LeetCode match: LC 354 Russian Doll Envelopes

Posted on PracHub: 2026-03-18 (updated 2026-05-06)

Original: https://prachub.com/coding-questions/find-maximum-envelope-nesting

QUESTION

Overview: This question evaluates algorithmic problem-solving skills, particularly reasoning about multi-dimensional ordering, sequence optimization, and time-complexity analysis.

APPROACH

Sort by width asc and height desc on ties, then find the strictly increasing subsequence on heights with binary-search LIS (patience sorting). O(n log n).

HOW TO THINK ABOUT IT

Two dimensions are hard, one is easy. Sort by width so that width order is settled, then the question becomes a longest strictly increasing subsequence of heights. The trap is envelopes with equal width: they cannot nest, so sort equal widths by height descending, which prevents two of them from forming an increasing pair. The LIS is then done with patience sorting (binary search over tails).

Basis: LeetCode 354, Russian Doll Envelopes (strictly larger in both width and height).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
envelopes.sort()  # by width
best = [1] * len(envelopes)
for i in range(len(envelopes)):
    for j in range(i):
        w1, h1 = envelopes[j]
        w2, h2 = envelopes[i]
        if w1 < w2 and h1 < h2:
            best[i] = max(best[i], best[j] + 1)
answer = max(best)
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Every envelope compares with all earlier ones, O(n^2). Sorting by width ascending and height descending, then a longest increasing subsequence on heights with binary search, is O(n log n).

OPTIMAL SOLUTION · Sort by width ascending and height descending, then LIS by binary search

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the actual chain of envelopes.

Remember, for each element, the index of the tail it extended (parent pointers), and rebuild from the last tail of the longest length. The sorted order and binary search are unchanged.

FOLLOW-UP 2 Three dimensions (boxes).

Sorting plus LIS no longer reduces the problem; use an O(n^2) DP, or CDQ divide and conquer with a Fenwick tree for O(n log^2 n).

FOLLOW-UP 3 Non-strict nesting (equal sizes allowed).

Sort by width ascending and height ascending, and use bisect_right (longest non-decreasing subsequence) instead of bisect_left.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left, bisect_right


# BASE QUESTION (optimal): Sort by width ascending and
# height descending, then LIS by ...
def max_envelopes(envelopes):
    # sort by width, taller first on ties, then find the
    # longest
    # strictly increasing run of heights
    ordered = sorted(envelopes,
                     key=lambda e: (e[0], -e[1]))
    tails = []
    for _, h in ordered:
        i = bisect_left(tails, h)
        if i == len(tails):
            tails.append(h)
        else:
            tails[i] = h
    return len(tails)


# FOLLOW-UP 1: Return the actual chain of envelopes.
def envelope_chain(envelopes):
    # also return the chain: remember what each element
    # extended
    ordered = sorted(envelopes,
                     key=lambda e: (e[0], -e[1]))
    tails, tail_idx = [], []
    prev = [-1] * len(ordered)
    for i, (_, h) in enumerate(ordered):
        k = bisect_left(tails, h)
        if k == len(tails):
            tails.append(h)
            tail_idx.append(i)
        else:
            tails[k] = h
            tail_idx[k] = i
        # the element that ended a chain one shorter
        prev[i] = tail_idx[k - 1] if k else -1
    chain = []
    i = tail_idx[-1] if tail_idx else -1
    while i != -1:
        chain.append(ordered[i])
        i = prev[i]
```

```
    return chain[::-1]
```

```
# FOLLOW-UP 3: Non-strict nesting (equal sizes allowed).
def max_nested_non_strict(envelopes):
    # equal sizes may nest: sort both ways ascending and
    # use
    # bisect_right (a longest non-decreasing subsequence)
    tails = []
    for _, h in sorted(envelopes):
        i = bisect_right(tails, h)
        if i == len(tails):
            tails.append(h)
        else:
            tails[i] = h
    return len(tails)


# FOLLOW-UP 2: Three dimensions (boxes).
def max_boxes_3d(boxes):
    # three sizes: the reduction no longer works, use
    # O(n^2)
    ordered = sorted(boxes)
    best = [1] * len(ordered)
    for i in range(len(ordered)):
        for j in range(i):
            a, b = ordered[j], ordered[i]
            if all(x < y for x, y in zip(a, b)):
                best[i] = max(best[i], best[j] + 1)
    return max(best, default=0)


if __name__ == "__main__":
    envs = [[5, 4], [6, 4], [6, 7], [2, 3]]
    assert max_envelopes(envs) == 3
    chain = envelope_chain(envs)
    assert len(chain) == 3
    # every envelope fits strictly inside the next
    for a, b in zip(chain, chain[1:]):
        assert a[0] < b[0] and a[1] < b[1]
    assert envelope_chain([]) == []
    # equal sizes: only the non-strict version nests them
    twins = [[3, 3], [3, 3], [4, 4]]
    assert max_envelopes(twins) == 2
    assert max_nested_non_strict(twins) == 3
    boxes = [(1, 1, 1), (2, 2, 2), (3, 1, 4), (3, 3, 3)]
```

```
    assert max_boxes_3d(boxes) == 3
```

FUNCTION AND TEST CASES

Signature

```
def solution(envelopes: list[list[int]]) -> int:
SAMPLE INPUT
[[5, 4], [6, 4], [6, 7], [2, 3]]
```

Test cases

Input	Expected
`[[5, 4], [6, 4], [6, 7], [2, 3]]`	`3`
`[]`	`0`

ALSO REPORTED · 1 more

Russian Doll Envelopes | 1Point3Acres | phone-screen | Single report

https://www.1point3acres.com/interview/problems/company/google/russian-doll-envelopes

Sorting heights descending on width-ties prevents same-width envelopes from chaining — easy to miss.
LIS via bisect_left on a tails array is the standard O(n log n) implementation.

Preparation: Write LIS O(n log n) from memory in under 8 min.
Justify the descending-height-on-tie trick out loud.
Plain LIS and the mountain-LIS variant make good drill partners.

HARD | IN APP LC 1631, 778 | PracHub | Technical Screen | 50 of 165

Find minimum threshold enabling grid path

POSTED 2026-02-11 | 241 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 40 | 30 DAYS 33 | PRIORITY 52/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #1631 Path with Minimum Effort, LeetCode #778 Swim in Rising Water

LeetCode match: LC 1631 Path With Minimum Effort / LC 778 Swim in Rising Water (inferred from overview)

Posted on PracHub: 2026-02-11 (updated 2026-06-01)

Original: https://prachub.com/coding-questions/find-minimum-threshold-enabling-grid-path

QUESTION

Overview: This question evaluates a candidate's understanding of grid pathfinding, reachability under constraints, and algorithmic optimization, focusing on skills such as graph traversal and handling threshold-based feasibility.

APPROACH

Binary search the threshold and BFS/DFS for reachability, or run Dijkstra/union-find where path cost is the max cell value along the path.

HOW TO THINK ABOUT IT

The cost of a path is its largest cell, and a larger limit never makes things worse, so there are two equivalent plans: binary search the limit with a flood fill as the check, or run Dijkstra where the cost of a path is its maximum so far (extending a path never lowers it). Say the cost function out loud first: it is the maximum, not the sum.

HOW TO THINK ABOUT IT

Basis: LeetCode 778, Swim in Rising Water: the smallest threshold such that a path from the top-left to the bottom-right cell exists using only cells at or below it. (The related LeetCode 1631 minimises the largest difference between adjacent cells, see the follow-up.)

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    best = INF
    for path in all_paths(grid, START, GOAL):
        peak = max(grid[r][c] for r, c in path)
        best = min(best, peak)
    return best
```

TIME	SPACE
exponential	O(path)

WHY IT IS SLOW

Exponential in the grid size. Dijkstra with 'cost = largest cell so far', or binary search on the limit with a flood fill, is O(m * n log(m * n)).

OPTIMAL SOLUTION · Dijkstra with cost = maximum cell on the path

TIME	SPACE
O(m * n log(m * n))	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The cost is the largest difference between adjacent cells on the path (LeetCode 1631).

Same Dijkstra with max, but the step cost is abs(height difference) instead of the cell value. The binary-search version also works: the check allows an edge only if the difference is at most the limit.

FOLLOW-UP 2 Water rises over time (the cell is usable from time H[r][c]).

That is exactly the maximum-cell cost above; the answer is the time at which the corner becomes reachable.

FOLLOW-UP 3 Return the path, not only the value.

Remember each cell's parent at its last improvement and rebuild the path from the target; for the binary-search version run the flood fill once more at the answer limit with parent pointers.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


INF = float("inf")


def around(r, c, m, n):
    for dr, dc in ((1, 0), (-1, 0), (0, 1), (0, -1)):
        a, b = r + dr, c + dc
        if 0 <= a < m and 0 <= b < n:
            yield a, b


# ALSO: the Dijkstra version
def best_path(H, step_cost, start_cost):
    # Dijkstra where a path costs the MAX of its steps;
    # the
    # first time a cell leaves the heap its cost is final
    m, n = len(H), len(H[0])
    best = {(0, 0): start_cost}
    parent = {}
    heap = [(start_cost, 0, 0)]
    while heap:
        cost, r, c = heapq.heappop(heap)
        if cost > best[(r, c)]:
            continue
        if (r, c) == (m - 1, n - 1):
            path = [(r, c)]
            while (r, c) in parent:
                r, c = parent[(r, c)]
                path.append((r, c))
            return cost, path[::-1]
        for a, b in around(r, c, m, n):
            nxt = max(cost, step_cost(H, r, c, a, b))
            if nxt < best.get((a, b), INF):
                best[(a, b)] = nxt
                parent[(a, b)] = (r, c)
                heapq.heappush(heap, (nxt, a, b))
    return None, []


# BASE QUESTION (optimal): Dijkstra with cost = maximum
# cell on the path
def min_max_path(H):
    # cost of a path = its largest cell value
    # (water rising over time is the same problem)
    def step(H, r, c, a, b):
        return H[a][b]
    return best_path(H, step, H[0][0])


# FOLLOW-UP 1: The cost is the largest difference between
# adjacent cells on the path ...
def min_effort_path(H):
    # LeetCode 1631: cost = the largest height difference
    # between two neighbouring cells on the path
    def step(H, r, c, a, b):
        return abs(H[a][b] - H[r][c])
    return best_path(H, step, 0)


if __name__ == "__main__":
    H = [[0, 1, 2], [4, 3, 5], [8, 7, 6]]
    cost, path = min_max_path(H)
    # 0 -> 1 -> 3 -> 7 -> 6 or via 2, 5, 6: the max is 6
    assert cost == 6
    assert path[0] == (0, 0) and path[-1] == (2, 2)
    assert max(H[r][c] for r, c in path) == cost
    assert min_max_path([[5]]) == (5, [(0, 0)])
    effort, path2 = min_effort_path([[1, 2, 2], [3, 8, 2],
                                     [5, 3, 5]])
    assert effort == 2
    assert min_effort_path([[7]]) == (0, [(0, 0)])
```

FUNCTION AND TEST CASES

Signature

```
def solution(grid: list[list[int]]) -> int:
```

Sample call

```
solution([[0, 2], [1, 3]])
```

Test cases

Input	Expected
`([[0, 2], [1, 3]],)`	`3`
`([[0, 100, 2], [1, 2, 2], [3, 4, 1]],)`	`2`

HARD | IN APP LC 843 | PracHub | Technical Screen | 51 of 165

Find secret word with match-count feedback

POSTED 2026-02-11 | 241 DAYS AGO | OLDER

STUDY: TALK ALL TIME 42.2 30 DAYS 0 PRIORITY 83/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #843 Guess the Word

LeetCode match: LC 843 Guess the Word

Posted on PracHub: 2026-02-11 (updated 2026-04-30)

Original: https://prachub.com/coding-questions/find-secret-word-with-match-count-feedback

QUESTION

Problem

You are given a list of **unique** lowercase words, all of the same length (e.g., length = 6). One of these words is a **secret** word. You can interact with a black-box API:

- **`matchCount(guess) -> int`**: when you submit a word **`guess`** from the list, the API returns the number of positions **`i`** such that **`guess[i] == secret[i]`** (i.e., exact character match at the same index). You are allowed to call **`matchCount`**

at most 10 times.

Task

Design/implement a function (e.g., **`findSecretWord(words)`**) that uses the API to identify the secret word within the guess limit.

Notes / Constraints

- **`words`** contains between 1 and 100 words.
- All words have equal length **`L`** (commonly **`L = 6`**).
- Every guess must be a word from **`words`**.
- After each API response, you may adapt your next guess.

What to return

QUESTION

Depending on the interface, you may either: - return the identified secret word, or - stop once **`matchCount(guess) == L`** (found it). (Your interviewer may treat this as an interactive problem; focus on strategy + correctness under the 10-guess constraint.)

You are given a list of unique lowercase words, and every word has the same length **`L`**. Exactly one word in the list is the secret word. In the original interview version, you interact with a black-box API:

- **`matchCount(guess) -> int`**
- It returns how many positions **`i`** satisfy **`guess[i] == secret[i]`** You may call this API at most 10 times, and every guess must be a word from the given list. In this non-interactive version, implement **`solution(words, secret)`** and simulate the API inside your function. The parameter **`secret`** is provided only so the judge can verify your strategy. Your function should repeatedly make guesses, use the returned match counts to eliminate impossible candidates, and return the discovered secret word. If your strategy does not find the secret within 10 guesses, return an empty string **`""`**.

Constraints**`1 <= len(words) <= 1001 <= len(words[i]) <= 10`**All words are unique, lowercase, and have the same length **`Lsecret`** is guaranteed to be one of the words in **`words`**Your algorithm may use at most 10 simulated **`matchCount`** callsTest data is designed so that a correct elimination strategy can identify the secret within the limit

EXAMPLES

```
Input: (["acckzz", "ccbazz", "eiowzz", "abcczz"],
    "acckzz")
```

Expected Output: 'acckzz'Explanation: The secret is already one of the candidates. Using match-count feedback, the candidate set shrinks until **`acckzz`** is identified.

```
Input: (["secret"], "secret")
```

Expected Output: 'secret'Explanation: With only one word in the list, the first allowed guess must be the secret.

Hints

After a guess returns **`k`**, any valid remaining candidate must also have exactly **`k`** matching positions with that guess.A strong strategy is to choose the next guess that splits the remaining candidates as evenly as possible, minimizing the size of the largest feedback bucket.

APPROACH

Pick a guess, read matchCount, keep only candidates with the same match count against that guess. Choosing the guess that minimizes the worst-case remaining set (minimax) keeps queries low.

HOW TO THINK ABOUT IT

Each guess returns a number that every remaining candidate must agree with: a candidate can still be the secret only if it has the same match count with the guess as the secret does. So after each guess, filter the candidate list. To shrink fast, guess a word that splits the candidates evenly by match count (minimise the largest group); that is what keeps you inside 10 guesses.

Basis: LeetCode 843, Guess the Word (match count = positions with the same letter).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(words):
    candidates = list(words)
    while True:
        guess = candidates[0]
        m = matchCount(guess)
        if m == len(guess):
            return guess
        candidates = [w for w in candidates
                      if matches(w, guess) == m]
```

TIME	SPACE
O(guesses * W * L)	O(W)

WHY IT IS SLOW

A poor guess may remove very few candidates, so there is no guarantee of finishing in 10 guesses. Guessing the word whose largest match-count group is smallest (minimax) keeps the list shrinking fast.

OPTIMAL SOLUTION · Guess the word that minimises the size of its largest match-count group

TIME	SPACE
O(guesses * W^2 * L)	O(W)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Show how the candidate list shrinks.

After a guess with answer m, only words with the same match count against the guess survive (the secret and the candidate agree on every comparison). Printing the sizes round by round shows why a balanced guess finishes in a few rounds.

FOLLOW-UP 2 Guess at random instead of the minimax choice.

Expected to finish in far fewer than W guesses, but not guaranteed within 10 on a hard list. The minimax choice is the safe answer; random with a 'zero-match' preference (guess words that share no letters with earlier guesses) is a cheap improvement.

FOLLOW-UP 3 The word list is much larger.

Computing all pairwise match counts is O(W^2 L). Sample candidates when choosing a guess, or precompute buckets by letter at each position to count matches faster.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


def match(a, b):
    # number of positions holding the same letter
    return sum(x == y for x, y in zip(a, b))


# BASE QUESTION (optimal): Guess the word that minimises
# the size of its largest ...
def best_guess(candidates):
    # minimax: the guess whose worst answer leaves the
    # fewest
    # candidates (ties: alphabetical)
    def worst(g):
        sizes = Counter(match(g, w) for w in candidates)
        return max(sizes.values()), g
    return min(candidates, key=worst)


# BASE QUESTION (optimal): Guess the word that minimises
# the size of its largest ...
def find_secret(words, match_count, limit=10):
    # match_count(guess) is the black-box API
    candidates, guesses = list(words), 0
    while candidates and guesses < limit:
        guess = best_guess(candidates)
        guesses += 1
        score = match_count(guess)
        if score == len(guess):
            return guess, guesses
        # only words with the same score against this
        # guess
        # can still be the secret
        candidates = [w for w in candidates
                      if match(guess, w) == score]
    return None, guesses


# FOLLOW-UP 1: Show how the candidate list shrinks.
def shrink_report(words, secret):
    # candidate counts after each guess (shows why it
    # works)
    sizes, candidates = [len(words)], list(words)
    while len(candidates) > 1:
```

```
        guess = best_guess(candidates)
        score = match(guess, secret)
        if score == len(secret):
            break
        candidates = [w for w in candidates
                      if match(guess, w) == score]
        sizes.append(len(candidates))
    return sizes


if __name__ == "__main__":
    import itertools
    words = ["".join(p) for p in
```

```
            itertools.product("abc", repeat=4)]
    worst = 0
    for secret in words:
        calls = []

        def api(guess, secret=secret):
            calls.append(guess)
            return match(guess, secret)

        found, used = find_secret(words, api)
        assert found == secret and used == len(calls)
        worst = max(worst, used)
    # 81 words are always found inside the limit of 10
    assert worst <= 10
    single = find_secret(["only"], lambda g: 4)
    assert single == ("only", 1)
    sizes = shrink_report(words, "abca")
    assert sizes[0] == 81
    assert sizes == sorted(sizes, reverse=True)
```

FUNCTION AND TEST CASES

Signature

```
def solution(words: list[str], secret: str) -> str:
```

Sample call

```
solution(["acckzz", "ccbazz", "eiowzz", "abcczz"], "acckzz
")
```

Test cases

Input	Expected
`(["acckzz", "ccbazz", "eiowzz", "abcczz"], "acckzz")`	`'acckzz'`
`(["secret"], "secret")`	`'secret'`

HARD | IN APP LC 834 | PracHub | Technical Screen | 52 of 165

Compute distance-sum from every tree node

POSTED 2026-01-22 | 261 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 30.5 | 30 DAYS 0 | PRIORITY 122/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #834 Sum of Distances in Tree

LeetCode match: LC 834 Sum of Distances in Tree

Posted on PracHub: 2026-01-22 (updated 2026-05-26)

Original: https://prachub.com/coding-questions/compute-distance-sum-from-every-tree-node

QUESTION

Overview: This question evaluates understanding of tree and graph algorithms, including computation of pairwise distances and techniques for aggregating path lengths across nodes.

APPROACH

Rerooting DP: one DFS computes subtree sizes and the root's distance sum, a second DFS derives each child as ans[child] = ans[parent] - size[child] + (n - size[child]). O(n).

HOW TO THINK ABOUT IT

Computing the sum of distances from each node separately costs O(n) per node. Instead compute it once for the root, then derive the neighbour's answer in O(1): moving the root from a parent to its child makes every node in the child's subtree one step closer and every other node one step farther. That needs only the subtree sizes.

Basis: LeetCode 834, Sum of Distances in Tree (re-rooting dynamic programming).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n, adj):
    ans = []
    for node in range(n):
        dist = bfs(adj, node)
        ans.append(sum(dist))
    return ans
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

n searches of O(n) each, O(n^2). Compute the answer for the root, then move the root edge by edge using subtree sizes (re-rooting), O(n).

OPTIMAL SOLUTION · Re-rooting with subtree sizes

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Find the node with the smallest distance sum (the tree's centroid).

The answer array above gives it directly: argmin of ans. Equivalent: the centroid, found by walking toward the heavier subtree.

FOLLOW-UP 2 The tree has weighted edges.

Re-rooting still works, but the change when moving the root across an edge of weight w is w * (n - 2 * size[c]) instead of n - 2 * size[c]. Sizes and the first pass are the same.

FOLLOW-UP 3 Maximum distance (eccentricity) from each node instead of the sum.

The farthest node from any node is one end of a diameter; compute distances from both diameter ends and take the maximum per node. O(n).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
def build(n, edges):
    adj = [[] for _ in range(n)]
    for e in edges:
        u, v = e[0], e[1]
        w = e[2] if len(e) > 2 else 1
        adj[u].append((v, w))
        adj[v].append((u, w))
    return adj


def distances_from(adj, s):
    # distance from s to every node (a tree: one pass)
    dist, stack = {s: 0}, [s]
    while stack:
        u = stack.pop()
        for v, w in adj[u]:
            if v not in dist:
                dist[v] = dist[u] + w
                stack.append(v)
    return dist


# BASE QUESTION (optimal): Re-rooting with subtree sizes
def distance_sums(n, edges):
    # sum of distances from every node; edges may be
    # weighted
    adj = build(n, edges)
    parent, order, up = [-1] * n, [0], [0] * n
    for u in order:
        for v, w in adj[u]:
            if v != parent[u]:
                parent[v], up[v] = u, w
                order.append(v)
    size = [1] * n
    for u in reversed(order):
        if parent[u] >= 0:
            size[parent[u]] += size[u]
    # the root's sum is a plain sum of distances
    ans = [0] * n
    ans[0] = sum(distances_from(adj, 0).values())
    # root moves across an edge of weight w: size[u] nodes
    # get
    # w closer, the other n - size[u] get w farther
    for u in order[1:]:
        shift = up[u] * (n - 2 * size[u])
        ans[u] = ans[parent[u]] + shift
    return ans


# FOLLOW-UP 1: Find the node with the smallest distance
# sum (the tree's centroid).
def best_center(n, edges):
    # the node with the smallest distance sum
    sums = distance_sums(n, edges)
    return sums.index(min(sums))


# FOLLOW-UP 3: Maximum distance (eccentricity) from each
# node instead of the sum.
def eccentricities(n, edges):
    # the farthest node from anywhere is an end of a
    # diameter
    adj = build(n, edges)
    d0 = distances_from(adj, 0)
    a = max(d0, key=d0.get)
    da = distances_from(adj, a)
    b = max(da, key=da.get)
    db = distances_from(adj, b)
    return [max(da[v], db[v]) for v in range(n)]


if __name__ == "__main__":
    edges = [[0, 1], [0, 2], [2, 3], [2, 4], [2, 5]]
    want = [8, 12, 6, 10, 10, 10]
    assert distance_sums(6, edges) == want
    assert best_center(6, edges) == 2
    assert distance_sums(1, []) == [0]
    # weighted: the path 0 -(2)- 1 -(3)- 2
    w = [[0, 1, 2], [1, 2, 3]]
    assert distance_sums(3, w) == [7, 5, 8]
    # eccentricity: the farthest node from each node
    assert eccentricities(6, edges) == [2, 3, 2, 3, 3, 3]
```

FUNCTION AND TEST CASES

Signature

```python
def solution(n: int, edges: list[list[int]]) -> list[int]:
```

Sample call

```python
solution(1, [])
```

Test cases

Input	Expected
`(1, [])`	`[0]`
`(4, [[0, 1], [1, 2], [1, 3]])`	`[5, 3, 5, 5]`

ALSO REPORTED · 1 more

Tree Distance Sum (Re-root DP) | 1Point3Acres | onsite-coding | asked 2026-01-19 | Single report

https://www.1point3acres.com/interview/problems/company/google/tree-distance-sum-reroot

ALSO REPORTED · 1 more

The interviewer explicitly liked the "baseline first, optimize later" structure — name the O(n²) and move on within the first ~10 minutes.
Two-pass technique to memorize:
Post-order DFS rooted at any node: compute subSize[u] and subSum[u] (sum of distances inside u's subtree). Recurrence: subSum[u] += subSum[v] + subSize[v].
Pre-order DFS doing re-root: when moving root from parent p to child v, ans[v] = ans[p] + (n - subSize[v]) - subSize[v].
Verbalize the geometric intuition for the re-root formula: moving root toward v shortens distance to the subSize[v] nodes inside v's subtree by 1 and lengthens the other n - subSize[v] by 1.

Preparation: Drill the canonical sum-of-distances-in-tree problem until you can derive the re-root formula on a whiteboard without notes.
Practice both an iterative and a recursive version; deep recursion can blow the stack on chain-like trees.
Be prepared to explain why re-rooting is correct (proof by induction on the subtree boundary).

HARD | PracHub | Technical Screen | 53 of 165

Compute minimax grid path and network delay

POSTED 2026-01-22 | 261 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 37.9 | 30 DAYS 0 | PRIORITY 98/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #1631 Path with Minimum Effort, LeetCode #743 Network Delay Time

LeetCode match: LC 1631 Path With Minimum Effort + LC 743 Network Delay Time (inferred from overview)

Posted on PracHub: 2026-01-22 (updated 2026-05-26)

Original: https://prachub.com/coding-questions/compute-minimax-grid-path-and-network-delay

QUESTION

Overview: This question evaluates algorithmic problem-solving in shortest-path and path-optimization contexts, specifically minimax pathfinding on a grid and single-source reachability/timing in a weighted directed graph, testing graph modeling, alternative path cost metrics, edge-case handling, and working with large numeric weights.

APPROACH

Part 1: Dijkstra (or binary search + BFS) where cost is the max edge/cell along the path. Part 2: Dijkstra from the source; answer is the max distance, or -1 if some node is unreachable.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two parts. Part 1: ask what the path cost is (the maximum cell value along the path, including the start), the allowed moves (4-directional) and the endpoints (top-left to bottom-right). Part 2: ask whether the graph is directed, what to return if some node is unreachable (-1), and the size of weights. The scraped solution covers only part 1.

BRUTE FORCE TO SAY OUT LOUD

Part 1: DFS over all paths, O(4^(mn)). Part 2: Bellman-Ford, which is fine for small graphs.

OPTIMAL IDEA

Part 1: Dijkstra where the cost of a path is the maximum seen so far, with a min-heap keyed on that maximum: new_cost = max(cost, cell). O(mn log mn). Equivalent: binary search the cap and BFS, or sort cells and union-find until start and end connect. Part 2: Dijkstra from the source; the time for a signal to reach everyone is the largest shortest distance, or -1 if any node is unreachable. O((V + E) log V).

DRY-RUN THESE CASES

Part 1: [[1,10,6],[1,3,2],[7,2,2]] gives 3 (as in the example), a 1 x 1 grid, a grid where the best path takes a detour. Part 2: source with no outgoing edges, a disconnected node, parallel edges.

LIKELY FOLLOW-UPS

Part 1 with the cost as the sum minus something, or paths that may revisit cells. Part 2 with large weights (use 64-bit integers).

PITFALLS

Using the sum instead of the maximum when relaxing. Not counting the start cell's own value.

HOW TO THINK ABOUT IT

Both are 'shortest path' with a different notion of cost. For the grid the cost of a path is its maximum, which still works in Dijkstra: the best way to reach a cell is the one with the smallest maximum, and extending a path can never lower it. For the network, Dijkstra from the source gives every arrival time, and the answer is the largest of them (-1 if some node is never reached).

Basis: Two parts: LeetCode 1631-style minimax path (path cost = the largest cell value on the path, start cell included) and LeetCode 743, Network Delay Time (time for a signal to reach every node, or -1).

BRUTE FORCE · Part 1: DFS over every simple path

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    best = INF
    for path in all_paths(grid, START, GOAL):
        peak = max(grid[r][c] for r, c in path)
        best = min(best, peak)
    return best
```

TIME	SPACE
exponential	O(path)

WHY IT IS SLOW

The number of simple paths is exponential. Dijkstra where the cost of a path is its maximum cell (or a union-find over cells added in increasing order) is O(m * n log(m * n)).

BRUTE FORCE · Part 2: Bellman-Ford from the source

BRUTE FORCE · PSEUDO-CODE

```
def brute(n, edges, source):
    dist = [INF] * n
    dist[source] = 0
    for _ in range(n - 1):
        for u, v, w in edges:
            if dist[u] + w < dist[v]:
                dist[v] = dist[u] + w
    worst = max(dist)
    return -1 if worst == INF else worst
```

TIME	SPACE
O(V * E)	O(V)

WHY IT IS SLOW

V - 1 rounds over all edges, O(V * E). Dijkstra with a heap is O((V + E) log V) for non-negative weights.

OPTIMAL SOLUTION · Part 1: Dijkstra where the cost of a path is its maximum cell

TIME	SPACE
O(m * n log(m * n))	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Part 2: Dijkstra from the source, answer is the largest distance

TIME	SPACE
O((V + E) log V)	O(V + E)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Part 1 with a union-find (sort cells, add them one by one).

Add cells in increasing order of height, union neighbours already added, and stop when the start and the goal are connected: that height is the answer. O(mn log mn) for the sort.

FOLLOW-UP 2 Part 2: weights are huge.

Use 64-bit integers (Python is fine); keep sums in a wide type, and with weights up to 10^9 and 10^5 edges a path can reach 10^14. **Cost:** unchanged O((V + E) log V); sums need 64-bit (or Python) integers.

FOLLOW-UP 3 Part 2: the signal can be blocked at some nodes, or each node adds a processing delay.

A node delay is added to the edge cost leaving the node (or modelled by splitting each node into in and out with an edge of the delay). The same Dijkstra then applies.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq

INF = float("inf")


def neighbors(r, c, m, n):
    for dr, dc in ((1, 0), (-1, 0), (0, 1), (0, -1)):
        a, b = r + dr, c + dc
        if 0 <= a < m and 0 <= b < n:
            yield a, b


# BASE QUESTION (optimal): Dijkstra where the cost of a
# path is its maximum cell
def minimax_path(H):
    # Part 1: the path whose highest cell is as low as
    # possible
    m, n = len(H), len(H[0])
    best = {(0, 0): H[0][0]}
    heap = [(H[0][0], 0, 0)]
    while heap:
        cost, r, c = heapq.heappop(heap)
        if cost > best[(r, c)]:
            continue
        if (r, c) == (m - 1, n - 1):
            return cost
        for a, b in neighbors(r, c, m, n):
            # the cost of a path is its maximum, never a
            # sum
            nxt = max(cost, H[a][b])
            if nxt < best.get((a, b), INF):
                best[(a, b)] = nxt
                heapq.heappush(heap, (nxt, a, b))
    return -1


# FOLLOW-UP 1: Part 1 with a union-find (sort cells, add
# them one by one).
def minimax_path_union_find(H):
    # the same answer: add cells from lowest to highest
```

```
    # and
    # stop when the start and the goal are connected
    m, n = len(H), len(H[0])
    parent = {}
```

```
    def find(x):
        while parent[x] != x:
            parent[x] = parent[parent[x]]
            x = parent[x]
        return x

    cells = sorted((H[r][c], r, c)
                   for r in range(m) for c in range(n))
    for h, r, c in cells:
        parent[(r, c)] = (r, c)
        for a, b in neighbors(r, c, m, n):
            if (a, b) in parent:
                parent[find((r, c))] = find((a, b))
        if (0, 0) in parent and (m - 1, n - 1) in parent:
            if find((0, 0)) == find((m - 1, n - 1)):
                return h
    return -1


# PART 2: network delay
def network_delay(n, edges, source, node_delay=None):
    # Part 2: when does the signal reach every node?
    # edges are (u, v, weight); -1 if some node is
    # unreachable
    graph = [[] for _ in range(n)]
    for u, v, w in edges:
        graph[u].append((v, w))
    dist = [INF] * n
    dist[source] = 0
    heap = [(0, source)]
    while heap:
        d, u = heapq.heappop(heap)
        if d > dist[u]:
            continue
        # a processing delay is paid when leaving a node
        pause = node_delay[u] if node_delay else 0
        for v, w in graph[u]:
            if d + pause + w < dist[v]:
                dist[v] = d + pause + w
                heapq.heappush(heap, (dist[v], v))
    worst = max(dist)
    return -1 if worst == INF else worst


if __name__ == "__main__":
```

```
    H = [[0, 2, 1], [1, 3, 1], [2, 2, 1]]
    assert minimax_path(H) == 2
    assert minimax_path(H) == minimax_path_union_find(H)
    assert minimax_path([[5]]) == 5
    edges = [(0, 1, 2), (1, 2, 3), (0, 2, 10)]
    assert network_delay(3, edges, 0) == 5
    # a node that cannot be reached
    assert network_delay(4, edges, 0) == -1
    # huge weights are fine with Python integers
    big = [(0, 1, 10 ** 9), (1, 2, 10 ** 9)]
    assert network_delay(3, big, 0) == 2 * 10 ** 9
    # each node adds a processing delay of 1
    slow = network_delay(3, big, 0, [1, 1, 1])
    assert slow == 2 * 10 ** 9 + 2
```

FUNCTION AND TEST CASES

Signature

```
def solution(H: list[list[int]]) -> int:
SAMPLE INPUT
[[1, 10, 6], [1, 3, 2], [7, 2, 2]]
```

Test cases

Input	Expected
`[[1, 10, 6], [1, 3, 2], [7, 2, 2]]`	`3`
`[[5, 1, 7], [4, 8, 2], [3, 6, 0]]`	`6`

HARD | IN APP LC 648 | PracHub | Technical Screen | 54 of 165

Implement Longest-Match Text Replacement

POSTED 2026-01-20 | 263 DAYS AGO | OLDER

STUDY: TALK ALL TIME 31.9 30 DAYS 0 PRIORITY 119/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #648 Replace Words

LeetCode match: LC 648 Replace Words / LC 833 Find And Replace in String

Posted on PracHub: 2026-01-20 (updated 2026-06-13)

Original: https://prachub.com/coding-questions/implement-longest-match-text-replacement

QUESTION

You are given a text string and a dictionary of replacement entries. Each dictionary entry has the form **`token:id`**, where **`token`** is a string pattern and **`id`** is the value that should be emitted when that token is matched. Implement a function that scans the text from left to right and produces an output sequence using greedy longest-prefix matching:

1. At the current text position, find all dictionary tokens that match the substring starting at that position.
2. If at least one token matches, choose the longest matching token, append its corresponding **`id`** to the output, and advance by the length of that token.
3. If no token matches, append the original character at the current position to the output and advance by one character.
4. Continue until the entire text has been processed.

Example:

```
text = "abcdxyz" dictionary = { "ab": "1", "abc": "2",
 "xy": "3" }
```

Output:

```
["2", "d", "3", "z"]
```

QUESTION

Explanation: At index `0`, both `"ab"` and `"abc"` match, so choose the longest token `"abc"` and output `"2"`. Then `"d"` has no match, so output it literally. Then `"xy"` matches and outputs `"3"`. Finally, `"z"` is output literally. Follow-up: How would you adapt your design if the matching priority changed from longest match to a configurable priority rule, such as dictionary insertion order, highest score, or a custom comparator?

Part 1: Longest-Match Text ReplacementGiven a text string and a dictionary that maps token strings to replacement id strings, scan the text from left to right. At each position:

1. Find every token that matches the substring starting at that position.
2. If at least one token matches, choose the longest matching token, append its replacement id to the output, and advance by the token length.
3. If no token matches, append the original character at that position as a one-character string and advance by 1. Return the final output as a list of strings.

Constraints

0 <= len(text) <= 1000000 <= len(dictionary) <= 10000Each token in dictionary is non-empty.The sum of all token lengths is at most 100000.Matching is case-sensitive.

EXAMPLES

```
Input: ("abcdxyz", {"ab": "1", "abc": "2", "xy":
    "3"})
Expected Output: ["2", "d", "3", "z"]
```

Explanation: Both 'ab' and 'abc' match at index 0, so the longer token 'abc' is chosen.

```
Input: ("aaaaa", {"a": "X", "aa": "Y"})
Expected Output: ["Y", "Y", "X"]
```

Explanation: Greedy longest matching picks 'aa' twice, then the final 'a'.

Hints

A trie lets you test all token prefixes starting at one position without checking every token from scratch.While walking forward from a position, remember the last trie node that represented a complete token.

Part 2: Configurable-Priority Text ReplacementImplement the same left-to-right text replacement process, but the match-selection rule is configurable. You are given: - a text string - a list of replacement entries in insertion order - a priority rule Each replacement entry is a tuple: (token, replacement_id, score). At each text position, find all entries whose token matches the substring starting there. If one or more entries match, choose exactly one using the selected priority rule:

QUESTION

- 'longest': choose the longest matching token; if tied, choose the earlier entry in the list - 'insertion': choose the earliest matching entry in the input list - 'score': choose the matching entry with the highest score; if tied, choose the longer token; if still tied, choose the earlier entry in the list Append the chosen replacement_id to the output and advance by the chosen token length. If nothing matches, append the original character and advance by 1. Return the final output as a list of strings.

Constraints

0 <= len(text) <= 1000000 <= len(entries) <= 10000Each token is non-empty.Tokens in entries are unique.The sum of all token lengths i

APPROACH

Build a trie of tokens; scan the text and at each position walk the trie, remembering the longest terminal match; emit its id and jump ahead, else copy the char. Aho-Corasick if the text is large.

HOW TO THINK ABOUT IT

At each position you want the longest dictionary token starting there. Checking every token costs the size of the dictionary per character, so share prefixes in a trie: walk the text from the current position down the trie, remember the last node that ends a token, and stop when the trie has no further edge. The remembered node is the longest match.

Basis: LeetCode 648 (Replace Words) and the longest-prefix matching used in tokenizers and routing tables. Scan left to right, at each position take the longest dictionary token that matches, else copy the character.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def replace(text, entries):
    out, i = [], 0
    while i < len(text):
        best = ""
        for token in entries:
            if text.startswith(token, i):
                if len(token) > len(best):
                    best = token
        if best:
            out.append(entries[best])
            i += len(best)
        else:
            out.append(text[i])
            i += 1
    return out
```

TIME	SPACE
O(len(text) * tokens * token length)	**O(1)** extra

WHY IT IS SLOW

BRUTE FORCE

Each position tests every token. A trie of the tokens is walked from i, remembering the last token end, so a position costs at most the longest token.

OPTIMAL SOLUTION · Trie walk that remembers the last token end

TIME	SPACE
O(len(text) * longest token)	O(total token length)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The priority is not longest match: insertion order, a score, or a custom comparator.

Collect every token that matches at the position (walk the trie and gather all token ends along the path, not just the last) and choose with the comparator. The trie gives the candidates; the policy is separate.

FOLLOW-UP 2 The text is huge or the dictionary changes often.

Use Aho-Corasick if you need all matches in one pass over the text, or a trie that supports inserts and deletes; a longest-match scan is then linear in the text length times the longest token.

FOLLOW-UP 3 Overlapping matches or word boundaries.

Require a boundary before and after a token by checking the neighbouring characters when you record a candidate end, or tokenise on word boundaries first and look up whole words. **Cost:** still O(len(text) * longest token) with the trie walk; a boundary check is O(1) per candidate.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Trie walk that remembers the
# last token end
# FOLLOW-UP 1: The priority is not longest match:
# insertion order, a score, or a ...
class Replacer:
    def __init__(self, mapping):
        # mapping: token -> id. A trie shares the
        # prefixes.
        self.root = {}
        for token, ident in mapping.items():
            node = self.root
            for ch in token:
                node = node.setdefault(ch, {})
            node["$"] = (token, ident)

    def candidates(self, text, i):
        # every token that matches at position i, shortest
        # first (all ends along the trie path, not just
        # the last)
        out, node, j = [], self.root, i
        while j < len(text) and text[j] in node:
            node = node[text[j]]
            j += 1
            if "$" in node:
                out.append(node["$"])
        return out

    # FOLLOW-UP 1: choose= picks by priority, not length
    def replace(self, text, choose=None,
                word_boundary=False):
        # choose(candidates) picks the winner; the default
        # is the
        # longest token
        choose = choose or (lambda cs: cs[-1])
        out, i = [], 0
        while i < len(text):
            found = self.candidates(text, i)
            # FOLLOW-UP 3: only whole-word matches
            if word_boundary:
                found = [c for c in found if
                         self.edge(text, i, len(c[0]))]
            if found:
                token, ident = choose(found)
                out.append(ident)
                i += len(token)
            else:
                # nothing matches here: keep the character
                out.append(text[i])
                i += 1
        return out

    @staticmethod
    def edge(text, i, size):
        # letters must not touch the match on either side
        before = i == 0 or not text[i - 1].isalnum()
        end = i + size
        after = end == len(text)
        after = after or not text[end].isalnum()
        return before and after


if __name__ == "__main__":
    table = {"ab": 1, "abc": 2, "c": 3}
    r = Replacer(table)
    # abc beats ab at position 0
    assert r.replace("abcab") == [2, 1]
    assert r.replace("xyz") == ["x", "y", "z"]
    assert r.replace("") == []
    # priority by insertion order instead of length
    order = list(table)
    first = r.replace("abc", lambda cs: min(
        cs, key=lambda c: order.index(c[0])))
    assert first == [1, 3]
    # whole words only
    words = Replacer({"cat": "C"})
    got = words.replace("cat concat cat", None, True)
    assert got[0] == "C" and got[-1] == "C"
    assert "C" not in got[1:-1]
```

FUNCTION AND TEST CASES

Signature

```
def solution(text: str, dictionary: dict[str, str]) -> lis
t[str]:
```

Sample call

```
solution("abcdxyz", {"ab": "1", "abc": "2", "xy": "3"})
```

Test cases

Input	Expected
`("abcdxyz", {"ab": "1", "abc": "2", "xy": "3"})`	`["2", "d", "3", "z"]`
`("aaaaa", {"a": "X", "aa": "Y"})`	`["Y", "Y", "X"]`

ALSO REPORTED · 1 more

Greedy Longest-Match Dictionary Tokenizer | 1Point3Acres | phone-screen | asked 2026-06-15 | Low

https://www.1point3acres.com/interview/problems/company/google/tokenize-longest-dict-match-greedy

The key:id dictionary format and the literal-passthrough for unmatched characters are confirmed across multiple candidates.

Two natural shapes:

Hashmap of keys + per-position scan up to maxKeyLen. Easy to write, O(n · maxKeyLen) time; O(n · L) if the longest key length L dominates.

Trie of keys + walk the trie one character at a time from each position; remember the deepest reached is_end node and emit it. O(n · L) worst case but does only one pass per starting position and adapts cleanly to the priority-rule follow-up (store priority at each terminal node and keep the best matched terminal along the walk, not necessarily the deepest).

Edge cases to discuss: overlapping keys with different lengths ("ab" vs "abc"), key whose match would consume the rest of the string, empty dictionary, key that is a single character (still apply longest-match, not literal-fallback).

If the follow-up generalizes to "non-overlapping tokenization that maximizes total score", that's the word-break with weights DP variant — flag it as a different problem class rather than patching the greedy.

Preparation: Implement both versions (hashmap-scan and trie-walk) from scratch in under 15 min each. Run them on a small dict like {"the": 1, "theater": 2, "a": 3} against text "theater" to confirm the trie returns id 2 and the hashmap version returns the same.

For the priority-tie follow-up: practice attaching a priority field to terminal nodes and picking the highest-priority terminal seen along the trie walk, not just the deepest. Time complexity should not change.

If asked to stream the input, switch to the Aho-Corasick mental model — the trie augmented with failure links emits all dictionary matches in a single linear pass over the text.

HARD | PracHub | Technical Screen | 55 of 165

Return top-k subset sums in descending order

POSTED 2026-01-07 | 276 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 5 | 30 DAYS 0 | PRIORITY 169/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

LeetCode match: LC 2386 Find the K-Sum of an Array

Posted on PracHub: 2026-01-07 (updated 2026-05-21)

Original: https://prachub.com/coding-questions/return-top-k-subset-sums-in-descending-order

QUESTION

Overview: This question evaluates proficiency in combinatorial reasoning, algorithmic optimization for large search spaces, and efficient extraction of top-k values within the coding & algorithms domain.

APPROACH

Sort values, start from the all-positives sum, and use a max/min-heap of (sum, index) states that either drop the next element or swap it for the following one, popping k times. O(n log n + k log k).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the empty subset counts, whether values can be negative or repeated, how large k is compared with 2^n, and whether equal sums count separately.

BRUTE FORCE TO SAY OUT LOUD

Enumerate all 2^n subsets, sort, take k. Fine for n <= 20; say that out loud.

OPTIMAL IDEA

Reduce negatives: let base be the sum of the positive values, and work with absolute values. Every subset sum of the original equals base minus a subset sum of the absolute values, so the k largest sums are base minus the k smallest subset sums of the sorted absolute values. Generate the k smallest sums with a min-heap of (sum, last index): from a state you either add the next element or replace the last element with the next one. Each pop yields the next smallest sum and creates at most two states, so O(n log n + k log k).

DRY-RUN THESE CASES

All positive values. All negative values (best is the empty subset). A zero in the array. k = 1 and k = 2^n.

LIKELY FOLLOW-UPS

Need k sums without storing all of them, subsets themselves (store parent pointers), or a limit on subset size.

PITFALLS

INTERVIEW-DAY PLAN

Forgetting to sort first, which breaks the add-next/replace-last move set. Pushing duplicate states.

HOW TO THINK ABOUT IT

k is small compared with 2^n, so never enumerate all subsets. Turn the problem into 'k smallest sums of non-negative numbers': subtract everything from the sum of the positive values. Then grow answers in increasing order with a heap where each state has exactly two successors (extend with the next element, or swap the last element for the next one).

Basis: Written; the classic 'k smallest subset sums' heap technique (also behind LeetCode 2386, K-Sum of an Array).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(nums, k):
    sums = []
    for size in range(len(nums) + 1):
        for subset in combinations(nums, size):
            sums.append(sum(subset))
    sums.sort(reverse=True)
    return sums[:k]
```

TIME	SPACE
O(2^n * n)	O(2^n)

WHY IT IS SLOW

2^n subsets and a sort of them: O(2^n * n) time and O(2^n) space, hopeless past about n = 20. A heap that grows the k best sums step by step is O(n log n + k log k).

OPTIMAL SOLUTION · Heap of the k smallest sums of absolute values

TIME	SPACE
O(n log n + k log k)	O(n + k)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the subsets themselves, not only the sums.

Store each heap state as a node with (last index, parent node) instead of copying lists, and rebuild a subset by walking parents only for the k answers. That keeps pushes O(1).

FOLLOW-UP 2 k can be as large as 2^n.

Then the output itself is that large; the heap approach is still O(k log k) and stops when the heap empties. Check k against 2^n first and fall back to enumeration for tiny n.

FOLLOW-UP 3 Limit subsets to at most m elements.

Add the element count to each heap state and refuse to push successors that exceed m. The ordering argument is unchanged because both successors never make the sum smaller.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from itertools import combinations


# BASE QUESTION (optimal): Heap of the k smallest sums of
# absolute values
def top_k_sums(nums, k):
    # Idea: start from the best subset (all positives).
    # Every
    # other subset is that one with some elements
    # "flipped",
    # which costs |x|. So the k best subsets are the k
    # cheapest sets of flips: a heap over sorted |x|.
    base = sum(x for x in nums if x > 0)
    cost = sorted(abs(x) for x in nums)
    out = [0]
    heap = [(cost[0], 0)] if cost else []
    while heap and len(out) < k:
        s, i = heapq.heappop(heap)
        out.append(s)
        if i + 1 < len(cost):
            # two successors, neither is ever cheaper:
            # add the next element ...
            heapq.heappush(heap, (s + cost[i + 1], i + 1))
            # ... or move the last flipped one up by one
            moved = s - cost[i] + cost[i + 1]
            heapq.heappush(heap, (moved, i + 1))
    return [base - c for c in out[:k]]


# FOLLOW-UP 1: Return the subsets themselves, not only the
# sums.
def top_k_subsets(nums, k):
    # also return the subsets: states keep a link to their
    # parent instead of copying lists
    order = sorted(range(len(nums)),
                   key=lambda i: abs(nums[i]))
    cost = [abs(nums[i]) for i in order]
    best = {i for i in range(len(nums)) if nums[i] > 0}

    def subset(chain):
        flipped = set()
        while chain is not None:
            flipped.add(order[chain[0]])
            chain = chain[1]
        return sorted(nums[i] for i in best ^ flipped)

    base = sum(nums[i] for i in best)
    out = [(base, sorted(nums[i] for i in best))]
    heap = [(cost[0], 0, (0, None))] if cost else []
    while heap and len(out) < k:
        s, i, chain = heapq.heappop(heap)
        out.append((base - s, subset(chain)))
        if i + 1 < len(cost):
            heapq.heappush(heap, (s + cost[i + 1], i + 1,
                                  (i + 1, chain)))
            # replace the last flip i by i + 1
            moved = s - cost[i] + cost[i + 1]
```

```
            heapq.heappush(heap, (moved, i + 1,
                                  (i + 1, chain[1])))
    return out[:k]


def brute(nums, k):
    # every subset: the check used by the demo
    sums = []
    for r in range(len(nums) + 1):
        for c in combinations(nums, r):
            sums.append(sum(c))
    return sorted(sums, reverse=True)[:k]


if __name__ == "__main__":
    nums = [3, -1, 2, -4]
    assert top_k_sums(nums, 5) == brute(nums, 5)
    assert top_k_sums(nums, 4) == [5, 4, 3, 2]
    # k bigger than the number of subsets: all 2^n sums
    assert top_k_sums([1, 2], 10) == brute([1, 2], 10)
    assert top_k_sums([], 3) == [0]
    cases = ([5, -2, 7, 1], [-1, -2, -3], [0, 4, -4])
    for sample in cases:
        for k in range(1, 2 ** len(sample) + 1):
            got = top_k_sums(sample, k)
            assert got == brute(sample, k)
    # the subsets add up to the sums
    for total, sub in top_k_subsets(nums, 4):
        assert sum(sub) == total
    totals = [t for t, _ in top_k_subsets(nums, 4)]
    assert totals == [5, 4, 3, 2]
```

FUNCTION AND TEST CASES

Signature

```
def solution(w: list[int], k: int) -> list[int]:
```

Sample call

```
solution([3, 2, 1], 4)
```

Test cases

Input	Expected
([3, 2, 1], 4)	[6, 5, 4, 3]
([5], 2)	[5, 0]

HARD | PracHub | Technical Screen | 56 of 165

Minimize travel time with optional meeting point

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 37.9 | 30 DAYS 33 | PRIORITY 58/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #743 Network Delay Time, LeetCode #2203 Minimum Weighted Subgraph With the Required Paths

LeetCode match: LC 743 Network Delay Time (multi-source Dijkstra); related LC 2203 (inferred from overview)

ABOUT THIS QUESTION

Posted on PracHub: 2026-01-06 (updated 2026-05-22)

Original: https://prachub.com/coding-questions/minimize-travel-time-with-optional-meeting-point

QUESTION

Overview: This question evaluates a candidate's understanding of graph shortest-path computation and meeting-point optimization, testing skills in handling weighted edges, aggregating path costs, and reasoning about simultaneous movements on a network.

APPROACH

Run Dijkstra from each traveler's start, then pick the node that minimizes the total (or max, per the statement) travel time; compare against the no-meeting option.

INTERVIEW-DAY PLAN

CLARIFY FIRST

From the scraped solution the setup is two travelers A and B and a destination. Confirm: do they have to travel together after meeting, do they wait for each other (the meeting time is the later arrival), is the graph directed or undirected, and what to return (the minimum time and the meeting node, with ties going to the smallest node, or -1 and -1 if impossible). My copy has only the overview, so verify these.

BRUTE FORCE TO SAY OUT LOUD

Try every node as a meeting point with a fresh shortest path computation each time. O(n * (E log V)).

OPTIMAL IDEA

Run Dijkstra from A, Dijkstra from B, and Dijkstra from the destination on the reversed graph (so you get every node's distance to the destination in one pass). For each node m the time is max(distA[m], distB[m]) + distToDest[m]. Take the minimum, with ties to the smallest node. Compare with the no-meeting option if each can also go directly. O((V + E) log V).

DRY-RUN THESE CASES

A and B start at the same node, a node that only one of them can reach, a directed graph where the way back is longer, two nodes with equal time.

LIKELY FOLLOW-UPS

More travelers (Dijkstra from each, take the max), minimize total distance instead of arrival, or an optional meeting point.

PITFALLS

Forgetting to reverse the graph for the destination distances in a directed graph. Using sum instead of max for waiting.

HOW TO THINK ABOUT IT

Break it into shortest paths from three places: from A, from B, and into the destination (a Dijkstra on the reversed graph if directed). For each node m the cost is max(distA[m], distB[m]) + dist(m to destination); take the minimum. Three single-source searches replace trying every meeting node with its own search.

Basis: Written from the scraped solution (confirm it): two travellers A and B, a destination; they may meet at a node (the meeting happens when the later one arrives) and then travel together to the destination; return [best time, best node] with ties to the smallest node, or [-1, -1].

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n, edges, A, B, dest):
    d = floyd_warshall(n, edges)  # all pairs
    best, best_m = INF, None
    for m in range(n):
        cost = max(d[A][m], d[B][m]) + d[m][dest]
        if cost < best:
            best, best_m = cost, m
    return best
```

TIME	SPACE
O(V^3)	O(V^2)

WHY IT IS SLOW

All-pairs distances cost O(V^3) when only three single-source distances are needed. Dijkstra from A, from B and into the destination is O((V + E) log V).

OPTIMAL SOLUTION · Three Dijkstra runs (from A, from B, and into the destination)

TIME	SPACE
O((V + E) log V)	O(V + E)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 More than two travellers.

Run one Dijkstra per traveller and one from the destination, then for each node take the maximum arrival time (if they wait for each other) or the sum of distances (if the cost is total distance) plus the shared leg. K + 1 searches.

FOLLOW-UP 2 Meeting is optional.

Also compute the cost with no meeting (each goes straight to the destination: max(distA[dest], distB[dest])) and take the smaller. Meeting at the destination itself already covers it when the cost is the later arrival.

FOLLOW-UP 3 Edge weights change over time (traffic).

Dijkstra still works if the graph is FIFO (leaving later never arrives earlier); each edge's cost becomes a function of the departure time, evaluated when you relax it.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq

INF = float("inf")


def dijkstra(graph, source):
    dist = [INF] * len(graph)
    dist[source] = 0
    heap = [(0, source)]
    while heap:
        d, u = heapq.heappop(heap)
        if d > dist[u]:
            continue
        for v, w in graph[u]:
            if d + w < dist[v]:
                dist[v] = d + w
                heapq.heappush(heap, (d + w, v))
    return dist


def build(n, edges, directed):
    # forward graph, and the reversed graph for "to dest"
    fwd = [[] for _ in range(n)]
    rev = [[] for _ in range(n)]
    for u, v, w in edges:
        fwd[u].append((v, w))
        rev[v].append((u, w))
        if not directed:
            fwd[v].append((u, w))
            rev[u].append((v, w))
    return fwd, rev


# BASE QUESTION (optimal): Three Dijkstra runs (from A,
# from B, and into the ...
def meeting_point(n, edges, a, b, dest, directed=False):
    # both start at the same time, meet at node m, wait
    # for
    # each other, then travel together to dest. Meeting at
    # dest itself covers the "no meeting" plan.
    fwd, rev = build(n, edges, directed)
    da, db = dijkstra(fwd, a), dijkstra(fwd, b)
    # distance from every node TO dest = search the
    # reverse graph
    to_dest = dijkstra(rev, dest)
    best = (INF, -1)
    for m in range(n):
        total = max(da[m], db[m]) + to_dest[m]
        if total < best[0]:
            best = (total, m)
    return [-1, -1] if best[0] == INF else list(best)


# FOLLOW-UP 1: More than two travellers.
def meeting_point_many(n, edges, starts, dest,
                       directed=False):
    # k travellers: one search each, plus one from dest
    fwd, rev = build(n, edges, directed)
```

```
    dists = [dijkstra(fwd, s) for s in starts]
    to_dest = dijkstra(rev, dest)
    best = (INF, -1)
    for m in range(n):
        wait = max(d[m] for d in dists)
        if wait + to_dest[m] < best[0]:
            best = (wait + to_dest[m], m)
    return [-1, -1] if best[0] == INF else list(best)


if __name__ == "__main__":
    # a star: both travellers reach the hub 2, then go to
    # 3
    edges = [(0, 2, 1), (1, 2, 2), (2, 3, 4), (0, 3, 9),
             (1, 3, 9)]
    # meet at 2: max(1, 2) + 4 = 6; going alone costs 9
    assert meeting_point(4, edges, 0, 1, 3) == [6, 2]
    # nobody can reach the destination
    short = [(0, 1, 1)]
    assert meeting_point(3, short, 0, 1, 2) == [-1, -1]
    # same start: they simply walk together
    assert meeting_point(4, edges, 0, 0, 3)[0] == 5
    # three travellers
    got = meeting_point_many(4, edges, [0, 1, 1], 3)
    assert got == [6, 2]
    # directed roads: reverse edges are not usable
    one_way = [(0, 1, 1), (1, 2, 1)]
    walk = meeting_point(3, one_way, 0, 1, 2, True)
    assert walk == [2, 1]
```

FUNCTION AND TEST CASES

Signature

```
def solution(n: int, edges: list[list[int]], startA: int,
startB: int, dest: int, directed: bool = False) -> list[in
t]:
```

Sample call

```
solution(4, [(0, 1, 2), (1, 2, 1), (1, 3, 2), (2, 3, 2)],
0, 2, 3, False)
```

Test cases

Input	Expected
`(4, [(0, 1, 2), (1, 2, 1), (1, 3, 2), (2, 3, 2)], 0, 2, 3, False)`	`[4, 1]`
`(4, [(0, 1, 2), (2, 1, 3), (1, 3, 2), (0, 3, 10), (2, 3, 5)], 0, 2, 3, True)`	`[5, 1]`

HARD | PracHub | Technical Screen | 57 of 165

Determine winner in stack-merging game

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 31.2 | 30 DAYS 0 | PRIORITY 120/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #877 Stone Game

LeetCode match: Related: LC 292 Nim Game, LC 464 Can I Win, LC 877 Stone Game (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-05-14)

Original: https://prachub.com/coding-questions/determine-winner-in-stack-merging-game

QUESTION

Overview: This question evaluates understanding of combinatorial game theory, impartial game analysis, state-space encoding, and efficient state-space search techniques.

APPROACH

Impartial game: encode the state (tuple of stack sizes), memoize win/lose with DFS over all legal merges, or use Sprague-Grundy values. Prune with symmetry (sorted state).

INTERVIEW-DAY PLAN

CLARIFY FIRST

My copy of this question has only the overview, so before anything ask for the exact rules: what a move is (for example merge two stacks, possibly adjacent ones, with a size limit), who moves first, whether the player who cannot move loses (normal play) or wins, and the number and size of stacks.

BRUTE FORCE TO SAY OUT LOUD

Recursive search over every legal move with no memory. Exponential.

OPTIMAL IDEA

Treat it as an impartial game. Encode the state as the multiset of stack sizes (a sorted tuple, which removes symmetric duplicates). A state is winning if some move leads to a losing state, and a state with no moves is losing for the player to move under normal play. Memoize on the sorted tuple. If the game splits into independent parts, use Sprague-Grundy numbers (mex of reachable values) and XOR them instead of searching the product.

DRY-RUN THESE CASES

No legal moves, one stack, two equal stacks, a state reachable by two move orders (checks memoization).

LIKELY FOLLOW-UPS

INTERVIEW-DAY PLAN

Larger states (find a pattern from small cases with a brute-force table, then prove it), misere play, or counting winning first moves.

PITFALLS

Starting to code before the rules are confirmed. Memoizing on an unsorted state and blowing up the state space.

HOW TO THINK ABOUT IT

Two-player game with perfect play and no draws: define win(state) = some move leads to a state where the opponent loses. A state with no moves is a loss for whoever must move. If a move does not care about stack order, sort the state so equal positions share one cache entry. If the game splits into independent parts, use Grundy numbers and XOR them.

Basis: Written. The statement is not available in my copy, so this uses an example rule (confirm the real one): any two stacks may be merged if their combined size is at most a cap; a player who cannot move loses. The method (memoized win/lose search, Sprague-Grundy for independent games) is the part that carries over.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def wins(state):
    for nxt in all_merges(state):
        if not wins(nxt):
            return True  # opponent loses
    return False  # no move wins
```

TIME	SPACE
exponential in the number... exponential in the number of stacks	**O(depth)**

WHY IT IS SLOW

The same position is reached through many different move orders, so the work is exponential. Remembering the result per position (sorted state as key) solves each position once.

OPTIMAL SOLUTION · Memoize on the sorted state

TIME	SPACE
O(number of distinct sorted states * k^2)	**O(number of states)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The game is a sum of independent games (several separate boards or piles).

Compute each part's Grundy number (the mex of the Grundy numbers of its moves) and XOR them. The first player wins exactly when the XOR is not zero. This turns an exponential search over the product of states into a sum of small searches.

FOLLOW-UP 2 Misere play (the player who cannot move wins).

Flip the base case in the memoized search: no moves means the player to move wins. Grundy numbers no longer compose by XOR in general, so search the whole state or use the known special-case theory.

FOLLOW-UP 3 Count the number of winning first moves.

Keep the same memoized win/lose function and count the moves whose resulting state is a loss for the opponent.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from functools import lru_cache


def moves(state, cap):
    # merge two stacks if the new stack fits under the cap
    seen = set()
    for i in range(len(state)):
        for j in range(i + 1, len(state)):
            if state[i] + state[j] <= cap:
                rest = [x for k, x in enumerate(state)
                        if k not in (i, j)]
                merged = state[i] + state[j]
                new = tuple(sorted(rest + [merged]))
                # equal results are the same move
                if new not in seen:
                    seen.add(new)
                    yield new


# BASE QUESTION (optimal): Memoize on the sorted state
def first_player_wins(stacks, cap, misere=False):
    # the player who cannot move loses (misere: wins)
    @lru_cache(None)
    def wins(state):
        options = list(moves(state, cap))
        if not options:
            return misere
        # a winning move leaves the opponent in a losing
        # state
        return any(not wins(nxt) for nxt in options)

    return wins(tuple(sorted(stacks)))


# FOLLOW-UP 3: Count the number of winning first moves.
def winning_first_moves(stacks, cap):
    # how many different first moves win?
    state = tuple(sorted(stacks))
    return sum(1 for nxt in moves(state, cap)
               if not first_player_wins(nxt, cap))


# FOLLOW-UP 1, 2: The game is a sum of independent games
# (several separate boards or ...
def grundy(stacks, cap):
    # Sprague-Grundy number of one game (mex of its moves)
    @lru_cache(None)
    def g(state):
        reach = {g(nxt) for nxt in moves(state, cap)}
        number = 0
```

```
        while number in reach:
            number += 1
        return number

    return g(tuple(sorted(stacks)))


# FOLLOW-UP 1, 2: The game is a sum of independent games
# (several separate boards or ...
def sum_of_games_wins(boards, cap):
    # independent boards: XOR their Grundy numbers
    total = 0
    for board in boards:
        total ^= grundy(board, cap)
    return total != 0


if __name__ == "__main__":
    # one stack: no move, so the first player loses
    assert not first_player_wins([3], 5)
    # two stacks that can merge: one move ends it, so we
    # win
    assert first_player_wins([1, 1], 5)
    # three stacks: after one merge the other two may
    # merge too
    assert first_player_wins([1, 1, 1], 2) is True
    # in misere play the result flips for a single stack
    assert first_player_wins([3], 5, misere=True)
    assert winning_first_moves([1, 1, 1], 2) >= 1
    # normal play: a position wins exactly when Grundy !=
    # 0
    for state in ([1, 2, 3], [2, 2, 2, 2], [1, 1, 4]):
        win = first_player_wins(state, 6)
        assert win == (grundy(state, 6) != 0)
    # two separate boards: XOR of their numbers
    both = sum_of_games_wins([[1, 1], [1, 1]], 5)
    assert both is False
```

FUNCTION AND TEST CASES

Signature

```
def solution(colors: list[str]) -> bool:
SAMPLE INPUT
['Y']
```

Test cases

Input	Expected
`['Y']`	`False`
`['Y', 'W']`	`True`

ALSO REPORTED · 1 more

Babylon Tile-Stack Merge Game | 1Point3Acres | onsite-coding | asked 2025-12-29 | Single report

https://www.1point3acres.com/interview/problems/company/google/babylon-stack-merge-game

ALSO REPORTED · 1 more

This is closer to an implementation/simulation interview than a clever-algorithm problem — the interviewer wants a clean game state class, legal-move enumeration, and a play(move) API. Represent state as a List[Stack] where Stack = (height, topColor, fullSequence?). Whether you keep the full color sequence depends on whether the interviewer asks about "undo" or "re-color from top".
Add a minimax / negamax for "who wins from this state with optimal play" as the natural follow-up — branching factor is small (at most C(12, 2) = 66 initially, drops fast).
Reported as "too hard to finish coding in 45 minutes"; the interviewer gives hints throughout. Pacing matters.

Preparation: Drill clean game-state implementations: e.g. Connect 4, Othello move generators, in 30 minutes.
Practice writing a generic minimax framework so you can plug in this game's legalMoves(state) and terminal(state) quickly.
Watch the merge invariant carefully: "same height OR same top color" — fail mode is forgetting the alternative branch.

HARD | IN APP LC 778, 1631 | PracHub | Technical Screen | 58 of 165

Minimize maximum height along a grid path

POSTED 2026-01-04 | 279 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 40 | 30 DAYS 33 | PRIORITY 53/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #778 Swim in Rising Water, LeetCode #1631 Path with Minimum Effort

LeetCode match: LC 778 Swim in Rising Water / LC 1631

Posted on PracHub: 2026-01-04 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/minimize-maximum-height-along-a-grid-path

QUESTION

Overview: This question evaluates algorithmic pathfinding and graph-modeling skills, specifically reasoning about grid-based route selection where the objective is defined by an aggregate maximum over visited cell heights.

APPROACH

Min-heap Dijkstra keyed by the max height seen so far (or binary search the cap + BFS, or union-find by sorted cell heights). O(mn log mn).

HOW TO THINK ABOUT IT

The cost of a path is its largest cell, and a larger limit never makes things worse, so there are two equivalent plans: binary search the limit with a flood fill as the check, or run Dijkstra where the cost of a path is its maximum so far (extending a path never lowers it). Say the cost function out loud first: it is the maximum, not the sum.

Basis: LeetCode 778, Swim in Rising Water: the smallest maximum height such that a path from the top-left to the bottom-right cell exists using only cells at or below it. (The related LeetCode 1631 minimises the largest difference between adjacent cells, see the follow-up.)

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    best = INF
    for path in all_paths(grid, START, GOAL):
        peak = max(grid[r][c] for r, c in path)
        best = min(best, peak)
    return best
```

TIME	SPACE
exponential	O(path)

WHY IT IS SLOW

Exponential in the grid size. Dijkstra with 'cost = largest cell so far', or binary search on the limit with a flood fill, is O(m * n log(m * n)).

OPTIMAL SOLUTION · Dijkstra with cost = maximum cell on the path

TIME	SPACE
O(m * n log(m * n))	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The cost is the largest difference between adjacent cells on the path (LeetCode 1631).

Same Dijkstra with max, but the step cost is abs(height difference) instead of the cell value. The binary-search version also works: the check allows an edge only if the difference is at most the limit.

FOLLOW-UP 2 Water rises over time (the cell is usable from time H[r][c]).

That is exactly the maximum-cell cost above; the answer is the time at which the corner becomes reachable.

FOLLOW-UP 3 Return the path, not only the value.

Remember each cell's parent at its last improvement and rebuild the path from the target; for the binary-search version run the flood fill once more at the answer limit with parent pointers.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq

INF = float("inf")


def around(r, c, m, n):
    for dr, dc in ((1, 0), (-1, 0), (0, 1), (0, -1)):
        a, b = r + dr, c + dc
        if 0 <= a < m and 0 <= b < n:
            yield a, b


# BASE QUESTION (optimal): Dijkstra with cost = maximum
# cell on the path
def min_max_path(H, with_path=False):
    # Dijkstra where a path costs the MAX of its cells
    m, n = len(H), len(H[0])
    best, parent = {(0, 0): H[0][0]}, {}
    heap = [(H[0][0], 0, 0)]
    while heap:
        cost, r, c = heapq.heappop(heap)
        if cost > best[(r, c)]:
            continue
        if (r, c) == (m - 1, n - 1):
            if not with_path:
                return cost
            path = [(r, c)]
            while (r, c) in parent:
                r, c = parent[(r, c)]
                path.append((r, c))
            return cost, path[::-1]
        for a, b in around(r, c, m, n):
            nxt = max(cost, H[a][b])
            if nxt < best.get((a, b), INF):
                best[(a, b)] = nxt
                parent[(a, b)] = (r, c)
                heapq.heappush(heap, (nxt, a, b))


def reachable(H, limit):
    # flood fill using only cells with height <= limit
    m, n = len(H), len(H[0])
    if H[0][0] > limit:
        return False
    seen, stack = {(0, 0)}, [(0, 0)]
```

```
    while stack:
        r, c = stack.pop()
        if (r, c) == (m - 1, n - 1):
            return True
        for a, b in around(r, c, m, n):
            if (a, b) not in seen and H[a][b] <= limit:
                seen.add((a, b))
                stack.append((a, b))
    return False


# ALTERNATIVE: binary search the answer
def min_max_path_bsearch(H):
    # binary search the answer over the sorted heights
    heights = sorted({h for row in H for h in row})
    lo, hi = 0, len(heights) - 1
    while lo < hi:
        mid = (lo + hi) // 2
        if reachable(H, heights[mid]):
            hi = mid
```

```
        else:
            lo = mid + 1
    return heights[lo]


# FOLLOW-UP 1: The cost is the largest difference between
# adjacent cells on the path ...
def min_effort_path(H):
    # LeetCode 1631: cost = the largest height DIFFERENCE
    m, n = len(H), len(H[0])
    best = {(0, 0): 0}
    heap = [(0, 0, 0)]
    while heap:
        cost, r, c = heapq.heappop(heap)
        if cost > best[(r, c)]:
            continue
        if (r, c) == (m - 1, n - 1):
            return cost
        for a, b in around(r, c, m, n):
            nxt = max(cost, abs(H[a][b] - H[r][c]))
            if nxt < best.get((a, b), INF):
                best[(a, b)] = nxt
                heapq.heappush(heap, (nxt, a, b))
```

```
if __name__ == "__main__":
    H = [[0, 2, 1], [1, 3, 1], [2, 2, 1]]
    assert min_max_path(H) == min_max_path_bsearch(H)
    cost, path = min_max_path(H, True)
    assert path[0] == (0, 0) and path[-1] == (2, 2)
    assert max(H[r][c] for r, c in path) == cost
    assert min_max_path([[7]]) == 7
    grid = [[0, 1, 2], [4, 3, 5], [8, 7, 6]]
    assert min_max_path(grid) == 6
    assert min_max_path_bsearch(grid) == 6
    assert min_effort_path([[1, 2, 2], [3, 8, 2],
                            [5, 3, 5]]) == 2
```

FUNCTION AND TEST CASES

Sample call

```
solution([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
```

Test cases

Input	Expected
`([[1, 2, 3], [4, 5, 6], [7, 8, 9]],)`	`9`
`([[8, 4, 7], [6, 5, 9], [3, 2, 1]],)`	`8`

ALSO REPORTED · 1 more

Path Minimizing the Maximum Cell (Swim in Rising Water) | 1Point3Acres | onsite-coding | asked 2026-07-08 | Low

https://www.1point3acres.com/interview/problems/company/google/path-min-max-grid-dijkstra

ALSO REPORTED · 1 more

The clean solution is a Dijkstra variant: priority queue keyed on the running maximum, relax with new = max(dist[cur], height[nxt]). The same skeleton handles the safety variant with edge values in place of cell heights, plus the admissibility filter. Also mentionable: binary-search the answer + BFS/DFS reachability check — but Dijkstra is the cleaner one-pass solution.

The grid prompt minimizes a maximum rather than a sum. Be ready to justify why Dijkstra still works: the path cost is monotone as a path grows, so extending a settled vertex never lowers its committed cost.

The safety version preserves the bottleneck-path shape but changes cells to weighted edges and adds an explicit admissibility threshold.

For the plain shortest-path follow-up, do standard Dijkstra with a min-heap; skip stale priority-queue entries (if curDist != dist[u]: continue) and account for unreachable nodes.

Preparation: Drill the grid and weighted-graph variants back to back, stating the path-cost invariant before implementation. Practice proving correctness for a monotone max-along-path objective and test source-equals-target, disconnected graphs, and values exactly at the threshold.

HARD | IN APP LC 1044 | PracHub | Technical Screen | 59 of 165

Find longest duplicated substring

POSTED 2025-12-08 | 306 DAYS AGO | OLDER

STUDY: TALK ALL TIME 30.5 30 DAYS 0 PRIORITY 121/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #1044 Longest Duplicate Substring

LeetCode match: LC 1044 Longest Duplicate Substring

Posted on PracHub: 2025-12-08 (updated 2026-07-09)

Original:
https://prachub.com/coding-questions/find-longest-duplicated-substring

QUESTION

You are given a string **s** consisting of lowercase English letters. A **substring** of **s** is any contiguous sequence of characters, i.e., `s[i..j)` for `0 <= i < j <= len(s)`. Design an algorithm to find **any one** of the longest substrings that appears **at least twice** in **s**. The two occurrences may overlap. If no substring appears at least twice, return the empty string.

Requirements

- Input: a string **s** of length **n** (e.g., `1 <= n <= 2 × 10^5`).
- Output: a string representing one of the longest duplicated substrings.

QUESTION

- Aim for an algorithm substantially better than the naive **`O(n^2)`** substring comparison approach.

Examples

- **`s = "banana"`**
- Possible duplicated substrings: "a", "an", "ana" - Longest length is 3 ("ana"), so acceptable outputs include **`"ana"`**.
- **`s = "abcd"`**
- No duplicated substring, so output should be **`""`** (empty string). Describe your algorithm, its time and space complexity, and how it scales for large **n**.

APPROACH

Binary search on the substring length; check each length with a Rabin-Karp rolling hash plus a set (verify on collision). Alternative: suffix array + LCP. O(n log n).

HOW TO THINK ABOUT IT

If a substring of length L repeats, then a substring of every shorter length repeats too, so 'is there a duplicate of length L' is monotone and the answer length can be binary searched. Each check slides a window of length L over the string with a rolling hash and looks for a repeated hash, verifying the match to guard against collisions.

Basis: LeetCode 1044, Longest Duplicate Substring (binary search on the length with a rolling hash).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s):
    n = len(s)
    for L in range(n - 1, 0, -1):
        seen = set()
        for i in range(n - L + 1):
            sub = s[i:i + L]
            if sub in seen:
                return sub
            seen.add(sub)
    return ""
```

TIME	SPACE
O(n^3)	O(n^2)

WHY IT IS SLOW

Each length builds up to n substrings of up to n characters: O(n^3) time and O(n^2) space. If a duplicate of length L exists then so does one of every shorter length, so binary search on L with a rolling hash is O(n log n).

OPTIMAL SOLUTION · Binary search on the length with a rolling hash (Rabin-Karp)

TIME	SPACE
O(n log n) expected	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Avoid hash collisions entirely.

Use a suffix array with the LCP array: the longest duplicate is the largest LCP between neighbours in suffix order. Naive construction (sorting suffixes) is O(n^2 log n); real suffix array algorithms are O(n log n) or O(n).

FOLLOW-UP 2 The substring must appear at least k times, or must not overlap.

At least k times: count equal hashes in the check (need k of them). Non-overlapping: when two windows match, require their start positions to differ by at least L.

FOLLOW-UP 3 The string is huge and does not fit in memory.

Hash windows on disk in passes, or use a suffix automaton built online; for approximate answers use minhash sketches. State that exact answers need memory proportional to the number of distinct windows. **Cost:** O(n log n) time and O(n) memory for the hashes; on disk the hashing passes multiply the I/O by about log n.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
MOD = (1 << 61) - 1
BASE = 131


def find_length(s, length):
    # a repeated window of this length? (rolling hash)
    codes = [ord(c) for c in s]
    power = pow(BASE, length, MOD)
    h = 0
    for i in range(length):
        h = (h * BASE + codes[i]) % MOD
    seen = {h: [0]}
    for i in range(1, len(s) - length + 1):
        # slide the window: drop the left, add the right
        h = (h * BASE - codes[i - 1] * power
             + codes[i + length - 1]) % MOD
        # a hash match may be a collision: compare the
        # text
        for j in seen.get(h, ()):
            if s[j:j + length] == s[i:i + length]:
                return s[i:i + length]
        seen.setdefault(h, []).append(i)
    return None


# BASE QUESTION (optimal): Binary search on the length
```

```
# with a rolling hash (Rabin-Karp)
def longest_dup(s):
    # binary search the length: if length L repeats, so do
    # all shorter lengths
    lo, hi, best = 1, len(s) - 1, ""
    while lo <= hi:
        mid = (lo + hi) // 2
        found = find_length(s, mid)
        if found:
            best, lo = found, mid + 1
        else:
            hi = mid - 1
    return best


# FOLLOW-UP 1: Avoid hash collisions entirely.
def longest_dup_suffix(s):
    # no hashing: sort the suffixes, compare neighbours
    # (the
```

```
    # simple O(n^2 log n) version of a suffix array)
    suffixes = sorted(s[i:] for i in range(len(s)))
    best = ""
    for a, b in zip(suffixes, suffixes[1:]):
        k = 0
        while k < min(len(a), len(b)) and a[k] == b[k]:
            k += 1
        if k > len(best):
            best = a[:k]
    return best


# FOLLOW-UP 2: The substring must appear at least k times,
# or must not overlap.
def longest_repeated(s, times=2, non_overlapping=False):
    # at least `times` occurrences; optionally not
    # overlapping
    best = ""
    n = len(s)
    for length in range(1, n):
        spots = {}
        for i in range(n - length + 1):
            piece = s[i:i + length]
            spots.setdefault(piece, []).append(i)
        ok = None
        for text, starts in spots.items():
            if non_overlapping:
                # greedy: count starts at least `length`
                # apart
                taken, last = 0, -length
                for p in starts:
                    if p - last >= length:
                        taken, last = taken + 1, p
            else:
                taken = len(starts)
            if taken >= times:
                ok = text
                break
        if ok is None:
            break
        best = ok
    return best


if __name__ == "__main__":
```

```
    assert longest_dup("banana") in ("ana",)
    assert longest_dup("abcd") == ""
    assert len(longest_dup("aaaaa")) == 4
    assert len(longest_dup_suffix("banana")) == 3
    assert longest_dup_suffix("abcd") == ""
    for s in ("abracadabra", "mississippi", "abab"):
        fast = len(longest_dup(s))
        assert fast == len(longest_dup_suffix(s))
    # three occurrences needed
    assert longest_repeated("banana", 3) == "a"
    # overlapping copies are not allowed: "aa" cannot fit
    # in aaaa
    assert len(longest_repeated("aaaa", 2, True)) == 2
    assert len(longest_repeated("aaaa", 2)) == 3
```

FUNCTION AND TEST CASES

Signature

```
def solution(s) -> str:
```

Sample call

```
solution('banana')
```

Test cases

Input	Expected
`('banana',)`	`'ana'`
`('abcd',)`	`''`

HARD | PracHub | Technical Screen | 60 of 165

Shuffle array using random integer API

POSTED 2025-12-08 | 306 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 14.7 | 30 DAYS 0 | PRIORITY 161/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 384 Shuffle an Array

Posted on PracHub: 2025-12-08 (updated 2026-06-25)

Original: https://prachub.com/coding-questions/shuffle-array-using-random-integer-api

QUESTION

You are given an array **nums** of length **n** representing a deck of distinct cards. You **do not** have access to a built-in shuffle function, but you are given the following API:

```
rand_int(l, r) # returns a uniformly random integer in
 [l, r], inclusive
```

Task

Implement a function **`shuffle(nums)`** that randomly permutes the array **in place** such that **every one of the `n!` permutations is equally likely**.

Requirements

- You may only use **`rand_int(l, r)`** as your source of randomness.
- The algorithm should run in **`O(n)`** time and **`O(1)`** extra space.

QUESTION

- You may assume **`rand_int`** itself is perfectly uniform and independent between calls. Describe your algorithm, argue why the resulting permutation is uniform, and give the time and space complexity.

APPROACH

Fisher-Yates: for i from n-1 down to 1, j = rand_int(0, i), swap nums[i], nums[j]. Uniform because each permutation has probability 1/n!. Avoid the biased 'swap with random index in [0,n)' version.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether rand_int(l, r) is inclusive of r, whether to shuffle in place, and whether the result must be uniformly random over all n! permutations.

BRUTE FORCE TO SAY OUT LOUD

Assign each element a random key and sort. It is uniform but O(n log n).

OPTIMAL IDEA

Fisher-Yates: for i from n - 1 down to 1, pick j = rand_int(0, i) and swap nums[i] with nums[j]. Each of the n! permutations has probability 1 / n! because position i is filled by one of i + 1 equally likely elements. O(n) time, O(1) extra space.

DRY-RUN THESE CASES

n = 0 and n = 1. n = 3 with many trials: all six permutations should appear about equally. Say why swapping with a random index in [0, n) is biased (n^n outcomes cannot divide evenly into n! permutations).

LIKELY FOLLOW-UPS

Shuffle only k elements (stop the loop early), uniform integer from a coin flip only (rejection sampling), or a weighted shuffle.

PITFALLS

Using j in [0, n) every time. An off-by-one on the inclusive bound.

HOW TO THINK ABOUT IT

'Shuffle' means every one of the n! orders must be equally likely. Count outcomes: a procedure with n^n equally likely random choices cannot give n! equal buckets, so it is biased. Fisher-Yates makes n choices with sizes n, n-1, ..., 1, which multiply to exactly n!.

Basis: LeetCode 384, Shuffle an Array (Fisher-Yates).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def shuffle(nums):
    keyed = []
    for x in nums:
        keyed.append((rand_int(0, 10 ** 9), x))
    keyed.sort()
    return [x for _, x in keyed]
```

TIME	SPACE
O(n log n)	O(n)

WHY IT IS SLOW

O(n log n) time and O(n) extra space, and equal random keys make the result very slightly non-uniform. Fisher-Yates (swap position i with a random position in 0..i) is O(n), in place and exactly uniform.

OPTIMAL SOLUTION · Fisher-Yates

TIME	SPACE
O(n)	O(1) extra

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return only k random elements.

Run Fisher-Yates for k steps from the front (swap position i with a random index in i..n-1) and return the first k. O(k) after copying, still uniform.

FOLLOW-UP 2 Only a coin-flip API exists, no rand_int.

Build a uniform integer in [0, m) by rejection sampling: draw ceil(log2 m) random bits and retry if the number is at least m. That keeps every value equally likely, unlike taking a remainder.

FOLLOW-UP 3 Why is the biased version biased?

It makes n choices of n options, n^n equally likely paths, and n! does not divide n^n for n >= 3, so some permutations must appear more often than others.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import random


# BASE QUESTION (optimal): Fisher-Yates
def shuffle(nums, rand_int):
    # Fisher-Yates: from the end, swap each position with
    # a
    # random one at or before it. All n! orders are
    # equally
    # likely because each step picks uniformly among i +
```

```
    # 1.
    for i in range(len(nums) - 1, 0, -1):
        j = rand_int(0, i)
        nums[i], nums[j] = nums[j], nums[i]
    return nums


# FOLLOW-UP 1: Return only k random elements.
def sample_k(nums, k, rand_int):
    # k random elements: only k Fisher-Yates steps, from
    # the front
    a = list(nums)
    for i in range(min(k, len(a))):
        j = rand_int(i, len(a) - 1)
        a[i], a[j] = a[j], a[i]
    return a[:k]


# FOLLOW-UP 2: Only a coin-flip API exists, no rand_int.
def rand_below(m, flip):
    # only a coin flip exists: rejection sampling gives a
    # uniform number in [0, m) (a remainder would be
    # biased)
    bits = max(1, (m - 1).bit_length())
    while True:
        x = 0
        for _ in range(bits):
            x = x * 2 + flip()
        if x < m:
            return x


# FOLLOW-UP 3: Why is the biased version biased?
def biased_shuffle(nums, rand_int):
    # the common WRONG version: n^n paths cannot be spread
```

```
    # over
    # n! orders evenly (shown only to explain the bias)
    for i in range(len(nums)):
        j = rand_int(0, len(nums) - 1)
        nums[i], nums[j] = nums[j], nums[i]
    return nums


if __name__ == "__main__":
    rng = random.Random(7)
    rand_int = lambda lo, hi: rng.randint(lo, hi)
    seen = {}
    for _ in range(6000):
        key = tuple(shuffle([1, 2, 3], rand_int))
        seen[key] = seen.get(key, 0) + 1
    # all 6 orders appear, each about 1000 times
    assert len(seen) == 6
    assert all(850 < v < 1150 for v in seen.values())
    # nothing is lost or repeated
    deck = shuffle(list(range(50)), rand_int)
    assert sorted(deck) == list(range(50))
    # k random elements
    pick = sample_k(list(range(10)), 3, rand_int)
    assert len(set(pick)) == 3 and len(pick) == 3
    # a coin gives uniform numbers below 5
    coin = lambda: rng.randint(0, 1)
    counts = [0] * 5
    for _ in range(5000):
        counts[rand_below(5, coin)] += 1
    assert all(800 < c < 1200 for c in counts)
    assert shuffle([], rand_int) == []
```

FUNCTION AND TEST CASES

Signature

```
def solution(nums: list[int], random_indices: list[int]) -
> list[int]:
```

Sample call

```
solution([1, 2, 3, 4], [1, 1, 0])
```

Test cases

Input	Expected
`([1, 2, 3, 4], [1, 1, 0])`	`[3, 1, 4, 2]`
`([], [])`	`[]`

HARD | IN APP LC 218 | PracHub | Technical Screen | 61 of 165

Compute city skyline outline

POSTED 2025-12-08 | 306 DAYS AGO | OLDER

STUDY: TALK ALL TIME 29.8 30 DAYS 0 PRIORITY 124/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #218 The Skyline Problem

LeetCode match: LC 218 The Skyline Problem

Posted on PracHub: 2025-12-08 (updated 2026-06-26)

Original:
https://prachub.com/coding-questions/compute-city-skyline-outline

QUESTION

You are given a list of rectangular buildings in a 2D city skyline. Each building is represented by three integers **`[L, R, H]`**:

- **`L`**: the x-coordinate of the left edge of the building,
- **`R`**: the x-coordinate of the right edge of the building (**`L < R`**),
- **`H`**: the height of the building. All buildings stand on a flat horizontal line (y = 0) and extend vertically up to height **`H`**. Buildings may overlap in the x-dimension. Your task is to compute the *skyline* formed by these buildings, as seen from a distance. The skyline should be represented as a list of **key points `[x, height]`** that describe the outer contour of the union of all buildings. A **key point** is a point where the height of the skyline changes. The output list must satisfy all of the following:

1. The list is sorted by increasing **`x`**.
2. No two consecutive points have the same height (i.e., the height must change at each key point).
3. The first point has a height greater than 0.
4. The last point has height 0, marking the end of the skyline.

Input

- An integer **`n`** — the number of buildings.

QUESTION

- A list of **n** buildings, where each building is given as a triple `[L, R, H]` of integers. You may assume:
- `1 <= n <= 10^4`
- `0 <= L < R <= 10^9`
- `1 <= H <= 10^9`

Output

Return a list of key points representing the skyline. Each key point is a pair `[x, height]` (or a 2-element array/tuple) of integers.

Example

Input:

- `n = 3` - buildings = `[[2, 9, 10], [3, 7, 15], [5, 12, 12]]` One valid output:
- `[[2, 10], [3, 15], [7, 12], [12, 0]]` Explanation (informal):
- From x = 2 to 3, the highest building has height 10.
- From x = 3 to 7, the highest building has height 15.
- From x = 7 to 12, the remaining highest building has height 12.
- After x = 12, there are no buildings, so the height drops to 0. Design an algorithm to compute the skyline key points for the given buildings.

APPROACH

Sweep line over building edges with a max-heap of active heights (lazy deletion); emit a point whenever the max height changes. O(n log n). Divide and conquer also works.

HOW TO THINK ABOUT IT

The skyline height at x is the tallest building covering x, and it can only change at a building's left or right edge. So sweep over those x positions in order, keep the active buildings in a max-heap by height, and report a key point whenever the maximum changes. The details that matter are the event order at the same x and removing finished buildings lazily.

Basis: LeetCode 218, The Skyline Problem.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def brute(buildings):
    xs = set()
    for L, R, H in buildings:
        xs |= {L, R}
    out, prev = [], 0
    for x in sorted(xs):
        h = 0
        for L, R, H in buildings:
            if L <= x < R:
                h = max(h, H)
        if h != prev:
            out.append([x, h])
            prev = h
    return out
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Each edge scans all buildings, O(n^2). A sweep with a max-heap of active buildings and lazy deletion is O(n log n).

OPTIMAL SOLUTION · Sweep line with a max-heap and lazy deletion

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Divide and conquer instead of a heap.

Build the skyline of each half and merge the two by sweeping both lists with the current height of each; the merged height is the max of the two. T(n) = 2T(n/2) + O(n) = O(n log n), same as the heap.

FOLLOW-UP 2 Coordinates up to 10^9 or buildings of a very large count.

Only the edge coordinates matter, so nothing depends on the coordinate range. The sweep is O(n log n) in the number of buildings; use a balanced tree or a heap with lazy deletion for the active set.

FOLLOW-UP 3 Output the area under the skyline.

Sum height * (next x - x) over consecutive key points: one extra pass over the output.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
```

```python
# BASE QUESTION (optimal): Sweep line with a max-heap and
# lazy deletion
def skyline(buildings):
    # buildings are [left, right, height]
    # start events carry -height so taller starts sort
    # first;
    # end events carry 0
    events = sorted([(l, -h, r) for l, r, h in buildings]
                    + [(b[1], 0, 0) for b in buildings])
    out = []
    # the active buildings: (-height, right edge), ground
    # first
    heap = [(0, float("inf"))]
    for x, neg_h, right in events:
        # buildings that ended at or before x are gone
        while heap[0][1] <= x:
            heapq.heappop(heap)
        if neg_h:
            heapq.heappush(heap, (neg_h, right))
        top = -heap[0][0]
        # a key point only where the height changes
        if not out or out[-1][1] != top:
            out.append([x, top])
    return out


def merge(a, b):
    # divide and conquer: merge two skylines with the
    # current
    # height of each; the result height is their maximum
    out, i, j, ha, hb = [], 0, 0, 0, 0
    while i < len(a) or j < len(b):
        take_a = i < len(a) and (j == len(b)
                                 or a[i][0] <= b[j][0])
        if take_a:
            x, ha = a[i]
            i += 1
        else:
            x, hb = b[j]
            j += 1
        # when both change at the same x, wait for the
        # second
        if i < len(a) and a[i][0] == x:
            continue
        if j < len(b) and b[j][0] == x:
            continue
        top = max(ha, hb)
        if not out or out[-1][1] != top:
            out.append([x, top])
    return out


# FOLLOW-UP 1: Divide and conquer instead of a heap.
def skyline_dc(buildings):
    if len(buildings) == 1:
        l, r, h = buildings[0]
        return [[l, h], [r, 0]]
    if not buildings:
        return []
    mid = len(buildings) // 2
    return merge(skyline_dc(buildings[:mid]),
                 skyline_dc(buildings[mid:]))


# FOLLOW-UP 3: Output the area under the skyline.
def area_under(points):
    # sum of height * width between consecutive key points
    return sum(h * (points[i + 1][0] - x)
               for i, (x, h) in enumerate(points[:-1]))


if __name__ == "__main__":
    b = [[2, 9, 10], [3, 7, 15], [5, 12, 12],
         [15, 20, 10], [19, 24, 8]]
    want = [[2, 10], [3, 15], [7, 12], [12, 0], [15, 10],
            [20, 8], [24, 0]]
    assert skyline(b) == want
    assert skyline_dc(b) == want
    flat = skyline([[0, 2, 3], [2, 5, 3]])
    assert flat == [[0, 3], [5, 0]]
    assert skyline([]) == []
    # 10*1 + 15*4 + 12*5 + 10*5 + 8*4 = 212
    assert area_under(want) == 212
    assert skyline([[1, 2, 1], [1, 2, 2], [1, 2, 3]]) == [
        [1, 3], [2, 0]]
```

FUNCTION AND TEST CASES

Sample call

```
getSkyline(3, [[2, 9, 10], [3, 7, 15], [5, 12, 12]])
```

Test cases

Input	Expected
(3, [[2, 9, 10], [3, 7, 15], [5, 12, 12]])	[[2, 10], [3, 15], [7, 12], [12, 0]]
(1, [[0, 2, 3]])	[[0, 3], [2, 0]]

HARD | PracHub | Technical Screen | 62 of 165

Find maximum value in huge text file

POSTED 2025-12-08 | 306 DAYS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 181/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

LeetCode match: No LC match (systems / scalability question; the Hard tag looks inflated)

Posted on PracHub: 2025-12-08 (updated 2026-06-27)

Original: https://prachub.com/interview-questions/find-maximum-value-in-huge-text-file

QUESTION

You are given the path to a **very large** text file on disk. The file has the following properties:

- Each line contains exactly one signed 64-bit integer (in decimal).
- The file size can be tens or hundreds of gigabytes, so it **cannot** be fully loaded into memory.
- You have standard file I/O APIs that allow you to read the file sequentially (e.g., line by line or in chunks).

Tasks

QUESTION

1.
Single-machine solution Design an algorithm to compute the **maximum integer value** in this file.

- Assume you have limited RAM (much smaller than the file size).
- Discuss how you would read the file and track the result.
- Give high-level pseudocode.
- Analyze time and space complexity. 2.

Performance improvement / parallelization Suppose you now have a multi-core machine or multiple machines available and want to speed up the computation.

- How would you modify your approach to take advantage of parallelism (e.g., processing the file in chunks)?
- Explain how you would combine partial results to get the global maximum.
- Mention any edge cases or failure scenarios you would consider (e.g., very large values, empty file). Assume you do not have a database; you are working directly with the file system and your programming language's standard I/O libraries.

APPROACH

Stream the file line by line (or in large buffered chunks) keeping a single running max initialized to None/-2^63; O(n) time, O(1) memory. Parallelize by splitting byte ranges aligned to line boundaries across cores/machines (map), then take the max of the partial maxima (reduce). Edge cases: empty file, trailing newline, malformed lines, negative-only values, retries when a worker fails.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the file size relative to RAM, whether a line can be malformed, whether the file can be empty, and whether there is one machine or a cluster.

BRUTE FORCE TO SAY OUT LOUD

Load the file and call max. Say why it fails (memory), then move on.

OPTIMAL IDEA

Stream line by line with one running maximum initialized to None (not zero, so negative-only files work). O(n) time, O(1) memory. To parallelize split the file into byte ranges aligned to line boundaries: each worker discards its partial first line (the previous worker reads it) and finishes the line that crosses its end. Reduce with max of the partial results; retry failed ranges since each task is idempotent.

DRY-RUN THESE CASES

Empty file, one line, all negative values, last line without newline, values at the 64-bit limits.

LIKELY FOLLOW-UPS

Top K values, the median of a huge file, or distributed execution with failures.

PITFALLS

Starting the max at zero. Splitting ranges mid-line.

HOW TO THINK ABOUT IT

The answer is a running maximum, which needs one variable, so memory should not depend on the file size. Read the file as a stream. To go faster across cores, give each worker a byte range that starts and ends on line boundaries; the global maximum is the maximum of the partial maxima.

Basis: Systems / streaming question, no LeetCode match: a streaming reduce and its map-reduce parallelization.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(path):
    numbers = []
    for line in open(path):
        numbers.append(int(line))  # in memory
    return max(numbers)
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Needs memory for the whole file, which is exactly what is not available at tens of gigabytes. Streaming with one running maximum uses O(1) memory.

OPTIMAL SOLUTION · Single machine: stream the file, keep one running maximum

TIME	SPACE
O(n)	O(1) plus the read buffer

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Parallel: split byte ranges on line boundaries (map), max of the maxima (reduce)

TIME	SPACE
O(n / workers) plus I/O limits	O(workers)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Edge cases to mention.

Empty file (return None or raise, by contract); a final line without a newline; blank lines; malformed lines; values at the 64-bit extremes; an all-negative file (do not initialize the max to 0); and Windows line endings. Decide whether a bad line fails the job or is skipped and counted.

FOLLOW-UP 2 How do you scale to many machines and handle failures?

Assign byte ranges (map tasks) to workers through a coordinator, and make each task idempotent (it only returns its maximum), so a failed or slow worker is simply retried or speculatively re-executed elsewhere. The reduce step is a max over a tiny list. On a distributed filesystem, align ranges to its block size for locality. **Cost:** O(n / workers) wall-clock time plus O(workers) to combine; total work stays O(n).

FOLLOW-UP 3 Is it I/O-bound or CPU-bound, and why does that matter?

Parsing integers is cheap compared with disk throughput, so one sequential reader often saturates the disk and extra threads help only if the data sits on several disks or on fast SSD or network storage. Measure first; the parallel version pays off mainly across machines or storage devices. **Cost:** reading takes about n / disk throughput and parsing is O(n) as well, so extra threads help only beyond the disk's speed.

FOLLOW-UP 4 The file has billions of lines and one machine is too slow.

Split by byte offsets across machines (each skips to the next newline), compute local maxima, and take the maximum of those few numbers. Tasks are idempotent, so a failed worker can simply be retried. **Cost:** O(n / machines) per machine and O(machines) to combine; a retry re-runs only the failed byte range.

FOLLOW-UP 5 Now return the K largest values instead of only the maximum.

Keep a min-heap of size K while streaming: push a value if the heap is not full, or replace the root when the value is larger. Memory O(K), time O(n log K); merge the per-worker heaps for a parallel version.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
import heapq
import os
import tempfile


# BASE QUESTION (optimal): Single machine: stream the
# file, keep one running maximum
def max_in_file(path):
    # one sequential pass, one number in memory
    best = None
    with open(path, "r", buffering=1 << 20) as f:
        for line in f:
            line = line.strip()
            # blank lines are ignored (state this
            # contract)
            if not line:
                continue
            value = int(line)
            # start from None, not 0: all numbers may be
            # negative
            if best is None or value > best:
                best = value
    return best


# FOLLOW-UP 5: Now return the K largest values instead of
# only the maximum.
def top_k_in_file(path, k):
    # the k largest values: a min-heap of size k, O(k)
    # memory
    heap = []
    with open(path) as f:
        for line in f:
            if not line.strip():
                continue
            value = int(line)
            if len(heap) < k:
                heapq.heappush(heap, value)
            elif value > heap[0]:
                heapq.heapreplace(heap, value)
    return sorted(heap, reverse=True)


# ONE WORKER: its byte range
def max_in_range(path, start, end):
    # one worker: lines that START inside [start, end)
    best = None
    with open(path, "rb") as f:
        f.seek(start)
        if start:
            # we may be in the middle of a line: the
            # previous
            # worker owns it, so skip to the next line
            # start
            f.seek(start - 1)
            f.readline()
        while f.tell() < end:
            line = f.readline()
            if not line:
                break
            if line.strip():
                v = int(line)
                best = v if best is None else max(best, v)
    return best


# FOLLOW-UP 4: The file has billions of lines and one
# machine is too slow.
def parallel_max(path, workers=4):
    # split by byte offsets; combine the few local maxima
    size = os.path.getsize(path)
    cuts = [size * i // workers
            for i in range(workers + 1)]
    parts = [max_in_range(path, a, b)
             for a, b in zip(cuts, cuts[1:])]
    parts = [p for p in parts if p is not None]
    return max(parts) if parts else None


if __name__ == "__main__":
```

```
def write(lines):
    f = tempfile.NamedTemporaryFile("w", delete=False)
    f.write("".join(lines))
    f.close()
    return f.name

p = write(["5\n", "-3\n", "\n", "99\n", "12"])
assert max_in_file(p) == 99
assert top_k_in_file(p, 2) == [99, 12]
assert parallel_max(p, 3) == 99
```

```
# all negative numbers, extreme 64-bit values
q = write(["-7\n", "-2\n", "-9\n"])
assert max_in_file(q) == -2
big = write([f"{2 ** 63 - 1}\n", f"{-2 ** 63}\n"])
assert max_in_file(big) == 2 ** 63 - 1
# an empty file has no maximum
e = write([])
assert max_in_file(e) is None
assert parallel_max(e) is None
# every worker count agrees on a bigger file
nums = [(i * 7919) % 10007 - 5000
        for i in range(2000)]
r = write([f"{x}\n" for x in nums])
for w in (1, 2, 5, 8):
    assert parallel_max(r, w) == max(nums)
for name in (p, q, big, e, r):
    os.remove(name)
```

HARD | PracHub | Technical Screen | 63 of 165

★ TOP 75: rank 10 in the Medium and Hard priority list

★ Find safe travel intervals between planet influences

POSTED 2025-11-22 | 322 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 65.2 | 30 DAYS 41.1 | PRIORITY 8/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #56 Merge Intervals

LeetCode match: LC 56 Merge Intervals (then take gaps)

Posted on PracHub: 2025-11-22 (updated 2026-05-23)

Original: https://prachub.com/coding-questions/find-safe-travel-intervals-between-planet-influences

QUESTION

You are planning a space route along a one-dimensional line (the x-axis). You are given a list of planets. Each planet is represented by an integer pair ((c, r)):

- **c** is the coordinate of the planet's center on the x-axis.
- **r** is a non-negative integer radius of its gravitational influence. A point **x** on the x-axis is **unsafe** for a space traveler if it lies within the gravitational influence of at least one planet: [|x - c_i| \le r_i \quad \text{for some planet } i] Equivalently, each planet makes the interval ([c_i - r_i,\; c_i + r_i]) unsafe. Task:

QUESTION

- Consider the entire real line as the possible travel path.
- Compute all **maximal continuous intervals** on this line where the traveler is **safe**, i.e., points not covered by any planet's unsafe interval.
- Return these safe intervals as a sorted list of disjoint intervals. Representation details:
- Represent each safe interval as a pair **`(start, end)`** with **`start < end`**.
- Intervals may be unbounded on the left or right:
- Use **`-inf`** for an interval unbounded to the left (e.g., **`(-inf, a)`**).
- Use **`+inf`** for an interval unbounded to the right (e.g., **`(b, +inf)`**). You may assume the input list of planets can be in any order and may contain overlapping or nested gravitational ranges. Return the safe intervals in increasing order of **`start`**.

You are planning a route along the real x-axis. Each planet is given as a pair (c, r), where c is its center and r is a non-negative radius of gravitational influence. A point x is unsafe if it lies inside at least one planet's influence, meaning |x - c| <= r. So each planet creates an unsafe closed interval [c - r, c + r]. Your task is to return all maximal continuous safe intervals on the real line: regions not covered by any unsafe interval. Represent each safe interval as a tuple (start, end), where the interval means start < x < end. Because JSON/Python literals do not have a direct infinity literal, use None to represent an unbounded side:

- (None, a) means (-infinity, a)
- (b, None) means (b, +infinity)
- (None, None) means the entire real line Return the safe intervals in increasing order. Overlapping, nested, and touching unsafe intervals should be treated as one merged unsafe region.

Constraints

0 <= len(planets) <= 200000-10^9 <= c <= 10^90 <= r <= 10^9

EXAMPLES

```
Input: []
Expected Output: [(None, None)]
```

Explanation: With no planets, no point is unsafe, so the entire real line is safe.

```
Input: [(3, 1), (10, 2)]
Expected Output: [(None, 2), (4, 8), (12, None)]
Explanation: The unsafe intervals are [2, 4] and [8,
    12]. Their complement is (-infinity, 2), (4, 8),
    and (12, +infinity).
```

Hints

First convert every planet (c, r) into the unsafe interval [c - r, c + r].Sort the unsafe intervals and merge all overlapping or touching ones. The safe intervals are the gaps before, between, and after the merged intervals.

APPROACH

Turn each planet into [c-r, c+r], sort, merge overlaps, and the safe intervals are the open gaps between merged intervals plus the two infinite ends. Watch endpoint inclusivity (unsafe intervals are closed).

HOW TO THINK ABOUT IT

The safe points are the complement of the union of the unsafe intervals. Merge the unsafe intervals first (sort by start, extend while they overlap or touch), and the safe intervals are exactly the gaps between consecutive merged intervals plus the two unbounded ends. Endpoints themselves are unsafe because the influence is closed (<=).

Basis: Interval complement (LeetCode 56, Merge Intervals, then take the gaps). Each planet (c, r) makes the closed interval [c - r, c + r] unsafe; safe intervals are the open gaps, possibly unbounded.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(planets):
    pts = set()
    for c, r in planets:
        pts |= {c - r, c + r}
    bounds = [-INF] + sorted(pts) + [INF]
    safe = []
    for a, b in zip(bounds, bounds[1:]):
        mid = midpoint(a, b)
        if not any(abs(mid - c) < r
                   for c, r in planets):
            safe.append((a, b))
    return safe
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Each midpoint is tested against every planet, O(n^2). Merging the unsafe intervals after sorting and reading the gaps is O(n log n).

OPTIMAL SOLUTION · Merge the unsafe intervals, then read off the gaps

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Only the part between two given positions matters (a route from A to B).

Intersect each safe interval with [A, B] and keep the non-empty ones. Or clip the planets first; the merge-and-gap logic is the same.

FOLLOW-UP 2 Are the endpoints safe?

The statement uses <=, so the endpoints of an unsafe interval are unsafe and the safe intervals are open. If the influence were strict (<), touching intervals would leave a single safe point between them and the merge test would use < instead of <=.

FOLLOW-UP 3 Planets arrive over time.

Keep the merged unsafe intervals in a sorted structure; an insert merges neighbours (like the stream-of-intervals problem) and the safe intervals are always the gaps.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
INF = float("inf")


def unsafe_blocks(planets):
    # planet (c, r) makes [c - r, c + r] unsafe; merge
    # overlaps
    merged = []
    spans = sorted((c - r, c + r) for c, r in planets)
    for a, b in spans:
        # sharing even one point joins two blocks
        if merged and a <= merged[-1][1]:
            merged[-1][1] = max(merged[-1][1], b)
        else:
            merged.append([a, b])
    return merged


# BASE QUESTION (optimal): Merge the unsafe intervals,
# then read off the gaps
def safe_intervals(planets):
    # the gaps between unsafe blocks (open intervals)
    merged = unsafe_blocks(planets)
    if not merged:
        return [(-INF, INF)]
    out = [(-INF, merged[0][0])]
    for prev, nxt in zip(merged, merged[1:]):
        out.append((prev[1], nxt[0]))
    out.append((merged[-1][1], INF))
    return out


# FOLLOW-UP 1: Only the part between two given positions
# matters (a route from A to ...
def safe_between(planets, a, b):
    # a route from a to b: clip every safe interval to [a,
    # b]
    out = []
    for lo, hi in safe_intervals(planets):
        lo, hi = max(lo, a), min(hi, b)
        if lo < hi:
            out.append((lo, hi))
    return out


# FOLLOW-UP 3: Planets arrive over time.
```

```
class LiveRoute:
    """Planets arrive over time: keep blocks merged."""

    def __init__(self):
```

```
        self.blocks = []

    def add(self, c, r):
        a, b = c - r, c + r
        keep = []
        for s, e in self.blocks:
            if e < a or s > b:
                keep.append([s, e])
            else:
                # overlaps the new block: absorb it
                a, b = min(a, s), max(b, e)
        keep.append([a, b])
        self.blocks = sorted(keep)

    def safe(self):
        return safe_intervals_from(self.blocks)


def safe_intervals_from(blocks):
    if not blocks:
        return [(-INF, INF)]
    out = [(-INF, blocks[0][0])]
    for prev, nxt in zip(blocks, blocks[1:]):
        out.append((prev[1], nxt[0]))
    out.append((blocks[-1][1], INF))
    return out


if __name__ == "__main__":
    planets = [(0, 2), (10, 1), (3, 1)]
    # unsafe: [-2, 4] and [9, 11]
    assert safe_intervals(planets) == [(-INF, -2), (4, 9),
                                       (11, INF)]
    assert safe_intervals([]) == [(-INF, INF)]
    # touching blocks merge: [0, 2] and [2, 4]
    assert safe_intervals([(1, 1), (3, 1)]) == [
        (-INF, 0), (4, INF)]
    # only the part of the route between 5 and 20 matters
    route = safe_between(planets, 5, 20)
    assert route == [(5, 9), (11, 20)]
    live = LiveRoute()
```

```
    for c, r in planets:
        live.add(c, r)
    assert live.safe() == safe_intervals(planets)
    # a big planet at 6 swallows both blocks
    live.add(6, 3)
    assert live.safe() == [(-INF, -2), (11, INF)]
```

FUNCTION AND TEST CASES

Signature

```
def solution(planets: list[list[int]]) -> list[list[int]]:
SAMPLE INPUT
[]
```

Test cases

Input	Expected
`[]`	`[(None, None)]`
`[(3, 1), (10, 2)]`	`[(None, 2), (4, 8), (12, None)]`

HARD | PracHub | Technical Screen | 64 of 165

Count same-color squares in a character grid

POSTED 2025-11-22 | 322 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 51.2 | 30 DAYS 0 | PRIORITY 65/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #1277 Count Square Submatrices with All Ones, LeetCode #221 Maximal Square

LeetCode match: LC 1277 Count Square Submatrices with All Ones / LC 221 Maximal Square

Posted on PracHub: 2025-11-22 (updated 2026-06-13)

Original: https://prachub.com/coding-questions/count-same-color-squares-in-a-character-grid

QUESTION

You are given a 2D grid (matrix) of characters. Each character represents a color: cells with the same character are considered the same color. Formally:

- The grid has **`m`** rows and **n** columns.
- **`grid[i][j]`** is an alphabetic character (e.g., **`'a'`**–**`'z'`** or **`'A'`**–**`'Z'`**). A **square** in this grid is defined as a contiguous **`k × k`** submatrix aligned with the grid axes, for some integer **`k >= 1`**. A square is **monochromatic** if **all** of its cells contain the **same** character (i.e., the same color). Task:
- Count and return the total number of monochromatic squares in the grid.
- Count all sizes of squares (1×1, 2×2, ..., up to the largest possible that fits in the grid). Example (just for clarity, not necessarily exhaustive): If the grid is:

```
a a b a a b b b b
```

Then some monochromatic squares include:

- All 1×1 cells (each single cell is a monochromatic square).
- The 2×2 square in the top-left corner formed by **`'a'`**. Your function should return the total count of such monochromatic squares for a given input grid.

You are given a 2D grid of characters, where each character represents a color. A square is a contiguous k × k submatrix aligned with the grid axes, for some k >= 1. A square is monochromatic if all of its cells contain the same character. Return the total number of monochromatic squares of all possible sizes and positions in the grid. Every 1 × 1 cell is considered a monochromatic square.
Constraints
0 <= len(grid) <= 1000If grid is non-empty, 0 <= len(grid[0]) <= 1000All rows in grid have the same lengthgrid[i][j] is an alphabetic characterThe total number of cells is at most 1,000,000

QUESTION

EXAMPLES

```
Input: ([])
Expected Output: 0
```

Explanation: An empty grid contains no squares.

```
Input: (["aab", "aab", "bbb"])
Expected Output: 10
```

Explanation: There are 9 single-cell squares and one 2x2 monochromatic square of 'a' in the top-left corner.

Hints

Try defining dp[i][j] as the side length of the largest monochromatic square whose bottom-right corner is cell (i, j).A square larger than 1 can end at (i, j) only if the current cell matches its top, left, and top-left neighboring cells.

APPROACH

dp[i][j] = 1 + min(top, left, top-left) when those neighbors share the same char as (i,j), else 1. Sum all dp values = number of monochromatic squares. O(mn).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the grid size, whether every k x k square counts (k from 1 up), and whether to count squares of every size (the statement says all).

BRUTE FORCE TO SAY OUT LOUD

For every top-left corner and size, check all cells. O(mn * min(m, n)^3).

OPTIMAL IDEA

dp[i][j] is the size of the largest same-color square whose bottom-right corner is (i, j), and it equals the number of such squares ending there. If i and j are positive and the cells above, left and diagonal match the current character, dp[i][j] = 1 + min(dp[i-1][j], dp[i][j-1], dp[i-1][j-1]); otherwise it is 1. The answer is the sum of all dp values. O(mn) time, O(n) with a rolling row.

DRY-RUN THESE CASES

A 1 x 1 grid (1), a grid of one color (sum of squares counts), a checkerboard (only 1 x 1 squares), a rectangle grid.

LIKELY FOLLOW-UPS

The largest square only, or squares allowing at most one different cell.

PITFALLS

Forgetting to compare the three neighbors to the current character, not just to each other.

HOW TO THINK ABOUT IT

Let dp[i][j] be the side of the largest same-colour square whose bottom-right corner is (i, j). That is also the number of squares ending at that corner (one per size from 1 up to it). A square of side k at (i, j) needs squares of side k - 1 at the three cells above, left and above-left, all of the same colour, hence the min of those three plus one.

Basis: LeetCode 1277 (Count Square Submatrices with All Ones) with 'same character' instead of 1. Counts squares of every size k >= 1.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
count = 0
for i, j in all_cells(grid):
    for k in range(1, min(m - i, n - j) + 1):
        cells = square(grid, i, j, k)
        if all(c == grid[i][j] for c in cells):
            count += 1
```

TIME	SPACE
O(m * n * min(m, n)^3)	O(1)

WHY IT IS SLOW

The same cells are rechecked for every size: O(m * n * min(m, n)^3). A table of the largest same-colour square ending at each cell, summed over all cells, is O(m * n).

OPTIMAL SOLUTION · DP: side of the largest square ending at each cell, summed

TIME	SPACE
O(m * n)	O(n) with a rolling row

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Only the largest square (LeetCode 221).

Keep the maximum of the same dp table instead of the sum.

FOLLOW-UP 2 Allow at most one different cell inside a square.

The simple min-of-three recurrence no longer works. Use 2D prefix counts per colour and test each (corner, size) with binary search on the size, or DP with a second layer 'one defect used'.

FOLLOW-UP 3 Count only squares of colour c, or only side >= 2.

Filter while summing: add dp only for cells of colour c, or add max(0, dp - 1) for sizes at least 2.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
def square_table(grid):
    # side[i][j]: the biggest same-colour square with its
    # bottom-right corner at (i, j)
    prev, rows = [0] * len(grid[0]), []
    for i, row in enumerate(grid):
        cur = [1] * len(row)
        for j, ch in enumerate(row):
            # the up, left and up-left cells must match
            # too
            if i and j and ch == grid[i - 1][j] \
                    and ch == grid[i][j - 1] \
                    and ch == grid[i - 1][j - 1]:
                cur[j] = 1 + min(prev[j], cur[j - 1],
                                 prev[j - 1])
        rows.append(cur)
        prev = cur
    return rows


# BASE QUESTION (optimal): DP: side of the largest square
# ending at each cell, summed
def count_same_color_squares(grid):
    # each cell adds one square for every size up to its
    # side
    return sum(sum(row) for row in square_table(grid))


# FOLLOW-UP 1: Only the largest square (LeetCode 221).
def largest_square(grid):
    # LeetCode 221 style: only the biggest side
    return max(max(row) for row in square_table(grid))


# FOLLOW-UP 3: Count only squares of colour c, or only
# side >= 2.
def count_of_color(grid, color, min_side=1):
    # squares of one colour, and/or of side at least
    # min_side
    total = 0
    for i, row in enumerate(square_table(grid)):
        for j, side in enumerate(row):
            if grid[i][j] == color:
                # sides min_side .. side are counted
                total += max(0, side - min_side + 1)
    return total
```

```python
if __name__ == "__main__":
    g = ["aab", "aab", "bbb"]
    # singles 9, plus the 2 x 2 block of a's
    assert count_same_color_squares(g) == 10
    assert largest_square(g) == 2
    assert count_of_color(g, "a") == 5
    assert count_of_color(g, "b") == 5
    full = ["zzz", "zzz", "zzz"]
    # 9 + 4 + 1 squares
    assert count_same_color_squares(full) == 14
    assert count_of_color(full, "z", 2) == 5
    assert count_of_color(full, "q") == 0
    assert count_same_color_squares(["a"]) == 1
```

FUNCTION AND TEST CASES

Signature

```
def solution(grid: list[str]) -> int:
SAMPLE INPUT
([])
```

Test cases

Input	Expected
`([])`	`0`
`(["aab", "aab", "bbb"])`	`10`

ALSO REPORTED · 1 more

Count Same-Color Squares in Matrix | 1Point3Acres | onsite-coding | Low

https://www.1point3acres.com/interview/problems/company/google/count-same-color-squares

Variant reported in both intern VO and an additional NG round. Common bug: assuming all four corners equal is sufficient — need all three neighbors (top, left, top-left) to match the current cell.

Preparation: Write the all-1-squares DP from memory in under 8 min.
Generalize to multi-color in <2 min — only the equality check changes.

Medium (48)

MEDIUM | PracHub | Technical Screen | 65 of 165

Can board states be transformed?

POSTED 2026-04-01 | 192 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 40.3 | 30 DAYS 0 | PRIORITY 92/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 777 Swap Adjacent in LR String (inferred from overview)

Posted on PracHub: 2026-04-01 (updated 2026-04-19)

Original:
https://prachub.com/coding-questions/can-board-states-be-transformed

QUESTION

Overview: This question evaluates reasoning about constrained piece movement, string transformation, and invariant-based correctness in the Coding & Algorithms domain, testing skills in string manipulation and combinatorial reasoning while examining both conceptual properties and practical algorithmic implementation.

APPROACH

Invariants: the sequence of non-empty pieces must match; each L can only move left and each R only right (compare positions with two pointers).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what the pieces are, which direction each may move, whether pieces may jump over each other, and what the empty cell is called.

BRUTE FORCE TO SAY OUT LOUD

BFS over all reachable board strings. Exponential but clear.

OPTIMAL IDEA

Invariants: pieces never cross, so the order of the non-empty pieces must be identical in both strings; an L can only move left, so in the start its index must be at least its index in the target; an R can only move right, so its start index must be at most its target index. Walk two pointers over the non-empty cells and check those conditions. O(n).

DRY-RUN THESE CASES

Equal strings. A different piece order. An L that would have to move right. Same pieces but different counts.

LIKELY FOLLOW-UPS

Add walls that cannot be passed or crossed, or ask for the minimum number of moves.

PITFALLS

Comparing counts only and not order. Skipping the empty cells incorrectly in the two-pointer loop.

HOW TO THINK ABOUT IT

Think invariants, not search. Pieces cannot jump each other, so the sequence of L and R letters (ignoring blanks) cannot change. Within that, an L can only go left and an R only right, so compare the position of each piece in the start and in the target. That reduces exponential BFS to one pass with two pointers.

Basis: LeetCode 777, Swap Adjacent in LR String: 'X' is an empty cell, 'L' only moves left, 'R' only moves right, pieces never pass each other.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def can_transform(start, target):
    seen, queue = {start}, deque([start])
    while queue:
        board = queue.popleft()
        if board == target:
            return True
        for nxt in legal_moves(board):
            if nxt not in seen:  # XL->LX, RX->XR
                seen.add(nxt)
                queue.append(nxt)
    return False
```

BRUTE FORCE

TIME	SPACE
exponential in the length	exponential

WHY IT IS SLOW

The number of reachable boards grows exponentially. Pieces never cross, so compare the sequence of L and R pieces and check that no L moved right and no R moved left, in O(n).

OPTIMAL SOLUTION · Two pointers over the pieces

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the minimum number of moves.

Because pieces never interact beyond keeping their order, each piece moves independently from its start index to its target index, so the minimum is the sum of the absolute index differences when the transformation is possible.

FOLLOW-UP 2 Add walls that cannot be crossed (next question).

A wall is just another piece that never moves: it stays in the sequence of non-blank symbols and must keep the same index in both strings. The same pointer walk handles it.

FOLLOW-UP 3 Pieces can move one step per round and several move at once.

The count of rounds is the maximum over pieces of their distance, if pieces never block each other; with blocking you simulate rounds or use the per-piece arrival times with the ordering constraint.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def pieces(board):
    # the non-blank symbols with their positions
    return [(ch, i) for i, ch in enumerate(board)
            if ch != "X"]


# BASE QUESTION (optimal): Two pointers over the pieces
def can_transform(start, end):
    # L moves left, R moves right, X is blank. Pieces
    # never pass
    # each other, so the order of the non-X symbols is
    # fixed;
    # a '#' is a wall: it never moves and no piece crosses
    # it.
    if len(start) != len(end):
        return False
    a, b = pieces(start), pieces(end)
```

```
    if len(a) != len(b):
        return False
    for (c1, i), (c2, j) in zip(a, b):
        if c1 != c2:
            return False
        # an L may only end up further left, an R further
        # right
        if c1 == "L" and i < j:
            return False
        if c1 == "R" and i > j:
            return False
        # a wall must stay exactly where it is
        if c1 == "#" and i != j:
            return False
    return True


# FOLLOW-UP 1: Return the minimum number of moves.
def min_moves(start, end):
    # every piece moves on its own, one cell per move
    if not can_transform(start, end):
        return None
    a, b = pieces(start), pieces(end)
    return sum(abs(i - j) for (_, i), (_, j) in zip(a, b))


# FOLLOW-UP 3: Pieces can move one step per round and
# several move at once.
```

```
def rounds_needed(start, end):
    # if all pieces move at once and never block each
    # other,
    # the number of rounds is the longest single trip
    if not can_transform(start, end):
        return None
    a, b = pieces(start), pieces(end)
    trips = [abs(i - j) for (_, i), (_, j) in zip(a, b)]
    return max(trips, default=0)


if __name__ == "__main__":
    assert can_transform("RXXLRXRXL", "XRLXXRRLX")
    assert not can_transform("X", "L")
    assert can_transform("XXXL", "XXLX")
    # R can not move left, L can not move right
    assert not can_transform("XR", "RX")
    assert not can_transform("LX", "XL")
    # pieces keep their order: RL can not become LR
    assert not can_transform("RL", "LR")
    assert min_moves("RXXLRXRXL", "XRLXXRRLX") == 4
    assert min_moves("RXX", "XXR") == 2
    assert min_moves("RX", "XR") == 1
    assert min_moves("LL", "RR") is None
    # a wall splits the board: R can not jump over it
    assert can_transform("R#X", "R#X")
    assert not can_transform("R#X", "X#R")
    assert rounds_needed("RXX", "XXR") == 2
    assert rounds_needed("LL", "RR") is None
```

FUNCTION AND TEST CASES

Signature

```
def solution(start: str, target: str) -> bool:
```

Sample call

```
solution("R_L|__L", "_RL|L__")
```

Test cases

Input	Expected
`("R_L|__L", "_RL|L__")`	`True`
`("L_|R", "L|_R")`	`False`

MEDIUM | PracHub | Technical Screen | 66 of 165

Check if all substrings are dictionary words

POSTED 2026-03-11 | 213 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 43.5 | 30 DAYS 0 | PRIORITY 81/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #139 Word Break

LeetCode match: No direct match; related LC 139 Word Break

Posted on PracHub: 2026-03-11 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/check-if-all-substrings-are-dictionary-words

QUESTION

You are given a string **`s`** (letters only) and access to an English dictionary **`dict`** (a set of valid words). Return **`true`** if **every contiguous substring** of **`s`** with length **`>= 3`** is a valid dictionary word (i.e., for all **`i, j`** with **`0 <= i <= j < n`** and **`j - i + 1 >= 3`**, **`s[i..j] in dict`**). Otherwise return **`false`**. Clarifications:

- Substring means **contiguous**.
- You may assume dictionary lookups are available (e.g., **`dict.contains(word)`**), or you can preprocess the dictionary. Example:
- If **`s = "cats"`**, you must check **`"cat"`**, **`"ats"`**, and **`"cats"`** (and any other substrings of length >= 3).

APPROACH

Enumerate all substrings of length >= 3 and look each up in the set; exit on the first failure. Prune: if any length-3 window fails return false immediately. O(n^2) lookups.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the dictionary access (a set or a trie), the maximum length of s, and whether case matters. A string of length n has about n^2 / 2 substrings of length at least 3, and each is a separate requirement.

BRUTE FORCE TO SAY OUT LOUD

Enumerate every substring of length at least 3 and look it up. O(n^2) lookups, each costing O(length) to hash, so O(n^3) characters.

INTERVIEW-DAY PLAN

OPTIMAL IDEA

Exit on the first failure; checking all length-3 windows first prunes most inputs. To avoid the length factor, walk a trie: for each start i descend the trie along s[i:], and at every depth of at least 3 require the end-of-word flag; if the path breaks, return false. That is O(n^2) node steps in total.

DRY-RUN THESE CASES

A string shorter than 3 (true vacuously), cats (needs cat, ats, cats), a failure on the first window, a failure only on the longest substring.

LIKELY FOLLOW-UPS

Anagram version (next question), or return the first failing substring.

PITFALLS

Checking only the whole string. Treating a string shorter than 3 as false.

HOW TO THINK ABOUT IT

Every substring is a separate requirement, so no clever skipping exists: you must test about n^2 / 2 substrings. What you can improve is the cost per test and the early exit. A trie lets you extend a start position one character at a time without rehashing the whole substring, and the first failure ends everything.

Basis: Written; every contiguous substring of length >= 3 must be a dictionary word. The dictionary is a set (optionally preprocessed into a trie).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s, dictionary):
    for i in range(len(s)):
        for j in range(i + 3, len(s) + 1):
            if s[i:j] not in dictionary:
                return False
    return True
```

TIME	SPACE
O(n^2)	**O(1)**
lookups, O(n^3) characters hashed	extra

WHY IT IS SLOW

About n^2 / 2 lookups and each hashes a whole substring, O(n^3) characters. Walking a trie from each start, one character at a time, is O(n^2) with no hashing of long strings.

OPTIMAL SOLUTION · Walk a trie from each start position

TIME	SPACE
O(n^2)	**O(dictionary size)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the first failing substring.

Same loops, but return the substring instead of False, which is what a user wants to see. Check the shorter ones first so the report is the smallest counterexample.

FOLLOW-UP 2 The string is very long.

The check is inherently quadratic in the number of substrings; any substring that fails ends the search, so cheap necessary checks first help: every length-3 window must be a word (O(n) lookups), then length 4, and so on.

FOLLOW-UP 3 The dictionary is huge and sharded.

Batch the lookups by length (a set per length) or use a Bloom filter in front of the real dictionary to reject most misses cheaply. **Cost:** still O(n^2) lookups, spread over shards (each lookup O(L)); a Bloom filter in front removes most remote calls.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# FOLLOW-UP 1: Return the first failing substring.
def first_failing(s, words, min_len=3):
    # the SHORTEST substring (length >= min_len) that is
    # not a
    # word, or None. Short lengths first gives the
    # smallest
    # counterexample, and cheap checks run before
    # expensive ones.
    words = set(words)
    longest = max(map(len, words), default=0)
    for length in range(min_len, len(s) + 1):
        # longer than every word: the first window already
        # fails
        if length > longest:
            return s[:length]
        for i in range(len(s) - length + 1):
            piece = s[i:i + length]
            if piece not in words:
                return piece
    return None


# BASE QUESTION (optimal): Walk a trie from each start
# position
def all_substrings_words(s, words, min_len=3):
    return first_failing(s, words, min_len) is None


# SAME CHECK with a trie
class Trie:
    """The same check with a trie."""

    def __init__(self, words):
        self.root = {}
        for w in words:
            node = self.root
            for ch in w:
                node = node.setdefault(ch, {})
            node["$"] = True

    def all_substrings(self, s, min_len=3):
```

```
        for i in range(len(s)):
            node = self.root
            for depth, ch in enumerate(s[i:], 1):
                node = node.get(ch)
```

```
                if node is None:
                    # no word has this prefix: fails if
                    # the
                    # substring is long enough to count
                    return len(s) - i < min_len
                if depth >= min_len and "$" not in node:
                    return False
        return True


if __name__ == "__main__":
    words = {"aaa", "aaaa", "aaaaa"}
    assert all_substrings_words("aaaaa", words)
    assert Trie(words).all_substrings("aaaaa")
    # "aab" is a window that is not a word
    assert first_failing("aaab", words) == "aab"
    assert first_failing("aab", words) == "aab"
    assert not all_substrings_words("aab", words)
    assert not Trie(words).all_substrings("aab")
    # shorter than 3 letters: nothing to check
    assert all_substrings_words("ab", set())
    assert Trie([]).all_substrings("ab")
    # longer than every word: fails immediately
    assert first_failing("aaaaaa", words) == "aaaaaa"
```

FUNCTION AND TEST CASES

Signature

```
def solution(s: str, dictionary: list[str]) -> bool:
```

Sample call

```
solution('cat', ['cat'])
```

Test cases

Input	Expected
`('cat', ['cat'])`	`True`
`('cats', ['cat', 'cas', 'cts', 'ats', 'cats'])`	`True`

MEDIUM | PracHub | Technical Screen | 67 of 165

★ TOP 75: rank 22 in the Medium and Hard priority list

★ Check if all substrings are anagrams of words

POSTED 2026-03-11 | 213 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 57.7 | 30 DAYS 51.4 | PRIORITY 15/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #49 Group Anagrams

LeetCode match: No direct match; related LC 49 Group Anagrams

ABOUT THIS QUESTION

Posted on PracHub: 2026-03-11 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/check-if-all-substrings-are-anagrams-of-words

QUESTION

You are given a string **`s`** (letters only) and access to an English dictionary **`dict`** (a set of valid words). Return **`true`** if **every contiguous substring** of **`s`** with length **`>= 3`** can be **rearranged (anagrammed)** into a valid dictionary word. Formally, for every substring **`t = s[i..j]`** with **`|t| >= 3`**, there exists some word **`w in dict`** such that **`w`** is a permutation of **`t`** (same multiset of characters). Otherwise return **`false`**. Clarifications:

- Substring means **contiguous**. - “Can be rearranged into a word” means the substring and the dictionary word have exactly the same character counts. Example:
- If **`t = "act"`**, it passes if the dictionary contains any of **`{ "act", "cat", "tac" }`**.

APPROACH

Precompute sorted-letter (or count-vector) signatures of dictionary words into a set; for each substring of length >= 3 compute its signature and look it up.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether every substring of length at least 3 must be rearrangeable into some dictionary word, the alphabet (letters only), and the dictionary size and word lengths.

BRUTE FORCE TO SAY OUT LOUD

For every substring, compare against every dictionary word by sorted letters. Very slow.

OPTIMAL IDEA

Preprocess the dictionary into a set of signatures, where a signature is the sorted letters or a 26-count tuple, and also record the set of word lengths present. For each start i extend j one letter at a time, updating a count vector incrementally; once the length is at least 3, look up its signature (skip lengths that no word has) and return false at the first miss. O(n^2 * 26) time.

DRY-RUN THESE CASES

A string shorter than 3, a failing length that has no dictionary words, a long repeated letter, all substrings valid.

LIKELY FOLLOW-UPS

Return the failing substring, or a larger alphabet (use a hash of counts).

PITFALLS

Sorting each substring from scratch, which costs an extra log factor. Forgetting that a signature must match the length too (a count tuple already does).

HOW TO THINK ABOUT IT

Anagrams share a signature: the multiset of letters (a sorted string or a 26-count tuple). So turn the dictionary into a set of signatures once, and test each substring by its signature. Extending a substring by one letter changes its count vector in O(1), so you do not rebuild the signature from scratch.

Basis: Written; every substring of length >= 3 must be a permutation of some dictionary word (compare Group Anagrams, LeetCode 49).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s, words):
    for i in range(len(s)):
        for j in range(i + 3, len(s) + 1):
            key = sorted(s[i:j])
            match = [w for w in words
                     if key == sorted(w)]
            if not match:
                return False
    return True
```

TIME	SPACE
O(n^2 * W * L log L)	O(1) extra

WHY IT IS SLOW

Each substring is compared with every word and sorted again: O(n^2 * W * L log L). A set of word signatures, with the substring's count vector updated incrementally, makes each check O(alphabet).

OPTIMAL SOLUTION · Set of signatures, incremental count vectors

TIME	SPACE
O(n^2 * A) for alphabet size A	O(dictionary size)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 A bigger alphabet or Unicode.

Replace the fixed array by a Counter and use a frozen tuple of sorted (letter, count) pairs, or a hash of the counts, as the signature. **Cost:** O(n^2 * distinct letters in a substring) with a Counter signature instead of a fixed array.

FOLLOW-UP 2 Only substrings of lengths that exist in the dictionary need checking.

Record the set of word lengths; a substring whose length is not in that set can never match, so you can return False the first time such a length is reached (assuming all substrings of length >= 3 up to n must match).

FOLLOW-UP 3 Subsets of the letters (any sub-multiset of a word) instead of a full permutation.

Then the test is containment of count vectors, which is a subset-of-multiset query; use a sorted signature trie or precompute all sub-multisets for short words.

FOLLOW-UP 4 Report the first failing substring instead of True or False.

Test substrings by length (shortest first) so the report is a smallest counterexample; the signature set makes each test one lookup after sorting the substring's letters.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter

ALPHABET = "abcdefghijklmnopqrstuvwxyz"


def signature(text):
    # the letters in sorted order: equal for anagrams
    return "".join(sorted(text))


# BASE QUESTION (optimal): Set of signatures, incremental
# count vectors
def all_anagram_words(s, words, min_len=3):
    # every substring needs a dictionary word with the
    # same
    # letters. Count vectors are updated as the window
    # grows.
    index = {c: i for i, c in enumerate(ALPHABET)}
    sigs = set()
    for w in words:
        v = [0] * len(ALPHABET)
        for ch in w:
            v[index[ch]] += 1
        sigs.add(tuple(v))
    for i in range(len(s)):
        v = [0] * len(ALPHABET)
        for j in range(i, len(s)):
            v[index[s[j]]] += 1
            long_enough = j - i + 1 >= min_len
            if long_enough and tuple(v) not in sigs:
                return False
    return True


# FOLLOW-UP 4: Report the first failing substring instead
# of True or False.
def first_failing(s, words, min_len=3):
    # smallest counterexample: lengths from short to long
    sigs = {signature(w) for w in words}
    lengths = {len(w) for w in words}
    for length in range(min_len, len(s) + 1):
        # no word has this length: the first window fails
        if length not in lengths:
            return s[:length]
        for i in range(len(s) - length + 1):
```

```
            piece = s[i:i + length]
            if signature(piece) not in sigs:
                return piece
```

```
    return None


# FOLLOW-UP 1: A bigger alphabet or Unicode.
def all_anagram_words_any_alphabet(s, words, min_len=3):
    # Unicode or a big alphabet: a frozen Counter as
    # signature
    sigs = {frozenset(Counter(w).items()) for w in words}
    for i in range(len(s)):
        count = Counter()
        for j in range(i, len(s)):
            count[s[j]] += 1
            key = frozenset(count.items())
            if j - i + 1 >= min_len and key not in sigs:
                return False
    return True


if __name__ == "__main__":
    words = {"cat", "act", "tac", "tact", "cats"}
    assert all_anagram_words("cat", words)
    assert all_anagram_words("tca", words)
    assert not all_anagram_words("tcaz", words)
    assert all_anagram_words_any_alphabet("cat", words)
    assert first_failing("cat", words) is None
    # "catz" fails at length 3? "atz" is not an anagram
    assert first_failing("catz", words) == "atz"
    assert all_anagram_words("ab", set())
    assert first_failing("aaaa", {"aaa"}) == "aaaa"
```

FUNCTION AND TEST CASES

Signature

```
def solution(s: str, words: list[str]) -> bool:
```

Sample call

```
solution("act", ["cat", "dog"])
```

Test cases

Input	Expected
`("act", ["cat", "dog"])`	`True`
`("abca", ["cab", "abca", "zzz"])`	`True`

MEDIUM | PracHub | Technical Screen | 68 of 165

Determine if a 14-tile hand is winning

POSTED 2026-03-09 | 215 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 19.6 | 30 DAYS 0 | PRIORITY 148/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #659 Split Array into Consecutive Subsequences

LeetCode match: No direct match; related LC 659 Split Array into Consecutive Subsequences

Posted on PracHub: 2026-03-09 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/determine-if-a-14-tile-hand-is-winning

QUESTION

You are given an integer array **`tiles`** of length 14 representing a Mahjong-like hand. Each integer is a tile value from 1 to 9 (single suit). You may reorder the tiles. A hand is **winning** if it can be partitioned into:

- **1 pair**: two identical tiles, and - **4 melds** (each meld uses 3 tiles), where each meld is either: - a **triplet**: three identical tiles (e.g., 7,7,7), or - a **sequence**: three consecutive values (e.g., 2,3,4). Each tile can be used at most once. Return **`true`** if the hand is winning, otherwise return **`false`**. Assumptions/constraints:
- **`tiles.length == 14`**
- **`1 <= tiles[i] <= 9`**
- Each value can appear multiple times (as in a real tile set).

APPROACH

Count array of tiles 1..9; try each value as the pair, then backtrack: take the smallest remaining tile as a triplet or a run of three. Tiny search space.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether sequences are only consecutive in one suit (values 1 to 9), whether a tile can be used only once, and whether other special hands exist (assume not).

BRUTE FORCE TO SAY OUT LOUD

Try every permutation of the 14 tiles and test the grouping. Far too slow.

OPTIMAL IDEA

Keep a count array of tiles 1 to 9. Try each value that has at least two tiles as the pair, remove it, then backtrack on the remaining 12 tiles: take the smallest value that still has tiles and either remove a triplet of it or a run of three consecutive values starting at it; if neither is possible, fail. Always handling the smallest value makes the search small. Time is tiny for 14 tiles.

DRY-RUN THESE CASES

Four triplets and a pair, four runs and a pair, a hand with two possible groupings, a hand with a pair but impossible melds, all 14 tiles equal (invalid since each value has at most four copies).

LIKELY FOLLOW-UPS

More suits, seven pairs, or all possible winning tiles for a 13-tile hand.

PITFALLS

Greedy without backtracking: a run versus a triplet choice can matter. Forgetting to restore counts.

HOW TO THINK ABOUT IT

Work with counts per value (at most nine numbers), not with the tile list. Try every value as the pair, then handle the lowest remaining value: it must belong to a triplet or to a sequence starting at it (nothing smaller is left to pair with it). Always processing the smallest value makes the search tiny and avoids trying the same grouping in different orders.

Basis: Written; a small exhaustive search like the Mahjong 'standard hand' check. Rule: 14 tiles of one suit with values 1..9 split into one pair and four melds, each meld a triplet (x, x, x) or a sequence (x, x + 1, x + 2).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def is_win(counts):
    for v in range(1, 10):
        if counts[v] >= 2:
            counts[v] -= 2  # the pair
            ok = remove_melds(counts)
            counts[v] += 2
            if ok:
                return True
    return False
def remove_melds(counts):
    v = first_value_with_tiles(counts)
    if v is None:
        return True
    for meld in (triple(v), run(v)):
        if can_take(counts, meld):
            take(counts, meld)
            ok = remove_melds(counts)
            give_back(counts, meld)
            if ok:
                return True
    return False
```

TIME	SPACE
exponential but small for... exponential but small for 14 tiles	**O(depth)**

WHY IT IS SLOW

It tries the same groupings in many different orders (still tiny for 14 tiles). Always grouping the smallest remaining tile tries each grouping once.

OPTIMAL SOLUTION · Counts, try each pair, then always group the smallest remaining tile

TIME	SPACE
O(9 * small branching) = constant for 14 tiles	**O(1)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Which tile would complete a 13-tile hand?

Try each of the nine values as the 14th tile and run the same check: 9 checks of a tiny search. That is how a player finds the tiles they are waiting for.

FOLLOW-UP 2 More suits or special hands (seven pairs).

Run the single-suit check on each suit separately (melds never cross suits) after splitting the hand; seven pairs is a separate one-line count check (seven values with count 2).

FOLLOW-UP 3 Why is the 'smallest remaining value' rule enough?

The smallest remaining value cannot be the middle or end of a sequence (the smaller values are gone), so it must be in a triplet or the start of a sequence. Trying those two options covers every legal grouping exactly once.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


def melds_ok(cnt, v=1):
    # can the tiles in cnt (value -> count) form only
    # melds?
    while v <= 9 and cnt[v] == 0:
        v += 1
    if v > 9:
        return True
    # the smallest tile is either in a triplet ...
    if cnt[v] >= 3:
        cnt[v] -= 3
        ok = melds_ok(cnt, v)
        cnt[v] += 3
        if ok:
            return True
    # ... or the start of a run v, v + 1, v + 2
    if v <= 7 and cnt[v + 1] and cnt[v + 2]:
        for t in (v, v + 1, v + 2):
            cnt[t] -= 1
        ok = melds_ok(cnt, v)
        for t in (v, v + 1, v + 2):
            cnt[t] += 1
        return ok
    return False


# BASE QUESTION (optimal): Counts, try each pair, then
# always group the smallest ...
def is_winning_hand(tiles):
    # one pair plus four melds, single suit, values 1..9
    cnt = Counter({v: 0 for v in range(1, 12)})
    for t in tiles:
        cnt[t] += 1
    for pair in range(1, 10):
        if cnt[pair] >= 2:
            cnt[pair] -= 2
            ok = melds_ok(cnt)
            cnt[pair] += 2
            if ok:
```

```
                return True
    return False
```

```
# FOLLOW-UP 1: Which tile would complete a 13-tile hand?
def waiting_tiles(tiles13):
    # follow-up: which 14th tile completes the hand?
    return [t for t in range(1, 10)
            if is_winning_hand(tiles13 + [t])]


# FOLLOW-UP 2: More suits or special hands (seven pairs).
def is_seven_pairs(tiles):
    # a special hand: seven different pairs
    counts = Counter(tiles)
    pairs = all(c == 2 for c in counts.values())
    return len(tiles) == 14 and pairs


# FOLLOW-UP 2: More suits or special hands (seven pairs).
def is_winning_multi(hand):
    # several suits: hand is a list of (suit, value);
    # melds
    # never cross suits, and exactly one suit holds the
    # pair
    suits = {}
    for suit, v in hand:
        suits.setdefault(suit, []).append(v)
    pair_suits = [s for s in suits
                  if len(suits[s]) % 3 == 2]
    if len(pair_suits) != 1:
        return False
    for s, vs in suits.items():
        if s == pair_suits[0]:
            if not is_winning_hand_with_len(vs):
                return False
        elif len(vs) % 3 or not melds_ok(count_of(vs)):
            return False
    return True


def count_of(values):
    cnt = Counter({v: 0 for v in range(1, 12)})
    for v in values:
        cnt[v] += 1
    return cnt


def is_winning_hand_with_len(values):
```

```
    cnt = count_of(values)
    for pair in range(1, 10):
        if cnt[pair] >= 2:
            cnt[pair] -= 2
            ok = melds_ok(cnt)
            cnt[pair] += 2
            if ok:
                return True
    return False


if __name__ == "__main__":
    win = [1, 1, 1, 2, 3, 4, 5, 5, 5, 6, 7, 8, 9, 9]
    assert is_winning_hand(win)
    # 3 and 6 are missing, so the runs cannot be formed
    lose = [1, 2, 4, 5, 7, 8, 1, 2, 4, 5, 7, 8, 9, 9]
    assert not is_winning_hand(lose)
    # thirteen tiles waiting for a 9 (or a 6)
    wait = [1, 1, 1, 2, 3, 4, 5, 5, 5, 6, 7, 8, 9]
    assert 9 in waiting_tiles(wait)
    assert is_seven_pairs([1, 1, 2, 2, 3, 3, 4, 4, 5, 5,
                           6, 6, 7, 7])
    hand = [("m", v) for v in (1, 1, 1, 2, 3)] + [
```

```
        ("p", v) for v in (4, 5, 6, 7, 7, 7)] + [
        ("s", v) for v in (2, 2, 2)]
    assert is_winning_multi(hand)
```

FUNCTION AND TEST CASES

Signature

```
def solution(tiles: list[int]) -> bool:
```

Sample call

```
solution([1,1,1,2,3,4,2,3,4,5,6,7,9,9])
```

Test cases

Input	Expected
`([1,1,1,2,3,4,2,3,4,5,6,7,9,9],)`	`True`
`([2,2,2,3,3,3,4,4,4,5,5,5,9,9],)`	`True`

ALSO REPORTED · 1 more

Mahjong Winning Hand Detection (14 Tiles) | 1Point3Acres | onsite-coding | asked 2026-07-20 | Low

https://www.1point3acres.com/interview/problems/company/google/mahjong-winning-hand-check

Clarify the rules — the prompt is intentionally sparse. Confirm: are honor tiles (winds/dragons) included? Do flowers count? Multi-suit?
Greedy + backtracking is the standard approach:
Try every possible pair (tile, tile); remove the pair.
On the remaining 12 tiles, repeatedly take the smallest remaining tile and try to form a triplet of it or a run starting at it; backtrack on failure.
For 14 tiles this runs in well under 1 ms; the interviewer cares more about the case analysis and clean recursion than micro-optimizations.
The same algorithm extends to special hands (seven pairs / ????) if the interviewer adds them as a follow-up.

Preparation: Practice writing the backtracking decomposer for tiles / counters; the canonical "expression add operators" recursion trains the same backtracking skeleton.
Have a tile-frequency-map mental model — sorting is the alternative but harder to reason about for runs across suits.
Pre-plan for the inevitable rules clarification: pull out at least 3 questions before coding.

MEDIUM | IN APP LC 208 | PracHub | Technical Screen | 69 of 165

Return dictionary words matching a prefix

POSTED 2026-03-09 | 215 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 36 | 30 DAYS 0 | PRIORITY 105/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #208 Implement Trie (Prefix Tree)

LeetCode match: LC 208 Implement Trie (Prefix Tree)

Posted on PracHub: 2026-03-09 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/return-dictionary-words-matching-a-prefix

QUESTION

You are given a list of strings **`words`** (a dictionary) and a string **`prefix`**. Return all words in **`words`** that start with **`prefix`**. Clarifications/constraints:

- Matching is case-sensitive.
- If no words match, return an empty list.
- If **`words`** contains duplicates, include duplicates in the output.
- You may return the result in any order unless the interviewer asks for a specific ordering (e.g., lexicographic).

APPROACH

Sort once and binary search the prefix range, or build a trie for repeated queries. O(log n + m) per query after preprocessing.

HOW TO THINK ABOUT IT

If the dictionary is sorted, all words with a prefix form one contiguous block, and its edges are found with binary search: the first word >= prefix, and the first word that is >= prefix with its last character incremented. For many queries on a static list this beats a trie in memory.

Basis: Search Suggestions System (LeetCode 1268) and prefix queries on a sorted list.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(words, prefix):
    found = [w for w in words
             if w.startswith(prefix)]
    return found
```

TIME	SPACE
O(W * L) per query	O(m)

BRUTE FORCE

WHY IT IS SLOW

Each query scans the whole dictionary, O(W * L). With the words sorted, binary search finds the block of matches directly.

OPTIMAL SOLUTION · Sort once, binary search the range

TIME	SPACE
O(log W + m) per query after O(W log W) sorting	O(W)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Only the first K matches (autocomplete).

Stop the forward walk after K words, as the limit parameter does; with the sorted list the first K in alphabetical order are already the first K in the block.

FOLLOW-UP 2 Words are added while queries run.

Keep the list sorted with bisect.insort (O(n) per insert, fast in practice) or use a balanced tree; a trie handles inserts in O(L).

FOLLOW-UP 3 Case-insensitive matching.

Store a casefolded sort key next to each word (a tuple (key, word)) and search on the key; do not lowercase the displayed word.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left, bisect_right, insort


# BASE QUESTION (optimal): Sort once, binary search the
# range
# FOLLOW-UP 1, 2: Only the first K matches (autocomplete).
class PrefixIndex:
    def __init__(self, words):
        # a sorted copy: all words with a prefix sit
        # together
        self.words = sorted(words)

    # FOLLOW-UP 1: limit= returns only the first K
    def matches(self, prefix, limit=None):
        # first possible position, then walk while it
        # matches
        lo = bisect_left(self.words, prefix)
        # one past the last word that starts with the
        # prefix
        hi = bisect_right(self.words, prefix + "")
        found = self.words[lo:hi]
        return found if limit is None else found[:limit]

    # FOLLOW-UP 2: words added while queries run
    def add(self, word):
        # words can arrive while queries run: keep it
```

```
        # sorted
        insort(self.words, word)


# FOLLOW-UP 3: Case-insensitive matching.
class CaseInsensitiveIndex:
    """Ignore case, but show the original words."""

    def __init__(self, words):
        keyed = ((w.casefold(), w) for w in words)
        self.items = sorted(keyed)

    def matches(self, prefix):
        key = prefix.casefold()
        lo = bisect_left(self.items, (key,))
        out = []
        while lo < len(self.items) and \
                self.items[lo][0].startswith(key):
            out.append(self.items[lo][1])
            lo += 1
        return out


# SIMPLE SCAN (say it first)
def matches_scan(words, prefix):
    # the simple O(n * L) answer, in the original order
    return [w for w in words if w.startswith(prefix)]


if __name__ == "__main__":
    words = ["apple", "app", "apricot", "Apple", "banana",
             "app"]
    idx = PrefixIndex(words)
    # duplicates are kept; matching is case sensitive
    assert idx.matches("ap") == ["app", "app", "apple",
                                 "apricot"]
    assert idx.matches("x") == []
    assert idx.matches("") == sorted(words)
    assert idx.matches("ap", limit=2) == ["app", "app"]
    scan = sorted(matches_scan(words, "ap"))
    assert scan == idx.matches("ap")
    idx.add("apex")
    assert "apex" in idx.matches("ap")
    ci = CaseInsensitiveIndex(words)
    got = ci.matches("APP")
    assert got == ["app", "app", "Apple", "apple"]
```

FUNCTION AND TEST CASES

Signature

```
def solution(words: list[str], prefix: str) -> list[str]:
```

Sample call

```
solution(['apple', 'app', 'banana', 'apply'], 'app')
```

Test cases

Input	Expected
`(['apple', 'app', 'banana', 'apply'], 'app')`	`['apple', 'app', 'apply']`
`(['Cat', 'car', 'Cart', 'dog'], 'Ca')`	`['Cat', 'Cart']`

MEDIUM | PracHub | Technical Screen | 70 of 165

Solve several coding interview problems

POSTED 2026-03-04 | 220 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 38.3 | 30 DAYS 0 | PRIORITY 97/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #160 Intersection of Two Linked Lists

LeetCode match: No direct match (multi-part); related LC 415 Add Strings, LC 160 Intersection of Two Linked Lists (inferred from overview)

Posted on PracHub: 2026-03-04 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/solve-several-coding-interview-problems

QUESTION

Overview: This set of problems evaluates proficiency in string processing and combinatorial parsing, arbitrary-precision arithmetic using string representations, pointer/ancestor-chain intersection detection, and computational geometry for overlap counting, emphasizing algorithmic design, correctness, and performance.

APPROACH

Multiple small tasks: string parsing, big-number string arithmetic, ancestor-chain intersection (hash set or depth alignment), etc. Solve each independently.

INTERVIEW-DAY PLAN

CLARIFY FIRST

My copy lists four small tasks: string parsing with combinatorial counting, adding two big integers given as strings, finding where two ancestor chains intersect, and counting overlaps in a geometry setting. Confirm each task's exact input and output, because the overview is the only statement I have.

BRUTE FORCE TO SAY OUT LOUD

Do each directly: parse and count with recursion, add digit by digit with a carry, compare ancestor lists, and test every pair of shapes.

OPTIMAL IDEA

Big integers: walk both digit strings from the right with a carry and build the result (O(max(m, n))), as in LeetCode 415. Ancestor chains: put one chain in a set and walk the other, or align by depth and step both up until they meet, as in LeetCode 160; O(n) time, O(1) space for the aligned version. Overlap counting: a sweep line over start and end events, taking the running maximum or counting pairs depending on the question. String parsing and counting: define the state and use memoized recursion.

INTERVIEW-DAY PLAN

DRY-RUN THESE CASES

Big integers with different lengths, a final carry, leading zeros. Chains that never meet, meet at the head, are identical. Overlaps that touch at a boundary.

LIKELY FOLLOW-UPS

Subtraction or multiplication of big integers, lowest common ancestor with parent pointers, or counting overlapping rectangles.

PITFALLS

Starting to code before the four statements are confirmed. Forgetting the final carry.

HOW TO THINK ABOUT IT

A set of unrelated small tasks: split them, restate each contract, and solve the smallest one first. Big numbers: add digit by digit with a carry. Two chains that meet: walk both and switch to the other head at the end so the lengths cancel. Overlap counting: sort start and end events and keep a running count.

Basis: Three of the small tasks the overview lists, with the standard versions (my copy has only the overview): adding two big integers given as strings (LeetCode 415), intersection of two chains such as ancestors or linked lists (LeetCode 160), and the largest number of overlapping intervals.

BRUTE FORCE · Big numbers: convert to integers and add

BRUTE FORCE · PSEUDO-CODE

```
def add_strings(a, b):
    return str(int(a) + int(b))
```

TIME	SPACE
O(n^2) for the conversions	O(n)

WHY IT IS SLOW

Relies on arbitrary-precision integers (not in every language) and the string-to-integer conversions are quadratic for very long inputs. Adding digit by digit from the right with a carry is O(max length).

BRUTE FORCE · Chains that meet: store one chain in a set

BRUTE FORCE · PSEUDO-CODE

```
def intersection(a, b):
    seen = set()
    node = a
    while node:
        seen.add(node)
        node = node.parent
    node = b
    while node:
        if node in seen:
            return node
        node = node.parent
    return None
```

BRUTE FORCE · Chains that meet: store one chain in a set

TIME	SPACE
O(m + n)	O(m)

WHY IT IS SLOW

O(m + n) time but O(m) extra memory. Two pointers that switch to the other chain's head at the end meet at the shared node with O(1) memory.

BRUTE FORCE · Overlap: test every time point

BRUTE FORCE · PSEUDO-CODE

```
def max_overlap(intervals):
    lo = min(s for s, e in intervals)
    hi = max(e for s, e in intervals)
    best = 0
    for t in range(lo, hi):
        busy = 0
        for s, e in intervals:
            if s <= t < e:
                busy += 1
        best = max(best, busy)
    return best
```

TIME	SPACE
O(range * n)	O(1)

WHY IT IS SLOW

Depends on the length of the time range, O(range * n). Sorting start and end events and keeping a running count is O(n log n).

OPTIMAL SOLUTION · Big numbers: digit by digit from the right with a carry

TIME	SPACE
O(max(m, n))	O(max(m, n))

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Chains that meet: two pointers that switch heads at the end

TIME	SPACE
O(m + n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Overlap: sweep over sorted start and end events

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Ancestors in a tree with parent pointers, not a linked list.

The same two-pointer trick works on parent chains (LeetCode 1650); with depths known, lift the deeper node first and then move both up together.

FOLLOW-UP 2 Add two big numbers stored as linked lists.

If the lists store the least significant digit first, walk both together with the carry (LeetCode 2); if most significant first, reverse them or use stacks.

FOLLOW-UP 3 Count overlapping rectangles instead of intervals.

Sweep over x with a data structure over y (a segment tree with range add and max) to find the largest point depth in O(n log n); the pairwise count is O(n^2) unless you use a sweep with an interval tree.

FOLLOW-UP 4 Add two big numbers stored as linked lists (least significant digit first).

Walk both lists together with a carry and build the result list as you go; no reversal needed. O(max(m, n)) time. If the most significant digit comes first, reverse the lists or use stacks.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Big numbers: digit by digit
# from the right with a carry
def add_strings(a, b):
    # big numbers kept as digit strings, added from the
    # right
    i, j, carry, out = len(a) - 1, len(b) - 1, 0, []
    while i >= 0 or j >= 0 or carry:
        total = carry
        if i >= 0:
            total += int(a[i])
        if j >= 0:
            total += int(b[j])
        out.append(str(total % 10))
        carry = total // 10
        i, j = i - 1, j - 1
    return "".join(out[::-1])


class ListNode:
    def __init__(self, val=0, next=None):
        self.val, self.next = val, next


# BASE QUESTION (optimal): Big numbers: digit by digit
# from the right with a carry
def intersection(head_a, head_b):
    # two chains meeting: each pointer walks its chain and
    # then
    # the other one, so both walk the same total length
    a, b = head_a, head_b
    while a is not b:
        a = a.next if a else head_b
        b = b.next if b else head_a
    return a


# FOLLOW-UP 2, 4: Add two big numbers stored as linked
# lists.
def add_lists(a, b):
    # digits stored least significant first: add with a
    # carry
    dummy = tail = ListNode()
    carry = 0
    while a or b or carry:
        total = carry
        total += a.val if a else 0
        total += b.val if b else 0
        tail.next = ListNode(total % 10)
        tail = tail.next
        carry = total // 10
        a = a.next if a else None
        b = b.next if b else None
    return dummy.next


def to_list(node):
    out = []
    while node:
        out.append(node.val)
        node = node.next
    return out


# BASE QUESTION (optimal): Big numbers: digit by digit
# from the right with a carry
def overlap_depth(rects):
    # rects (x1, y1, x2, y2), half-open: the largest
    # number of
    # rectangles sharing one point. The best point can be
    # a
    # rectangle's lower-left corner, so test those.
    best = 0
    for x, y, _, _ in rects:
        inside = [r for r in rects if r[0] <= x < r[2]
                  and r[1] <= y < r[3]]
        best = max(best, len(inside))
    return best


# FOLLOW-UP 3: Count overlapping rectangles instead of
# intervals.
def overlapping_pairs(rects):
    # how many pairs of rectangles overlap?
    count = 0
    for i in range(len(rects)):
        for j in range(i + 1, len(rects)):
            a, b = rects[i], rects[j]
            if a[0] < b[2] and b[0] < a[2] \
                    and a[1] < b[3] and b[1] < a[3]:
                count += 1
    return count


if __name__ == "__main__":
    assert add_strings("999", "1") == "1000"
    assert add_strings("0", "0") == "0"
    big = add_strings("123456789123456789", "987654321")
    assert big == str(123456789123456789 + 987654321)
    shared = ListNode(8, ListNode(9))
    a = ListNode(1, ListNode(2, shared))
    b = ListNode(5, shared)
    assert intersection(a, b) is shared
    # no meeting: both end at None
    assert intersection(ListNode(1), ListNode(2)) is None
```

```
    # 342 + 465 = 807 with digits reversed
    x = ListNode(2, ListNode(4, ListNode(3)))
    y = ListNode(5, ListNode(6, ListNode(4)))
    assert to_list(add_lists(x, y)) == [7, 0, 8]
    rects = [(0, 0, 4, 4), (2, 2, 6, 6), (3, 3, 5, 5)]
    assert overlap_depth(rects) == 3
    assert overlapping_pairs(rects) == 3
    assert overlap_depth([]) == 0
```

FUNCTION AND TEST CASES

Signature

```
def solution(s) -> list[str]:
```

Sample call

```
solution('.-')
```

Test cases

Input	Expected
`('.-',)`	`['A', 'ET']`
`('...',)`	`['EEE', 'EI', 'IE', 'S']`

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 71 of 165

★ TOP 75: rank 73 in the Medium and Hard priority list

★ Design a restaurant waitlist system

POSTED 2026-03-01 | 223 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 57.3 | 30 DAYS 0 | PRIORITY 48/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #146 LRU Cache

LeetCode match: No direct match; related LC 146 LRU Cache (ordered map)

Posted on PracHub: 2026-03-01 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/design-a-restaurant-waitlist-system

QUESTION

You are implementing the waitlist system for a restaurant. Parties arrive over time, can cancel, and get seated when a table becomes available.

Rules

- Each party has a unique **`partyId`**, a **`name`**, and a **`size`** (number of people).
- Parties are seated in **arrival order**, but only if they **fit** the available table.
- When a table of capacity **c** becomes available, you must seat the **earliest-arrived** party whose **`size <= c`**.

QUESTION

- If no party fits, the table remains unused for that event.

Operations to support Design a

data structure / class that supports the following operations efficiently:

1. **`addParty(name, size) -> partyId`**
   - Adds a new party to the end of the waitlist and returns its id.
2. **`cancelParty(partyId) -> bool`**
   - Removes the party from the waitlist if present.
   - Returns **`true`** if removed, otherwise **`false`**.
3. **`seatTable(capacity) -> partyId or null`**
   - Finds and removes the earliest party with **`size <= capacity`**.
   - Returns that party's id, or **`null`** if nobody fits.
4. **`getPosition(partyId) -> int`**
   - Returns how many parties are ahead of this party in the current waitlist order (0-based).
   - If the party is not in the waitlist, return **`-1`**.

Constraints

- Up to **`2 * 10^5`** operations.
- Party size is a small positive integer (e.g., 1–20).
- Aim for better-than-linear time per operation (especially for **`seatTable`** and **`getPosition`**).

Example

(one possible interaction) - addParty("A", 4) -> id1 - addParty("B", 2) -> id2 - seatTable(2) -> id2 (B fits and is earliest among those that fit) - seatTable(4) -> id1

APPROACH

Hash map partyId -> party plus an ordered queue (linked list/OrderedDict) for arrival order; on a free table of size s, seat the earliest waiting party that fits; cancel is O(1) with lazy deletion.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the exact API (add party, cancel, seat when a table of capacity c frees up), what happens when no party fits, and whether a larger table may seat a smaller party (yes, if size <= c).

BRUTE FORCE TO SAY OUT LOUD

Keep a list in arrival order; on a table of capacity c scan from the front for the first party that fits. O(n) per seating, O(n) per cancel.

OPTIMAL IDEA

INTERVIEW-DAY PLAN

Keep id to party in a dict. For efficiency use a segment tree over arrival order storing the minimum party size in each range; the earliest party that fits is the leftmost position with size <= c, found by descending the tree in O(log n). Cancel and seat set that position's size to infinity. The simpler version uses an ordered dict plus lazy deletion and scans, O(n) in the worst case, which is fine to start with and to improve.

DRY-RUN THESE CASES

A table that fits nobody, a party that cancels before being seated, ties on arrival, a table that fits the second party but not the first, duplicate party id.

LIKELY FOLLOW-UPS

Large parties waiting too long (starvation), time-based expiry, or estimating wait time.

PITFALLS

Skipping a party that cancelled but is still in the queue. Choosing the best fit instead of the earliest fit.

HOW TO THINK ABOUT IT

'Earliest arrival whose size fits' is a query on an ordered sequence: find the leftmost position whose value is at most c. A scan does it in O(n); a segment tree that stores the minimum size over each range answers it in O(log n) by walking down to the leftmost child whose range minimum fits. Cancelling or seating simply sets that position to infinity.

Basis: Written design (compare LeetCode 146 for the ordered-map idea). API assumed (confirm it): add(id, name, size), cancel(id), seat(capacity) seats and returns the earliest-arrived waiting party whose size is at most the capacity, or None.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
parties = []  # in arrival order
def join(party):
    parties.append(party)
def seat(capacity):
    for party in parties:
        if party.size <= capacity:
            parties.remove(party)
            return party
    return None
def cancel(party_id):
    for party in parties:
        if party.id == party_id:
            parties.remove(party)
            return
```

TIME	SPACE
O(n) per seat and per cancel	O(n)

WHY IT IS SLOW

Both operations walk the list, O(n). A segment tree of the smallest size per range finds the leftmost party that fits in O(log n).

OPTIMAL SOLUTION · Segment tree of minimum size over arrival order

TIME	SPACE
O(log n) per operation	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Parties that wait too long should be seated first (starvation).

Add an aging rule: if the earliest party has waited longer than a threshold and a table of at least its size appears, seat it before anyone else. The segment tree can query 'leftmost size <= c' with c = the table, so order is preserved.

FOLLOW-UP 2 Seat the best-fitting party, not the earliest.

That is a different policy: keep sizes in a sorted structure of (size, arrival) and take the largest size at most the capacity (ties by arrival). A sorted container with bisect gives O(log n) lookups.

FOLLOW-UP 3 Estimate the waiting time of a party.

Track the arrival rate and typical table turnover per capacity; the estimate is the expected time until enough tables of at least that size free up, ahead of the party in the queue.

FOLLOW-UP 4 Seat the best-fitting party (the largest that fits), not the earliest.

Group waiting parties by size in queues (arrival order inside a size) and keep the sizes in a sorted list: the best fit for a table of capacity c is the largest size at most c, found with bisect, then the oldest party of that size. O(log distinct sizes) per seating. Verified against a linear scan.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_right, insort
from collections import defaultdict, deque

INF = float("inf")


# BASE QUESTION (optimal): Segment tree of minimum size
# over arrival order
class Waitlist:
    """Earliest party that fits: a segment tree of the
    smallest size over arrival slots."""

    def __init__(self, capacity=1024):
        self.cap = capacity
        self.tree = [INF] * (2 * capacity)
        self.count = 0
        self.slot, self.who = {}, {}
```

```
    def update(self, i, value):
        i += self.cap
        self.tree[i] = value
        while i > 1:
            i //= 2
            self.tree[i] = min(self.tree[2 * i],
                               self.tree[2 * i + 1])

    def add(self, party_id, name, size):
        self.slot[party_id] = self.count
        self.who[self.count] = party_id
        self.update(self.count, size)
        self.count += 1

    def cancel(self, party_id):
        i = self.slot.get(party_id)
        if i is None or self.tree[i + self.cap] == INF:
            return False
        self.update(i, INF)
        return True

    def seat(self, capacity):
        # no party small enough: nobody is seated
        if self.tree[1] > capacity:
            return None
        i = 1
        # go left whenever the left half holds a party
```

```
        # that fits
        while i < self.cap:
            left = self.tree[2 * i] <= capacity
            i = 2 * i if left else 2 * i + 1
        self.update(i - self.cap, INF)
        return self.who[i - self.cap]


# FOLLOW-UP 2, 4: Seat the best-fitting party, not the
# earliest.
class BestFit:
    """Policy B: the largest party that fits the table."""

    def __init__(self):
        # size -> parties of that size, oldest first
        self.queues = defaultdict(deque)
        self.sizes = []

    def add(self, party_id, size):
        if not self.queues[size]:
            insort(self.sizes, size)
        self.queues[size].append(party_id)

    def seat(self, capacity):
        k = bisect_right(self.sizes, capacity)
        if k == 0:
            return None
        size = self.sizes[k - 1]
        party = self.queues[size].popleft()
        if not self.queues[size]:
            self.sizes.pop(k - 1)
        return party


if __name__ == "__main__":
    w = Waitlist(8)
    w.add("p1", "Ann", 4)
    w.add("p2", "Bob", 2)
    w.add("p3", "Cy", 6)
    # a table for 3: the earliest party that fits is Bob
    assert w.seat(3) == "p2"
    # cancel Ann; a table for 6 now seats Cy
    assert w.cancel("p1") and not w.cancel("p1")
    assert w.seat(6) == "p3"
    assert w.seat(10) is None
```

```
    b = BestFit()
    parties = (("a", 2), ("b", 4), ("c", 4), ("d", 6))
    for pid, size in parties:
        b.add(pid, size)
    # a table for 5: the biggest fit is size 4, oldest
    # first
    assert b.seat(5) == "b"
    assert b.seat(5) == "c"
    assert b.seat(5) == "a"
    assert b.seat(1) is None
```

FUNCTION AND TEST CASES

Test cases

Input	Expected
`[('addParty', 'A', 4), ('addParty', 'B', 2), ('seatTable', 2), ('seatTable', 4)]`	`[1, 2, 2, 1]`
`[('addParty', 'A', 4), ('addParty', 'B', 2), ('addParty', 'C', 3), ('getPosition', 3), ('seatTable', 2), ('getPosition', 3), ('cancelParty', 1), ('getPosition', 3), ('cancelParty', 1), ('seatTable', 2), ('seatTable', 3), ('getPosition', 3)]`	`[1, 2, 3, 2, 2, 1, True, 0, False, None, 3, -1]`

ALSO REPORTED · 1 more

Restaurant Waitlist: join / delete / find_first_match | 1Point3Acres | onsite-coding | asked 2026-02-01 | Single report

https://www.1point3acres.com/interview/problems/company/google/waitlist-data-structure-with-table-size-match

A doubly-linked list + hashmap (LRU-style) gives O(1) join and delete; find_first_match then walks the list.
For faster find, bucket users by party size (e.g. one queue per size), and on find_first_match(t) scan sizes 1..t and pick the queue with the smallest head timestamp.
The interviewer cares more about clean class design + tradeoff discussion than a single optimal solution; mention what you'd cache to speed up repeated finds.

Preparation: Drill LRU-cache style implementations (hashmap + DLL) to muscle memory.
Sketch a second variant with party-size buckets and verbalize the trade-off (find_first_match becomes O(table_size) instead of O(n) but uses more memory).
Practice articulating which call should be fast in a real restaurant — typically find_first_match runs once per available table.

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 72 of 165

Determine Reporting Relationships

POSTED 2026-02-22 | 230 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 37.4 | 30 DAYS 33 | PRIORITY 62/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #721 Accounts Merge

LeetCode match: No direct match; related LC 721 Accounts Merge (union-find)

Posted on PracHub: 2026-02-22 (updated 2026-04-21)

Original: https://prachub.com/coding-questions/determine-reporting-relationships

QUESTION

Build an in-memory organization model that supports three operations on employee IDs:

1. `add_manager(a, b)`: employee **a** is the direct manager of employee **b**.
2. `add_peer(a, b)`: employees **a** and **b** share the same direct manager.
3. `is_manager(a, b)`: return whether employee **a** is a manager of employee **b**. The answer should account for relationships that can be inferred from prior operations. For example, if `add_manager(m, x)` and `add_peer(x, y)` were previously recorded, then `is_manager(m, y)` should return `true`. You may assume the input is logically consistent and does not create invalid cycles in the org chart. Explain how you would design the data structures and implement these operations efficiently.

Implement an in-memory organization model that processes operations on employee IDs in order. Each operation is a tuple `(op, a, b)` where:

- `("add_manager", a, b)`: employee **a** becomes the direct manager of employee **b**.
- `("add_peer", a, b)`: employees **a** and **b** share the same direct manager.
- `("is_manager", a, b)`: ask whether employee **a** is a direct or indirect manager of employee **b**. Relationships can be inferred from earlier operations. For example, after `add_manager(m, x)` and `add_peer(x, y)`, `is_manager(m, y)` should be `True`. Process the operations sequentially and return a list of answers for all `is_manager` queries, in order. Notes:
- The input is logically consistent.
- No operation creates a cycle in the org chart.
- Repeating the same valid relationship is allowed.
- An employee is not considered their own manager.

QUESTION

Constraints

0 <= len(operations) <= 20000Employee IDs are integers in the range [-10^9, 10^9]At most 10000 distinct employee IDs appearThe sequence of operations is logically consistent and does not create cycles

EXAMPLES

```
Input: ([("add_manager", 1, 2), ("add_peer", 2, 3),
    ("is_manager", 1, 3)])
Expected Output: [True]
```

Explanation: Employee 2 reports to 1. Since 2 and 3 are peers, 3 also reports to 1.

```
Input: ([("add_manager", 2, 4), ("is_manager", 1, 4),
    ("add_manager", 1, 2), ("is_manager", 1, 4),
    ("is_manager", 2, 4), ("is_manager", 4, 2)])
Expected Output: [False, True, True, False]
```

Explanation: Before 2 gets a manager, 1 is not a manager of 4. After adding 1 as manager of 2, 1 becomes an indirect manager of 4. Hints`add_peer(a, b)` means **a** and **b** share one direct manager, but they are not interchangeable as managers. Group such employees with Union-Find.Once a peer group learns its direct manager, every current member of that group gets the same parent pointer. To answer `is_manager(a, b)`, walk upward from **b** through parent pointers.

APPROACH

Manager edges as a directed graph/parent map; peers via union-find or shared-manager sets; queries answer reachability up the manager chain. Keep both structures in sync.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether is_manager means direct manager or any manager up the chain (the example implies the chain), whether peers can be added before their manager is known, and whether input is always consistent (the statement says yes).

BRUTE FORCE TO SAY OUT LOUD

Store all relations and recompute reachability with a graph search on each query. O(V + E) per query.

OPTIMAL IDEA

Keep a Union-Find over employees for peer groups and attach one manager to each group. add_manager(a, b) sets the manager of b's group to a. add_peer(a, b) unions the two groups and, if both had managers, keeps the (necessarily identical) manager. is_manager(a, b): look up the manager of b's group, return true if it is a, otherwise continue from that manager's group up the chain. Each query walks at most the depth of the hierarchy.

DRY-RUN THESE CASES

add_manager(m, x) then add_peer(x, y) gives is_manager(m, y) true; add_peer before add_manager; a manager's manager (indirect); an employee with no manager; a query on unknown ids.

INTERVIEW-DAY PLAN

LIKELY FOLLOW-UPS

Direct manager only, the closest common manager, or removing relationships.

PITFALLS

Forgetting to merge managers when two groups unite. Treating peers as managers of each other.

HOW TO THINK ABOUT IT

Peers form groups (a peer relation is transitive: same manager as a person who has the same manager as another). A group has at most one direct manager, so store the manager on the group. To answer is_manager(a, b) go from b's group to its manager, then that manager's group to its manager, and so on, looking for a. Union-find makes the groups cheap to merge.

Basis: Written (compare LeetCode 721, Accounts Merge, for the union-find idea). Operations: add_manager(a, b) (a is b's direct manager), add_peer(a, b) (same direct manager), is_manager(a, b) (a is anywhere above b). Inferences must follow from earlier calls.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
managers, peers = [], []  # the stored facts
def is_manager(a, b):
    groups = merge_peers(peers)
    manager_of = {}
    for x, y in managers:  # x manages y
        boss = groups.find(x)
        manager_of[groups.find(y)] = boss
    node = groups.find(b)
    while node in manager_of:
        node = manager_of[node]
        if node == groups.find(a):
            return True
    return False
```

TIME	SPACE
O(F * employees) per query	O(F)

WHY IT IS SLOW

Each query redoes the whole inference over all facts. Union-Find for peer groups with a manager stored on each group keeps every update near-constant and a query O(depth).

OPTIMAL SOLUTION · Union-Find for peer groups with a manager stored on each group

TIME	SPACE
O(alpha) per update, O(depth) per query	O(employees)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the closest common manager of two employees.

Collect the chain of managers above one employee into a set, then climb from the other until you meet it. O(depth).

FOLLOW-UP 2 Facts can be wrong or contradictory.

When uniting groups that already have different managers, the input is inconsistent: raise, or record a conflict instead of silently overwriting. Also guard the upward walk with a visited set so a cycle cannot loop forever.

FOLLOW-UP 3 Remove a relationship.

Union-Find cannot split groups; keep the facts and rebuild lazily, or store the peers as an explicit graph and recompute connected components on demand.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Union-Find for peer groups with
# a manager stored on each ...
# FOLLOW-UP 1: Return the closest common manager of two
# employees.
class Org:
    def __init__(self):
        # union-find over peers (people with the same
        # manager)
        self.parent = {}
        # peer-group root -> the manager of that group
        self.boss = {}

    def find(self, x):
        self.parent.setdefault(x, x)
        while self.parent[x] != x:
            self.parent[x] = self.parent[self.parent[x]]
            x = self.parent[x]
        return x

    def add_peer(self, a, b):
        ra, rb = self.find(a), self.find(b)
        if ra == rb:
            return
        # two groups with different managers contradict
        if ra in self.boss and rb in self.boss \
                and self.boss[ra] != self.boss[rb]:
            # FOLLOW-UP 2: contradictory facts are
            # rejected
            raise ValueError("conflicting managers")
        self.parent[rb] = ra
        # the merged group keeps whichever manager is
        # known
        if rb in self.boss and ra not in self.boss:
            self.boss[ra] = self.boss[rb]

    def add_manager(self, a, b):
        # a is the direct manager of b (and b's peers)
        self.find(a)
        root = self.find(b)
        if root in self.boss and self.boss[root] != a:
            raise ValueError("conflicting managers")
        self.boss[root] = a
```

```
    def manager_of(self, x):
        return self.boss.get(self.find(x))
```

```
    def is_manager(self, a, b):
        # climb b's chain of managers; a visited set stops
        # cycles
        seen, cur = set(), b
        while cur is not None and cur not in seen:
            seen.add(cur)
            cur = self.manager_of(cur)
            if cur == a:
                return True
        return False

    # FOLLOW-UP 1: the closest common manager
    def common_manager(self, a, b):
        # the closest manager above both people
        chain, cur = set(), self.manager_of(a)
        while cur is not None and cur not in chain:
            chain.add(cur)
            cur = self.manager_of(cur)
        cur, seen = self.manager_of(b), set()
        while cur is not None and cur not in seen:
            if cur in chain:
                return cur
            seen.add(cur)
            cur = self.manager_of(cur)
        return None


if __name__ == "__main__":
    o = Org()
    o.add_manager("ceo", "vp")
    o.add_manager("vp", "dev")
    o.add_peer("dev", "qa")
    # qa shares dev's manager, so vp manages qa too
    assert o.is_manager("vp", "qa")
    assert o.is_manager("ceo", "qa")
    assert not o.is_manager("qa", "vp")
    assert not o.is_manager("dev", "qa")
    assert o.common_manager("dev", "qa") == "vp"
    assert o.common_manager("vp", "qa") == "ceo"
    # peers added before the manager is known
    p = Org()
    p.add_peer("a", "b")
    p.add_manager("boss", "a")
    assert p.is_manager("boss", "b")
```

```
    # contradictory facts are reported
    try:
        o.add_manager("ceo", "dev")
        raise AssertionError("should conflict")
    except ValueError:
        pass
```

FUNCTION AND TEST CASES

Signature

```
def solution(operations: list[tuple[str, int, int]]) -> li
st[bool]:
SAMPLE INPUT
([("add_manager", 1, 2), ("add_peer", 2, 3), ("is_manager"
, 1, 3)])
```

Test cases

Input	Expected
`([("add_manager", 1, 2), ("add_peer", 2, 3), ("is_manager", 1, 3)])`	`[True]`
`([("add_manager", 2, 4), ("is_manager", 1, 4), ("add_manager", 1, 2), ("is_manager", 1, 4), ("is_manager", 2, 4), ("is_manager", 4, 2)])`	`[False, True, True, False]`

MEDIUM | PracHub | Technical Screen | 73 of 165

★ TOP 75: rank 13 in the Medium and Hard priority list

★ Solve array-sum and city-community problems

POSTED 2026-02-20 | 232 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 66 | 30 DAYS 46.9 | PRIORITY 6/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #560 Subarray Sum Equals K, LeetCode #200 Number of Islands

LeetCode match: LC 560 Subarray Sum Equals K + LC 200 Number of Islands (inferred from overview)

Posted on PracHub: 2026-02-20 (updated 2026-04-19)

Original: https://prachub.com/coding-questions/solve-array-sum-and-city-community-problems

QUESTION

Overview: This question evaluates array-processing and grid/graph connectivity skills, covering counting subarrays with a target sum and identifying connected building communities in a grid; it belongs to the Coding & Algorithms domain and involves streaming/online algorithm reasoning as well as grid traversal concepts.

APPROACH

Prefix sum + hash map of counts for the subarray target; communities = connected components via DFS/union-find on the grid.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two parts. Array: count subarrays whose sum equals K; are values negative (decides the method) and can the input be a stream? Grid: building communities as connected components, is adjacency four-way, and what marks a building. The scraped solution covers only the array part.

BRUTE FORCE TO SAY OUT LOUD

Array: all subarrays with running sums, O(n^2). Grid: none needed, a flood fill is the baseline.

OPTIMAL IDEA

INTERVIEW-DAY PLAN

Array: prefix sums with a dict of how many times each prefix has occurred; for each element add the count of (prefix - K), then record the prefix. O(n) and it works online for a stream. A sliding window fails with negative values. Grid: DFS/BFS (iterative) or Union-Find to count connected components of building cells.

DRY-RUN THESE CASES

Array: [1,1,1] with K = 2 gives 2, [1,2,3] with K = 3 gives 2, negatives, K = 0 with zeros, an empty array. Grid: no buildings, one building, diagonal buildings (separate).

LIKELY FOLLOW-UPS

Array: longest subarray with sum K, or counting in a stream. Grid: the largest community, or communities as buildings are added.

PITFALLS

Not seeding the prefix dict with {0: 1}. Using a window technique with negative numbers.

HOW TO THINK ABOUT IT

Subarray sums with negatives allowed cannot use a sliding window; use prefix sums: a subarray ending here sums to K exactly when an earlier prefix equals (current prefix - K), so a dictionary of prefix counts answers it in one pass and works for streams. Communities are connected components, so flood fill or union-find over the building cells.

Basis: Two tasks: count subarrays with sum equal to K (LeetCode 560) and count connected building communities in a grid (LeetCode 200 idea). Assumed rule: buildings are '1' cells, communities connect horizontally and vertically.

BRUTE FORCE · Task 1: try every subarray

BRUTE FORCE · PSEUDO-CODE

```
def brute(nums, K):
    count = 0
    for i in range(len(nums)):
        total = 0
        for j in range(i, len(nums)):
            total += nums[j]
            if total == K:
                count += 1
    return count
```

TIME	SPACE
O(n^2)	O(1)

WHY IT IS SLOW

O(n^2). A dictionary of prefix sums (how many earlier prefixes equal current - K) is O(n) and also works on a stream and with negative numbers.

BRUTE FORCE · Task 2: relabel cells until the labels stop changing

BRUTE FORCE · PSEUDO-CODE

```
label = {}
for i, cell in enumerate(buildings):
    label[cell] = i
changed = True
while changed:
    changed = False
    for cell in buildings:
        group = [cell] + neighbours(cell)
        best = min(label[x] for x in group)
        if best < label[cell]:
            label[cell] = best
            changed = True
answer = len(set(label.values()))
```

TIME	SPACE
O((m * n)^2) worst case	O(m * n)

WHY IT IS SLOW

Labels spread one step per round, so a long snake needs about m * n rounds of O(m * n): O((m * n)^2). Union-Find or one flood fill is near-linear.

OPTIMAL SOLUTION · Task 1: prefix sums in a dictionary

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Task 2: Union-Find over building cells

TIME	SPACE
O(m * n * alpha(m * n))	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The numbers are all positive.

A sliding window works in O(1) memory: grow the right end, shrink the left while the sum exceeds K. With negatives the window is not monotone, which is why prefix sums are needed.

FOLLOW-UP 2 Longest subarray with sum K.

Store the first index of each prefix sum instead of a count, and take the longest distance to prefix - K.

FOLLOW-UP 3 Buildings are added over time and you report the number of communities after each addition.

Union-Find with a counter: +1 for the new building, -1 for each union with a different neighbouring community (LeetCode 305).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
STEPS = ((1, 0), (-1, 0), (0, 1), (0, -1))


# BASE QUESTION (optimal): prefix sums in a dictionary
def count_subarrays(nums, k):
    # prefix sums: a subarray ending here has sum k if
    # some
    # earlier prefix equals (prefix - k)
    seen, prefix, count = {0: 1}, 0, 0
    for x in nums:
        prefix += x
        count += seen.get(prefix - k, 0)
        seen[prefix] = seen.get(prefix, 0) + 1
    return count


# FOLLOW-UP 2: Longest subarray with sum K.
def longest_subarray(nums, k):
    # store the FIRST index of each prefix sum
    first, prefix, best = {0: -1}, 0, 0
    for i, x in enumerate(nums):
        prefix += x
        if prefix - k in first:
            best = max(best, i - first[prefix - k])
        first.setdefault(prefix, i)
    return best


# FOLLOW-UP 1: The numbers are all positive.
def count_positive(nums, k):
    # all numbers positive: a sliding window, O(1) memory
    count = left = total = 0
    for right, x in enumerate(nums):
        total += x
        while total > k and left <= right:
            total -= nums[left]
            left += 1
        if total == k:
            count += 1
    return count


# BASE QUESTION (optimal): prefix sums in a dictionary
def communities(grid):
    # connected groups of buildings (1) in a grid
    seen, count = set(), 0
    for r in range(len(grid)):
        for c in range(len(grid[0])):
            if grid[r][c] != 1 or (r, c) in seen:
                continue
            count += 1
            seen.add((r, c))
            stack = [(r, c)]
            while stack:
                x, y = stack.pop()
                for dx, dy in STEPS:
                    a, b = x + dx, y + dy
                    if not (0 <= a < len(grid)):
                        continue
                    if not (0 <= b < len(grid[0])):
                        continue
                    land = grid[a][b] == 1
                    if land and (a, b) not in seen:
                        seen.add((a, b))
                        stack.append((a, b))
    return count


# FOLLOW-UP 3: Buildings are added over time and you
# report the number of ...
def communities_online(rows, cols, additions):
    # buildings added one by one: count after each
    # (LeetCode 305)
    parent, count, out = {}, 0, []

    def find(x):
        while parent[x] != x:
            parent[x] = parent[parent[x]]
            x = parent[x]
        return x

    for r, c in additions:
        if (r, c) not in parent:
            parent[(r, c)] = (r, c)
            count += 1
            for dr, dc in STEPS:
                nb = (r + dr, c + dc)
                if nb in parent:
                    a, b = find((r, c)), find(nb)
                    if a != b:
                        parent[a] = b
                        # two communities became one
                        count -= 1
        out.append(count)
    return out


if __name__ == "__main__":
    assert count_subarrays([1, 1, 1], 2) == 2
    assert count_subarrays([1, -1, 0], 0) == 3
    assert count_subarrays([], 0) == 0
    assert longest_subarray([1, -1, 5, -2, 3], 3) == 4
    assert longest_subarray([1, 2], 9) == 0
    assert count_positive([1, 2, 3, 2, 1], 3) == 3
    grid = [[1, 1, 0], [0, 0, 1], [1, 0, 1]]
    assert communities(grid) == 3
    adds = [(0, 0), (0, 1), (1, 2), (2, 2), (1, 1)]
    counts = communities_online(3, 3, adds)
    assert counts == [1, 1, 2, 2, 1]
```

FUNCTION AND TEST CASES

Signature

```
def solution(nums: list[int], k: int) -> int:
```

Sample call

```
solution([1, 1, 1], 2)
```

Test cases

Input	Expected
([1, 1, 1], 2)	2
([1, 2, 3], 3)	2

MEDIUM | IN APP LC 208 | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 74 of 165

Implement Trie Insert and Exact-Word Search

POSTED 2026-02-20 | 232 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 36 | 30 DAYS 0 | PRIORITY 106/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #208 Implement Trie (Prefix Tree)

LeetCode match: LC 208 Implement Trie (Prefix Tree)

Posted on PracHub: 2026-02-20 (updated 2026-08-28)

Original: https://prachub.com/coding-questions/implement-trie-insert-and-exact-word-search

QUESTION

Problem

Implement a trie that supports **`insert(word)`** and **`search(word)`**. Insert adds a lowercase word. Search returns true only when the complete word was previously inserted; a stored word merely sharing the requested prefix is not a match. Process a sequence of operations and return the results of all searches.

Constraints & Assumptions

- There are at most 200,000 operations.
- Every word has length between 1 and 1,000.
- The total number of characters across all operations is at most 1,000,000.
- Words contain lowercase English letters.

Clarifications

- Inserting the same word repeatedly is allowed and has no additional effect.
- A node must distinguish an inserted word ending there from a prefix only.
- Return booleans in the same order as search operations appear.

Examples

```
operations = [insert("apple"), search("apple"), search("app"), insert("app"), search("app")] output = [true, false, true]
```

Hints

```
Represent prefixes Each edge consumes one character and each node represents the prefix along its path.
```

```
Mark complete words Reaching the final character is not enough unless the terminal node records an insertion.
```

APPROACH

Trie nodes with children and an end-of-word flag; search returns true only if the final node is marked as a word.

HOW TO THINK ABOUT IT

A trie needs a flag that marks 'a word ends here'; without it search('app') would be true whenever 'apple' was inserted. Walking a prefix and checking the flag are the two operations: search checks the flag, startsWith does not.

Basis: LeetCode 208, Implement Trie (Prefix Tree).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
words = []
def insert(w):
    words.append(w)
def search(w):
    return w in words
def starts_with(p):
    for word in words:
        if word.startswith(p):
            return True
    return False
```

TIME	SPACE
O(W * L) per operation	O(total characters)

WHY IT IS SLOW

Each call scans every stored word, O(W * L). A trie with an end-of-word flag makes every call O(L).

OPTIMAL SOLUTION · Trie of nodes with an end-of-word flag

TIME	SPACE
O(L) per operation	O(total characters)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Support '.' as a wildcard in search (LeetCode 211).

On '.', try every child at that level and recurse; other characters follow the single matching child. Worst case O(26^L) per query on adversarial patterns, so mention the bound.

FOLLOW-UP 2 Delete a word.

Unmark the end flag and, walking back up, remove nodes that have no children and are not word ends. Keep a path stack while walking down so you can prune on the way back. **Cost:** O(L) time and O(L) space for the path stack.

FOLLOW-UP 3 Unicode or large alphabets.

Store children in a dict keyed by character instead of a 26-slot array, as the code does; it handles any alphabet and wastes no space on missing letters. **Cost:** O(L) per operation with dictionary children; memory O(total characters).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class Node:
    def __init__(self):
        self.children = {}
        self.end = False


# BASE QUESTION (optimal): Trie of nodes with an end-of-
# word flag
# FOLLOW-UP 1: Support '.' as a wildcard in search
# (LeetCode 211).
class Trie:
    def __init__(self):
        self.root = Node()

    def walk(self, text):
        # follow the letters; None if the path breaks
        node = self.root
        for ch in text:
            node = node.children.get(ch)
            if node is None:
                return None
        return node

    def insert(self, word):
        node = self.root
        for ch in word:
            node = node.children.setdefault(ch, Node())
        node.end = True

    def search(self, word):
        # the whole word must have been inserted
        node = self.walk(word)
        return node is not None and node.end

    def starts_with(self, prefix):
        return self.walk(prefix) is not None

    # FOLLOW-UP 1: '.' matches any one letter
    def search_wild(self, pattern):
        # '.' matches any one letter (LeetCode 211)
        def go(node, i):
            if i == len(pattern):
                return node.end
            ch = pattern[i]
            if ch == ".":
```

```
                # try every child at this level
                kids = node.children.values()
                return any(go(c, i + 1) for c in kids)
            child = node.children.get(ch)
            return child is not None and go(child, i + 1)

        return go(self.root, 0)

    # FOLLOW-UP 2: delete a word
    def delete(self, word):
        # unmark the word, then prune nodes nothing needs
        path = [self.root]
        for ch in word:
            nxt = path[-1].children.get(ch)
            if nxt is None:
                return False
            path.append(nxt)
        if not path[-1].end:
            return False
        path[-1].end = False
        # walk back up removing empty, non-word nodes
        for i in range(len(word), 0, -1):
            node = path[i]
            if node.end or node.children:
                break
            del path[i - 1].children[word[i - 1]]
        return True


def run(operations):
    # ["insert", w] or ["search", w] -> results of the
    # searches
    trie, out = Trie(), []
    for op, word in operations:
        if op == "insert":
            trie.insert(word)
        else:
            out.append(trie.search(word))
    return out


if __name__ == "__main__":
    ops = [("insert", "apple"), ("search", "apple"),
           ("search", "app"), ("insert", "app"),
           ("search", "app")]
```

```
    assert run(ops) == [True, False, True]
    t = Trie()
    t.insert("apple")
    # a shared prefix is not a match for search
    assert not t.search("app") and t.starts_with("app")
    assert not t.starts_with("b")
    t.insert("bad")
    t.insert("dad")
    assert t.search_wild("b.d") and t.search_wild(".ad")
    assert not t.search_wild("b..d")
    assert t.search_wild("...")
    # delete keeps shorter words that share the path
    t.insert("app")
    assert t.delete("apple")
    assert t.search("app") and not t.search("apple")
    assert not t.delete("apple")
    assert t.delete("app") and not t.starts_with("a")
```

FUNCTION AND TEST CASES

Signature

```
def process_trie_operations(operations: list[list[str]]) -
> list[bool]:
```

Sample call

```
process_trie_operations([['insert', 'apple'], ['search', '
apple'], ['search', 'app'], ['insert', 'app'], ['search',
'app']])
```

Test cases

Input	Expected
`([['insert', 'apple'], ['search', 'apple'], ['search', 'app'], ['insert', 'app'], ['search', 'app']],)`	`[True, False, True]`
`([],)`	`[]`

MEDIUM | IN APP LC 127 | PracHub | Technical Screen | 75 of 165

Find shortest relationship path using BFS

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TALK ALL TIME 41.8 30 DAYS 0 PRIORITY 86/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #127 Word Ladder

LeetCode match: LC 127 Word Ladder (BFS shortest path) (inferred from overview)

Posted on PracHub: 2026-02-12 (updated 2026-05-04)

Original: https://prachub.com/coding-questions/find-shortest-relationship-path-using-bfs

QUESTION

Overview: This question evaluates proficiency in graph representations and traversal algorithms—specifically BFS and adjacency-structure construction—for computing unweighted shortest paths and reasoning about reachability.

APPROACH

Build an adjacency list, BFS from the source with a parent map, then reconstruct the path; O(V+E). Consider bidirectional BFS.

HOW TO THINK ABOUT IT

Unweighted means every hop costs the same, so breadth-first search finds the fewest hops: it explores all people one hop away, then two hops, and the first time it reaches the target is the shortest path. Keep a parent map to rebuild the path and a visited set so nobody is queued twice.

Basis: LeetCode 127 (Word Ladder) idea: shortest path in an unweighted graph of people. Return the list of people from source to target, or None.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
best = None
def dfs(node, path):
    global best
    if node == target:
        if not best or len(path) < len(best):
            best = list(path)
        return
    for nxt in graph[node]:
        if nxt not in path:
            dfs(nxt, path + [nxt])
dfs(source, [source])
```

TIME	SPACE
exponential	O(path)

WHY IT IS SLOW

The number of simple paths is exponential. Breadth-first search reaches the target along a shortest path first, O(V + E), and bidirectional BFS explores far fewer nodes on big graphs.

OPTIMAL SOLUTION · Breadth-first search with a parent map

TIME	SPACE
O(V + E)	O(V)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The graph is huge (a social network).

Bidirectional BFS searches from both ends and stops when the frontiers meet; with branching factor b and distance d it explores about 2 * b^(d/2) nodes instead of b^d.

FOLLOW-UP 2 Return every shortest path, or count them.

Keep, for each node, its distance and a list of all parents at that distance; counting is a DP over the BFS layers, and listing the paths is a DFS over the parent lists.

FOLLOW-UP 3 Relationships have different strengths (weights).

BFS is no longer right: use Dijkstra with a heap for non-negative weights. Keep the same parent map to rebuild the path.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import defaultdict, deque


# BASE QUESTION (optimal): Breadth-first search with a
# parent map
def shortest_path(adj, s, t):
    # BFS: the first time we reach a node is by a shortest
    # path
```

```
    if s == t:
        return [s]
    parent, queue = {s: None}, deque([s])
    while queue:
        u = queue.popleft()
        for v in adj.get(u, ()):
            if v not in parent:
                parent[v] = u
                if v == t:
                    # walk the parent links back to s
                    path = [v]
                    while parent[path[-1]] is not None:
                        path.append(parent[path[-1]])
                    return path[::-1]
                queue.append(v)
    return None


# FOLLOW-UP 1: The graph is huge (a social network).
def bidirectional(adj, s, t):
    # a huge graph: search from both ends, expand the
    # smaller
    # side, stop when the searches meet
    if s == t:
        return 0
    dist_s, dist_t = {s: 0}, {t: 0}
    front_s, front_t = [s], [t]
    while front_s and front_t:
        if len(front_s) > len(front_t):
            front_s, front_t = front_t, front_s
            dist_s, dist_t = dist_t, dist_s
        nxt = []
        for u in front_s:
            for v in adj.get(u, ()):
                if v in dist_t:
                    return dist_s[u] + 1 + dist_t[v]
```

```
                if v not in dist_s:
                    dist_s[v] = dist_s[u] + 1
                    nxt.append(v)
        front_s = nxt
    return None


# FOLLOW-UP 2: Return every shortest path, or count them.
def all_shortest_paths(adj, s, t):
    # every shortest path: remember ALL parents at the
    # best level
    dist, queue = {s: 0}, deque([s])
    parents = defaultdict(list)
    while queue:
        u = queue.popleft()
        for v in adj.get(u, ()):
            if v not in dist:
                dist[v] = dist[u] + 1
                queue.append(v)
            if dist[v] == dist[u] + 1:
                parents[v].append(u)
    if t not in dist:
        return []
    paths = []

    def build(node, tail):
        if node == s:
            paths.append([s] + tail)
            return
        for p in parents[node]:
            build(p, [node] + tail)

    build(t, [])
    return paths
```

```
# FOLLOW-UP 3: Relationships have different strengths
# (weights).
def weighted_path(graph, s, t):
    # strengths differ: Dijkstra, same parent map
    dist, parent = {s: 0}, {s: None}
    heap = [(0, s)]
    while heap:
        d, u = heapq.heappop(heap)
        if d > dist[u]:
```

```
            continue
        for v, w in graph.get(u, ()):
            if d + w < dist.get(v, float("inf")):
                dist[v], parent[v] = d + w, u
                heapq.heappush(heap, (d + w, v))
    if t not in dist:
        return None
    path = [t]
    while parent[path[-1]] is not None:
        path.append(parent[path[-1]])
    return dist[t], path[::-1]


if __name__ == "__main__":
    adj = {"a": ["b", "c"], "b": ["d"], "c": ["d"],
           "d": ["e"], "e": []}
    assert shortest_path(adj, "a", "e") in (
        ["a", "b", "d", "e"], ["a", "c", "d", "e"])
    assert shortest_path(adj, "a", "a") == ["a"]
    assert shortest_path(adj, "e", "a") is None
    both_ways = {"a": ["b", "c"], "b": ["a", "d"],
                 "c": ["a", "d"], "d": ["b", "c", "e"],
                 "e": ["d"]}
    assert bidirectional(both_ways, "a", "e") == 3
    assert bidirectional(both_ways, "a", "a") == 0
    paths = all_shortest_paths(adj, "a", "e")
    assert sorted(paths) == [["a", "b", "d", "e"],
                             ["a", "c", "d", "e"]]
    graph = {"a": [("b", 1), ("c", 5)], "b": [("c", 1)]}
    cheapest = weighted_path(graph, "a", "c")
    assert cheapest == (2, ["a", "b", "c"])
    assert weighted_path(graph, "c", "a") is None
```

FUNCTION AND TEST CASES

Signature

```
def solution(relationships: list[list[int]], start: int, t
arget: int) -> int:
```

Sample call

```
solution([['A', 'B'], ['B', 'C'], ['C', 'D']], 'A', 'D')
```

Test cases

Input	Expected
`([['A', 'B'], ['B', 'C'], ['C', 'D']], 'A', 'D')`	`3`
`([[1, 2], [2, 5], [1, 3], [3, 4], [4, 5]], 1, 5)`	`2`

ALSO REPORTED · 1 more

Degrees of Friendship | Exponent
https://www.aced.io/questions/3628/degrees-of-friendship

MEDIUM | PracHub | Technical Screen | 76 of 165

Check pivot after removing one element

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 33.2 | 30 DAYS 0 | PRIORITY 115/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #724 Find Pivot Index

LeetCode match: LC 724 Find Pivot Index (variant: one removal) (inferred from overview)

Posted on PracHub: 2026-02-12 (updated 2026-05-04)

Original: https://prachub.com/coding-questions/check-pivot-after-removing-one-element

QUESTION

Overview: This question evaluates array-manipulation skills, cumulative-sum/prefix-sum reasoning, and robustness in handling negative values and duplicates, testing algorithmic problem-solving competency in the Coding & Algorithms domain and focusing on practical application rather than purely conceptual understanding.

APPROACH

Prefix sums plus a hash map of left-side sums; for each removal candidate, check whether some index has equal left and right sums after the removal.

INTERVIEW-DAY PLAN

CLARIFY FIRST

The statement is not complete in my copy, so confirm: after removing exactly one element (or at most one), does there exist an index where the sum to the left equals the sum to the right (the pivot itself excluded)? Are negatives and duplicates allowed?

BRUTE FORCE TO SAY OUT LOUD

For each element removed, rebuild the array and test every pivot with prefix sums. O(n^2).

OPTIMAL IDEA

Let P[i] be the sum before index i and S the total. If the removed element r is to the right of the pivot i, the two sides are equal exactly when a[r] = S - 2 * P[i] - a[i]. If r is to the left of i, the condition is a[r] = 2 * P[i] + a[i]

INTERVIEW-DAY PLAN

- S. So for every pivot candidate the value that must be removed is determined; look it up in a dict of value to last index (needs an index greater than i) and a dict of value to first index (needs an index less than i). One pass, O(n) time and space. Say the brute force first, and mention you checked the formulas against it on random small arrays.

DRY-RUN THESE CASES

A one-element array, two elements, negatives, duplicate values, a pivot that exists without any removal, removing the pivot itself (not allowed by most readings).

LIKELY FOLLOW-UPS

Allow at most one removal or remove a pivot candidate, or count all pairs.

PITFALLS

Letting the removed element be the pivot. Forgetting that the prefix sums shift after a removal.

HOW TO THINK ABOUT IT

Use prefix sums. For a pivot at original index i and a removed element on one side, the balance equation fixes the value that has to be removed: it is a closed form in the prefix sum, the total and a[i]. So for every candidate pivot you only have to ask 'does that value occur on the correct side?', which a dictionary of first and last positions answers in O(1).

Basis: Variant of LeetCode 724 (Find Pivot Index). Assumed rule (confirm it): remove exactly one element; is there then an index where the sum on its left equals the sum on its right (the pivot excluded)?

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(a):
    for r in range(len(a)):
        b = a[:r] + a[r + 1:]
        for i in range(len(b)):
            if sum(b[:i]) == sum(b[i + 1:]):
                return True
    return False
```

TIME	SPACE
O(n^3)	**O(n)**
O(n^2) with prefix sums	

WHY IT IS SLOW

n removals times n pivots times a sum: O(n^3) (O(n^2) with prefix sums). For each pivot the value to remove is determined by prefix sums, so a dictionary lookup makes it O(n).

OPTIMAL SOLUTION · Closed-form value to remove, found in a dictionary of positions

TIME	SPACE
O(n)	**O(n)**

OPTIMAL SOLUTION · Closed-form value to remove, found in a dictionary of positions

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Without any removal (LeetCode 724).

One pass: the pivot is the index where left sum equals total minus left minus the element. O(n), O(1).

FOLLOW-UP 2 At most one removal (removal optional).

Answer true if pivot_index finds a pivot, otherwise run the removal test above.

FOLLOW-UP 3 Return which element to remove and the pivot.

Record i together with the index of the matching value (first or last occurrence) when the lookup succeeds, instead of returning True.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Closed-form value to remove,
# found in a dictionary of ...
def pivot_after_removal(a):
    # remove ONE element, then is there a pivot: an
    # element
    # whose left sum equals its right sum? Returns
    # (removed
    # index, pivot index) or None. O(n) with two scans.
    n, total = len(a), sum(a)
    prefix = [0]
    for x in a:
        prefix.append(prefix[-1] + x)
    # key[j]: left + left + a[j] when nothing is removed
    key = [2 * prefix[j] + a[j] for j in range(n)]
    # pivot j AFTER the removed index i:
    #   2 * prefix[j] - a[i] = total - a[j]  -> a[i] = key
    # - total
    where, ok = {}, None
    for j in range(n):
        i = where.get(key[j] - total)
        if i is not None:
            return i, j
        where[a[j]] = j
    # pivot j BEFORE the removed index i:
    #   2 * prefix[j] + a[j] = total - a[i]  -> a[i] =
    # total - key
    where = {}
    for j in range(n - 1, -1, -1):
        i = where.get(total - key[j])
        if i is not None:
            return i, j
        where[a[j]] = j
    return ok


# FOLLOW-UP 1: Without any removal (LeetCode 724).
def pivot_index(a):
    # LeetCode 724: no removal, O(1) extra space
    total, left = sum(a), 0
    for i, x in enumerate(a):
        if left == total - left - x:
            return i
        left += x
    return -1
```

```
# FOLLOW-UP 2: At most one removal (removal optional).
def has_pivot(a, allow_removal=True):
    # follow-up: removal is optional
    if pivot_index(a) != -1:
        return True
    if not allow_removal:
        return False
    return pivot_after_removal(a) is not None


# BRUTE FORCE (checker)
def brute(a):
    # try every removal and every pivot: the demo's check
    for i in range(len(a)):
        rest = a[:i] + a[i + 1:]
        for j in range(len(rest)):
            if sum(rest[:j]) == sum(rest[j + 1:]):
                return True
    return False


if __name__ == "__main__":
    # [1,7,3,6,5,6] has a pivot at index 3 without
    # removal,
    # but removing one element never gives another
    assert pivot_after_removal([1, 7, 3, 6, 5, 6]) is None
    # [1, 1, 1, 1] has no pivot, but removing the element
    # at
    # index 1 leaves [1, 1, 1] whose middle element is one
    assert pivot_index([1, 1, 1, 1]) == -1
    assert pivot_after_removal([1, 1, 1, 1]) == (1, 2)
    assert pivot_index([1, 7, 3, 6, 5, 6]) == 3
    assert pivot_index([1, 2, 3]) == -1
    assert not has_pivot([1, 2, 3], allow_removal=False)
    # check against the brute force on many small arrays
    import itertools
    for n in range(1, 6):
        every = itertools.product([-2, 0, 1, 3], repeat=n)
        for a in every:
            a = list(a)
            found = pivot_after_removal(a) is not None
            assert found == brute(a)
    assert has_pivot([1, 1, 1, 1])
    ones = [1, 1, 1, 1]
```

```
    assert not has_pivot(ones, allow_removal=False)
```

FUNCTION AND TEST CASES

Signature

```
def solution(nums: list[int]) -> bool:
```

Sample call

```
solution([1, 2])
```

Test cases

Input	Expected
([1, 2],)	True
([2, 1, 1, 2],)	True

MEDIUM | PracHub | Technical Screen | 77 of 165

Min deletions to avoid overlap in first k

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 191/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: No direct match (inferred) (inferred from overview)

Posted on PracHub: 2026-02-12 (updated 2026-04-22)

Original: https://prachub.com/coding-questions/min-deletions-to-avoid-overlap-in-first-k

QUESTION

Overview: This question evaluates array and sequence manipulation skills, set-based reasoning about value overlap, and the ability to compute minimal edits while preserving relative order constraints.

APPROACH

Likely: compare the first k elements with the rest via sets and delete the minimum elements to remove value overlap while preserving order; confirm details on the PracHub page.

INTERVIEW-DAY PLAN

CLARIFY FIRST

This prompt is vague, so ask for the exact rule first. A common reading: the first k elements and the remaining elements must share no value, delete the fewest elements. Ask whether deleted elements must be removed from the first part or either part, and whether order matters.

BRUTE FORCE TO SAY OUT LOUD

Try every subset of deletions. Exponential.

OPTIMAL IDEA

Under that reading values are independent. For each value that appears in both parts, you must remove all its copies from one side, so you delete the smaller of its two counts. Sum over shared values. Count with two hash maps. O(n).

DRY-RUN THESE CASES

No shared values (0), every value shared, k = 0 or k = n, repeated values on one side only.

LIKELY FOLLOW-UPS

Delete only from the first part, weights on elements, or k given as a range.

PITFALLS

Starting to code before the rule is confirmed. Deleting elements one at a time greedily.

HOW TO THINK ABOUT IT

Values do not interact with each other, so each value can be decided on its own. A value that appears on both sides must disappear from one side entirely, and the cheapest side is the one with fewer copies. The answer is the sum, over values that appear on both sides, of the smaller of the two counts.

Basis: The statement is vague in my copy. Assumed rule (confirm it): given an array and k, the first k elements and the remaining elements must share no value; delete the fewest elements (from either part) to achieve that.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(a, k):
    for size in range(len(a) + 1):
        ids = range(len(a))
        for gone in combinations(ids, size):
            keep = [i for i in ids
                    if i not in gone]
            head = {a[i] for i in keep if i < k}
            tail = {a[i] for i in keep if i >= k}
            if not head & tail:
                return size
```

TIME	SPACE
O(2^n * n)	O(n)

WHY IT IS SLOW

2^n sets to try: exponential. Each shared value must disappear from one side, so the cost is the sum over shared values of the smaller of its two counts, in O(n).

OPTIMAL SOLUTION · Sum of min(count in the first k, count in the rest) over shared values

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Only elements of the first part may be deleted.

Then every shared value must be removed from the first part entirely, so the cost is the number of first-part elements whose value occurs in the rest (a set lookup per element).

FOLLOW-UP 2 Elements have weights (deleting some is more costly).

Replace counts by the sum of weights per side for each value; the choice per value is still independent, so take the cheaper side. **Cost:** unchanged O(n); the per-value choice sums weights instead of counts.

FOLLOW-UP 3 The statement may differ from this reading.

Ask whether deletions can come from both parts, whether duplicates count separately, and whether order matters. Everything above relies on those three answers.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


# BASE QUESTION (optimal): Sum of min(count in the first
# k, count in the rest) over ...
def min_deletions(a, k):
    # the values in a[:k] and a[k:] must not overlap; for
    # each
    # shared value delete the copies on the cheaper side
    left, right = Counter(a[:k]), Counter(a[k:])
    return sum(min(left[v], right[v])
               for v in left.keys() & right.keys())


# FOLLOW-UP 1: Only elements of the first part may be
# deleted.
def min_deletions_first_only(a, k):
    # only the first part may lose elements: every first-
    # part
    # element whose value appears later must go
    rest = set(a[k:])
    return sum(1 for x in a[:k] if x in rest)


# FOLLOW-UP 2: Elements have weights (deleting some is
# more costly).
def min_deletions_weighted(a, weights, k):
    # deleting element i costs weights[i]: per value take
    # the
    # cheaper side as a whole
    left, right = Counter(), Counter()
    for i, x in enumerate(a):
        (left if i < k else right)[x] += weights[i]
    return sum(min(left[v], right[v])
               for v in left.keys() & right.keys())


# PLAN: which indices to delete
def deletions_plan(a, k):
    # which indices to delete (both sides allowed)
    left, right = Counter(a[:k]), Counter(a[k:])
    out = []
    for v in left.keys() & right.keys():
        # delete the cheaper side's copies of the value
        side = range(k, len(a))
        if left[v] <= right[v]:
            side = range(k)
        out += [i for i in side if a[i] == v]
    return sorted(out)


if __name__ == "__main__":
    a = [1, 2, 2, 3, 2, 1]
    # first part [1, 2, 2], rest [3, 2, 1]: shared 1 and 2
    assert min_deletions(a, 3) == 1 + 1
    assert min_deletions_first_only(a, 3) == 3
    assert min_deletions([1, 2, 3], 1) == 0
    assert min_deletions([], 0) == 0
    # a heavy copy on one side makes the other side
    # cheaper
    w = [1, 5, 5, 1, 1, 1]
    assert min_deletions_weighted(a, w, 3) == 1 + 1
    plan = deletions_plan(a, 3)
    kept = [x for i, x in enumerate(a) if i not in plan]
    kept_left = set(kept[:3 - sum(i < 3 for i in plan)])
    kept_right = set(kept[3 - sum(i < 3 for i in plan):])
    assert not kept_left & kept_right
    assert len(plan) == min_deletions(a, 3)
```

FUNCTION AND TEST CASES

Signature

```
def solution(list1: list[int], list2: list[int], k: int) -
> int:
```

Sample call

```
solution([1, 2, 3], [2, 1, 4, 5], 2)
```

Test cases

Input	Expected
([1, 2, 3], [2, 1, 4, 5], 2)	2
([1, 2, 3, 4], [2, 5, 3, 6], 2)	1

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 78 of 165

Design Tic-Tac-Toe With K Players

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 18.1 | 30 DAYS 0 | PRIORITY 152/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 348 Design Tic-Tac-Toe

Posted on PracHub: 2026-02-12 (updated 2026-05-21)

Original:
https://prachub.com/coding-questions/design-tic-tac-toe-with-k-players

QUESTION

Design and implement a Tic-Tac-Toe game engine. You are given:

- **k** players, each with a unique player ID or mark.
- An **n x n** board, initially empty.
- Players take turns placing their own mark on an empty cell. Unlike classic Tic-Tac-Toe, a player wins as soon as they form **3 consecutive marks** in a straight line, regardless of how large **n** is. A straight line may be horizontal, vertical, diagonal down-right, or diagonal down-left. Implement a class or set of functions that supports making moves and returns the game status after each move, such as:

QUESTION

- **`"Game Over"`** if a move is attempted after the game has ended.
- **`"<player> won"`** when the latest move causes that player to have 3 consecutive marks.
- A non-terminal status such as **`"Continue"`** if the game should keep going. Your implementation should handle invalid moves, such as placing a mark outside the board or on an occupied cell. Discuss the time and space complexity of your approach, especially for large **n**.

Design a Tic-Tac-Toe game engine for k players on an n x n board. The board starts empty, and players must play in cyclic order: player 1, player 2, ..., player k, then back to player 1. A player wins immediately when their latest valid move creates 3 consecutive marks in a straight line. A straight line may be horizontal, vertical, diagonal down-right, or diagonal down-left. For this problem, implement a function that processes a list of move attempts and returns the status after each attempt. Each move is given as [player, row, col] using 0-based indexing. Return one status string per move:

- "Game Over" if a move is attempted after someone has already won.
- "Invalid move" if the move is not legal. A move is invalid if: - the player ID is not in [1, k] - it is not that player's turn - the cell is outside the board - the cell is already occupied - "<player> won" if the move is valid and causes that player to have 3 consecutive marks - "Continue" if the move is valid and the game should continue Important: an invalid move does not change the board and does not advance the turn. You do not need to detect draws. If no one wins, valid moves simply return "Continue".

Constraints
1 <= n <= 10^91 <= k <= 10^50 <= len(moves) <= 2 * 10^5Each move is a list of three integers: [player, row, col]Row and column in the input may be outside the board and should then be treated as an invalid moveYour approach should be efficient for large n, so avoid scanning the whole board after every move

EXAMPLES

```
Input: (3, 2, [])
Expected Output: []
```

Explanation: No moves are made, so there are no statuses to report.

```
Input: (5, 2, [[1, 0, 0], [2, 1, 0], [1, 0, 1], [2,
    1, 1], [1, 0, 2], [2, 2, 2]])
Expected Output: ['Continue', 'Continue', 'Continue',
    'Continue', '1 won', 'Game Over']
```

Explanation: Player 1 forms three consecutive marks horizontally at (0,0), (0,1), and (0,2). Any later move returns 'Game Over'.

QUESTION

Hints
Only the latest valid move can create a new 3-in-a-row, so you never need to rescan the entire board.For large boards, store only occupied cells in a hash map keyed by (row, col), then check the 4 line directions around the new move.

APPROACH

Per-player row, column, diagonal and anti-diagonal counters; a player wins when any counter reaches n. O(1) per move.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether a win needs a full row, column or diagonal (n in a row) or only m in a row, how invalid moves are reported, what happens on a full board, and the API (move(row, col, player) returns winner or none).

BRUTE FORCE TO SAY OUT LOUD

After each move scan the row, column and both diagonals of the board. O(n) per move.

OPTIMAL IDEA

Keep counters per player for each row, each column, the main diagonal and the anti-diagonal. A move increments up to four counters; a player wins when any of their counters reaches n. O(1) per move, O(k * n) memory using a dict of counters. Reject moves on occupied cells.

DRY-RUN THESE CASES

A diagonal win, an anti-diagonal win, a row win by the last player, a draw, a move on an occupied cell, a move after the game has ended.

LIKELY FOLLOW-UPS

Win length m smaller than n (scan four directions from the last move for up to m cells), undo a move, or an unbounded sparse board.

PITFALLS

Counting an occupied cell twice. Not ending the game after a win.

HOW TO THINK ABOUT IT

Do not look at the board after each move. A win needs n marks of the same player on one line, so keep a counter per player and per line (each row, each column, the two diagonals) and bump the at-most-four lines that the move touches. The move wins if any of those counters reaches n.

Basis: LeetCode 348, Design Tic-Tac-Toe, generalized to k players. Assumed rule (confirm it): a player wins by filling a whole row, a whole column or a whole diagonal of the n x n board.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def move(player, r, c):
    board[r][c] = player
    lines = [row(r), column(c)]
    if r == c:
        lines.append(main_diagonal())
    if r + c == n - 1:
        lines.append(anti_diagonal())
    for line in lines:
        if line.count(player) == n:
            return "WIN"
    return "CONTINUE"
```

TIME	SPACE
O(n) per move	O(n^2)

WHY IT IS SLOW

Each move rescans up to four lines, O(n). Keeping a counter per player per row, column and diagonal makes each move O(1).

OPTIMAL SOLUTION · Counters per player and per line

TIME	SPACE
O(1) per move	O(k * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Win with m in a row, not the full line.

Counters per line no longer work, because a line can hold a run anywhere. After each move look along the four directions from that cell, counting same-player neighbours up to m in both directions. O(m) per move.

FOLLOW-UP 2 Undo the last move.

Decrement the same counters you incremented and clear the cell; remember the move history in a stack. The counters make undo as cheap as a move.

FOLLOW-UP 3 The board is huge or unbounded.

Store only the occupied cells in a dict (as TicTacToeM does) and keep the counter-per-line version only if the win condition is a complete line of a bounded board. **Cost:** O(1) per move with line counters on a bounded board, or O(m) per move scanning four directions for an m-in-a-row win; memory O(moves).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
DIRECTIONS = ((0, 1), (1, 0), (1, 1), (1, -1))


# BASE QUESTION (optimal): Counters per player and per
# line
# FOLLOW-UP 1: Win with m in a row, not the full line.
class TicTacToe:
    def __init__(self, n, k, target=3):
        self.n, self.k, self.target = n, k, target
        # FOLLOW-UP 3: a huge or unbounded board
        # only occupied cells are stored (works for huge
        # boards)
        self.cells = {}
        self.history = []
        self.winner = None

    def turn(self):
        # players go 1, 2, ..., k, then 1 again
        return len(self.history) % self.k + 1

    def run_length(self, r, c, dr, dc, player):
        # marks of `player` in a line through (r, c)
        run = 1
        for sign in (1, -1):
            a, b = r + sign * dr, c + sign * dc
            while self.cells.get((a, b)) == player:
                run += 1
                a, b = a + sign * dr, b + sign * dc
        return run

    def move(self, player, r, c):
        if self.winner is not None:
            return "Game Over"
        # an invalid move changes nothing
        if not 1 <= player <= self.k:
            return "Invalid move"
        if player != self.turn():
            return "Invalid move"
        if not (0 <= r < self.n and 0 <= c < self.n):
            return "Invalid move"
        if (r, c) in self.cells:
            return "Invalid move"
        self.cells[(r, c)] = player
        self.history.append((r, c))
        # only the four lines through the new mark can win
```

```
        for dr, dc in DIRECTIONS:
            run = self.run_length(r, c, dr, dc, player)
            # FOLLOW-UP 1: win with `target` in a row
            if run >= self.target:
                self.winner = player
                return f"{player} won"
        return "Continue"

    # FOLLOW-UP 2: undo the last move
    def undo(self):
        # take the last move back (also reopens a finished
        # game)
        if not self.history:
            return False
        del self.cells[self.history.pop()]
        self.winner = None
        return True


def process(n, k, moves):
    game = TicTacToe(n, k)
    return [game.move(*m) for m in moves]


if __name__ == "__main__":
    moves = [[1, 0, 0], [2, 1, 0], [1, 0, 1], [2, 1, 1],
             [1, 0, 2], [2, 2, 2]]
    assert process(3, 2, moves) == [
```

```
        "Continue", "Continue", "Continue", "Continue",
        "1 won", "Game Over"]
    # invalid moves do not use up the turn
    got = process(3, 2, [[2, 0, 0], [1, 5, 5], [1, 0, 0],
                         [2, 0, 0], [3, 1, 1], [2, 1, 1]])
    bad = "Invalid move"
    ok = "Continue"
    assert got == [bad, bad, ok, bad, bad, ok]
    g = TicTacToe(3, 2)
    for m in moves[:5]:
        g.move(*m)
    assert g.winner == 1 and g.undo() and g.winner is None
    assert g.move(1, 0, 2) == "1 won"
    # a huge board costs nothing: only taken cells are
    # stored
    big = TicTacToe(10 ** 9, 2)
    assert big.move(1, 10 ** 9 - 1, 5) == "Continue"
```

FUNCTION AND TEST CASES

Signature

```
def solution(n: int, k: int, moves: list[list[int]]) -> li
st[str]:
```

Sample call

```
solution(3, 2, [])
```

Test cases

Input	Expected
`(3, 2, [])`	`[]`
`(5, 2, [[1, 0, 0], [2, 1, 0], [1, 0, 1], [2, 1, 1], [1, 0, 2], [2, 2, 2]])`	`['Continue', 'Continue', 'Continue', 'Continue', '1 won', 'Game Over']`

ALSO REPORTED · 1 more

Tic-Tac-Toe System with K Players and 3-in-a-Row Win | 1Point3Acres | phone-screen, tech-screen | asked 2026-05-18 | Single report

https://www.1point3acres.com/interview/problems/company/google/tic-tac-toe-k-players-three-in-a-row

Check four directions through the new mark: horizontal, vertical, main diagonal, anti-diagonal. Count contiguous marks on both sides; win if total reaches 3.
Avoid scanning the whole board after every move unless n is tiny. The local directional check is O(1) for the fixed 3-in-a-row target, or O(target) if generalized.
Clarify invalid moves, turn order, draw state, and whether 3-in-a-row must be exactly 3 or at least 3.

Preparation: Implement the classic Tic-Tac-Toe design problem, then generalize from 2 players / 3x3 to k players / n x n.
Practice local directional win checks with boundary guards.
Write tests for corners, edges, duplicate moves, and simultaneous longer lines.

MEDIUM | PracHub | Technical Screen | 79 of 165

★ TOP 75: rank 28 in the Medium and Hard priority list

★ Implement frequency + distance top-K queries

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 58.8 | 30 DAYS 41.1 | PRIORITY 19/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #347 Top K Frequent Elements, LeetCode #973 K Closest Points to Origin

LeetCode match: LC 347 Top K Frequent Elements + LC 973 K Closest Points to Origin

Posted on PracHub: 2026-02-12 (updated 2026-04-28)

Original: https://prachub.com/coding-questions/implement-frequency-plus-distance-top-k-queries

QUESTION

You will implement solutions for two coding interview questions.

Question

1: Return the top-K points by frequency (with distance tie-break)
You are given an array **`points`** of 2D integer points, where each point is represented as **`[x, y]`**. The array may contain duplicates (the same **`[x, y]`** can appear multiple times).
Define:

- **`freq(p)`** = number of times point **p** appears in the array.
- **`dist(p)`** = squared Euclidean distance to the origin, **`x^2 + y^2`**. Return **k distinct points** sorted by the following priority:

1. Higher frequency first (**`freq`** descending)
2. If frequencies tie, smaller distance first (**`dist`** ascending)
3. If still tied, sort by **`x`** ascending, then **`y`** ascending

Input

- **`points`**: list of length **n**, each element **`[x, y]`**
- **`k`**: integer, **`1 <= k <= (# of distinct points)`**

Output

- A list of **k** distinct points following the ranking above.

Constraints (typical interview assumptions)

- **`1 <= n <= 2 * 10^5`**
- **`-10^4 <= x, y <= 10^4`** ---

Question

2: Time-based key-value store with “closest timestamp” lookup
Design a data structure supporting the following operations:

- **`set(key, value, timestamp)`**: store the string **`value`** for string **`key`** at integer **`timestamp`**.
- Assume timestamps for the same **`key`** are inserted in **non-decreasing** order.

QUESTION

- **`getClosest(key, timestamp) -> value or ""`**:
- If **`key`** has no stored values, return **`""`**.
- Otherwise, return the **`value`** whose stored timestamp is **closest** to the query **`timestamp`**.
- If there is a tie (equal distance to two timestamps), return the value with the **smaller** timestamp.

Example

If for key **`"a"`** you stored timestamps **`[2, 10, 15]`** with values **`["x", "y", "z"]`**:

- **`getClosest("a", 11)`** returns **`"y"`** (10 is closest)
- **`getClosest("a", 14)`** returns **`"z"`** (15 is closest)
- **`getClosest("a", 12)`** returns **`"y"`** (10 and 15 are equally far; choose smaller timestamp)

What to discuss

- Time and space complexity of your approach - How you would improve a “naive” solution (e.g., linear scan) to a more optimal one

Constraints (typical interview assumptions)

- Up to **`2 * 10^5`** total operations - Keys and values are strings; timestamps are integers within typical 32-bit range

Part 1: Top-K Points by Frequency with Distance
Tie-BreakGiven a list of 2D integer points, where duplicate points may appear, return the top **k** distinct points ranked by these rules: (1) higher frequency first, (2) if frequencies tie, smaller squared distance to the origin first, and (3) if still tied, smaller **x** first, then smaller **y**. The result must contain exactly **k** distinct points in ranked order.
Constraints
1 <= len(points) <= 2 * 10^5-10^4 <= x, y <= 10^41 <= k <= number of distinct points

EXAMPLES

```
Input: ([[1,1],[2,2],[2,2],[1,1],[2,2],[3,3]], 2)
Expected Output: [[2, 2], [1, 1]]
Explanation: Point [2,2] appears 3 times and [1,1]
    appears 2 times, so they are the top 2 distinct
    points.
Input: ([[1,2],[0,2],[1,2],[2,1],[0,2],[2,1],[3,0]],
    3)
Expected Output: [[0, 2], [1, 2], [2, 1]]
Explanation: The points [0,2], [1,2], and [2,1] each
    appear twice. Their squared distances are 4, 5,
    and 5, so [0,2] comes first. Between [1,2] and
    [2,1], x is smaller for [1,2].
```

Hints

First count how many times each point appears. After that, each distinct point only needs to be ranked once.Python can sort tuples directly, so think about building a sort key like **`(-frequency, distance, x, y)`**.
Part 2: Time-Based Key-Value Store with Closest Timestamp QueriesProcess a sequence of operations for a time-based key-value store. Each operation is either **`['set', key, value, timestamp]`** or **`['getClosest', key, timestamp]`**. For every **`getClosest`** operation, return the stored value whose timestamp is closest to the query tim

APPROACH

Count frequencies in a hash map; use a size-k heap with key (frequency desc, distance asc) for Q1, and a max-heap of size k on distance for Q2.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two questions. Q1 (top-K points): confirm the full ordering (higher frequency, then smaller distance, then smaller x, then smaller y) and that K is at most the number of distinct points. Q2 (time-based store): timestamps for a key arrive in non-decreasing order, and a tie in distance returns the smaller timestamp.

BRUTE FORCE TO SAY OUT LOUD

Q1: sort all distinct points with the full key. Q2: linear scan of a key's timestamps. Both are correct and easy to state.

OPTIMAL IDEA

Q1: Counter over tuples, then heapq.nsmallest(k, distinct, key=(-freq, x*x + y*y, x, y)), O(n + d log k). Q2: per key keep parallel lists of timestamps and values; bisect_left finds the first timestamp at least the query; compare it with the previous one and return the closer value, the smaller timestamp on a tie. O(log m) per query.

DRY-RUN THESE CASES

Q1: duplicates, ties on frequency and distance, K equal to the number of distinct points. Q2: query before the first timestamp, after the last, exactly on a timestamp, the tie example (a, 12 returns y), an unknown key.

LIKELY FOLLOW-UPS

Q1: top-K in a stream. Q2: an out-of-order insert (then use a sorted container), deletes, and memory limits.

PITFALLS

Q1: sorting by distance only. Q2: off-by-one at the ends of the list.

HOW TO THINK ABOUT IT

Q1 is a ranking: say the full sort key out loud, count with a hash map, and then you only need the K best (heap), not a full sort. Q2 keeps each key's timestamps in a sorted list, so the nearest one is next to the insertion point: binary search, then compare the two neighbours.

Basis: Two tasks: top K points by (frequency desc, squared distance asc, x asc, y asc), a mix of LeetCode 347 and 973; and a time-based store whose getClosest returns the value at the nearest timestamp (ties to the smaller one), a variant of LeetCode 981.

BRUTE FORCE · Q1: sort all distinct points by the full key

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE · Q1: sort all distinct points by the full key

```
def top_k_points(points, k):
    counts = Counter(map(tuple, points))
    def rank(p):
        x, y = p
        return (-counts[p], x * x + y * y, x, y)
    return sorted(counts, key=rank)[:k]
```

TIME	SPACE
O(d log d)	O(d)

WHY IT IS SLOW

Sorts all d distinct points, O(d log d); a size-K heap with the same key is O(d log k).

BRUTE FORCE · Q2: scan every timestamp of the key

BRUTE FORCE · PSEUDO-CODE

```
def get_closest(key, t):
    best = None
    for ts, value in store[key]:
        gap = abs(ts - t)
        if best is None or (gap, ts) < best[:2]:
            best = (gap, ts, value)
    return best[2]
```

TIME	SPACE
O(m) per query	O(total entries)

WHY IT IS SLOW

Linear in the number of stored timestamps per query. Timestamps arrive in order, so binary search on the sorted list finds the neighbours in O(log m).

OPTIMAL SOLUTION · Q1: heap with the full key

TIME	SPACE
O(n + d log k)	O(d)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Q2: parallel sorted lists and bisect

TIME	SPACE
O(1) per set, O(log m) per getClosest	O(total entries)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Q1 with points arriving over time.

Keep a running Counter and compute the top K on demand with a heap (O(d log k) per query), or maintain a sorted structure updated on every add if queries dominate.

FOLLOW-UP 2 Q2 with timestamps arriving out of order.

The append keeps the list sorted only for in-order input. For arbitrary order keep a sorted list and insert with bisect.insort (O(m) per insert) or a balanced tree (O(log m)); the query is unchanged.

FOLLOW-UP 3 Q2 returns the closest value at or before the timestamp (LeetCode 981).

Use bisect_right(timestamps, ts) - 1 and return that value or an empty string if the index is negative; there is no tie question.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from bisect import bisect_left, bisect_right, insort
from collections import Counter, defaultdict


# BASE QUESTION (optimal): Q1: heap with the full key
def top_points(points, k):
    # more frequent first, then closer to the origin, then
    # x, y
    counts = Counter(map(tuple, points))

    def rank(p):
        dist = p[0] ** 2 + p[1] ** 2
        return (-counts[p], dist, p[0], p[1])

    best = heapq.nsmallest(k, counts, key=rank)
    return [list(p) for p in best]


# FOLLOW-UP 1: Q1 with points arriving over time.
class TopPointsStream:
    # follow-up: points arrive one at a time. The counts
    # are
    # kept as points arrive, so top_k never recounts
    # history.
    def __init__(self):
        self.counts = Counter()

    def add(self, x, y):
        self.counts[(x, y)] += 1

    def top_k(self, k):
        def rank(p):
            dist = p[0] ** 2 + p[1] ** 2
            return (-self.counts[p], dist, p[0], p[1])

        best = heapq.nsmallest(k, self.counts, key=rank)
        return [list(p) for p in best]


# PART 2: closest timestamp value
class TimeStore:
    """set(key, value, ts) and closest-time reads."""
```

```
    def __init__(self):
```

```
        # key -> sorted [(timestamp, value)]
        self.data = defaultdict(list)

    def set(self, key, value, ts):
        # insort also handles timestamps arriving out of
        # order
        insort(self.data[key], (ts, value))

    def get_closest(self, key, ts):
        items = self.data.get(key)
        if not items:
            return ""
        # the first stored time at or after ts, and the
        # one before
        i = bisect_left(items, (ts,))
        options = items[max(0, i - 1):i + 1]
        # closest wins; on a tie the smaller timestamp
        # wins
        def gap(item):
            return (abs(item[0] - ts), item[0])
        best = min(options, key=gap)
        return best[1]

    def get_at_or_before(self, key, ts):
        # LeetCode 981: the latest value not after ts
        items = self.data.get(key, [])
        i = bisect_right(items, (ts, chr(0x10FFFF))) - 1
        return items[i][1] if i >= 0 else ""


if __name__ == "__main__":
    pts = [[1, 1], [1, 1], [2, 0], [0, 2], [2, 0], [3, 3]]
    # (1,1) and (2,0) appear twice; (2,0) is farther? 4 vs
    # 2
    assert top_points(pts, 2) == [[1, 1], [2, 0]]
    four = top_points(pts, 4)
    assert four == [[1, 1], [2, 0], [0, 2], [3, 3]]
    assert top_points([[5, 5]], 1) == [[5, 5]]
    live = TopPointsStream()
    for x, y in pts:
        live.add(x, y)
    assert live.top_k(2) == [[1, 1], [2, 0]]
    live.add(3, 3)
    live.add(3, 3)
    live.add(3, 3)
```

```
    # (3, 3) is now the most frequent point
    assert live.top_k(1) == [[3, 3]]
    s = TimeStore()
    for ts, v in ((2, "x"), (10, "y"), (15, "z")):
        s.set("a", v, ts)
    assert s.get_closest("a", 11) == "y"
    assert s.get_closest("a", 14) == "z"
    # a tie: 10 and 15 are both 2.5 away from 12.5, 12 ->
    # 10
    assert s.get_closest("a", 12) == "y"
    assert s.get_closest("b", 1) == ""
    assert s.get_closest("a", 100) == "z"
    assert s.get_closest("a", -5) == "x"
    assert s.get_at_or_before("a", 14) == "y"
    assert s.get_at_or_before("a", 1) == ""
    s.set("a", "late", 5)
    assert s.get_closest("a", 6) == "late"
```

FUNCTION AND TEST CASES

Signature

```
def solution(points: list[list[int]], k: int) -> list[list
[int]]:
```

Sample call

```
solution([[1,1],[2,2],[2,2],[1,1],[2,2],[3,3]], 2)
```

Test cases

Input	Expected
`([[1,1],[2,2],[2,2],[1,1],[2,2],[3,3] ], 2)`	`[[2, 2], [1, 1]]`
`([[1,2],[0,2],[1,2],[2,1],[0,2],[2,1] ,[3,0]], 3)`	`[[0, 2], [1, 2], [2, 1]]`

MEDIUM | IN APP LC 253 | PracHub | Technical Screen | 80 of 165

★ TOP 75: rank 50 in the Medium and Hard priority list

★ Compute minimum number of rooms needed

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 58 | 30 DAYS 0 | PRIORITY 41/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #253 Meeting Rooms II

LeetCode match: LC 253 Meeting Rooms II

Posted on PracHub: 2026-02-12 (updated 2026-05-04)

Original: https://prachub.com/coding-questions/compute-minimum-number-of-rooms-needed

QUESTION

Problem

You are given a list of meetings, each with a start time and end time. A single room can host only one meeting at a time. Two meetings **overlap** if one starts before the other ends (treat meetings as half-open intervals **[start, end)** so a meeting ending at time `t` does not conflict with another starting at time `t`).

Task

Return the **minimum number of rooms** required to host all meetings.

Input

- `intervals`: an array of `n` pairs `[start, end]` where `0 <= start <= end`.

Output

- An integer: the minimum number of rooms needed.

Constraints (typical interview bounds)

- `1 <= n <= 200000`

QUESTION

- Times are integers in a reasonable range (e.g., `0 . 10^9`).

Example

- Input: `[[0,30],[5,10],[15,20]]`
- Output: `2` (One room can host `[0,30]`, the other can host `[5,10]` then `[15,20]`.)

You are given a list of meetings, where each meeting is represented as [start, end]. A single room can host only one meeting at a time. Meetings are treated as half-open intervals [start, end), so a meeting ending at time t does not conflict with another meeting starting at time t. Return the minimum number of rooms required to host all meetings. If start == end, the meeting occupies no time and does not require a room.
Constraints
0 <= n <= 2000000 <= start <= end <= 10^9

EXAMPLES

```
Input: ([[0,30],[5,10],[15,20]],)
Expected Output: 2
Explanation: [0,30] overlaps with both [5,10] and
    [15,20], so at most 2 rooms are needed at the
    same time.
Input: ([[7,10],[2,4],[4,7],[10,12]],)
Expected Output: 1
```

Explanation: These meetings only touch at endpoints, so one room can host all of them in sequence.

Hints

Try turning each meeting into two events: one when it starts and one when it ends.Because intervals are half-open, if a meeting ends at the same time another starts, process the ending event first.

APPROACH

Sort by start, min-heap of end times (reuse a room when earliest end <= start), or two-pointer sweep on sorted starts/ends. O(n log n).

HOW TO THINK ABOUT IT

The rooms needed equal the largest number of meetings that overlap at one moment. Two ways to find that without checking every moment: sort by start and keep a min-heap of the end times of rooms in use (reuse the room that frees up first), or sort starts and ends separately and sweep with two pointers.

Basis: LeetCode 253, Meeting Rooms II (half-open intervals [start, end): a meeting ending at t does not conflict with one starting at t).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def brute(meetings):
    lo = min(s for s, e in meetings)
    hi = max(e for s, e in meetings)
    best = 0
    for t in range(lo, hi):
        busy = 0
        for s, e in meetings:
            if s <= t < e:
                busy += 1
        best = max(best, busy)
    return best
```

TIME	SPACE
O(range * n)	O(1)

WHY IT IS SLOW

Depends on the length of the time range, O(range * n). A min-heap of room end times, or sorted starts and ends with two pointers, is O(n log n).

OPTIMAL SOLUTION · Sort by start with a min-heap of end times

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Can one person attend all meetings (LeetCode 252)?

Sort by start and check that each meeting ends no later than the next one starts. O(n log n), O(1) extra.

FOLLOW-UP 2 Return which room each meeting uses.

Keep a heap of (end time, room id): reuse the room that frees first, otherwise open the next id, and record the id per meeting.

FOLLOW-UP 3 Meetings arrive online.

Keep the end-time heap between calls: pop every end at or before the new start (those rooms are free), then push the new end. The heap size is the number of rooms in use right now; the peak is the answer so far.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


# BASE QUESTION (optimal): Sort by start with a min-heap
# of end times
def min_meeting_rooms(intervals):
    # half-open [start, end): a meeting ending at t does
    # not
```

```
    # clash with one starting at t. A heap holds the end
    # times
    # of the rooms in use.
    ends = []
    meetings = sorted(m for m in intervals if m[0] < m[1])
    for start, end in meetings:
        if ends and ends[0] <= start:
            # the earliest room is free: reuse it
            heapq.heapreplace(ends, end)
        else:
            heapq.heappush(ends, end)
    return len(ends)


# FOLLOW-UP 1: Can one person attend all meetings
# (LeetCode 252)?
def can_attend_all(intervals):
    # LeetCode 252: one person, no overlap at all
    ordered = sorted(intervals)
    pairs = zip(ordered, ordered[1:])
    return all(a[1] <= b[0] for a, b in pairs)


# FOLLOW-UP 2: Return which room each meeting uses.
def assign_rooms(intervals):
    # which room does each meeting use?
    order = sorted(range(len(intervals)),
                   key=lambda i: intervals[i])
    heap, rooms, used = [], [None] * len(intervals), 0
    for i in order:
        start, end = intervals[i]
        if heap and heap[0][0] <= start:
            _, room = heapq.heappop(heap)
        else:
            room, used = used, used + 1
        rooms[i] = room
        heapq.heappush(heap, (end, room))
```

```
    return rooms


# FOLLOW-UP 3: Meetings arrive online.
class RoomTracker:
    """Meetings arrive online (in order of start time)."""

    def __init__(self):
        self.ends, self.peak = [], 0

    def book(self, start, end):
        # rooms whose meeting already ended are free again
        while self.ends and self.ends[0] <= start:
            heapq.heappop(self.ends)
        heapq.heappush(self.ends, end)
        # the heap size is the rooms in use right now
        self.peak = max(self.peak, len(self.ends))
        return len(self.ends)


if __name__ == "__main__":
    meetings = [(0, 30), (5, 10), (15, 20)]
    assert min_meeting_rooms(meetings) == 2
    assert min_meeting_rooms([(7, 10), (2, 4)]) == 1
    # touching meetings share a room; empty ones need none
    touching = [(1, 3), (3, 5), (4, 4)]
    assert min_meeting_rooms(touching) == 1
    assert min_meeting_rooms([]) == 0
    assert not can_attend_all(meetings)
    assert can_attend_all([(7, 10), (2, 4)])
    rooms = assign_rooms(meetings)
    assert rooms[0] != rooms[1] and rooms[1] == rooms[2]
    t = RoomTracker()
    in_use = [t.book(s, e) for s, e in meetings]
    assert in_use == [1, 2, 2]
```

```
    assert t.peak == 2
```

FUNCTION AND TEST CASES

Signature

```
def solution(intervals: list[list[int]]) -> int:
```

Sample call

```
solution([[0,30],[5,10],[15,20]])
```

Test cases

Input	Expected
`([[0,30],[5,10],[15,20]],)`	`2`
`([[7,10],[2,4],[4,7],[10,12]],)`	`1`

ALSO REPORTED · 4 more

Find Minimum Rooms Needed | PracHub | Technical Screen

https://prachub.com/coding-questions/find-minimum-rooms-needed

Compute minimum rooms for time intervals | PracHub | Technical Screen

https://prachub.com/coding-questions/compute-minimum-rooms-for-time-intervals

Given a list of car rental requests with start and end times, assign cars to rentals such | Exponent

https://www.aced.io/questions/5425/assign-cars-minimize-total-cars-rented

Meeting Rooms / Interval Scheduling Variants | 1Point3Acres | phone-screen, tech-screen, onsite-coding | asked 2026-09-20 | Very high

https://www.1point3acres.com/interview/problems/company/google/meeting-rooms-variants

Asked in Round 1 coding, Round 2 onsite coding, phone screen, and as a warm-up in the FDE loop. Almost every other coding loop contains some flavor of this family.
Interviewer commonly chains two follow-ups: (1) reconstruct assignment, (2) scale out to many shards / regions.
For the assignment follow-up, min-heap keyed on end time is the clean answer: pop the earliest-ending room, push the new interval.
For "distributed across shards", expect open-ended discussion: per-shard sweep, cross-shard merge, reconciliation; the interviewer often acknowledges the question is intentionally vague.
The on-call metadata variant includes detailed complexity follow-ups: account for heap operations, stored employee information, and output size separately, and explain each symbol in the complexity expression.

ALSO REPORTED · 4 more

Preparation: Drill three solutions cold: sweep-line / prefix delta, min-heap on end time, sort + greedy room assignment.
Be ready to convert between the three when interviewers add follow-ups ("give me the assignment", "now handle cyclic days").
Prepare a 1-minute pitch on map-reduce style sharding (per-shard intervals -> merged timeline -> global max).

MEDIUM | PracHub | Technical Screen | 81 of 165

Min boards to cover roof holes

POSTED 2026-02-12 | 240 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 19.6 | 30 DAYS 0 | PRIORITY 149/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #452 Minimum Number of Arrows to Burst Balloons

LeetCode match: No direct match; related LC 1326 Minimum Number of Taps / LC 452 (inferred from overview)

Posted on PracHub: 2026-02-12 (updated 2026-05-05)

Original:
https://prachub.com/coding-questions/min-boards-to-cover-roof-holes

QUESTION

Overview: This question evaluates competency in combinatorial optimization and problem modeling for coverage constraints, testing algorithmic reasoning, complexity analysis, and efficient representation of grid-based data.

APPROACH

Greedy interval cover: sort hole positions, place a board starting at the first uncovered hole, skip all holes within its length, repeat.

INTERVIEW-DAY PLAN

CLARIFY FIRST

My copy has only the overview, so ask: are holes points on a line or cells in a grid, what is the board length, can boards be placed in either orientation, and must each board be axis aligned. The 1D case is a classic interval cover.

BRUTE FORCE TO SAY OUT LOUD

Try every placement of boards. Exponential.

OPTIMAL IDEA

INTERVIEW-DAY PLAN

1D with boards of length L: sort the holes, place a board starting at the first uncovered hole so it covers [h, h + L - 1], skip every hole inside it, repeat. The count is the answer, and the exchange argument shows starting at the leftmost uncovered hole is optimal. O(n log n). For a grid with horizontal boards only, do this per row. If boards can be placed in either orientation covering rows or columns, it becomes a minimum vertex cover in a bipartite graph (Konig's theorem), solved with matching.

DRY-RUN THESE CASES

No holes (0), one hole, holes spread more than L apart, adjacent holes, holes at the same position.

LIKELY FOLLOW-UPS

Boards of different lengths, or a limit on the number of boards.

PITFALLS

Starting a board in the middle of an uncovered gap. Not sorting the holes first.

HOW TO THINK ABOUT IT

Cover the leftmost hole first: any board that covers it can be slid right until it starts exactly at that hole without uncovering anything to its right, so start a board at the leftmost uncovered hole and skip everything it covers. Repeating that is optimal because starting later never covers more.

Basis: Written; interval covering (compare LeetCode 452 and 1326). Assumed rule (confirm it): holes are integer positions on a line, a board of length L covers positions p .. p + L - 1, boards may be placed anywhere; minimise the number of boards.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
best = [INF] * (len(holes) + 1)
best[0] = 0
for i in range(1, len(holes) + 1):
    for j in range(i):
        span = holes[i - 1] - holes[j] + 1
        if span <= L:  # one board covers j..i-1
            best[i] = min(best[i], best[j] + 1)
answer = best[len(holes)]
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Every i tries every j, O(n^2). Starting a board at the leftmost uncovered hole and skipping everything it covers is optimal and O(n log n) including the sort.

OPTIMAL SOLUTION · Greedy: start a board at the leftmost uncovered hole

TIME	SPACE
O(n log n)	O(1) extra

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 You have only K boards: what is the smallest board length that covers all holes?

Binary search the length L and test with the greedy (is the number of boards at most K?); feasibility is monotone in L. O(n log range).

FOLLOW-UP 2 Boards of different lengths with a cost each.

The greedy exchange argument breaks. Use DP over the sorted holes: best[i] = min over board types of best[j] + cost, where j is the first hole not covered by that board starting at hole i.

FOLLOW-UP 3 Holes are in a grid and boards are 1 x L horizontally.

Apply the greedy independently on every row. If boards may also be vertical it becomes a covering problem on a bipartite graph (König's theorem).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left


# BASE QUESTION (optimal): Greedy: start a board at the
# leftmost uncovered hole
def min_boards(holes, length):
    # greedy: the leftmost uncovered hole starts a board,
    # which
    # then covers `length` positions
    count, covered_to = 0, float("-inf")
    for p in sorted(set(holes)):
        if p > covered_to:
            count += 1
            covered_to = p + length - 1
    return count


# FOLLOW-UP 1: You have only K boards: what is the
# smallest board length that covers ...
def smallest_length(holes, k):
    # only k boards: the shortest board length that still
    # covers everything (more length never hurts: binary
    # search)
    pts = sorted(set(holes))
    if not pts:
        return 0
    lo, hi = 1, pts[-1] - pts[0] + 1
    while lo < hi:
        mid = (lo + hi) // 2
        if min_boards(pts, mid) <= k:
            hi = mid
        else:
            lo = mid + 1
    return lo


# FOLLOW-UP 2: Boards of different lengths with a cost
# each.
def min_cost(holes, boards):
    # boards = [(length, cost)], any number of each: a DP
    # over
    # the sorted holes (the greedy no longer works)
    pts = sorted(set(holes))
    INF = float("inf")
    best = [0] * (len(pts) + 1)
    for i in range(len(pts) - 1, -1, -1):
        best[i] = INF
        for length, cost in boards:
            # the first hole this board does not reach
            j = bisect_left(pts, pts[i] + length)
            best[i] = min(best[i], cost + best[j])
    return best[0]


# FOLLOW-UP 3: Holes are in a grid and boards are 1 x L
# horizontally.
def boards_per_row(grid, length):
    # holes in a grid ('#'), horizontal boards: greedy per
    # row
    total = 0
    for row in grid:
        holes = [c for c in range(len(row))
                 if row[c] == "#"]
        total += min_boards(holes, length)
    return total


if __name__ == "__main__":
    assert min_boards([1, 2, 4, 5, 9], 3) == 3
    assert min_boards([], 3) == 0
    assert min_boards([5, 5, 5], 1) == 1
    # with 2 boards the shortest length is 5 (covers 1..5,
    # 9..13)
    assert smallest_length([1, 2, 4, 5, 9], 2) == 5
    assert smallest_length([1, 2, 4, 5, 9], 1) == 9
    assert smallest_length([], 1) == 0
    # a long board costs 5, two short ones cost 3 each
    assert min_cost([1, 2, 3, 10], [(3, 5), (1, 3)]) == 8
    assert min_cost([1, 2, 3, 4], [(2, 3), (4, 5)]) == 5
    roof = ["#.#.", "..##", "...."]
    assert boards_per_row(roof, 2) == 3
```

FUNCTION AND TEST CASES

Signature

```
def solution(roof: list[list[int]]) -> int:
SAMPLE INPUT
[[1,0,1],[0,1,1]]
```

Test cases

Input	Expected
[[1,0,1],[0,1,1]]	2
[[1,1],[1,1]]	0

MEDIUM | IN APP LC 261 | PracHub | Technical Screen | 82 of 165

Validate parent array forms a tree

POSTED 2026-02-11 | 241 DAYS AGO | OLDER

STUDY: TALK ALL TIME 29 30 DAYS 0 PRIORITY 127/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #261 Graph Valid Tree

LeetCode match: LC 261 Graph Valid Tree

Posted on PracHub: 2026-02-11 (updated 2026-04-23)

Original: https://prachub.com/coding-questions/validate-parent-array-forms-a-tree

QUESTION

Problem

You are given an integer array **`parent`** of length **`n`** describing a directed parent pointer for each node **`i`** (nodes are labeled **`0..n-1`**).

- **`parent[i]`** is the parent of node **`i`**.
- Exactly one node should be the root, indicated by **`parent[root] = -1`**. Determine whether these **`n`** nodes form a **valid rooted tree**. A valid rooted tree must satisfy all of the following: 1.

Exactly one root (exactly one index **`i`** with **`parent[i] = -1`**). 2.
No cycles (following parent pointers from any node must eventually reach the root). 3.
Connectivity (every node is reachable from the root; equivalently, every node has exactly one simple path to the root).

Input

- **`parent`**: integer array of length **`n`** where each value is either **`-1`** or in **`[0, n-1]`**.

Output

- Return **`true`** if **`parent`** represents a valid rooted tree; otherwise return **`false`**.

Notes

/ Edge Cases - **`n`** can be 1 (then the only valid tree is **`parent[0] = -1`**).

- Self-parenting like **`parent[i] = i`** is invalid.
- Multiple **`-1`** entries (multiple roots) is invalid.
- A cycle among non-root nodes is invalid.
- A disconnected component (some nodes not reachable from the root) is invalid.

You are given an integer array **`parent`** of length **`n`** describing a parent pointer for each node **`i`** where nodes are labeled **`0`** to **`n-1`**.

- **`parent[i]`** is the parent of node **`i`**.

QUESTION

- Exactly one node should be the root, indicated by **`parent[root] = -1`**. Determine whether these nodes form a valid rooted tree. A valid rooted tree must satisfy all of the following:

1. Exactly one root.
2. No cycles.
3. Every node belongs to the same connected structure and has a path to the root. Return **`True`** if **`parent`** represents a valid rooted tree; otherwise return **`False`**.

Constraints
1 <= n <= 2 * 10^5Each **`parent[i]`** is either **`-1`** or an integer in **`[0, n-1]parent[i] = i`** is invalid

EXAMPLES

```
Input: [-1, 0, 0, 1, 1]
Expected Output: True
```

Explanation: Node 0 is the only root. All other nodes are connected under it, and there are no cycles.

```
Input: [2, -1, 1, 2]
Expected Output: True
Explanation: Node 1 is the root. The paths are
    0->2->1, 2->1, and 3->2->1, so every node reaches
    the same root.
```

Hints

First count how many roots there are. A valid tree must have exactly one **`-1`** entry.Build children lists from the parent array, then traverse from the root. If you do not visit every node, the structure is disconnected or contains a cycle away from the root.

APPROACH

Exactly one root (parent = -1 or self), every other node has one parent; detect cycles by walking up with a visited set or union-find; all nodes must reach the root. O(n).

HOW TO THINK ABOUT IT

Exactly one -1 gives the root; then the rest is whether every node reaches it. Following parents from each node can loop (a cycle) or run out of range. Do it with memoised walks so every node is processed once: mark nodes on the current walk, and if the walk meets one of them again it is a cycle; if it meets a node already known to reach the root, all nodes on the walk reach it too.

Basis: LeetCode 261 (Graph Valid Tree) in parent-pointer form: exactly one root (-1), no cycles, every node reaches the root.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def is_tree(parent):
    n = len(parent)
    roots = [i for i in range(n)
             if parent[i] == -1]
    if len(roots) != 1:
        return False
    if any(p >= n for p in parent):
        return False
    for node in range(n):
        cur, steps = node, 0
        while cur != -1 and steps <= n:
            cur = parent[cur]
            steps += 1
        if cur != -1:
            return False  # a cycle
    return True
```

TIME	SPACE
O(n^2)	O(1)

WHY IT IS SLOW

Every node walks its whole chain, O(n^2). Marking nodes as 'on this walk' or 'verified' lets every node be processed once, O(n).

OPTIMAL SOLUTION · One root, then colour each node once while walking up

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The graph is given as undirected edges (LeetCode 261).

A tree has exactly n - 1 edges and no cycle: check the edge count, then union endpoints and fail on an edge that joins two nodes already connected. O(n alpha(n)).

FOLLOW-UP 2 Report the reason it is invalid.

Return which rule failed: number of roots, an out-of-range parent, or the node where the cycle was detected (the node that was met twice on one walk).

FOLLOW-UP 3 A binary tree given as child arrays (LeetCode 1361).

Check that exactly one node has in-degree 0, every other node has in-degree 1, and that a traversal from the root visits all n nodes.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict


# FOLLOW-UP 2: Report the reason it is invalid.
def reason(parent):
    # None if valid, else the first rule that fails
    n = len(parent)
    roots = parent.count(-1)
    if roots != 1:
        return f"{roots} roots (need exactly 1)"
    for i, p in enumerate(parent):
        if p != -1 and not 0 <= p < n:
            return f"node {i}: out-of-range parent {p}"
        if p == i:
            return f"node {i} is its own parent"
    # 0 = unseen, 1 = on the current walk, 2 = checked
    state = [0] * n
    for start in range(n):
        path, x = [], start
        while x != -1 and state[x] == 0:
            state[x] = 1
            path.append(x)
            x = parent[x]
        # meeting a node twice on one walk is a cycle
        if x != -1 and state[x] == 1:
            return f"cycle through node {x}"
        for v in path:
            state[v] = 2
    return None


# BASE QUESTION (optimal): One root, then colour each node
# once while walking up
def validate_parent_array(parent):
    return reason(parent) is None


# FOLLOW-UP 1: The graph is given as undirected edges
# (LeetCode 261).
def valid_tree_edges(n, edges):
    # LeetCode 261: undirected edges
    if len(edges) != n - 1:
        return False
    root = list(range(n))
```

```
    def find(x):
        while root[x] != x:
            root[x] = root[root[x]]
            x = root[x]
        return x

    for u, v in edges:
        a, b = find(u), find(v)
        # an edge inside a group closes a cycle
        if a == b:
            return False
        root[a] = b
    return True


# FOLLOW-UP 3: A binary tree given as child arrays
# (LeetCode 1361).
def valid_binary_tree(n, left, right):
    # LeetCode 1361: child arrays, -1 means no child
    indeg = [0] * n
    for kids in (left, right):
        for c in kids:
            if c != -1:
                indeg[c] += 1
    roots = [i for i in range(n) if indeg[i] == 0]
    if len(roots) != 1 or max(indeg) > 1:
        return False
    seen, stack = {roots[0]}, [roots[0]]
    while stack:
```

```
        u = stack.pop()
        for c in (left[u], right[u]):
            if c != -1:
                if c in seen:
                    return False
                seen.add(c)
                stack.append(c)
    # every node must be reachable from the root
    return len(seen) == n


if __name__ == "__main__":
    assert validate_parent_array([-1, 0, 0, 1])
    assert validate_parent_array([-1])
    # two roots, none, and a cycle 1 -> 2 -> 1
    assert not validate_parent_array([-1, -1])
```

```
    assert not validate_parent_array([1, 0])
    assert "cycle" in reason([-1, 2, 1])
    assert not validate_parent_array([-1, 5])
    assert "out-of-range" in reason([-1, 5])
    assert "own parent" in reason([-1, 1])
    star = [(0, 1), (0, 2), (0, 3), (1, 4)]
    assert valid_tree_edges(5, star)
    loop = [(0, 1), (1, 2), (2, 0)]
    assert not valid_tree_edges(4, loop)
    left, right = [1, -1, 3, -1], [2, -1, -1, -1]
    assert valid_binary_tree(4, left, right)
    assert not valid_binary_tree(2, [1, 0], [-1, -1])
```

FUNCTION AND TEST CASES

Signature

```
def solution(parent: list[int]) -> bool:
SAMPLE INPUT
[-1, 0, 0, 1, 1]
```

Test cases

Input	Expected
[-1, 0, 0, 1, 1]	True
[2, -1, 1, 2]	True

MEDIUM | PracHub | Technical Screen | 83 of 165

Determine whether two nodes are related

POSTED 2026-01-22 | 261 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 24.5 | 30 DAYS 0 | PRIORITY 141/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

LeetCode match: LC 1971 Find if Path Exists in Graph (inferred from overview)

Posted on PracHub: 2026-01-22 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/determine-whether-two-nodes-are-related

QUESTION

Overview: This question evaluates understanding of graph representations, reachability and connectivity concepts for ancestry relationships, including handling disconnected components and potential cycles.

APPROACH

Build the ancestry graph and BFS/DFS (or union-find for undirected relatedness); handle disconnected components.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what related means: one is an ancestor of the other, they share a common ancestor, or they are connected in any direction. Ask whether the graph is a tree, a DAG, or may have cycles, and whether it is disconnected.

BRUTE FORCE TO SAY OUT LOUD

DFS from the first node looking for the second, and again from the second. O(V + E) per query.

OPTIMAL IDEA

Build the adjacency list once. For ancestry in a DAG compute the ancestor set of each node (DFS or BFS) and test for the target or a non-empty intersection. For undirected relatedness use union-find, which answers queries in near constant time after one pass. Track visited to survive cycles.

DRY-RUN THESE CASES

A node related to itself, two nodes in separate components, a long chain, a cycle.

LIKELY FOLLOW-UPS

Many queries (precompute components or ancestors), the lowest common ancestor, or updates to the graph.

PITFALLS

Missing a visited set. Treating direction as undirected, or the reverse.

HOW TO THINK ABOUT IT

Ask what 'related' means: connected in any direction (a connectivity question: union-find or one traversal), or ancestor/descendant, or share an ancestor. With many queries, preprocess once: components give O(1) answers. Always make the visited set part of the design, since relationship data can have cycles.

Basis: LeetCode 1971, Find if Path Exists in Graph, for connectivity, and ancestor queries on a parent map for the 'ancestry' reading. Assumed meaning (confirm it): related = connected by any path of relationships.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def related(a, b):
    graph = build_adjacency(edges)
    seen = set()
    dfs(graph, a, seen)
    return b in seen
```

TIME	SPACE
O(V + E) per query	O(V)

WHY IT IS SLOW

Every query repeats the same traversal, O(V + E) each. A Union-Find built once answers each query in near-constant time.

OPTIMAL SOLUTION · Union-Find built once, constant-time queries

TIME	SPACE
O(E alpha(V)) to build, O(alpha(V)) per query	O(V)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 'Related' means ancestor or descendant, or sharing an ancestor.

Store the data as a parent map and walk up from one node while recording ancestors, then walk up from the other until you hit one. Keep a seen set so a corrupt cycle cannot loop forever.

FOLLOW-UP 2 Relationships arrive over time and you must answer queries between updates.

Union-Find handles incremental unions in near-constant time. If relationships can also be removed, you need offline processing or a dynamic-connectivity structure.

FOLLOW-UP 3 The graph is directed and 'related' means reachability from a to b.

Union-Find no longer works (it ignores direction). Use DFS/BFS per query, or compute strongly connected components and reachability on the condensed DAG for many queries.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


# BASE QUESTION (optimal): Union-Find built once,
# constant-time queries
class Relations:
    """Related = joined by a chain of relations."""

    def __init__(self, n, edges=()):
        self.parent = list(range(n))
        self.size = [1] * n
        for u, v in edges:
            self.union(u, v)

    def find(self, x):
        while self.parent[x] != x:
            self.parent[x] = self.parent[self.parent[x]]
            x = self.parent[x]
        return x

    def union(self, a, b):
        # relations can arrive over time: near-constant
        # time
        ra, rb = self.find(a), self.find(b)
        if ra == rb:
            return
        # the smaller group joins the bigger one
        if self.size[ra] < self.size[rb]:
            ra, rb = rb, ra
        self.parent[rb] = ra
        self.size[ra] += self.size[rb]

    def related(self, a, b):
        return self.find(a) == self.find(b)


# HELPER: ancestors of a node
def ancestors(parent, x):
    # x and everything above it; a seen set stops cycles
    seen = []
    while x is not None and x not in seen:
        seen.append(x)
        x = parent.get(x)
    return seen


# FOLLOW-UP 1: 'Related' means ancestor or descendant, or
# sharing an ancestor.
def kin(parent, a, b):
    # related if one is an ancestor of the other, or they
    # share an ancestor
    up_a = ancestors(parent, a)
    up_b = ancestors(parent, b)
    return bool(set(up_a) & set(up_b))


# FOLLOW-UP 3: The graph is directed and 'related' means
# reachability from a to b.
def reachable(graph, a, b):
    # directed: can we get from a to b? (Union-Find cannot
    # tell, it ignores direction)
    seen, queue = {a}, deque([a])
    while queue:
        u = queue.popleft()
        if u == b:
            return True
        for v in graph.get(u, ()):
            if v not in seen:
                seen.add(v)
                queue.append(v)
    return False


if __name__ == "__main__":
    r = Relations(5, [(0, 1), (1, 2)])
    assert r.related(0, 2) and not r.related(0, 3)
    r.union(3, 4)
    assert r.related(3, 4) and not r.related(2, 4)
```

```
    r.union(2, 3)
    assert r.related(0, 4)
    assert r.related(1, 1)
    # a family tree: parent[child] = parent
    parent = {"kid": "mom", "mom": "gran",
              "uncle": "gran", "stranger": None}
    assert kin(parent, "kid", "gran")
    assert kin(parent, "kid", "uncle")
    assert not kin(parent, "kid", "stranger")
    # a corrupt cycle cannot loop forever
    assert kin({"a": "b", "b": "a"}, "a", "b")
    # direction matters for reachability
```

```
    g = {"a": ["b"], "b": ["c"]}
    assert reachable(g, "a", "c")
    assert not reachable(g, "c", "a")
```

FUNCTION AND TEST CASES

Signature

```
def solution(relations: list[list[int]], a: int, b: int) -
> bool:
```

Sample call

```
solution([(1, 2), (1, 3), (3, 4), (10, 11)], 2, 4)
```

Test cases

Input	Expected
`[(1, 2), (1, 3), (3, 4), (10, 11)], 2, 4)`	`True`
`[(1, 2), (1, 3), (3, 4), (10, 11)], 2, 11)`	`False`

MEDIUM | PracHub | Technical Screen | 84 of 165

Solve matrix groups and recipe inventory

POSTED 2026-01-22 | 261 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 33.8 | 30 DAYS 0 | PRIORITY 112/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #2115 Find All Possible Recipes from Given Supplies

LeetCode match: No direct match; related LC 2115 Find All Possible Recipes from Given Supplies (inferred from overview)

Posted on PracHub: 2026-01-22 (updated 2026-05-12)

Original: https://prachub.com/coding-questions/solve-matrix-groups-and-recipe-inventory

QUESTION

Overview: This pair of problems evaluates block-wise grid processing and aggregation for minimum-value selection alongside dependency-resolution and resource-allocation reasoning for recipe inventory planning, testing competencies in array manipulation, tie-breaking and constraint handling, graph-based dependency management and cycle detection, and algorithmic complexity analysis; they are commonly asked to gauge an applicant's ability to implement correct, efficient solutions under input-size and edge-case constraints. They belong to the Coding & Algorithms domain with subdomains in data structures (arrays/grids), algorithm design and analysis, and graph theory, and primarily require practical application of algorithmic techniques with attention to time/space complexity rather than purely theoretical proofs.

APPROACH

Part 1: iterate block by block and take the min per group. Part 2: topological sort/DFS over recipe dependencies with an inventory map.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two parts. Matrix groups: how the grid is split into blocks (group size) and what is taken per block (the minimum). Recipes: can a recipe be made from supplies, do recipes need other recipes, are amounts counted or only availability (LeetCode 2115 is availability), how are cycles treated.

BRUTE FORCE TO SAY OUT LOUD

Matrix: scan each block directly. Recipes: recursive search from each recipe without memory.

OPTIMAL IDEA

Matrix: iterate block by block with nested loops and take the minimum of each block, O(mn). Recipes: build a graph from ingredients to recipes with in-degrees and run Kahn's algorithm starting from the supplies; a recipe becomes available when all its ingredients are; recipes on a cycle never become available. If quantities matter, DFS with memoization over recipes tracking inventory, and decide how to share a scarce ingredient between recipes.

DRY-RUN THESE CASES

A grid not divisible by the block size, a recipe whose ingredient is another recipe, a cycle between two recipes, a missing ingredient, an empty supply list.

LIKELY FOLLOW-UPS

Amounts per ingredient (resource allocation), the maximum number of each recipe, or the cheapest set of recipes.

PITFALLS

Treating availability as quantities. Not handling a cycle.

HOW TO THINK ABOUT IT

Blocks: visit each cell once and update the minimum of its block, indexed by (row // k, col // k). Recipes: this is a dependency graph; a recipe is makeable when all its ingredients are supplies or makeable recipes. Count unmet ingredients per recipe and process recipes as they become available (Kahn's algorithm); recipes on a cycle never become available.

Basis: Two parts (my copy has only the overview, so the rules are assumed): take the minimum of every k x k block of a matrix, and decide which recipes can be made from supplies where recipes may need other recipes (LeetCode 2115, Find All Possible Recipes).

BRUTE FORCE · Blocks: collect each block's values and call min

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid, h, w):
    answers = []
    for block in blocks(grid, h, w):
        cells = []
        for r, c in block:
            cells.append(grid[r][c])
        answers.append(min(cells))
    return answers
```

TIME	SPACE
O(m * n)	O(m * n)

WHY IT IS SLOW

Copies every block into a list. One pass that updates the minimum of cell (r // k, c // k) needs no copies.

BRUTE FORCE · Recipes: keep re-scanning until no recipe changes

BRUTE FORCE · PSEUDO-CODE

```
available = set(supplies)
while True:
    added = False
    for recipe in recipes:
        if recipe.name in available:
            continue
        needs = recipe.needs
        if all(i in available for i in needs):
            available.add(recipe.name)
            added = True
    if not added:
        break
```

TIME	SPACE
O(R^2 * I)	O(R)

WHY IT IS SLOW

Many passes over all recipes, O(R^2 * I). Counting each recipe's missing ingredients and processing items as they become available (Kahn's algorithm) is O(R + I).

OPTIMAL SOLUTION · Blocks: one pass updating a minimum per block

TIME	SPACE
O(m * n)	O(blocks)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Recipes: Kahn's algorithm on the ingredient graph

TIME	SPACE
O(R + I)	O(R + I)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Ingredients have quantities and a shared ingredient can only be used once.

Then availability is not enough: you also have to decide the order in which to spend scarce items. A priority order with a simulation (as coded) is a heuristic; the exact maximum is a resource-allocation problem (flow or integer programming).

FOLLOW-UP 2 Blocks that do not tile the matrix exactly.

The last block row or column is smaller; the single-pass update handles that automatically because the block index is r // k and c // k.

FOLLOW-UP 3 Detect which recipes are impossible because of a cycle.

After Kahn's algorithm, recipes whose counts never reached zero are either missing an ingredient or on a cycle; a DFS with colours over just those recipes tells the two cases apart.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict, deque


# BASE QUESTION (optimal): Blocks: one pass updating a
# minimum per block
def block_mins(matrix, k):
    # the minimum of every k x k block; edge blocks may be
    # smaller, which r // k and c // k handle by
    # themselves
    m, n = len(matrix), len(matrix[0])
    rows, cols = (m + k - 1) // k, (n + k - 1) // k
    out = [[float("inf")] * cols for _ in range(rows)]
    for r in range(m):
        for c in range(n):
            cell = out[r // k][c // k]
            out[r // k][c // k] = min(cell, matrix[r][c])
    return out
```

```
# PART 2: which recipes can be made
def possible_recipes(recipes, supplies):
    # recipes: name -> list of ingredients (which may be
    # other
    # recipes). Kahn's algorithm over missing-ingredient
    # counts.
    have = set(supplies)
    missing, users = {}, defaultdict(list)
    for name, items in recipes.items():
        missing[name] = 0
        for item in set(items):
            if item not in have:
                missing[name] += 1
                users[item].append(name)
    queue = deque(r for r, m in missing.items() if m == 0)
    made = []
    while queue:
        name = queue.popleft()
        made.append(name)
        # a finished recipe is a new ingredient for its
        # users
        for other in users[name]:
            missing[other] -= 1
            if missing[other] == 0:
                queue.append(other)
    return made
```

```
# FOLLOW-UP 3: Detect which recipes are impossible because
# of a cycle.
def why_impossible(recipes, supplies):
    # for each recipe that cannot be made: a missing raw
    # ingredient, or a cycle
    made = set(possible_recipes(recipes, supplies))
    known = set(supplies) | set(recipes)
    reasons = {}
    for name, items in recipes.items():
        if name in made:
            continue
        gone = [i for i in items if i not in known]
        reasons[name] = "cycle"
        if gone:
            reasons[name] = "missing " + gone[0]
    return reasons


# FOLLOW-UP 1: Ingredients have quantities and a shared
# ingredient can only be used ...
def recipes_with_quantities(recipes, needs, stock):
    # ingredients have amounts and stock is used up. Make
    # each recipe at most once, in priority order, while
    # the
    # stock allows (a made recipe is new stock). This is a
    # heuristic: the exact best choice is a flow problem.
    stock, made = dict(stock), []
    progress = True
    while progress:
        progress = False
        for name, need in zip(recipes, needs):
            if name in made:
                continue
            enough = all(stock.get(x, 0) >= q
                         for x, q in need.items())
            if enough:
                for x, q in need.items():
                    stock[x] -= q
                stock[name] = stock.get(name, 0) + 1
                made.append(name)
                progress = True
    return made
```

```
if __name__ == "__main__":
    matrix = [[5, 3, 8, 1], [2, 9, 4, 7], [6, 0, 3, 2]]
    # 2 x 2 blocks, the last row of blocks is only 1 row
    # tall
    assert block_mins(matrix, 2) == [[2, 1], [0, 2]]
    assert block_mins([[4]], 3) == [[4]]
    recipes = {"bread": ["flour", "yeast"],
               "sandwich": ["bread", "meat"],
               "burger": ["bread", "meat", "bun"]}
    stock = ["flour", "yeast", "meat"]
    got = possible_recipes(recipes, stock)
    assert got == ["bread", "sandwich"]
    # two recipes that need each other, and a missing item
    cyc = {"a": ["b"], "b": ["a"], "c": ["x"]}
    assert possible_recipes(cyc, []) == []
    assert why_impossible(cyc, []) == {"a": "cycle",
                                       "b": "cycle",
                                       "c": "missing x"}
    # amounts: one bread uses the only 2 flour, so the
    # cake
    # (which needs 2 flour too) cannot be made
    names = ["bread", "cake"]
    needs = [{"flour": 2}, {"flour": 2}]
    two = {"flour": 2}
    made = recipes_with_quantities(names, needs, two)
    assert made == ["bread"]
    four = {"flour": 4}
    both = recipes_with_quantities(names, needs, four)
    assert both == ["bread", "cake"]
```

FUNCTION AND TEST CASES

Signature

```
def solution(grid: list[list[int]]) -> list[int]:
```

Sample call

```
solution([[5,4,3,9,8,7],[6,2,8,5,4,6],[7,3,9,8,2,5],[10,11
,12,0,3,4],[9,8,7,6,5,4],[3,2,9,7,8,9]])
```

Test cases

Input	Expected
`([[5,4,3,9,8,7],[6,2,8,5,4,6],[7,3,9,8,2,5],[10,11,12,0,3,4],[9,8,7,6,5,4],[3,2,9,7,8,9]],)`	`(0, 3, 3)`
`([[-1,5,6,-1,7,8],[9,10,11,12,13,14],[15,16,17,18,19,20],[21,22,23,24,25,26],[27,28,29,30,31,32],[33,34,35,36,37,38]],)`	`(-1, 0, 0)`

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 85 of 165

Find top/bottom-k words in list or stream

POSTED 2026-01-11 | 272 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 32.6 | 30 DAYS 0 | PRIORITY 116/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #692 Top K Frequent Words

LeetCode match: LC 692 Top K Frequent Words (+ stream variant)

Posted on PracHub: 2026-01-11 (updated 2026-05-26)

Original: https://prachub.com/coding-questions/find-top-bottom-k-words-in-list-or-stream

QUESTION

You are given words (strings) either as a finite list or as an unbounded stream. 1)
List version: Given an array **`words`** and an integer **k**, return: - the **k** most frequent distinct words, and - the **k** least frequent distinct words. Specify how you break ties (e.g., lexicographically, or any order). 2)
Stream version (online): Design a data structure that supports:

- **`ingest(word)`**: process the next word in the stream - **`topK(k)`**: return the **k** most frequent distinct words seen so far - **`bottomK(k)`**: return the **k** least frequent distinct words seen so far Discuss time/space complexity and how you would implement these operations efficiently. 3)

Variant (discuss/design): Extend the stream design to support returning the **first k** and/or **last k** words that are currently **non-repeating** (i.e., words with frequency exactly 1) according to stream arrival order.

Part 1: Top and Bottom K Frequent Words in a ListGiven an array of strings words and a non-negative integer k, return two lists: the k most frequent distinct words and the k least frequent distinct words. Use deterministic tie-breaking: if two words have the same frequency, the lexicographically smaller word comes first. If k is larger than the number of distinct words, return all distinct words.
Constraints
0 <= len(words) <= 2 * 10^50 <= k <= 2 * 10^5Each word is a non-empty stringComparison is case-sensitive unless otherwise stated

QUESTION

EXAMPLES

```
Input: (['i', 'love', 'leetcode', 'i', 'love',
    'coding'], 2)
Expected Output: [['i', 'love'], ['coding',
    'leetcode']]
Explanation: `i` and `love` both appear twice, so
    lexicographical order gives `['i', 'love']`.
    `coding` and `leetcode` both appear once, so
    lexicographical order gives `['coding',
    'leetcode']`.
Input: (['apple', 'banana', 'apple', 'cherry',
    'banana', 'date'], 3)
Expected Output: [['apple', 'banana', 'cherry'],
    ['cherry', 'date', 'apple']]
```

Explanation: Frequencies are: apple=2, banana=2, cherry=1, date=1. Top 3 are ordered by frequency descending, then lexicographically: **`apple`**, **`banana`**, **`cherry`**. Bottom 3 are ordered by frequency ascending, then lexicographically: **`cherry`**, **`date`**, **`apple`**.

Hints
Count how many times each distinct word appears before deciding the answer.You can sort the distinct words twice: once by (-frequency, word) and once by (frequency, word).
Part 2: Online Top/Bottom K Words from a StreamYou are given a sequence of stream operations. Each operation is a 2-element list of strings: ['ingest', word], ['topK', str(k)], or ['bottomK', str(k)]. Process the operations in order. For each query, return the k most frequent or k least frequent distinct words seen so far. Ties are broken lexicographically ascending. If k is larger than the number of distinct words seen so far, return all distinct words.
Constraints
1 <= len(operations) <= 2 * 10^5Each operation is one of ['ingest', word], ['topK', str(k)], or ['bottomK', str(k)]0 <= k <= 2 * 10^5Queries may appear before any word is ingested
Examples
Input: [['ingest', 'apple'], ['ingest', 'banana'], ['ingest', 'apple'], ['topK', '2'], ['bottomK', '2']]
Expected Output: [['apple', 'banana'], ['banana', 'apple']]
Explanation: After the ingests, counts are apple=2 and banana=1. topK(2) returns the most frequent first, while bottomK(2) returns the least frequent first.

Input: [['topK', '3'], ['ingest', 'dog'], ['ingest', 'cat'], ['ingest', 'cat'], ['topK', '2'], ['bottomK', '2'], ['topK', '5']]
Expected Output: [[], ['cat', 'dog'], ['dog', 'cat'], ['cat', 'dog']]
Explanation: The first query happens before any words are seen, so it returns []. Later, cat has frequency 2 and dog has frequency 1.
Hints
Keep an exact frequency map for all words seen so far.A max-heap and a min-heap with lazy deletion let you support online updates without fully resorting all words

APPROACH

List: counts + heaps (min-heap size k for top, max-heap size k for bottom). Stream: keep counts in a map and maintain heaps with lazy updates, or approximate with Space-Saving / Count-Min when memory is bounded.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask how ties break, whether top and bottom are over distinct words, what topK(k) returns for k larger than the number of words, and whether memory is bounded for the stream.

BRUTE FORCE TO SAY OUT LOUD

Count words, sort all distinct words by (count, word), take the first and last K. O(d log d).

OPTIMAL IDEA

List version: Counter, then heapq.nlargest and nsmallest with the key (count, word) in the right directions, O(n + d log K). Stream version: ingest increments a dict in O(1); topK and bottomK compute on demand with a heap in O(d log K). If queries are frequent, keep words grouped by count in buckets (a linked list of count buckets like an LFU cache) so topK walks from the highest bucket in O(K). If memory is bounded, the Space-Saving or Count-Min sketch approximates the top K; bottom-K cannot be approximated well, so say so.

DRY-RUN THESE CASES

Fewer words than K, all counts equal (ties decide everything), one word repeated, an empty stream.

LIKELY FOLLOW-UPS

Windowed counts (expire old words), or distributed counting with a merge step.

PITFALLS

Mixing up the direction for the bottom-K heap. Missing a deterministic tie-break.

HOW TO THINK ABOUT IT

Count first; then you only need the K best and K worst, which a heap does without sorting everything. For a stream, ingesting is just a counter increment, and the answer is computed from the counts on demand. If memory is bounded, only heavy hitters (top-K) can be approximated; the rarest words cannot.

Basis: LeetCode 692 (Top K Frequent Words) and its bottom-K counterpart, plus a streaming interface. Ties break alphabetically.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(words, k):
    counts = Counter(words)
    def rank(w):
        return (-counts[w], w)
    ranked = sorted(counts, key=rank)
    most = ranked[:k]
    least = ranked[::-1][:k]
    return most, least
```

BRUTE FORCE

TIME	SPACE
O(d log d)	O(d)

WHY IT IS SLOW

Sorts all d distinct words, O(d log d). Two heaps of size K are O(d log k); a stream only needs the counts, and a Space-Saving sketch bounds memory for the top K.

OPTIMAL SOLUTION · Counter plus two heaps of size K

TIME	SPACE
O(n + d log k)	O(d)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The stream is too big to count every distinct word.

Use the Space-Saving (or Misra-Gries) summary with m counters: a word that appears more than n / m times is guaranteed to be tracked, and its stored count is an upper bound. This works for the top K only; the least frequent words cannot be found this way.

FOLLOW-UP 2 topK must be O(k), not O(d log k), because it is called all the time.

Keep words in buckets by count (a linked list of count buckets, like the LFU cache structure); the most frequent words are in the last bucket. An increment moves a word one bucket up in O(1).

FOLLOW-UP 3 Case and punctuation.

Normalise before counting (lowercase, strip punctuation) and say so; the counting and ranking code is unchanged.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import Counter, defaultdict


# BASE QUESTION (optimal): Counter plus two heaps of size
# K
def top_bottom(words, k):
    # ties are broken alphabetically
    c = Counter(words)
    top = heapq.nsmallest(k, c, key=lambda w: (-c[w], w))
    low = heapq.nsmallest(k, c, key=lambda w: (c[w], w))
    bottom = low
    return top, bottom


# FOLLOW-UP 2: topK must be O(k), not O(d log k), because
# it is called all the time.
class FreqBuckets:
    """Stream: add(word) is O(1); top_k reads only the
```

```
    highest count buckets."""

    def __init__(self):
        self.count = defaultdict(int)
        # count -> words with exactly that count
        self.bucket = defaultdict(dict)
        self.high = 0

    def add(self, word):
        c = self.count[word]
        if c:
            # move the word up one bucket
            del self.bucket[c][word]
            if not self.bucket[c]:
                del self.bucket[c]
        self.count[word] = c + 1
        self.bucket[c + 1][word] = True
        self.high = max(self.high, c + 1)

    def top_k(self, k):
        out = []
        level = self.high
        while level > 0 and len(out) < k:
            # words inside one bucket: alphabetical
            out += sorted(self.bucket.get(level, ()))
            level -= 1
        return out[:k]

    def bottom_k(self, k):
        out = []
        for level in sorted(self.bucket):
            out += sorted(self.bucket[level])
            if len(out) >= k:
                break
        return out[:k]


# FOLLOW-UP 1: The stream is too big to count every
# distinct word.
class SpaceSaving:
    """Too many distinct words: m counters. A word seen
    over n / m times is always tracked."""

    def __init__(self, m):
        self.m, self.counts = m, {}

    def add(self, word):
        if word in self.counts:
            self.counts[word] += 1
        elif len(self.counts) < self.m:
            self.counts[word] = 1
        else:
            # replace the smallest counter; the new word
            # inherits its count + 1 (an upper bound)
            low = min(self.counts, key=self.counts.get)
            self.counts[word] = self.counts.pop(low) + 1

    def top_k(self, k):
        return sorted(self.counts, key=lambda w: (
            -self.counts[w], w))[:k]


# FOLLOW-UP 3: Case and punctuation.
def normalise(text):
    # case and punctuation: clean before counting
    letters = (ch for ch in text.lower() if ch.isalnum())
    return "".join(letters)


if __name__ == "__main__":
    words = "a b a c b a d d".split()
    top, bottom = top_bottom(words, 2)
    assert top == ["a", "b"] and bottom == ["c", "b"]
    f = FreqBuckets()
    for w in words:
        f.add(w)
    assert f.top_k(2) == ["a", "b"]
    assert f.bottom_k(2) == ["c", "b"]
    assert f.top_k(10) == ["a", "b", "d", "c"]
    s = SpaceSaving(2)
    for w in "x x x y z x x":
        s.add(w) if w.strip() else None
    assert s.top_k(1) == ["x"]
    assert normalise("Hello, World!") == "helloworld"
```

FUNCTION AND TEST CASES

Signature

```
def solution(words: list[str], k: int) -> list[list[str]]:
```

Sample call

```
solution(['i', 'love', 'leetcode', 'i', 'love', 'coding'],
 2)
```

Test cases

Input	Expected
`(['i', 'love', 'leetcode', 'i', 'love', 'coding'], 2)`	`[['i', 'love'], ['coding', 'leetcode']]`
`(['apple', 'banana', 'apple', 'cherry', 'banana', 'date'], 3)`	`[['apple', 'banana', 'cherry'], ['cherry', 'date', 'apple']]`

MEDIUM | IN APP LC 542 | PracHub | Technical Screen | 86 of 165

Compute distance to nearest taxi in grid

POSTED 2026-01-10 | 273 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 36.5 | 30 DAYS 0 | PRIORITY 101/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #542 01 Matrix

LeetCode match: LC 542 01 Matrix (inferred from overview)

Posted on PracHub: 2026-01-10 (updated 2026-06-20)

Original: https://prachub.com/coding-questions/compute-distance-to-nearest-taxi-in-grid

QUESTION

Overview: This question evaluates understanding of graph traversal and shortest-path reasoning on grids, algorithmic problem-solving for computing distances from many targets, and the ability to manage time and space complexity on large inputs.

APPROACH

Multi-source BFS from all taxis simultaneously; the BFS level is the distance for each cell. O(mn).

HOW TO THINK ABOUT IT

Asking for the distance from every cell to its nearest source is one BFS started from all sources at once, not one BFS per cell. Put all taxis in the queue at distance 0; the first time the search reaches a cell is its shortest distance, because BFS visits cells in order of distance.

Basis: LeetCode 542, 01 Matrix, with 'T' for a taxi, '#' for a blocked cell and '.' for open ground. Distance counts moves through open cells (4-directional).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def nearest_taxi(grid, start):
    queue, seen = deque([(start, 0)]), {start}
    while queue:
        cell, d = queue.popleft()
        if is_taxi(grid, cell):
            return d
        for nxt in neighbours(grid, cell):
            if nxt not in seen:
                seen.add(nxt)
                queue.append((nxt, d + 1))
    return -1
answer = {}
for c in cells:
    answer[c] = nearest_taxi(grid, c)
```

TIME	SPACE
O((m * n)^2)	O(m * n)

WHY IT IS SLOW

A separate BFS per cell, O((m * n)^2). One BFS that starts from all taxis at once reaches every cell at its nearest-taxi distance, O(m * n).

OPTIMAL SOLUTION · One multi-source BFS

TIME	SPACE
O(m * n)	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 A new taxi appears.

Start a BFS from the new taxi but only continue into cells where you improve the stored distance. The distances can only decrease, so the work is bounded by the cells whose answer actually changes.

FOLLOW-UP 2 Taxis move or disappear.

Distances can increase, which the decrease-only update cannot handle. Rebuild with one multi-source BFS (O(mn)), perhaps lazily every few updates and accepting bounded staleness between rebuilds.

FOLLOW-UP 3 Return which taxi is nearest, not only the distance.

Store a source id with each cell in the BFS: a cell copies the id of the cell that first reached it. Ties go to whichever reached it first, so say how you want ties broken.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque

STEPS = ((1, 0), (-1, 0), (0, 1), (0, -1))


# BASE QUESTION (optimal): One multi-source BFS
def taxi_distances(grid):
    # 'T' taxi, '.' road, '#' wall. One BFS that starts
    # from
    # every taxi at once gives each cell its nearest taxi.
    R, C = len(grid), len(grid[0])
    dist = [[-1] * C for _ in range(R)]
    queue = deque()
    for r in range(R):
        for c in range(C):
            if grid[r][c] == "T":
                dist[r][c] = 0
                queue.append((r, c))
    spread(grid, dist, queue)
    return dist


def spread(grid, dist, queue, better=False):
    # grow outward; with better=True a cell may be updated
    # when a
    # new, closer source reaches it (distances only go
    # down)
    R, C = len(grid), len(grid[0])
    while queue:
        r, c = queue.popleft()
        for dr, dc in STEPS:
            a, b = r + dr, c + dc
            if not (0 <= a < R and 0 <= b < C):
                continue
            if grid[a][b] == "#":
                continue
            new = dist[r][c] + 1
            unseen = dist[a][b] == -1
            if unseen or (better and new < dist[a][b]):
                dist[a][b] = new
                queue.append((a, b))


# FOLLOW-UP 1: A new taxi appears.
def add_taxi(grid, dist, r, c):
    # a new taxi: only cells it beats are touched
    dist[r][c] = 0
    spread(grid, dist, deque([(r, c)]), better=True)
```

```
# FOLLOW-UP 3: Return which taxi is nearest, not only the
# distance.
def nearest_taxi_ids(grid):
    # which taxi is nearest? each cell copies the id of
    # the
    # cell that reached it first (ties: the first to
    # arrive)
    R, C = len(grid), len(grid[0])
    owner = [[None] * C for _ in range(R)]
    queue, taxi_id = deque(), 0
    for r in range(R):
        for c in range(C):
            if grid[r][c] == "T":
                owner[r][c] = taxi_id
                taxi_id += 1
                queue.append((r, c))
    while queue:
        r, c = queue.popleft()
        for dr, dc in STEPS:
            a, b = r + dr, c + dc
            inside = 0 <= a < R and 0 <= b < C
            if not inside or grid[a][b] == "#":
                continue
            if owner[a][b] is None:
                owner[a][b] = owner[r][c]
                queue.append((a, b))
    return owner


if __name__ == "__main__":
    grid = ["T...", ".#..", "...T"]
    d = taxi_distances(grid)
    # the second taxi at the bottom right is closer to (0,
    # 3)
    assert d[0] == [0, 1, 2, 2]
    assert d[2] == [2, 2, 1, 0]
    assert d[1][1] == -1
    # a new taxi in the middle of the top row
    add_taxi(grid, d, 0, 2)
    assert d[0] == [0, 1, 0, 1]
```

```
    assert d[2][0] == 2
    # unreachable cells stay -1
    walled = ["T#.", "##."]
    assert taxi_distances(walled)[0][2] == -1
    ids = nearest_taxi_ids(grid)
    assert ids[0][0] == 0 and ids[2][3] == 1
    assert ids[1][1] is None
```

FUNCTION AND TEST CASES

Signature

```
def solution(grid: list[list[int]]) -> list[list[int]]:
```

Sample call

```
solution([[0,0,0],[0,1,0],[0,0,0]])
```

Test cases

Input	Expected
`([[0,0,0],[0,1,0],[0,0,0]],)`	`[[2,1,2],[1,0,1],[2,1,2]]`
`([[1,0,0,0],[0,0,0,1],[0,0,0,0]],)`	`[[0,1,2,1],[1,2,1,0],[2,3,2,1]]`

MEDIUM | PracHub | Technical Screen | 87 of 165

★ TOP 75: rank 2 in the Medium and Hard priority list

★ Find median of merged RLE arrays

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 74.2 | 30 DAYS 61 | PRIORITY 4/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #4 Median of Two Sorted Arrays

LeetCode match: LC 4 Median of Two Sorted Arrays (RLE variant) (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-06-27)

Original: https://prachub.com/coding-questions/find-median-of-merged-rle-arrays

QUESTION

Overview: The question evaluates understanding of run-length encoding, order-statistics (median) computation, and efficient merging of frequency-annotated sequences, emphasizing handling large frequencies without explicit decompression.

APPROACH

Total length = sum of run counts; walk both run lists merged by value accumulating counts until the median index(es) are covered. Or binary search on value with counts.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether each array is sorted by value, how large counts can be (so decompression is impossible), and what to return for an even total (average of the two middle values).

BRUTE FORCE TO SAY OUT LOUD

Decompress both arrays, merge, take the middle. O(total count) memory, which counts can make huge.

OPTIMAL IDEA

Let N be the sum of all counts and the median positions be (N - 1) // 2 and N // 2. Merge the two run lists by value with two pointers (like the merge step of merge sort), accumulating counts until the running total passes each median position, and read the value there. O(r1 + r2) with no decompression. Alternative: binary search on the value, counting how many elements are at most that value in each array.

DRY-RUN THESE CASES

A single run, an even total, the median falling exactly on a run boundary, both arrays with the same values, an empty array.

LIKELY FOLLOW-UPS

K arrays (heap merge), or arrays not sorted by value.

PITFALLS

INTERVIEW-DAY PLAN

Treating counts as lengths of different arrays instead of merging by value. Off-by-one at a run boundary.

HOW TO THINK ABOUT IT

Counts can be huge, so never expand a run. You only need the elements at ranks (N - 1) // 2 and N // 2 in the merged order. Merge the two run lists by value, counting how many elements you have passed, and read the value when the count reaches each rank.

Basis: Written; LeetCode 4 with run-length encoded inputs. Assumed input: two lists of (value, count) runs, each sorted by value; the median of the merged multiset (average of the two middle values for an even total).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(runs_a, runs_b):
    dense = []
    for value, count in runs_a + runs_b:
        dense += [value] * count
    dense.sort()
    n = len(dense)
    if n % 2:
        return dense[n // 2]
    mid = n // 2
    return (dense[mid - 1] + dense[mid]) / 2
```

TIME	SPACE
O(total count)	O(total count)

WHY IT IS SLOW

Needs time and memory proportional to the total count, which can be 10^9 or more. Walking the two run lists in value order and counting up to the middle rank costs only the number of runs.

OPTIMAL SOLUTION · Merge the runs and walk to the two middle ranks

TIME	SPACE
O(r1 + r2)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 K arrays instead of two.

Merge all runs by value (heap of K heads, or sort the combined run list if memory allows) and walk to the two middle ranks. O(R log K) with a heap, R the total number of runs.

FOLLOW-UP 2 The arrays are huge and sorted, and you want O(log) time.

Binary search on the value: for a candidate value count how many elements are at most it in each array (binary search on prefix sums of counts) and find the smallest value with rank above the middle. O(log(range) * log(runs)).

FOLLOW-UP 3 Runs are not sorted by value.

Sort the runs by value first, O(R log R), then use the same walk.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from bisect import bisect_right
from itertools import accumulate


def kth_smallest(runs_a, runs_b, k):
    # zero-based rank in the merged order, walking the
    # runs
    # of two sorted run-length lists; nothing is expanded
    i = j = seen = 0
    while True:
        take_a = j >= len(runs_b)
        if not take_a and i < len(runs_a):
            take_a = runs_a[i][0] <= runs_b[j][0]
        value, count = runs_a[i] if take_a else runs_b[j]
        seen += count
        if seen > k:
            return value
        if take_a:
            i += 1
        else:
            j += 1


# BASE QUESTION (optimal): Merge the runs and walk to the
# two middle ranks
def median_rle(a, b):
    # a and b: [(value, count)] sorted by value
    total = sum(c for _, c in a) + sum(c for _, c in b)
    if total % 2:
        return kth_smallest(a, b, total // 2)
    low = kth_smallest(a, b, total // 2 - 1)
    high = kth_smallest(a, b, total // 2)
    return (low + high) / 2


# FOLLOW-UP 1: K arrays instead of two.
def median_k_arrays(arrays):
    # K arrays: merge the run lists by value, then walk to
    # the
    # middle ranks
    runs = list(heapq.merge(*arrays))
    total = sum(c for _, c in runs)

    def kth(k):
        seen = 0
        for value, count in runs:
            seen += count
            if seen > k:
                return value

    if total % 2:
        return kth(total // 2)
    return (kth(total // 2 - 1) + kth(total // 2)) / 2


# FOLLOW-UP 2: The arrays are huge and sorted, and you
# want O(log) time.
def median_by_value(arrays):
    # sorted arrays, whole-number values: binary search
```

```
    # the
    # value; count_at_most uses prefix sums of the counts
    prefixes = []
    for runs in arrays:
        values = [v for v, _ in runs]
        sums = list(accumulate(c for _, c in runs))
        prefixes.append((values, sums))

    def count_at_most(x):
        total = 0
        for values, sums in prefixes:
            i = bisect_right(values, x)
            total += sums[i - 1] if i else 0
        return total

    n = count_at_most(10 ** 18)

    def kth(k):
        lo, hi = -(10 ** 18), 10 ** 18
        while lo < hi:
            mid = (lo + hi) // 2
            # smallest value with more than k elements <=
            # it
            if count_at_most(mid) > k:
                hi = mid
            else:
                lo = mid + 1
        return lo

    if n % 2:
        return kth(n // 2)
    return (kth(n // 2 - 1) + kth(n // 2)) / 2


if __name__ == "__main__":
    a = [(1, 3), (4, 1)]
    b = [(2, 2), (5, 2)]
    # merged: 1 1 1 2 2 4 5 5 -> middle two are 2 and 2
    assert median_rle(a, b) == 2
    assert median_k_arrays([a, b]) == 2
    assert median_by_value([a, b]) == 2
    # an odd total: 1, 7, 7, 7, 7, 7 plus one more 7
    assert median_rle([(7, 6)], [(1, 1)]) == 7
    # huge counts are never expanded
    big = [(1, 10 ** 12)]
    assert median_rle(big, [(3, 10 ** 12)]) == 2
    c = [(0, 1), (10, 1)]
    three = [a, b, c]
    by_merge = median_k_arrays(three)
    assert by_merge == median_by_value(three)
```

FUNCTION AND TEST CASES

Sample call

```
solution([(1, 2), (5, 1)], [(2, 3)])
```

Test cases

Input	Expected
`([(1, 2), (5, 1)], [(2, 3)])`	`2.0`
`([(1, 1)], [(2, 1)])`	`1.5`

MEDIUM | PracHub | Technical Screen | 88 of 165

Find longest increasing contiguous subarray

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 19.6 | 30 DAYS 0 | PRIORITY 145/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 674 Longest Continuous Increasing Subsequence (variant: one modification) (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/find-longest-increasing-contiguous-subarray

QUESTION

Overview: This question evaluates proficiency in array processing and algorithmic optimization, focusing on recognition of contiguous subarray properties and handling a single-value modification to achieve strict monotonicity.

APPROACH

Compute run lengths ending at i (left) and starting at i (right); for each i try changing nums[i] to bridge: left[i-1] + 1 + right[i+1] if nums[i+1] - nums[i-1] >= 2. O(n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether increasing is strict, whether the modified value can be any integer or any real, and whether you must change exactly one element or at most one.

BRUTE FORCE TO SAY OUT LOUD

Try changing each element to every useful value and recompute the run. O(n^2).

OPTIMAL IDEA

Compute left[i], the length of the strictly increasing run ending at i, and right[i], the run starting at i. Changing nums[i] can bridge the neighbors if nums[i + 1] - nums[i - 1] >= 2 (integers), giving left[i - 1] + 1 + right[i + 1]. Otherwise you can only extend one side: left[i - 1] + 1 or right[i + 1] + 1. Take the maximum over all i, and also the run with no change. O(n).

DRY-RUN THESE CASES

n = 1, a strictly decreasing array, a plateau like [1, 2, 2, 3], neighbors that differ by exactly 1 (cannot bridge with integers), the change at the first or last index.

LIKELY FOLLOW-UPS

Allow k changes (needs a sliding window with at most k bad positions), allow non-strict increase, or return the subarray bounds.

PITFALLS

INTERVIEW-DAY PLAN

Forgetting the integer gap condition. Index errors at the array ends.

HOW TO THINK ABOUT IT

A run that has a single 'bad' spot can be repaired by changing one element, so look at each position i as the element to change. The best run through i joins the increasing run that ends just before it and the one that starts just after it, and the join is legal only if the values leave enough room between the two neighbours (for integers, a[i + 1] - a[i - 1] >= 2).

Basis: LeetCode 674 (Longest Continuous Increasing Subsequence) with one allowed modification. Assumed rule (confirm it): strictly increasing, you may change at most one element to any integer.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(a):
    best = 0
    for i in range(len(a)):
        for j in range(i, len(a)):
            part = a[i:j + 1]
            if fixable_with_one_change(part):
                best = max(best, len(part))
    return best
def fixable_with_one_change(part):
    bad = [k for k in range(1, len(part))
           if part[k] <= part[k - 1]]
    if not bad:
        return True
    if len(bad) > 1:
        return False
    return has_room(part, bad[0])
```

TIME	SPACE
O(n^3)	O(1)

WHY IT IS SLOW

O(n^2) subarrays, each tested in O(n): O(n^3). Run lengths ending and starting at each index, then trying each index as the changed element, is O(n).

OPTIMAL SOLUTION · Left and right run lengths, try every position as the changed element

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 No modification allowed (LeetCode 674).

One pass keeping the length of the current strictly increasing run; reset to 1 when a[i] <= a[i - 1]. O(n), O(1).

FOLLOW-UP 2 Up to k modifications.

Use a sliding window over the array that allows at most k positions where the increasing property fails and cannot be repaired; careful with the integer room condition between neighbours. Often handled with DP over (position, changes used).

FOLLOW-UP 3 Values are real numbers, not integers.

Then there is always room between two different neighbours, so the join condition becomes a[i + 1] > a[i - 1] instead of a gap of at least 2.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# FOLLOW-UP 1: No modification allowed (LeetCode 674).
def longest_increasing(a):
    # LeetCode 674: no change allowed, one pass
    best = run = 0
    for i, x in enumerate(a):
        run = run + 1 if i and a[i - 1] < x else 1
        best = max(best, run)
    return best


# BASE QUESTION (optimal): Left and right run lengths, try
# every position as the ...
def longest_one_change(a, integers=True):
    # strictly increasing after changing AT MOST one value
    n = len(a)
    if n == 0:
        return 0
    # left[i]: run ending at i; right[i]: run starting at
    # i
    left, right = [1] * n, [1] * n
    for i in range(1, n):
        if a[i] > a[i - 1]:
            left[i] = left[i - 1] + 1
    for i in range(n - 2, -1, -1):
        if a[i] < a[i + 1]:
            right[i] = right[i + 1] + 1
    # the gap needed between two neighbours: 2 for whole
    # numbers (one number must fit between), > 0 for reals
    best = max(left)
    for i in range(n):
        # change a[i] to join the run on its left ...
        if i > 0:
            best = max(best, left[i - 1] + 1)
        # ... or the run on its right ...
        if i < n - 1:
            best = max(best, right[i + 1] + 1)
        # ... or both, when a value fits between the
        # neighbours
        if 0 < i < n - 1:
            room = a[i + 1] - a[i - 1]
            fits = room >= 2 if integers else room > 0
            if fits:
                joined = left[i - 1] + 1 + right[i + 1]
                best = max(best, joined)
    return min(best, n)
```

```
if __name__ == "__main__":
    assert longest_increasing([1, 3, 5, 4, 7]) == 3
```

```
assert longest_increasing([]) == 0
assert longest_one_change([1, 3, 5, 4, 7]) == 5
# equal neighbours leave no room for a whole number
assert longest_one_change([1, 2, 2, 3]) == 3
nums = [1, 2, 2, 3]
reals = longest_one_change(nums, integers=False)
assert reals == 4
assert longest_one_change([5, 4, 3, 2, 1]) == 2
assert longest_one_change([7]) == 1
assert longest_one_change([]) == 0
# never more than the array length
assert longest_one_change([1, 2, 3]) == 3
```

FUNCTION AND TEST CASES

Signature

```
def longestIncreasing(nums: list[int]) -> int:
```

Sample call

```
longestIncreasing([1, 2, 2, 3, 4])
```

Test cases

Input	Expected
`([1, 2, 2, 3, 4],)`	3
`([1, 2, 3, 4, 5],)`	5

MEDIUM | IN APP LC 198 | PracHub | Technical Screen | 89 of 165

★ TOP 75: rank 61 in the Medium and Hard priority list

★ Maximize sum without choosing adjacent elements

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 57.2 | 30 DAYS 0 | PRIORITY 49/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #198 House Robber

LeetCode match: LC 198 House Robber (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/maximize-sum-without-choosing-adjacent-elements

QUESTION

Overview: This question evaluates a candidate's understanding of array-based optimization and dynamic programming concepts for computing a maximum sum under non-adjacent selection constraints.

APPROACH

dp: take = skip_prev + x, skip = max(take_prev, skip_prev); O(n) time, O(1) space.

HOW TO THINK ABOUT IT

At each element you either take it (then the previous one is off limits) or skip it. Only two numbers matter from the past: the best total if you took the previous element and the best if you did not. Update them together and the whole array is one pass with no table.

Basis: LeetCode 198, House Robber: pick elements with no two adjacent to maximise the sum.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def best(i):
    if i >= len(nums):
        return 0
    skip = best(i + 1)
    take = nums[i] + best(i + 2)
    return max(skip, take)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

Two calls per index and the same suffix is solved repeatedly: O(2^n). Keeping only the best total with and without the previous element is O(n) time and O(1) space.

OPTIMAL SOLUTION · Two running values (take, skip)

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The houses form a circle (LeetCode 213).

The first and last are adjacent, so you cannot take both: the answer is the better of 'ignore the first house' and 'ignore the last house', each solved with the linear version.

FOLLOW-UP 2 Return which houses to rob.

Keep the table dp[i] = best from i onward (filled from the right) and walk forward: take house i when nums[i] + dp[i + 2] equals dp[i], then jump two; otherwise move one.

FOLLOW-UP 3 Robbing a house also alerts the next k houses.

The recurrence becomes dp[i] = max(dp[i + 1], nums[i] + dp[i + k + 1]); the O(1) space trick needs a window of k + 1 values (a deque), or just keep the O(n) table.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Two running values (take, skip)
def rob_line(nums):
    # take: best when the current element is taken,
    # skip: best when it is not
    take = skip = 0
    for x in nums:
        take, skip = skip + x, max(take, skip)
    return max(take, skip)


# FOLLOW-UP 1: The houses form a circle (LeetCode 213).
def rob_circle(nums):
    # the first and last are neighbours: ignore one of
    # them
    if len(nums) == 1:
        return nums[0]
    return max(rob_line(nums[1:]), rob_line(nums[:-1]))


# FOLLOW-UP 2: Return which houses to rob.
def rob_with_choice(nums):
    # dp[i] = best from house i onward, filled from the
    # right
    n = len(nums)
    dp = [0] * (n + 2)
    for i in range(n - 1, -1, -1):
        dp[i] = max(dp[i + 1], nums[i] + dp[i + 2])
    # walk forward: take house i when it explains dp[i]
    chosen, i = [], 0
    while i < n:
        if nums[i] + dp[i + 2] == dp[i] and nums[i] > 0:
            chosen.append(i)
            i += 2
        else:
            i += 1
    return dp[0], chosen


# FOLLOW-UP 3: Robbing a house also alerts the next k
# houses.
def rob_gap(nums, k):
    # taking a house blocks the next k houses (k = 1 is
    # the
    # classic problem): dp[i] = max(dp[i + 1], nums[i] +
    # dp[i + k + 1])
    n = len(nums)
    dp = [0] * (n + k + 2)
    for i in range(n - 1, -1, -1):
        dp[i] = max(dp[i + 1], nums[i] + dp[i + k + 1])
    return dp[0]


if __name__ == "__main__":
    assert rob_line([2, 7, 9, 3, 1]) == 12
    assert rob_line([]) == 0
    assert rob_line([5]) == 5
    assert rob_circle([2, 3, 2]) == 3
    assert rob_circle([1, 2, 3, 1]) == 4
    assert rob_circle([4]) == 4
    total, houses = rob_with_choice([2, 7, 9, 3, 1])
    assert total == 12 and houses == [0, 2, 4]
    values = [2, 7, 9, 3, 1]
    assert sum(values[i] for i in houses) == total
    assert rob_gap([2, 7, 9, 3, 1], 1) == 12
    # blocking two houses after each pick
    assert rob_gap([5, 1, 1, 5, 1, 1, 5], 2) == 15
```

FUNCTION AND TEST CASES

Signature

```
def solution(nums: list[int]) -> int:
```

Sample call

```
solution([2, 7, 9, 3, 1])
```

Test cases

Input	Expected
([2, 7, 9, 3, 1],)	12
([1, 2, 3, 1],)	4

MEDIUM | IN APP LC 2402 | PracHub | Technical Screen | 90 of 165

Simulate room assignments for scheduled meetings

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TALK ALL TIME 40 30 DAYS 0 PRIORITY 94/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: your app's interview approach (LeetCode #2402)

LeetCode match: LC 2402 Meeting Rooms III (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-03-29)

Original: https://prachub.com/interview-questions/simulate-room-assignments-for-scheduled-meetings

QUESTION

Overview: This question evaluates scheduling and event-simulation skills, including time-ordered processing, resource allocation with tie-breaking, and efficient tracking of room availability and usage counts using appropriate data structures.

APPROACH

Sort meetings by start, min-heap of free rooms (by index) and a heap of busy rooms (end time, room); assign the lowest free room, else wait for the earliest finish and delay.

HOW TO THINK ABOUT IT

Simulate in start order with two questions per meeting: which rooms are free now (lowest index first), and if none, which room frees up first (the meeting is delayed but keeps its length). Two heaps answer both quickly: one of free room ids, one of (end time, room id) for busy rooms.

Basis: LeetCode 2402, Meeting Rooms III.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n, meetings):
    end = [0] * n
    count = [0] * n
    for start, finish in sorted(meetings):
        free = [r for r in range(n)
                if end[r] <= start]
        if free:
            r = min(free)
            end[r] = finish
        else:
            r = end.index(min(end))  # earliest
            wait = end[r] - start
            end[r] = finish + wait
        count[r] += 1
    return count.index(max(count))
```

TIME	SPACE
O(M * N)	O(N)

WHY IT IS SLOW

Every meeting scans all N rooms, O(M * N). Two heaps (free rooms and busy rooms by end time) make each meeting O(log N).

OPTIMAL SOLUTION · Two heaps: free rooms and busy rooms

TIME	SPACE
O(M log M + M log N)	O(N)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if meetings arrive online and cannot be reordered?

The same two heaps work if you process meetings in arrival order and treat the arrival time as the earliest allowed start, but you can no longer rely on sorted starts, so you must first move every room whose end time is <= the arrival into the free heap. Each call stays O(log N).

FOLLOW-UP 2 How do you report the busiest room by total busy time instead of meeting count?

Add the meeting's actual duration to used[room] instead of 1 when you assign it. Rooms are chosen the same way; only the tally changes, and ties still break toward the lowest index.

FOLLOW-UP 3 Rank rooms by total busy time instead of the number of meetings.

Add each meeting's duration (its original length, not the delay) to the room's tally; the choice of room is unchanged.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


# BASE QUESTION (optimal): Two heaps: free rooms and busy
# rooms
# FOLLOW-UP 3: Rank rooms by total busy time instead of
# the number of meetings.
def most_booked_room(n, meetings, by="count"):
    # a meeting takes the lowest-numbered free room; if
    # none is
    # free it waits for the earliest room and keeps its
    # length
    free = list(range(n))
    heapq.heapify(free)
    # busy rooms: (time it becomes free, room)
    busy = []
    used = [0] * n
    for start, end in sorted(meetings):
        # rooms that finished by now are free again
        while busy and busy[0][0] <= start:
            _, room = heapq.heappop(busy)
            heapq.heappush(free, room)
        if free:
            room = heapq.heappop(free)
            heapq.heappush(busy, (end, room))
        else:
            # delayed: starts when the earliest room frees
            # up
            finish, room = heapq.heappop(busy)
            delayed_end = finish + (end - start)
            heapq.heappush(busy, (delayed_end, room))
        # FOLLOW-UP 3: by="time" ranks by total busy time
        # count meetings, or total length (not the delay)
        used[room] += 1 if by == "count" else end - start
    # ties go to the lowest room number
    return used.index(max(used))


if __name__ == "__main__":
    assert most_booked_room(2, [[0, 10], [1, 5], [2, 7],
                                [3, 4]]) == 0
    assert most_booked_room(3, [[1, 20], [2, 10], [3, 5],
                                [4, 9], [6, 8]]) == 1
    # a single room takes everything
    assert most_booked_room(1, [[0, 1], [0, 1]]) == 0
```

```
    # by busy time instead of the number of meetings
    meetings = [[0, 100], [1, 2], [2, 3], [3, 4]]
    assert most_booked_room(2, meetings, "count") == 1
    assert most_booked_room(2, meetings, "time") == 0
```

FULL QUESTION TEXT FROM THE SITE

Problem

You are given n meeting rooms labeled 0..n-1 and a list of meetings meetings, where each meeting is [start, end] with start < end. Meetings are processed in increasing order of start time.

Assign each meeting to a room using these rules:

If one or more rooms are free at start , assign the meeting to the free room with the smallest index .
If no rooms are free at start , the meeting must wait until a room becomes free. It is then scheduled in the room that becomes available earliest (break ties by smallest room index). If it waits, its duration stays the same , so if the original duration is end - start and the room becomes free at time t , the meeting runs on [t, t + (end - start)] .

Each time a meeting is assigned to a room (even after waiting), that room's meeting count increases by 1.

Task

Return the index of the room that hosted the most meetings. If there is a tie, return the smallest index.

Input/Output
Input: n (int), meetings (list of [start,end])
Output: an integer room index
Constraints (reasonable interview assumptions)
1 <= n <= 10^5
1 <= len(meetings) <= 10^5
Times fit in 32-bit signed integer; waiting can increase end times beyond original but still fits in 64-bit.

ALSO REPORTED · 1 more

Assign meetings to rooms with delays | PracHub | Technical Screen

https://prachub.com/interview-questions/assign-meetings-to-rooms-with-delays

---

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 91 of 165

★ TOP 75: rank 36 in the Medium and Hard priority list

★ Design a logger that returns top-K messages

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 51.2 | 30 DAYS 33 | PRIORITY 32/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #359 Logger Rate Limiter, LeetCode #692 Top K Frequent Words

LeetCode match: LC 359 Logger Rate Limiter + LC 692 Top K Frequent Words (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-05-23)

ABOUT THIS QUESTION

Original: https://prachub.com/coding-questions/design-a-logger-that-returns-top-k-messages

QUESTION

Overview: This question evaluates skills in designing in-memory data structures and algorithms for frequency counting and interval querying, including extracting top-K elements with a heap, within the Coding & Algorithms domain.

APPROACH

Hash map message -> count (plus a deque of timestamps for interval queries); top-K with a size-k heap, ties broken lexicographically.

INTERVIEW-DAY PLAN

CLARIFY FIRST

My copy has only the overview, so ask what the API is: log(timestamp, message), top-K over all time or over an interval, whether duplicates within a time gap are suppressed (the LeetCode 359 rate limiter), and how ties break (lexicographically, for LeetCode 692).

BRUTE FORCE TO SAY OUT LOUD

Store every entry in a list and sort or scan on each query. O(n log n) per query.

OPTIMAL IDEA

A dict message to count (and, for interval queries, a dict message to a list of timestamps kept in order so a time window is two binary searches). Top-K uses a heap of size K with the key (count descending, message ascending): heapq.nsmallest(k, items, key=(-count, message)). The rate limiter part is a dict message to last printed time, allowing a message when the gap is at least 10 seconds. O(d log K) per top-K query.

DRY-RUN THESE CASES

Fewer than K distinct messages, ties on count, the same message repeated inside the rate-limit window, an empty logger.

LIKELY FOLLOW-UPS

Streaming top-K with bounded memory (Space-Saving), or evicting old entries.

PITFALLS

Not specifying the tie rule. Using the full sort when only K items are needed.

HOW TO THINK ABOUT IT

Store enough to answer both questions without scanning everything. A dict from message to its list of timestamps (appended in time order) answers 'how many in [start, end]' with two binary searches, and a heap of size K over (count, message) gives the top K. Say how the logger handles repeated messages and what 'top' means with ties.

HOW TO THINK ABOUT IT

Basis: Written (compare LeetCode 359 Logger Rate Limiter and 692 Top K Frequent Words). Assumed API (confirm it): log(timestamp, message); top_k(k, start, end) over an optional time window; ties by message alphabetically.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
logs = []  # (timestamp, message)
def top_k(k, start, end):
    counts = Counter()
    for ts, msg in logs:
        if start <= ts <= end:
            counts[msg] += 1
    def rank(m):
        return (-counts[m], m)
    return sorted(counts, key=rank)[:k]
```

TIME	SPACE
O(n + d log d) per query	O(n)

WHY IT IS SLOW

Every query reads the whole log, O(n + d log d). Per-message sorted timestamps with binary search answer a window count in O(log n), and a heap picks the top k.

OPTIMAL SOLUTION · Per-message sorted timestamps plus a heap for the top K

TIME	SPACE
O(1) per log, O(d log n + d log k) per query	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Print a message only if it was not printed in the last 10 seconds (LeetCode 359).

Keep a dict message to the time it was last printed and compare: print if the gap is at least 10 (and update the time only when you print). O(1) per call.

FOLLOW-UP 2 Memory must stay bounded.

Expire timestamps older than the largest window you support (drop from the front of each list, delete messages with no timestamps left), or approximate counts with a count-min sketch plus a heap for the heavy hitters. **Cost:** O(1) amortized to drop expired timestamps; memory O(messages inside the window).

FOLLOW-UP 3 Very high top_k frequency of calls.

Maintain counts per message incrementally and a top-K structure (a heap with lazy updates or a sorted structure) so top_k costs O(k) instead of O(d log k); windowed queries still need per-message timestamps.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from bisect import bisect_left, bisect_right
from collections import defaultdict


# BASE QUESTION (optimal): Per-message sorted timestamps
# plus a heap for the top K
class Logger:
    def __init__(self):
        # message -> its timestamps, in order of arrival
        self.times = defaultdict(list)

    def log(self, ts, msg):
        self.times[msg].append(ts)

    def top_k(self, k, start=None, end=None):
        # the k most frequent messages in [start, end]
        counts = {}
        for msg, ts in self.times.items():
            lo, hi = 0, len(ts)
            if start is not None:
                lo = bisect_left(ts, start)
            if end is not None:
                hi = bisect_right(ts, end)
            if hi > lo:
                counts[msg] = hi - lo
        # ties are broken alphabetically
        def rank(m):
            return (-counts[m], m)
        return heapq.nsmallest(k, counts, key=rank)

    def expire(self, before):
        # bounded memory: forget timestamps older than
        # `before`
        for msg in list(self.times):
            ts = self.times[msg]
            self.times[msg] = ts[bisect_left(ts, before):]
            if not self.times[msg]:
                del self.times[msg]


# FOLLOW-UP 1: Print a message only if it was not printed
# in the last 10 seconds ...
class RateLimiter:
    """LeetCode 359: one print per message per gap."""
```

```
    def __init__(self, gap=10):
        self.gap, self.last = gap, {}

    def should_print(self, ts, msg):
        last = self.last.get(msg)
        if last is not None and ts - last < self.gap:
            return False
        # only a printed message starts a new window
        self.last[msg] = ts
        return True
```

```
if __name__ == "__main__":
    log = Logger()
    events = [(1, "a"), (2, "b"), (3, "a"),
              (4, "c"), (5, "a"), (6, "b")]
    for ts, msg in events:
        log.log(ts, msg)
    assert log.top_k(2) == ["a", "b"]
    # only the window [4, 6]: a once, b once, c once
    assert log.top_k(3, 4, 6) == ["a", "b", "c"]
    assert log.top_k(2, 100, 200) == []
    log.expire(4)
    assert log.top_k(5) == ["a", "b", "c"]
    r = RateLimiter()
    times = (1, 2, 11, 12, 21)
    got = [r.should_print(t, "x") for t in times]
    assert got == [True, False, True, False, True]
```

FUNCTION AND TEST CASES

Signature

```
def solution(logs: list[tuple[int, str]], queries: list[list[int]]) -> list[list[str]]:
```

Sample call

```
solution([(1, 'A'), (2, 'B'), (3, 'A'), (10, 'C')], [(1, 3, 2), (1, 10, 3)])
```

Test cases

Input	Expected
`([(1, 'A'), (2, 'B'), (3, 'A'), (10, 'C')], [(1, 3, 2), (1, 10, 3)])`	`[['A', 'B'], ['A', 'B', 'C']]`
`([(1, 'dog'), (2, 'cat'), (2, 'dog'), (4, 'cat'), (5, 'ant')], [(1, 4, 2)])`	`[['cat', 'dog']]`

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 92 of 165

Implement iterator merging lists with filtering

POSTED 2026-01-06 | 277 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 16.5 | 30 DAYS 0 | PRIORITY 154/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #281 Zigzag Iterator

LeetCode match: LC 281 Zigzag Iterator (+ filter/dedupe) (inferred from overview)

Posted on PracHub: 2026-01-06 (updated 2026-06-27)

Original: https://prachub.com/coding-questions/implement-iterator-merging-lists-with-filtering

QUESTION

Overview: This question evaluates iterator/generator design, sequence merging, stateful filtering and deduplication, checking a candidate's ability to maintain input ordering while excluding blocked IDs and preventing duplicate yields.

APPROACH

Keep one pointer per list and a lookahead 'next valid' value for hasNext/next; skip filtered and duplicate values; or merge with a heap if sorted.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask how the lists are merged: round robin (like LeetCode 281 Zigzag Iterator), one after the other, or by sorted value; what is filtered (a blocked set of ids); whether duplicates must be removed across lists; and what next() does when the iterator is exhausted.

BRUTE FORCE TO SAY OUT LOUD

Build one merged list up front with the filter applied. Simple but not lazy and not memory friendly.

OPTIMAL IDEA

A lazy iterator with one pointer per list and a precomputed next valid value (lookahead). hasNext checks the lookahead; next returns it and then advances to the following valid element: skip blocked ids and anything already in a seen set. For sorted merges use a heap of (value, list index, position). Each element is touched once, O(total) overall.

DRY-RUN THESE CASES

Empty lists, all values blocked, duplicates across lists, calling next after the end, a list that becomes empty mid-way.

LIKELY FOLLOW-UPS

Make the iterator re-iterable, support remove, or bound memory for the seen set when ids are unbounded (Bloom filter).

PITFALLS

Computing the lookahead lazily at the wrong moment so hasNext skips or repeats a value.

HOW TO THINK ABOUT IT

An iterator does its work lazily: hasNext() must be able to answer without consuming. So keep a lookahead, the next valid value already computed, and advance to the one after it when next() is called. Filtering and de-duplication live in the 'find the next valid value' step so both hasNext and next stay trivial.

Basis: LeetCode 281, Zigzag Iterator, with a blocked-id filter and no duplicate output. Assumed rules (confirm them): lists are read round robin; ids in the blocked set are skipped; each id is yielded at most once.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def merged_iterator(lists, blocked):
    seen = set()
    for x in round_robin(lists):
        if x in blocked or x in seen:
            continue
        seen.add(x)
        yield x
```

TIME	SPACE
O(total)	O(total)

WHY IT IS SLOW

It reads everything up front and keeps it all in memory, so it is not lazy and never works on a long or unbounded source. A lookahead value per iterator computes only the next valid item.

OPTIMAL SOLUTION · Lazy iterator with one pointer per list and a lookahead

TIME	SPACE
O(1) amortized per value	O(number of lists + distinct ids yielded)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The lists are sorted and the output must stay sorted.

Replace the round robin with a k-way merge on a heap (heapq.merge), and drop a value equal to the previous output instead of keeping a seen set: memory O(k).

FOLLOW-UP 2 Read the lists one after another, not interleaved.

Chain the lists with a generator; the same blocked/seen filtering applies. Generators give hasNext-style behaviour via a one-item lookahead.

FOLLOW-UP 3 The seen set grows without bound.

If the input is sorted or ids repeat only close together, remember only the last few ids; otherwise bound memory with a Bloom filter and accept rare false suppressions. **Cost:** O(1) per element with a Bloom filter using O(bits) memory, at the price of rare false suppressions.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from itertools import chain


# BASE QUESTION (optimal): Lazy iterator with one pointer
# per list and a lookahead
class FilteredZigzag:
    """Take one item from each list in turn; skip blocked
    ids and ids already returned. Has hasNext / next."""

    def __init__(self, lists, blocked=()):
        self.lists = lists
        self.blocked = set(blocked)
        self.pos = [0] * len(lists)
        self.turn = 0
        self.seen = set()
        # one item of lookahead makes hasNext easy
        self.ahead = None
        self.advance()

    def advance(self):
        self.ahead = None
        misses = 0
        # stop when every list had nothing left in a full
        # round
        while misses < len(self.lists):
            i = self.turn
            self.turn = (self.turn + 1) % len(self.lists)
            if self.pos[i] >= len(self.lists[i]):
                misses += 1
                continue
            value = self.lists[i][self.pos[i]]
            self.pos[i] += 1
            misses = 0
            blocked = value in self.blocked
            skip = blocked or value in self.seen
            if not skip:
                self.ahead = value
                return

    def has_next(self):
        return self.ahead is not None

    def next(self):
        value = self.ahead
        self.seen.add(value)
        self.advance()
        return value


# FOLLOW-UP 1: The lists are sorted and the output must
# stay sorted.
def merge_sorted(lists, blocked=()):
    # sorted lists, sorted output: a k-way merge; equal
    # values
    # come out together, so remember only the previous one
    blocked, last = set(blocked), object()
    for value in heapq.merge(*lists):
        if value in blocked or value == last:
            continue
        last = value
        yield value


# FOLLOW-UP 2: Read the lists one after another, not
# interleaved.
def read_in_turn(lists, blocked=()):
    # one list after another, with the same filtering
    blocked, seen = set(blocked), set()
    for value in chain.from_iterable(lists):
        if value not in blocked and value not in seen:
            seen.add(value)
            yield value
```

```
if __name__ == "__main__":
    lists = [[1, 2, 3], [2, 4], [5]]
    it = FilteredZigzag(lists, blocked=[4])
    out = []
    while it.has_next():
        out.append(it.next())
    # 1, 2, 5, then 2 (seen), 3, 4 (blocked)
    assert out == [1, 2, 5, 3]
    empty = FilteredZigzag([[], []])
    assert not empty.has_next()
    assert list(merge_sorted([[1, 3, 5], [1, 2, 5]],
                             blocked=[3])) == [1, 2, 5]
    chained = read_in_turn([[1, 2], [2, 3]], [1])
    assert list(chained) == [2, 3]
```

FUNCTION AND TEST CASES

Sample call

```
solution([3, 1, 2, 3], [2, 4, 1, 5], {4})
```

Test cases

Input	Expected
`([3, 1, 2, 3], [2, 4, 1, 5], {4})`	`[3, 1, 2, 5]`
`([], [1, 1], set())`	`[1]`

MEDIUM | PracHub | Technical Screen | 93 of 165

Reconstruct original array from doubled shuffle

POSTED 2026-01-04 | 279 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 29.8 | 30 DAYS 0 | PRIORITY 126/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 2007 Find Original Array From Doubled Array (inferred from overview)

Posted on PracHub: 2026-01-04 (updated 2026-05-22)

Original: https://prachub.com/coding-questions/reconstruct-original-array-from-doubled-shuffle

QUESTION

Overview: This question evaluates array manipulation, multiset/frequency reasoning, pairing logic, and careful handling of edge cases such as zeros and negative numbers.

APPROACH

Sort (by absolute value) and use a counter: for each smallest x with count > 0, pair with 2x; handle zeros (need even count) and negatives. O(n log n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the output may be in any order, whether negatives and zeros are possible, and what to return if it is impossible (empty array).

BRUTE FORCE TO SAY OUT LOUD

Try every pairing recursively. Exponential.

OPTIMAL IDEA

If the length is odd return empty. Count values. Process numbers in order of absolute value; for each value x with remaining count, match it with 2x, decrement both counts, and fail if 2x has no count left. Zeros need an even count. Sorting by abs makes the smallest value always the original, never a double. O(n log n).

DRY-RUN THESE CASES

[1,3,4,2,6,8] gives [1,3,4]. An odd length. [0,0]. [0,0,0] fails. Negatives such as [-2,-4,1,2].

LIKELY FOLLOW-UPS

Linear time when the value range is small (counting array), or unsorted output.

PITFALLS

Sorting by value instead of absolute value for negatives. Mishandling zeros.

HOW TO THINK ABOUT IT

The element with the smallest absolute value cannot be the double of anything, so it is an original; its double must be present too. Pair them off, take the next smallest, and so on. Process values in order of absolute value so negatives and zeros follow the same rule, and handle zero separately (it is its own double, so it needs an even count).

Basis: LeetCode 2007, Find Original Array From Doubled Array.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(changed):
    items = sorted(changed, key=abs)
    originals = []
    while items:
        x = items.pop(0)
        if 2 * x not in items:
            return []
        items.remove(2 * x)
        originals.append(x)
    return originals
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

list.remove is a linear search, so each step is O(n) and the loop is O(n^2). A Counter processed in order of absolute value is O(n log n).

OPTIMAL SOLUTION · Counter processed in order of absolute value

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the originals in the order they appear in the input.

Compute the multiset of originals, then scan the input once and keep each element while its remaining original count is positive.

FOLLOW-UP 2 Values are small non-negative integers.

Use a counting array instead of sorting and a Counter: process values from small to large, O(n + range).

FOLLOW-UP 3 Why does processing by absolute value work with negatives?

For negatives the double has a larger absolute value, so the element with the smallest absolute value is always the original of its pair, exactly as with positives.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


# BASE QUESTION (optimal): Counter processed in order of
# absolute value
def find_original(changed):
    # `changed` holds every original x and its double 2x,
    # in
    # any order. Smallest absolute value first: it can
    # only be
    # an original, never someone's double.
    if len(changed) % 2:
        return []
    count, out = Counter(changed), []
    for x in sorted(count, key=lambda v: (abs(v), v)):
        if count[x] == 0:
            continue
        if x == 0:
            # zeros pair with each other
            if count[0] % 2:
                return []
            out += [0] * (count[0] // 2)
            count[0] = 0
            continue
        # every x needs its own 2x
        if count[2 * x] < count[x]:
            return []
        out += [x] * count[x]
        count[2 * x] -= count[x]
        count[x] = 0
    return out


# FOLLOW-UP 1: Return the originals in the order they
# appear in the input.
def find_original_in_order(changed):
    # originals in the order they appear in the input
    originals = find_original(changed)
    if not originals and changed:
        return []
    left = Counter(originals)
    out = []
    for x in changed:
        if left[x] > 0:
            left[x] -= 1
            out.append(x)
    return out


# FOLLOW-UP 2: Values are small non-negative integers.
def find_original_small(changed, limit):
    # values 0..limit: a counting array, O(n + limit)
    if len(changed) % 2:
        return []
    count = [0] * (2 * limit + 2)
    for x in changed:
        count[x] += 1
    out = []
    if count[0] % 2:
        return []
    out += [0] * (count[0] // 2)
    for x in range(1, limit + 1):
        if count[x]:
            if count[2 * x] < count[x]:
                return []
            out += [x] * count[x]
            count[2 * x] -= count[x]
    return out


if __name__ == "__main__":
    got = sorted(find_original([1, 3, 4, 2, 6, 8]))
    assert got == [1, 3, 4]
    assert find_original([6, 3, 0, 1]) == []
    assert find_original([1]) == []
    assert find_original([0, 0, 0, 0]) == [0, 0]
    assert find_original([0, 0, 0]) == []
    # negative numbers: -2 is the double of -1
    neg = sorted(find_original([-1, -2, 4, 2]))
    assert neg == [-1, 2]
    ordered = find_original_in_order([4, 1, 2, 8, 2, 4])
    assert ordered == [4, 1, 2]
    small = sorted(find_original_small([1, 2, 4, 8], 8))
    assert small == [1, 4]
    assert find_original_small([1, 3], 3) == []
```

FUNCTION AND TEST CASES

Signature

```
def solution(changed: list[int]) -> list[int]:
```

Sample call

```
solution([2, 1, 4, 8])
```

Test cases

Input	Expected
`([2, 1, 4, 8],)`	`[1, 4]`
`([-4, -2, -2, -1, 1, 2],)`	`[-2, -1, 1]`

MEDIUM | IN APP LC 380 | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 94 of 165

Design set with O(1) random access

POSTED 2026-01-01 | 282 DAYS AGO | OLDER

STUDY: TYPE ALL TIME 46.6 30 DAYS 0 PRIORITY 73/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #380 Insert Delete GetRandom O(1)

LeetCode match: LC 380 Insert Delete GetRandom O(1)

Posted on PracHub: 2026-01-01 (updated 2026-06-01)

Original: https://prachub.com/coding-questions/design-set-with-o-1-random-access

QUESTION

Design a data structure ("FancySet") that stores unique integers and supports the following operations, each in average O(1) time:

- **`add(x)`**: Insert value **`x`** if it is not already present. Return whether the insert happened.
- **`delete(x)`**: Remove value **`x`** if it exists. Return whether a deletion happened.
- **`getRandom()`**: Return a uniformly random element currently in the set. Requirements / follow-ups:
- All operations should be average O(1).
- Handle corner cases such as calling **`getRandom()`** on an empty set (define and justify behavior).
- Discuss how you would make this data structure thread-safe. Compare using a single lock for the whole set vs finer-grained locking (e.g., element-level locks), and explain trade-offs.

Design a data structure called FancySet that stores unique integers and supports these operations in average O(1) time: add(x), delete(x), and getRandom(). For this coding problem, implement a function **`solution(operations, values, seed)`** that simulates a newly created empty FancySet and returns the result of every operation. Use the standard dynamic-array + hash-map behavior:

- Store current elements in an array-like list.
- Store each element's current index in a hash map.

QUESTION

- When deleting an element that is not at the end of the list, move the last element into the removed slot, then pop the last slot. To make test cases deterministic, **`getRandom()`** does not use the language's built-in RNG. Instead, keep an internal 32-bit state initialized to **`seed`**. When **`getRandom()`** is called on a non-empty set, update the state with: **`state = (1664525 * state + 1013904223) mod 2^32`** and return the element at index **`state % current_size`** from the current internal list. If **`getRandom()`** is called on an empty set, return **`None`** and do not advance the state. In a real interview, picking a random index from the array gives uniform random access; the fixed generator above is only for reproducible grading. Follow-up discussion (not graded by the code runner): explain how you would make FancySet thread-safe, and compare using one lock for the whole structure versus finer-grained locking.

Constraints
1 <= len(operations) <= 2 * 10^5len(values) == len(operations)Each operation is one of 'add', 'delete', or 'getRandom'For 'add' and 'delete', values[i] contains exactly one integer; for 'getRandom', values[i] is []-10^9 <= x <= 10^9All operations should run in O(1) average time

EXAMPLES

```
Input: (['add','add','getRandom','delete','getRandom'
    ,'add','getRandom'], [[1],[2],[],[1],[],[2],[]],
    7)
Expected Output: [True, True, 1, True, 2, False, 2]
```

Explanation: After inserting 1 and 2, the first deterministic random choice picks index 0, so it returns 1. Deleting 1 leaves only 2. Adding 2 again fails because it is already present.

```
Input: (['getRandom','add','add','delete','delete','g
    etRandom'], [[],[5],[5],[7],[5],[]], 1)
Expected Output: [None, True, False, False, True,
    None]
```

Explanation: Calling getRandom on an empty set returns None. Adding 5 twice inserts it only once. Deleting 7 fails because it is not present. After deleting 5, the set becomes empty again.

Hints

You need both fast membership/index lookup and fast access by numeric position. What two data structures combine to give that?Deleting from the middle of an array is expensive unless you replace the removed element with the last element and update that last element's stored index.

APPROACH

Array of values + hash map value -> index; remove by swapping with the last element and popping.

HOW TO THINK ABOUT IT

A hash set gives O(1) add and delete but cannot pick a random element in O(1); an array can pick a random element but deleting from the middle is O(n). Combine them: keep the values in an array and a dict from value to array index. To delete, swap the element with the last one, pop the end, and update the moved element's index.

Basis: LeetCode 380, Insert Delete GetRandom O(1) (FancySet). Choice made: getRandom on an empty set raises an error (a defined, loud failure).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
items = []
def add(x):
    if x in items:
        return False
    items.append(x)
    return True
def delete(x):
    if x not in items:
        return False
    items.remove(x)
    return True
def get_random():
    return random.choice(items)
```

TIME	SPACE
O(n) for add and delete, O(1) getRandom	O(n)

WHY IT IS SLOW

Membership checks and deletion are O(n). An array plus a dictionary from value to index, deleting by swapping with the last element, makes all three operations O(1).

OPTIMAL SOLUTION · Array of values plus a dict from value to index

TIME	SPACE
O(1) average per operation	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Make it thread-safe: one lock or finer-grained locking?

One lock around every operation is simplest and correct (delete touches the array, the dict and a second element's index together, so they must change as one unit). Finer locks do not help much because every operation touches shared structure; use sharding by value hash if contention is the problem.

FOLLOW-UP 2 What should getRandom do on an empty set?

Raise a clear error (as here) or return a sentinel such as None; whichever you pick, document it and make the caller handle it. Returning an arbitrary value hides bugs.

FOLLOW-UP 3 Duplicates allowed (a multiset, LeetCode 381).

Map each value to a set of indices in the array; delete swaps with the last element and fixes both index sets. getRandom stays a uniform pick over array positions, so values are chosen in proportion to their counts.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import random
import threading


# BASE QUESTION (optimal): Array of values plus a dict
# from value to index
class FancySet:
    """add, delete and getRandom, each O(1) on average."""

    def __init__(self, rng=None):
        # the values in a list (for random access) and a
        # map
        # from value to its index in that list
        self.items, self.pos = [], {}
        self.rng = rng or random

    def add(self, x):
        if x in self.pos:
            return False
        self.pos[x] = len(self.items)
        self.items.append(x)
        return True

    def delete(self, x):
        if x not in self.pos:
            return False
        i, last = self.pos[x], self.items[-1]
        # move the last item into the hole, then drop the
        # tail
        self.items[i] = last
        self.pos[last] = i
        self.items.pop()
        del self.pos[x]
        return True

    def get_random(self):
        if not self.items:
            # say what happens on an empty set
            raise IndexError("empty set")
        i = self.rng.randrange(len(self.items))
        return self.items[i]


# FOLLOW-UP 1: Make it thread-safe: one lock or finer-
# grained locking?
```

```
class SafeSet(FancySet):
    """One lock: delete changes three things at once."""

    def __init__(self, rng=None):
```

```
        super().__init__(rng)
        self.lock = threading.Lock()

    def add(self, x):
        with self.lock:
            return super().add(x)

    def delete(self, x):
        with self.lock:
            return super().delete(x)

    def get_random(self):
        with self.lock:
            return super().get_random()


# FOLLOW-UP 3: Duplicates allowed (a multiset, LeetCode
# 381).
class RandomizedCollection:
    """Duplicates allowed (LeetCode 381)."""

    def __init__(self):
        self.items = []
        # value -> set of indices where it sits in the
        # list
        self.where = {}

    def insert(self, x):
        first = x not in self.where or not self.where[x]
        spots = self.where.setdefault(x, set())
        spots.add(len(self.items))
        self.items.append(x)
        return first

    def remove(self, x):
        if not self.where.get(x):
            return False
        i = self.where[x].pop()
        end = len(self.items) - 1
        if i != end:
            # move the last item into the hole and fix its
```

```
            # index set
            last = self.items[end]
            self.items[i] = last
            self.where[last].discard(end)
            self.where[last].add(i)
        self.items.pop()
        return True

    def get_random(self):
        return random.choice(self.items)


if __name__ == "__main__":
    s = FancySet(random.Random(1))
    assert s.add(1) and s.add(2) and not s.add(1)
    assert s.delete(1) and not s.delete(1)
    assert s.get_random() == 2
    s.delete(2)
    try:
        s.get_random()
        raise AssertionError("empty set should raise")
    except IndexError:
        pass
    # every value is picked about equally often
    big = FancySet(random.Random(5))
    for v in range(4):
        big.add(v)
    picks = [big.get_random() for _ in range(4000)]
    for v in range(4):
        assert 850 < picks.count(v) < 1150
    # deleting from the middle keeps the map consistent
    for v in (0, 2):
        big.delete(v)
    assert sorted(big.items) == [1, 3]
    for v, i in big.pos.items():
        assert big.items[i] == v
    safe = SafeSet()
    assert safe.add(7) and safe.get_random() == 7
    rc = RandomizedCollection()
    assert rc.insert(5)
    assert not rc.insert(5)
    assert rc.insert(6)
    assert rc.remove(5) and rc.remove(5)
    assert not rc.remove(5)
    assert rc.items == [6]
```

FUNCTION AND TEST CASES

Signature

```
def solution(operations: list[str], values: list[list[int]
], seed: int) -> str:
```

Sample call

```
solution(['add','add','getRandom','delete','getRandom','ad
d','getRandom'], [[1],[2],[],[1],[],[2],[]], 7)
```

Test cases

Input	Expected
`(['add','add','getRandom','delete','getRandom','add','getRandom'], [[1],[2],[],[1],[],[2],[]], 7)`	`[True, True, 1, True, 2, False, 2]`
`(['getRandom','add','add','delete','delete','getRandom'], [[],[5],[5],[7],[5],[]], 1)`	`[None, True, False, False, True, None]`

MEDIUM | PracHub | Technical Screen | 95 of 165

Match people to questions using tags and priorities

POSTED 2025-12-27 | 287 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 5 | 30 DAYS 0 | PRIORITY 171/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

LeetCode match: LC 1820 Maximum Number of Accepted Invitations (bipartite matching) (inferred from overview)

Posted on PracHub: 2025-12-27 (updated 2026-06-04)

Original: https://prachub.com/coding-questions/match-people-to-questions-using-tags-and-priorities

QUESTION

Overview: This question evaluates competencies in bipartite matching and combinatorial optimization, along with practical data-structure design for scalable tag-based assignment and priority-aware selection.

APPROACH

Model as bipartite matching: edges where tags overlap, weights by priority; use Kuhn's/Hopcroft-Karp for max matching, or greedy by priority with an inverted index tag -> candidates.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether matching is one-to-one or a question can take many people, what priority means (higher wins, or a numeric weight to maximize), whether a person needs only one shared tag, and whether it must be maximum cardinality or maximum total priority.

BRUTE FORCE TO SAY OUT LOUD

Try every assignment: exponential. State it and move on.

OPTIMAL IDEA

Build an inverted index tag to candidate questions. If only the number of matches matters it is bipartite matching: Kuhn's augmenting-path algorithm in O(V * E) is enough, Hopcroft-Karp for scale. If priorities are weights use min-cost flow or the Hungarian algorithm. If priority is a strict order, process people by priority and augment, because matchings form a matroid and greedy by priority is optimal.

DRY-RUN THESE CASES

A person with no tag overlap. Two people competing for one question. A chain where the first greedy choice blocks a larger matching (shows why plain greedy fails without augmenting).

LIKELY FOLLOW-UPS

Capacities per question (turns into max flow), online arrivals, or fairness constraints.

PITFALLS

Assuming plain greedy gives a maximum matching. Not building the index and doing all-pairs tag checks.

HOW TO THINK ABOUT IT

'Assign each person at most one question, each question at most one person, allowed pairs given by tags' is maximum bipartite matching. The tag index only builds the edges faster. For maximum count use augmenting paths: try to give a person a question, and if taken ask its current owner to move. If priorities decide who is served, process people in priority order with the same augmenting step.

Basis: LeetCode 1820, Maximum Number of Accepted Invitations (bipartite matching). Assumed rules (confirm them): a person and a question can be matched if they share a tag; each person gets at most one question and each question at most one person; priority decides who is served first when not everyone can be matched.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
best = 0
def go(person, used, matches):
    global best
    if person == len(people):
        best = max(best, matches)
        return
    go(person + 1, used, matches)  # skip
    for q in range(len(questions)):
        if q in used:
            continue
        if not shares_tag(person, q):
            continue
        go(person + 1, used | {q},
           matches + 1)
```

TIME	SPACE
O((Q + 1)^P)	O(P)

WHY IT IS SLOW

Each person branches over all questions: exponential. Augmenting paths (move an earlier person to another question when needed) solve it in O(people * edges).

OPTIMAL SOLUTION · Augmenting paths (Kuhn's algorithm)

TIME	SPACE
O(P * E)	O(P + Q)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Priorities: higher-priority people must be served first.

Process people in decreasing priority and run the same augmenting step. Matchings of this kind form a matroid, so this greedy choice gives a matched set with the maximum total priority (checked against exhaustive search).

FOLLOW-UP 2 Edges have weights (how good a match is).

Then it is maximum-weight bipartite matching: the Hungarian algorithm in O(n^3), or min-cost max-flow. Kuhn's algorithm only maximises the count.

FOLLOW-UP 3 A question may take several people (capacity c).

Replicate the question c times as separate right-hand nodes, or run max flow with capacities on the question-to-sink edges.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
# BUILD the person-question graph
def build_graph(people, questions):
    # a person can take a question if they share a tag
    # people: [(name, priority, tags)], questions: [(id,
    # tags, cap)]
    adj = {}
    for name, _, tags in people:
        adj[name] = [q for q, qtags, _ in questions
                     if set(tags) & set(qtags)]
    return adj


# FOLLOW-UP 1: Priorities: higher-priority people must be
# served first.
def assign(people, questions):
    # Kuhn's augmenting paths. People are tried by
    # priority
    # (highest first): such matchings form a matroid, so
    # this
    # greedy order keeps the best possible set of people.
    adj = build_graph(people, questions)
    cap = {q: c for q, _, c in questions}
    # question -> the people currently holding its places
    held = {q: [] for q in cap}

    def try_assign(person, seen):
        for q in adj[person]:
            if q in seen:
                continue
            seen.add(q)
            # a free place, or someone who can move
            # elsewhere
            if len(held[q]) < cap[q]:
                held[q].append(person)
                return True
            for other in list(held[q]):
                if try_assign(other, seen):
                    held[q].remove(other)
                    held[q].append(person)
                    return True
        return False

    order = sorted(people, key=lambda p: -p[1])
    for name, _, _ in order:
        try_assign(name, set())
```

```python
    return {p: q for q, ps in held.items() for p in ps}


# BASE QUESTION (optimal): Augmenting paths (Kuhn's
# algorithm)
def max_matching(adj):
    # the plain version: adj[p] = list of questions for
    # person p
    owner = {}

    def try_assign(p, seen):
        for q in adj[p]:
            if q in seen:
                continue
            seen.add(q)
            free = q not in owner
            if free or try_assign(owner[q], seen):
                owner[q] = p
                return True
        return False

    people = range(len(adj))
    return sum(try_assign(p, set()) for p in people)


if __name__ == "__main__":
    assert max_matching([[0, 1], [0], [1, 2]]) == 3
    assert max_matching([[0], [0], [0]]) == 1
```

```python
    people = [("ann", 1, {"dp"}),
              ("bob", 5, {"dp", "graph"}),
              ("cy", 3, {"graph"})]
    questions = [("q1", {"dp"}, 1), ("q2", {"graph"}, 1)]
    got = assign(people, questions)
    # bob (priority 5) is served first, and the matching
    # is
    # still the largest possible: ann -> q1, bob or cy ->
    # q2
    assert len(got) == 2
    assert got["bob"] in ("q1", "q2")
    # a question with two places takes two people
    q = [("q1", {"dp"}, 2)]
    both = assign(people[:2], q)
    assert set(both) == {"ann", "bob"}
    # nobody shares a tag: nobody is matched
    nobody = assign([("x", 1, {"a"})], [("q", {"b"}, 1)])
```

```python
    assert nobody == {}
```

FUNCTION AND TEST CASES

Signature

```python
def solution(people: list[list[str]], question_tags: list[
list[str]], priorities: list[int]) -> list[int]:
```

Sample call

```python
solution([['python', 'sql'], ['java'], ['ml']], [['sql'],
['java', 'python'], ['ml'], ['go']], [5, 7, 4, 10])
```

Test cases

Input	Expected
`([['python', 'sql'], ['java'], ['ml']], [['sql'], ['java', 'python'], ['ml'], ['go']], [5, 7, 4, 10])`	`(3, 16)`
`([['a'], ['a']], [['a'], ['a'], ['b']], [1, 10, 100])`	`(2, 11)`

MEDIUM | PracHub | Technical Screen | 96 of 165

Maximize 1D deliveries within distance and minimize total distance

POSTED 2025-12-27 | 287 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 36.9 | 30 DAYS 0 | PRIORITY 100/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #455 Assign Cookies, LeetCode #475 Heaters

LeetCode match: No direct match; related LC 455 Assign Cookies / LC 475 Heaters (inferred from overview)

Posted on PracHub: 2025-12-27 (updated 2026-04-23)

Original: https://prachub.com/coding-questions/maximize-1d-deliveries-within-distance-and-minimize-total-distance

QUESTION

Overview: This question evaluates combinatorial optimization and constrained matching skills, focusing on reasoning about distance-based pairings, lexicographic objective prioritization, and edge-case handling such as duplicates and empty inputs.

APPROACH

Sort both lists; two-pointer greedy matching each order to the nearest available driver within the limit, maximizing count first, then minimizing total distance as the tie-break.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what an order and a driver are (points on a line), the distance limit, whether each driver takes one order, and the objective order: first the maximum number of deliveries, then the smallest total distance among those.

BRUTE FORCE TO SAY OUT LOUD

Try every matching of orders to drivers. Exponential.

OPTIMAL IDEA

Sort both lists. On a line there is an optimal matching that does not cross, so a DP over (i, j), the first i orders and first j drivers, works: dp[i][j] is the best pair (maximum matches, minimum distance), taking the maximum of skipping an order, skipping a driver, or matching order i with driver j if their distance is within the limit. O(n * m), reducible to O(n * window) because only drivers within the limit matter. A two-pointer greedy that matches the nearest available driver gives the maximum count in O(n log n) but not necessarily the minimum total distance, so say that.

DRY-RUN THESE CASES

No feasible pairs, duplicates, empty inputs, an order that could match two drivers equally, more drivers than orders.

LIKELY FOLLOW-UPS

Minimizing the maximum distance instead, or drivers with capacities.

PITFALLS

Assuming greedy nearest matching minimizes the total. Comparing the two objectives as a sum instead of lexicographically.

HOW TO THINK ABOUT IT

On a line there is always an optimal matching that does not cross itself, so sort both lists and match in order: a DP over (orders considered, drivers considered) with the pair (matches, total distance) compared lexicographically solves both objectives together. A greedy that matches each order to the nearest free driver gets the count right but not always the smallest total distance.

HOW TO THINK ABOUT IT

Basis: Written; matching on a line. Assumed rules (confirm them): orders and drivers are positions on a line; an order can be served by a driver within distance D; each driver takes at most one order; first maximise the number of deliveries, then minimise the total distance.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
best = (0, 0)  # (matches, -distance)
def go(i, used, matches, dist):
    global best
    if i == len(orders):
        best = max(best, (matches, -dist))
        return
    go(i + 1, used, matches, dist)  # skip
    for d, x in enumerate(drivers):
        gap = abs(orders[i] - x)
        if d not in used and gap <= D:
            go(i + 1, used | {d},
               matches + 1, dist + gap)
```

TIME	SPACE
O(drivers^orders)	O(n)

WHY IT IS SLOW

Each order branches over all drivers: exponential. After sorting, a DP over (orders considered, drivers considered) that compares (matches, minus distance) is O(n * m).

OPTIMAL SOLUTION · DP over sorted orders and drivers, maximising (matches, -distance)

TIME	SPACE
O(n * m)	O(n * m)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Only the number of deliveries matters.

Two pointers on the sorted lists: match when within D, otherwise advance whichever is further left. O(n log n). It maximises the count (checked against exhaustive search) but not the total distance.

FOLLOW-UP 2 A driver can take several orders (capacity c).

Replicate each driver c times (as separate sorted points) and use the same DP, or treat it as min-cost flow with capacities.

FOLLOW-UP 3 Minimise the largest single distance instead of the total.

Binary search the largest allowed distance D and test whether all orders can be served with the two-pointer matching; the check is monotone in D. **Cost:** O(n log n + (n + m) log(range)): sorting plus a binary search whose check is a two-pointer pass.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): DP over sorted orders and
# drivers, maximising (matches ...
def deliveries(orders, drivers, D):
    # first maximise the number of deliveries, then
    # minimise
    # the total distance: a DP over the sorted positions
    o, d = sorted(orders), sorted(drivers)
    # dp[i][j] = (deliveries, -distance) using the first i
    # orders and j drivers; tuples compare
    # lexicographically
    dp = [[(0, 0)] * (len(d) + 1)
          for _ in range(len(o) + 1)]
    for i in range(1, len(o) + 1):
        for j in range(1, len(d) + 1):
            # skip this order or skip this driver ...
            best = max(dp[i - 1][j], dp[i][j - 1])
            gap = abs(o[i - 1] - d[j - 1])
            if gap <= D:
                # ... or pair them
                count, neg = dp[i - 1][j - 1]
                best = max(best, (count + 1, neg - gap))
            dp[i][j] = best
    count, neg = dp[-1][-1]
    return count, -neg


# FOLLOW-UP 1: Only the number of deliveries matters.
def max_count(orders, drivers, D):
    # only the number matters: two pointers on sorted
    # lists
    o, d = sorted(orders), sorted(drivers)
    i = j = count = 0
    while i < len(o) and j < len(d):
        if abs(o[i] - d[j]) <= D:
            count, i, j = count + 1, i + 1, j + 1
        elif o[i] < d[j]:
            # this order is too far left for every driver
            i += 1
        else:
            j += 1
    return count


# FOLLOW-UP 3: Minimise the largest single distance
# instead of the total.
```

```
def smallest_limit(orders, drivers):
    # minimise the LARGEST single distance while serving
    # as
    # many orders as possible: binary search on the limit
    target = min(len(orders), len(drivers))
    lo, hi = 0, 10 ** 9
    while lo < hi:
        mid = (lo + hi) // 2
        if max_count(orders, drivers, mid) >= target:
            hi = mid
        else:
            lo = mid + 1
    return lo


# FOLLOW-UP 2: A driver can take several orders (capacity
# c).
def with_capacity(orders, drivers, D, cap):
    # each driver can take cap orders: repeat the driver
    return deliveries(orders, [x for x in drivers
                               for _ in range(cap)], D)


if __name__ == "__main__":
    assert deliveries([1, 5], [2, 6], 1) == (2, 2)
    # pairing 1-2 and 3-4 beats 1-4 and 3-2? both count 2
    assert deliveries([1, 3], [2, 4], 1) == (2, 2)
    assert deliveries([], [1], 5) == (0, 0)
    # a distance limit of 0 needs identical positions
    assert deliveries([1, 2], [2, 3], 0) == (1, 0)
    assert max_count([1, 3], [2, 4], 1) == 2
    assert max_count([1, 10], [5], 2) == 0
    assert smallest_limit([1, 5], [2, 9]) == 4
    assert with_capacity([1, 2, 3], [2], 1, 3) == (3, 2)
```

FUNCTION AND TEST CASES

Signature

```
def solution(people: list[int], shops: list[int], D: int)
-> tuple[int, int]:
```

Sample call

```
solution([1, 7, 10], [2, 6, 12], 2)
```

Test cases

Input	Expected
([1, 7, 10], [2, 6, 12], 2)	(3, 4)
([0, 4], [2, 5], 3)	(2, 3)

MEDIUM | PracHub | Technical Screen | 97 of 165

★ TOP 75: rank 70 in the Medium and Hard priority list

★ Solve chat, grid paths, and car rentals

POSTED 2025-12-02 | 312 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 58 | 30 DAYS 0 | PRIORITY 42/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #692 Top K Frequent Words, LeetCode #62 Unique Paths, LeetCode #253 Meeting Rooms II

LeetCode match: LC 692 Top K Frequent Words + LC 62/63 Unique Paths + LC 253

Posted on PracHub: 2025-12-02 (updated 2026-05-02)

Original: https://prachub.com/interview-questions/solve-chat-grid-paths-and-car-rentals

QUESTION

You are given three independent programming tasks. For each, describe and implement an efficient algorithm, and be prepared to analyze its time and space complexity. ---

Q1.

QUESTION

Find top-K most active chat users You are given a log of chat messages from a messaging application.
Input:

- An array **`messages`** of length **`n`**, where each element **`messages[i]`** is the **`user_id`** (string or integer) of the sender of the i-th message.
- An integer **`k`** (1 <= k <= number of distinct users).

Output:

- Return a list of **`k`** user IDs corresponding to the users who have sent the most messages.

Details & requirements:

- The "activity" of a user is defined as the number of messages they have sent (i.e., their frequency in **`messages`**).
- If there are fewer than **`k`** distinct users, return all distinct users.
- If multiple users have the same frequency, you may break ties arbitrarily, or (for determinism) sort tied users by **`user_id`** in ascending order.
- Aim for an algorithm that is more efficient than sorting all users by count when **`k`** is much smaller than the number of distinct users. Design and implement a function, for example:
- **`List<UserId> topKActiveUsers(List<UserId> messages, int k)`** Also explain:
- At least two different approaches (e.g., based on sorting, heaps, or selection algorithms).
- The time and space complexity of each approach. ---

Q2.

Count paths in a 2D grid with constrained moves You have a 2D grid with **`m`** rows and **`n`** columns. Index rows from top to bottom as **`0..m-1`** and columns from left to right as **`0..n-1`**.

- The **start** cell is the bottom-left corner: **`(m-1, 0)`**.
- The **end** cell is the bottom-right corner: **`(m-1, n-1)`**. From any cell **`(r, c)`**, you may move **only** to the next column to the right, in one of up to three ways (if within bounds):
- Right-up: **`(r-1, c+1)`**
- Right: **`(r, c+1)`**
- Right-down: **`(r+1, c+1)`** You cannot move left or stay in the same column. All cells are passable (no obstacles).

Task:

- Given integers **`m`** and **`n`**, compute the total number of distinct paths from the start cell **`(m-1, 0)`** to the end cell **`(m-1, n-1)`** using only the allowed moves.

Requirements:

- Implement a function such as **`long countPaths(int m, int n)`**.

QUESTION

- The result may be large; assume it fits in a 64-bit integer, or, if you prefer, you may return the count modulo a large prime (e.g., 1,000,000,007) — specify which convention you are using.
- First design a straightforward dynamic programming solution using O(m·n) time and O(m·n) space.
- Then describe how to optimize the space usage (e.g., to O(m)) while keeping the same time complexity, and explain why the optimization is correct. ---

Q3.

Minimum cars needed for rentals and assignment You work at a car rental company. You are given a list of rental bookings, each with a pickup and return time.
Input:

- An array of **`R`** rental records. Each record has:
- **`rental_id`**: a unique identifier (e.g., integer or string).
- **`pickup_time`**: an integer start time.
- **`return_time`**: an integer end time, with **`pickup_time < return_time`**. Assume times are on a single timeline (e.g., minutes from some epoch). A car can be reassigned immediately after it is returned, i.e., if one rental ends at time **`t`** and another starts at time **`t`**, the same car can serve both.

Tasks: 1.
Capacity: Compute the **minimum number of cars** required so that all rentals can be fulfilled without time conflicts on any single car. 2.
Assignment: Produce one valid assignment of rentals to cars that uses exactly that minimum number of cars.
Output:

- An integer **`C`** = minimal number of cars needed.
- A mapping from each **`rental_id`** to a **`car_id`** in the range **`1..C`**, such that no two rentals assigned to the same **`car_id`** overlap in time.

Requirements & clarifications:

- Overlap definition: two rentals with intervals **`[s1, e1)`** and **`[s2, e2)`** overlap if their time intervals intersect with non-empty duration. Using half-open intervals, if **`e1 == s2`** they do **not** over

APPROACH

Top-K messages via counts + heap; grid paths via DP (with obstacles if present); car rentals = minimum fleet = max overlapping reservations (sweep line).

INTERVIEW-DAY PLAN

CLARIFY FIRST

INTERVIEW-DAY PLAN

Three independent tasks. Chat: activity means the number of messages, ties resolved how? Grid paths: moves right or down only, with or without obstacles, modulo? Car rentals: minimum cars equals the maximum overlap of reservations; does a car returned at time t serve a rental starting at t?

BRUTE FORCE TO SAY OUT LOUD

Chat: sort the counts. Grid: recursion without memory. Cars: assign reservations to cars one by one.

OPTIMAL IDEA

Chat: Counter and heapq.nsmallest with the key (count descending, user id ascending). Grid: dp over cells with a rolling row, dp[j] += dp[j - 1], and 0 on obstacles; O(mn) time, O(n) space. Cars: sort the reservations by start and keep a min-heap of end times; reuse the earliest-ending car if it is free, else add one. The heap size at the end is the answer.

DRY-RUN THESE CASES

Chat: ties, fewer users than K. Grid: 1 x n, an obstacle on the start, no path. Cars: back-to-back rentals, one rental, all identical.

LIKELY FOLLOW-UPS

Chat in a stream, grid paths with diagonal moves, cars with a fixed fleet size and rejecting requests.

PITFALLS

Treating back-to-back as overlapping. Forgetting the modulo in the grid count if the statement requires it.

HOW TO THINK ABOUT IT

Three unrelated tasks, so say so and give each a one-line plan. Chat: count, then take the top K with a heap. Grid: each column depends only on the previous one, so keep one column. Cars: the minimum number of cars is the largest number of rentals that overlap at once, which a heap of return times tracks while also giving an assignment.

Basis: Three independent tasks: top K frequent items (LeetCode 347 / 692), grid path counting (a Unique Paths variant) and minimum meeting rooms with assignment (LeetCode 253 plus the assignment step).

BRUTE FORCE · Q1: sort all users by (count, user id)

BRUTE FORCE · PSEUDO-CODE

```
def top_k_users(log, k):
    counts = Counter(msg.user for msg in log)
    def rank(u):
        return (-counts[u], u)
    return sorted(counts, key=rank)[:k]
```

TIME	SPACE
O(d log d)	O(d)

WHY IT IS SLOW

Sorting all d distinct users costs O(d log d) even though only K are needed; a heap of size K costs O(d log k).

BRUTE FORCE · Q2: plain recursion over the moves

BRUTE FORCE · PSEUDO-CODE

```
def ways(r, c):
    if c == n - 1:
        return 1 if r == n - 1 else 0
    total = 0
    for dr in (-1, 0, 1):
        if 0 <= r + dr < n:
            total += ways(r + dr, c + 1)
    return total
```

TIME	SPACE
O(3^n)	O(n)

WHY IT IS SLOW

Three calls per cell and the same cell is reached by many paths, so the call tree has about 3^n nodes. One column at a time with a rolling array is O(m * n).

BRUTE FORCE · Q3: count the overlap at every time and assign greedily without a heap

BRUTE FORCE · PSEUDO-CODE

```
def cars_needed(rentals):
    free_at = []  # per car
    for start, end in sorted(rentals):
        for i, f in enumerate(free_at):
            if f <= start:
                free_at[i] = end  # reuse
                break
        else:
            free_at.append(end)  # new car
    return len(free_at)
```

TIME	SPACE
O(R^2)	O(R)

WHY IT IS SLOW

Each rental scans every car, so the cost is O(R * cars), up to O(R^2). A heap of free times finds the earliest-free car in O(log R).

OPTIMAL SOLUTION · Q1: top-K active users with a size-K heap

TIME	SPACE
O(n + d log k) for d distinct users	O(d)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Q2: count constrained paths with a rolling column

TIME	SPACE
O(m * n)	O(m)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Q3: minimum cars and one valid assignment

TIME	SPACE
O(R log R)	O(R)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Q1: what if the log is a stream and memory is limited?

Use a heavy-hitters sketch: Misra-Gries keeps k counters and is exact for any user with more than n / (k + 1) messages; a count-min sketch plus a small heap estimates the top K in O(1) memory per update. For exact answers across machines, count per shard, send each shard's local top-K plus a threshold, and merge.

FOLLOW-UP 2 Q2: what changes if there are obstacles or the path may also go straight up and down?

Obstacles just force ways[r] = 0 for blocked cells in the column being built. Allowing vertical moves inside a column makes each column a chain, so the transition becomes a linear recurrence solved by a prefix pass, still O(m * n). For huge n, use matrix exponentiation of the m x m transition matrix: O(m^3 log n).

FOLLOW-UP 3 Q3: how do you answer 'is one more rental possible' online?

Keep the busy heap and the free-car count between calls. A new rental fits without a new car if any car's return time is <= its pickup, which is a heap peek after popping everything that returned before the pickup. That is O(log R) per query.

FOLLOW-UP 4 Q2 with obstacles.

A blocked cell contributes zero ways when its column is built; everything else is unchanged. O(m * n).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import Counter


# BASE QUESTION (optimal): Q1: top-K active users with a
# size-K heap
def top_k_users(messages, k):
    # Q1, heap: O(n + d log k); sorted order breaks ties
    counts = Counter(messages)
    best = heapq.nsmallest(
        k, counts.items(), key=lambda kv: (-kv[1], kv[0]))
    return [user for user, _ in best]


# Q1 second approach: sort every user
def top_k_users_sorted(messages, k):
    # Q1, second approach: sort every user, O(d log d)
    counts = Counter(messages)
    ranked = sorted(counts, key=lambda u: (-counts[u], u))
    return ranked[:k]


# BASE QUESTION (optimal): Q1: top-K active users with a
# size-K heap
def count_paths(m, n, blocked=(), mod=None):
    # Q2: start (m-1, 0), end (m-1, n-1), moves right-up,
    # right, right-down. One column of ways is enough:
    # O(m).
    wall = set(blocked)
    ways = [0] * m
    ways[m - 1] = 1
    for c in range(1, n):
        nxt = [0] * m
        for r in range(m):
            # FOLLOW-UP 4: blocked cells (obstacles) give
            # no paths
            if (r, c) in wall:
                # a blocked cell contributes no paths
                continue
            total = ways[r]
            if r > 0:
                total += ways[r - 1]
            if r + 1 < m:
                total += ways[r + 1]
            nxt[r] = total % mod if mod else total
        ways = nxt
    return ways[m - 1]


# BASE QUESTION (optimal): Q1: top-K active users with a
# size-K heap
def min_cars(rentals):
    # Q3: rentals are (pickup, return); how many cars are
    # needed?
    # A heap holds the return times of the cars on the
    # road.
    cars = []
    for pickup, back in sorted(rentals):
        if cars and cars[0] <= pickup:
            # a car came back in time: reuse it
            heapq.heapreplace(cars, back)
        else:
            heapq.heappush(cars, back)
    return len(cars)


# FOLLOW-UP 3: Q3: how do you answer 'is one more rental
# possible' online?
class RentalDesk:
    """Online: can one more rental be served right now?"""

    def __init__(self, fleet):
        self.fleet, self.out = fleet, []

    def rent(self, pickup, back):
        # cars returned by `pickup` are free again
        while self.out and self.out[0] <= pickup:
            heapq.heappop(self.out)
        if len(self.out) >= self.fleet:
            return False
        heapq.heappush(self.out, back)
        return True


if __name__ == "__main__":
    log = ["a", "b", "a", "c", "a", "b"]
    assert top_k_users(log, 2) == ["a", "b"]
```

```
assert top_k_users_sorted(log, 5) == ["a", "b", "c"]
# grid paths: a 3 x 3 grid has 2 paths along the
# bottom
```

```
assert count_paths(3, 3) == 2
assert count_paths(1, 5) == 1
assert count_paths(3, 1) == 1
assert count_paths(4, 5) == 9
# an obstacle in the middle of the bottom row
assert count_paths(3, 3, blocked=[(2, 1)]) == 1
modulus = 10 ** 9 + 7
assert count_paths(5, 30, mod=modulus) < modulus
cars = [(1, 4), (2, 5), (4, 6), (5, 8)]
assert min_cars(cars) == 2
assert min_cars([]) == 0
desk = RentalDesk(1)
assert desk.rent(1, 4) and not desk.rent(2, 3)
assert desk.rent(4, 6)
```

FULL QUESTION TEXT FROM THE SITE

You are given three independent programming tasks. For each, describe and implement an efficient algorithm, and be prepared to analyze its time and space complexity.

Q1. Find top-K most active chat users

You are given a log of chat messages from a messaging application.

Input:

An array messages of length n , where each element messages[i] is the user_id (string or integer) of the sender of the i-th message.
An integer k (1 <= k <= number of distinct users).

Output:

Return a list of k user IDs corresponding to the users who have sent the most messages.

Details & requirements:

The "activity" of a user is defined as the number of messages they have sent (i.e., their frequency in messages).
If there are fewer than k distinct users, return all distinct users.
If multiple users have the same frequency, you may break ties arbitrarily, or (for determinism) sort tied users by user_id in ascending order.
Aim for an algorithm that is more efficient than sorting all users by count when k is much smaller than the number of distinct users.

Design and implement a function, for example:

List<UserId> topKActiveUsers(List<UserId> messages, int k)

Also explain:

At least two different approaches (e.g., based on sorting, heaps, or selection algorithms).
The time and space complexity of each approach.
Q2. Count paths in a 2D grid with constrained moves

You have a 2D grid with m rows and n columns. Index rows from top to bottom as 0..m-1 and columns from left to right as 0..n-1.

FULL QUESTION TEXT FROM THE SITE

The start cell is the bottom-left corner: (m-1, 0) .
The end cell is the bottom-right corner: (m-1, n-1) .

From any cell (r, c), you may move only to the next column to the right, in one of up to three ways (if within bounds):

Right-up: (r-1, c+1)
Right: (r, c+1)
Right-down: (r+1, c+1)

You cannot move left or stay in the same column. All cells are passable (no obstacles).

Task:

Given integers m and n , compute the total number of distinct paths from the start cell (m-1, 0) to the end cell (m-1, n-1) using only the allowed moves.

Requirements:

Implement a function such as long countPaths(int m, int n) .
The result may be large; assume it fits in a 64-bit integer, or, if you prefer, you may return the count modulo a large prime (e.g., 1,000,000,007) — specify which convention you are using.
First design a straightforward dynamic programming solution using O(m·n) time and O(m·n) space.
Then describe how to optimize the space usage (e.g., to O(m)) while keeping the same time complexity, and explain why the optimization is correct.
Q3. Minimum cars needed for rentals and assignment

You work at a car rental company. You are given a list of rental bookings, each with a pickup and return time.

Input:

An array of R rental records. Each record has:
rental_id : a unique identifier (e.g., integer or string).
pickup_time : an integer start time.
return_time : an integer end time, with pickup_time < return_time .

Assume times are on a single timeline (e.g., minutes from some epoch). A car can be reassigned immediately after it is returned, i.e., if one rental ends at time t and another starts at time t, the same car can serve both.

Tasks:

Capacity : Compute the minimum number of cars required so that all rentals can be fulfilled without time conflicts on any single car.
Assignment : Produce one valid assignment of rentals to cars that uses exactly that minimum number of cars.

Output:

An integer C = minimal number of cars needed.
A mapping from each rental_id to a car_id in the range 1..C , such that no two rentals assigned to the same car_id overlap in time.

Requirements & clarifications:

FULL QUESTION TEXT FROM THE SITE

Overlap definition: two rentals with intervals [s1, e1) and [s2, e2) overlap if their time intervals intersect with non-empty duration. Using half-open intervals, if e1 == s2 they do not overlap.
Aim for an algorithm that is efficient for up to, say, 10^5 rental records.
Discuss a naive approach and then an optimized approach (for example, using a min-heap/priority queue keyed by the earliest return time to track currently in-use cars).
Analyze the time and space complexity of your final solution.

MEDIUM | IN APP LC 2 | PracHub | Technical Screen | 98 of 165

★ TOP 75: rank 1 in the Medium and Hard priority list

★ Add two big integers from digit lists

POSTED 2025-11-24 | 320 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 78.7 | 30 DAYS 69.3 | PRIORITY 1/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #2 Add Two Numbers

LeetCode match: LC 2 Add Two Numbers

Posted on PracHub: 2025-11-24 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/add-two-big-integers-from-digit-lists

QUESTION

You are given two non-empty singly linked lists (or arrays) representing two non-negative integers. The digits are stored in **reverse order**, and each node contains a single digit from 0 to 9. Your task is to add the two numbers and return the sum as a new linked list, also in reverse order. You may assume:

- Each list has at least one node.
- The integers do not contain leading zeros, except the number 0 itself.

Example

Input:

- List 1: 2 -> 4 -> 3 (represents the integer 342)
- List 2: 5 -> 6 -> 4 (represents the integer 465)

Output:

- 7 -> 0 -> 8 (represents the integer 807, since 342 + 465 = 807)

Another example

Input:

- List 1: 9 -> 9 -> 9 (represents 999)
- List 2: 1 (represents 1)

Output:

- 0 -> 0 -> 0 -> 1 (represents 1000)

QUESTION

Constraints

- Let n be the length of the first list and m be the length of the second list.
- 1 <= n, m <= 10^5.
- Each node value is an integer in the range [0, 9].

Task: Describe an algorithm to perform this addition and construct the resulting linked list in O(n + m) time and O(1) additional space (excluding the space for the output list).

You are given two non-empty arrays of digits representing two non-negative integers. The digits are stored in **reverse order** (least significant digit first), and each element is a single digit from 0 to 9. Add the two numbers and return the sum as a new array of digits, also in reverse order.

Assumptions

- Each array has at least one element.
- The integers do not contain leading zeros, except the number 0 itself.

Example 1

```
Input: l1 = [2, 4, 3], l2 = [5, 6, 4] (342 + 465)
Output: [7, 0, 8] (807)
```

Example 2

```
Input: l1 = [9, 9, 9], l2 = [1] (999 + 1)
Output: [0, 0, 0, 1] (1000)
```

Implement **`add_two_numbers(l1, l2)`** (camelCase **`addTwoNumbers`** in Java/C++/JS) returning the digit array of the sum in reverse order. Aim for O(n + m) time and O(1) extra space beyond the output.
Constraints
1 <= n, m <= 10^5 where n = len(l1), m = len(l2)Each element is an integer in the range [0, 9]Digits are stored in reverse order (least significant digit first)No leading zeros except for the number 0 itself

EXAMPLES

```
Input: ([2, 4, 3], [5, 6, 4])
Expected Output: [7, 0, 8]
Explanation: 342 + 465 = 807, stored reversed as [7,
    0, 8].
Input: ([9, 9, 9], [1])
Expected Output: [0, 0, 0, 1]
```

Explanation: 999 + 1 = 1000; carry propagates through all three digits and creates a new leading digit.

Hints

Walk both arrays from index 0 (the least significant digit) toward the end, just like grade-school column addition.Maintain a single carry variable. At each position, sum the available digits plus the carry; append (sum % 10) and set carry = sum // 10.When one array runs out, keep going with just the carry and the remaining longer array. Don't forget a final carry can add one extra digit (e.g. 999 + 1 -> [0,0,0,1]).

APPROACH

Walk both lists with a carry, build the result list. O(max(m, n)).

HOW TO THINK ABOUT IT

Addition by hand: start at the least significant end, add the two digits and the carry, write digit % 10, carry digit // 10. The only edge cases are different lengths and a final carry. Never convert to a machine integer in an interview about big numbers, since the point is that the numbers do not fit.

Basis: LeetCode 989 / 415 (Add to Array-Form of Integer, Add Strings). Assumed input: lists of decimal digits, most significant digit first.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def add_lists(a, b):
    x = digits_to_int(a)  # reverse-order digits
    y = digits_to_int(b)
    return int_to_digits(x + y)
```

TIME	SPACE
O(n^2) for the string-to-integer conversions	O(n)

WHY IT IS SLOW

It relies on arbitrary-size integers and the conversions are quadratic for very long inputs. Adding digit by digit from the right with a carry is O(max length).

OPTIMAL SOLUTION · Digit by digit with a carry

TIME	SPACE
O(max(m, n))	O(max(m, n))

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The digits are stored least significant first in a linked list.

Then the head is already the low end, so walk both lists together with the same carry loop and build the result list as you go. No reversal needed (LeetCode 2).

FOLLOW-UP 2 Multiply instead of add.

Schoolbook multiplication: the product of digits a[i] and b[j] lands in position i + j + 1, with the carry spilling to i + j. O(m * n); Karatsuba or FFT for very long numbers.

FOLLOW-UP 3 Subtract, or numbers in another base.

Subtraction borrows instead of carrying and needs the larger number first (compare lengths, then digits). Another base replaces 10 with the base in % and //.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val, self.next = val, next


def make(digits):
    # digits least significant first -> linked list
    head = tail = ListNode(digits[0])
    for d in digits[1:]:
        tail.next = ListNode(d)
        tail = tail.next
    return head


def to_digits(node):
    out = []
    while node:
        out.append(node.val)
        node = node.next
    return out


# FOLLOW-UP 1: The digits are stored least significant
# first in a linked list.
def add_lists(a, b):
    # digits least significant first: add with a carry,
    # one pass
    dummy = tail = ListNode()
    carry = 0
    while a or b or carry:
        total = carry
        total += a.val if a else 0
        total += b.val if b else 0
        tail.next = ListNode(total % 10)
        tail, carry = tail.next, total // 10
        a = a.next if a else None
        b = b.next if b else None
    return dummy.next


# BASE QUESTION (optimal): Digit by digit with a carry
def add_digits(a, b):
    # arrays with the most significant digit FIRST
    i, j, carry, out = len(a) - 1, len(b) - 1, 0, []
    while i >= 0 or j >= 0 or carry:
        total = carry
        total += a[i] if i >= 0 else 0
        total += b[j] if j >= 0 else 0
        out.append(total % 10)
        carry = total // 10
        i, j = i - 1, j - 1
    return out[::-1] or [0]


# FOLLOW-UP 2: Multiply instead of add.
def multiply_digits(a, b):
    # schoolbook: digit a[i] * b[j] lands at position i +
    # j + 1
```

```
    res = [0] * (len(a) + len(b))
    for i in range(len(a) - 1, -1, -1):
        for j in range(len(b) - 1, -1, -1):
            total = a[i] * b[j] + res[i + j + 1]
            res[i + j + 1] = total % 10
            res[i + j] += total // 10
    while len(res) > 1 and res[0] == 0:
        res.pop(0)
    return res


# FOLLOW-UP 3: Subtract, or numbers in another base.
def subtract_digits(a, b):
    # a - b where a >= b (most significant first): borrow
    i, j, borrow, out = len(a) - 1, len(b) - 1, 0, []
    while i >= 0:
        d = a[i] - borrow - (b[j] if j >= 0 else 0)
        borrow = 1 if d < 0 else 0
        out.append(d + 10 * borrow)
        i, j = i - 1, j - 1
    while len(out) > 1 and out[-1] == 0:
        out.pop()
    return out[::-1]


if __name__ == "__main__":
    # 342 + 465 = 807, digits reversed
    got = add_lists(make([2, 4, 3]), make([5, 6, 4]))
    assert to_digits(got) == [7, 0, 8]
    # a final carry adds a digit: 99 + 1 = 100
    carry = add_lists(make([9, 9]), make([1]))
    assert to_digits(carry) == [0, 0, 1]
```

```
    assert add_digits([9, 9, 9], [1]) == [1, 0, 0, 0]
    assert add_digits([0], [0]) == [0]
    product = multiply_digits([1, 2, 3], [4, 5])
    assert product == [5, 5, 3, 5]
    assert multiply_digits([0], [9, 9]) == [0]
    assert subtract_digits([1, 0, 0], [1]) == [9, 9]
    assert subtract_digits([5, 0], [5, 0]) == [0]
```

FUNCTION AND TEST CASES

Sample call

```
add_two_numbers([2, 4, 3], [5, 6, 4])
```

Test cases

Input	Expected
`([2, 4, 3], [5, 6, 4])`	`[7, 0, 8]`
`([9, 9, 9], [1])`	`[0, 0, 0, 1]`

MEDIUM | IN APP LC 501 | PracHub | Technical Screen | 99 of 165

Find mode in a trinary search tree

POSTED 2025-11-16 | 328 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 25.5 | 30 DAYS 0 | PRIORITY 136/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #501 Find Mode in Binary Search Tree

LeetCode match: LC 501 Find Mode in Binary Search Tree

Posted on PracHub: 2025-11-16 (updated 2026-06-20)

Original:
https://prachub.com/coding-questions/find-mode-in-a-trinary-search-tree

QUESTION

You are given the root of a **trinary search tree** where each node has up to three children:

```
class Node { int val; Node left; // all values < val N
ode middle; // all values = val Node right; // all val
ues > val }
```

Assume the tree is intended to satisfy the ordering rules above.

Task

Return the **mode(s)** of the tree: the value(s) that occur most frequently among all nodes.

- If there is one mode, return a single-element list.
- If multiple values tie for highest frequency, return **all** such values (in any order).

Constraints (typical)

- Number of nodes **n** can be large (e.g., up to **`10^5`**).
- Values can be any 32-bit signed integers.

Follow-up

How would your approach change if the tree is **broken** (i.e., it may not respect the **<**, **=**, **>** constraints), but you still must return the correct mode(s)?

QUESTION

Part 1: Find Mode(s) in a Valid Trinary Search TreeYou are given a valid trinary search tree. Each node has an integer value and up to three children: left, middle, and right. For every node, all values in its left subtree are strictly less than the node's value, all values in its middle subtree are equal to the node's value, and all values in its right subtree are strictly greater than the node's value. The tree is encoded using parallel arrays instead of Node objects. Return the value or values that occur most frequently in the tree. To make the output deterministic, return the modes in increasing order. If the tree is empty, return an empty list.
Constraints
0 <= n <= 100000, where n == len(values)len(left) == len(middle) == len(right) == nEach child index is either -1 or an integer in [0, n - 1]root == -1 if n == 0; otherwise 0 <= root < nThe nodes reachable from root form a valid tree with no cyclesThe tree satisfies the trinary search ordering rules recursivelyEach value is a 32-bit signed integer

EXAMPLES

```
Input: ([], [], [], [], -1)
Expected Output: []
```

Explanation: The tree is empty, so there are no modes.

```
Input: ([42], [-1], [-1], [-1], 0)
Expected Output: [42]
```

Explanation: A single-node tree has that node's value as the only mode.

Hints
In a valid trinary search tree, an inorder traversal using left, node, middle, right visits values in nondecreasing order.Because equal values appear consecutively during that traversal, you can track only the current run length and the best run length so far.
Part 2: Find Mode(s) in a Broken Trinary TreeYou are given a trinary tree with integer values. Each node has up to three children: left, middle, and right. Unlike a valid trinary search tree, this tree may be broken: the left, middle, and right children do not necessarily follow any ordering rules. Return the value or values that occur most frequently among all reachable nodes. To make the output deterministic, return the modes in increasing order. If the tree is empty, return an empty list.
Constraints
0 <= n <= 100000, where n == len(values)len(left) == len(middle) == len(right) == nEach child index is either -1 or an integer in [0, n - 1]root == -1 if n == 0; otherwise 0 <= root < nThe nodes reachable from root form a tree with no cyclesNo ordering rule is guaranteed between a node and its childrenEach value is a 32-bit signed integer
Examples
Input: ([], [], [], [], -1)
Expected Output: []

QUESTION

Explanation: The tree is empty, so there are no modes.
Input: ([-2147483648], [-1], [-1], [-1], 0)
Expected Output: [-2147483648]
Explanation: A single-node tree has that node's value as the only mode.
Hints
Without the ordering property, equal values are not guaranteed to be adjacent in any traversal.Use a frequency table while traversing the entire tree.

APPROACH

In-order traversal (left, middle, right) so equal values are consecutive; track current run length and the max; O(h) extra space.

HOW TO THINK ABOUT IT

In a valid search tree an in-order walk (left, middle, right) visits values in sorted order, so equal values are adjacent and you can count runs with a single running counter and O(height) memory instead of a dictionary. If the tree may be broken, the order guarantee is gone and you need a real frequency table.

Basis: LeetCode 501, Find Mode in Binary Search Tree, with a middle child for equal values. Valid case: left < val, middle = val, right > val.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def modes(root):
    counts = Counter()
    stack = [root]
    while stack:
        node = stack.pop()
        if node:
            counts[node.val] += 1
            stack += [node.left, node.middle,
                      node.right]
    top = max(counts.values())
    return [v for v in counts
            if counts[v] == top]
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

O(n) time but memory for every distinct value. In a valid tree an in-order walk (left, middle, right) gives equal values consecutively, so a running counter needs only O(height) space.

OPTIMAL SOLUTION · In-order traversal counting runs (O(height) extra space)

TIME	SPACE
O(n)	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The tree may be broken (it does not respect the ordering).

In-order no longer gives sorted values, so equal values need not be adjacent. Fall back to a frequency table over a full traversal (the Counter version): O(n) time, O(distinct values) space.

FOLLOW-UP 2 Only O(1) extra space (no stack, no dictionary).

Use Morris traversal for the in-order walk (temporary threads) with the same running-count logic; it mutates the tree briefly, so restore the pointers. Adapting it to the middle child needs care.

FOLLOW-UP 3 The tree is huge and values arrive in a stream.

For a stream use a count dictionary (or a Misra-Gries summary if only frequent values matter); the sorted-order trick needs the whole tree in order. **Cost:** O(1) per value with a counter and O(d) memory for the distinct values (or O(1 / epsilon) with Misra-Gries).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


class TNode:
    def __init__(self, val, left=None, middle=None,
                 right=None):
        # left < val, middle == val, right > val
        self.val, self.left = val, left
        self.middle, self.right = middle, right


# BASE QUESTION (optimal): In-order traversal counting
# runs (O(height) extra space)
def find_modes(root):
    # in-order: equal values are next to each other, so a
    # running count needs no dictionary
    best, modes, cur, run = 0, [], None, 0

    def visit(v):
        nonlocal best, modes, cur, run
        run = run + 1 if v == cur else 1
        cur = v
        if run > best:
            best, modes = run, [v]
        elif run == best and v not in modes:
            modes.append(v)

    stack, node = [], root
    while stack or node:
        while node:
            stack.append(node)
            node = node.left
        node = stack.pop()
        visit(node.val)
        # the middle chain repeats node.val once per child
        mid = node.middle
        while mid:
            visit(mid.val)
            mid = mid.middle
        node = node.right
    return sorted(modes)


# FOLLOW-UP 1: The tree may be broken (it does not respect
# the ordering).
```

```
def find_modes_counter(root):
    # a broken tree (ordering not respected): count
    # everything
    counts, stack = Counter(), [root] if root else []
    while stack:
        node = stack.pop()
        counts[node.val] += 1
        for child in (node.left, node.middle, node.right):
            if child:
                stack.append(child)
    if not counts:
        return []
    top = max(counts.values())
    return sorted(v for v in counts if counts[v] == top)


if __name__ == "__main__":
    #        5
    #     /  |  \
    #    3   5   8
    #   /|       |
    #  3 3       8
    threes = TNode(3, None, TNode(3, None, TNode(3)))
    tree = TNode(5, threes, TNode(5),
                 TNode(8, None, TNode(8)))
    assert find_modes(tree) == [3]
    assert find_modes_counter(tree) == [3]
    # a tie between 1 and 2
    tie = TNode(2, TNode(1), TNode(2), None)
    assert find_modes(tie) == [2]
    assert find_modes_counter(tie) == [2]
    assert find_modes(None) == []
    assert find_modes_counter(None) == []
    tie2 = TNode(2, TNode(1), None, TNode(3))
    assert find_modes(tie2) == [1, 2, 3]
```

FUNCTION AND TEST CASES

Signature

```
def solution(values: list[int], left: list[int], middle: l
ist[int], right: list[int], root: int) -> list[int]:
```

Sample call

```
solution([], [], [], [], -1)
```

Test cases

Input	Expected
([], [], [], [], -1)	[]
([42], [-1], [-1], [-1], 0)	[42]

MEDIUM | PracHub | Technical Screen | 100 of 165

★ TOP 75: rank 35 in the Medium and Hard priority list

★ Find shared objects across two log files

POSTED 2025-11-05 | 339 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 50.4 | 30 DAYS 46.9 | PRIORITY 22/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 349 Intersection of Two Arrays

Posted on PracHub: 2025-11-05 (updated 2026-06-27)

Original: https://prachub.com/coding-questions/find-shared-objects-across-two-log-files

QUESTION

You are given two large log files representing activity on two different days. Each line of each log has three fields:

- **`timestamp`**: a time value (you may treat it as an opaque string or integer)
- **`obj_id`**: identifier of an object (string or integer)
- **`client_id`**: identifier of a client (string or integer) The logs are not necessarily sorted by any field. Define an object as **interesting** if:

1. Its **`obj_id`** appears at least once in day 1's log **and** at least once in day 2's log; and 2. Across all of its appearances in both days combined, it is associated with at least **two distinct `client_id`** values.

Tasks

1. Design and implement a function that, given file handles (or streaming iterators) for the two log files, returns the set of all such interesting **`obj_id`**s.
2. For your initial, straightforward in-memory solution (you may assume both logs fit in memory), state the time and space complexity in terms of the total number of log records.
3. Follow-up (memory constrained): Now assume the logs are very large and **cannot** both fit into memory at once.

- You may still sequentially scan each file and you may perform external sorting.
- Describe how you would modify your approach to work under this memory constraint.
- Analyze the time and space complexity of this memory-efficient solution.

Return sorted obj_ids that appear in both day logs and have at least two distinct client_ids across both days combined.
Constraints
Rows are [timestamp, obj_id, client_id] or dicts with those fields

QUESTION

EXAMPLES

```
Input: ([['t1', 'o1', 'c1'], ['t2', 'o2', 'c1']],
    [['t3', 'o1', 'c2'], ['t4', 'o2', 'c1']])
Expected Output: ['o1']
Input: ([], [['t', 'o', 'c']])
Expected Output: []
```

Hints

Track which days each object appears in and its set of clients.

APPROACH

Load the smaller file's obj_ids into a hash set, stream the other and collect matches; if both are huge use external sort/merge or hash partitioning to disk (or a Bloom filter prefilter).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether to report distinct ids or every occurrence, how large each file is, whether order matters, and what to output (ids only or full lines).

BRUTE FORCE TO SAY OUT LOUD

For each id in file A scan file B. O(n * m), unusable at scale.

OPTIMAL IDEA

Load the ids of the smaller file into a hash set, stream the larger file and collect hits (O(n + m) time). If both do not fit in memory, hash-partition both files by id into buckets on disk so each bucket pair fits, then join bucket by bucket; or external sort both and merge. A Bloom filter of one file prefilters the other.

DRY-RUN THESE CASES

Empty file, duplicate ids, identical files, no overlap, ids that differ only in case or whitespace.

LIKELY FOLLOW-UPS

Distributed version (shuffle by key), top N shared ids by frequency, restrict to a time window.

PITFALLS

Loading both files into memory. Not deduplicating output.

HOW TO THINK ABOUT IT

A common key in two files is a join. If one file fits in memory, load its keys into a set and stream the other. If neither fits, split both files by hash of the key into buckets small enough for memory; equal keys always land in the same bucket number, so you only compare bucket i of one file with bucket i of the other (Grace hash join).

Basis: Written; a join of two large relations (external hash join). Line format assumed: 'timestamp obj_id other'.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(file_a, file_b):
    shared = set()
    for a in file_a:
        for b in file_b:
            if a.obj_id == b.obj_id:
                shared.add(a.obj_id)
    return shared
```

TIME	SPACE
O(n * m)	O(1) extra

WHY IT IS SLOW

O(n * m) comparisons. Loading the smaller file's ids into a hash set and streaming the other file is O(n + m); if neither fits, partition both by a hash of the id.

OPTIMAL SOLUTION · Hash set of the smaller file's ids

TIME	SPACE
O(n + m)	O(distinct ids of the smaller file)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Both files are too big for memory.

Hash-partition both files into B buckets on disk by hash of the object id, then process bucket pairs one at a time with the in-memory set join. Choose B so that one bucket of the smaller file fits in memory. External sort and merge also works.

FOLLOW-UP 2 Want objects seen on both days within an hour of each other.

Keep a list of timestamps per id in the set join and compare timestamps (sorted lists with two pointers), instead of just membership.

FOLLOW-UP 3 A tiny memory budget and an approximate answer is fine.

Build a Bloom filter from one file and test the other against it, accepting a small false-positive rate; verify the few hits exactly in a second pass if needed. **Cost:** O(n + m) time with O(bits) memory for the Bloom filter and a small false-positive rate.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import zlib
from collections import defaultdict


# BASE QUESTION (optimal): Hash set of the smaller file's
# ids
def shared_objects(day1, day2):
    # rows are [timestamp, obj_id, client_id]. Remember,
    # per
    # object, which days it appeared on and its clients.
    days, clients = defaultdict(set), defaultdict(set)
    for number, rows in ((1, day1), (2, day2)):
        for _, obj, client in rows:
            days[obj].add(number)
            clients[obj].add(client)
    return sorted(o for o in days
                  if len(days[o]) == 2
                  and len(clients[o]) >= 2)


def bucket_of(obj, buckets):
    # a stable hash (Python's own hash changes between
    # runs)
    return zlib.crc32(str(obj).encode()) % buckets


# FOLLOW-UP 1: Both files are too big for memory.
def shared_objects_partitioned(day1, day2, buckets=4):
    # memory limit: write each row to a bucket "file"
    # chosen by
    # the hash of its object, then solve one bucket at a
    # time.
    # All rows of an object land in the same bucket.
    parts1 = [[] for _ in range(buckets)]
    parts2 = [[] for _ in range(buckets)]
    for rows, parts in ((day1, parts1), (day2, parts2)):
        for row in rows:
            parts[bucket_of(row[1], buckets)].append(row)
    out = []
    for b in range(buckets):
        out += shared_objects(parts1[b], parts2[b])
    return sorted(out)


# OTHER WAY: external sort of both days
def shared_objects_sorted(day1, day2):
    # the other way: external sort both days by object,
    # then a
    # merge that holds only one object's clients at a time
    a = sorted(day1, key=lambda r: r[1])
    b = sorted(day2, key=lambda r: r[1])
    i = j = 0
    out = []
    while i < len(a) and j < len(b):
        if a[i][1] < b[j][1]:
            i += 1
        elif a[i][1] > b[j][1]:
            j += 1
        else:
            obj, clients = a[i][1], set()
            while i < len(a) and a[i][1] == obj:
                clients.add(a[i][2])
                i += 1
            while j < len(b) and b[j][1] == obj:
                clients.add(b[j][2])
                j += 1
            if len(clients) >= 2:
                out.append(obj)
    return out


# FOLLOW-UP 3: A tiny memory budget and an approximate
# answer is fine.
class Bloom:
```

```
    """Tiny memory, approximate: may say 'yes' for a few
    objects that were never added."""

    def __init__(self, bits=1 << 16, hashes=3):
        self.bits, self.hashes = bytearray(bits), hashes

    def spots(self, key):
        for seed in range(self.hashes):
            text = f"{seed}:{key}".encode()
            yield zlib.crc32(text) % len(self.bits)

    def add(self, key):
        for s in self.spots(key):
            self.bits[s] = 1

    def maybe(self, key):
```

```
        return all(self.bits[s] for s in self.spots(key))


if __name__ == "__main__":
    d1 = [["t1", "o1", "c1"], ["t2", "o2", "c1"]]
    d2 = [["t3", "o1", "c2"], ["t4", "o2", "c1"]]
    assert shared_objects(d1, d2) == ["o1"]
    assert shared_objects([], [["t", "o", "c"]]) == []
    assert shared_objects_partitioned(d1, d2, 3) == ["o1"]
    assert shared_objects_sorted(d1, d2) == ["o1"]
    many1 = [[i, f"o{i % 7}", f"c{i % 3}"]
             for i in range(40)]
    many2 = [[i, f"o{i % 5}", f"c{i % 2}"]
             for i in range(40)]
    want = shared_objects(many1, many2)
    parts = shared_objects_partitioned(many1, many2, 5)
    assert parts == want
    assert shared_objects_sorted(many1, many2) == want
    bloom = Bloom()
    for row in d1:
        bloom.add(row[1])
    assert bloom.maybe("o1") and not bloom.maybe("o999")
```

ALSO REPORTED · 1 more

Two-Day Log Intersection under Memory Limit | 1Point3Acres | onsite-coding | asked 2025-11-27 | Single report

https://www.1point3acres.com/interview/problems/company/google/two-logs-intersection-memory-limit

In-memory solution: build a hashmap obj_id -> set(client_id) while scanning each file; intersect keys across the two hashmaps at the end.
Memory-limited solution: external sort each file by obj_id, then run a merge / two-pointer scan over both sorted files. For each matching obj_id group, count distinct client_id on the fly (HyperLogLog if duplicates are large).
The interviewer explicitly preferred sort + two-pointer over a streaming hashmap — be prepared to defend the choice (sort is O(n log n) on disk vs O(n) RAM-bound for the hashmap).
For distributed scale, hash-partition by obj_id and run the same algorithm per partition.

ALSO REPORTED · 1 more

Preparation: Practice external-sort / merge-step problems (classic in-memory merge / k-way-merge / partition problems — and discuss disk-based variants verbally).
Drill the streaming hashmap vs external sort trade-off conversation.
Have ready: HyperLogLog (or Count-Min Sketch) one-liner for approximate distinct-count under tight memory.

MEDIUM | PracHub | Technical Screen | 101 of 165

Minimize calls to find all bad test pairs

POSTED 2025-11-05 | 339 DAYS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 190/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: No direct match (adaptive group testing)

Posted on PracHub: 2025-11-05 (updated 2026-06-18)

Original: https://prachub.com/coding-questions/minimize-calls-to-find-all-bad-test-pairs

QUESTION

You have (n) atomic tests (t_1, t_2, \dots, t_n). You are given access to a black-box function:

```
bool runTest(set<Test> S)
```

which behaves as follows:

- **`runTest(S) == True`** if the subset (S) contains **no** incompatible (bad) pair of tests.
- **`runTest(S) == False`** if the subset (S) contains **at least one** incompatible (bad) pair of tests. There is some unknown set of unordered **bad pairs** ((t_i, t_j)), where (i\ne j). You do **not** know in advance which pairs are bad or how many bad pairs there are. Your goal is to discover **all** bad pairs while making as few calls to **`runTest`** as possible. You may adaptively choose each subset (S) based on the results of previous calls.

Tasks

1. Design an algorithm that, using only calls to **`runTest`**, finds **all** bad pairs ((t_i, t_j)).
2. Analyze the number of calls to **`runTest`** your algorithm requires, as a function of:

- (n): the total number of tests, and - (k): the total number of bad pairs.

3. Argue why your algorithm is correct (i.e., why it will eventually find every bad pair and not report any good pair as bad). You do not need to provide full production code, but describe the algorithm clearly enough that it could be implemented.

QUESTION

You have n atomic tests numbered 0 to n - 1. Some unknown unordered pairs of tests are incompatible, called bad pairs. A black-box oracle runTest(S) returns True if the subset S contains no bad pair, and False if S contains at least one bad pair. In this non-interactive version, you are given bad_pairs only so your code can simulate the oracle. Implement the following deterministic oracle-discovery strategy and return both the bad pairs it discovers and the number of oracle calls it makes. Strategy:

1. Process vertices from right to left: v = n - 1, n - 2, ..., 0.
2. Maintain all bad pairs already discovered among vertices greater than the current v.
3. For the suffix vertices v + 1 through n - 1, greedily partition them into color classes such that no discovered bad pair appears inside one color class. Since all suffix-suffix bad pairs have already been discovered, every color class is truly compatible internally.
4. For each color class C, find all bad partners of v inside C using recursive group testing:

- Call runTest({v} union C).
- If the oracle returns True, v has no bad pair with any test in C.
- If C has size 1 and the oracle returns False, that single pair is bad.
- Otherwise split C into two halves and recurse on both halves. Return all discovered bad pairs sorted lexicographically, where each pair is represented as [i, j] with i < j, along with the exact number of runTest calls made by this strategy.

Constraints
0 <= n <= 5000 <= len(bad_pairs) <= n * (n - 1) / 2Each bad pair contains two distinct test indices in the range [0, n - 1]bad_pairs may be given in any endpoint order

EXAMPLES

```
Input: (0, [])
Expected Output: ([], 0)
```

Explanation: There are no tests and therefore no oracle calls are needed.

```
Input: (4, [])
Expected Output: ([], 3)
```

Explanation: For v = 2, 1, and 0, the algorithm queries the compatible suffix once and finds no bad pairs. v = 3 has an empty suffix.

Hints

If a candidate set C is internally compatible, then runTest({v} union C) tells you whether v conflicts with at least one element of C.Process tests from right to left so that when handling v, all bad pairs inside the suffix v + 1 ... n - 1 are already known and can be used to build compatible groups.

APPROACH

Binary search to find a minimal failing prefix (its last element is in a bad pair), then binary search among earlier tests for its partner; remove and repeat. About O(p log n) calls for p pairs.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what runTest returns (true if the set contains no incompatible pair), whether a test can be in more than one bad pair, and whether you may call it on any subset.

BRUTE FORCE TO SAY OUT LOUD

Call runTest on every pair of tests. O(n^2) calls.

OPTIMAL IDEA

Find a minimal failing prefix by binary search: add tests one at a time conceptually and binary search for the smallest prefix that fails; the last element of that prefix is part of a bad pair. Then binary search over the earlier tests to find its partner. Record the pair, remove one of the two as needed, and repeat. About O(p log n) calls for p bad pairs.

DRY-RUN THESE CASES

No bad pairs (one call). One bad pair. A test that conflicts with many others. Two disjoint bad pairs.

LIKELY FOLLOW-UPS

Batch calls, noisy tests, or a limit on subset size.

PITFALLS

Removing both members of a pair and missing other pairs that involve them. Binary searching without the monotone property of prefixes.

HOW TO THINK ABOUT IT

Each call is a yes/no question about a whole set, so binary search is possible: a failing set can be narrowed by halving. Keep the tests you have processed in groups that each pass runTest (independent sets). A new test only needs to be checked against each group, and if a group plus the new test fails, binary search finds its partners in that group in about log(size) calls each.

Basis: Written; group testing / finding all edges of a hidden graph with independent-set queries. runTest(S) is True when S contains no incompatible (bad) pair.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
bad = []
for a, b in combinations(tests, 2):
    if not runTest({a, b}):
        bad.append((a, b))
```

TIME	SPACE
n(n - 1) / 2 calls	O(1)

WHY IT IS SLOW

BRUTE FORCE

n(n - 1) / 2 calls even when nothing is bad. Keeping groups of mutually compatible tests and binary searching only when a group fails needs about n + p log n calls for p bad pairs.

OPTIMAL SOLUTION · Independent groups plus binary search for partners

TIME	SPACE
O(n * g + p log n) calls (g = number of groups, p = number of bad pairs)	**O(n)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How many calls does it need, and can you prove a lower bound?

With p bad pairs among n tests about p log n calls are needed in the worst case (each pair carries log n bits of information about where it is), and the group method uses O(n * g + p log n). With no bad pairs it uses n - 1 calls, one per test after the first.

FOLLOW-UP 2 Only one bad pair exists.

Binary search for the smallest failing prefix (its last element is in the pair), then binary search among the earlier elements for the partner: about 2 log n calls.

FOLLOW-UP 3 runTest is expensive but can run in parallel.

Test all groups for the new element in the same round, or process several elements at once with their own groups, trading a few extra calls for fewer sequential rounds.

FOLLOW-UP 4 Only one bad pair exists.

Binary search the shortest failing prefix (its last element is in the pair), then binary search the earlier tests for the partner: about 2 log2(n) calls instead of n(n - 1) / 2 (verified by counting calls).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import itertools


# BRUTE FORCE: ask about every pair
def bad_pairs_brute(tests, run_test):
    # every pair costs a call: n * (n - 1) / 2 calls
    pairs = itertools.combinations(tests, 2)
    return {(a, b) for a, b in pairs
            if not run_test({a, b})}


def shortest_failing_prefix(items, extra, run_test):
    # binary search: the smallest prefix of `items` that
    # fails
    # together with `extra`; its last item is a partner
    lo, hi = 1, len(items)
    while lo < hi:
        mid = (lo + hi) // 2
        if run_test(set(items[:mid]) | extra):
            lo = mid + 1
        else:
            hi = mid
    return items[lo - 1]


# FOLLOW-UP 2, 4: Only one bad pair exists.
def one_bad_pair(tests, run_test):
    # exactly one bad pair: about 2 * log2(n) calls
    if run_test(set(tests)):
        return None
    # the shortest failing prefix ends with one of the
    # pair
    b = shortest_failing_prefix(tests, set(), run_test)
    earlier = tests[:tests.index(b)]
    # then search the earlier tests for the partner
    a = shortest_failing_prefix(earlier, {b}, run_test)
    return (a, b)


def partners(group, t, run_test):
    # every member of the group that is bad with t
    rest, found = list(group), []
    while rest and not run_test(set(rest) | {t}):
        x = shortest_failing_prefix(rest, {t}, run_test)
        found.append(x)
        rest.remove(x)
    return found


# BASE QUESTION (optimal): Independent groups plus binary
# search for partners
def find_bad_pairs(tests, run_test):
    # keep groups of tests that pass together; a new test
    # is
    # checked against each group and joins one with no
    # partner
    groups, pairs = [], set()
    for t in tests:
        placed = False
        for group in groups:
            found = partners(group, t, run_test)
            for x in found:
                pairs.add((min(x, t), max(x, t)))
            if not found and not placed:
                group.append(t)
                placed = True
        if not placed:
            groups.append([t])
    return pairs


if __name__ == "__main__":
    def make_oracle(bad):
        calls = [0]

        def run_test(subset):
            calls[0] += 1
            ordered = sorted(subset)
            pairs = itertools.combinations(ordered, 2)
            return not any(p in bad for p in pairs)
        return run_test, calls

    bad = {(3, 17), (5, 29)}
    run, calls = make_oracle(bad)
    assert find_bad_pairs(list(range(30)), run) == bad
```

```
    assert calls[0] < 435 // 2
    run, calls = make_oracle(set())
    assert find_bad_pairs(list(range(30)), run) == set()
    assert calls[0] <= 30
    run, calls = make_oracle({(10, 40)})
```

```
    assert one_bad_pair(list(range(64)), run) == (10, 40)
    # about 2 * log2(64) = 12 calls, far below 2016 pairs
    assert calls[0] <= 16
    run, _ = make_oracle({(1, 2)})
    assert bad_pairs_brute([1, 2, 3, 4], run) == {(1, 2)}
```

FUNCTION AND TEST CASES

Signature

```
def solution(n: int, bad_pairs: list[list[int]]) -> tuple[
list[list[int]], int]:
```

Sample call

```
solution(0, [])
```

Test cases

Input	Expected
`(0, [])`	`([], 0)`
`(4, [])`	`([], 3)`

ALSO REPORTED · 1 more

Find All Bad Pairs Using runTest Oracle | 1Point3Acres | onsite-coding | asked 2025-11-27 | Single report

https://www.1point3acres.com/interview/problems/company/google/find-bad-pairs-with-oracle

Standard "group testing" / Dorfman testing problem. Walk through the analogy with COVID pooled tests for intuition.
Algorithm sketch:
Test the full set. If true, no bad pairs.
Otherwise, binary-search to find one bad pair by partitioning the set and testing halves.
Remove the items that participate in the located bad pair; repeat.
Tighter bound: with up to K bad pairs, total queries are O(K log N) using adaptive group testing.
A naive O(N²) pairwise scheme works but the interviewer expects you to beat it with adaptive splitting.
Verbalize correctness: each binary-search step rules out half the candidates; you can always reduce the search space until exactly one bad pair is isolated.

Preparation: Read the Wikipedia article on group testing and Dorfman's two-stage scheme.
Drill recursive binary partitioning on a candidate set with positive/negative oracle feedback.
Have a back-of-envelope analysis ready: "Total calls O(K log N) for K bad pairs and N items."

MEDIUM | IN APP LC 253 | PracHub | Technical Screen | 102 of 165

★ TOP 75: rank 58 in the Medium and Hard priority list

★ Compute servers needed for daily recurring jobs

POSTED 2025-11-05 | 339 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 58 | 30 DAYS 0 | PRIORITY 40/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #253 Meeting Rooms II

LeetCode match: LC 253 Meeting Rooms II

Posted on PracHub: 2025-11-05 (updated 2026-06-25)

Original: https://prachub.com/coding-questions/compute-servers-needed-for-daily-recurring-jobs

QUESTION

You operate a cluster of identical servers that run recurring **daily** jobs. For a single day, you are given a list of job execution intervals. Each interval has:

- **`job_id`** (string or integer),
- **`start_time`** (timestamp within that day),
- **`end_time`** (timestamp within that day), with **`start_time < end_time`**. Interpret each interval as a half-open time range **`[start_time, end_time)`** during which that job must be running on some server **on that day**. Rules and constraints:
- Each physical server can execute at most **one job at a time**.
- However, if multiple intervals in the input correspond to the **same `job_id`**, they may overlap in time **on the same server** (they are considered parts or retries of the same job and do not consume extra capacity).
- If a job's true execution would extend past midnight into the next day, it is conceptually **truncated at the end of the current day** for scheduling purposes; for each day you only see the portion that falls within that day's 24-hour window.

Tasks

1. Given all job intervals for a single day (potentially with repeated **`job_id`**s and overlapping intervals), compute the **minimum number of servers** required to schedule all the jobs under the above rules.
2. Describe the time and space complexity of your algorithm in terms of the number of intervals (m).

Follow-up

Some rare jobs are extremely long-running and conceptually span **multiple days** without restart. For such a multi-day job, you decide to reserve a **dedicated server** that is not shared with any other jobs, but which may still handle different intervals of that same **`job_id`**. Explain how you would extend or adapt your solution to:

QUESTION

- Detect which jobs require a dedicated server based on their multi-day duration or configuration.
- Account for these dedicated servers when computing the total number of servers needed for the system.

Part 1: Minimum Servers for One Day with Overlapping Same-Job IntervalsYou are given all job execution intervals for a single day. Each interval is half-open, meaning [start_time, end_time), and represents a time range during which a job must be running. A server can run at most one job at a time. However, if multiple intervals have the same job_id, they are considered parts or retries of the same job, so overlapping intervals with the same job_id consume only one server total during the overlap. Return the minimum number of servers required to run all intervals for the day.
Constraints
0 <= len(intervals) <= 2000000 <= job_id <= 10^90 <= start_time < end_time <= 1440Intervals are half-open: an interval ending at time t does not overlap an interval starting at time t.Multiple intervals may have the same job_id.

EXAMPLES

```
Input: ([],)
Expected Output: 0
```

Explanation: There are no jobs, so no servers are needed.

```
Input: ([[5, 100, 200], [5, 150, 250], [5, 240,
    300]],)
Expected Output: 1
```

Explanation: All intervals belong to the same job_id. Even though they overlap, they can share one server.

Hints
At any moment, one server is needed for each distinct active job_id, not for each active interval.Try merging all intervals belonging to the same job_id first, then run a sweep-line algorithm over the merged intervals.
Part 2: Total Servers with Dedicated Multi-Day JobsYou are given true job execution intervals that may span multiple days. Some jobs require dedicated servers. A job is dedicated if its job_id is listed in configured_dedicated, or if any one of its true intervals has duration at least min_dedicated_duration minutes. A dedicated job uses one reserved server for that job_id and does not share that server with other jobs, though multiple intervals of the same dedicated job_id may use the same dedicated server. For a given target_day, compute the total number of

APPROACH

Max concurrent jobs = servers needed; sweep line over start/end events, or min-heap of end times. Handle intervals wrapping midnight by splitting.

HOW TO THINK ABOUT IT

The number of servers is the largest number of jobs running at the same time. First remove the twist: overlapping intervals of the same job are really one longer interval, so merge the intervals of each job_id. Then it is the plain maximum overlap: sort start and end events and keep a running count.

Basis: LeetCode 253 (Meeting Rooms II) with a twist from the statement: intervals of the same job_id may overlap on one server and count once. Intervals are half-open [start, end) within one day.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def servers_needed(intervals):
    best = 0
    for t in range(DAY):
        jobs = set()
        for job_id, s, e in intervals:
            if s <= t < e:
                jobs.add(job_id)
        best = max(best, len(jobs))
    return best
```

TIME	SPACE
O(T * m)	O(m)

WHY IT IS SLOW

Depends on the length of the day, O(T * m). Merge each job's own intervals first, then sort start and end events and keep a running count, O(m log m).

OPTIMAL SOLUTION · Merge each job's intervals, then sweep start and end events

TIME	SPACE
O(m log m)	O(m)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Some rare jobs run for several days without restart and get a dedicated server.

Remove those jobs from the daily intervals and add one server per such job: servers = (number of dedicated jobs) + (maximum overlap of the remaining jobs).

FOLLOW-UP 2 Jobs that cross midnight.

Truncate at the end of the day for each day's schedule (as the statement says). For a recurring daily job that wraps, split it into two pieces (the end of the day and the start of the day); the sweep then handles both on the same circular day.

FOLLOW-UP 3 Return which server each job runs on.

Sort merged intervals by start and keep a min-heap of (end time, server id): reuse the server that frees up first if it is free, otherwise open a new one. The number of servers opened equals the maximum overlap.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import defaultdict


def merge_by_job(intervals):
    # intervals of the SAME job may overlap on one server,
    # so
    # merge them first: (job, start, end) -> disjoint
    # blocks
    by_job = defaultdict(list)
    for job, start, end in intervals:
        by_job[job].append((start, end))
    blocks = []
    for job, spans in by_job.items():
        cur = None
        for s, e in sorted(spans):
            if cur and s <= cur[1]:
                cur[1] = max(cur[1], e)
            else:
                if cur:
                    blocks.append((cur[0], cur[1], job))
                cur = [s, e]
        blocks.append((cur[0], cur[1], job))
    return blocks


# BASE QUESTION (optimal): Merge each job's intervals,
# then sweep start and end events
# FOLLOW-UP 1: Some rare jobs run for several days without
# restart and get a ...
def servers_needed(intervals, dedicated=()):
    # FOLLOW-UP 1: rare multi-day jobs get their own
    # server
    # dedicated jobs (they span several days) get their
    # own
    # server; the rest share servers: the answer is the
    # largest number of blocks running at the same moment
    dedicated = set(dedicated)
    shared = [i for i in intervals
              if i[0] not in dedicated]
    events = []
    for start, end, _ in merge_by_job(shared):
        events.append((start, 1))
        # [start, end): at equal times an end comes first
        events.append((end, -1))
```

```
    run = best = 0
    for _, delta in sorted(events):
        run += delta
        best = max(best, run)
    used = {i[0] for i in intervals if i[0] in dedicated}
    return best + len(used)


# FOLLOW-UP 3: Return which server each job runs on.
def assign_servers(intervals):
    # which server runs each block of each job?
    heap, plan, opened = [], [], 0
    blocks = sorted(merge_by_job(intervals))
    for start, end, job in blocks:
        if heap and heap[0][0] <= start:
            _, server = heapq.heappop(heap)
        else:
            server, opened = opened, opened + 1
        plan.append((job, server))
        heapq.heappush(heap, (end, server))
    return plan, opened


# FOLLOW-UP 2: Jobs that cross midnight.
def split_over_midnight(start, end, day=24 * 60):
    # a daily job that wraps past midnight: two pieces
    if start < end:
        return [(start, end)]
    return [(start, day), (0, end)]


if __name__ == "__main__":
    jobs = [("a", 0, 10), ("a", 5, 12), ("b", 3, 8),
            ("c", 10, 15)]
    # job a is one block [0, 12); b overlaps it; c starts
    # at 10
    assert servers_needed(jobs) == 2
    # touching half-open intervals share a server
    assert servers_needed([("a", 0, 5), ("b", 5, 9)]) == 1
    assert servers_needed([]) == 0
    # job b runs for days: it gets a dedicated server
    assert servers_needed(jobs, dedicated=["b"]) == 3
    assert servers_needed(jobs, dedicated=["a", "b"]) == 3
    plan, count = assign_servers(jobs)
    assert count == 2 and len(plan) == 3
```

```
    assert split_over_midnight(1380, 60) == [(1380, 1440),
                                             (0, 60)]
```

FUNCTION AND TEST CASES

Signature

```
def solution(intervals: list[list[int]]) -> int:
```

Sample call

```
solution([])
```

Test cases

Input	Expected
`([],)`	`0`
`([[5, 100, 200], [5, 150, 250], [5, 240, 300]],)`	`1`

ALSO REPORTED · 1 more

Compute minimum servers for cyclic tasks | PracHub | Technical Screen

https://prachub.com/coding-questions/compute-minimum-servers-for-cyclic-tasks

MEDIUM | PracHub | Technical Screen | 103 of 165

Choose optimal guesses for green-only Wordle

POSTED 2025-10-14 | 361 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 42.2 | 30 DAYS 0 | PRIORITY 85/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #843 Guess the Word

LeetCode match: No direct match; related LC 843 Guess the Word (inferred from overview)

Posted on PracHub: 2025-10-14 (updated 2026-03-29)

Original: https://prachub.com/interview-questions/choose-optimal-guesses-for-green-only-wordle

QUESTION

Overview: This question evaluates probabilistic reasoning, expected-value optimization, information partitioning, and algorithmic efficiency in selecting guesses under partial (green-only) feedback; it belongs to the Coding & Algorithms domain, specifically search and probabilistic modeling, and emphasizes practical algorithm design and implementation rather than purely theoretical concepts. It is commonly asked to assess a candidate's ability to model uncertainty with weighted distributions, minimize the expected remaining search space, and manage time/space trade-offs for inputs up to several thousand words.

APPROACH

Filter candidates by green-position constraints, then pick the guess that maximizes expected information (partition sizes) over the remaining words.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what feedback exists (only green: letter in the right position), whether answers are equally likely or weighted, whether guesses must come from the candidate list, and the objective (minimize the expected size of the remaining set).

BRUTE FORCE TO SAY OUT LOUD

For each candidate guess and each possible answer compute the feedback and count the survivors. O(W^2 * L).

OPTIMAL IDEA

A guess g splits the candidates by its pattern against each answer, a bitmask of which positions are green. If groups have sizes s_1 ... s_k, the expected number of survivors is the sum of s_i^2 divided by W (weights replace sizes with weight sums). Pick the guess minimizing it. To speed up, store for each (position, letter) a bitset of candidate words so groups come from bit operations instead of pairwise comparisons.

INTERVIEW-DAY PLAN

DRY-RUN THESE CASES

Two candidates (any guess), words that differ in one position, a guess that is itself the answer (pattern all green), a single candidate.

LIKELY FOLLOW-UPS

Full Wordle feedback with yellow, multiple rounds, or an adaptive strategy.

PITFALLS

Minimizing the number of groups instead of the expected survivors. Recomputing the filter from scratch each round.

HOW TO THINK ABOUT IT

A guess splits the candidates into groups by which positions turned green. If the groups have sizes s_1 ... s_k out of W candidates, the expected size of what remains is the sum of s_i squared divided by W (a candidate falls in a group of size s with probability s / W, and then s remain). Pick the guess with the smallest value. To make it fast, store for each (position, letter) the set of words with that letter there as a bitset, so the groups come from a few AND operations.

Basis: Written. Assumed rules (confirm them): words of equal length, the answer is uniformly random among the candidates, a guess must be a candidate, feedback marks only the positions where the guess letter equals the answer letter (green). Goal: minimise the expected number of candidates left.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(guesses, answers):
    best, best_score = None, INF
    for g in guesses:
        groups = Counter()
        for a in answers:
            groups[green_pattern(g, a)] += 1
        sizes = groups.values()
        score = sum(c * c for c in sizes)
        score /= len(answers)
        if score < best_score:
            best, best_score = g, score
    return best
```

TIME	SPACE
O(W^2 * L)	O(W)

WHY IT IS SLOW

Compares every pair of words, O(W^2 * L). Bitsets per (position, letter) split the candidates into pattern groups with a few AND operations.

OPTIMAL SOLUTION · Bitsets per (position, letter), splitting groups with AND

TIME	SPACE
O(W * L * groups) with bit-parallel work per group	**O(W * L)**

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Play a whole game, using the feedback after each guess.

Keep the candidates that would have produced exactly the observed green pattern (filter_candidates), then choose the best guess among the remaining ones. Each round at least removes the guess itself, so the game ends.

FOLLOW-UP 2 Answers are not equally likely (weights).

Replace group sizes by group weights: score = sum(weight(group)^2) / total weight. The grouping step is unchanged; use sums of weights instead of popcounts.

FOLLOW-UP 3 Real Wordle also gives yellow feedback.

The pattern becomes three-valued per position (green, yellow, grey) with the usual duplicate-letter rules, so the pattern space is 3^L; bitsets still work if you precompute patterns, but the computation is O(W^2) pattern evaluations for a full table.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict
from fractions import Fraction


def green(guess, answer):
    # green-only feedback: which positions match exactly
    return tuple(g == a for g, a in zip(guess, answer))


def partition(guess, words):
    # group the possible answers by the feedback they
    # would give
    groups = defaultdict(list)
    for w in words:
        groups[green(guess, w)].append(w)
    return list(groups.values())


def score(guess, words, weight=None):
    # expected number of answers left after this guess:
    # sum(group^2) / total, with optional per-word weights
    weight = weight or (lambda w: 1)
    total = sum(weight(w) for w in words)
    spread = sum(sum(weight(w) for w in g) ** 2
                 for g in partition(guess, words))
    return Fraction(spread, total)


# BASE QUESTION (optimal): Bitsets per (position, letter),
# splitting groups with AND
def best_guess(words, weight=None):
    # the guess that leaves the fewest answers on average
    # (ties: alphabetical, so the result is deterministic)
    def rank(g):
        return (score(g, words, weight), g)
    return min(words, key=rank)


# FASTER: bitsets
def best_guess_bitsets(words):
    # faster: one bitmask per (position, letter); each
    # position
    # splits every group in two with two AND operations
    W = len(words)
    bits = [defaultdict(int)
            for _ in range(len(words[0]))]
    for i, w in enumerate(words):
        for pos, ch in enumerate(w):
            bits[pos][ch] |= 1 << i
    best = None
    for g in words:
        groups = [(1 << W) - 1]
        for pos, ch in enumerate(g):
            mask, nxt = bits[pos][ch], []
            for grp in groups:
                for part in (grp & mask, grp & ~mask):
                    if part:
                        nxt.append(part)
            groups = nxt
        sizes = [bin(g).count("1") for g in groups]
        spread = sum(s * s for s in sizes)
        cand = (Fraction(spread, W), g)
        if best is None or cand < best:
            best = cand
    return best[1]


# FOLLOW-UP 1: Play a whole game, using the feedback after
# each guess.
def filter_candidates(words, guess, pattern):
    # keep only answers that would give the observed
    # feedback
    return [w for w in words
            if green(guess, w) == pattern]


def play(words, secret):
    # a whole game: guess, read the feedback, narrow down
    candidates, guesses = list(words), []
    while True:
        guess = best_guess(candidates)
        guesses.append(guess)
        if guess == secret:
            return guesses
        pattern = green(guess, secret)
        candidates = filter_candidates(
            candidates, guess, pattern)


if __name__ == "__main__":
    words = ["crane", "crate", "grape", "grade", "trade",
             "slate", "plate"]
    assert best_guess(words) == best_guess_bitsets(words)
    # a guess can never leave more than all the words
    assert score("crane", words) <= len(words)
    for secret in words:
        path = play(words, secret)
        assert path[-1] == secret
        # each round removes at least the guess itself
```

```
    assert len(path) <= len(words)
# weights: a very likely word makes its guess more
# attractive
heavy = lambda w: 100 if w == "slate" else 1
slate = score("slate", words, heavy)
crane = score("crane", words, heavy)
assert slate < crane
assert partition("crane", ["crane"]) == [["crane"]]
```

FULL QUESTION TEXT FROM THE SITE

Problem

You are playing a simplified 5-letter word guessing game.

There is a hidden secret word of length 5 .
You have a dictionary of valid 5-letter words. Each word may also have an associated frequency/weight representing how likely it is to be the secret.
When you guess a 5-letter word, the game returns only “green” information (correct letter in the correct position). There is no information about letters that exist in the word but are in the wrong position (“yellow”), and no explicit info about letters that are absent.
Feedback definition

For a guess g and secret s, define the feedback as a 5-bit mask m where:

m[i] = 1 iff g[i] == s[i]
otherwise m[i] = 0

Example: g="crane", s="cared" -> mask is 1 0 0 0 0 (only position 0 matches).

Task

Given:

words : a list of N valid 5-letter words
weight[w] (optional): a positive number for each word (if omitted, assume uniform)
candidates : the current set of possible secret words consistent with feedback so far (initially all words)

Write an algorithm/function to choose the next guess that is optimal under the following objective:

Choose a guess word g (typically from words) that minimizes the expected size of the remaining candidate set after receiving the green-only mask, where the expectation is taken over the secret word drawn from candidates according to weight .

Formally, if C is the current candidate set and C_m(g) is the subset of candidates that would produce mask m for guess g, choose g that minimizes:

FULL QUESTION TEXT FROM THE SITE

E
[
|
C
m
a
s
k
(
g
)
|
]
=
sum
m
in
{
0
,
1
}
5
P
(

m
a
s
k
=
m
)
*
|
C
m
(
g
)
|
E[|C
mask
(g)|]=sum
min{0,1}
5
P(mask=m)*|C
m
(g)|

FULL QUESTION TEXT FROM THE SITE

where
P
(
m
a
s
k
=
m
)
P(mask=m) is induced by the weighted distribution over secrets in C.

Input/Output expectations
Input sizes: 1 <= N <= 5,000 (you may propose optimizations if needed), word length is always 5.
Output: the selected next guess word.
Follow-ups (optional)
How would you incorporate non-uniform word frequencies?
How would you scale if N is very large (e.g., 100k)?
How would you change the objective to minimize expected number of guesses instead of expected remaining candidates?

ALSO REPORTED · 1 more

Wordle-Style 5-Letter Minimum-Guess Strategy | 1Point3Acres | phone-screen, onsite-coding | asked 2025-12-15 | Single report

https://www.1point3acres.com/interview/problems/company/google/wordle-min-guess-strategy

Without the dictionary, query positions in order; per position, query letters in descending frequency (e, t, a, o, i, n, ...) and stop as soon as one returns true.
With the dictionary, maintain a candidate set; at each step pick the (position, letter) query whose true/false outcome splits the candidate set most evenly (entropy maximization).
Mention information theory: each query yields <= 1 bit, so the absolute lower bound on calls is ceil(log2(|candidates|)).
Don't waste minutes on a closed-form optimum — the interviewer mostly wants you to articulate the entropy heuristic and pick one reasonable scoring function.

Preparation: Drill information-theoretic puzzles (egg drop, twenty questions) to internalize the entropy-split heuristic.
Practice maintaining a candidate set under positive/negative oracle feedback (filter on each query result).
Be ready with a one-liner on Wordle's known optimal first guess (SOARE / CRANE) for intuition; do not hard-code it.

MEDIUM | PracHub | Technical Screen | 104 of 165

★ TOP 75: rank 65 in the Medium and Hard priority list

★ Compute shortest paths with blocked nodes

POSTED 2025-09-06 | 399 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 37.9 | 30 DAYS 33 | PRIORITY 59/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #743 Network Delay Time

LeetCode match: LC 743 Network Delay Time (Dijkstra with blocked nodes skipped)

Posted on PracHub: 2025-09-06 (updated 2026-06-27)

Original: https://prachub.com/coding-questions/compute-shortest-paths-with-blocked-nodes

QUESTION

Given a graph with nodes and edges and a designated source node s, compute the shortest distance from s to every other node. Some nodes are inaccessible (blocked) and cannot be traversed or reached; treat them as removed from the graph. Return a distance for each node where unreachable nodes (including blocked ones) are -1. Describe your algorithm, data structures, and time/space complexity, and note any differences for directed vs. undirected graphs.

Given n nodes labeled 0..n-1, edges, a source, and blocked nodes, return shortest unweighted distances from the source. Blocked and unreachable nodes must be -1. Set directed=True to treat edges as directed.
Constraints
Nodes are labeled 0 through n-1Edges are unweighted

EXAMPLES

```
Input: (5, [[0, 1], [1, 2], [0, 3], [3, 4]], 0, [3],
    False)
Expected Output: [0, 1, 2, -1, -1]
Input: (4, [[0, 1], [1, 2], [2, 3]], 0, [], True)
Expected Output: [0, 1, 2, 3]
```

Hints
Treat blocked nodes as removed before BFS.For directed graphs, only add the given edge direction.

APPROACH

Run Dijkstra (BFS if unweighted) from s, never relaxing into blocked nodes; blocked/unreachable nodes stay at infinity. O((V+E) log V).

HOW TO THINK ABOUT IT

Blocked nodes are simply not in the graph, so skip them when you queue neighbours and never start from one. After that it is plain BFS from the source: first discovery gives the shortest distance. State the edge cases: a blocked source makes everything unreachable, and directed edges must only be added in their given direction.

Basis: Unweighted shortest distances (BFS) with some nodes removed from the graph. Output: a distance per node, -1 for unreachable or blocked nodes; directed=True uses edges one way only.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n, edges, blocked, s):
    keep = []
    for u, v, w in edges:
        if u not in blocked and v not in blocked:
            keep.append((u, v, w))
    d = floyd_warshall(n, keep)  # all pairs
    return d[s]
```

TIME	SPACE
O(V^3)	O(V^2)

WHY IT IS SLOW

All-pairs distances cost O(V^3) and O(V^2) memory when one source is needed. A BFS from the source that never enters a blocked node is O(V + E).

OPTIMAL SOLUTION · BFS that never enters a blocked node

TIME	SPACE
O(V + E)	O(V + E)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The edges have weights.

BFS is no longer correct: use Dijkstra with a heap and skip blocked nodes the same way. O((V + E) log V). Directed and undirected differ only in whether you add the reverse edge.

FOLLOW-UP 2 Directed versus undirected.

For an undirected graph add each edge in both directions; for a directed one only as given. A node may be reachable in one case and not in the other, so state which you assume.

FOLLOW-UP 3 Nodes get blocked over time and you must keep distances up to date.

Decremental shortest paths is hard in general; for few updates rerun BFS, and for many offline queries process the changes in reverse order (unblocking only improves distances).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import defaultdict, deque

INF = float("inf")


# BASE QUESTION (optimal): BFS that never enters a blocked
# node
def blocked_distances(n, edges, source, blocked,
                      directed=False):
    # BFS that treats blocked nodes as removed;
    # unreachable
    # and blocked nodes get -1
    bad = set(blocked)
    if source in bad:
        return [-1] * n
    adj = defaultdict(list)
    for u, v in edges:
        adj[u].append(v)
        if not directed:
            adj[v].append(u)
    dist = [-1] * n
    dist[source] = 0
    queue = deque([source])
    while queue:
        u = queue.popleft()
        for v in adj[u]:
            if v not in bad and dist[v] == -1:
                dist[v] = dist[u] + 1
                queue.append(v)
    return dist


# FOLLOW-UP 1: The edges have weights.
def blocked_distances_weighted(n, edges, source, blocked,
                               directed=False):
    # edges (u, v, w): BFS is wrong now, use Dijkstra
    bad = set(blocked)
    if source in bad:
        return [-1] * n
    adj = defaultdict(list)
    for u, v, w in edges:
        adj[u].append((v, w))
        if not directed:
            adj[v].append((u, w))
    dist = [INF] * n
    dist[source] = 0
    heap = [(0, source)]
    while heap:
        d, u = heapq.heappop(heap)
        if d > dist[u]:
            continue
        for v, w in adj[u]:
            if v not in bad and d + w < dist[v]:
                dist[v] = d + w
                heapq.heappush(heap, (d + w, v))
    return [-1 if d == INF else d for d in dist]


if __name__ == "__main__":
    edges = [(0, 1), (1, 2), (0, 3), (3, 2), (2, 4)]
    free = blocked_distances(5, edges, 0, [])
    assert free == [0, 1, 2, 1, 3]
    # blocking 1 forces the route through 3
    assert blocked_distances(5, edges, 0, [1])[2] == 2
```

```
    # blocking 2 cuts node 4 off; blocked nodes are -1
    cut = blocked_distances(5, edges, 0, [2])
    assert cut == [0, 1, -1, 1, -1]
    start = blocked_distances(3, edges[:2], 0, [0])
    assert start == [-1, -1, -1]
    # directed edges only go one way
    path = [(0, 1), (1, 2)]
    one_way = blocked_distances(3, path, 2, [], True)
    assert one_way == [-1, -1, 0]
    weighted = [(0, 1, 5), (1, 2, 1), (0, 2, 10)]
    wd = blocked_distances_weighted
    assert wd(3, weighted, 0, []) == [0, 5, 6]
    assert wd(3, weighted, 0, [1])[2] == 10
```

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 105 of 165

Design server allocation for multi-type nodes

POSTED 2025-09-06 | 399 DAYS AGO | OLDER

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 216/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

LeetCode match: No direct match; related LC 1912 Design Movie Rental System

Posted on PracHub: 2025-09-06 (updated 2026-08-05)

Original: https://prachub.com/interview-questions/design-server-allocation-for-multi-type-nodes

QUESTION

Design a service to manage a large pool (about 100, 000) of server nodes. Each node can satisfy multiple instance types; clients call getServer(reqNumOfServer, instanceTypes[]) to request servers that collectively meet the requested types, and returnServer(ids[]) to release them. Propose data structures and indexes for fast matching, availability tracking, fragmentation minimization, and scaling. Address concurrency, starvation, and failure handling.

APPROACH

Map instance type -> ordered set of free nodes; allocating a node removes it from every type's set (lazy deletion with an allocated flag); release re-adds it. Pick by the rule in the prompt.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what getServer returns when it cannot be satisfied, whether it must be atomic, what collectively meet the types means (every requested type is covered by at least one chosen server), and the scale (about 100,000 nodes).

BRUTE FORCE TO SAY OUT LOUD

Scan all nodes on every request and test their types. O(N) per call.

OPTIMAL IDEA

Keep, for each instance type, a heap or sorted set of free node ids ordered by how few types the node supports (least flexible first). To serve, pick for each requested type the least flexible free node not already chosen, then fill the remaining count with least flexible nodes that match any requested type. Mark nodes allocated (lazy deletion in the other types' structures). Roll back if the request cannot be completed. Release re-adds the node to each of its types.

DRY-RUN THESE CASES

Request larger than the free pool, a node shared by two requested types, return then re-request, releasing an id that is not allocated.

LIKELY FOLLOW-UPS

Concurrency (per-type locks or a single allocator thread), starvation (FIFO queue), fragmentation, failure handling (leases and timeouts).

PITFALLS

Allocating a node and forgetting to remove it from the other type indexes. Greedy choices that are not optimal set cover; say so.

HOW TO THINK ABOUT IT

A request mentions a few types, so index the free servers by type and avoid scanning all 100,000. To keep versatile servers available for harder requests, always prefer the server that supports the fewest types. Allocation touches every type index of a server, so use lazy deletion: mark it allocated and let the stale heap entries be skipped when they surface.

Basis: Written design. Assumed contract (confirm it): getServer(count, types) returns `count` free server ids such that every requested type is supported by at least one returned server, or None and no change; releaseServer(ids) frees them. To limit fragmentation the least flexible servers (supporting the fewest types) are used first.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def get_server(count, types):
    chosen = []
    for t in types:
        pool = [s for s in free if t in s.types
                and s not in chosen]
        chosen.append(min(pool, key=flexibility))
    rest = [s for s in free if s not in chosen
            and s.types & set(types)]
    chosen += rest[:count - len(chosen)]
    if len(chosen) < count:
        return None  # not enough
    return chosen
```

TIME	SPACE
O(N * T) per request (N servers)	O(N)

BRUTE FORCE

WHY IT IS SLOW

Every request scans all N servers, O(N * types). Per-type heaps ordered by flexibility with lazy deletion make a request O((count + types) log N).

OPTIMAL SOLUTION · Per-type heaps ordered by flexibility, with lazy deletion

TIME	SPACE
O((count + types) log N) amortized per request	O(total type memberships)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Many clients call at the same time.

Make allocation atomic: one lock around the allocate step, or shard the pool by type or by id range and route requests to shards. The roll-back-on-failure design means a failed request leaves no trace.

FOLLOW-UP 2 Clients keep asking for rare types and starve.

Use a FIFO queue per request class and hold back versatile servers for waiting rare-type requests, or age requests so an old one outranks new ones. Fragmentation control (least flexible first) already reduces the pressure.

FOLLOW-UP 3 Servers fail while allocated.

Track a lease or heartbeat per allocation; when a server stops responding mark it unavailable, remove it from the heaps (lazy deletion handles stale entries), and tell the client so it can request a replacement.

FOLLOW-UP 4 A client dies without releasing its servers.

Give every allocation a lease (expiry time). A periodic sweep returns servers whose lease has expired to the free pool (the lazy-deletion indexes make a release cheap), and clients renew the lease while they are alive.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import defaultdict


# BASE QUESTION (optimal): Per-type heaps ordered by
# flexibility, with lazy deletion
# FOLLOW-UP 4: A client dies without releasing its
# servers.
class ServerPool:
    """Servers with several instance types. Each type has
    a heap of (number of types, id): the LEAST flexible
    server goes first, which keeps versatile ones free."""

    def __init__(self, servers):
        # servers: id -> set of instance types
        self.types = {s: frozenset(t)
                      for s, t in servers.items()}
        self.allocated = set()
        self.heaps = defaultdict(list)
        # FOLLOW-UP 4: a dead client's lease expires
        # lease expiry time of every allocated server
        self.lease = {}
        for s, ts in self.types.items():
            for t in ts:
                heap = self.heaps[t]
                heapq.heappush(heap, (len(ts), s))

    def best_for(self, t, skip):
        # the best free server of type t that is not in
        # `skip`;
        # allocated entries are dropped lazily
        heap, held = self.heaps[t], []
        while heap:
            flex, s = heap[0]
            if s in self.allocated:
                heapq.heappop(heap)
            elif s in skip:
                held.append(heapq.heappop(heap))
            else:
                break
        best = heap[0] if heap else None
        # put back the entries we only looked past
        for item in held:
            heapq.heappush(heap, item)
        return best

    def get_server(self, count, types):
        # pick servers first, commit only if the whole
        # request works
        chosen = []
        for t in types:
            # a server already chosen may cover this type
            if any(t in self.types[c] for c in chosen):
                continue
            top = self.best_for(t, set(chosen))
            if top is None:
                return None
            chosen.append(top[1])
        # fill up to `count` with the least flexible free
        # servers
        while len(chosen) < count:
            skip = set(chosen)
            found = [self.best_for(t, skip)
                     for t in types]
            options = [o for o in found if o]
            if not options:
                return None
            chosen.append(min(options)[1])
        # more servers than allowed were needed to cover
        # the types
        if len(chosen) > count:
            return None
        self.allocated |= set(chosen)
        return chosen

    def release(self, ids):
        for s in ids:
            if s in self.allocated:
                self.allocated.discard(s)
                self.lease.pop(s, None)
                flex = len(self.types[s])
                for t in self.types[s]:
```

```
                    heap = self.heaps[t]
                    heapq.heappush(heap, (flex, s))

    def rent(self, count, types, now, ttl):
        # a client that dies must not hold servers forever
        got = self.get_server(count, types)
        for s in got or []:
            self.lease[s] = now + ttl
        return got

    def expire(self, now):
        # return servers whose lease ran out to the free
        # pool
        late = [s for s in self.lease
                if self.lease[s] <= now]
        self.release(late)
        return late


if __name__ == "__main__":
    pool = ServerPool({1: {"gpu"}, 2: {"gpu", "big"},
                       3: {"big"}, 4: {"cpu"}})
    # the least flexible server for each type is used
    # first
    assert pool.get_server(2, ["gpu", "big"]) == [1, 3]
    # the versatile server 2 is still there for a combined
    # need
    assert pool.get_server(1, ["gpu", "big"]) == [2]
    # nothing is left for a gpu request
    assert pool.get_server(1, ["gpu"]) is None
    # a request that cannot fit in `count` servers changes
    # nothing
    assert pool.get_server(1, ["cpu", "gpu"]) is None
    assert pool.get_server(1, ["cpu"]) == [4]
    pool.release([2])
    assert pool.get_server(1, ["gpu"]) == [2]
    # leases: a dead client's servers come back
    p2 = ServerPool({1: {"a"}})
    assert p2.rent(1, ["a"], now=0, ttl=10) == [1]
    assert p2.get_server(1, ["a"]) is None
    assert p2.expire(now=5) == []
    assert p2.expire(now=10) == [1]
    assert p2.get_server(1, ["a"]) == [1]
```

MEDIUM | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 106 of 165

Design an elevator control system

POSTED 2025-09-06 | 399 DAYS AGO | OLDER

STUDY: READ **NO LEETCODE FREQUENCY** **PRIORITY 217/224**

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

LeetCode match: No direct match (OOP / low-level design)

Posted on PracHub: 2025-09-06 (updated 2026-10-07)

Original: https://prachub.com/interview-questions/design-an-elevator-control-system-2

QUESTION

Design the software for a multi-elevator control system in a high-rise building. Specify classes, scheduling algorithms for car assignments, handling peak traffic, fairness, fault tolerance, and safety constraints. Consider real-time constraints and a simulation and testing strategy.

APPROACH

Model Elevator, Request and Controller classes; scheduling by nearest-car or SCAN/LOOK direction-based assignment; queue targets per elevator, handle peak traffic, fairness, fault tolerance and safety; discuss simulation and testing strategy.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask how many elevators and floors, whether to design only the control logic or also the hardware, request types (hall call with direction, destination inside), and what to optimize (wait time, fairness, energy).

BRUTE FORCE TO SAY OUT LOUD

A single queue: serve requests first come first served with the nearest idle car. Easy but wasteful.

OPTIMAL IDEA

Classes: Request, Elevator (floor, direction, state, a set of stops), Controller (assigns requests). Use SCAN/LOOK inside each car: keep moving in the current direction serving stops, then reverse. Assign a hall call to the car with the lowest cost, such as distance plus a penalty if it is moving away or is full. Add a step method that advances time so it can be simulated and tested.

DRY-RUN THESE CASES

One request while idle, a request in the opposite direction, two cars equally close, a car out of service with pending stops, the top and bottom floors.

LIKELY FOLLOW-UPS

Peak traffic modes, weight limits, fault tolerance (reassign stops on failure), and safety (doors, overload).

PITFALLS

Putting all logic in one class. Not saying how you will test it.

HOW TO THINK ABOUT IT

Separate three things: the data (Request), one car's behaviour (Elevator: floor, direction, stops, door/state) and the policy that decides which car takes a call (Controller). Say the scheduling rule out loud: a car keeps going in its direction serving stops, then reverses (SCAN/LOOK), which avoids the back-and-forth of first-come-first-served. Add a step() so the whole thing can be simulated and tested.

Basis: Written object-oriented design (the classic low-level design question). A SCAN (elevator) scheduling policy per car with a cost-based assignment of hall calls.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
requests = deque()  # arrival order
def run():
    while requests:
        req = requests.popleft()
        car = nearest_idle_car(req.floor)
        car.go_to(req.floor)
        car.go_to(req.destination)
```

TIME	SPACE
O(requests * cars)	O(requests)

WHY IT IS SLOW

Cars zig-zag across the building and requests wait behind far-away ones, so total travel and waiting are high. Serving stops in sweep order (SCAN) and assigning by cost cuts both.

OPTIMAL SOLUTION · Elevator (SCAN) per car and cost-based assignment of calls

TIME	SPACE
O(cars) per call, O(1) per car per step	O(stops)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Peak traffic (morning lobby rush, evening exodus).

Add modes: during the morning rush park idle cars in the lobby and let them go up with a full load; in the evening do the opposite. Zone cars (low floors, high floors) or use destination dispatch (passengers enter their floor first) to group riders by destination.

FOLLOW-UP 2 Fairness and starvation.

SCAN already guarantees every stop is reached within one sweep. For hall calls add an aging term to the cost so a long-waiting call wins over a closer new one.

FOLLOW-UP 3 Safety and fault tolerance.

Keep door and overload as explicit states; a car that fails is marked out of service and its stops are reassigned (the controller does this), and the controller should be restartable from persistent state of cars and pending calls.

FOLLOW-UP 4 Morning rush: idle cars should wait at the lobby.

When a car has no stops, give it a stop at the lobby (or a configured parking floor per car). Peak modes are just policies layered on the same step() and cost-based assignment; the elevator algorithm does not change.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
INF = float("inf")


class Request:
    def __init__(self, floor, direction):
        # direction: +1 up, -1 down
        self.floor, self.direction = floor, direction


# BASE QUESTION (optimal): Elevator (SCAN) per car and
# cost-based assignment of calls
class Elevator:
    def __init__(self, car_id, floor=0):
        self.id, self.floor = car_id, floor
        # 0 = idle, +1 = going up, -1 = going down
        self.direction = 0
        self.stops = set()
        self.in_service = True

    def cost(self, req):
        # how bad is it to give this car the request?
        if not self.in_service:
            return INF
        dist = abs(self.floor - req.floor)
        if self.direction == 0:
            return dist
        # on the way: the car is moving toward the floor
        # and
        # the call goes the same way
        gap = req.floor - self.floor
        ahead = gap * self.direction >= 0
        if ahead and req.direction == self.direction:
            return dist
        # otherwise it finishes its sweep first
        span = max(self.stops) - min(self.stops) + 1
        return dist + 2 * span + 10

    def step(self):
        # one tick: serve a stop here, then move one floor
        served = None
        if self.floor in self.stops:
            self.stops.discard(self.floor)
            served = self.floor
        if not self.stops:
            self.direction = 0
```

```
            return served
        up = [s for s in self.stops if s > self.floor]
        down = [s for s in self.stops if s < self.floor]
        # keep the direction while there are stops ahead
        # (SCAN)
        if (self.direction >= 0 and up) or (
                self.direction < 0 and not down):
            self.direction = 1
        else:
            self.direction = -1
        self.floor += self.direction
        return served


# BASE QUESTION (optimal): Elevator (SCAN) per car and
# cost-based assignment of calls
# FOLLOW-UP 1: Peak traffic (morning lobby rush, evening
# exodus).
class Controller:
    def __init__(self, cars, lobby=0):
```

```
        self.cars, self.lobby = cars, lobby

    def assign(self, req):
        # the cheapest in-service car takes the call
        car = min(self.cars, key=lambda c: c.cost(req))
        if car.cost(req) == INF:
            return None
        car.stops.add(req.floor)
        return car.id

    def tick(self):
        return {c.id: c.step() for c in self.cars}

    # FOLLOW-UP 3: a failed car hands its stops over
    def fail(self, car_id):
        # a broken car: take it out and hand its stops to
        # others
        car = next(c for c in self.cars if c.id == car_id)
        car.in_service = False
        orphans, car.stops = car.stops, set()
        for floor in orphans:
            self.assign(Request(floor, 0))

    # FOLLOW-UP 1, 4: morning rush: idle cars wait in the
    # lobby
```

```
    def park_idle(self):
        # morning rush: idle cars wait in the lobby
        for car in self.cars:
            if car.in_service and not car.stops:
                car.stops.add(self.lobby)


if __name__ == "__main__":
    a, b = Elevator("A", 0), Elevator("B", 10)
    ctl = Controller([a, b])
    # the closest idle car takes the call
    assert ctl.assign(Request(2, 1)) == "A"
    assert ctl.assign(Request(9, -1)) == "B"
    for _ in range(3):
        served = ctl.tick()
    assert a.floor == 2 and served["A"] in (None, 2)
    assert 2 not in a.stops
    # a failed car hands its stops to the other car
    b.stops = {8}
    ctl.fail("B")
    assert not b.in_service and 8 in a.stops
    assert ctl.assign(Request(1, 1)) == "A"
    # nobody in service: the request cannot be taken
    a.in_service = False
    assert ctl.assign(Request(1, 1)) is None
    # idle cars go back to the lobby
    c = Elevator("C", 5)
    Controller([c]).park_idle()
    assert c.stops == {0}
```

MEDIUM | PracHub | Technical Screen | 107 of 165

★ TOP 75: rank 46 in the Medium and Hard priority list

★ Solve tree, graph, sliding-window problems

POSTED 2025-08-04 | 432 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 51.9 | 30 DAYS 33 | PRIORITY 28/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #103 Binary Tree Zigzag Level Order Traversal, LeetCode #207 Course Schedule

LeetCode match: LC 103 Binary Tree Zigzag Level Order Traversal + LC 207 Course Schedule

Posted on PracHub: 2025-08-04 (updated 2026-05-26)

Original: https://prachub.com/coding-questions/solve-tree-graph-sliding-window-problems

QUESTION

Question

LeetCode 103. Binary Tree Zigzag Level Order Traversal – given a binary tree root, return its zigzag level-order traversal. LeetCode 207. Course Schedule – given course prerequisites, determine if all courses can be finished by detecting cycles with topological sort. LeetCode 340. Longest Substring with At Most K Distinct Characters – given string s and integer k, return the length of the longest substring containing at most k distinct characters. https://leetcode.com/problems/binary-tree-zigzag-level-order-traversal/description/ https://leetcode.com/problems/course-schedule/description/ https://leetcode.com/problems/longest-substring-with-at-most-k-distinct-characters/description/

Part 1: Binary Tree Zigzag Level Order TraversalYou are given a binary tree in level-order array form, where each element is either an integer or None for a missing child. Return the zigzag level-order traversal of the tree's node values. In a zigzag traversal, the first level is read from left to right, the second from right to left, the third from left to right, and so on.

Constraints

0 <= len(root) <= 2000Each non-None node value is an integer in the range [-10^4, 10^4]The input list represents a valid binary tree in level-order form

EXAMPLES

```
Input: ([3, 9, 20, None, None, 15, 7],)
Expected Output: [[3], [20, 9], [15, 7]]
```

Explanation: Level 1 is read left-to-right, level 2 right-to-left, and level 3 left-to-right.

```
Input: ([1],)
Expected Output: [[1]]
```

Explanation: A single-node tree has only one level.

QUESTION

Hints

A breadth-first search naturally processes the tree one level at a time.You can collect each level left-to-right, then reverse every other level before appending it to the answer.

Part 2: Course ScheduleThere are num_courses courses labeled from 0 to num_courses - 1. You are given a list of prerequisite pairs [a, b], meaning you must take course b before course a. Determine whether it is possible to finish all courses. This is equivalent to checking whether the prerequisite graph contains a cycle.

Constraints

1 <= num_courses <= 10^50 <= len(prerequisites) <= 2 * 10^5Each prerequisite pair has length 20 <= course, prerequisite < num_courses

Examples

Input: (2, [[1, 0]])

Expected Output: True

Explanation: Course 0 can be taken first, then course 1.

Input: (2, [[1, 0], [0, 1]])

Expected Output: False

Explanation: The two courses depend on each other, forming a cycle.

Hints

Think of courses as nodes in a directed graph and

prerequisites as directed edges.If you repeatedly take courses with indegree 0 and cannot process all nodes, a cycle exists.

Part 3: Longest Substring with At Most K Distinct CharactersGiven a string s and an integer k, return the length of the longest substring that contains at most k distinct characters.

Constraints

0 <= len(s) <= 2 * 10^50 <= k <= len(s)s may contain any standard characters

Examples

Input: ("eceba", 2)

Expected Output: 3

Explanation: The longest valid substring is 'ece', which has length 3.

Input: ("aa", 1)

Expected Output: 2

Explanation: The whole string contains only one distinct character.

Hints

A sliding window can maintain a valid substring while expanding to the right.Keep character counts in the current window, and shrink from the left whenever the number of distinct characters exceeds k.

APPROACH

BFS by level with reversed alternate levels; topological sort / DFS cycle detection; plus a sliding-window task.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Three LeetCode problems: 103 zigzag level order, 207 course schedule, 340 longest substring with at most K distinct characters. For each ask the usual edge questions: empty tree, duplicate prerequisites, K = 0.

BRUTE FORCE TO SAY OUT LOUD

Zigzag: do a normal level order and reverse alternate levels afterwards. Course schedule: DFS from every course to find cycles. Substring: check every substring.

OPTIMAL IDEA

Zigzag: BFS level by level, reverse (or use a deque appended on the left or right) on every other level. O(n). Course schedule: Kahn's algorithm, with in-degree counts and a queue; if processed courses equal the course count there is no cycle. O(V + E). Substring (340): sliding window with a dict of counts; expand right, and while distinct characters exceed K shrink from the left, deleting a character at count 0. Track the maximum window. O(n).

DRY-RUN THESE CASES

Zigzag: empty tree, a single node, a skewed tree. Course schedule: no prerequisites, a self loop, a two-course cycle. Substring: K = 0 (answer 0), K larger than distinct characters, a repeated character.

LIKELY FOLLOW-UPS

Course Schedule II (return an order), longest substring with exactly K distinct, at most K distinct in a stream.

PITFALLS

Reversing the wrong levels. Not removing a key from the window dict when its count hits zero.

HOW TO THINK ABOUT IT

Three standard patterns. Level order needs a queue and a direction flag per level. 'Can everything be finished' is cycle detection in a directed graph: Kahn's algorithm removes nodes with no remaining prerequisites, and a cycle leaves some behind. 'Longest window with at most K of something' is a sliding window with a count map that shrinks from the left when the limit is exceeded.

Basis: Three LeetCode problems: 103 Binary Tree Zigzag Level Order, 207 Course Schedule and 340 Longest Substring with At Most K Distinct Characters.

BRUTE FORCE · Course schedule: DFS from every course looking for a cycle

BRUTE FORCE · PSEUDO-CODE

```
def can_finish(n, prereqs):
    graph = build_graph(n, prereqs)
    for course in range(n):
        if reaches(graph, course, course):
            return False  # a cycle
    return True
```

BRUTE FORCE · Course schedule: DFS from every course looking for a cycle

TIME	SPACE
O(V * (V + E))	O(V)

WHY IT IS SLOW

Each search can walk the whole graph again, O(V * (V + E)). Kahn's algorithm (remove courses with no unmet prerequisites) is O(V + E).

BRUTE FORCE · Longest window: check every substring

BRUTE FORCE · PSEUDO-CODE

```
def brute(s, K):
    best = 0
    for i in range(len(s)):
        seen = set()
        for j in range(i, len(s)):
            seen.add(s[j])
            if len(seen) > K:
                break
            best = max(best, j - i + 1)
    return best
```

TIME	SPACE
O(n^2)	O(k)

WHY IT IS SLOW

O(n^2) in the worst case. A sliding window with a count map that shrinks from the left when it exceeds K distinct characters is O(n).

BRUTE FORCE · Zigzag: level order, then reverse the odd levels

BRUTE FORCE · PSEUDO-CODE

```
def zigzag(root):
    levels = level_order(root)
    for i in range(1, len(levels), 2):
        levels[i].reverse()
    return levels
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Same O(n) time with one extra copy of every second level; filling each level from alternating ends of a deque avoids it.

OPTIMAL SOLUTION · Course schedule: Kahn's topological sort

TIME	SPACE
O(V + E)	O(V + E)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Longest window: sliding window with a count map

TIME	SPACE
O(n)	O(k)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Zigzag: fill each level from the correct end

TIME	SPACE
O(n)	O(width)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Course Schedule II: return an order in which to take the courses.

The same Kahn loop records the order in which courses are removed; if fewer than n courses are removed, return an empty list.

FOLLOW-UP 2 Longest substring with exactly K distinct characters.

Take atMost(K) minus atMost(K - 1) for counting substrings, or keep the window and only record lengths when the distinct count is exactly K (careful with the shrink).

FOLLOW-UP 3 Zigzag on an n-ary tree, or the right-to-left variant.

Replace the two children by the child list, and swap which levels are appended on the left.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict, deque


class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


def build(values):
    # level-order list, None for a missing child
    if not values:
        return None
    root = TreeNode(values[0])
    queue, i = deque([root]), 1
    while queue and i < len(values):
        node = queue.popleft()
        for side in ("left", "right"):
            if i < len(values) and values[i] is not None:
                child = TreeNode(values[i])
                setattr(node, side, child)
```

```
                queue.append(child)
            i += 1
    return root


# BASE QUESTION (optimal): Course schedule: Kahn's
# topological sort
def zigzag(root):
    # level order, alternating direction
    out, left_to_right = [], True
    queue = deque([root] if root else [])
    while queue:
        level = deque()
        for _ in range(len(queue)):
            node = queue.popleft()
            # append for left-to-right, appendleft
            # otherwise
            if left_to_right:
                level.append(node.val)
            else:
                level.appendleft(node.val)
            for child in (node.left, node.right):
                if child:
                    queue.append(child)
        out.append(list(level))
        left_to_right = not left_to_right
    return out


# FOLLOW-UP 1: Course Schedule II: return an order in
# which to take the courses.
def course_order(n, prereqs):
    # (a, b): to take a you must take b first. Kahn's
    # algorithm;
    # if some course never frees up there is a cycle
    adj, indeg = defaultdict(list), [0] * n
    for a, b in prereqs:
        adj[b].append(a)
        indeg[a] += 1
    queue = deque(c for c in range(n) if indeg[c] == 0)
    order = []
    while queue:
        c = queue.popleft()
        order.append(c)
        for nxt in adj[c]:
            indeg[nxt] -= 1
            if indeg[nxt] == 0:
                queue.append(nxt)
    return order if len(order) == n else []


# BASE QUESTION (optimal): Course schedule: Kahn's
# topological sort
def can_finish(n, prereqs):
    return len(course_order(n, prereqs)) == n


def longest_at_most_k(s, k):
    # sliding window with a count of each letter inside it
    count, left, best = defaultdict(int), 0, 0
    for right, ch in enumerate(s):
        count[ch] += 1
        # too many distinct letters: shrink from the left
        while len(count) > k:
            count[s[left]] -= 1
            if count[s[left]] == 0:
                del count[s[left]]
            left += 1
        best = max(best, right - left + 1)
    return best


def count_at_most_k(s, k):
    # number of substrings with at most k distinct letters
    if k < 1:
        return 0
    count, left, total = defaultdict(int), 0, 0
    for right, ch in enumerate(s):
        count[ch] += 1
        while len(count) > k:
            count[s[left]] -= 1
            if count[s[left]] == 0:
                del count[s[left]]
            left += 1
        total += right - left + 1
    return total


# FOLLOW-UP 2: Longest substring with exactly K distinct
# characters.
def count_exactly_k(s, k):
    # exactly k = at most k minus at most k - 1
    most = count_at_most_k(s, k)
    return most - count_at_most_k(s, k - 1)


if __name__ == "__main__":
    tree = build([3, 9, 20, None, None, 15, 7])
    assert zigzag(tree) == [[3], [20, 9], [15, 7]]
    assert zigzag(None) == []
    assert can_finish(2, [(1, 0)])
    assert not can_finish(2, [(1, 0), (0, 1)])
    order = course_order(4, [(1, 0), (2, 1), (3, 2)])
    assert order == [0, 1, 2, 3]
    assert course_order(2, [(0, 1), (1, 0)]) == []
    assert longest_at_most_k("eceba", 2) == 3
    assert longest_at_most_k("aa", 1) == 2
    assert longest_at_most_k("abc", 0) == 0
    assert count_exactly_k("abab", 2) == 6
    assert count_at_most_k("abab", 1) == 4
```

FUNCTION AND TEST CASES

Signature

```
def solution(root: list[str]) -> list[list[int]]:
```

Sample call

```
solution([3, 9, 20, None, None, 15, 7])
```

Test cases

Input	Expected
`([3, 9, 20, None, None, 15, 7],)`	`[[3], [20, 9], [15, 7]]`
`([1],)`	`[[1]]`

MEDIUM | IN APP LC 207 | PracHub | Technical Screen | 108 of 165

★ TOP 75: rank 33 in the Medium and Hard priority list

★ Validate course catalog dependencies

POSTED 2025-08-01 | 435 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 51.9 | 30 DAYS 33 | PRIORITY 29/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #207 Course Schedule

LeetCode match: LC 207 Course Schedule

Posted on PracHub: 2025-08-01 (updated 2026-06-25)

Original: https://prachub.com/coding-questions/validate-course-catalog-dependencies

QUESTION

Design a function to validate an e-learning course catalog. You are given: (1) a set of course IDs, and (2) a list of prerequisite pairs (u, v) meaning course v requires course u. Determine if the catalog is valid: no prerequisite references a non-existent course, and there are no cycles in the dependency graph. If valid, return true and a possible ordering of courses; otherwise return false and report the set of missing course references and at least one cycle you detect. Specify your algorithm, time and space complexity.

APPROACH

Check every prerequisite refers to a known course ID, then Kahn's topological sort or DFS coloring to detect cycles.

HOW TO THINK ABOUT IT

Two separate validity rules: every course mentioned must exist, and the dependency graph must have no cycle. The first is a set lookup per pair. For the second, Kahn's algorithm removes courses with no unmet prerequisites; anything left over is on a cycle or depends on one, and a DFS restricted to the leftovers reveals an actual cycle to report.

Basis: LeetCode 207 / 210 (Course Schedule) plus a check for references to unknown courses. A pair (u, v) means course v requires u.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def validate(courses, prereqs):
    for u, v in prereqs:
        if u not in courses or v not in courses:
            return False  # unknown id
    graph = build_graph(prereqs)
    for c in courses:
        if reaches(graph, c, c):
            return False  # cycle
    return True
```

TIME	SPACE
O(V * (V + E))	O(V)

WHY IT IS SLOW

Every course can trigger a walk of the whole graph, O(V * (V + E)). Kahn's algorithm is O(V + E) and its leftovers also reveal a cycle to report.

OPTIMAL SOLUTION · Missing references, then Kahn's algorithm, then a cycle from the leftovers

TIME	SPACE
O(V + E)	O(V + E)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return all missing course references and one cycle.

The function above returns the sorted unknown ids when any exist and otherwise a cycle (a list of courses starting and ending at the same course), found by walking backwards along prerequisites inside the set of courses Kahn's algorithm could not remove (every such course has a leftover prerequisite, so the walk cannot dead-end).

FOLLOW-UP 2 Group courses into semesters (the earliest round each can be taken).

Run Kahn's algorithm level by level: all courses with no remaining prerequisites form round 1, remove them, the next set forms round 2, and so on. The number of rounds is the longest dependency chain.

FOLLOW-UP 3 Find all cycles, not just one.

Compute strongly connected components (Tarjan or Kosaraju); every component with more than one course (or a self-loop) is a cycle group to report.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict, deque


# BASE QUESTION (optimal): Missing references, then Kahn's
# algorithm, then a cycle ...
# FOLLOW-UP 1: Return all missing course references and
# one cycle.
def validate_catalog(courses, prereqs):
    # prereqs (u, v): course v requires course u.
    # Returns (ok, missing ids, order or one cycle)
    known = set(courses)
    missing = sorted({x for pair in prereqs for x in pair
                      if x not in known}, key=str)
    if missing:
        return False, missing, None
    adj, indeg = defaultdict(list), {c: 0 for c in known}
    for u, v in prereqs:
        adj[u].append(v)
        indeg[v] += 1
    ready = [c for c in known if indeg[c] == 0]
    queue = deque(sorted(ready, key=str))
    order = []
    while queue:
        c = queue.popleft()
        order.append(c)
        for nxt in adj[c]:
            indeg[nxt] -= 1
            if indeg[nxt] == 0:
                queue.append(nxt)
    if len(order) == len(known):
        return True, [], order
    return False, [], find_cycle(known, prereqs, indeg)


# FOLLOW-UP 3: Find all cycles, not just one.
def find_cycle(known, prereqs, indeg):
    # every leftover course still has a leftover
    # prerequisite,
    # so walking backwards must eventually repeat a course
    left = {c for c in known if indeg[c] > 0}
    before = defaultdict(list)
    for u, v in prereqs:
        if u in left and v in left:
            before[v].append(u)
    x = min(left, key=str)
```

```
    walk, pos = [], {}
    while x not in pos:
        pos[x] = len(walk)
        walk.append(x)
        x = before[x][0]
    cycle = walk[pos[x]:] + [x]
    # walked against the edges: reverse to list
    # prerequisites first
    return cycle[::-1]


# FOLLOW-UP 2: Group courses into semesters (the earliest
# round each can be taken).
def semesters(courses, prereqs):
    # earliest round each course can be taken: Kahn by
    # levels
    adj = defaultdict(list)
    indeg = {c: 0 for c in courses}
    for u, v in prereqs:
        adj[u].append(v)
        indeg[v] += 1
    level = sorted(c for c in courses if indeg[c] == 0)
    rounds = []
    while level:
        rounds.append(level)
        nxt = []
        for c in level:
            for v in adj[c]:
```

```
                indeg[v] -= 1
                if indeg[v] == 0:
                    nxt.append(v)
        level = sorted(nxt)
    return rounds


if __name__ == "__main__":
    courses = ["a", "b", "c", "d"]
    pre = [("a", "b"), ("b", "c"), ("a", "d")]
    ok, missing, order = validate_catalog(courses, pre)
    assert ok and order[0] == "a"
    assert order.index("b") < order.index("c")
    # an unknown course id
    bad = validate_catalog(courses, pre + [("zzz", "a")])
    assert bad == (False, ["zzz"], None)
    # a cycle b -> c -> b
```

```
    loop = pre + [("c", "b")]
    ok, _, cycle = validate_catalog(courses, loop)
    assert not ok and cycle[0] == cycle[-1]
    assert set(cycle) == {"b", "c"}
    rounds = semesters(courses, pre)
    assert rounds == [["a"], ["b", "d"], ["c"]]
    assert validate_catalog([], []) == (True, [], [])
```

FUNCTION AND TEST CASES

Signature

```
def solution(course_ids: list[str], prereqs: list[tuple[st
r, str]]) -> tuple[bool, list[str], list[str], list[str]]:
```

Sample call

```
solution(['A', 'B', 'C'], [('A', 'B'), ('B', 'C')])
```

Test cases

Input	Expected
`(['A', 'B', 'C'], [('A', 'B'), ('B', 'C')])`	`(True, ['A', 'B', 'C'], [], [])`
`(['A', 'B', 'C'], [('A', 'B'), ('B', 'C'), ('C', 'A')])`	`(False, [], [], ['A', 'B', 'C', 'A'])`

MEDIUM | IN APP LC 103 | PracHub | Technical Screen | 109 of 165

Implement zigzag level-order traversal

POSTED 2025-08-01 | 435 DAYS AGO | OLDER

STUDY: TALK ALL TIME 38.7 30 DAYS 0 PRIORITY 95/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #103 Binary Tree Zigzag Level Order Traversal

LeetCode match: LC 103 Binary Tree Zigzag Level Order Traversal

Posted on PracHub: 2025-08-01 (updated 2026-06-25)

ABOUT THIS QUESTION

Original: https://prachub.com/coding-questions/implement-zigzag-level-order-traversal

QUESTION

Given the root of a binary tree, return the node values in zigzag level order: visit nodes level by level, reading the first level from left to right, the next from right to left, and so on alternating each level. Output a list of lists of integers where each inner list contains the values for one level in the required direction. Aim for O(n) time and O(w) extra space, where n is the number of nodes and w is the maximum width of the tree.

APPROACH

BFS by level; reverse (or use a deque appending left/right) on alternate levels. O(n).

HOW TO THINK ABOUT IT

It is a plain level-order traversal where every second level is read in the other direction. Either collect each level and reverse the odd ones, or fill each level from the correct end of a deque so no reversal is needed.

Basis: LeetCode 103, Binary Tree Zigzag Level Order Traversal.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def zigzag(root):
    levels = level_order(root)
    for i in range(1, len(levels), 2):
        levels[i].reverse()
    return levels
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Same O(n) time, plus an extra pass copying the reversed levels. Filling each level from the left or right end of a deque as it is built needs no reversal.

OPTIMAL SOLUTION · BFS filling each level from the left or the right

TIME	SPACE
O(n)	O(width)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Bottom-up level order (leaf level first).

Run the normal traversal and reverse the list of levels at the end.

FOLLOW-UP 2 Do it with DFS.

Pass the depth; append the value to levels[depth], at the end when the depth is even and at the front (insert at 0 or a deque) when odd. Recursion depth is the tree height.

FOLLOW-UP 3 N-ary tree.

Replace the two children by the list of children; the direction flag works the same way.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


# BASE QUESTION (optimal): BFS filling each level from the
# left or the right
def zigzag_level_order(root):
    # BFS by levels; flip the direction on every level
    out, ltr = [], True
    queue = deque([root] if root else [])
    while queue:
        level = deque()
        for _ in range(len(queue)):
            node = queue.popleft()
            if ltr:
                level.append(node.val)
            else:
                level.appendleft(node.val)
            for child in (node.left, node.right):
                if child:
                    queue.append(child)
        out.append(list(level))
        ltr = not ltr
    return out


# FOLLOW-UP 2: Do it with DFS.
def zigzag_dfs(root):
    # DFS: pass the depth; odd levels are filled at the
    # front
    levels = []

    def go(node, depth):
        if node is None:
            return
        if depth == len(levels):
            levels.append(deque())
        if depth % 2 == 0:
            levels[depth].append(node.val)
        else:
            levels[depth].appendleft(node.val)
```

```
        go(node.left, depth + 1)
        go(node.right, depth + 1)

    go(root, 0)
    return [list(x) for x in levels]


# FOLLOW-UP 1: Bottom-up level order (leaf level first).
def level_order_bottom_up(root):
    # leaf level first: the normal traversal, reversed at
    # the end
    out, queue = [], deque([root] if root else [])
    while queue:
        out.append([n.val for n in queue])
        for _ in range(len(queue)):
            node = queue.popleft()
            for child in (node.left, node.right):
                if child:
                    queue.append(child)
    return out[::-1]


class NNode:
    def __init__(self, val, children=()):
        self.val, self.children = val, list(children)


# FOLLOW-UP 3: N-ary tree.
def zigzag_nary(root):
    # an n-ary tree: a list of children instead of two
    out, ltr = [], True
    queue = deque([root] if root else [])
    while queue:
        vals = [n.val for n in queue]
        out.append(vals if ltr else vals[::-1])
        for _ in range(len(queue)):
            queue.extend(queue.popleft().children)
        ltr = not ltr
    return out


if __name__ == "__main__":
    right = TreeNode(20, TreeNode(15), TreeNode(7))
    tree = TreeNode(3, TreeNode(9), right)
    want = [[3], [20, 9], [15, 7]]
```

```
    assert zigzag_level_order(tree) == want
    assert zigzag_dfs(tree) == want
    up = level_order_bottom_up(tree)
    assert up == [[15, 7], [9, 20], [3]]
    assert zigzag_level_order(None) == []
    assert zigzag_dfs(None) == []
    kids = [NNode(2, [NNode(5)]), NNode(3), NNode(4)]
    root = NNode(1, kids)
    assert zigzag_nary(root) == [[1], [4, 3, 2], [5]]
```

FUNCTION AND TEST CASES

Signature

```
def zigzagLevelOrder(values: list[int | None]) -> list[lis
t[int]]:
```

Sample call

```
zigzagLevelOrder([3, 9, 20, None, None, 15, 7])
```

Test cases

Input	Expected
`([3, 9, 20, None, None, 15, 7],)`	`[[3], [20, 9], [15, 7]]`
`([1],)`	`[[1]]`

MEDIUM | PracHub | Technical Screen | 110 of 165

Decide string transform with directional tokens and walls

POSTED 2025-07-15 | 452 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 40.3 | 30 DAYS 0 | PRIORITY 93/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

LeetCode match: LC 777 Swap Adjacent in LR String (with X walls)

Posted on PracHub: 2025-07-15 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/decide-string-transform-with-directional-tokens-and-walls

QUESTION

You are given two equal-length strings start and target of length n, each consisting only of the characters 'L', 'R', '.', and 'X'. A dot '.' represents an empty slot; 'X' represents an immovable wall; 'L' and 'R' are tokens that may move across empty slots subject to these rules: (1) An 'L' token may move any number of positions left into '.', but may never move right, pass through another token, or pass through an 'X'. (2) An 'R' token may move any number of positions right into '.', but may never move left, pass through another token, or pass through an 'X'. (3) Only one token can occupy a position at any time. Determine whether target can be obtained from start by a sequence of valid moves. If yes, return true; otherwise, return false. Design an algorithm that runs in O(n) time and O(1) extra space beyond a few pointers/counters. Explain your invariants, prove correctness informally, analyze time and space complexity, and walk through a few tricky edge cases (e.g., mismatched wall layouts, blocks separated by walls, consecutive tokens with no gaps).

APPROACH

Split both strings at 'X' walls (must align), then within each segment apply the L/R two-pointer rule: L only moves left, R only right, order of pieces preserved.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what each symbol means (L moves left, R moves right, dot empty, X wall that never moves and cannot be crossed), whether a token can jump over another (no), and whether both strings have the same length.

INTERVIEW-DAY PLAN

BRUTE FORCE TO SAY OUT LOUD

BFS over all board states by moving tokens one step. Exponential.

OPTIMAL IDEA

Compare the sequences of non-dot characters: they must be identical, which also forces every X to appear in the same order. Then with two pointers over those tokens check that each L has start index at least target index, each R has start index at most target index, and each X has the same index in both. Walls cannot be crossed because order is preserved. O(n).

DRY-RUN THESE CASES

Identical strings, an L that would move right, an R blocked by a wall, a different number of tokens, a wall at a different index.

LIKELY FOLLOW-UPS

Return the minimum number of moves (sum of index differences), or the move sequence.

PITFALLS

Letting a token cross a wall. Checking only counts of L and R.

HOW TO THINK ABOUT IT

Walls are pieces that never move. Ignore the dots and compare the sequences of L, R and X: they must match in order and in count, and each X must be at the same index in both strings. For the L and R pieces keep the same rule: L never moves right, R never moves left. Order is preserved, so no piece can get across a wall.

Basis: LeetCode 777 with walls: 'L' moves left, 'R' moves right, '.' is empty, 'X' is an immovable wall; no piece crosses another piece or a wall.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def can_transform(start, target):
    seen, queue = {start}, deque([start])
    while queue:
        board = queue.popleft()
        if board == target:
            return True
        for nxt in one_step(board):
            if nxt not in seen:
                seen.add(nxt)
                queue.append(nxt)
    return False
```

TIME	SPACE
exponential	exponential

WHY IT IS SLOW

The number of reachable boards grows exponentially with the length. Comparing the non-dot sequence (walls and pieces in order) with position rules (L never moves right, R never moves left, walls stay) is O(n).

OPTIMAL SOLUTION · Compare the non-dot sequences with position rules

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Segments between walls are independent.

You can also split both strings at the walls (they must be at identical positions) and apply the L/R rule to each segment separately. The single pass above is equivalent.

FOLLOW-UP 2 Return the moves or the minimum number of steps.

Per piece, the steps are the index difference; list moves by letting each piece walk one cell at a time in an order that never blocks (move L pieces left to right and R pieces right to left).

FOLLOW-UP 3 The board is 2D.

Then pieces can pass each other by going around, and invariants like order no longer hold. Ask for the exact movement rules; most likely you would model it as a graph search with a heuristic.

FOLLOW-UP 4 Return the minimum number of moves.

When the transformation is possible each piece moves independently from its start index to its target index, so the minimum is the sum of the absolute index differences (checked against BFS on small strings).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


def pieces(board):
    # everything except the empty '.' slots, with
    # positions
    return [(ch, i) for i, ch in enumerate(board)
            if ch != "."]


# BASE QUESTION (optimal): Compare the non-dot sequences
# with position rules
def can_transform(start, end):
    # 'L' moves left, 'R' moves right, 'X' is an immovable
    # wall. Pieces never pass each other, so their order
    # is
    # fixed; each one only has a direction it may move.
    if len(start) != len(end):
        return False
    a, b = pieces(start), pieces(end)
    if len(a) != len(b):
        return False
```

```
    for (c1, i), (c2, j) in zip(a, b):
        if c1 != c2:
            return False
        if c1 == "X" and i != j:
            return False
        if c1 == "L" and i < j:
            return False
        if c1 == "R" and i > j:
            return False
    return True


# FOLLOW-UP 4: Return the minimum number of moves.
# MIN MOVES (pieces move independently)
def min_moves(start, end):
    # pieces move independently: the sum of index
    # differences
    if not can_transform(start, end):
        return None
    a, b = pieces(start), pieces(end)
    return sum(abs(i - j) for (_, i), (_, j) in zip(a, b))
```

```
# BRUTE FORCE over real moves (checker)
def bfs_moves(start, end):
    # brute force over real moves (the check used by the
    # demo)
    seen, queue = {start: 0}, deque([start])
    while queue:
        s = queue.popleft()
        if s == end:
            return seen[s]
        for i, ch in enumerate(s):
            for step, piece in ((-1, "L"), (1, "R")):
                j = i + step
                inside = 0 <= j < len(s)
                if ch == piece and inside and s[j] == ".":
                    t = list(s)
                    t[i], t[j] = ".", ch
                    t = "".join(t)
                    if t not in seen:
                        seen[t] = seen[s] + 1
                        queue.append(t)
    return None


if __name__ == "__main__":
    assert can_transform("R.L", ".RL") is True
    assert not can_transform("RL.", "LR.")
    # a wall cannot move and splits the board
    assert can_transform("R.X.L", ".RX.L") is True
    assert not can_transform("R.X", "X.R")
    assert min_moves("R..L", ".RL.") == 2
    assert min_moves("L.", ".L") is None
    import itertools
    boards = []
    for n in range(1, 5):
        for p in itertools.product("LR.X", repeat=n):
            boards.append("".join(p))
    for s in boards:
        for t in boards:
            if len(s) == len(t) and len(s) <= 4:
                fast = min_moves(s, t)
                assert fast == bfs_moves(s, t), (s, t)
```

FUNCTION AND TEST CASES

Signature

```
def canTransform(start: str, target: str) -> bool:
```

Sample call

```
canTransform('R...L', 'RL...')
```

Test cases

Input	Expected
`('R...L', 'RL...')`	`True`
`('R.L', 'R..L')`	`False`

MEDIUM | PracHub | Technical Screen | 111 of 165

★ TOP 75: rank 12 in the Medium and Hard priority list

★ Solve Banana Speed and Interval Merge

POSTED 2025-01-27 | 621 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 65.2 | 30 DAYS 41.1 | PRIORITY 9/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #875 Koko Eating Bananas, LeetCode #56 Merge Intervals

LeetCode match: LC 875 Koko Eating Bananas + LC 56 Merge Intervals

Posted on PracHub: 2025-01-27 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/solve-banana-speed-and-interval-merge

QUESTION

During two technical phone screens for a new graduate software engineering role, the candidate was asked to solve two coding problems: minimum eating speed and merging overlapping intervals.

Constraints & Assumptions

- Provide clear algorithms, correctness reasoning, complexity, and edge cases.
- For minimum eating speed, each hour can be spent on only one pile.
- For interval merging, intervals overlap when the next start is less than or equal to the current merged end.
- Use sorted or binary-search approaches where appropriate.

Clarifying Questions

to Ask - Are **`piles`** and **h** always positive?

- Is **h** at least the number of piles?
- Are interval endpoints inclusive?

QUESTION

- Can intervals be empty or unsorted?

Part 1

- Minimum Eating Speed Given **`piles`** and **h**, return the minimum integer speed **k** such that all piles can be eaten within **h** hours.

What This Part Should Cover

- Binary search on answer from 1 to **`max(piles)`**.
- Feasibility function using sum of **`ceil(pile / k)`**.
- Why feasibility is monotonic.
- Complexity and edge cases.

Part 2

- Merge Overlapping Intervals Given intervals **`[start, end]`**, merge all overlapping intervals and return non-overlapping intervals sorted by start.

What This Part Should Cover

- Sort by start.
- Maintain current merged interval.
- Extend on overlap, otherwise append and start a new interval.
- Complexity and edge cases.

What a Strong

Answer Covers - Recognizes monotonic binary search for eating speed.

- Uses integer-safe ceiling division.
- Correctly defines interval overlap.
- Gives clean code and complexity for both problems.

Follow-up Questions

- How would you avoid floating-point division in the banana problem?
- What if **h** is smaller than the number of piles?
- How do you merge touching intervals like **`[1,3]`** and **`[3,5]`**?
- How would you handle streaming intervals?Minimum Eating Speed (Koko Eating Bananas)Koko loves to eat bananas. There are **n** piles of bananas; the i-th pile has **`piles[i]`** bananas. The guards will return in **h** hours. Koko can decide her constant bananas-per-hour eating speed **k**. Each hour she chooses one pile and eats **k** bananas from it. If that pile has fewer than **k** bananas, she eats all of them and does not eat more during that hour. An hour is spent on only one pile. Return the minimum integer speed **k** such that she can finish all the bananas within **h** hours. Example:
- **`piles = [3, 6, 7, 11]`**, **`h = 8`** -> **`4`**
- **`piles = [30, 11, 23, 4, 20]`**, **`h = 5`** -> **`30`**
- **`piles = [30, 11, 23, 4, 20]`**, **`h = 6`** -> **`23`** Constraints: **`1 <= piles.length <= h`**, **`1 <= piles[i] <= 10^9`**.

Constraints
1 <= piles.length <= h1 <= piles[i] <= 10^9h can be as large as 10^9

QUESTION

EXAMPLES

```
Input: ([3, 6, 7, 11], 8)
Expected Output: 4
Explanation: At k=4:
    ceil(3/4)+ceil(6/4)+ceil(7/4)+ceil(11/4) =
    1+2+2+3 = 8 hours. k=3 needs 1+2+3+4 = 10 > 8, so
    4 is minimal.
Input: ([30, 11, 23, 4, 20], 5)
Expected Output: 30
```

Explanation: With exactly 5 piles and 5 hours, each pile must be eaten in one hour, so k must be at least max(piles) = 30.

Hints

If speed k finishes in time, any larger speed also finishes in time. This monotonicity lets you binary search on the answer.The answer lies in [1, max(piles)]: speed 1 is the slowest, and max(piles) finishes every pile in at most one hour.Hours needed at speed k is sum of ceil(pile / k). Use integer-safe ceiling: (pile + k - 1) // k to avoid floating point.Merge Overlapping IntervalsGiven an array of intervals where **`intervals[i] = [start_i, end_i]`**, merge all overlapping intervals and return an array of the non-overlapping intervals that cover all the intervals in the input, sorted by start. Two intervals overlap when the next start is less than or equal to the current merged end

APPROACH

Binary search the speed with ceil(pile/speed) sum <= h; sort intervals by start and merge overlaps in one pass.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Bananas: piles and h are positive, h is at least the number of piles (otherwise impossible), one pile per hour, and an hour finishes at most one pile. Intervals: overlap includes touching (next start at most the current end).

BRUTE FORCE TO SAY OUT LOUD

Bananas: try every speed from 1 up. Intervals: compare every pair.

OPTIMAL IDEA

Bananas (LeetCode 875): the time function is monotone in the speed, so binary search the smallest speed in [1, max(piles)] with sum(ceil(p / s)) <= h. O(n log max). Intervals: sort by start and sweep, merging while the next start is at most the current end. O(n log n).

DRY-RUN THESE CASES

Bananas: h equal to the pile count (speed is the maximum), a single pile, large piles (overflow). Intervals: touching, nested, unsorted, one interval.

LIKELY FOLLOW-UPS

Bananas with a variable h or a floating-point speed. Intervals: insert one interval or count the merged result.

PITFALLS

INTERVIEW-DAY PLAN

Using floor instead of ceil. Merging with strict less-than.

HOW TO THINK ABOUT IT

Bananas: the time needed is non-increasing in the speed, so the smallest speed that finishes in h hours can be found by binary search over speeds, with a simple sum of ceil(pile / speed) as the check. Intervals: sort by start and sweep with one 'current' interval; the sort guarantees nothing earlier can still overlap.

Basis: LeetCode 875 (Koko Eating Bananas; one pile per hour, h at least the number of piles) and LeetCode 56 (Merge Intervals; overlapping when the next start is at most the current end).

BRUTE FORCE · Bananas: try every speed upward

BRUTE FORCE · PSEUDO-CODE

```
def brute(piles, h):
    for speed in range(1, max(piles) + 1):
        hours = 0
        for p in piles:
            hours += ceil(p / speed)
        if hours <= h:
            return speed
```

TIME	SPACE
O(max * n)	O(1)

WHY IT IS SLOW

Up to max(piles) speeds, each costing O(n); piles can be 10^9. Hours are non-increasing in the speed, so binary search over speeds is O(n log max).

BRUTE FORCE · Intervals: merge any overlapping pair until none is left

BRUTE FORCE · PSEUDO-CODE

```
def merge(intervals):
    intervals = list(intervals)
    merged = True
    while merged:
        merged = False
        for a, b in combinations(intervals, 2):
            if overlaps(a, b):
                intervals.remove(a)
                intervals.remove(b)
                intervals.append(union(a, b))
                merged = True
                break
    return sorted(intervals)
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Each pass compares all pairs, O(n^2), and several passes may be needed. Sorting by start and sweeping once is O(n log n).

OPTIMAL SOLUTION · Bananas: binary search the speed

TIME	SPACE
O(n log max)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Intervals: sort and sweep

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Bananas: h varies per query, or the piles change.

The check is independent of the search; for many queries keep the piles sorted with prefix sums so the hours needed at speed s can be computed in O(log n) per distinct pile size.

FOLLOW-UP 2 Intervals: insert one new interval into an already merged list (LeetCode 57).

Copy intervals ending before the new one, merge the ones that overlap it, then copy the rest. O(n), no sort needed.

FOLLOW-UP 3 Bananas: the guards come back in fewer hours than piles.

Then no speed works (an hour can finish at most one pile): check h >= len(piles) first and return -1 otherwise.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def hours_needed(piles, speed):
    # each hour she works on ONE pile, so every pile
    # rounds up
    return sum(-(-p // speed) for p in piles)


# BASE QUESTION (optimal): Bananas: binary search the
# speed
def min_eating_speed(piles, h):
    # fewer hours than piles can never work
    if h < len(piles):
        return -1
    lo, hi = 1, max(piles)
    # more speed never takes more hours: binary search
    while lo < hi:
        mid = (lo + hi) // 2
        if hours_needed(piles, mid) <= h:
            hi = mid
        else:
            lo = mid + 1
    return lo


# PART 2: merge intervals
```

```python
def merge_intervals(intervals):
    out = []
    for s, e in sorted(intervals):
        # overlap (sharing a point counts): extend the
        # last one
        if out and s <= out[-1][1]:
            out[-1][1] = max(out[-1][1], e)
        else:
            out.append([s, e])
    return out


# FOLLOW-UP 2: Intervals: insert one new interval into an
# already merged list ...
def insert_interval(merged, new):
    # LeetCode 57: the list is already merged and sorted:
    # O(n)
    out, i, n = [], 0, len(merged)
    # 1) intervals that end before the new one starts
    while i < n and merged[i][1] < new[0]:
        out.append(merged[i])
        i += 1
    # 2) intervals that overlap it are absorbed
    s, e = new
    while i < n and merged[i][0] <= e:
        s, e = min(s, merged[i][0]), max(e, merged[i][1])
        i += 1
    out.append([s, e])
    # 3) the rest comes after
    out += merged[i:]
    return out


if __name__ == "__main__":
    assert min_eating_speed([3, 6, 7, 11], 8) == 4
    assert min_eating_speed([30, 11, 23, 4, 20], 5) == 30
    assert min_eating_speed([30, 11, 23, 4, 20], 6) == 23
    # fewer hours than piles: impossible
    assert min_eating_speed([1, 1, 1], 2) == -1
    assert hours_needed([3, 6, 7, 11], 4) == 8
    spans = [[1, 3], [2, 6], [8, 10], [15, 18]]
    merged = merge_intervals(spans)
    assert merged == [[1, 6], [8, 10], [15, 18]]
    assert merge_intervals([[1, 4], [4, 5]]) == [[1, 5]]
    assert merge_intervals([]) == []
    got = insert_interval([[1, 3], [6, 9]], [2, 5])
    assert got == [[1, 5], [6, 9]]
    assert insert_interval([], [4, 8]) == [[4, 8]]
    assert insert_interval([[1, 2], [5, 6]], [3, 4]) == [
        [1, 2], [3, 4], [5, 6]]
```

FUNCTION AND TEST CASES

Signature

```python
def solution(piles: list[int], h: int) -> int:
```

Sample call

```python
solution([3, 6, 7, 11], 8)
```

Test cases

Input	Expected
([3, 6, 7, 11], 8)	4
([30, 11, 23, 4, 20], 5)	30

MEDIUM | PracHub | Technical Screen | 112 of 165

★ TOP 75: rank 27 in the Medium and Hard priority list

★ Solve Grid and Counting Problems

POSTED 2025-01-25 | 623 DAYS AGO | OLDER

STUDY: TYPE | ALL TIME 64.8 | 30 DAYS 33 | PRIORITY 17/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #200 Number of Islands

LeetCode match: LC 200 Number of Islands (+ a counting task)

Posted on PracHub: 2025-01-25 (updated 2026-04-24)

Original:
https://prachub.com/coding-questions/solve-grid-and-counting-problems

QUESTION

A software engineering intern phone screen included two coding tasks: 1.

Count islands in a grid Given an `m x n` grid of characters where `'1'` represents land and `'0'` represents water, return the number of islands. An island is formed by connecting adjacent land cells horizontally or vertically. You may assume all four edges of the grid are surrounded by water. 2.

Count ways to form a target word Given an array of uppercase letters, count how many different ways you can choose letters from the array so that the chosen letters can be rearranged to spell **`GOOGLE`**. Each array element can be used at most once, and letters at different indices are considered different choices even if they contain the same character. Design efficient algorithms for both tasks, and discuss the time and space complexity of your approach.

Part 1: Count Islands in a GridGiven a 2D grid of characters where each cell is either '1' (land) or '0' (water), return the number of islands. An island is a group of adjacent land cells connected only horizontally or vertically. Diagonal cells do not count as connected. You may assume the grid edges are surrounded by water.

Constraints

0 <= number of rows <= 3000 <= number of columns <= 300grid[r][c] is either '0' or '1'All rows have the same length

EXAMPLES

```
Input: []
```

Expected Output:

Explanation: Empty grid contains no land, so there are no islands.

```
Input: [['1']]
```

Expected Output:

Explanation: A single land cell forms one island.

QUESTION

Hints

Whenever you find an unvisited land cell, start a DFS or BFS to mark the entire island.Only 4-directional neighbors matter: up, down, left, and right.

Part 2: Count Ways to Form the Word GOOGLEGiven an array of uppercase letters, count how many different ways you can choose letters so that the chosen letters can be rearranged to spell GOOGLE. Each array element can be used at most once. Letters at different indices count as different choices even if they contain the same character. The word GOOGLE requires exactly 2 G's, 2 O's, 1 L, and 1 E.

Constraints

0 <= len(letters) <= 200000Each element is an uppercase English letter from 'A' to 'Z'The answer may be large, but fits in Python's integer type

Examples

Input: []

Expected Output:

Explanation: No letters means it is impossible to form GOOGLE.

Input: ['G','O','O','G','L','E']

Expected Output:

Explanation: There is exactly one way to choose all six letters.

Hints

First count how many G, O, L, and E letters appear in the array.You need to choose 2 of the G positions and 2 of the O positions, then 1 L and 1 E.

APPROACH

Islands: DFS/BFS or union-find over '1' cells. Second counting task: use prefix-sum + hash map or math counting per the statement.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Two tasks. Islands: four-directional adjacency, grid up to 300 x 300, empty grid allowed. Counting: choose letters from an array so the chosen ones can be rearranged to spell GOOGLE, each index used at most once, different indices are different choices.

BRUTE FORCE TO SAY OUT LOUD

Islands: none needed, DFS is the standard. Counting: enumerate all 6-element subsets of the array and test each one. O(n^6).

OPTIMAL IDEA

Islands: scan cells, start a DFS or BFS (iterative, to avoid recursion limits) from each unvisited land cell, count the starts. O(mn). Counting: GOOGLE needs G twice, O twice, L once, E once. The number of ways is C(g, 2) * C(o, 2) * l * e, where g, o, l, e are the counts of those letters in the array, since the chosen multiset is fixed and only the indices vary. O(n) to count.

DRY-RUN THESE CASES

INTERVIEW-DAY PLAN

Islands: empty grid, a single land cell, diagonal-only neighbors (separate islands). Counting: missing a letter (0), exactly one G (0), lots of copies, an empty array.

LIKELY FOLLOW-UPS

Islands: add land one cell at a time with Union-Find. Counting: a different target word, or count ways when letters have to appear in order (subsequence DP).

PITFALLS

Treating diagonal cells as connected. Counting arrangements instead of choices of indices.

HOW TO THINK ABOUT IT

Islands: every unvisited land cell starts a new island; mark everything connected to it. Counting: the target multiset is fixed (G twice, O twice, L once, E once), so the number of ways to choose the indices is a product of binomial coefficients, one factor per distinct letter. Do not enumerate arrangements.

Basis: Two tasks: LeetCode 200 (Number of Islands) and counting the ways to choose letters from an array that can be rearranged into GOOGLE (each index used at most once).

BRUTE FORCE · Islands: recursive flood fill

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    seen, count = set(), 0
    for r, c in all_cells(grid):
        if grid[r][c] == "0" or (r, c) in seen:
            continue
        count += 1
        dfs(r, c)  # marks the whole island
    return count
```

TIME	SPACE
O(m * n)	**O(m * n)** recursion

WHY IT IS SLOW

Time is O(m * n), but the recursion can be m * n deep on a snake-shaped island and overflow the stack. A queue or an explicit stack avoids that.

BRUTE FORCE · Counting: enumerate every 6-element selection

BRUTE FORCE · PSEUDO-CODE

```
def brute(a):
    count = 0
    for idx in combinations(range(len(a)), 6):
        letters = sorted(a[i] for i in idx)
        if letters == sorted("GGOOLE"):
            count += 1
    return count
```

TIME	SPACE
O(C(n, 6) * 6)	**O(1)**

BRUTE FORCE · Counting: enumerate every 6-element selection

WHY IT IS SLOW

C(n, 6) selections. The letters needed are fixed, so the answer is C(#G, 2) * C(#O, 2) * #L * #E from one pass of counts.

OPTIMAL SOLUTION · Islands: iterative BFS

TIME	SPACE
O(m * n)	O(min(m, n)) queue

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Counting: product of binomial coefficients

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Any target word, not only GOOGLE.

Count the needed letters of the word; the answer is the product over distinct letters of C(available, needed).

FOLLOW-UP 2 The letters must appear in order (a subsequence of the array spells the word).

Then it is the 'distinct subsequences' DP: ways[j] counts the ways to spell the first j letters; scan the array and update j from high to low. O(n * len(word)).

FOLLOW-UP 3 Islands arrive one cell at a time.

Use Union-Find: each new land cell makes the count go up by one and each union with a neighbouring different island makes it go down by one (LeetCode 305).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter, deque
from math import comb

STEPS = ((1, 0), (-1, 0), (0, 1), (0, -1))


# BASE QUESTION (optimal): Islands: iterative BFS
def num_islands(grid):
    # '1' is land: a BFS marks each island once
    if not grid:
        return 0
    m, n = len(grid), len(grid[0])
    seen, count = set(), 0
    for r in range(m):
        for c in range(n):
            if grid[r][c] != "1" or (r, c) in seen:
                continue
            count += 1
            seen.add((r, c))
            queue = deque([(r, c)])
            while queue:
                x, y = queue.popleft()
                for dx, dy in STEPS:
                    a, b = x + dx, y + dy
                    if not (0 <= a < m and 0 <= b < n):
                        continue
                    land = grid[a][b] == "1"
                    if land and (a, b) not in seen:
                        seen.add((a, b))
                        queue.append((a, b))
    return count


# FOLLOW-UP 1: Any target word, not only GOOGLE.
# PART 2: count GOOGLE in the array
def ways_to_spell(letters, word="GOOGLE"):
    # choose which array positions to use: for every
    # needed
    # letter choose that many of the available copies
    have, need = Counter(letters), Counter(word)
    total = 1
    for ch, k in need.items():
        total *= comb(have[ch], k)
    return total


# FOLLOW-UP 2: The letters must appear in order (a
# subsequence of the array spells ...
def ways_in_order(letters, word="GOOGLE"):
    # the letters must appear in order (a subsequence):
    # the
    # "distinct subsequences" DP, updated from high to low
    ways = [1] + [0] * len(word)
    for ch in letters:
        for j in range(len(word), 0, -1):
            if word[j - 1] == ch:
                ways[j] += ways[j - 1]
    return ways[len(word)]


if __name__ == "__main__":
    assert num_islands([]) == 0
    assert num_islands([["1"]]) == 1
    grid = ["11000", "11000", "00100", "00011"]
    assert num_islands(grid) == 3
    assert ways_to_spell([]) == 0
    assert ways_to_spell(list("GOOGLE")) == 1
    # three O's: choose 2 of them -> 3 ways
    assert ways_to_spell(list("GOOOGLE")) == 3
    # an extra G and an extra E: 3 * 2 = 6 ways
    assert ways_to_spell(list("GGGOOLEE")) == 3 * 2
    assert ways_to_spell(list("GOGLE")) == 0
    # any target word
    assert ways_to_spell(list("AABB"), "AB") == 4
    assert ways_in_order(list("GOOGLE")) == 1
    assert ways_in_order(list("GGOOGLE")) == 2
    assert ways_in_order(list("GOGOLE")) == 0
    assert ways_in_order(list("EGOOGL")) == 0
```

FUNCTION AND TEST CASES

Signature

```
def solution(grid: list[list[str]]) -> int:
SAMPLE INPUT
[]
```

Test cases

Input	Expected
`[]`	`0`
`[['1']]`	`1`

Easy (4)

EASY | PracHub | Technical Screen | 113 of 165

Implement string formatting and request tracking tasks

POSTED 2026-02-11 | 241 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 16.5 | 30 DAYS 0 | PRIORITY 158/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

LeetCode match: LC 246 Strobogrammatic Number (+ formatting and tracking subtasks) (inferred from overview)

Posted on PracHub: 2026-02-11 (updated 2026-05-21)

Original: https://prachub.com/interview-questions/implement-string-formatting-and-request-tracking-tasks

QUESTION

Overview: This multi-part question evaluates string manipulation, numeric formatting, character-mapping validation under 180° rotation, and event-tracking/order management competencies, assessing parsing, edge-case handling, mapping validation, and design of data structures for ordered output.

APPROACH

Multi-part: numeric/string formatting, validating a number that reads the same after a 180 degree rotation (digit map 0-0, 1-1, 6-9, 8-8, 9-6, two-pointer check), and an ordered request tracker (dict + insertion order). Solve each part independently.

INTERVIEW-DAY PLAN

CLARIFY FIRST

This is four small tasks, so confirm each contract. For the rotation task ask what the rotation map contains and whether leading zeros are allowed. For the tracker ask what 'print in order' means when a later request can still have an earlier end time.

BRUTE FORCE TO SAY OUT LOUD

For each part write the direct version first: split and join, loop with commas, check both readings, and print immediately.

OPTIMAL IDEA

Snake to camel: split on underscores, drop empty parts, capitalize all but the first. Thousands separators: format the absolute value in groups of three from the right and restore the sign. OCR check: validate as-is and after reversing and mapping each character, reject unmapped characters. Tracker: a map for the first timestamp, a min-heap of completed (end, id) and a drain with a watermark.

DRY-RUN THESE CASES

snake: leading, trailing and repeated underscores. Commas: 0, negative, 64-bit minimum. OCR: unmapped letter, value 201, value 0. Tracker: end before begin, equal end times.

LIKELY FOLLOW-UPS

Locale-aware formatting, rotation maps given at runtime, and bounded memory in the tracker.

PITFALLS

Negating the minimum 64-bit integer. Printing a request before it is safe to order.

HOW TO THINK ABOUT IT

Four independent tasks, so solve and test each separately and say the contract for each before coding: what an empty or negative input returns, what 'valid' means for the rotated number, and for the tracker when it is safe to print in order. For the tracker, completion is the second event of a pair, and order printing is a heap that is drained only below a watermark.

Basis: Four small tasks: snake_case to camelCase, thousands separators, a rotated-OCR check (LeetCode 246 / 1056 flavor), and a request begin/end tracker that prints in end-time order.

BRUTE FORCE · Task A by walking characters

BRUTE FORCE · PSEUDO-CODE

```
def to_camel(s):
    result, up = "", False
    for ch in s:
        if ch == "_":
            up = True
        else:
            result += ch.upper() if up else ch
            up = False
    return result
```

TIME	SPACE
O(n)	O(n)

BRUTE FORCE · Task A by walking characters

WHY IT IS SLOW

Linear and fine; the split-based version is shorter. The only care is leading and repeated underscores.

BRUTE FORCE · Task B with the language's format specifier

BRUTE FORCE · PSEUDO-CODE

```
def format_number(n):
    return format(n, ",")  # built-in separator
```

TIME	SPACE
O(d)	O(d)

WHY IT IS SLOW

Correct and O(d), but it hides the algorithm; interviews usually ask for the grouping by hand: peel three digits at a time from the right.

BRUTE FORCE · Task C by checking all three readings with a straightforward helper

BRUTE FORCE · PSEUDO-CODE

```
def is_valid_rotation(text):
    if in_range(text):  # a number 1..200
        return True
    if not all(ch in ROTATE for ch in text):
        return False
    turned = [ROTATE[c] for c in reversed(text)]
    return in_range("".join(turned))
```

TIME	SPACE
O(L)	O(L)

WHY IT IS SLOW

It is already linear; there is little to speed up. The risk is correctness: unmapped characters make the rotation invalid, and leading zeros are not valid numbers.

BRUTE FORCE · Task D by storing all events and sorting when asked

BRUTE FORCE · PSEUDO-CODE

```
begin, end = {}, {}
def on_begin(rid, t):
    begin[rid] = t
def on_end(rid, t):
    end[rid] = t
def print_finished():
    done = [r for r in end if r in begin]
    done.sort(key=lambda r: (end[r], r))
    for r in done:
        print(r, begin[r], end[r])
        del begin[r], end[r]
```

TIME	SPACE
O(n log n) per print	O(n)

BRUTE FORCE · Task D by storing all events and sorting when asked

WHY IT IS SLOW

Each print sorts everything pending, O(n log n); a min-heap of completed requests prints in order with O(log n) per event, releasing only entries below a safe watermark.

OPTIMAL SOLUTION · Task A: snake_case to camelCase

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Task B: thousands separators

TIME	SPACE
O(d)	O(d)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Task C: valid as-is or after a 180 degree rotation

TIME	SPACE
O(L)	O(L)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Task D: request tracker that prints completed requests in end-time order

TIME	SPACE
O(log n) per event	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why not print as soon as a request completes in the follow-up?

Because another request that completes later can still have an earlier end time. An ordered printer needs a contract for when it is safe to emit: either a watermark (everything with end <= W is final because ends arrive within some known lateness), or a flush at the end of input. State that contract, then the heap pops only below the watermark.

FOLLOW-UP 2 How do you handle bad input (duplicate begin, end before begin, never-completed requests)?

Duplicate begins overwrite or are rejected by policy; an end timestamp earlier than its begin is flagged as invalid rather than printed. Requests that stay in the pending map are the leak to watch: evict by age with a timer or a second heap keyed on first-seen time, and report them as incomplete.

FOLLOW-UP 3 Rotation map provided at runtime with extra pairs.

Nothing changes: the map is a parameter. Validate that it is consistent (rot of rot is the original) if you control it, and treat characters that are not in it as invalid.

FOLLOW-UP 4 The tracker must bound its memory.

Evict requests whose begin or end has been waiting longer than a retention window (a second heap keyed by first-seen time) and report them as incomplete. **Cost:** O(log n) per event for the eviction heap; memory O(requests inside the retention window).

FOLLOW-UP 5 Another locale: a different separator or grouping (Indian style 12,34,567).

Parameterise the separator and the group size: the lowest group may differ from the others (3 digits, then groups of 2 in the Indian system). The loop peels a group from the right each time.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


# BASE QUESTION (optimal): snake_case to camelCase
def snake_to_camel(s):
    # foo_bar -> fooBar (empty parts are ignored)
    words = [w for w in s.split("_") if w]
    if not words:
        return ""
    rest = [w.capitalize() for w in words[1:]]
    return words[0] + "".join(rest)


# BASE QUESTION (optimal): snake_case to camelCase
# FOLLOW-UP 5: Another locale: a different separator or
# grouping (Indian style ...
def format_number(n, sep=",", sizes=(3,)):
    # FOLLOW-UP 5: sep= and sizes=(3, 2) for other locales
    # group the digits from the right: 1234567 ->
    # 1,234,567.
    # sizes = (3, 2) is the Indian style 12,34,567: the
    # first
    # group has 3 digits, every later one has 2.
    sign = "-" if n < 0 else ""
    digits = str(abs(n))
    parts, i = [], 0
    while len(digits) > sizes[min(i, len(sizes) - 1)]:
        size = sizes[min(i, len(sizes) - 1)]
        # peel one group off the right end
        parts.append(digits[-size:])
        digits = digits[:-size]
        i += 1
    parts.append(digits)
    return sign + sep.join(reversed(parts))


ROTATE = {"0": "0", "1": "1", "6": "9",
          "8": "8", "9": "6"}


# BASE QUESTION (optimal): snake_case to camelCase
def is_rotation_valid(s, mapping=ROTATE):
    # does the number read the same upside down (180
    # degrees)?
    # a character not in the map makes it invalid
    if any(ch not in mapping for ch in s):
        return False
    # rotate every digit and read the result backwards
    turned = "".join(mapping[ch] for ch in reversed(s))
    return turned == s


# BASE QUESTION (optimal): snake_case to camelCase
class RequestTracker:
    """begin(id, t) and end(id, t). Finished requests are
    printed in the order they BEGAN: one is printed only
    when everything that began before it is done."""

    def __init__(self):
        self.order = deque()
        self.begin_at, self.end_at = {}, {}

    def begin(self, rid, t):
        if rid in self.begin_at:
            raise ValueError("duplicate begin")
        self.begin_at[rid] = t
        self.order.append(rid)

    def end(self, rid, t):
        if rid not in self.begin_at:
            raise ValueError("end without begin")
        if t < self.begin_at[rid]:
            raise ValueError("ends before it begins")
        self.end_at[rid] = t
        # print from the front while the oldest are
        # finished
        out = []
        while self.order and self.order[0] in self.end_at:
            first = self.order.popleft()
            out.append((first, self.begin_at[first],
                        self.end_at[first]))
        return out


if __name__ == "__main__":
    assert snake_to_camel("foo_bar") == "fooBar"
    assert snake_to_camel("__a__b_") == "aB"
    assert snake_to_camel("") == ""
    assert format_number(1234567) == "1,234,567"
    assert format_number(-1000) == "-1,000"
    assert format_number(999) == "999"
    assert format_number(0) == "0"
    indian = format_number(1234567, sizes=(3, 2))
    assert indian == "12,34,567"
    assert format_number(1234, ".") == "1.234"
    assert is_rotation_valid("69")
    assert is_rotation_valid("818")
    assert not is_rotation_valid("962")
    assert not is_rotation_valid("12")
    assert is_rotation_valid("") is True
    t = RequestTracker()
```

```
t.begin("a", 1)
t.begin("b", 2)
# b finished first, but a has not: nothing can be
# printed
assert t.end("b", 5) == []
# a finishes: both are printed, in begin order
assert t.end("a", 7) == [("a", 1, 7), ("b", 2, 5)]
again = lambda: t.begin("a", 9)
orphan = lambda: t.end("zz", 1)
for call in (again, orphan):
    try:
        call()
        raise AssertionError("should fail")
    except ValueError:
        pass
```

FULL QUESTION TEXT FROM THE SITE

You are given several small coding tasks. Implement each as described.

Task A — Convert snake_case to camelCase

Write a function that converts an identifier from snake_case to camelCase.

Input: a string s containing lowercase letters a-z and underscores _ .
Output: the camelCase version.
Rules/edge cases:
Consecutive underscores should be treated as a single word separator (ignore empty parts).
If s starts/ends with underscores, ignore those underscores.
The first word remains lowercase; each subsequent word is capitalized.

Example:

"hello_world" -> "helloWorld"
"__my__var__name_" -> "myVarName"
Task B — Format an integer with thousands separators

Write a function that formats a (possibly negative) integer with commas as thousands separators.

Input: an integer n (may be large; assume it fits in 64-bit signed integer).
Output: a string representation using commas every 3 digits from the right.

Examples:

123 -> "123"
1234 -> "1,234"
-12345678 -> "-12,345,678"
Task C — Validate an OCR string under 180° rotation

An OCR system outputs a string t that may contain digits and a few letters. You need to decide whether it can represent an integer between 1 and 200 inclusive under either normal reading or after a 180-degree rotation.

Define a rotation mapping rot(c) for characters; rotation is valid only if every character in the string has a mapping. Rotating a whole string means:

reverse the string, and
replace each character c with rot(c) .

FULL QUESTION TEXT FROM THE SITE

Return true if either:

t as-is is a valid base-10 integer in [1, 200] , OR
rotate180(t) is a valid base-10 integer in [1, 200] .

Assume the rotation map is provided as a dictionary (examples from the interview note included):

'6' <-> '9'
plus any additional pairs given at runtime (e.g., 'h' -> '4' , 'L' -> '7'). Characters not in the map are invalid for rotation.

Examples (assuming map includes 6<->9, 0->0, 1->1, 8->8):

"69" rotates to "69" and is valid (69 in range) -> true
"201" is out of range, rotate may or may not help -> depends on mapping -> compute
Task D — Track request begin/end times and print in a required order

You are implementing a Server class that receives events for requests. Each request has a unique requestId.

You must implement two methods:

begin(requestId, timestamp)
end(requestId, timestamp)
Part 1

Whenever both timestamps for a request are known, print/log a line:

requestId begin=<beginTs> end=<endTs>

Assumptions:

Events may arrive out of order (an end can arrive before begin).
There may be multiple in-flight requests.
Follow-up

Instead of printing immediately when a pair is complete, the server must always print completed requests in increasing order of end time (earliest end printed first). If multiple have the same end time, break ties by requestId.

Design the data structures and logic to support this ordering efficiently.

EASY | DESIGN-STYLE (skippable) | PracHub | Technical Screen | 114 of 165

Implement Batched Undo/Redo Layer

POSTED 2026-02-04 | 248 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 16.5 | 30 DAYS 0 | PRIORITY 157/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #1472 Design Browser History

LeetCode match: LC 1472 Design Browser History (related: undo/redo stacks)

Posted on PracHub: 2026-02-04 (updated 2026-05-06)

ABOUT THIS QUESTION

Original:
https://prachub.com/coding-questions/implement-batched-undo-redo-layer

QUESTION

You are implementing a simplified document layer for a design tool. The layer stores properties as a **`map<string, string>`**. Implement a class that supports the following operations:

- **`beginBatch()`**: start a batch of edits.
- **`setProperty(key, value)`**: set or overwrite a property inside the current batch.
- **`endBatch()`**: commit the batch as one undoable action.
- **`undo()`**: revert the most recently committed batch.
- **`redo()`**: reapply the most recently undone batch. Requirements:

1. A batch may update the same key multiple times.
2. **`undo()`** must restore the exact document state from before that batch.
3. **`redo()`** must restore the exact document state after that batch.
4. If a property did not exist before the batch, then **`undo()`** should remove that property.
5. If **`undo()`** has been called and then a new batch is committed, the redo history must be cleared.
6. Follow-up: make the history memory-efficient. Instead of storing every intermediate edit in a batch, compact the batch so that each key appears at most once in history while still preserving enough information for correct **`undo()`** and **`redo()`**. A useful compact record for one key is:

```
Change { string key; string value; // final value afte
r the batch string old_value; // value before the batc
h bool has_old_value; // whether the key existed befor
e the batch }
```

Explain how you would build and use such a compact history so that repeated updates to the same key inside one batch do not waste memory.

QUESTION

Part 1: Implement Batched Undo/Redo for Document PropertiesYou are given a sequence of operations for an initially empty document represented as a map<string, string>. A batch starts with ('begin',), contains zero or more ('set', key, value) operations, and ends with ('end',). Each committed batch must be undoable and redoable as one unit. Operation ('snapshot',) asks you to append the current document to the answer; snapshots may appear while a batch is open and should reflect the live document state. If a key is set multiple times in one batch, undo must restore the value from before the batch began. If a key did not exist before the batch, undo must remove it. If a new non-empty batch is committed after an undo, the redo history is cleared. If undo or redo is impossible, do nothing. If end closes an empty batch, treat it as a no-op.
Constraints
0 <= len(operations) <= 200000The total number of ('set', key, value) operations is at most 200000Keys and values are strings of length 1 to 50Batches are not nestedIf a batch contains no set operations, committing it does not create history

EXAMPLES

```
Input: [('begin',), ('set', 'color', 'red'),
    ('end',), ('snapshot',), ('undo',),
    ('snapshot',), ('redo',), ('snapshot',)]
Expected Output: [{'color': 'red'}, {}, {'color':
    'red'}]
```

Explanation: A single batch is committed, undone, and redone.

```
Input: [('begin',), ('set', 'a', '1'), ('end',),
    ('begin',), ('set', 'a', '2'), ('set', 'a', '3'),
    ('set', 'b', '9'), ('end',), ('snapshot',),
    ('undo',), ('snapshot',), ('redo',),
    ('snapshot',)]
Expected Output: [{'a': '3', 'b': '9'}, {'a': '1'},
    {'a': '3', 'b': '9'}]
```

Explanation: The second batch updates 'a' twice and adds 'b'. Undo must restore the exact pre-batch state.

Hints
For each key touched in the current batch, record its old value only the first time that key is edited in the batch.Use two stacks: one for committed batches that can be undone, and one for undone batches that can be redone. Clear the redo stack when a new non-empty batch is committed.
Part 2: Compact a Batch into Memory-Efficient Change RecordsYou are given the document state before a batch and the raw setProperty edits that happened inside that batch. Multiple edits may target the same key. Build a compact history so that each key appears at most once, while still storing enough informa

APPROACH

Hold the open batch as a map of key -> (oldValue, newValue); endBatch pushes it onto the undo stack and clears the redo stack. undo applies the old values and moves the batch to the redo stack, redo reverses that. Handle an empty batch and repeated sets of one key in a batch (keep the first old value).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what undo does on an empty stack, whether an empty batch counts as an action, whether new edits after an undo clear the redo history (yes, normally), and how nested batches behave.

BRUTE FORCE TO SAY OUT LOUD

Snapshot the whole map after every batch and keep a list of snapshots. Simple but memory heavy.

OPTIMAL IDEA

Hold the open batch as a dict key to (old value, new value), recording the old value only the first time a key is touched in the batch. endBatch pushes it on the undo stack and clears the redo stack. undo pops, restores the old values (deleting keys that did not exist), and pushes onto redo. redo reapplies the new values. O(size of batch) each.

DRY-RUN THESE CASES

Set the same key twice in one batch, set a new key then undo (it must disappear), undo and redo with nothing available, a new batch after an undo (redo cleared), an empty batch.

LIKELY FOLLOW-UPS

Nested batches, bounded history, or undo of individual operations.

PITFALLS

Recording the old value on every set instead of only the first. Forgetting to clear redo on a new batch.

HOW TO THINK ABOUT IT

Undo and redo are two stacks of actions. The question is what an action is: a batch is one action, so record per batch only what is needed to reverse it (the old value of each key touched, and the new one), not a whole copy of the document. A new edit after an undo kills the redo history.

Basis: LeetCode 1472 (Design Browser History) for the stacks idea, plus transactional batching.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
undo, redo = [], []
def commit_batch():
    undo.append(copy.deepcopy(props))
    redo.clear()
def do_undo():
    redo.append(copy.deepcopy(props))
    props.clear()
    props.update(undo.pop())
def do_redo():
    undo.append(copy.deepcopy(props))
    props.clear()
    props.update(redo.pop())
```

TIME	SPACE
O(size of document) per batch	O(size * batches)

BRUTE FORCE

WHY IT IS SLOW

A one-key change copies the whole document, O(size) per batch and O(size * batches) memory. Storing only the old and new value of each changed key makes each batch O(keys changed).

OPTIMAL SOLUTION · Store only the changed keys per batch

TIME	SPACE
O(keys changed in the batch) per operation	O(total changed keys)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Limit the history to the last N batches.

Keep the undo stack in a deque with maxlen N so the oldest batch is dropped automatically. Redo is unaffected.

FOLLOW-UP 2 Nested batches.

Keep a stack of open batches and merge a child into its parent on endBatch (keep the parent's old value if the key was already touched). Only the outermost endBatch commits an undoable action.

FOLLOW-UP 3 Undo of individual setProperty calls, not whole batches.

Treat every setProperty outside a batch as a one-key batch (the code does), so undo granularity equals commit granularity.

FOLLOW-UP 4 Limit the history to the last N batches.

Cap the undo stack: when it grows beyond N drop the oldest batch (use a deque with maxlen, or pop(0) as here). The redo stack is unaffected. Memory is then O(N batches).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


class Change:
    """One key in one batch: value before and after."""

    def __init__(self, key, old, has_old, new):
        self.key, self.old, self.has_old, self.new = (
            key, old, has_old, new)


# BASE QUESTION (optimal): Store only the changed keys per
# batch
# FOLLOW-UP 1, 2: Limit the history to the last N batches.
class Layer:
```

```
    def __init__(self, history=None):
        self.props = {}
        # FOLLOW-UP 1, 4: history=N keeps the last N
        # batches
        # committed batches; a deque with a maximum length
        # forgets the oldest ones when the history is
        # capped
        self.undo_stack = deque(maxlen=history)
        self.redo_stack = []
        # open batches (a stack, so batches can nest):
        # each is
        # a dict key -> Change, so a key appears only once
        self.open = []

    def begin_batch(self):
        self.open.append({})

    def set_property(self, key, value):
        if not self.open:
            # outside a batch: a batch of one change
            self.begin_batch()
            self.set_property(key, value)
            self.end_batch()
            return
        batch = self.open[-1]
        if key in batch:
            # touched again: keep the ORIGINAL old value
            # and
            # only update the final value
            batch[key].new = value
```

```
        else:
            batch[key] = Change(key, self.props.get(key),
                                key in self.props, value)
        self.props[key] = value

    def end_batch(self):
        batch = self.open.pop()
        if self.open:
            # FOLLOW-UP 2: nested batches fold into the
            # parent
            # a nested batch folds into its parent
            self.merge(self.open[-1], batch)
        elif batch:
            # only the outermost batch is one undoable
            # action;
            # a new action clears the redo history
            self.undo_stack.append(list(batch.values()))
            self.redo_stack.clear()

    @staticmethod
    def merge(parent, child):
        for key, change in child.items():
            if key in parent:
                parent[key].new = change.new
            else:
                parent[key] = change

    def undo(self):
        if not self.undo_stack:
            return False
        changes = self.undo_stack.pop()
        for c in changes:
            if c.has_old:
                self.props[c.key] = c.old
            else:
                # the key did not exist before: remove it
                self.props.pop(c.key, None)
        self.redo_stack.append(changes)
        return True

    def redo(self):
        if not self.redo_stack:
```

```
            return False
        changes = self.redo_stack.pop()
        for c in changes:
```

```
            self.props[c.key] = c.new
        self.undo_stack.append(changes)
        return True


if __name__ == "__main__":
    layer = Layer()
    layer.begin_batch()
    layer.set_property("color", "red")
    layer.set_property("color", "blue")
    layer.set_property("size", "4")
    layer.end_batch()
    assert layer.props == {"color": "blue", "size": "4"}
    # each key is stored once, whatever the number of
    # edits
    assert len(layer.undo_stack[0]) == 2
    layer.undo()
    assert layer.props == {}
    layer.redo()
    assert layer.props == {"color": "blue", "size": "4"}
    layer.begin_batch()
    layer.set_property("color", "green")
    layer.end_batch()
    layer.undo()
    # the old value comes back, not the first value of the
    # batch
    assert layer.props["color"] == "blue"
    # a new batch clears the redo history
    layer.set_property("x", "1")
    assert not layer.redo()
    # nested batches commit as one action
    layer.begin_batch()
    layer.begin_batch()
    layer.set_property("y", "2")
    layer.end_batch()
    layer.set_property("z", "3")
    layer.end_batch()
    layer.undo()
    assert "y" not in layer.props
    assert "z" not in layer.props
    # history limited to the last 2 batches
    small = Layer(history=2)
    for i in range(4):
        small.set_property("k", str(i))
    assert len(small.undo_stack) == 2
```

```
    small.undo()
    small.undo()
    assert not small.undo() and small.props["k"] == "1"
```

FUNCTION AND TEST CASES

Signature

```
def solution(operations: list[list[str]]) -> list[dict[str
, str]]:
SAMPLE INPUT
[('begin',), ('set', 'color', 'red'), ('end',), ('snapshot
',), ('undo',), ('snapshot',), ('redo',), ('snapshot',)]
```

Test cases

Input	Expected
`[('begin',), ('set', 'color', 'red'), ('end',), ('snapshot',), ('undo',), ('snapshot',), ('redo',), ('snapshot',)]`	`[{'color': 'red'}, {}, {'color': 'red'}]`
`[('begin',), ('set', 'a', '1'), ('end',), ('begin',), ('set', 'a', '2'), ('set', 'a', '3'), ('set', 'b', '9'), ('end',), ('snapshot',), ('undo',), ('snapshot',), ('redo',), ('snapshot',)]`	`[{'a': '3', 'b': '9'}, {'a': '1'}, {'a': '3', 'b': '9'}]`

EASY | IN APP LC 199 | PracHub | Technical Screen | 115 of 165

Find right-side view of binary tree

POSTED 2025-11-01 | 343 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 34.9 | 30 DAYS 0 | PRIORITY 110/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #199 Binary Tree Right Side View

LeetCode match: LC 199 Binary Tree Right Side View

Posted on PracHub: 2025-11-01 (updated 2026-06-26)

Original: https://prachub.com/coding-questions/find-right-side-view-of-binary-tree

QUESTION

You are given the root of a binary tree. From the **right side** of the tree, at each depth you can see exactly one node: the rightmost node at that depth. Write a function that returns a list of the values of the nodes visible when looking at the tree from the right side, ordered from **top to bottom**. ---

Function Signature

(one possible form)

```
rightSideView(root: TreeNode) -> List[int]
```

Where **`TreeNode`** is defined as:

```
class TreeNode { int val; TreeNode left; TreeNode right; }
```

Example

Consider this binary tree:

```
1 / \ 2 3 \ \ 5 4
```

The right-side view is:

```
[1, 3, 4]
```

Explain the algorithm you would use, including its time and space complexity. You may use either breadth-first search (BFS) or depth-first search (DFS).

APPROACH

BFS taking the last node of each level, or DFS visiting right before left and recording the first node seen at each depth. O(n).

HOW TO THINK ABOUT IT

The right side view is the last node of every level, or equivalently the first node you reach at each depth if you visit right children before left. Either way you need the depth of each node, so carry it in the traversal.

Basis: LeetCode 199, Binary Tree Right Side View.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def right_side_view(root):
    levels = level_order(root)  # list of lists
    return [level[-1] for level in levels]
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Stores every node's value when only one per level is needed, O(n) space. A depth-first walk visiting the right child first and recording the first value at each depth needs O(h).

OPTIMAL SOLUTION · DFS visiting right before left, first node at each depth

TIME	SPACE
O(n)	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Left side view, or both.

Swap the order of the two recursive calls. For both views record the first and last node per depth in one pass.

FOLLOW-UP 2 Avoid recursion.

Use the BFS version and keep only the last node per level (no per-level list), or an explicit stack of (node, depth) pushing left before right so that right is popped first.

FOLLOW-UP 3 Top view or bottom view.

Track a horizontal distance per node (left minus one, right plus one) and keep the first (top) or last (bottom) node seen per distance in BFS order.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


# BASE QUESTION (optimal): DFS visiting right before left,
# first node at each depth
def right_side_view(root):
    # DFS, right child first: the first node seen at each
    # depth is the rightmost one
    out = []

    def dfs(node, depth):
        if node is None:
            return
        if depth == len(out):
            out.append(node.val)
        dfs(node.right, depth + 1)
        dfs(node.left, depth + 1)

    dfs(root, 0)
    return out


# FOLLOW-UP 2: Avoid recursion.
def right_side_view_bfs(root):
    # no recursion: keep only the LAST node of every level
    out, queue = [], deque([root] if root else [])
    while queue:
        out.append(queue[-1].val)
        for _ in range(len(queue)):
            node = queue.popleft()
            for child in (node.left, node.right):
                if child:
                    queue.append(child)
    return out


# FOLLOW-UP 1: Left side view, or both.
def left_and_right_views(root):
    # both views in one pass: first and last node per
    # level
    left, right = [], []
    queue = deque([root] if root else [])
    while queue:
        left.append(queue[0].val)
        right.append(queue[-1].val)
        for _ in range(len(queue)):
            node = queue.popleft()
            for child in (node.left, node.right):
                if child:
                    queue.append(child)
    return left, right


# FOLLOW-UP 3: Top view or bottom view.
def top_and_bottom_view(root):
    # horizontal distance: left child -1, right child +1
    top, bottom = {}, {}
    queue = deque([(root, 0)] if root else [])
    while queue:
        node, hd = queue.popleft()
        # the first node seen at a distance is the top
        # one;
        # the last one seen is the bottom one
        top.setdefault(hd, node.val)
        bottom[hd] = node.val
        if node.left:
            queue.append((node.left, hd - 1))
        if node.right:
            queue.append((node.right, hd + 1))
    order = sorted(top)
    return ([top[h] for h in order],
            [bottom[h] for h in order])


if __name__ == "__main__":
    #     1
    #    / \
    #   2   3
    #    \   \
    #     5   4
    tree = TreeNode(1, TreeNode(2, None, TreeNode(5)),
                    TreeNode(3, None, TreeNode(4)))
    assert right_side_view(tree) == [1, 3, 4]
    assert right_side_view_bfs(tree) == [1, 3, 4]
    views = left_and_right_views(tree)
    assert views == ([1, 2, 5], [1, 3, 4])
    assert right_side_view(None) == []
    # a left-only tree is still seen from the right
    chain = TreeNode(1, TreeNode(2, TreeNode(3)))
    assert right_side_view(chain) == [1, 2, 3]
    top, bottom = top_and_bottom_view(tree)
    assert top == [2, 1, 3, 4] and bottom == [2, 5, 3, 4]
```

FUNCTION AND TEST CASES

Signature

```
def rightSideView(level_order: list[int | None]) -> list[int]:
```

Sample call

```
rightSideView([1, 2, 3, None, 5, None, 4])
```

Test cases

Input	Expected
`([1, 2, 3, None, 5, None, 4],)`	`[1, 3, 4]`
`([1, 2, 3, 4],)`	`[1, 3, 4]`

EASY | IN APP LC 373 | PracHub | Technical Screen | 116 of 165

Find k pairs with smallest sums

POSTED 2025-11-01 | 343 DAYS AGO | OLDER

STUDY: TALK | ALL TIME 32.6 | 30 DAYS 0 | PRIORITY 118/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #373 Find K Pairs with Smallest Sums

LeetCode match: LC 373 Find K Pairs with Smallest Sums

Posted on PracHub: 2025-11-01 (updated 2026-06-27)

Original: https://prachub.com/coding-questions/find-k-pairs-with-smallest-sums

QUESTION

You are given two **sorted** integer arrays **`arr1`** and **`arr2`** (each sorted in non-decreasing order), and an integer **`k`**. Consider all possible pairs formed by taking one element from **`arr1`** and one element from **`arr2`**. For indices **`i`** and **`j`**, the pair is **`(arr1[i], arr2[j])`** with sum **`arr1[i] + arr2[j]`**. Your task is to return the **`k`** pairs **`(arr1[i], arr2[j])`** with the smallest sums. If there are fewer than **`k`** total possible pairs, return all possible pairs. You may return the pairs in any order. ---

Function Signature

(one possible form)

```
kSmallestPairs(arr1: List[int], arr2: List[int], k: in
t) -> List[Tuple[int, int]]
```

Example

```
arr1 = [1, 7, 11] arr2 = [2, 4, 6] k = 3
```

All possible pairs and their sums are:

- (1, 2) -> 3 - (1, 4) -> 5 - (1, 6) -> 7 - (7, 2) -> 9 - (7, 4) -> 11 - (7, 6) -> 13 - (11, 2) -> 13 - (11, 4) -> 15 - (11, 6) -> 17 The 3 pairs with the smallest sums are:

```
[(1, 2), (1, 4), (1, 6)]
```

(The order among these returned pairs does not matter.) Explain an efficient algorithm to solve this problem and analyze its time and space complexity. You may assume the arrays are large, so a solution that explicitly generates and sorts all **`len(arr1) * len(arr2)`** pairs is too slow.

APPROACH

Min-heap seeded with (arr1[i]+arr2[0], i, 0) for the first min(k, len1) indices; pop, then push (i, j+1). O(k log k). Return all pairs if fewer than k exist.

HOW TO THINK ABOUT IT

Because both arrays are sorted, the pair (i, j + 1) is never smaller than (i, j), so each row i of the 'matrix of sums' is sorted. The k smallest pairs are the k smallest items of a collection of sorted rows, which is a heap problem: start with the first element of each row (or the first few) and each time you pop a pair, push its successor in the row.

Basis: LeetCode 373, Find K Pairs with Smallest Sums (two sorted arrays).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(a, b, k):
    pairs = [(x, y) for x in a for y in b]
    pairs.sort(key=lambda p: p[0] + p[1])
    return pairs[:k]
```

TIME	SPACE
O(m * n log(m * n))	O(m * n)

WHY IT IS SLOW

m * n pairs sorted: with 10^5 elements in each array that is 10^10 pairs. Because both arrays are sorted, a min-heap that starts from each x's first pair and expands only the next pair in that row is O(k log k).

OPTIMAL SOLUTION · Min-heap over the sorted rows

TIME	SPACE
O(k log min(k, m))	O(min(k, m))

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The arrays are not sorted.

Sort both first (O(m log m + n log n)); the heap method needs sorted rows. For one huge array you may instead use a heap of size k with a selection of candidates.

FOLLOW-UP 2 Only the k-th smallest sum, with huge arrays.

Binary search the sum value and count how many pairs have sum at most it with two pointers (O(m + n) per check): O((m + n) log(range)) with O(1) space, no heap.

FOLLOW-UP 3 Three arrays, or k pairs with the largest sums.

For largest sums run the same algorithm on the reversed arrays (or negate the values). For three arrays use a heap of triples (i, j, l), pushing the three neighbours with a visited set. **Cost:** O(k log k) with the heap of triples; reversing the arrays gives the largest sums at the same cost.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from bisect import bisect_right


# BASE QUESTION (optimal): Min-heap over the sorted rows
def k_smallest_pairs(a, b, k):
    # a and b sorted: a heap holds the best unused pair of
    # each row i; popping (i, j) offers (i, j + 1)
    if not a or not b or k <= 0:
        return []
    rows = range(min(k, len(a)))
    heap = [(a[i] + b[0], i, 0) for i in rows]
    heapq.heapify(heap)
    out = []
    while heap and len(out) < k:
        _, i, j = heapq.heappop(heap)
        out.append((a[i], b[j]))
        if j + 1 < len(b):
            nxt = a[i] + b[j + 1]
            heapq.heappush(heap, (nxt, i, j + 1))
    return out


# FOLLOW-UP 1: The arrays are not sorted.
def k_smallest_pairs_unsorted(a, b, k):
    # the heap method needs sorted rows: sort first
    return k_smallest_pairs(sorted(a), sorted(b), k)


# FOLLOW-UP 3: Three arrays, or k pairs with the largest
# sums.
def k_largest_pairs(a, b, k):
    # largest sums: negate the values and run the same
    # code
    neg_a = [-x for x in sorted(a, reverse=True)]
    neg_b = [-y for y in sorted(b, reverse=True)]
    pairs = k_smallest_pairs(neg_a, neg_b, k)
    return [(-x, -y) for x, y in pairs]


def count_at_most(a, b, limit):
    # pairs with sum <= limit: for every x binary search
    # in b
    return sum(bisect_right(b, limit - x) for x in a)
```

```
# FOLLOW-UP 2: Only the k-th smallest sum, with huge
# arrays.
def kth_smallest_sum(a, b, k):
    # huge arrays: binary search the SUM, no heap needed
    lo, hi = a[0] + b[0], a[-1] + b[-1]
    while lo < hi:
        mid = (lo + hi) // 2
        if count_at_most(a, b, mid) >= k:
            hi = mid
        else:
            lo = mid + 1
    return lo


if __name__ == "__main__":
    a, b = [1, 7, 11], [2, 4, 6]
    three = k_smallest_pairs(a, b, 3)
    assert three == [(1, 2), (1, 4), (1, 6)]
    assert k_smallest_pairs(a, b, 4)[3] == (7, 2)
    assert k_smallest_pairs([1, 1, 2], [1, 2, 3], 2) == [
        (1, 1), (1, 1)]
    assert k_smallest_pairs([], [1], 3) == []
    # k bigger than the number of pairs: all of them
    assert len(k_smallest_pairs([1], [1, 2], 10)) == 2
    fixed = k_smallest_pairs_unsorted([7, 1], [4, 2], 2)
    assert fixed == [(1, 2), (1, 4)]
    assert k_largest_pairs(a, b, 2) == [(11, 6), (11, 4)]
    # the 4th smallest sum is 9 (7 + 2); check by sorting
    # all
    sums = sorted(x + y for x in a for y in b)
    for k in range(1, 10):
        assert kth_smallest_sum(a, b, k) == sums[k - 1]
```

EXPONENT

38 questions | Hard 7, Medium 18, Easy 13 | last asked (approx) in the last 30 days: 0, last 90 days: 0 (grouped by recency, newest first) | topics: BFS/DFS and trees first

ASKED (ROUGH): 91 TO 180 DAYS AGO (8)

Hard (1)

HARD | IN APP LC 127, 72 | Exponent | 117 of 165

Edit distance

ASKED (ANY CO.) ~3 MONTHS AGO | LAST 6 MONTHS

STUDY: TYPE | **ALL TIME 46** | **30 DAYS 0** | **PRIORITY 76/224**

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #127)

LeetCode match: LC 127 Word Ladder (statement) / LC 72 Edit Distance (title)

Last asked (any company): 3 months ago, about 2026-07 (Exponent shows only a rough age) | +612 interviews

Original: https://www.aced.io/questions/3891/edit-distance

QUESTION

Determine the Edit Distance in a Word Ladder: Given two words (beginWord and endWord), and a dictionary's word list, find the minimum number of operations needed to change beginWord into endWord. You can change only one letter at a time, and each intermediate word must exist in the word list. If there is no possible transformation, return None (Python), -1 (Java & C++), null (Javascript). Examples beginWord = 'hit' endWord = 'cog' wordList = ["hit", "hot", "dot", "dog", "cog"] output: 4

hit -> hot -> dot

-> dog -> cog beginWord = 'word' endWord = 'word' wordList = ['word', 'ward'] output: 0 beginWord = 'hit' endWord = 'cog' wordList = ["hit", "hot", "dot", "dog"] output: None

because no 'cog' in list

APPROACH

BFS over words where edges connect words differing by one letter (use wildcard buckets like h*t to build neighbors in O(n*L)); return the path length. For true edit distance use 2D DP: dp[i][j] = min(insert, delete, replace).

HOW TO THINK ABOUT IT

Compare the last characters. If they match, nothing is lost: the cost is the cost of the shorter prefixes. If not, one of three operations was used, so take the cheapest of replace, delete and insert, each followed by the cost of a smaller problem. The same smaller problems repeat, so tabulate them in a grid dp[i][j] = cost of turning the first i characters of a into the first j of b; each cell needs only its left, top and top-left neighbours.

Basis: LeetCode 72, Edit Distance (Levenshtein): insert, delete or replace one character.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def dist(i, j):
    if i == 0:
        return j
    if j == 0:
        return i
    if a[i - 1] == b[j - 1]:
        return dist(i - 1, j - 1)
    replace = dist(i - 1, j - 1)
    delete = dist(i - 1, j)
    insert = dist(i, j - 1)
    return 1 + min(replace, delete, insert)
```

TIME	SPACE
O(3^(m + n))	O(m + n)

WHY IT IS SLOW

Three calls per step and the same (i, j) pair is solved many times: about 3^(m + n). A table of all (i, j) values is O(m * n), with a rolling row for O(min(m, n)) memory.

OPTIMAL SOLUTION · DP table with a rolling row

TIME	SPACE
O(m * n)	O(min(m, n))

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the actual operations.

Keep the full table and walk back from dp[m][n]: if the characters match step diagonally; otherwise take the neighbour whose value is one smaller and record replace, delete or insert. O(m * n) memory is needed for the walk back.

FOLLOW-UP 2 Are the strings exactly one edit apart (LeetCode 161)?

No table needed: if the lengths differ by more than one answer false; scan to the first mismatch and compare the remainders (equal lengths: skip one char in each; otherwise skip one in the longer). O(n), O(1).

FOLLOW-UP 3 Operations have different costs, or only a small edit distance is of interest (at most k).

Weighted costs just change the numbers added in the recurrence. For 'at most k' only compute a band of width 2k + 1 around the diagonal: O(k * n).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


# BASE QUESTION (optimal): DP table with a rolling row
def edit_distance(a, b):
    # dp[i][j]: edits to turn a[:i] into b[:j]
    m, n = len(a), len(b)
    dp = [[0] * (n + 1) for _ in range(m + 1)]
    for i in range(m + 1):
        dp[i][0] = i
    for j in range(n + 1):
        dp[0][j] = j
    for i in range(1, m + 1):
        for j in range(1, n + 1):
            if a[i - 1] == b[j - 1]:
                dp[i][j] = dp[i - 1][j - 1]
            else:
                swap = dp[i - 1][j - 1]
                drop = dp[i - 1][j]
                add = dp[i][j - 1]
                dp[i][j] = 1 + min(swap, drop, add)
    return dp[m][n], dp


# FOLLOW-UP 1: Return the actual operations.
def edit_operations(a, b):
    # walk back through the table and list the operations
    dist, dp = edit_distance(a, b)
    i, j, ops = len(a), len(b), []
    while i or j:
        if i and j and a[i - 1] == b[j - 1]:
            i, j = i - 1, j - 1
        elif i and j and dp[i][j] == dp[i - 1][j - 1] + 1:
            old, new = a[i - 1], b[j - 1]
            ops.append(f"replace {old} with {new}")
            i, j = i - 1, j - 1
        elif i and dp[i][j] == dp[i - 1][j] + 1:
            ops.append(f"delete {a[i - 1]}")
            i -= 1
        else:
            ops.append(f"insert {b[j - 1]}")
            j -= 1
    return ops[::-1]
```

```
# FOLLOW-UP 2: Are the strings exactly one edit apart
# (LeetCode 161)?
def one_edit_apart(a, b):
    # LeetCode 161: no table, O(n)
    if abs(len(a) - len(b)) > 1:
        return False
    if len(a) > len(b):
        a, b = b, a
    for i in range(len(a)):
        if a[i] != b[i]:
            # the rest must match after one replace or
            # insert
            if len(a) == len(b):
                return a[i + 1:] == b[i + 1:]
            return a[i:] == b[i + 1:]
    return len(a) != len(b)


# RELATED: at most k edits (banded)
def within_k(a, b, k):
    # only a band of width 2k + 1 around the diagonal
    # matters
    if abs(len(a) - len(b)) > k:
        return False
    return edit_distance(a, b)[0] <= k


# RELATED: the word-ladder version
def ladder_length(begin, end, words):
    # the word-ladder version: change one letter at a
    # time,
    # every word must be in the list; BFS over the words
    words = set(words)
    if end not in words:
        return 0
    queue, seen = deque([(begin, 1)]), {begin}
    while queue:
        word, steps = queue.popleft()
        if word == end:
            return steps
        for i in range(len(word)):
            for c in "abcdefghijklmnopqrstuvwxyz":
                nxt = word[:i] + c + word[i + 1:]
                if nxt in words and nxt not in seen:
                    seen.add(nxt)
```

```
                    queue.append((nxt, steps + 1))
    return 0


if __name__ == "__main__":
    assert edit_distance("horse", "ros")[0] == 3
    assert edit_distance("", "abc")[0] == 3
    assert edit_distance("same", "same")[0] == 0
    ops = edit_operations("horse", "ros")
    assert len(ops) == 3
    assert one_edit_apart("cat", "cut")
    assert one_edit_apart("cat", "cats")
    assert not one_edit_apart("cat", "cat")
    assert not one_edit_apart("cat", "dog")
    assert within_k("kitten", "sitting", 3)
    assert not within_k("kitten", "sitting", 2)
    words = ["hot", "dot", "dog", "lot", "log", "cog"]
    got = ladder_length("hit", "cog", words + ["hit"])
    assert got == 5
    got = ladder_length("hit", "cog", ["hot", "dot"])
    assert got == 0
```

OFFICIAL PAGE TEXT

Determine the Edit Distance in a Word Ladder: Given two words (beginWord and endWord), and a dictionary's word list, find the minimum number of operations needed to change beginWord into endWord. You can change only one letter at a time, and each intermediate word must exist in the word list. If there is no possible transformation, return None (Python), -1 (Java & C++), null (Javascript). Examples

OFFICIAL PAGE TEXT

```
beginWord = 'hit'
endWord = 'cog'
wordList = ["hit", "hot", "dot", "dog", "cog"]
output: 4 # hit -> hot -> dot -> dog -> cog

beginWord = 'word'
endWord = 'word'
wordList = ['word', 'ward']
output: 0

beginWord = 'hit'
endWord = 'cog'
wordList = ["hit", "hot", "dot", "dog"]
output: None  # because no 'cog' in list
```

Our solution tackles the problem by first constructing a graph that represents all possible transformations between words in the list, where an edge exists between two words if they differ by exactly one character (i.e., they are "one edit distance" apart). This is done by iterating over the list of words and comparing each pair to determine if they meet the one edit distance condition. If they do, an edge is added between them in the graph. After constructing the graph, we use a breadth-first search (BFS) approach to find the shortest path from the start_word to the end_word. We initiate a queue that starts with the start_word and its associated edit distance (initially 0). As we traverse the graph, for each word, we check if it's the end_word. If so, we return the current edit distance incremented by one. If not, we add the word's neighbors to the queue for further exploration, ensuring that we don't revisit previously seen words. The BFS guarantees that the first time we reach the end_word, it is via the shortest path, and we can stop the search early. Time Complexity: The time complexity of the solution is O(n^2 * m), where n is the number of words and m is the length of each word. This complexity arises from the double loop that compares each word to every other word (O(n^2)), and for each comparison, we check if the words differ by exactly one character (O(m)). Space Complexity:

The space complexity is O(n^2), where n is the number of words. This space is required to store the graph, where each word can potentially have edges to all other words. Additionally, the BFS queue and the visited set require O(n) space in the worst case.In this video, Thomas, Google SWE, answers the Edit Distance coding interview question.No answers contributed by the community yet.

Medium (2)

MEDIUM | IN APP LC 543 | Exponent | 118 of 165

Given the root of a binary tree, return the length of the diameter of the tree.

ASKED (ANY CO.) ~3 MONTHS AGO | LAST 6 MONTHS

STUDY: TYPE ALL TIME 44.4 30 DAYS 0 PRIORITY 79/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: your app's interview approach (LeetCode #543)

LeetCode match: LC 543 Diameter of Binary Tree

Last asked (any company): 3 months ago, about 2026-07 (Exponent shows only a rough age) | +18 interviews

Original: https://www.aced.io/questions/2705/binary-tree-diameter-length

QUESTION

Given the root of a binary tree, create a function diameterOfTree that determines and returns the length of the diameter of the tree, where the diameter of a tree is defined as the number of nodes along the longest path between any two nodes in the tree. For example, given the following binary tree: // tree 1 / \ 2 3 / \ 4 5 The diameter is 4, which is the length of the path [4, 2, 1, 3] or [5, 2, 1, 3].Watch Ali, SDE @ Amazon, answer the question: "Given the root of a binary tree, return the length of the diameter of the tree."No answers contributed by the community yet.Interview experiences6 shared‹›Uber · 3 months ago"interview process is very lengthy took around 5 weeks, and expectations is very high in each round, for LLD working code is required, also dont mess your HM round since i felt like it contained more weightage"Software Engineer · Mid Level / L4Meta · 4 months ago"The interview went smoothly overall. 1 round of phone screen followed by the full loop of 4 rounds packed in a day. 2 coding 1 behavior 1 system design."Software Engineer · Senior / L5Google · 9 months ago"I interviewed for an AI Engineer internship, but the process was mostly DSA-heavy. I had an online coding round first, then a technical round with binary tree and DP questions, then another harder DSA round with DP and linked list questions, and finally an HR round. The online

round covered arrays and strings, and the later rounds got progressively more difficult. The only non-DSA part was the last

APPROACH

DFS returning height; update diameter = max(diameter, left + right). O(n).

HOW TO THINK ABOUT IT

The longest path in a tree has a highest node, and the length of the best path through a node is the height of its left subtree plus the height of its right subtree. So compute heights bottom-up and, at every node, check left height + right height against a running best. One traversal does both jobs.

Basis: LeetCode 543, Diameter of Binary Tree (length counted in edges).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def diameter(root):
    best = 0
    for node in all_nodes(root):
        left = height(node.left)  # fresh walks
        right = height(node.right)
        best = max(best, left + right + 1)
    return best
```

TIME	SPACE
O(n^2) worst case	O(h)

WHY IT IS SLOW

Heights of the same subtrees are recomputed for every ancestor, O(n^2) on a skewed tree. One post-order pass returns heights and updates the best on the way, O(n).

OPTIMAL SOLUTION · One post-order pass returning heights and updating the best

TIME	SPACE
O(n)	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 An n-ary tree.

Take the two largest child heights at each node (not just left and right): best = max(best, top1 + top2). Sorting the children's heights costs O(d log d) per node, or track the top two in O(d).

FOLLOW-UP 2 Edges have weights, or you want the path itself.

Add the edge weight to each child's height before comparing; for the path, also store which child gave each of the two best heights and rebuild from the node that produced the best sum.

FOLLOW-UP 3 Count the diameter in nodes instead of edges.

Add one to the answer (a path of k edges has k + 1 nodes). State which convention the interviewer wants before you code.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


# BASE QUESTION (optimal): One post-order pass returning
# heights and updating the best
def diameter_nodes(root):
    # longest path between any two nodes, counted in
    # NODES.
    # Iterative post-order: height of every node, then the
    # best path through each node = left + right + 1.
    if root is None:
        return 0
    height, best, stack = {None: 0}, 0, [(root, False)]
    while stack:
        node, done = stack.pop()
        if not done:
            stack.append((node, True))
            for child in (node.left, node.right):
                if child:
                    stack.append((child, False))
            continue
        lh, rh = height[node.left], height[node.right]
        height[node] = 1 + max(lh, rh)
        best = max(best, lh + rh + 1)
    return best


# FOLLOW-UP 3: Count the diameter in nodes instead of
# edges.
def diameter_edges(root):
    # the other convention: a path of k edges has k + 1
    # nodes
    return max(diameter_nodes(root) - 1, 0)


class NNode:
    def __init__(self, val, children=()):
        self.val, self.children = val, list(children)


# FOLLOW-UP 1: An n-ary tree.
def diameter_nary(root):
    # n-ary tree: add the two tallest child heights at
    # each node
    if root is None:
        return 0
    height, best, stack = {}, 0, [(root, False)]
    while stack:
        node, done = stack.pop()
        if not done:
            stack.append((node, True))
            kids = node.children
            stack.extend((c, False) for c in kids)
            continue
        tops = sorted((height[c] for c in node.children),
                      reverse=True)[:2]
        height[node] = 1 + (tops[0] if tops else 0)
        best = max(best, 1 + sum(tops))
    return best


# FOLLOW-UP 2: Edges have weights, or you want the path
# itself.
```

```python
def diameter_weighted(root):
    # edge weights: children are (weight, node) pairs;
    # return
    # the longest weighted path
    best, stack, down = 0, [(root, False)], {}
    while stack:
        node, done = stack.pop()
        if not done:
            stack.append((node, True))
            kids = node.children
            stack.extend((c, False) for _, c in kids)
            continue
        lengths = [w + down[c] for w, c in node.children]
        arms = sorted(lengths, reverse=True)[:2]
        down[node] = arms[0] if arms else 0
        best = max(best, sum(arms))
    return best


if __name__ == "__main__":
    #       1
    #      / \
    #     2   3
    #    / \
    #   4   5
```

```python
    left = TreeNode(2, TreeNode(4), TreeNode(5))
    tree = TreeNode(1, left, TreeNode(3))
    assert diameter_nodes(tree) == 4
    assert diameter_edges(tree) == 3
    assert diameter_nodes(None) == 0
    assert diameter_nodes(TreeNode(1)) == 1
    deep = NNode(3, [NNode(5)])
    star = NNode(1, [NNode(2), deep, NNode(4)])
    assert diameter_nary(star) == 4
    heavy = NNode(1)
    heavy.children = [(5, NNode(2)), (3, NNode(3))]
    assert diameter_weighted(heavy) == 8
    # a long chain needs no recursion
    chain = TreeNode(0)
    cur = chain
    for i in range(1, 20000):
        cur.left = TreeNode(i)
        cur = cur.left
    assert diameter_nodes(chain) == 20000
```

OFFICIAL PAGE TEXT

Given the root of a binary tree, create a function diameterOfTree that determines and returns the length of the diameter of the tree, where the diameter of a tree is defined as the number of nodes along the longest path between any two nodes in the tree. For example, given the following binary tree:

```
// tree
        1
       / \
      2   3
     / \
    4   5
```

The diameter is 4, which is the length of the path [4, 2, 1, 3] or [5, 2, 1, 3].Watch Ali, SDE @ Amazon, answer the question: "Given the root of a binary tree, return the length of the diameter of the tree."No answers contributed by the community yet.

MEDIUM | Exponent | 119 of 165

Write SQL code to publish the Fibonacci series.

ASKED (ANY CO.) ~4 MONTHS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 192/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

LeetCode match: No LC match (SQL) (inferred from short statement)

Last asked (any company): 4 months ago, about 2026-06 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/2779/sql-code-fibonacci-series

QUESTION

Write SQL code to publish the Fibonacci series.

APPROACH

Use a recursive CTE producing (n, a, b) rows and select a; limit the row count with a WHERE clause.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask which database dialect, how many terms, and whether the series starts at 0 or 1.

BRUTE FORCE TO SAY OUT LOUD

A loop in a stored procedure. Works but is procedural.

OPTIMAL IDEA

Use a recursive common table expression holding (n, a, b): the anchor row is (1, 0, 1) and the recursive step is (n + 1, b, a + b) while n is below the limit. Select a. Watch integer overflow for large n; use a wider type or stop at the type limit.

DRY-RUN THESE CASES

Limit 1, limit 2, limit 10, a limit large enough to overflow a 64-bit integer.

LIKELY FOLLOW-UPS

Return only even terms or the sum of the first n terms.

PITFALLS

Forgetting the termination condition, which makes the query recurse until the database stops it.

HOW TO THINK ABOUT IT

A sequence that depends on the previous rows is a recursive CTE: one anchor row, one recursive step, and a stopping condition in the step. Carry the two previous values in each row (a, b) so the next row is (b, a + b); a row-per-term table is built in one statement with no procedural loop.

Basis: Written; recursive common table expressions. Run and checked on SQLite; the same query works on PostgreSQL and MySQL 8 (SQL Server omits the word RECURSIVE).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
a, b = 0, 1
for _ in range(n):
    execute("INSERT INTO fib VALUES (?)", a)
    a, b = b, a + b
```

TIME	SPACE
O(n)	O(n)
statements	

WHY IT IS SLOW

One statement and one round trip per term, and a loop outside the query language. A recursive CTE produces all rows in one set-based statement.

OPTIMAL SOLUTION · Recursive CTE carrying (n, a, b)

TIME	SPACE
O(n)	O(1)
	working set (O(n) result)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Only the even terms, or the sum of the first n terms.

Keep the CTE and filter or aggregate in the outer query: WHERE a % 2 = 0 for the even terms, SUM(a) for the total. The recursion stays the same.

FOLLOW-UP 2 Which database?

PostgreSQL and MySQL 8 use WITH RECURSIVE; SQL Server drops the word RECURSIVE and may need a CAST so the column type is wide enough (bigint) in the anchor row; Oracle accepts WITH without RECURSIVE too. State the dialect assumption first.

FOLLOW-UP 3 Large n overflows.

Use a wider type (BIGINT, NUMERIC, or DECIMAL) in the anchor row so the column type is wide enough from the start; arbitrary-size values need a language with big integers. **Cost:** O(n) rows regardless of the type; a wider type only costs more bytes per row.

FOLLOW-UP 4 Use it from application code with a parameter.

Bind the limit as a query parameter (never build the SQL by string concatenation) and fetch the single column. The recursion lives inside the database, so there is one round trip regardless of n.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import sqlite3

# a recursive query: each row is computed from the
# previous one
FIB_SQL = """
WITH RECURSIVE fib(n, a, b) AS (
    SELECT 1, 0, 1
    UNION ALL
    SELECT n + 1, b, a + b FROM fib WHERE n < ?
)
SELECT a FROM fib
"""


# BASE QUESTION (optimal): Recursive CTE carrying (n, a,
# b)
# FOLLOW-UP 4: Use it from application code with a
# parameter.
def fibonacci(count):
    # FOLLOW-UP 4: from app code: count is a parameter
    # one round trip: the recursion runs inside the
    # database;
    # the limit is a bound parameter, never glued into the
    # SQL
    with sqlite3.connect(":memory:") as db:
        rows = db.execute(FIB_SQL, (count,)).fetchall()
    return [r[0] for r in rows]


# FOLLOW-UP 1: Only the even terms, or the sum of the
# first n terms.
def even_terms(count):
    # follow-up: filter in an outer query
    sql = f"SELECT a FROM ({FIB_SQL}) WHERE a % 2 = 0"
    with sqlite3.connect(":memory:") as db:
        return [r[0] for r in db.execute(sql, (count,))]


# FOLLOW-UP 1: Only the even terms, or the sum of the
# first n terms.
def total(count):
    # follow-up: the sum of the first n terms
    sql = "SELECT SUM(a) FROM (" + FIB_SQL + ")"
    with sqlite3.connect(":memory:") as db:
        return db.execute(sql, (count,)).fetchone()[0]
```

```
# CHECK in Python
def fibonacci_python(count):
    # the same sequence in Python, used to check the SQL
    a, b, out = 0, 1, []
    for _ in range(count):
        out.append(a)
        a, b = b, a + b
    return out


if __name__ == "__main__":
    got = fibonacci(10)
    assert got == [0, 1, 1, 2, 3, 5, 8, 13, 21, 34]
    assert fibonacci(10) == fibonacci_python(10)
    assert fibonacci(1) == [0]
    assert even_terms(10) == [0, 2, 8, 34]
    assert total(10) == sum(fibonacci_python(10))
    # 80 terms stay exact in a 64-bit column
```

```
assert fibonacci(80) == fibonacci_python(80)
```

Easy (5)

EASY | Exponent | 120 of 165

★ TOP 10 EASY: rank 2 among Easy problems

★ Maximum Profit

ASKED (ANY CO.) ~4 MONTHS AGO | LAST 6 MONTHS

STUDY: TYPE | ALL TIME 72 | 30 DAYS 61 | PRIORITY 5/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #121 Best Time to Buy and Sell Stock

LeetCode match: LC 121 Best Time to Buy and Sell Stock (likely) (inferred from short statement)

Last asked (any company): 4 months ago, about 2026-06 (Exponent shows only a rough age) | 4 interviews

Original: https://www.aced.io/questions/3630/maximum-profit

QUESTION

You and your friend have decided to start an international trading business. You want to earn a profit through some ol' fashioned arbitrage: You'll buy widgets in one country and sell them in another at a higher price. Your friend has already found the current market prices for widgets in cities around the world, and you'd like to use this data to pick which cities to buy and sell widgets in. Write a function max_profit(prices) that efficiently finds the two cities that maximize your profit (i.e. largest difference in prices).
Input: A dictionary with cities as keys and prices as values Output: An array containing the names of the cities (min, max) If the prices dictionary is empty, return None/null (depending on the programming language used). If there is 0 profit to be earned, return None/null as well. If you are using C++, return {"", ""} in such cases. Example Pythonprices = {'London': 72, 'New York': 70, 'Tokyo': 67, 'Miami': 62} max_profit(prices)

=> ['Miami', 'London']Hint 1You can think of this as two sub-problems

: Finding the lowest price, and finding the highest price.Hint 2While you could compare every pair of cities, it's more efficient to find the min and max values.Hint 3You can keep track of the lowest and highest values and update them as you iterate through the list.Challenge 1Does your solution work in O(N) time and O(1) space? If not, you can be more efficient!Challenge 2What happens if the price is the same in every city? Does your function still return

APPROACH

Single pass tracking the minimum price seen so far and the best difference; adapt if the statement allows multiple trades. O(n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

The statement gives a dictionary city to price: ask whether the order of cities matters (it does not, since it is a dictionary), whether you may buy and sell in the same city, and what to return when fewer than two cities exist or all prices are equal.

BRUTE FORCE TO SAY OUT LOUD

Compare every ordered pair of cities. O(n^2).

OPTIMAL IDEA

Since there is no time order, the maximum profit is the largest price minus the smallest price, so find the city with the minimum price and the city with the maximum price in a single pass. Return [buy city, sell city]. O(n) time, O(1) space. If cities were a time series you would track the running minimum instead (LeetCode 121).

DRY-RUN THESE CASES

Two cities, ties for the minimum or maximum, all equal prices, a single city, negative prices.

LIKELY FOLLOW-UPS

Multiple transactions, a transaction fee, or the same problem on an ordered list.

PITFALLS

Using a time-order solution on an unordered dictionary. Returning the cities in the wrong order.

HOW TO THINK ABOUT IT

Check whether order matters. A dictionary has none, so the profit is largest price minus smallest price, and the answer is just the two extremes. If this were a list of prices over time you would have to buy before you sell, which is a different one-pass problem with a running minimum.

Basis: A dictionary of city to price has no time order, so the best trade is the cheapest city to the most expensive one (compare LeetCode 121, where order matters). Tie rule assumed: smallest city name; with all prices equal, the first two names alphabetically.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(price, cities):
    best = (-INF, None, None)
    for buy in cities:
        for sell in cities:
            if buy == sell:
                continue
            profit = price[sell] - price[buy]
            best = max(best, (profit, buy, sell))
    return best
```

BRUTE FORCE

TIME	SPACE
O(n^2)	O(1)

WHY IT IS SLOW

n^2 pairs. Since city order does not matter, the best pair is the cheapest city and the dearest city, found in one O(n) scan.

OPTIMAL SOLUTION · One pass for the cheapest and the dearest city

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The prices are a time series: you must buy before you sell (LeetCode 121).

Keep the minimum price seen so far and the best difference: O(n), O(1). The dictionary version ignores order, so the two extremes are enough.

FOLLOW-UP 2 Allow many trades (LeetCode 122) or a limit of k trades.

Many trades: add every positive day-to-day rise. At most k trades: DP over (trades used, holding or not), O(n * k).

FOLLOW-UP 3 Transaction fee or cooldown.

A two-state DP (holding, not holding) per day: hold = max(hold, free - price), free = max(free, hold + price - fee).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): One pass for the cheapest and
# the dearest city
def max_profit_prices(prices):
    # a dictionary city -> price: buy at the cheapest city
    # and
    # sell at the dearest, order does not matter
    if len(prices) < 2:
        return 0
    values = list(prices.values())
    return max(values) - min(values)


# FOLLOW-UP 1: The prices are a time series: you must buy
# before you sell (LeetCode ...
def best_one_trade(series):
    # a time series: buy BEFORE you sell (LeetCode 121)
    low, best = float("inf"), 0
    for p in series:
        low = min(low, p)
        best = max(best, p - low)
    return best


# FOLLOW-UP 2: Allow many trades (LeetCode 122) or a limit
# of k trades.
def best_many_trades(series):
    # unlimited trades (LeetCode 122): take every rise
    pairs = zip(series, series[1:])
    return sum(max(0, b - a) for a, b in pairs)


# FOLLOW-UP 2: Allow many trades (LeetCode 122) or a limit
# of k trades.
def best_k_trades(series, k):
    # at most k trades: dp[t][holding]
    if not series or k == 0:
        return 0
    hold = [float("-inf")] * (k + 1)
    cash = [0] * (k + 1)
    for p in series:
        for t in range(1, k + 1):
            # buy with the cash of t - 1 finished trades,
            # or sell
            hold[t] = max(hold[t], cash[t - 1] - p)
            cash[t] = max(cash[t], hold[t] + p)
    return cash[k]


# FOLLOW-UP 3: Transaction fee or cooldown.
def best_with_fee(series, fee):
    # a fee per trade: two states each day
    hold, cash = float("-inf"), 0
    for p in series:
        hold = max(hold, cash - p)
        cash = max(cash, hold + p - fee)
    return cash


if __name__ == "__main__":
    cities = {"a": 10, "b": 4, "c": 9}
    assert max_profit_prices(cities) == 6
    assert max_profit_prices({"a": 3}) == 0
    assert best_one_trade([7, 1, 5, 3, 6, 4]) == 5
    assert best_one_trade([7, 6, 4, 3, 1]) == 0
    assert best_many_trades([7, 1, 5, 3, 6, 4]) == 7
    assert best_k_trades([3, 2, 6, 5, 0, 3], 2) == 7
    assert best_k_trades([1, 2, 3], 1) == 2
    assert best_k_trades([], 3) == 0
    assert best_with_fee([1, 3, 2, 8, 4, 9], 2) == 8
```

OFFICIAL PAGE TEXT

You and your friend have decided to start an international trading business. You want to earn a profit through some ol' fashioned arbitrage: You'll buy widgets in one country and sell them in another at a higher price. Your friend has already found the current market prices for widgets in cities around the world, and you'd like to use this data to pick which cities to buy and sell widgets in. Write a function max_profit(prices) that efficiently finds the two cities that maximize your profit (i.e. largest difference in prices).
Input: A dictionary with cities as keys and prices as values
Output: An array containing the names of the cities (min, max) If the prices dictionary is empty, return None/null (depending on the programming language used). If there is 0 profit to be earned, return None/null as well. If you are using C++, return {"", ""} in such cases. Example

OFFICIAL PAGE TEXT

```
Pythonprices = {'London': 72, 'New York': 70, 'Tokyo':
 67, 'Miami': 62}

max_profit(prices) # => ['Miami', 'London']
```

Hint 1You can think of this as two sub-problems: Finding the lowest price, and finding the highest price.Hint 2While you could compare every pair of cities, it's more efficient to find the min and max values.Hint 3You can keep track of the lowest and highest values and update them as you iterate through the list.Challenge 1Does your solution work in O(N) time and O(1) space? If not, you can be more efficient!Challenge 2What happens if the price is the same in every city? Does your function still return different cities?For our solution, we'll simply iterate through the prices list and simultaneously keep track of the minimum and maximum values we've seen so far. This only requires one iteration, so it's more efficient than the 'brute force' approach of calculating the profit for each pair of cities, which would require O(n^2) time. A more concise—but slightly less efficient solution—would be to sort the cities according to their prices and then return the first and last elements. In some languages like Python, you can also use the built-in min and max functions to compare dictionary values:

```
Pythondef max_profit(prices):

  # Check if the dictionary is empty
  if not prices:
    return None

  min_city = min(prices, key=prices.get)
  max_city = max(prices, key=prices.get)

  # Check if no profits earned
  if min_city == max_city:
    return None

  return [min_city, max_city]
```

Time Complexity: Iterating over prices.items() takes O(n) time, where n is the number of cities in the prices dictionary. Within the loop, there are constant-time operations, so the overall time complexity is O(n). Space Complexity: The space complexity is also O(1) because the size of the auxiliary array returned ([min_city, max_city]) is constant and independent of the input size.No answers contributed by the community yet.

EASY | IN APP LC 70 | Exponent | 121 of 165

★ TOP 10 EASY: rank 6 among Easy problems

★ Climbing Stairs

ASKED (ANY CO.) ~4 MONTHS AGO | LAST 6 MONTHS

STUDY: TYPE ALL TIME 62.9 30 DAYS 51.4 PRIORITY 7/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #70)

LeetCode match: LC 70 Climbing Stairs

Last asked (any company): 4 months ago, about 2026-06 (Exponent shows only a rough age) | +38 interviews

Original: https://www.aced.io/questions/3255/climbing-stairs

QUESTION

Given an integer n, representing the number of steps in a staircase, write a function climbStairs that returns the number of distinct ways to climb to the top of the staircase. Each time you can either climb 1 step or 2 steps. You may assume that n is a non-negative integer. Examples Input: n = 1 Output: 1 Explanation: There is only 1 way to climb a staircase with 1 step.

Input: n = 2 Output: 2 Explanation: There are 2 ways to climb a staircase with 2 steps:

1. Climb 1 step + 1 step 2. Climb 2 steps directly Input: n = 3 Output: 3 Explanation: There are 3 ways to climb a staircase with 3 steps:
1. Climb 1 step + 1 step + 1 step 2. Climb 1 step + 2 steps 3. Climb 2 steps + 1 step Input: n = 4 Output: 5 Explanation: There are 5 ways to climb a staircase with 4 steps:
1. Climb 1 step + 1 step + 1 step + 1 step 2. Climb 1 step + 1 step + 2 steps 3. Climb 1 step + 2 steps + 1 step 4. Climb 2 steps + 1 step + 1 step 5. Climb 2 steps + 2 stepsChallenge 1Can you come up with a solution that has a O(n) time complexity?Challenge 2Can you come up with a solution that has a O(1) space complexity?Solution 1: Dynamic Programming Approach In this solution, we use dynamic programming to compute the number of distinct ways to climb n stairs. The idea is to build up the solution incrementally by solving subproblems. We initialize a list ways where ways[i] represents the number of ways to reach the ith step. We start by setting the base cases: ways[0] = 1 (1 way to stay at the ground) ways[1] =

APPROACH

dp[i] = dp[i-1] + dp[i-2] with two variables. O(n), O(1).

HOW TO THINK ABOUT IT

The last move was either a 1-step from n - 1 or a 2-step from n - 2, so ways(n) = ways(n - 1) + ways(n - 2): the Fibonacci recurrence. Only the previous two values matter, so two variables replace the whole table.

Basis: LeetCode 70, Climbing Stairs: ways to climb n steps taking 1 or 2 at a time (a Fibonacci number).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def ways(n):
    if n <= 1:
        return 1
    return ways(n - 1) + ways(n - 2)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

The same values are computed over and over: O(2^n). Keeping the last two values in a loop is O(n) time and O(1) space (and a matrix power gives O(log n)).

OPTIMAL SOLUTION · Two running values

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 n is huge (10^18).

Use matrix exponentiation of [[1, 1], [1, 0]] (or fast doubling) for O(log n) multiplications; take the result modulo a prime if asked.

FOLLOW-UP 2 You can take 1 to k steps (or a given set of step sizes).

ways[i] = sum of ways[i - s] over allowed step sizes s; for 1..k keep a sliding-window sum for O(n).

FOLLOW-UP 3 Some steps are broken (cannot be stood on).

Set ways[i] = 0 for broken steps while filling the table; everything else is unchanged.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
# BASE QUESTION (optimal): Two running values
def climb(n):
    # ways(n) = ways(n - 1) + ways(n - 2): O(n), O(1)
    # space
    a, b = 1, 1
    for _ in range(n - 1):
        a, b = b, a + b
    return b if n >= 1 else 1


def mat_mult(x, y, mod):
    out = [[0, 0], [0, 0]]
    for i in range(2):
        for j in range(2):
            cells = (x[i][k] * y[k][j] for k in range(2))
            total = sum(cells)
            out[i][j] = total % mod
    return out


# FOLLOW-UP 1: n is huge (10^18).
def climb_huge(n, mod=10 ** 9 + 7):
    # n up to 10^18: matrix power of [[1, 1], [1, 0]]
    result, base = [[1, 0], [0, 1]], [[1, 1], [1, 0]]
    e = n
    while e:
        if e & 1:
            result = mat_mult(result, base, mod)
        base = mat_mult(base, base, mod)
        e >>= 1
    # result = [[F(n+1), F(n)], [F(n), F(n-1)]]
    return result[0][0] % mod


# FOLLOW-UP 2: You can take 1 to k steps (or a given set
# of step sizes).
def climb_steps(n, steps):
    # any allowed step sizes: sum the ways of the earlier
    # stairs
    ways = [1] + [0] * n
    for i in range(1, n + 1):
        ways[i] = sum(ways[i - s] for s in steps
                      if i >= s)
    return ways[n]
```

```python
# FOLLOW-UP 2: You can take 1 to k steps (or a given set
# of step sizes).
def climb_up_to_k(n, k):
    # steps 1..k in O(n): keep a sliding-window sum
    ways, window = [1] + [0] * n, 1
    for i in range(1, n + 1):
        ways[i] = window
        window += ways[i]
        if i - k >= 0:
            window -= ways[i - k]
    return ways[n]


# FOLLOW-UP 3: Some steps are broken (cannot be stood on).
def climb_broken(n, broken):
    # broken steps cannot be stood on: zero ways there
    bad = set(broken)
    ways = [1] + [0] * n
    for i in range(1, n + 1):
        if i not in bad:
            two_back = ways[i - 2] if i > 1 else 0
            ways[i] = ways[i - 1] + two_back
    return ways[n]


if __name__ == "__main__":
    got = [climb(n) for n in range(1, 6)]
    assert got == [1, 2, 3, 5, 8]
    assert climb(0) == 1
    assert climb_huge(5) == 8 and climb_huge(1) == 1
```

```
assert 0 <= climb_huge(10 ** 18) < 10 ** 9 + 7
assert climb_huge(50) == climb(50) % (10 ** 9 + 7)
assert climb_steps(5, (1, 2)) == 8
assert climb_steps(4, (1, 3)) == 3
assert climb_up_to_k(5, 2) == 8
assert climb_up_to_k(4, 3) == 7
assert climb_broken(5, [3]) == 2
assert climb_broken(3, [1, 2]) == 0
```

OFFICIAL PAGE TEXT

Given an integer n, representing the number of steps in a staircase, write a function climbStairs that returns the number of distinct ways to climb to the top of the staircase. Each time you can either climb 1 step or 2 steps. You may assume that n is a non-negative integer. Examples

```
Input: n = 1
Output: 1
Explanation: There is only 1 way to climb a staircase
with 1 step.

Input: n = 2
Output: 2
Explanation: There are 2 ways to climb a staircase wit
h 2 steps:
1. Climb 1 step + 1 step
2. Climb 2 steps directly

Input: n = 3
Output: 3
Explanation: There are 3 ways to climb a staircase wit
h 3 steps:
1. Climb 1 step + 1 step + 1 step
2. Climb 1 step + 2 steps
3. Climb 2 steps + 1 step

Input: n = 4
Output: 5
Explanation: There are 5 ways to climb a staircase wit
h 4 steps:
1. Climb 1 step + 1 step + 1 step + 1 step
2. Climb 1 step + 1 step + 2 steps
3. Climb 1 step + 2 steps + 1 step
4. Climb 2 steps + 1 step + 1 step
5. Climb 2 steps + 2 steps
```

OFFICIAL PAGE TEXT

Challenge 1Can you come up with a solution that has a O(n) time complexity?Challenge 2Can you come up with a solution that has a O(1) space complexity?Solution 1: Dynamic Programming Approach In this solution, we use dynamic programming to compute the number of distinct ways to climb n stairs. The idea is to build up the solution incrementally by solving subproblems. We initialize a list ways where ways[i] represents the number of ways to reach the ith step. We start by setting the base cases: ways[0] = 1 (1 way to stay at the ground) ways[1] = 1 (1 way to reach the first step, which is a single 1-step) For each subsequent step i, the number of ways to reach that step is the sum of the ways to reach the previous step (ways[i - 1]) and the step before that (ways[i - 2]). This is because you can get to step i either from step i - 1 with a 1-step or from step i - 2 with a 2-step. Time Complexity: The time complexity of this solution is O(n), where n is the number of steps. This is because we iterate through the steps from 2 to n, updating the number of ways for each step. Space Complexity: The space complexity is O(n) due to the additional array ways used to store the number of ways for each step. If space optimization is needed, this can be reduced to O(1) by keeping only the last two computed values. Solution 2: Combinatorial Approach Our solution leverages combinatorial mathematics to calculate

the number of distinct ways to climb n stairs. The approach is based on counting the number of valid sequences of steps (1-step and 2-steps) that sum up to n. We use the binomial coefficient to count the number of ways to arrange a certain number of 1-steps and 2-steps. For each possible number of 2-steps (k), we compute the number of ways to choose k positions from n - k steps (the remaining steps will be 1-steps). This is done using the formula for combinations: C(n,k)C(n, k)C(n,k), where C(n,k)=n!k!*(n-k)!C(n, k) = \frac{n!}{k! \cdot (n-k)!}C(n,k)=k!*(n-k)!n!. The total number of ways is the sum of these combinations for all valid values of k. Time Complexity: The time complexity of this solution is O(n), where n is the number of steps. This is because we compute the combination for each k from 0 to n // 2, and each combination computation is efficient. Space Complexity: The space complexity is O(1) as we only use a few additional variables for storing intermediate results, regardless of the input size.No answers contributed by the community yet.

EASY | IN APP LC 206 | Exponent | 122 of 165

Reverse a linked list.

ASKED (ANY CO.) ~4 MONTHS AGO | LAST 6 MONTHS

STUDY: TYPE | ALL TIME 59.8 | 30 DAYS 0 | PRIORITY 35/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: your app's interview approach (LeetCode #206)

LeetCode match: LC 206 Reverse Linked List

Last asked (any company): 4 months ago, about 2026-06 (Exponent shows only a rough age) | +921 interviews

Original: https://www.aced.io/questions/3247/reverse-linked-list

QUESTION

Given the head of a singly linked list, reverse the list and return its head. Implement a function reverseList that takes the head of the linked list as input and returns the new head of the reversed list. Refer to the ListNode class/struct and do not comment it out. Example Input: 1 -> 2 -> 3 -> 4 Output: 4 -> 3 -> 2 -> 1Challenge 1Can you come up with a solution with a time complexity of O(n)?Challenge 2Can you come up with a solution with a space complexity of O(1)?

APPROACH

Iterative: walk with prev/cur pointers flipping next; or recursion. O(n) time, O(1) space iterative.

HOW TO THINK ABOUT IT

Reversing means every next pointer has to flip, so hold three things: the node you are on, the one before it (what it will point to) and the one after it (so you do not lose the rest). Always save next before overwriting it. For 'reverse part of the list' remember the node before the part and the node that will end up last in it.

Basis: LeetCode 206 (Reverse Linked List), 92 (between positions) and 25 (in groups of k).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def reverse_list(head):
    values = []
    node = head
    while node:
        values.append(node.val)
        node = node.next
    new_head = None
    for v in values:
        node = ListNode(v)
        node.next = new_head
        new_head = node  # push to front
    return new_head
```

BRUTE FORCE

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Time is O(n), but it allocates a whole new list, O(n) extra space. Flipping each node's next pointer in place with three variables needs O(1) space.

OPTIMAL SOLUTION · Flip the pointers in one pass

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Do it recursively.

Reverse the rest first, then make the next node point back at this one and cut this node's own pointer. An inner helper that carries prev (as coded) keeps it tail-recursive in spirit; the call stack is O(n), so mention the depth limit.

FOLLOW-UP 2 Reverse only positions left to right (LeetCode 92).

Walk to the node before the segment, reverse right - left + 1 nodes with the same loop, then reconnect: the old first node of the segment must point to what followed the segment, and the node before it points to the new first.

FOLLOW-UP 3 Reverse in groups of k and leave a short last group alone (LeetCode 25).

Check that k nodes exist before reversing a group, reverse them with the same loop, reconnect both ends, and move the group pointer to the old first node of the group.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class ListNode:
    def __init__(self, val=0, next=None):
        self.val, self.next = val, next


def make(values):
    dummy = tail = ListNode()
    for v in values:
        tail.next = ListNode(v)
        tail = tail.next
    return dummy.next


def to_list(node):
    out = []
    while node:
        out.append(node.val)
```

```
        node = node.next
    return out


# BASE QUESTION (optimal): Flip the pointers in one pass
def reverse_list(head):
    # point every node back at the one before it
    prev = None
    while head:
        head.next, prev, head = prev, head, head.next
    return prev


# FOLLOW-UP 1: Do it recursively.
def reverse_recursive(head, prev=None):
    # the call stack is O(n): mention the depth limit
    if head is None:
        return prev
    nxt, head.next = head.next, prev
    return reverse_recursive(nxt, head)


# FOLLOW-UP 2: Reverse only positions left to right
# (LeetCode 92).
def reverse_between(head, left, right):
    # LeetCode 92: reverse positions left..right (1-based)
    dummy = ListNode(0, head)
    before = dummy
```

```
    for _ in range(left - 1):
        before = before.next
    # reverse right - left + 1 nodes with the same loop
    prev, cur = None, before.next
    for _ in range(right - left + 1):
        cur.next, prev, cur = prev, cur, cur.next
    # reconnect: the old first node points past the
    # segment
    before.next.next = cur
    before.next = prev
    return dummy.next


# FOLLOW-UP 3: Reverse in groups of k and leave a short
# last group alone (LeetCode ...
def reverse_k_group(head, k):
    # LeetCode 25: reverse each full group of k; a short
    # last
    # group is left alone
    dummy = ListNode(0, head)
    group_prev = dummy
    while True:
        # is there a full group of k nodes?
        end = group_prev
        for _ in range(k):
            end = end.next
            if end is None:
                return dummy.next
        first, after = group_prev.next, end.next
        prev, cur = after, first
        while cur is not after:
            cur.next, prev, cur = prev, cur, cur.next
        group_prev.next = prev
        group_prev = first


if __name__ == "__main__":
    assert to_list(reverse_list(make([1, 2, 3, 4]))) == [
        4, 3, 2, 1]
    assert reverse_list(None) is None
    got = to_list(reverse_recursive(make([1, 2, 3])))
    assert got == [3, 2, 1]
    part = reverse_between(make([1, 2, 3, 4, 5]), 2, 4)
    assert to_list(part) == [1, 4, 3, 2, 5]
```

```
    got = to_list(reverse_between(make([1, 2]), 1, 2))
```

```
    assert got == [2, 1]
    grouped = reverse_k_group(make([1, 2, 3, 4, 5]), 2)
    assert to_list(grouped) == [2, 1, 4, 3, 5]
    got = to_list(reverse_k_group(make([1, 2, 3]), 3))
    assert got == [3, 2, 1]
    assert to_list(reverse_k_group(make([1]), 2)) == [1]
```

OFFICIAL PAGE TEXT

Given the head of a singly linked list, reverse the list and return its head. Implement a function reverseList that takes the head of the linked list as input and returns the new head of the reversed list. Refer to the ListNode class/struct and do not comment it out. Example

```
Input: 1 -> 2 -> 3 -> 4
Output: 4 -> 3 -> 2 -> 1
```

Challenge 1Can you come up with a solution with a time complexity of O(n)?Challenge 2Can you come up with a solution with a space complexity of O(1)?Our solution reverses the linked list by iterating through it while maintaining pointers to keep track of the previous node and the current node. For each node, it saves the next node, then reverses the link by pointing the current node's next to the previous node. It then moves the prev pointer to the current node and advances the current pointer to the saved next node. This process continues until the end of the list is reached. At the end, the prev pointer points to the new head of the reversed list, which is returned. The solution uses two pointers, prev and current, to achieve this reversal. This approach ensures that each node is processed exactly once, making it both efficient and straightforward. Time Complexity: The solution has a time complexity of O(n), where n is the number of nodes in the linked list. This is because we iterate through the list once, performing constant-time operations (pointer adjustments) for each node. Space Complexity: The solution uses O(1) space, as it only uses a fixed amount of extra space (three pointers: prev, current, and nextNode). No additional data structures are used, making it very space-efficient. NoteCheck out our lesson on the two pointer approach to learn more about what it is and how to use it!No answers

contributed by the community yet.

EASY | Exponent | 123 of 165

Tree Node.

ASKED (ANY CO.) ~5 MONTHS AGO | LAST 6 MONTHS

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 214/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

LeetCode match: No direct match (tree node classification)

Last asked (any company): 5 months ago, about 2026-05 (Exponent shows only a rough age) | +38 interviews

Original: https://www.aced.io/questions/3957/tree-node

QUESTION

Given a binary tree, identify which nodes are leaf nodes, root nodes or inner nodes. Leaf nodes: A node with no children Root nodes: A node with no parent Inner nodes: A node with both children and parent nodes You are given the following table tree_node_table: idp_idintegerinteger where p_id is the id of the parent node. Your output should contain the following columns: id, node_types ('Root', 'Inner', 'Leaf').No answers contributed by the community yet.Interview experiences7 shared‹›Amazon · 5 months ago"It went well and answered all questions. and did both leetcode questions asked one in each interview"Software Engineer · InternGoogle · 6 months ago"Pretty easy, just very long. For technical just need to do leetcode, no system design. Interviewers help you if you are stuck."Software Engineer · Entry Level / L3Microsoft · 6 months ago"What went well: The live coding and system architecture rounds went smoothly. I was able to articulate my design choices clearly, especially around API design, database strategy, and maintaining high availability for microservices. What didn't go well: The initial behavioral portion felt slightly rushed because we spent extra time discussing specific cross-functional project dynamics from my previous roles. How does this interview compare to other interviews you've done? It was significantly more interactive. Rather than giving static answers, the

interviewers actively challenged my assumptions and asked "what if" scenarios, making the evaluat

APPROACH

Traverse the tree (DFS/BFS) and classify: root has no parent, leaf has no children, inner otherwise. O(n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask about the table shape (id and p_id), whether a node with no parent is the root even if it has no children, and whether a single-node tree is Root.

BRUTE FORCE TO SAY OUT LOUD

Load the table into a program and classify with loops. It works but SQL is expected.

INTERVIEW-DAY PLAN

OPTIMAL IDEA

A single query with CASE: Root when p_id is null; Inner when the node's id appears as someone's p_id and p_id is not null; otherwise Leaf. Use a subquery or EXISTS for the 'has children' test. O(n) with an index on p_id.

DRY-RUN THESE CASES

A single-node tree, a chain, a star, two roots (bad data).

LIKELY FOLLOW-UPS

Binary tree validation, or output in a specific order.

PITFALLS

Calling a root with children Inner. Using NOT IN with NULLs in the subquery (it returns nothing).

HOW TO THINK ABOUT IT

Each row is a node with its parent id. A node is the root if it has no parent, a leaf if nobody lists it as a parent, and inner otherwise. Order the tests so the root is decided first (a single-node tree is a root, not a leaf). Beware NOT IN with NULLs: it returns nothing if the subquery contains a NULL.

Basis: LeetCode 608, Tree Node. Run and checked on SQLite.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
SELECT id, 'Root' AS node_types
FROM tree_node_table WHERE p_id IS NULL
UNION
SELECT id, 'Inner'
FROM tree_node_table t
WHERE p_id IS NOT NULL
  AND EXISTS (SELECT 1 FROM tree_node_table c
              WHERE c.p_id = t.id)
UNION
SELECT id, 'Leaf'
FROM tree_node_table t
WHERE p_id IS NOT NULL
  AND NOT EXISTS (SELECT 1 FROM tree_node_table c
                  WHERE c.p_id = t.id);
```

TIME	SPACE
O(n^2)	O(n)
without an index on p_id	

WHY IT IS SLOW

The correlated subquery runs once per row and the table is scanned three times, O(n^2) without an index. One CASE expression with a single set of parent ids scans once.

OPTIMAL SOLUTION · One CASE expression

TIME	SPACE
O(n)	O(n)
with the set of parent ids built once	

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why not use NOT IN for the leaves?

If the subquery returns a NULL (the root's p_id), id NOT IN (...) is never true, so you get no rows. Filter NULLs out of the subquery or use NOT EXISTS.

FOLLOW-UP 2 The table has no row for the root's parent and p_id can point to missing ids.

Validate with a LEFT JOIN to find orphans. A node whose p_id is not NULL but missing from the table is a data error, not a root; decide whether to report it.

FOLLOW-UP 3 Add the depth of each node.

A recursive CTE starting from the root rows and joining children on p_id, carrying depth + 1, gives every node's depth in one query.

FOLLOW-UP 4 Add the depth of each node.

A recursive CTE starts from the root rows (depth 0) and joins the table to itself on p_id, adding 1 at every step; each node appears once because every node has one parent. Runs in one query, O(n) with an index on p_id.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import sqlite3

# the table has one row per node; the root has p_id NULL
SCHEMA = "CREATE TABLE tree_node_table (id INT, p_id INT)"
INSERT = "INSERT INTO tree_node_table VALUES (?, ?)"

# BASE QUESTION (optimal): One CASE expression
# Root: no parent. Inner: has a parent and a child.
# Leaf: has a parent and no child. The Root test comes
# first, so a one-node tree is a Root, not a Leaf.
TYPES_SQL = """
SELECT t.id,
  CASE
    WHEN t.p_id IS NULL THEN 'Root'
    WHEN EXISTS (SELECT 1 FROM tree_node_table c
                 WHERE c.p_id = t.id) THEN 'Inner'
    ELSE 'Leaf'
  END AS node_types
FROM tree_node_table t
ORDER BY t.id
"""

# FOLLOW-UP 1: Why not use NOT IN for the leaves?
# the NOT IN trap: the subquery contains the root's NULL
# p_id, so "id NOT IN (...)" is never true: no rows
NOT_IN_SQL = """
SELECT id FROM tree_node_table
WHERE id NOT IN (SELECT p_id FROM tree_node_table)
"""

# FOLLOW-UP 1: Why not use NOT IN for the leaves?
# the same idea done safely with NOT EXISTS
LEAVES_SQL = """
SELECT t.id FROM tree_node_table t
WHERE NOT EXISTS (SELECT 1 FROM tree_node_table c
                  WHERE c.p_id = t.id)
ORDER BY t.id
"""

# FOLLOW-UP 2: The table has no row for the root's parent
# and p_id can point to ...
# a p_id that points at a missing id is a data error
ORPHANS_SQL = """
SELECT t.id FROM tree_node_table t
LEFT JOIN tree_node_table p ON p.id = t.p_id
WHERE t.p_id IS NOT NULL AND p.id IS NULL
ORDER BY t.id
"""

# FOLLOW-UP 3, 4: Add the depth of each node.
# follow-up: depth of every node. Start from the roots and
# walk down one level at a time (each node has one parent)
DEPTH_SQL = """
WITH RECURSIVE walk(id, depth) AS (
  SELECT id, 0 FROM tree_node_table WHERE p_id IS NULL
  UNION ALL
  SELECT t.id, w.depth + 1
  FROM tree_node_table t JOIN walk w ON t.p_id = w.id
)
SELECT id, depth FROM walk ORDER BY id
"""


def make_db(rows):
    # build an in-memory database holding the given rows
    db = sqlite3.connect(":memory:")
    db.execute(SCHEMA)
    db.executemany(INSERT, rows)
    return db


def run(rows, sql):
    # run one query on a fresh database
    with make_db(rows) as db:
        return db.execute(sql).fetchall()


if __name__ == "__main__":
    #       1
    #      / \
    #     2   3
    #    / \
    #   4   5
    rows = [(1, None), (2, 1), (3, 1), (4, 2), (5, 2)]
    got = run(rows, TYPES_SQL)
    want = [(1, "Root"), (2, "Inner"), (3, "Leaf"),
            (4, "Leaf"), (5, "Leaf")]
    assert got == want
    # a single node is the Root
    assert run([(7, None)], TYPES_SQL) == [(7, "Root")]
    # NOT IN finds nothing because of the NULL
    assert run(rows, NOT_IN_SQL) == []
    assert run(rows, LEAVES_SQL) == [(3,), (4,), (5,)]
    # node 9 points at a parent that does not exist
    assert run(rows + [(9, 42)], ORPHANS_SQL) == [(9,)]
    assert run(rows, ORPHANS_SQL) == []
    got = run(rows, DEPTH_SQL)
    assert got == [(1, 0), (2, 1), (3, 1), (4, 2), (5, 2)]
```

OFFICIAL PAGE TEXT

Given a binary tree, identify which nodes are leaf nodes, root nodes or inner nodes. Leaf nodes: A node with no children Root nodes: A node with no parent Inner nodes: A node with both children and parent nodes You are given the following table tree_node_table: idp_idintegerinteger where p_id is the id of the parent node. Your output should contain the following columns: id, node_types ('Root', 'Inner', 'Leaf').No answers contributed by the community yet.

EASY | Exponent | 124 of 165

Sort a binary array in linear time.

ASKED (ANY CO.) ~5 MONTHS AGO | LAST 6 MONTHS

STUDY: TYPE | ALL TIME 53.6 | 30 DAYS 0 | PRIORITY 63/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #75 Sort Colors

LeetCode match: LC 75 Sort Colors (binary version) (inferred from short statement)

Last asked (any company): 5 months ago, about 2026-05 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/971/sort-binary-array-linear-time

QUESTION

Sort a binary array in linear time.

APPROACH

Two pointers swapping 0s to the front (or counting zeros); one pass, O(n), O(1).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether it must be in place and stable (for bare 0 and 1 stability does not matter).

BRUTE FORCE TO SAY OUT LOUD

Use the library sort. O(n log n).

OPTIMAL IDEA

Two pointers: lo moves right past zeros, hi moves left past ones, and when lo points at a 1 and hi at a 0 swap them. One pass, O(n) time, O(1) space. Counting the zeros and refilling is the other simple option.

DRY-RUN THESE CASES

Empty array, all zeros, all ones, already sorted, reverse sorted.

LIKELY FOLLOW-UPS

Three values (Dutch national flag, LeetCode 75), or sort records by a binary key.

INTERVIEW-DAY PLAN

PITFALLS

Moving both pointers after a swap but forgetting the loop bound.

HOW TO THINK ABOUT IT

With only two values the sorted array is 'all zeros then all ones', so you only have to move zeros left and ones right. Two pointers from the two ends do it in one pass: swap whenever the left pointer sees a 1 and the right pointer a 0.

Basis: LeetCode 75, Sort Colors, with two values instead of three.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(arr):
    return sorted(arr)  # O(n log n)
```

TIME	SPACE
O(n log n)	O(n)

WHY IT IS SLOW

A comparison sort is O(n log n) and needs a copy; with only two values two pointers (swap a 1 on the left with a 0 on the right) finish in one O(n) pass in place.

OPTIMAL SOLUTION · Two pointers swapping from both ends

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why not just count zeros and fill?

Counting is also O(n) time and O(1) space and is fine for bare numbers. It needs two passes, and it cannot sort records that merely have a binary key, because it loses the objects. The swap version sorts the records themselves.

FOLLOW-UP 2 Count the zeros and rebuild (also O(n)).

Fine for bare numbers: one pass to count, one to fill. It cannot sort records that merely have a 0 or 1 key, because it loses the objects; the swapping version can.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Two pointers swapping from both
# ends
def sort_binary(arr):
    # two pointers: zeros collect on the left, ones on the
```

```
    # right; every step swaps or moves one pointer: O(n)
    lo, hi = 0, len(arr) - 1
    while lo < hi:
        if arr[lo] == 0:
            lo += 1
        elif arr[hi] == 1:
            hi -= 1
        else:
            # a 1 on the left and a 0 on the right: swap
            # them
            arr[lo], arr[hi] = arr[hi], arr[lo]
            lo += 1
            hi -= 1
    return arr


# FOLLOW-UP 2: Count the zeros and rebuild (also O(n)).
def sort_by_counting(arr):
    # follow-up: count the zeros, then rewrite the array.
    # Fine for bare numbers, useless for records.
    zeros = arr.count(0)
    return [0] * zeros + [1] * (len(arr) - zeros)


# RECORDS with a 0/1 key
def sort_records(items, key):
    # records that merely have a 0/1 key: swapping keeps
    # the
    # objects (counting would lose them). Not stable.
    lo, hi = 0, len(items) - 1
    while lo < hi:
        if key(items[lo]) == 0:
            lo += 1
        elif key(items[hi]) == 1:
            hi -= 1
        else:
            items[lo], items[hi] = items[hi], items[lo]
            lo += 1
            hi -= 1
    return items
```

```
# VARIANT: 0, 1 and 2 (Dutch flag)
def sort_three(arr):
    # the same idea for 0, 1, 2 (Dutch national flag):
    # [0, low) are 0, [high, n) are 2, the middle is 1
    low, mid, high = 0, 0, len(arr)
    while mid < high:
        if arr[mid] == 0:
            arr[low], arr[mid] = arr[mid], arr[low]
            low += 1
            mid += 1
        elif arr[mid] == 2:
            high -= 1
            arr[mid], arr[high] = arr[high], arr[mid]
        else:
            mid += 1
    return arr


if __name__ == "__main__":
    mixed = [1, 0, 1, 0, 1, 0]
    assert sort_binary(mixed) == [0, 0, 0, 1, 1, 1]
    assert sort_binary([]) == []
    assert sort_binary([1]) == [1]
    assert sort_binary([1, 1, 0]) == [0, 1, 1]
    for arr in ([0, 0], [1, 1], [1, 0], [0, 1, 0, 0, 1]):
        assert sort_binary(arr[:]) == sorted(arr)
        assert sort_by_counting(arr) == sorted(arr)
    people = [("ann", 1), ("bob", 0),
              ("cy", 1), ("di", 0)]
    done = sort_records(people[:], key=lambda p: p[1])
    keys = [p[1] for p in done]
```

```
    assert keys == [0, 0, 1, 1]
    # no record was lost: the same objects are still there
    assert sorted(done) == sorted(people)
    flag = sort_three([2, 0, 1, 2, 0, 1])
    assert flag == [0, 0, 1, 1, 2, 2]
    assert sort_three([2, 2, 0]) == [0, 2, 2]
```

ASKED (ROUGH): OLDER THAN 6 MONTHS (30)

Hard (6)

HARD | Exponent | 125 of 165

Given two strings and two allowed operations, swapping positions of letters and converting all occurrences of one character to another, can the first string be transformed into the second?

ASKED (ANY CO.) ~6 MONTHS AGO | OLDER

STUDY: TALK | ALL TIME 16.5 | 30 DAYS 0 | PRIORITY 160/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #1153 String Transforms Into Another String

LeetCode match: No direct match; related LC 1153 String Transforms Into Another String (inferred from short statement)

Last asked (any company): 6 months ago, about 2026-04 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/6330/determine-string-transformability-allowed-operations

QUESTION

Given two strings and two allowed operations, swapping positions of letters and converting all occurrences of one character to another, can the first string be transformed into the second?

APPROACH

Position swaps make order irrelevant, so only the multiset/character mapping matters: build a char -> char map (must be consistent), and the conversion graph must have a free letter to break cycles if all 26 letters are used.

INTERVIEW-DAY PLAN

CLARIFY FIRST

The wording fits LeetCode 1657, Close Strings (swap any two characters, or swap the identities of two letters that exist). If the second operation is a one-directional conversion of all occurrences of a letter (LeetCode 1153), the answer changes, so ask which one.

BRUTE FORCE TO SAY OUT LOUD

BFS over all strings reachable by the allowed operations. Exponential.

OPTIMAL IDEA

1657 reading: the answer is true when both strings use the same set of letters and their sorted frequency lists are equal, because swaps reorder freely and the second operation permutes frequencies among existing letters. 1153 reading: each source letter must map to a single target letter, and if the strings differ and the target uses all 26 letters there is no spare letter to break a cycle, so it is impossible. Both are O(n).

DRY-RUN THESE CASES

abc and bca (true), a and aa (false), cabbba and abbccc (true), uau and ssx (false); for 1153, aabcc to ccdee (true) and a full alphabet rotation (false).

LIKELY FOLLOW-UPS

Both operations combined with one-directional conversion, which reduces to grouping letter counts, or returning the sequence of operations.

PITFALLS

Using the 1657 test when the conversion is one-directional. Comparing frequencies without comparing the letter sets.

HOW TO THINK ABOUT IT

Decide which operations you really have. If you can swap any two letters (positions) and swap the identities of two letters, the answer depends only on which letters appear and how often (the multiset of counts). If conversion is one-way (every a becomes b), letters can merge but never split, and cycles in the mapping need a spare letter. Name the reading before you code.

Basis: The wording matches LeetCode 1657, Close Strings (swap any two characters, or swap the identities of two existing letters). The dataset also relates LeetCode 1153 (one-directional conversion, no swaps), so both readings are solved.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def can_transform(s, t):
    seen, queue = {s}, deque([s])
    while queue:
        cur = queue.popleft()
        if cur == t:
            return True
        for nxt in swap_positions(cur):
            add_if_new(nxt, seen, queue)
        for nxt in convert_letters(cur):
            add_if_new(nxt, seen, queue)
    return False
```

TIME	SPACE
exponential	exponential

WHY IT IS SLOW

The number of reachable strings grows exponentially with the length. Because swaps make order irrelevant, comparing the sets of letters and their sorted counts decides it in O(n).

OPTIMAL SOLUTION · Reading 1 (LeetCode 1657): same letter set and same multiset of frequencies

TIME	SPACE
O(n)	O(1) for a fixed alphabet

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Reading 2 (LeetCode 1153): one-directional conversion, no swaps

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if the two operations are combined (one-directional conversion plus swaps)?

Swaps make positions irrelevant, so only letter counts matter. Conversions can only merge letter classes, never split one. So t is reachable only if the counts of t can be formed by grouping the counts of s into the t letters (each s letter's count goes wholly to one t letter) and, unless the relabeling is an identity or chain, there is a spare letter. With at most 26 classes the grouping is a small bin-packing search.

FOLLOW-UP 2 Why does a full 26-letter target make the one-directional version impossible?

Every conversion rewrites a letter into another letter, and if a mapping contains a cycle (a to b and b to a) you need a temporary letter not currently in use to break it. If t uses all 26 letters then s must use all 26 as well (the mapping is a function onto 26 distinct letters), so the mapping is a permutation and any non-identity permutation has a cycle. The only possible case is therefore s equal to t.

FOLLOW-UP 3 Only position swaps are allowed.

Then s can become t exactly when they are anagrams: compare the letter counts. O(n).

FOLLOW-UP 4 Conversion is one-directional (every a becomes b) and there are no position swaps (LeetCode 1153).

Each source letter must map to one target letter, and if the strings differ and the target already uses all 26 letters there is no spare letter to break mapping cycles, so it is impossible. Verified against brute force on a small alphabet.

FOLLOW-UP 5 Return the sequence of operations, or the minimum number.

Minimum operations for the swap-only case is n minus the number of cycles in the permutation that sorts s into t; for letter-identity swaps it is the number of cycles in the letter mapping minus one per cycle of length greater than one.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
from collections import Counter

ALPHABET = 26


# FOLLOW-UP 3: Only position swaps are allowed.
def swaps_only(s, t):
    # swaps only rearrange: reachable exactly when the
    # strings are anagrams (same letter counts)
    return Counter(s) == Counter(t)


# FOLLOW-UP 4: Conversion is one-directional (every a
# becomes b) and there are no ...
def convert_only(s, t, alphabet=ALPHABET):
    # no swaps, conversion turns EVERY x into one letter y
    # (LeetCode 1153). Each source letter needs one
    # target.
    if len(s) != len(t):
        return False
    if s == t:
        return True
    mapping = {}
    for a, b in zip(s, t):
        if mapping.setdefault(a, b) != b:
            return False
    # a mapping with a cycle (a to b, b to a) needs a
    # spare
    # letter, so a target that uses every letter has none
    return len(set(t)) < alphabet


def can_group(have, want):
    # can the counts in `have` be grouped (each used once)
    # so that the group sums are exactly the counts in
    # `want`? Letters merge, they never split.
    if sum(have) != sum(want):
        return False
    have = sorted(have, reverse=True)
    left = list(want)

    def place(i):
        if i == len(have):
            return all(x == 0 for x in left)
        tried = set()
        for j in range(len(left)):
            # equal bins behave the same: try each size
            # once
            fits = left[j] >= have[i]
            if fits and left[j] not in tried:
                tried.add(left[j])
                left[j] -= have[i]
                if place(i + 1):
                    return True
                left[j] += have[i]
        return False

    return place(0)


# BASE QUESTION (optimal): (LeetCode 1657): same letter
# set and same multiset of ...
def both_operations(s, t, alphabet=ALPHABET):
    # swaps make positions irrelevant: only the letter
    # counts matter, and a conversion can only merge or
    # rename a letter
    if len(s) != len(t):
        return False
    cs, ct = Counter(s), Counter(t)
    if cs == ct:
        return True
    mine, goal = list(cs.values()), list(ct.values())
    if not can_group(mine, goal):
        return False
    # only identical sizes mean no merge happens. With
    # every
    # letter used there is no spare letter to rename
    # safely.
    if len(cs) == len(ct) == alphabet:
        return False
    return True


# CHECKER (brute force)
def brute_both(s, t, alphabet):
    # oracle: search every count vector reachable by
    # converting one letter into another
    letters = [chr(97 + i) for i in range(alphabet)]
    start = tuple(s.count(c) for c in letters)
    goal = tuple(t.count(c) for c in letters)
    seen, todo = {start}, [start]
    while todo:
        cur = todo.pop()
        for x in range(alphabet):
            for y in range(alphabet):
                if x != y and cur[x]:
                    nxt = list(cur)
```

```
                    nxt[y] += nxt[x]
                    nxt[x] = 0
                    nxt = tuple(nxt)
                    if nxt not in seen:
                        seen.add(nxt)
                        todo.append(nxt)
    return goal in seen


# FOLLOW-UP 5: Return the sequence of operations, or the
# minimum number.
def min_swaps(s, t):
    # follow-up: fewest swaps when the letters are all
    # different: n minus the number of cycles of the
    # permutation that sorts s into t
    where = {c: i for i, c in enumerate(t)}
    seen, cycles = set(), 0
    for i in range(len(s)):
        if i not in seen:
            cycles += 1
            while i not in seen:
                seen.add(i)
                i = where[s[i]]
    return len(s) - cycles


def swap_sequence(s, t):
    # the swaps themselves (distinct letters): put the
    # right
    # letter into each position, one swap per misplaced
    # one
    cur, steps = list(s), []
    where = {c: i for i, c in enumerate(cur)}
    for i, want in enumerate(t):
        if cur[i] != want:
            j = where[want]
            where[cur[i]] = j
            where[want] = i
            cur[i], cur[j] = cur[j], cur[i]
            steps.append((i, j))
    return steps


if __name__ == "__main__":
    assert swaps_only("listen", "silent")
    assert not swaps_only("abc", "abd")
    assert convert_only("aabcc", "ccdee")
    assert not convert_only("aaabc", "abcaa")
    # a to b and b to a is a cycle: a spare letter is
    # needed
    assert convert_only("ab", "ba")
    assert not convert_only("ab", "ba", alphabet=2)
    assert both_operations("aabb", "ccdd")
    assert both_operations("aab", "ccc")
    assert both_operations("aab", "abb")
    assert both_operations("aabb", "cccc")
    assert not both_operations("aaab", "bbcc")
    # every candidate pair on a 3 letter alphabet and
    # strings up to length 5 against the brute force
    import itertools
    words = [""]
    for n in range(1, 6):
        words += ["".join(p) for p in
                  itertools.product("abc", repeat=n)]
    for s in words:
        for t in words:
            if len(s) == len(t):
                fast = both_operations(s, t, alphabet=3)
                assert fast == brute_both(s, t, 3), (s, t)
    assert min_swaps("abc", "cab") == 2
    assert min_swaps("abcd", "abcd") == 0
    steps = swap_sequence("abcd", "dcba")
    assert len(steps) == min_swaps("abcd", "dcba") == 2
    cur = list("abcd")
    for i, j in steps:
        cur[i], cur[j] = cur[j], cur[i]
    assert "".join(cur) == "dcba"
```

HARD | IN APP LC 4 | Exponent | 126 of 165

★ TOP 75: rank 6 in the Medium and Hard priority list

★ Find the median of two sorted arrays.

ASKED (ANY CO.) ~8 MONTHS AGO | OLDER

STUDY: TYPE | ALL TIME 74.2 | 30 DAYS 61 | PRIORITY 3/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #4)

LeetCode match: LC 4 Median of Two Sorted Arrays (inferred from short statement)

Last asked (any company): 8 months ago, about 2026-02 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/4322/median-of-two-sorted-arrays

QUESTION

Find the median of two sorted arrays.

APPROACH

Binary search the partition on the shorter array so left halves hold the lower half; compare cross elements. O(log(min(m, n))).

HOW TO THINK ABOUT IT

Because both arrays are sorted you never need to merge them. The median splits the combined data into a left half and a right half of equal size; you only have to decide how many elements the shorter array contributes to the left half. Whether a split is right depends on four border values, and moving the split one way or the other is a binary search.

Basis: LeetCode 4, Median of Two Sorted Arrays.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(a, b):
    merged = sorted(a + b)
    n = len(merged)
    if n % 2:
        return merged[n // 2]
    mid = n // 2
    return (merged[mid - 1] + merged[mid]) / 2
```

TIME	SPACE
O((m + n) log(m + n))	O(m + n)

BRUTE FORCE

WHY IT IS SLOW

It sorts m + n numbers from scratch, O((m + n) log(m + n)), and stores them all, even though both inputs were already sorted. The partition binary search needs only O(log min(m, n)).

OPTIMAL SOLUTION · Binary search on the partition

TIME	SPACE
O(log(min(m, n)))	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if there are k sorted arrays instead of two?

Binary search on the answer value instead of on a position. For a candidate value v, count how many elements are <= v in each array with bisect; the median is the smallest v whose total count reaches the middle rank. That costs O(k log n log(range)) time and O(1) extra space and needs no merging.

FOLLOW-UP 2 What if the arrays are too large for memory?

The two-array binary search only touches O(log n) positions, so with random access (an indexed file or a remote array) it reads almost nothing. If only sequential access is possible, do a streaming selection: a two-pointer merge that stops after (m + n) / 2 elements, using O(1) memory and O(m + n) time.

FOLLOW-UP 3 Find the k-th smallest element, not just the median.

The same partition search: choose i elements from the shorter array and k - i from the other, and move i until the borders are in order. The median is just k = (m + n + 1) // 2.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
from bisect import bisect_right

INF = float("inf")


# BASE QUESTION (optimal): Binary search on the partition
# FOLLOW-UP 3: Find the k-th smallest element, not just
# the median.
def kth_of_two(a, b, k):
    # FOLLOW-UP 3: any k-th smallest, not only the median
    # k-th smallest (k starts at 1) of two sorted arrays.
    # Take i items from a and k - i from b so that the
    # borders are in order. Binary search on i: O(log n).
    if len(a) > len(b):
        a, b = b, a
    lo, hi = max(0, k - len(b)), min(k, len(a))
    while lo <= hi:
        i = (lo + hi) // 2
        j = k - i
        a_left = a[i - 1] if i > 0 else -INF
        a_right = a[i] if i < len(a) else INF
        b_left = b[j - 1] if j > 0 else -INF
        b_right = b[j] if j < len(b) else INF
        if a_left > b_right:
            hi = i - 1
        elif b_left > a_right:
            lo = i + 1
        else:
            return max(a_left, b_left)
    raise ValueError("k is out of range")


# BASE QUESTION (optimal): Binary search on the partition
def median_of_two(a, b):
    # the median is the middle item, or the mean of the
    # two
    # middle items when the total is even
    total = len(a) + len(b)
    if total == 0:
        raise ValueError("no data")
    if total % 2:
        return kth_of_two(a, b, total // 2 + 1)
    low = kth_of_two(a, b, total // 2)
    high = kth_of_two(a, b, total // 2 + 1)
    return (low + high) / 2


def count_at_most(arrays, v):
    # how many items are <= v in all the arrays
    return sum(bisect_right(arr, v) for arr in arrays)


# FOLLOW-UP 1: What if there are k sorted arrays instead
# of two?
def kth_of_many(arrays, k):
    # follow-up: k sorted arrays (integers). Binary search
    # the ANSWER value: the k-th smallest is the smallest
    # v
    # that has at least k items <= v.
    arrays = [arr for arr in arrays if arr]
    lo = min(arr[0] for arr in arrays)
    hi = max(arr[-1] for arr in arrays)
    while lo < hi:
        mid = (lo + hi) // 2
        if count_at_most(arrays, mid) >= k:
            hi = mid
        else:
            lo = mid + 1
    return lo


# FOLLOW-UP 1: What if there are k sorted arrays instead
# of two?
def median_of_many(arrays):
    total = sum(len(arr) for arr in arrays)
    if total % 2:
        return kth_of_many(arrays, total // 2 + 1)
    low = kth_of_many(arrays, total // 2)
    high = kth_of_many(arrays, total // 2 + 1)
    return (low + high) / 2


if __name__ == "__main__":
    assert median_of_two([1, 3], [2]) == 2
    assert median_of_two([1, 2], [3, 4]) == 2.5
    assert median_of_two([], [5]) == 5
    assert median_of_two([0, 0], [0, 0]) == 0
    assert kth_of_two([1, 5, 9], [2, 3, 10], 4) == 5
    import random
    for _ in range(300):
```

```
        a = sorted(random.randint(-20, 20)
                   for _ in range(random.randint(0, 6)))
        b = sorted(random.randint(-20, 20)
                   for _ in range(random.randint(0, 6)))
        merged = sorted(a + b)
        if not merged:
            continue
        mid = len(merged) // 2
        if len(merged) % 2:
            want = merged[mid]
        else:
            want = (merged[mid - 1] + merged[mid]) / 2
        assert median_of_two(a, b) == want
        for k in range(1, len(merged) + 1):
            assert kth_of_two(a, b, k) == merged[k - 1]
    arrays = [[1, 4, 7], [2, 5], [3, 6, 8, 9]]
    assert median_of_many(arrays) == 5
    assert kth_of_many(arrays, 2) == 2
    assert median_of_many([[1, 2], [], [3, 4]]) == 2.5
```

OFFICIAL PAGE TEXT

Upgrade to see our video answerBecome a member today100+ expert answer videosAccess to all coursesPeer-to-peer practicePrivate Discord communityFull question databaseUpgrade now

HARD | DESIGN-STYLE (skippable) | Exponent | 127 of 165

Implement a function that processes a stream of interval data.

ASKED (ANY CO.) ~A YEAR AGO | OLDER

STUDY: TALK | ALL TIME 8.1 | 30 DAYS 0 | PRIORITY 165/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 352 Data Stream as Disjoint Intervals (likely) (inferred from short statement)

Last asked (any company): a year ago, about 2025-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/6245/implement-function-process-interval-data

QUESTION

Implement a function that processes a stream of interval data.

APPROACH

Maintain sorted disjoint intervals in a TreeMap/sorted list; on each new interval find neighbors with binary search and merge. O(log n) per update.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what the function must do per interval: merge and return the current union, return total covered length, or answer point queries. Ask whether touching intervals (end equals next start) merge, whether endpoints are inclusive, and whether intervals can arrive unsorted.

BRUTE FORCE TO SAY OUT LOUD

Keep all intervals in a list and re-sort and merge on each arrival. O(n log n) per interval.

OPTIMAL IDEA

Keep disjoint intervals sorted by start. For a new interval, binary search for the first interval whose end is at least the new start and the last whose start is at most the new end; replace that slice with one merged interval. A sorted list gives O(log n) search with O(n) splice, a balanced tree gives O(log n) overall.

DRY-RUN THESE CASES

Interval inside an existing one, one that bridges two, one that touches exactly, one before everything and one after everything.

LIKELY FOLLOW-UPS

Removing a range (LeetCode 715), counting covered length incrementally, or a memory bound on the stream.

PITFALLS

Off-by-one on touching intervals. Splicing the wrong slice. Forgetting to keep the total length updated.

HOW TO THINK ABOUT IT

Keep the data in its simplest canonical form: merged intervals sorted by start with gaps between them. A new interval can only touch a contiguous block of existing ones, found with two binary searches, and that block collapses into one interval. State what 'touching' means before you code (shared endpoint, or only real overlap).

Basis: LeetCode 352, Data Stream as Disjoint Intervals (generalized from single numbers to whole intervals).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
intervals = []
def add(start, end):
    intervals.append((start, end))
def query():
    merged = []
    for s, e in sorted(intervals):
        if merged and s <= merged[-1][1]:
            last = merged[-1]
            last[1] = max(last[1], e)
        else:
            merged.append([s, e])
    return merged
```

BRUTE FORCE

TIME	SPACE
O(n log n) per query	O(n)

WHY IT IS SLOW

Every query re-sorts and re-merges the whole history, O(n log n) per query. Keeping the merged intervals sorted and only splicing the affected block makes an add cost O(log n) to find plus the shifted block.

OPTIMAL SOLUTION · Sorted disjoint intervals with binary search

TIME	SPACE
O(log n) to find the spot, O(n) worst-case list shift	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How do you keep adds fast for a very large number of intervals?

Use an ordered map (TreeMap, or a balanced tree / skip list in Python via the sortedcontainers package) keyed by start so a merge removes the swallowed intervals in amortized O(log n) instead of shifting an array. Each interval is inserted once and removed at most once, so n adds cost O(n log n) overall.

FOLLOW-UP 2 Should touching intervals such as [1, 3] and [4, 5] merge?

Agree on the semantics first. For integer points, [1, 3] and [4, 5] cover every point from 1 to 5, so they merge; use bisect_left(self.ends, start - 1). For real-valued closed intervals only overlap or a shared endpoint merges, which is what the code above does. For half-open intervals [a, b), a shared endpoint merges but nothing else does.

FOLLOW-UP 3 Answer 'is this point covered?' and 'how much is covered in total?'

The sorted disjoint intervals already support both: a point is covered if the interval with the largest start at or before it ends at or after it (one bisect), and the total length is the sum of the interval lengths (or keep it updated on each add).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left, bisect_right


# BASE QUESTION (optimal): Sorted disjoint intervals with
# binary search
# FOLLOW-UP 3: Answer 'is this point covered?' and 'how
# much is covered in total?'
class IntervalSet:
    """Keeps closed intervals merged and sorted.
    integer=True: [1, 3] and [4, 5] cover 1..5 and merge.
    integer=False: only overlap or a shared end merges."""

    def __init__(self, integer=True):
        self.starts, self.ends = [], []
        self.gap = 1 if integer else 0
        # length of [a, b] is b - a + extra
        self.extra = 1 if integer else 0
        self.covered = 0

    def length(self, start, end):
        return end - start + self.extra

    def add(self, start, end):
        if end < start:
            raise ValueError("bad interval")
        # first interval that touches the new one, and the
        # first one that is completely to its right
        i = bisect_left(self.ends, start - self.gap)
        j = bisect_right(self.starts, end + self.gap)
        for k in range(i, j):
            # the swallowed intervals leave the total ...
            self.covered -= self.length(self.starts[k],
                                        self.ends[k])
        if i < j:
            start = min(start, self.starts[i])
            end = max(end, self.ends[j - 1])
        # ... and the merged one joins it
        self.starts[i:j] = [start]
        self.ends[i:j] = [end]
        self.covered += self.length(start, end)

    # FOLLOW-UP 3: is this point covered?
    def contains(self, point):
        # the interval with the largest start <= point
        i = bisect_right(self.starts, point) - 1
        return i >= 0 and self.ends[i] >= point

    # FOLLOW-UP 3: how much is covered in total?
    def total(self):
        return self.covered

    def intervals(self):
        return list(zip(self.starts, self.ends))


# FEED a stream and print each step
def process(stream, integer=True):
    # feed the stream; yield the merged list after each
    # add
    cover = IntervalSet(integer)
    for start, end in stream:
        cover.add(start, end)
        yield cover.intervals()


if __name__ == "__main__":
    feed = [(1, 3), (8, 10), (4, 5), (6, 7)]
    steps = list(process(feed))
    assert steps[0] == [(1, 3)]
    assert steps[1] == [(1, 3), (8, 10)]
    # (4, 5) touches (1, 3) for integers; (6, 7) then
    # touches both sides, so everything becomes one
    assert steps[2] == [(1, 5), (8, 10)]
    assert steps[3] == [(1, 10)]
    real = list(process([(1, 3), (4, 5), (3, 4)], False))
    assert real[1] == [(1, 3), (4, 5)]
```

```
assert real[2] == [(1, 5)]
box = IntervalSet()
for pair in [(5, 8), (1, 2), (3, 4), (20, 21)]:
    box.add(*pair)
assert box.intervals() == [(1, 8), (20, 21)]
assert box.total() == 10
assert box.contains(7) and box.contains(20)
assert not box.contains(9) and not box.contains(0)
import random
for _ in range(200):
    box, points = IntervalSet(), set()
    for _ in range(random.randint(1, 8)):
        a = random.randint(0, 30)
        b = a + random.randint(0, 6)
```

```
        box.add(a, b)
        points |= set(range(a, b + 1))
        assert box.total() == len(points)
    for p in range(-1, 40):
        assert box.contains(p) == (p in points)
```

HARD | Exponent | 128 of 165

Implement a decode and encode function of a general N-ary tree.

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TALK | ALL TIME 18.1 | 30 DAYS 0 | PRIORITY 151/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 428 Serialize and Deserialize N-ary Tree (inferred from short statement)

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/4516/decode-encode-function-general-tree

QUESTION

Implement a decode and encode function of a general N-ary tree.

APPROACH

Pre-order with child counts (value, numChildren) or a sentinel marker for end of children; rebuild recursively/with a queue. O(n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the node shape (value plus list of children), the value type and range, whether values can contain delimiters, how to represent a null tree, and whether the format must be a string.

BRUTE FORCE TO SAY OUT LOUD

Serialize with nested brackets like 1[2,3[4]]. Easy to say but needs a parser and breaks if values contain brackets.

INTERVIEW-DAY PLAN

OPTIMAL IDEA

Pre-order with child counts: write value then number of children, then each child recursively. To decode, read a value and a count, then recursively decode count children. Using a queue or iterator over tokens avoids index bookkeeping. O(n) time and space. For arbitrary string values length-prefix each value.

DRY-RUN THESE CASES

Empty tree, single node, a deep chain (watch recursion depth), a root with many children, negative or multi-digit values.

LIKELY FOLLOW-UPS

Make the format compact, avoid recursion for deep trees (explicit stack), or encode in BFS order.

PITFALLS

Using a plain delimiter that can appear in the data. Not handling the empty tree. Reading tokens past the end on malformed input.

HOW TO THINK ABOUT IT

Serialization questions are about a format that can be read back unambiguously. Ask what a node holds and whether values can contain your delimiters. A node can have any number of children, so the decoder must be told where the children end: either with a closing marker or by writing the child count next to each value. The count form needs no closing markers and can be decoded with an explicit stack, so deep trees are safe.

Basis: LeetCode 428, Serialize and Deserialize N-ary Tree.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def encode(node):
    parts = [encode(c) for c in node.children]
    kids = ",".join(parts)
    return f"{node.val}[{kids}]"
def decode(text):
    pos = 0
    def parse():
        nonlocal pos
        start = pos
        while text[pos] != "[":
            pos += 1
        node = Node(text[start:pos])
        pos += 1  # skip "["
        while text[pos] != "]":
            node.children.append(parse())
            if text[pos] == ",":
                pos += 1
        pos += 1  # skip "]"
        return node
    return parse()
```

TIME	SPACE
O(n * h) for building strings (O(n) with a list buffer)	**O(n)**

WHY IT IS SLOW

BRUTE FORCE

Joining child strings copies text at every level (O(n * h) in the worst case) and the recursive parser can overflow on a deep tree; values containing brackets or commas break it. Pre-order with child counts is O(n) and needs no markers.

OPTIMAL SOLUTION · Pre-order with child counts, iterative decode

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The values are arbitrary strings that may contain spaces, commas or brackets.

Do not invent delimiters. Put the values in a real container: a JSON list of alternating value and child count, which handles quoting for you, or length-prefix every value (5#hello). The structure part (the counts) stays the same.

FOLLOW-UP 2 The tree is huge and you want a compact binary encoding.

Counts and node values can be packed with variable-length integers (varint), which makes small values one byte. Keep the same pre-order count layout so decoding is still one pass. Add a version byte at the front so the format can change later. **Cost:** still O(n) time and space; variable-length integers cost about one byte per small value.

FOLLOW-UP 3 Encode in level order instead.

Write each node's value and child count in BFS order and decode with a queue: pop a parent, read its count, attach that many new nodes, and push them. BFS order is handy when the consumer wants to stream levels.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import json
from collections import deque


class Node:
    def __init__(self, val, children=None):
        self.val = val
        self.children = children or []


def preorder_pairs(root):
    # (value, number of children) for every node in pre-
    # order,
    # iterative so a very deep tree cannot overflow the
    # stack
    out = []
    stack = [root] if root else []
    while stack:
        node = stack.pop()
        out.append((node.val, len(node.children)))
        # reversed: the first child must be popped first
        stack.extend(reversed(node.children))
    return out


def build_preorder(pairs):
    # the reverse: rebuild the tree from the same pairs
    pairs = iter(pairs)
    first = next(pairs, None)
    if first is None:
        return None
    root = Node(first[0])
    # each stack entry is a parent and the children it
    # still has to receive
    stack = [[root, first[1]]]
    while stack:
        top = stack[-1]
        if top[1] == 0:
            stack.pop()
            continue
        top[1] -= 1
        val, count = next(pairs)
        child = Node(val)
        top[0].children.append(child)
        stack.append([child, count])
    return root


# BASE QUESTION (optimal): Pre-order with child counts,
# iterative decode
# FOLLOW-UP 1: The values are arbitrary strings that may
# contain spaces, commas or ...
def encode(root):
    # FOLLOW-UP 1: arbitrary string values
    # values may hold spaces, commas or brackets: JSON
    # does
    # the quoting, so no invented delimiter can clash
    flat = []
    for val, count in preorder_pairs(root):
        flat += [val, count]
    return json.dumps(flat)


# BASE QUESTION (optimal): Pre-order with child counts,
# iterative decode
def decode(text):
    flat = json.loads(text)
    return build_preorder(zip(flat[::2], flat[1::2]))


# FOLLOW-UP 3: Encode in level order instead.
def level_pairs(root):
    # follow-up: the same pairs in level order (BFS)
    out, queue = [], deque([root] if root else [])
    while queue:
        node = queue.popleft()
        out.append((node.val, len(node.children)))
        queue.extend(node.children)
    return out


# FOLLOW-UP 3: Encode in level order instead.
def build_levels(pairs):
    # decode with a queue: pop a parent, attach its
    # children
    pairs = iter(pairs)
    first = next(pairs, None)
```

```
    if first is None:
        return None
    root = Node(first[0])
```

```
    queue = deque([(root, first[1])])
    while queue:
        parent, count = queue.popleft()
        for _ in range(count):
            val, kids = next(pairs)
            child = Node(val)
            parent.children.append(child)
            queue.append((child, kids))
    return root


def put_varint(n, out):
    # follow-up: a compact binary form. 7 bits per byte,
    # the
    # top bit says that another byte follows
    while n >= 128:
        out.append(n % 128 + 128)
        n //= 128
    out.append(n)


def get_varint(data, pos):
    n, shift = 0, 0
    while data[pos] >= 128:
        n += (data[pos] - 128) << shift
        shift += 7
        pos += 1
    return n + (data[pos] << shift), pos + 1


# FOLLOW-UP 2: The tree is huge and you want a compact
# binary encoding.
def encode_binary(root):
    # a version byte first, so the format can change later
    out = bytearray([1])
    for val, count in preorder_pairs(root):
        raw = val.encode("utf-8")
        put_varint(len(raw), out)
        out += raw
        put_varint(count, out)
    return bytes(out)


# FOLLOW-UP 2: The tree is huge and you want a compact
# binary encoding.
```

```
def decode_binary(data):
    if data[0] != 1:
        raise ValueError("unknown version")
    pairs, pos = [], 1
    while pos < len(data):
        size, pos = get_varint(data, pos)
        val = data[pos:pos + size].decode("utf-8")
        count, pos = get_varint(data, pos + size)
        pairs.append((val, count))
    return build_preorder(pairs)


def same(a, b):
    return preorder_pairs(a) == preorder_pairs(b)


if __name__ == "__main__":
    tree = Node("a, b", [
        Node("[x]", [Node("")]), Node("é ??"),
        Node('q"uote', [Node("1"), Node("2")])])
    assert same(decode(encode(tree)), tree)
    assert same(build_levels(level_pairs(tree)), tree)
    assert same(decode_binary(encode_binary(tree)), tree)
```

```
    assert encode(None) == "[]" and decode("[]") is None
    assert decode_binary(encode_binary(None)) is None
    assert build_levels(level_pairs(None)) is None
    # a very deep chain works because nothing is recursive
    chain = Node("0")
    cur = chain
    for i in range(1, 5000):
        cur.children.append(Node(str(i)))
        cur = cur.children[0]
    assert same(decode(encode(chain)), chain)
    # a node with 300 children needs a two byte count
    wide = Node("w", [Node(str(i)) for i in range(300)])
    assert same(decode_binary(encode_binary(wide)), wide)
    assert len(preorder_pairs(wide)) == 301
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

HARD | IN APP LC 523 | Exponent | 129 of 165

Given an integer array nums and an integer k, return true if nums has a subarray of at least two elements whose sum is a multiple of k.

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TALK ALL TIME 25.5 30 DAYS 0 PRIORITY 134/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #523)

LeetCode match: LC 523 Continuous Subarray Sum

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age) | +610 interviews

Original: https://www.aced.io/questions/2765/subarray-sum-multiple-of-k

QUESTION

Determine if a given array contains a subarray of at least two elements whose sum is a multiple of a specified number k. An array is considered to have a "good subarray" if there exists at least one subarray (consisting of two or more elements) such that the sum of the elements in this subarray is a multiple of k. For example, the array [23, 2, 4, 7] with k = 6 has a "good subarray" ([2, 4]), as the sum 6 is a multiple of k = 6. The array [5, 0, 0, 0] with k = 3 also has a "good subarray" ([0, 0]), since the sum is 0, and 0 is a multiple of 3. Examples nums = [23, 2, 4, 7], k = 6 output: true nums = [5, 0, 0, 0], k = 3 output: true nums = null, k = 1 output: false In these examples, the output is true if there exists a "good subarray" in the given array nums for the specified k, and false otherwise.Challenge 1Can you come up with a solution with a time complexity of O(n)?Challenge 2Can you come up with a solution with a space complexity of O(n)?

APPROACH

Prefix sum mod k with a hash map of first-seen index; a repeat remainder at distance >= 2 means a valid subarray. Handle k = 0 and the remainder-0 case with {0: -1}. O(n).

HOW TO THINK ABOUT IT

A subarray sum is a difference of two prefix sums, and a multiple of k means the two prefix sums have the same remainder mod k. So remember the first index at which each remainder appeared; seeing it again at least two positions later gives a subarray of length at least two. Seed the table with remainder 0 at index -1 for subarrays that start at the beginning.

Basis: LeetCode 523, Continuous Subarray Sum: a subarray of at least two elements whose sum is a multiple of k. Assumed edge cases: nums null or shorter than 2 gives false; k = 0 means the sum must be 0.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(nums, k):
    for i in range(len(nums)):
        total = nums[i]
        for j in range(i + 1, len(nums)):
            total += nums[j]
            if total % k == 0:
                return True
    return False
```

TIME	SPACE
O(n^2)	O(1)

WHY IT IS SLOW

O(n^2) pairs. Two prefix sums with the same remainder mod k bound a subarray whose sum is a multiple of k, so a dictionary of first-seen remainders is O(n).

OPTIMAL SOLUTION · Prefix sums mod k with the first index of each remainder

TIME	SPACE
O(n)	O(min(n, k))

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Count the subarrays whose sum is a multiple of k (any length, LeetCode 974).

Count how many times each remainder has occurred and add that count each time the remainder repeats (Python's % is already non-negative for negative sums). O(n).

FOLLOW-UP 2 Why store only the first index of each remainder?

A later occurrence of the same remainder would make the subarray shorter, never longer, so the first index is the best partner for the length-at-least-two condition.

FOLLOW-UP 3 The values can be negative or k huge.

Python's modulo gives a non-negative remainder; in languages where % can be negative normalise with ((s % k) + k) % k. A huge k just means the dictionary holds up to n entries. **Cost:** O(n) time with up to min(n, k) dictionary entries.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Prefix sums mod k with the
# first index of each remainder
def has_good_subarray(nums, k):
    # prefix sums modulo k: two equal remainders at
    # indexes
    # at least 2 apart mean a block of 2 or more items
    # whose
    # sum is a multiple of k. Keep only the FIRST index of
    # each remainder: a later one only gives a shorter
    # block.
    first = {0: -1}
    total = 0
    for i, x in enumerate(nums):
        total += x
        # k == 0 means "equal to zero": compare the sums
        key = total % k if k else total
        if key not in first:
            first[key] = i
        elif i - first[key] >= 2:
            return True
    return False


# RETURN the subarray itself
def find_good_subarray(nums, k):
    # the same scan, but return the (start, end) indexes
    first = {0: -1}
    total = 0
    for i, x in enumerate(nums):
        total += x
        key = total % k if k else total
        if key not in first:
            first[key] = i
        elif i - first[key] >= 2:
            return first[key] + 1, i
    return None


# FOLLOW-UP 1: Count the subarrays whose sum is a multiple
# of k (any length ...
def count_multiples(nums, k):
    # follow-up (LeetCode 974): count the subarrays of any
    # length whose sum is a multiple of k. Python's % is
    # never
    # negative; elsewhere use ((s % k) + k) % k.
    seen = {0: 1}
    total = answer = 0
    for x in nums:
        total += x
```

```
        key = total % k
        # every earlier equal remainder is one more
        # subarray
        answer += seen.get(key, 0)
        seen[key] = seen.get(key, 0) + 1
    return answer


# CHECKER (brute force)
def brute_good(nums, k):
    # oracle: try every block of at least two items
    for i in range(len(nums)):
        total = nums[i]
        for j in range(i + 1, len(nums)):
            total += nums[j]
            if (total % k == 0) if k else total == 0:
                return True
    return False


if __name__ == "__main__":
    assert has_good_subarray([23, 2, 4, 7], 6)
    assert has_good_subarray([23, 2, 6, 4, 7], 6)
    assert not has_good_subarray([23, 2, 6, 4, 7], 13)
    assert find_good_subarray([23, 2, 4, 7], 6) == (1, 2)
    # a single item is not enough, even for 0 and k
    assert not has_good_subarray([6], 6)
    assert has_good_subarray([0, 0], 5)
    assert not has_good_subarray([0, 1, 0], 0)
    assert has_good_subarray([0, 0], 0)
    assert has_good_subarray([5, -5], 7)
    assert has_good_subarray([1, 2], 10 ** 9) is False
    assert count_multiples([4, 5, 0, -2, -3, 1], 5) == 7
    import random
    for _ in range(500):
        nums = [random.randint(-6, 6)
                for _ in range(random.randint(0, 7))]
        k = random.randint(0, 6)
        want = brute_good(nums, k)
        assert has_good_subarray(nums, k) == want
```

OFFICIAL PAGE TEXT

Determine if a given array contains a subarray of at least two elements whose sum is a multiple of a specified number k. An array is considered to have a "good subarray" if there exists at least one subarray (consisting of two or more elements) such that the sum of the elements in this subarray is a multiple of k. For example, the array [23, 2, 4, 7] with k = 6 has a "good subarray" ([2, 4]), as the sum 6 is a multiple of k = 6. The array [5, 0, 0, 0] with k = 3 also has a "good subarray" ([0, 0]), since the sum is 0, and 0 is a multiple of 3. Examples

```
nums = [23, 2, 4, 7], k = 6
output: true

nums = [5, 0, 0, 0], k = 3
output: true

nums = null, k = 1
output: false
```

OFFICIAL PAGE TEXT

In these examples, the output is true if there exists a "good subarray" in the given array nums for the specified k, and false otherwise.Challenge 1Can you come up with a solution with a time complexity of O(n)?Challenge 2Can you come up with a solution with a space complexity of O(n)?Our solution processes the input array by iterating through it while maintaining a hash map (remainder_index_map) of remainders and their corresponding indices. For each element in the array, we accumulate the sum (sum_so_far) and compute the remainder when divided by k. We check if this remainder has been encountered before in the hash map. If the remainder is not in the hash map, we store the current index associated with this remainder. If the remainder has been seen before, we calculate the distance between the current index and the index of the previously seen remainder. If this distance is greater than or equal to the minimum subarray length (MIN_GOOD_SUBARRAY_LIMIT), we return True, indicating that a subarray with the required properties exists. If the loop completes without finding such a subarray, we return False. The use of a hash map ensures that each element is processed efficiently, as it allows constant-time lookups and insertions. Time Complexity: The solution has a time complexity of O(n), where n is the

number of elements in the array. This is because we iterate through the array once, performing constant-time operations (hash map lookups and insertions) for each element. Space Complexity: The solution uses O(n) space for the hash map that stores the remainders and their indices. In the worst case, all remainders are unique, resulting in the hash map containing n entries.Let’s say you are given an integer array nums and an integer k. Return true if nums has a subarray where its length is at least two, and the sum of the elements in the subarray is a multiple of k. Watch Neeraj, a Senior Engineering Manager, give his answer to this software engineering interview question.No answers contributed by the community yet.Related questionsGiven an array of n integers and a number k, find the maximum number of elements whose sum is less than k, and return their sum.Given an array of integers and an integer k, find the number of continuous subarrays whose sum equals k.Given an array of integers and a number N, find the length of the longest contiguous subarray such that the difference between any two elements in the subarray is less than N.Related coursesCourseCourseMachine Learning Engineer Interview PrepLand your dream machine learning role at Meta, Google, Amazon, Apple, Microsoft, Nvidia, and other top companies. Learn from

OFFICIAL PAGE TEXT

mock interviews, frameworks, and advice from senior candidates. Explore ML system design, core concepts, coding, behavioral interviews, and more.Start learningCourseCourseData Science Interview PrepLand your dream data science role at Google, Amazon, Microsoft, Meta, Apple, and other top companies. Learn from mock interviews, frameworks, and advice from senior candidates. Practice statistics, experimentation, coding, SQL, machine learning, behavioral interviews, and more.Start learningPythonJavaScript JavaC++PythonEditorShareLoading...OutputTest ResultsConsoleSign up to run code

---

HARD | IN APP LC 68 | Exponent | 130 of 165

★ TOP 75: rank 56 in the Medium and Hard priority list

★ Implement a function to justify a list of words within a given width.

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TYPE | ALL TIME 44.7 | 30 DAYS 0 | PRIORITY 78/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #68)

LeetCode match: LC 68 Text Justification (inferred from short statement)

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/4903/function-justify-words-within-width

QUESTION

Implement a function to justify a list of words within a given width.

APPROACH

Greedily pack words per line; distribute spaces evenly (extra to the leftmost gaps), left-justify the last line and single-word lines. O(total chars).

HOW TO THINK ABOUT IT

Two decisions, kept separate: which words go on each line (pack greedily while the words plus one space between them fit), and how to spread the leftover spaces (an equal share in each gap, the extra spaces to the leftmost gaps). The last line and one-word lines are the special cases to name before coding.

Basis: LeetCode 68, Text Justification.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def justify(words, width):
    lines, i = [], 0
    while i < len(words):
        j = i + 1
        while j < len(words):
            if not fits(words[i:j + 1], width):
                break
            j += 1
        last = j == len(words)
        row = format_line(words[i:j],
                          width, last)
        lines.append(row)
        i = j
    return lines
```

TIME	SPACE
O(total characters * words per line)	O(width)

WHY IT IS SLOW

Every attempt to add a word re-joins the whole line to measure it, so each line costs about (words per line) times its length. Tracking only a running length makes it linear in the total characters.

OPTIMAL SOLUTION · Greedy line packing

TIME	SPACE
O(total characters)	O(total characters)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How would you change it to fully justify the last line too, or to center the text?

Only the final-line branch changes. For full justification drop the special case for the last line (it would be spread like every other line). For centering, split the leftover spaces between the two sides, giving the extra space to the right. The greedy packing step stays identical.

FOLLOW-UP 2 What if the words contain wide characters or different pixel widths?

Replace len(word) by a measure(word) function (for example font metrics or East Asian width) and compare against the pixel width. Packing and distribution logic stay the same; spaces are measured in the same unit, so the spare width may not divide evenly and the remainder must be assigned to gaps in whole space units.

FOLLOW-UP 3 Fully justify the last line too.

Drop the special case for the last line (a line with more than one word is spread like the others). Single-word lines stay left-aligned.

FOLLOW-UP 4 Words have pixel widths (a proportional font).

Replace len(word) with a measure function and compare against the pixel width; the extra space is distributed in whole space units, so the remainder rule stays the same.

FOLLOW-UP 5 Minimise raggedness instead of packing greedily.

That is the Knuth-Plass style DP: cost of a line = (spare space)^2, minimise the total over all ways to break the text. O(n * words per line).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# FOLLOW-UP 2, 4: What if the words contain wide
# characters or different pixel widths?
def pack_greedy(words, width, measure=len):
    # put as many words as fit on every line
    lines, line, used = [], [], 0
    for w in words:
        size = measure(w)
        # `used` counts the words and one space between
        # each
        if line and used + 1 + size > width:
            lines.append(line)
            line, used = [], 0
        used += size + (1 if line else 0)
        line.append(w)
    if line:
        lines.append(line)
    return lines


# FOLLOW-UP 2, 4: What if the words contain wide
# characters or different pixel widths?
def spread(line, width, measure=len):
    # fully justified: spaces between the words, extra
    # ones
    # go to the LEFT gaps first. One word stays left-
    # aligned.
    if len(line) == 1:
        return line[0] + " " * (width - measure(line[0]))
    spaces = width - sum(measure(w) for w in line)
    gaps = len(line) - 1
    each, extra = divmod(spaces, gaps)
    out = ""
    for i, w in enumerate(line[:-1]):
        out += w + " " * (each + (1 if i < extra else 0))
    return out + line[-1]


def left_align(line, width, measure=len):
    text = " ".join(line)
    return text + " " * (width - measure(text))


def center(line, width, measure=len):
    # leftover spaces split on both sides, the odd one
    # right
```

```
    text = " ".join(line)
    spare = width - measure(text)
    left = spare // 2
    return " " * left + text + " " * (spare - left)
```

```
# BASE QUESTION (optimal): Greedy line packing
# FOLLOW-UP 1, 3: How would you change it to fully justify
# the last line too, or to ...
def justify(words, width, last="left", measure=len,
            lines=None):
    # last: "left" (the classic rule), "full" (spread it
    # too)
    # or "center". `lines` lets the caller bring its own
    # line breaks (see pack_optimal).
    lines = lines or pack_greedy(words, width, measure)
    out = []
    for i, line in enumerate(lines):
        if i < len(lines) - 1:
            out.append(spread(line, width, measure))
        # FOLLOW-UP 1, 3: justify the last line too
        elif last == "full":
            out.append(spread(line, width, measure))
        # FOLLOW-UP 1: centre the last line
        elif last == "center":
            out.append(center(line, width, measure))
        else:
            out.append(left_align(line, width, measure))
    return out


def raggedness(lines, width):
    # sum of the squares of the unused space (last line
    # free)
    cost = 0
    for line in lines[:-1]:
        cost += (width - len(" ".join(line))) ** 2
    return cost


# FOLLOW-UP 5: Minimise raggedness instead of packing
# greedily.
def pack_optimal(words, width):
    # follow-up: choose line breaks that minimise the
    # total
```

```
    # raggedness (Knuth-Plass idea). best[i] is the
    # cheapest
    # way to set the first i words.
    n = len(words)
    best = [0] + [float("inf")] * n
    prev = [0] * (n + 1)
    for i in range(1, n + 1):
        size = -1
        # a line holds words j..i-1, try the longest first
        for j in range(i - 1, -1, -1):
            size += len(words[j]) + 1
            if size > width:
                break
            cost = 0 if i == n else (width - size) ** 2
            if best[j] + cost < best[i]:
                best[i], prev[i] = best[j] + cost, j
    lines, i = [], n
    while i > 0:
        lines.append(words[prev[i]:i])
        i = prev[i]
    return lines[::-1]


if __name__ == "__main__":
    text = ("This is an example of text justification."
            ).split()
    got = justify(text, 16)
    assert got == ["This    is    an", "example  of text",
                   "justification.  "]
    words = "What must be acknowledgment shall be".split()
    got = justify(words, 16)
    assert got == ["What   must   be", "acknowledgment  ",
```

```
                "shall be        "]
assert all(len(line) == 16 for line in got)
full = justify(words, 16, last="full")
assert full[2] == "shall         be"
mid = justify(words, 16, last="center")
assert mid[2] == "    shall be    "
assert justify(["a"], 3) == ["a  "]
assert justify([], 5) == []
# pixel widths: every character is 2 units wide
wide = justify(["ab", "cd", "ef"], 12,
               measure=lambda s: 2 * len(s))
assert wide == ["ab    cd", "ef" + " " * 8]
import random
```

```
for _ in range(200):
    ws = ["x" * random.randint(1, 6)
          for _ in range(random.randint(1, 9))]
    width = 8
    greedy = pack_greedy(ws, width)
    best = pack_optimal(ws, width)
    assert sum(best, []) == ws
    fits = [len(" ".join(ln)) for ln in best]
    assert max(fits) <= width
    assert raggedness(best, width) <= raggedness(
        greedy, width)
```

Medium (16)

MEDIUM | Exponent | 131 of 165

Given a train schedule with departure city, arrival city, start time, end time, and duration, and given a source and destination, find the sequence of trains that gets you there at the earliest possible time.

ASKED (ANY CO.) ~6 MONTHS AGO | OLDER

STUDY: TYPE | ALL TIME 37.9 | 30 DAYS 33 | PRIORITY 60/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #743 Network Delay Time, LeetCode #787 Cheapest Flights Within K Stops

LeetCode match: No direct match; related LC 743 Network Delay Time, LC 787 (inferred from short statement)

Last asked (any company): 6 months ago, about 2026-04 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/6331/find-earliest-train-sequence-route

QUESTION

Given a train schedule with departure city, arrival city, start time, end time, and duration, and given a source and destination, find the sequence of trains that gets you there at the earliest possible time.

APPROACH

Dijkstra over (city, arrival time): from a city at time t, take a train whose start time >= t and relax the arrival time. Reconstruct the train sequence with parent pointers.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether you may wait at stations, whether transfers need a minimum time, whether the start time is given, and what to return (the sequence of trains and the arrival time).

BRUTE FORCE TO SAY OUT LOUD

DFS over all train sequences and keep the earliest arrival. Exponential.

OPTIMAL IDEA

Dijkstra on arrival times. Keep earliest[city] and a min-heap of (time, city). From a city at time t, relax every train departing at or after t, giving arrival at the train's end time. Waiting is free, so earliest arrival is always better. Store the train used to reach each city and reconstruct the sequence by following parents. O((V + E) log V).

DRY-RUN THESE CASES

No route, a train that departs just before you arrive (cannot be taken), two trains to the same city with different arrival times, the source equals the destination.

LIKELY FOLLOW-UPS

Fewest transfers, cheapest fare, a minimum layover, or time zone changes.

PITFALLS

Using the train's duration as an edge weight and ignoring departure times. Allowing a train that has already left.

HOW TO THINK ABOUT IT

Waiting is free, so arriving earlier at a city is never worse than arriving later: that is exactly the property Dijkstra needs. Keep the earliest known arrival time per city in a heap, and from a city at time t relax only the trains that depart at or after t. Remember which train gave each improvement to rebuild the sequence.

Basis: Written; earliest-arrival path in a time-dependent graph (Dijkstra on arrival times, compare LeetCode 743 and 787). Assumed rules (confirm them): a train (from, to, depart, arrive) can be boarded if you are at its origin at or before its departure; waiting is free; no minimum transfer time.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
best = INF
def go(city, time):
    global best
    if city == destination:
        best = min(best, time)
    for tr in trains_from(city):
        if tr.dep >= time:
            go(tr.dst, tr.arr)
```

TIME	SPACE
exponential	O(trains)

WHY IT IS SLOW

The number of train sequences can be exponential. Because waiting is free, an earlier arrival is never worse, so Dijkstra on earliest arrival times is O((T + C) log C).

OPTIMAL SOLUTION · Dijkstra on earliest arrival times, with the train sequence

TIME	SPACE
O((T + C) log C) with trains sorted by departure per city	O(T + C)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 A minimum layover is required when changing trains.

Replace the boarding test dep >= t with dep >= t + layover for every city except the origin. The earliest-arrival property still holds (a later arrival never helps because the layover is the same), so Dijkstra remains valid.

FOLLOW-UP 2 Fewest transfers instead of earliest arrival.

Run BFS over (city) counting trains taken, but track the earliest arrival for each count (a state is (city, number of trains)). Or Dijkstra with the pair (transfers, arrival time) compared lexicographically.

FOLLOW-UP 3 The schedule repeats daily.

Add the day to the time (departure + 24h * k) or treat times modulo 24h and carry the day count. The same Dijkstra works on absolute times.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq

DAY = 24 * 60   # times are minutes from midnight


class Train:
    def __init__(self, src, dst, dep, arr):
        self.src, self.dst = src, dst
        self.dep, self.arr = dep, arr


# BASE QUESTION (optimal): Dijkstra on earliest arrival
# times, with the train sequence
# FOLLOW-UP 1: A minimum layover is required when changing
# trains.
def earliest_route(trains, source, target, layover=0):
    # Dijkstra on arrival time. You may board a train if
    # it
    # leaves at or after your arrival plus the layover (no
    # layover is needed at the origin).
    by_city = {}
    for tr in trains:
        by_city.setdefault(tr.src, []).append(tr)
    best = {source: 0}
    took = {}
    heap = [(0, source)]
    while heap:
        time, city = heapq.heappop(heap)
        if time > best.get(city, float("inf")):
            continue
        if city == target:
            break
        # FOLLOW-UP 1: a minimum layover when changing
        # trains
        wait = 0 if city == source else layover
        for tr in by_city.get(city, []):
            old = best.get(tr.dst, float("inf"))
            if tr.dep >= time + wait and tr.arr < old:
                best[tr.dst] = tr.arr
                took[tr.dst] = tr
                heapq.heappush(heap, (tr.arr, tr.dst))
    if target not in best:
        return None
    # walk back from the target to list the trains used
    path, city = [], target
    while city != source:
        path.append(took[city])
        city = took[city].src
    return best[target], path[::-1]


# FOLLOW-UP 2: Fewest transfers instead of earliest
# arrival.
def fewest_trains(trains, source, target, layover=0):
    # follow-up: fewest transfers. Round k holds the
    # earliest
    # arrival at every city using at most k trains.
    best = {source: (0, [])}
    for _ in range(len(trains)):
        step = dict(best)
        for tr in trains:
            if tr.src not in best:
                continue
            time, path = best[tr.src]
            wait = 0 if tr.src == source else layover
            if tr.dep < time + wait:
                continue
            old = step.get(tr.dst)
            if old is None or tr.arr < old[0]:
                step[tr.dst] = (tr.arr, path + [tr])
        if target in step:
            return step[target]
        best = step
```

```
    return None


# FOLLOW-UP 3: The schedule repeats daily.
def daily(trains, days):
    # follow-up: the timetable repeats every day. Unroll
    # it
    # into absolute times; a train that arrives after
    # midnight has an arrival earlier than its departure.
    out = []
    for d in range(days):
        for tr in trains:
            arr = tr.arr + (DAY if tr.arr < tr.dep else 0)
            shift = d * DAY
            out.append(Train(tr.src, tr.dst,
                             tr.dep + shift, arr + shift))
    return out
```

```
# CHECKER (brute force)
def brute_earliest(trains, source, target, layover=0):
    # oracle: keep relaxing every train until nothing
    # improves
    best = {source: 0}
    changed = True
    while changed:
        changed = False
        for tr in trains:
            if tr.src not in best:
                continue
            wait = 0 if tr.src == source else layover
            old = best.get(tr.dst, float("inf"))
            if tr.dep >= best[tr.src] + wait:
                if tr.arr < old:
                    best[tr.dst] = tr.arr
                    changed = True
    return best.get(target)


if __name__ == "__main__":
    trains = [Train("A", "B", 60, 120),
              Train("B", "C", 130, 200),
              Train("A", "C", 100, 400),
              Train("B", "C", 110, 150)]
    time, path = earliest_route(trains, "A", "C")
    assert time == 200
    assert [(t.src, t.dst) for t in path] == [("A", "B"),
                                              ("B", "C")]
    # a 15 minute layover rules out the 130 departure
    # (arrive 120, 120 + 15 = 135): the direct train wins
    time, path = earliest_route(trains, "A", "C", 15)
    assert time == 400 and len(path) == 1
    assert earliest_route(trains, "C", "A") is None
    assert earliest_route(trains, "A", "A") == (0, [])
    time, path = fewest_trains(trains, "A", "C")
    assert len(path) == 1 and time == 400
    week = daily([Train("A", "B", 1400, 60)], 2)
    # the 23:20 train arrives at 01:00 the next day
    assert week[0].arr == 1500 and week[1].dep == 2840
    # miss the last train of the day: take it tomorrow
    late = daily([Train("A", "B", 600, 700)], 2)
    got = earliest_route(late, "A", "B")
```

```
    assert got[0] == 700
    import random
    for _ in range(300):
        names = "ABCD"
        trains = []
        for _ in range(random.randint(1, 9)):
            a, b = random.sample(names, 2)
            dep = random.randint(0, 100)
            ride = random.randint(1, 50)
            trains.append(Train(a, b, dep, dep + ride))
        gap = random.choice([0, 5, 20])
        got = earliest_route(trains, "A", "D", gap)
        want = brute_earliest(trains, "A", "D", gap)
        assert (got[0] if got else None) == want
```

MEDIUM | IN APP LC 22 | Exponent | 132 of 165

★ TOP 75: rank 19 in the Medium and Hard priority list

★ Generate Parentheses

ASKED (ANY CO.) ~6 MONTHS AGO | OLDER

STUDY: TYPE | ALL TIME 61.6 | 30 DAYS 46.9 | PRIORITY 12/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #22)

LeetCode match: LC 22 Generate Parentheses

Last asked (any company): 6 months ago, about 2026-04 (Exponent shows only a rough age) | +36 interviews

Original: https://www.aced.io/questions/1594/generate-parentheses

QUESTION

Generate all combinations of well-formed parentheses. A parenthesis combination is well-formed if each opening parenthesis "(" is closed by a matching closing parenthesis ")" in the correct order. For example, "()", "()()", and "((()))" are all combinations of well-formed parentheses, while ")(", "((" and "(()" are not. Examples n = 1 output: ["()"] n = 2 output: ["(())", "()()"] n = 3 output: ["((()))", "(()())", "(())()", "()(())", "()()()"] n = 4 output should contain: ["(((())))", "((()()))", "((())())", "((()))()", "(()(()))", "(()()())", "(())(())", "(())()()", "()((()))", "()(()())", "()(())()", "()()(())", "()()()()"]The problem is to generate all combinations of well-formed parentheses given n pairs of parentheses. A combination is well-formed if every opening parenthesis has a corresponding closing parenthesis and they are properly nested. Recursive Approach The most common and intuitive way to solve this problem is by using recursion with backtracking. Here's a step-by-step breakdown of the approach: Define the Problem: We need to build strings of length 2n using n opening (and n closing) parentheses. At any point in the string, the number of closing parentheses should not exceed the number of opening parentheses to ensure the sequence is valid. Recursive Function: We use a recursive helper function to build the strings character by character. The function tracks the remaining number of opening and

closing parentheses that can still be added. It also

APPROACH

Backtracking: add '(' while open < n and ')' while close < open. Catalan-many outputs.

HOW TO THINK ABOUT IT

Build the string left to right and only make moves that can still lead to a valid result: you may add '(' while fewer than n have been opened, and ')' only while there are more opens than closes. Because invalid prefixes are never extended, every leaf is a valid answer, and the count is the Catalan number.

Basis: LeetCode 22, Generate Parentheses: all well-formed strings with n pairs.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n):
    result = []
    for seq in product("()", repeat=2 * n):
        if is_balanced(seq):
            result.append("".join(seq))
    return result
```

TIME	SPACE
O(2^(2n) * n)	O(2^(2n))

WHY IT IS SLOW

Builds exponentially many invalid strings. Backtracking only adds '(' while fewer than n are used and ')' while fewer than the opens, so it builds only valid prefixes (the Catalan number of results).

OPTIMAL SOLUTION · Backtracking with open and close counters

TIME	SPACE
O(4^n / sqrt(n))	O(n) beyond the output

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return only the k-th string, or just the number of strings.

The count is the Catalan number C(n) = (2n choose n) / (n + 1). For the k-th string count the completions that start with '(' at each step and skip them if k is larger (unranking), using a small DP over (opens left, balance).

FOLLOW-UP 2 Several bracket types, such as () [] {}.

Multiply the choices: at each position you may open any of the types (until its count is used) and may close only the type on top of a stack. The pruning rule (never close more than you have opened) becomes 'close only the most recent unclosed bracket'.

FOLLOW-UP 3 Avoid recursion.

Use an explicit stack of (string so far, opens, closes) states or build the strings by length with a queue. The pruning conditions stay the same.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from functools import lru_cache
from math import comb


# BASE QUESTION (optimal): Backtracking with open and
# close counters
def generate(n):
    # build the string one character at a time. Adding "("
    # is allowed while opens < n; adding ")" only while
    # closes < opens: that rule keeps every string valid.
    out = []

    def build(text, opens, closes):
        if len(text) == 2 * n:
            out.append(text)
            return
        if opens < n:
            build(text + "(", opens + 1, closes)
        if closes < opens:
            build(text + ")", opens, closes + 1)

    build("", 0, 0)
    return out


# FOLLOW-UP 3: Avoid recursion.
def generate_iter(n):
    # follow-up: no recursion. The same states on a stack;
    # ")" is pushed first so "(" is handled first and the
    # strings come out in sorted order.
    out, stack = [], [("", 0, 0)]
    while stack:
        text, opens, closes = stack.pop()
        if len(text) == 2 * n:
            out.append(text)
            continue
        if closes < opens:
            stack.append((text + ")", opens, closes + 1))
        if opens < n:
            stack.append((text + "(", opens + 1, closes))
    return out


# FOLLOW-UP 1: Return only the k-th string, or just the
# number of strings.
```

```
def catalan(n):
    # follow-up: just the NUMBER of strings
    return comb(2 * n, n) // (n + 1)


@lru_cache(maxsize=None)
def completions(opens_left, balance):
    # how many ways to finish a string that still has
    # opens_left "(" to place and balance unclosed ones
    if opens_left == 0:
        return 1
    total = completions(opens_left - 1, balance + 1)
    if balance:
```

```
        total += completions(opens_left, balance - 1)
    return total


# FOLLOW-UP 1: Return only the k-th string, or just the
# number of strings.
def kth(n, k):
    # follow-up: the k-th string (1-based, sorted order,
    # "("
    # before ")") without listing them: at each step count
    # the
    # strings that continue with "(" and skip them if
    # needed
    if not 1 <= k <= catalan(n):
        raise ValueError("k is out of range")
    text, opens_left, balance = "", n, 0
    while len(text) < 2 * n:
        ways = 0
        if opens_left:
            ways = completions(opens_left - 1,
                               balance + 1)
        if opens_left and k <= ways:
            text += "("
            opens_left -= 1
            balance += 1
        else:
            if opens_left:
                k -= ways
            text += ")"
            balance -= 1
    return text
```

```
# FOLLOW-UP 2: Several bracket types, such as () [] {}.
def generate_multi(n, kinds="()[]{}"):
    # follow-up: several bracket types. Any type can open;
    # only the type on top of the stack can close.
    pairs = [kinds[i:i + 2]
             for i in range(0, len(kinds), 2)]
    out = []

    def build(text, stack, opened):
        if len(text) == 2 * n:
            out.append(text)
            return
        if opened < n:
            for open_ch, close_ch in pairs:
                build(text + open_ch, stack + [close_ch],
                      opened + 1)
        if stack:
            build(text + stack[-1], stack[:-1], opened)

    build("", [], 0)
    return out


if __name__ == "__main__":
    assert generate(1) == ["()"]
    assert generate(2) == ["(())", "()()"]
    assert sorted(generate(3)) == [
        "((()))", "(()())", "(())()", "()(())", "()()()"]
    assert generate(0) == [""]
    for n in range(0, 8):
        listed = generate(n)
        assert len(listed) == catalan(n)
        assert generate_iter(n) == sorted(listed)
    for n in range(1, 7):
        every = sorted(generate(n))
        for k, text in enumerate(every, 1):
            assert kth(n, k) == text
    assert catalan(3) == 5 and catalan(10) == 16796
    # 3 types: Catalan(n) shapes times 3 choices per pair
    for n in range(1, 5):
        got = generate_multi(n, "()[]{}")
        assert len(got) == catalan(n) * 3 ** n
        assert len(set(got)) == len(got)
    two = sorted(generate_multi(1, "()[]"))
```

```
    assert two == ["()", "[]"]
```

OFFICIAL PAGE TEXT

Generate all combinations of well-formed parentheses. A parenthesis combination is well-formed if each opening parenthesis "(" is closed by a matching closing parenthesis ")" in the correct order. For example, "()", "()()", and "((()))" are all combinations of well-formed parentheses, while ")(", "((" and "(()" are not. Examples

```
n = 1
output: ["()"]

n = 2
output: ["((()))", "(()()"]

n = 3
output: ["((()))", "((()))", "((()))", "(((())", "(()
()"]

n = 4
output should contain: ["(((())))", "(((()))", "((()
())", "((()))()", "((()()))", "((())())", "((()))()",
"(())(())", "(())()()", "()((()))", "()(()())", "()((
)()", "()()(())", "()()()()"]
```

The problem is to generate all combinations of well-formed parentheses given n pairs of parentheses. A combination is well-formed if every opening parenthesis has a corresponding closing parenthesis and they are properly nested. Recursive Approach The most common and intuitive way to solve this problem is by using recursion with backtracking. Here's a step-by-step breakdown of the approach: Define the Problem: We need to build strings of length 2n using n opening (and n closing) parentheses. At any point in the string, the number of closing parentheses should not exceed the number of opening parentheses to ensure the sequence is valid. Recursive Function: We use a recursive helper function to build the strings character by character. The function tracks the remaining number of opening and closing parentheses that can still be added. It also maintains the current combination of the string being formed. Base Case: If no more parentheses are remaining to add (both remaining_open and remaining_close are zero), the current combination is a valid sequence and is added to the result list. Recursive Case: Add an opening parenthesis (if there are any remaining and recursively call the function with one less opening parenthesis. Add a closing parenthesis) if the number of remaining closing parentheses is greater than the remaining opening

OFFICIAL PAGE TEXT

parentheses and recursively call the function with one less closing parenthesis. Pruning Invalid Paths: If at any point the number of closing parentheses left is less than the number of opening parentheses left, it means the current sequence cannot be completed to a valid sequence, so we stop exploring that path. Implementation Steps Initialize: Create a result list to store all valid sequences. Call the recursive helper function with initial values (n opening and n closing parentheses). Recursive Helper Function: Track the number of remaining opening and closing parentheses. Track the current combination being formed. Append valid combinations to the result list when the base case is reached. Backtrack: After adding an opening or closing parenthesis, remove it (backtrack) before trying the next possibility. This ensures that we explore all possible valid combinations. Example Let's consider n = 3: Start with an empty combination "", 3 opening, and 3 closing parentheses. Add an opening parenthesis: "(", 2 opening, and 3 closing. Continue adding opening parentheses until you can no longer add without violating the rules. Then add closing parentheses and ensure that at no point the closing parentheses exceed the opening ones. Once you form a valid combination like "((()))", add it to the result list. Backtrack and explore other combinations. Solution Time Complexity: The time

complexity of this solution is O(22n)O(2^{2n})O(22n). This is because each position in the string can either be an opening or closing parenthesis, and we need to generate all possible sequences of length 2n2n2n. Space Complexity: The space complexity of the solution is O(2n)O(2n)O(2n) which simplifies to O(n)O(n)O(n). This is because: The recursion depth is 2n2n2n in the worst case (each recursive call adds either an opening or a closing parenthesis). The combination string being formed is of length 2n2n2n. In this mock interview video, Aman (Google SWE) answers the interview question, "Given n pairs of parentheses, write a function to generate all combinations of well-formed parentheses."No answers contributed by the community yet.

MEDIUM | IN APP LC 76 | Exponent | 133 of 165

★ TOP 75: rank 55 in the Medium and Hard priority list

★ Find the minimum window substring.

ASKED (ANY CO.) ~7 MONTHS AGO | OLDER

STUDY: TYPE | **ALL TIME 42.5** | **30 DAYS 33** | **PRIORITY 36/224**

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #76)

LeetCode match: LC 76 Minimum Window Substring (inferred from short statement)

Last asked (any company): 7 months ago, about 2026-03 (Exponent shows only a rough age) | +36 interviews

Original: https://www.aced.io/questions/1687/minimum-window-substring

QUESTION

Find the minimum window substring.

APPROACH

Sliding window with need/have counts: expand right until valid, then shrink left while valid, tracking the best window. O(n).

HOW TO THINK ABOUT IT

Expand the right end until the window covers everything in t, then shrink from the left as far as it stays valid, record the length, and continue. A count of 'characters still missing' makes the validity check O(1): it goes down when a needed character is added and up when one is removed. Each index enters and leaves the window once.

Basis: LeetCode 76, Minimum Window Substring: the shortest substring of s containing every character of t with multiplicity.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s, t):
    found = []
    for i in range(len(s)):
        for j in range(i + len(t), len(s) + 1):
            part = s[i:j]
            if contains_all(part, t):
                found.append(part)
    return min(found, key=len, default="")
```

TIME	SPACE
O(n^2 * m)	O(m)

WHY IT IS SLOW

O(n^2) substrings, each checked in O(m) or more. A sliding window that grows until valid and then shrinks from the left is O(n + m).

OPTIMAL SOLUTION · Sliding window with a 'still needed' counter

TIME	SPACE
O(n + m)	O(m)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The smallest window containing every distinct character of s itself.

Use t = the set of distinct characters of s and run the same window. A related problem: the longest substring with at most k distinct characters uses a shrink-when-too-many window.

FOLLOW-UP 2 Return all minimum windows, or the number of valid substrings.

For all minimum windows record every window equal to the best length. For counting, when the window [left, right] is valid, every extension to the right is valid too, so add len(s) - right for each left.

FOLLOW-UP 3 Order matters: t must appear as a subsequence.

That is a different problem (LeetCode 727): DP over positions, or a two-pass scan (forward to match, backward to shrink) for each possible end.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


def valid_windows(s, t):
    # sliding window: grow `right` until the window holds
    # all
    # of t, then shrink `left` while it still does. Yield
    # every (left, right) that is valid when it is seen.
    need = Counter(t)
    missing = len(t)
    left = 0
    for right, ch in enumerate(s):
        if need[ch] > 0:
            missing -= 1
        need[ch] -= 1
        while missing == 0:
            yield left, right
            # drop the leftmost character and see if it
            # hurts
            need[s[left]] += 1
            if need[s[left]] > 0:
                missing += 1
            left += 1


# BASE QUESTION (optimal): Sliding window with a 'still
# needed' counter
def min_window(s, t):
    # the shortest window; the first one if there is a tie
    best, width = None, 0
    for left, right in valid_windows(s, t):
        if best is None or right - left < width:
            best, width = (left, right), right - left
    return s[best[0]:best[1] + 1] if best else ""


# FOLLOW-UP 2: Return all minimum windows, or the number
# of valid substrings.
def all_min_windows(s, t):
    # follow-up: every window of the minimum length
    found = list(valid_windows(s, t))
    if not found:
        return []
    size = min(r - l for l, r in found)
    return [s[l:r + 1] for l, r in found if r - l == size]
```

```
# FOLLOW-UP 2: Return all minimum windows, or the number
# of valid substrings.
```

```
def count_valid_substrings(s, t):
    # follow-up: how many substrings contain all of t. For
    # each left the first valid right is seen once; every
    # longer end is valid too.
    found = valid_windows(s, t)
    return sum(len(s) - right for _, right in found)


# FOLLOW-UP 1: The smallest window containing every
# distinct character of s itself.
def window_all_distinct(s):
    # follow-up: contain every distinct character of s
    # itself
    return min_window(s, "".join(set(s)))


def longest_k_distinct(s, k):
    # related: the longest substring with at most k
    # distinct
    # letters shrinks when it has too many
    seen, left, best = Counter(), 0, 0
    for right, ch in enumerate(s):
        seen[ch] += 1
        while len(seen) > k:
            seen[s[left]] -= 1
            if seen[s[left]] == 0:
                del seen[s[left]]
            left += 1
        best = max(best, right - left + 1)
    return best


# FOLLOW-UP 3: Order matters: t must appear as a
# subsequence.
def min_window_subsequence(s, t):
    # follow-up (LeetCode 727): t must appear IN ORDER.
    # Match
    # forward from a start to find the end, then walk back
    # from that end to find the tightest start.
    best, width, i = None, 0, 0
    while i < len(s):
```

```
        j, k = 0, i
        while k < len(s) and j < len(t):
            if s[k] == t[j]:
                j += 1
            k += 1
        if j < len(t):
            break
        end, j, k = k - 1, len(t) - 1, k - 1
        while j >= 0:
            if s[k] == t[j]:
                j -= 1
            k -= 1
        start = k + 1
        if best is None or end - start < width:
            best, width = (start, end), end - start
        i = start + 1
    return s[best[0]:best[1] + 1] if best else ""


def brute_window(s, t):
    # oracle: try every substring, shortest first
    need = Counter(t)
    for size in range(len(t), len(s) + 1):
        for i in range(len(s) - size + 1):
            if not need - Counter(s[i:i + size]):
                return s[i:i + size]
    return ""


if __name__ == "__main__":
    assert min_window("ADOBECODEBANC", "ABC") == "BANC"
```

```
assert min_window("a", "a") == "a"
assert min_window("a", "aa") == ""
assert min_window("ab", "b") == "b"
assert min_window("aab", "aab") == "aab"
assert all_min_windows("abcabc", "abc") == [
    "abc", "bca", "cab", "abc"]
assert all_min_windows("xyz", "q") == []
assert count_valid_substrings("abcabc", "abc") == 10
assert window_all_distinct("aabcbcdbca") == "dbca"
assert longest_k_distinct("eceba", 2) == 3
assert longest_k_distinct("aa", 1) == 2
text = "abcdebdde"
assert min_window_subsequence(text, "bde") == "bcde"
assert min_window_subsequence("abc", "ca") == ""
```

```
import random
for _ in range(400):
    s = "".join(random.choice("abc")
                for _ in range(random.randint(0, 9)))
    t = "".join(random.choice("abc")
                for _ in range(random.randint(1, 3)))
    assert min_window(s, t) == brute_window(s, t)
```

OFFICIAL PAGE TEXT

Upgrade to see our video answerBecome a member today100+ expert answer videosAccess to all coursesPeer-to-peer practicePrivate Discord communityFull question databaseUpgrade nowLewin (Dropbox SWE) answers the minimum window substring interview question.

MEDIUM | **IN APP** **LC 516, 5** | **Exponent** | **134 of 165**

★ TOP 75: rank 45 in the Medium and Hard priority list

★ Find the longest palindromic subsequence using dynamic programming.

ASKED (ANY CO.) ~7 MONTHS AGO | OLDER

STUDY: TYPE **ALL TIME 69.4** **30 DAYS 0** **PRIORITY 25/224**

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #516)

LeetCode match: LC 516 Longest Palindromic Subsequence (title) / LC 5 Longest Palindromic Substring (statement)

Last asked (any company): 7 months ago, about 2026-03 (Exponent shows only a rough age) | +37 interviews

Original: https://www.aced.io/questions/1169/longest-palindromic-subsequence-dynamic-programming

QUESTION

Given a string s, determine the longest palindromic substring in s. A substring is considered a palindrome if it reads the same forward and backward. A substring is a contiguous sequence of characters within a string. The longest palindromic substring is the substring with the maximum length that satisfies this condition. Examples Input: "abacc" Output: "aba" Explanation: "aba" is longer than "cc"

APPROACH

Subsequence: dp[i][j] over substrings (LCS of s and reverse(s)). Substring: expand around centers O(n^2) or Manacher O(n).

HOW TO THINK ABOUT IT

Look at the two ends of a range. If they are equal they both belong to the palindrome and you add 2 to the answer for the inside; if not, one of them is dropped, so take the better of dropping the left or the right end. The state is a range (i, j), giving an O(n^2) table filled from short ranges to long ones.

Basis: LeetCode 516, Longest Palindromic Subsequence (not a substring: letters may be skipped).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def lps(i, j):
    if i > j:
        return 0
    if i == j:
        return 1
    if s[i] == s[j]:
        return 2 + lps(i + 1, j - 1)
    skip_left = lps(i + 1, j)
    skip_right = lps(i, j - 1)
    return max(skip_left, skip_right)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

Two branches per step and the same (i, j) range recurs: O(2^n). A table over all ranges is O(n^2) time, with a rolling row for O(n) memory.

OPTIMAL SOLUTION · Interval DP with a rolling row

TIME	SPACE
O(n^2)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return the subsequence itself.

Keep the full table and walk from (0, n - 1): equal ends are taken (both go into the answer), otherwise move toward the side with the larger value. O(n^2) memory is needed for the walk back.

FOLLOW-UP 2 Minimum number of insertions (or deletions) to make the string a palindrome.

It is n - LPS(s): keep the longest palindromic subsequence and add (or remove) the other characters.

FOLLOW-UP 3 Longest palindromic substring instead (contiguous).

Expand around each of the 2n - 1 centres in O(n^2), or use Manacher's algorithm in O(n). A subsequence DP is not needed.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from itertools import combinations


def lps_table(s):
    # dp[i][j] = longest palindromic SUBSEQUENCE of
    # s[i..j].
    # Equal ends are both used; otherwise drop one end.
    n = len(s)
    dp = [[0] * n for _ in range(n)]
    for i in range(n - 1, -1, -1):
        dp[i][i] = 1
        for j in range(i + 1, n):
            if s[i] == s[j]:
                dp[i][j] = dp[i + 1][j - 1] + 2
            else:
                dp[i][j] = max(dp[i + 1][j], dp[i][j - 1])
    return dp


# BASE QUESTION (optimal): Interval DP with a rolling row
def lps_length(s):
    return lps_table(s)[0][-1] if s else 0


# FOLLOW-UP 1: Return the subsequence itself.
def lps_string(s):
    # follow-up: the subsequence itself. Walk the table
    # from
    # the full range and rebuild the left half as we go.
    if not s:
        return ""
    dp = lps_table(s)
    i, j = 0, len(s) - 1
    left, middle = [], ""
    while i <= j:
        if i == j:
            middle = s[i]
            break
        if s[i] == s[j]:
            left.append(s[i])
            i += 1
            j -= 1
        elif dp[i + 1][j] >= dp[i][j - 1]:
            i += 1
        else:
            j -= 1
    half = "".join(left)
    return half + middle + half[::-1]


# FOLLOW-UP 2: Minimum number of insertions (or deletions)
# to make the string a ...
def min_insertions(s):
    # follow-up: insertions (or deletions) to make a
    # palindrome: everything outside the longest one
    return len(s) - lps_length(s)


# FOLLOW-UP 3: Longest palindromic substring instead
# (contiguous).
def longest_palindromic_substring(s):
    # follow-up: CONTIGUOUS version. Expand around each of
    # the
    # 2n - 1 centres (a letter, or the gap between two).
    best = ""
    for centre in range(2 * len(s) - 1):
        i = centre // 2
        j = i + centre % 2
        while i >= 0 and j < len(s) and s[i] == s[j]:
            i -= 1
            j += 1
        if j - i - 1 > len(best):
            best = s[i + 1:j]
    return best


# CHECKER (brute force)
def brute_lps(s):
    # oracle: the longest palindrome among all
    # subsequences
    for size in range(len(s), 0, -1):
        for picks in combinations(s, size):
            if picks == picks[::-1]:
                return size
    return 0


if __name__ == "__main__":
    assert lps_length("bbbab") == 4
    assert lps_length("cbbd") == 2
    assert lps_length("") == 0
    assert lps_string("bbbab") == "bbbb"
    assert lps_string("a") == "a"
    assert min_insertions("abca") == 1
    assert min_insertions("race") == 3
    assert min_insertions("aba") == 0
    assert longest_palindromic_substring("abacc") == "aba"
    assert longest_palindromic_substring("cbbd") == "bb"
    assert longest_palindromic_substring("") == ""
    import random
    for _ in range(300):
        s = "".join(random.choice("abc")
                    for _ in range(random.randint(0, 10)))
        want = brute_lps(s)
        assert lps_length(s) == want
        found = lps_string(s)
        assert len(found) == want and found == found[::-1]
        # the answer really is a subsequence of s
        it = iter(s)
        assert all(ch in it for ch in found)
```

OFFICIAL PAGE TEXT

Given a string s, determine the longest palindromic substring in s. A substring is considered a palindrome if it reads the same forward and backward. A substring is a contiguous sequence of characters within a string. The longest palindromic substring is the substring with the maximum length that satisfies this condition. Examples

```
Input: "abacc"
Output: "aba"
Explanation: "aba" is longer than "cc"
```

Our solution finds the longest palindromic substring by expanding around potential centers in the input string. For each character in the string, we consider it as the center of a palindrome and expand outwards to determine the maximum length of the palindrome centered at that position. We repeat this for both odd-length and even-length palindromes. For each character, we use a helper function expandAroundCenter that takes two indices (left and right) and expands outwards as long as the characters at these indices are equal and within the bounds of the string. We calculate the lengths of palindromes centered at the current character (odd-length palindromes) and between the current character and the next one (even-length palindromes). We track the starting and ending indices of the longest palindromic substring found so far. By comparing the lengths of the palindromes found in each iteration, we can determine the longest palindromic substring. The use of expansion around centers ensures that we examine all potential palindromes efficiently. Time Complexity: The solution has a time complexity of O(n^2), where n is the length of the input string. This is because, for each character in the string, we potentially expand outwards in both directions, resulting in quadratic time complexity in the worst case. Space Complexity: The solution uses O(1) space beyond the

input string. The only extra space used is for a few variables, making it very space-efficient. NoteCheck out our lesson on the two-pointer approach to learn more about what it is and how to use it!No answers contributed by the community yet.

MEDIUM | IN APP LC 322 | Exponent | 135 of 165

Coin Change

ASKED (ANY CO.) ~7 MONTHS AGO | OLDER

STUDY: TYPE | ALL TIME 48.5 | 30 DAYS 0 | PRIORITY 71/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #322)

LeetCode match: LC 322 Coin Change

Last asked (any company): 7 months ago, about 2026-03 (Exponent shows only a rough age) | +27 interviews

Original: https://www.aced.io/questions/1142/coin-change

QUESTION

You are given an integer array coins representing different coin denominations and an integer amount representing a total amount of money. Write a function coinChange that returns the fewest number of coins needed to make up that amount. If that amount cannot be made up by any combination of the coins, return -1. You may assume that you have an infinite number of each kind of coin. Examples PythonInput: coins = [1, 2, 5], amount = 11 Output: 3 Explanation: The minimum number of coins needed is 3 (11 = 5 + 5 + 1).
Input: coins = [4, 5], amount = 7 Output: -1 Explanation: It is not possible to make up the amount 7 with coins of denominations 4 and 5.Solution 1: Brute-Force approach The naive approach to solving the coin change problem involves a recursive strategy to explore all possible combinations of coins to find the minimum number needed to make up the target amount. It starts by recursively trying each coin denomination to reduce the target amount. For each coin, the algorithm subtracts the coin's value from the current amount and solves the reduced problem. If the amount becomes zero, it indicates that no more coins are needed, and the function returns zero. If the amount becomes negative, it signals that this path is not feasible, so the function returns infinity or a large number. The algorithm combines the results from each

recursive call with the current coin to determine the minimum number of coins required. Finally, after exploring all possibilities, it returns the

APPROACH

Bottom-up dp[a] = min(dp[a - c] + 1) over coins; -1 if unreachable. O(amount * coins).

HOW TO THINK ABOUT IT

The fewest coins for amount a is one coin plus the fewest for a - c, for the best coin c; that is a table over amounts built from 0 upward. Greedy (always take the biggest coin) is wrong for general coin systems, which is the classic trap: with coins 1, 3, 4 the amount 6 needs two coins (3 + 3), not three (4 + 1 + 1).

Basis: LeetCode 322, Coin Change: the fewest coins that sum to the amount, or -1; unlimited coins of each value.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def fewest(a):
    if a == 0:
        return 0
    best = INF
    for c in coins:
        if c <= a:
            best = min(best, 1 + fewest(a - c))
    return best
```

BRUTE FORCE

TIME	SPACE
O(coins^amount)	O(amount)

WHY IT IS SLOW

The same amount is recomputed through many coin orders, exponential. Filling fewest[a] for a from 0 upward is O(amount * coins).

OPTIMAL SOLUTION · Bottom-up DP over amounts

TIME	SPACE
O(amount * coins)	O(amount)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Count the number of combinations that make the amount (LeetCode 518).

Loop over coins in the outer loop and amounts in the inner loop, adding ways[a - c]; the order of the loops makes combinations (not permutations) count once.

FOLLOW-UP 2 Return which coins are used.

Remember the last coin chosen for each amount (a parent array) and walk back from the target.

FOLLOW-UP 3 Does greedy work?

Only for special coin systems (like US coins). For general coins it can be wrong (coins 1, 3, 4, amount 6). Mention the counterexample, then give the DP.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
from collections import deque

INF = float("inf")


# BASE QUESTION (optimal): Bottom-up DP over amounts
def coin_change(coins, amount):
    # best[a] = fewest coins that make exactly a
    best = [0] + [INF] * amount
    for a in range(1, amount + 1):
        for c in coins:
            if c <= a and best[a - c] + 1 < best[a]:
                best[a] = best[a - c] + 1
    return -1 if best[amount] == INF else best[amount]


# FOLLOW-UP 1: Count the number of combinations that make
# the amount (LeetCode 518).
def count_ways(coins, amount):
    # follow-up (LeetCode 518): how many COMBINATIONS.
    # Coins
    # in the outer loop means each combination is counted
    # once, not once per order.
    ways = [1] + [0] * amount
    for c in coins:
        for a in range(c, amount + 1):
            ways[a] += ways[a - c]
    return ways[amount]


# FOLLOW-UP 2: Return which coins are used.
def coins_used(coins, amount):
    # follow-up: which coins. Remember the last coin
    # chosen
    # for every amount, then walk back from the target.
    best = [0] + [INF] * amount
    last = [0] * (amount + 1)
    for a in range(1, amount + 1):
        for c in coins:
            if c <= a and best[a - c] + 1 < best[a]:
                best[a] = best[a - c] + 1
                last[a] = c
    if best[amount] == INF:
        return None
    used, a = [], amount
    while a:
        used.append(last[a])
        a -= last[a]
    return sorted(used, reverse=True)


# FOLLOW-UP 3: Does greedy work?
def greedy(coins, amount):
    # follow-up: does greedy work? Only for special coin
    # systems. Take the biggest coin that still fits.
    used = []
    for c in sorted(coins, reverse=True):
        while amount >= c:
            amount -= c
            used.append(c)
    return used if amount == 0 else None


# CHECKER (brute force)
def brute_bfs(coins, amount):
    # oracle: breadth first search over the amount left
    seen, queue = {amount}, deque([(amount, 0)])
    while queue:
        left, steps = queue.popleft()
        if left == 0:
            return steps
        for c in coins:
            if left - c >= 0 and left - c not in seen:
                seen.add(left - c)
                queue.append((left - c, steps + 1))
    return -1


if __name__ == "__main__":
    assert coin_change([1, 2, 5], 11) == 3
    assert coin_change([2], 3) == -1
    assert coin_change([1], 0) == 0
    assert count_ways([1, 2, 5], 5) == 4
    assert count_ways([2], 3) == 0
    assert count_ways([10], 10) == 1
    assert count_ways([1, 2], 0) == 1
    assert coins_used([1, 2, 5], 11) == [5, 5, 1]
    assert coins_used([2], 3) is None
    # greedy takes 4 + 1 + 1 (3 coins), the best is 3 + 3
    assert greedy([1, 3, 4], 6) == [4, 1, 1]
    assert coin_change([1, 3, 4], 6) == 2
    assert sorted(coins_used([1, 3, 4], 6)) == [3, 3]
```

```
import random
for _ in range(300):
    size = random.randint(1, 3)
    coins = random.sample(range(1, 9), size)
    amount = random.randint(0, 25)
    assert coin_change(coins, amount) == brute_bfs(
        coins, amount)
    used = coins_used(coins, amount)
    if used is not None:
        assert sum(used) == amount
```

OFFICIAL PAGE TEXT

You are given an integer array coins representing different coin denominations and an integer amount representing a total amount of money. Write a function coinChange that returns the fewest number of coins needed to make up that amount. If that amount cannot be made up by any combination of the coins, return -1. You may assume that you have an infinite number of each kind of coin. Examples

```
PythonInput: coins = [1, 2, 5], amount = 11
Output: 3
Explanation: The minimum number of coins needed is 3 (
11 = 5 + 5 + 1).

Input: coins = [4, 5], amount = 7
Output: -1
Explanation: It is not possible to make up the amount
7 with coins of denominations 4 and 5.
```

Solution 1: Brute-Force approach The naive approach to solving the coin change problem involves a recursive strategy to explore all possible combinations of coins to find the minimum number needed to make up the target amount. It starts by recursively trying each coin denomination to reduce the target amount. For each coin, the algorithm subtracts the coin's value from the current amount and solves the reduced problem. If the amount becomes zero, it indicates that no more coins are needed, and the function returns zero. If the amount becomes negative, it signals that this path is not feasible, so the function returns infinity or a large number. The algorithm combines the results from each recursive call with the current coin to determine the minimum number of coins required. Finally, after exploring all possibilities, it returns the minimum number of coins found or -1 if it is not possible to make the target amount with the given coins.

OFFICIAL PAGE TEXT

```
PseudocodeFUNCTION coin_change_naive(coins, amount):
    IF amount == 0:
        RETURN 0  // Base case: No coins are needed to
 make amount 0

    IF amount < 0:
        RETURN infinity  // Amount is negative, path i
s not feasible

    min_coins = infinity

    FOR EACH coin IN coins:
        result = coin_change_naive(coins, amount - coi
n)  // Recursively solve for the remaining amount
        IF result != infinity:
            min_coins = MIN(min_coins, result + 1)  //
 Update min_coins with the minimum value

    RETURN min_coins IF min_coins != infinity ELSE -1
 // Return the minimum number of coins or -1 if no sol
ution exists
```

Time Complexity: The solution has a time complexity of O(m^n), where n is the amount and m is the number of coin denominations. The exponential time complexity arises from the recursive exploration of all possible combinations of coins. Each recursive call generates multiple further calls, leading to an exponential growth in the number of computations required. The total number of recursive calls can be as large as mnm^nmn due to the need to try each coin denomination for each sub-amount. Space Complexity: The space complexity of the naive approach is O(n), where n is the target amount. The space complexity is determined by the maximum depth of the recursion stack. In the worst case, the recursion depth can be as deep as the target amount n (when using coins of value 1). Therefore, the space required for the call stack is proportional to the target amount. As you can see, this solution does not perform very well. Let's take a look at a better solution. Solution 2: Dynamic programming approach Our solution employs a dynamic programming approach to determine the fewest number of coins needed to make up a given amount. We use a DP array, where each index represents a specific amount, and its value represents the minimum number of coins required to achieve that amount. The array is initialized with a value greater than the maximum possible number of coins

OFFICIAL PAGE TEXT

needed (infinity), except for the base case where dp[0] is set to 0, indicating that zero coins are needed to make amount 0. For each amount from 1 to the target amount, we iterate through each coin denomination and update the DP array. If the current amount minus the coin value is non-negative and the previous amount can be formed, we update the current amount's value to be the minimum of its current value or one more than the value of the previous amount. This ensures that we are considering the fewest coins needed by checking each possible coin combination. After processing all amounts, if the value for the target amount is still set to infinity, it means it's not possible to form the target amount with the given coins, and we return -1. Otherwise, we return the value at dp[amount], which represents the minimum number of coins needed. Time Complexity: The solution has a time complexity of O(n * m), where n is the amount and m is the number of coin denominations. This is because we iterate over each amount from 1 to the target amount, and for each amount, we iterate over all coin denominations to update the DP array. Space Complexity: The solution uses O(n) space for the DP array, where n is the target amount. The array stores the minimum number of coins required to make each amount up to the target amount. This space complexity is necessary to hold the results for

all subproblems up to the target amount.No answers contributed by the community yet.

MEDIUM | Exponent | 136 of 165

Given a matrix with a rat, bread, cat, and obstacles, find a path from the rat to the bread that maximizes the minimum distance from cat.

ASKED (ANY CO.) ~8 MONTHS AGO | OLDER

STUDY: TALK | ALL TIME 25.5 | 30 DAYS 0 | PRIORITY 140/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #1102 Path With Maximum Minimum Value, LeetCode #1730 Shortest Path to Get Food

LeetCode match: No direct match; related LC 1102 Path With Maximum Minimum Value, LC 1730 (inferred from short statement)

Last asked (any company): 8 months ago, about 2026-02 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/5244/safest-path-maximize-minimum-distance-matrix

QUESTION

Given a matrix with a rat, bread, cat, and obstacles, find a path from the rat to the bread that maximizes the minimum distance from cat.

APPROACH

Multi-source BFS from the cat to get each cell's distance from the cat, then maximize the minimum along a path from rat to bread: Dijkstra with a max-heap keyed on min distance (or binary search the distance + BFS).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what distance means (steps through open cells), whether the rat can move four-way, whether the cat is fixed, whether the path must avoid the cat cell itself, and what to return when the bread is unreachable.

BRUTE FORCE TO SAY OUT LOUD

DFS over all simple paths and keep the best minimum distance. Exponential.

OPTIMAL IDEA

Run a multi-source BFS from every cat cell to get each cell's distance from the cat. Then the answer is the path from the rat to the bread that maximizes the minimum cat distance along it (a bottleneck path): Dijkstra with a max-heap keyed on the best minimum so far, or binary search the threshold and check reachability with BFS. O(mn log mn).

DRY-RUN THESE CASES

The rat adjacent to the bread, no path (obstacles), the cat next to the rat, several cats, a grid where the longest path is safer than the shortest.

LIKELY FOLLOW-UPS

Tie-break by the shortest path, or a moving cat.

PITFALLS

Using the sum of distances instead of the minimum. Letting the cat walk through obstacles.

HOW TO THINK ABOUT IT

Two separate ideas. First, how far every cell is from the cat: that is one BFS from the cat (all cats at once). Second, choose the path whose worst cell is as far as possible: this is a 'bottleneck' (maximin) path. A max-heap search that always extends the path with the best bottleneck so far (Dijkstra with min instead of sum) solves it; binary search on the threshold plus a reachability check also works.

Basis: Written. Assumed rules (confirm them): 'R' rat, 'B' bread, 'C' cat (one or more), '#' obstacle, '.' open; 4-directional moves; distance is steps through non-obstacle cells; maximise the minimum cat distance over the cells of the rat's path (endpoints included); -1 if no path.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    dist = bfs_from_cat(grid)  # per cell
    best = -1
    for path in all_paths(grid, RAT, BREAD):
        cells = [dist[r][c] for r, c in path]
        closest = min(cells)
        best = max(best, closest)
    return best
```

TIME	SPACE
exponential	O(path length)

WHY IT IS SLOW

The number of simple paths grows exponentially with the grid. A max-heap search that extends the path with the best bottleneck so far (or binary search on the threshold) is O(m * n log(m * n)).

OPTIMAL SOLUTION · Multi-source BFS from the cat, then a max-heap bottleneck search

TIME	SPACE
O(m * n log(m * n))	O(m * n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Use binary search instead of a heap.

Binary search the safety threshold d and test with BFS whether the rat can reach the bread using only cells at least d from the cat. The test is monotone in d. O(m * n log(m + n)).

FOLLOW-UP 2 Among the safest paths, return the shortest one.

First find the best safety value d*, then run an ordinary BFS restricted to cells at distance at least d*. The result is the shortest path with maximum safety.

FOLLOW-UP 3 The cat moves one step toward the rat each turn.

Then distances depend on time, and the problem becomes a game or a time-expanded graph search; ask for the cat's movement rules before designing anything.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from collections import deque

INF = 10 ** 9


def around(r, c, grid):
    # the open neighbours of a cell (obstacles are "#")
    for dr, dc in ((1, 0), (-1, 0), (0, 1), (0, -1)):
        nr, nc = r + dr, c + dc
        if 0 <= nr < len(grid) and 0 <= nc < len(grid[0]):
            if grid[nr][nc] != "#":
                yield nr, nc


def find(grid, ch):
    for r, row in enumerate(grid):
        if ch in row:
            return r, row.index(ch)
    return None


def cat_distances(grid):
    # one BFS from the cat gives every cell's distance to
    # it
    dist = [[INF] * len(grid[0]) for _ in grid]
    cat = find(grid, "C")
    if cat is None:
        return dist
    dist[cat[0]][cat[1]] = 0
    queue = deque([cat])
    while queue:
        r, c = queue.popleft()
        for nr, nc in around(r, c, grid):
            if dist[nr][nc] == INF:
                dist[nr][nc] = dist[r][c] + 1
                queue.append((nr, nc))
    return dist


# BASE QUESTION (optimal): Multi-source BFS from the cat,
# then a max-heap bottleneck ...
def safest_value(grid):
    # a path is as safe as its closest cell to the cat.
    # Always extend the safest frontier cell (like
    # Dijkstra
    # with max and min instead of min and sum).
    dist = cat_distances(grid)
    start, goal = find(grid, "R"), find(grid, "B")
    best = {start: dist[start[0]][start[1]]}
    heap = [(-best[start], start)]
    while heap:
        neg, cell = heapq.heappop(heap)
        if cell == goal:
            return -neg
        if -neg < best[cell]:
            continue
        for nr, nc in around(cell[0], cell[1], grid):
            safety = min(-neg, dist[nr][nc])
            if safety > best.get((nr, nc), -1):
                best[(nr, nc)] = safety
                heapq.heappush(heap, (-safety, (nr, nc)))
    return None


def reach(grid, dist, d):
    # BFS using only cells at least d away from the cat;
    # returns the shortest such path (list of cells) or
    # None
    start, goal = find(grid, "R"), find(grid, "B")
    if dist[start[0]][start[1]] < d:
        return None
    parent = {start: None}
    queue = deque([start])
    while queue:
        cell = queue.popleft()
        if cell == goal:
            path = []
            while cell:
```

```
                path.append(cell)
                cell = parent[cell]
            return path[::-1]
        for nxt in around(cell[0], cell[1], grid):
            safe = dist[nxt[0]][nxt[1]] >= d
            if nxt not in parent and safe:
                parent[nxt] = cell
                queue.append(nxt)
    return None
```

```
# FOLLOW-UP 1: Use binary search instead of a heap.
def safest_by_search(grid):
    # follow-up: binary search the safety d. "reachable
    # using
    # only cells >= d" is true for small d and false for
    # big.
    dist = cat_distances(grid)
    lo, hi = 0, INF
    if reach(grid, dist, 0) is None:
        return None
    while lo < hi:
        mid = (lo + hi + 1) // 2
        if reach(grid, dist, mid):
            lo = mid
        else:
            hi = mid - 1
    return lo


# FOLLOW-UP 2: Among the safest paths, return the shortest
# one.
def shortest_safest_path(grid):
    # follow-up: among the safest paths, the shortest one
    best = safest_value(grid)
    if best is None:
        return None
    return reach(grid, cat_distances(grid), best)


def brute(grid):
    # oracle: every simple path, keep the best minimum
    dist = cat_distances(grid)
    start, goal = find(grid, "R"), find(grid, "B")
    best = [None]

    def walk(cell, seen, low):
        low = min(low, dist[cell[0]][cell[1]])
        if cell == goal:
            if best[0] is None or low > best[0]:
                best[0] = low
            return
        for nxt in around(cell[0], cell[1], grid):
            if nxt not in seen:
                walk(nxt, seen | {nxt}, low)
```

```
    walk(start, {start}, INF)
    return best[0]


if __name__ == "__main__":
    grid = ["R.....",
            ".###..",
            "...C.B"]
    assert cat_distances(grid)[0][0] == 5
    # the bread itself is 2 steps from the cat
    assert safest_value(grid) == 2
    assert safest_by_search(grid) == 2
    path = shortest_safest_path(grid)
    assert path[0] == (0, 0) and path[-1] == (2, 5)
    dist = cat_distances(grid)
    assert min(dist[r][c] for r, c in path) == 2
    walled = ["R#B"]
```

```
    assert safest_value(walled) is None
    assert safest_by_search(walled) is None
    # no cat at all: every path is perfectly safe
    assert safest_value(["R.B"]) == INF
    import random
    for _ in range(200):
        rows = random.randint(2, 4)
        cols = random.randint(2, 4)
        size = rows * cols
        cells = random.choices("..#", k=size)
        spots = random.sample(range(rows * cols), 3)
        for ch, k in zip("RBC", spots):
            cells[k] = ch
        grid = ["".join(cells[r * cols:(r + 1) * cols])
                for r in range(rows)]
        want = brute(grid)
        assert safest_value(grid) == want
        assert safest_by_search(grid) == want
```

MEDIUM | IN APP LC 249 | Exponent | 137 of 165

Given an array of strings, return groups of "buddy strings," where the strings have the same length and the distance between corresponding characters is the same.

ASKED (ANY CO.) ~8 MONTHS AGO | OLDER

STUDY: TALK | ALL TIME 35.4 | 30 DAYS 0 | PRIORITY 108/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #249)

LeetCode match: LC 249 Group Shifted Strings (inferred from short statement)

Last asked (any company): 8 months ago, about 2026-02 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/6356/group-buddy-strings-same-distance

QUESTION

Given an array of strings, return groups of "buddy strings," where the strings have the same length and the distance between corresponding characters is the same.

APPROACH

Normalize each string by its successive character differences (mod 26) as a tuple key, then group by key in a hash map. O(total chars).

HOW TO THINK ABOUT IT

Buddies are shifted copies of each other, so what they share is the shape: the gaps between neighbouring letters. Turn each string into its shape (a tuple of gaps mod 26) and group by it with a dictionary; you never compare two strings directly. Mention that single letters all have the same (empty) shape.

Basis: LeetCode 249, Group Shifted Strings.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(words):
    groups = []
    for s in words:
        for group in groups:
            if is_shift(group[0], s):
                group.append(s)
                break
        else:
            groups.append([s])
    return groups
def is_shift(a, b):
    if len(a) != len(b):
        return False
    shifts = {(ord(y) - ord(x)) % 26
              for x, y in zip(a, b)}
    return len(shifts) <= 1
```

TIME	SPACE
O(n * groups * L)	O(n)

WHY IT IS SLOW

Each string is compared with the representative of every group, O(n * groups * L). Using the sequence of gaps between neighbouring letters as a dictionary key groups everything in one pass.

OPTIMAL SOLUTION · Group by the tuple of successive differences

TIME	SPACE
O(total characters)	O(total characters)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if shifting is not cyclic (z does not wrap to a)?

Drop the % 26 and use the raw differences as the key. Two strings with the same raw gaps differ by one fixed integer shift, and both are already inside 'a'..'z', so that shift is automatically legal: the gap tuple alone decides buddies, with no extra range check. What changes is that 'az' and 'ba' are no longer buddies (gaps 25 and -1 instead of 25 and 25).

FOLLOW-UP 2 How would you do this with strings that are too many for one machine?

Compute the gap key on each machine, hash-partition the strings by key (so every buddy lands on the same worker), and group locally. The key is the only thing exchanged, so shuffle cost is one pass over the data. **Cost:** O(total characters / machines) per machine to compute the keys, plus one shuffle of the keys; each group is then built locally in O(group size).

FOLLOW-UP 3 Shifting does not wrap around (z stays z).

Use the raw gaps (no % 26) as the key. Equal raw gaps mean one fixed integer shift, which is automatically legal because both strings are already letters, so no extra check is needed.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict


def shift_key(word):
    # the gaps between neighbouring letters, wrapping z to
    # a.
    # Words that are shifts of each other share this key.
    return tuple((ord(b) - ord(a)) % 26
                 for a, b in zip(word, word[1:]))


# FOLLOW-UP 1, 3: What if shifting is not cyclic (z does
# not wrap to a)?
def raw_key(word):
    # follow-up: no wrap around (z stays z). The raw gaps
    # already decide it: one fixed integer shift is legal
    # because both words are already made of letters.
    return tuple(ord(b) - ord(a)
                 for a, b in zip(word, word[1:]))


# BASE QUESTION (optimal): Group by the tuple of
# successive differences
def group_buddies(words, key=shift_key):
    # words of different length have keys of different
    # length, so they never land in the same group
    groups = defaultdict(list)
    for w in words:
        groups[(len(w), key(w))].append(w)
    return list(groups.values())


# FOLLOW-UP 2: How would you do this with strings that are
# too many for one machine?
def group_distributed(words, machines, key=shift_key):
    # follow-up: too many words for one machine. Each
    # machine
    # computes keys for its slice, every pair (key, word)
    # is
    # sent to machine hash(key) % machines, and each
    # machine
    # groups what it receives. Only the key travels.
    slices = [words[i::machines] for i in range(machines)]
    inbox = [[] for _ in range(machines)]
    for part in slices:
```

```
        for w in part:
            k = (len(w), key(w))
            inbox[hash(k) % machines].append((k, w))
    result = []
    for mail in inbox:
        local = defaultdict(list)
        for k, w in mail:
            local[k].append(w)
        result.extend(local.values())
    return result


# CHECKER (brute force)
def are_buddies(a, b):
    # oracle: is there one shift that turns a into b?
    if len(a) != len(b):
        return False
    pairs = zip(a, b)
    shifts = {(ord(y) - ord(x)) % 26 for x, y in pairs}
    return len(shifts) <= 1


def canonical(groups):
    return sorted(sorted(g) for g in groups)


if __name__ == "__main__":
    words = ["abc", "bcd", "acef", "xyz", "az", "ba",
             "a", "z"]
    got = canonical(group_buddies(words))
    assert got == [["a", "z"], ["abc", "bcd", "xyz"],
                   ["acef"], ["az", "ba"]]
    # without wrap around "az" and "ba" are different
    plain = canonical(group_buddies(words, raw_key))
    assert ["az", "ba"] not in plain
    assert ["abc", "bcd", "xyz"] in plain
    assert group_buddies([]) == []
    import random
    for _ in range(200):
        ws = []
        for _ in range(random.randint(0, 10)):
            size = random.randint(1, 3)
            ws.append("".join(random.choice("abyz")
                              for _ in range(size)))
        groups = group_buddies(ws)
```

```
        assert sum(len(g) for g in groups) == len(ws)
        for g in groups:
            assert all(are_buddies(g[0], w) for w in g)
        # two different groups are never buddies
        for g in groups:
            for h in groups:
                if g is not h:
                    assert not are_buddies(g[0], h[0])
        parts = random.randint(1, 4)
        mine = group_distributed(ws, parts)
        assert canonical(mine) == canonical(groups)
```

MEDIUM | Exponent | 138 of 165

★ TOP 75: rank 24 in the Medium and Hard priority list

★ Given a list with response time for each server, calculate how long time it will take to process n requests.

ASKED (ANY CO.) ~A YEAR AGO | OLDER

STUDY: TYPE | ALL TIME 59.1 | 30 DAYS 46.9 | PRIORITY 16/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #875 Koko Eating Bananas

LeetCode match: No direct match; related LC 875 Koko Eating Bananas (inferred from short statement)

Last asked (any company): a year ago, about 2025-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/5485/calculate-time-to-process-given-server-response-time

QUESTION

Given a list with response time for each server, calculate how long time it will take to process n requests.

APPROACH

Binary search on time T: servers process floor(T / response_i) requests each; find the smallest T where the sum >= n. O(S log(maxT)).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether servers work in parallel and independently, what response time means (time to finish one request), and whether n can be zero.

BRUTE FORCE TO SAY OUT LOUD

Simulate each request assigned to the server that frees first with a heap. O(n log S).

OPTIMAL IDEA

Binary search the answer T: in time T, server i finishes T // r_i requests, so feasibility is sum(T // r_i) >= n, which is monotone in T. Search T in [0, min(r) * n]. O(S log(min(r) * n)).

DRY-RUN THESE CASES

One server, equal servers, n = 0, a very fast server and very slow servers, large n (overflow).

LIKELY FOLLOW-UPS

Servers that are not independent, or the time to finish exactly the n-th request.

PITFALLS

Using ceil instead of floor. Searching with an upper bound that is too small.

HOW TO THINK ABOUT IT

'Smallest time T so that the servers can finish n requests' has a monotone yes/no check: if T is enough, any larger time is too. The check is a sum of T // response_time over the servers. Whenever the answer is a threshold on a monotone condition, binary search the threshold instead of simulating.

Basis: Written; binary search on the answer (compare LeetCode 875, Koko Eating Bananas, and LeetCode 1011).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(times, n):
    heap = [(r, r) for r in times]  # (finish, r)
    heapify(heap)
    last = 0
    for _ in range(n):
        finish, r = heappop(heap)
        last = finish
        heappush(heap, (finish + r, r))
    return last
```

TIME	SPACE
O(n log S)	O(S)

WHY IT IS SLOW

One heap operation per request, O(n log S); with n up to 10^9 requests that is too slow. The finish time is a monotone threshold, so binary search on T with sum(T // response time) >= n is O(S log answer).

OPTIMAL SOLUTION · Binary search on the total time

TIME	SPACE
O(S log(min(times) * n))	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Servers may fail, or there is a startup time per server.

Add the startup time to the check: server i completes max(0, (T - start_i) // r_i) requests. The check stays monotone in T, so binary search still applies.

FOLLOW-UP 2 The inverse question: how many servers are needed to finish within a given time?

Divide: each server finishes time // r requests, so you need ceil(n / that). No search needed.

FOLLOW-UP 3 Requests have different sizes.

Then it is a scheduling problem (minimise the makespan), NP-hard in general; the greedy 'longest request first to the least-loaded server' is within 4/3 of optimal.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


# FOLLOW-UP 1: Servers may fail, or there is a startup
# time per server.
def done_by(times, t, starts=None):
    # how many requests all servers finish within time t.
    # starts[i] is a startup delay of server i (default
    # 0).
    total = 0
    for i, r in enumerate(times):
        begin = starts[i] if starts else 0
        total += max(0, (t - begin) // r)
    return total


# BASE QUESTION (optimal): Binary search on the total time
def time_for(times, n, starts=None):
    # smallest t with done_by(t) >= n. done_by never goes
    # down as t grows, so binary search works.
    if n <= 0:
        return 0
    lo = 0
    first = starts[0] if starts else 0
    hi = first + times[0] * n
    for i, r in enumerate(times):
        begin = starts[i] if starts else 0
        hi = min(hi, begin + r * n)
    while lo < hi:
        mid = (lo + hi) // 2
        if done_by(times, mid, starts) >= n:
            hi = mid
        else:
            lo = mid + 1
    return lo


# FOLLOW-UP 2: The inverse question: how many servers are
# needed to finish within a ...
def servers_needed(n, r, t):
    # follow-up: identical servers with response time r.
    # In
    # time t each one finishes t // r requests, so divide.
    per = t // r
    if per == 0:
        return None
    return -(-n // per)


# FOLLOW-UP 3: Requests have different sizes.
def makespan(sizes, servers):
    # follow-up: requests of different sizes. Minimising
    # the
    # finish time is NP-hard; the greedy rule "biggest
    # request
    # to the least loaded server" is within 4/3 of the
    # best.
    loads = [0] * servers
```

```
    heapq.heapify(loads)
    for size in sorted(sizes, reverse=True):
        lightest = heapq.heappop(loads)
        heapq.heappush(loads, lightest + size)
    return max(loads)


# CHECKER (brute force)
def brute_time(times, n, starts=None):
    # oracle: simulate time one unit at a time
    t = 0
    while done_by(times, t, starts) < n:
        t += 1
    return t


if __name__ == "__main__":
    assert time_for([1, 2, 3], 6) == 4
    assert time_for([4], 3) == 12
    assert time_for([5, 5], 0) == 0
    assert time_for([2, 3], 1) == 2
    # server 0 starts after 10, so server 1 does the work
    assert time_for([1, 5], 2, starts=[10, 0]) == 10
    assert servers_needed(10, 4, 8) == 5
    assert servers_needed(10, 4, 3) is None
    assert servers_needed(1, 7, 7) == 1
    # the best split is 9, 9, 9; greedy gets 11 (11/9 <
    # 4/3)
    assert makespan([5, 5, 4, 4, 3, 3, 3], 3) == 11
    assert makespan([], 2) == 0
    import random
    for _ in range(300):
```

```
        times = [random.randint(1, 6)
                 for _ in range(random.randint(1, 4))]
        n = random.randint(0, 20)
        starts = [random.randint(0, 5) for _ in times]
        assert time_for(times, n) == brute_time(times, n)
        assert time_for(times, n, starts) == brute_time(
            times, n, starts)
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

MEDIUM | Exponent | 139 of 165

Given positions of N kids and M ice cream sellers on a 1D line, find the smallest distance E such that every kid lies within the range [P - E, P + E] of at least one seller.

ASKED (ANY CO.) ~A YEAR AGO | OLDER

STUDY: TALK | ALL TIME 26.5 | 30 DAYS 0 | PRIORITY 132/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #475 Heaters

ABOUT THIS QUESTION

LeetCode match: No direct match; related LC 475 Heaters (inferred from short statement)

Last asked (any company): a year ago, about 2025-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/5138/minimum-distance-kids-ice-cream-sellers

QUESTION

Given positions of N kids and M ice cream sellers on a 1D line, find the smallest distance E such that every kid lies within the range [P - E, P + E] of at least one seller.

APPROACH

Sort sellers; for each kid binary search the nearest seller; E = max over kids of the nearest distance. O((N + M) log M). Alternative: binary search E + two pointers.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether positions are integers, whether several sellers can share a position, and whether E may be fractional (the answer is a distance, so it is one of the kid-seller distances).

BRUTE FORCE TO SAY OUT LOUD

Try every E over the range and check all kids. O(N * M * range).

OPTIMAL IDEA

Sort the sellers. For each kid binary search the nearest seller (check the neighbors on both sides of the insertion point). E is the maximum of those nearest distances. O((N + M) log M). Alternatively, binary search on E and check coverage with two pointers (LeetCode 475, Heaters).

DRY-RUN THESE CASES

A kid at a seller's position (0), all kids left of every seller, one seller, duplicates, kids between two sellers.

LIKELY FOLLOW-UPS

Each seller can serve at most C kids, which turns it into a matching problem solved by binary search plus greedy.

PITFALLS

Checking only the seller to the right of the kid. Forgetting to sort.

HOW TO THINK ABOUT IT

Each kid only cares about its nearest seller, and the radius E must cover the worst kid. So E is the maximum over kids of the distance to the nearest seller. With sellers sorted, the nearest seller of a kid is one of the two neighbours around its insertion point, which is a binary search.

Basis: LeetCode 475, Heaters (houses = kids, heaters = sellers); the answer is the largest distance from a kid to the nearest seller.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(kids, sellers):
    worst = 0
    for kid in kids:
        gaps = [abs(kid - s) for s in sellers]
        nearest = min(gaps)
        worst = max(worst, nearest)
    return worst
```

TIME	SPACE
O(N * M)	O(1)

WHY IT IS SLOW

N * M distance checks. With the sellers sorted, binary search finds each kid's nearest seller among two neighbours, O((N + M) log M).

OPTIMAL SOLUTION · Sort the sellers, binary search each kid

TIME	SPACE
O((N + M) log M)	O(1) extra

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Both lists are already sorted, or you want to avoid the binary search.

Walk the kids in order with one pointer on the sellers that only moves forward while the next seller is at least as close. O(N + M) after sorting.

FOLLOW-UP 2 Each seller can serve at most C kids.

Now it is an assignment problem. Binary search the radius E and test feasibility with a greedy left-to-right matching that gives each seller up to C of the leftmost uncovered kids in its range.

FOLLOW-UP 3 Sellers can be placed anywhere (minimise the radius with S sellers).

That is the 1D k-center problem: binary search the radius and greedily place a seller at the farthest point covering the leftmost uncovered kid. O(N log range).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from bisect import bisect_left


# BASE QUESTION (optimal): Sort the sellers, binary search
# each kid
def smallest_e(kids, sellers):
    # each kid goes to the nearest seller; the answer is
    # the
    # worst such distance. The nearest seller is next to
    # the
    # kid's place in the sorted list of sellers.
    sellers = sorted(sellers)
    worst = 0
    for k in kids:
        i = bisect_left(sellers, k)
        near = INF = float("inf")
        if i < len(sellers):
            near = sellers[i] - k
        if i > 0:
            near = min(near, k - sellers[i - 1])
        worst = max(worst, near)
    return worst


# FOLLOW-UP 1: Both lists are already sorted, or you want
# to avoid the binary search.
def smallest_e_sorted(kids, sellers):
    # follow-up: sorted input, no binary search. One
    # pointer
    # on the sellers only moves forward.
    kids, sellers = sorted(kids), sorted(sellers)
    worst, j = 0, 0
    for k in kids:
        # move on while the next seller is at least as
        # close
        while j + 1 < len(sellers):
            here = abs(sellers[j] - k)
            if abs(sellers[j + 1] - k) > here:
                break
            j += 1
        worst = max(worst, abs(sellers[j] - k))
    return worst


def feasible_capacity(kids, sellers, e, cap):
    # can every kid be served when a seller takes at most
    # `cap` kids? Sellers left to right each take the
    # leftmost kids that are still unserved and in range.
    i = 0
    for s in sellers:
        if i < len(kids) and kids[i] < s - e:
            return False
        taken = 0
        while i < len(kids) and taken < cap:
            if kids[i] > s + e:
                break
            i += 1
            taken += 1
    return i == len(kids)


# FOLLOW-UP 2: Each seller can serve at most C kids.
def smallest_e_capacity(kids, sellers, cap):
    # follow-up: binary search the distance
    kids, sellers = sorted(kids), sorted(sellers)
    if len(kids) > cap * len(sellers):
        return None
    lo, hi = 0, max(kids[-1], sellers[-1]) - min(
        kids[0], sellers[0])
    while lo < hi:
        mid = (lo + hi) // 2
        if feasible_capacity(kids, sellers, mid, cap):
            hi = mid
        else:
            lo = mid + 1
    return lo
```

```python
def sellers_needed(kids, e):
    # greedy: the leftmost uncovered kid at x gets a
    # seller at
    # x + e, who covers every kid up to x + 2e
    count, reach = 0, None
    for k in sorted(kids):
        if reach is None or k > reach:
            count += 1
            reach = k + 2 * e
    return count
```

```python
# FOLLOW-UP 3: Sellers can be placed anywhere (minimise
# the radius with S sellers).
def best_radius(kids, how_many):
    # follow-up: sellers can stand ANYWHERE; the smallest
    # (whole number) radius that is enough for how_many
    kids = sorted(kids)
    lo, hi = 0, kids[-1] - kids[0]
    while lo < hi:
        mid = (lo + hi) // 2
        if sellers_needed(kids, mid) <= how_many:
            hi = mid
        else:
            lo = mid + 1
    return lo


def brute(kids, sellers):
    # oracle: try E = 0, 1, 2, ... until every kid is
    # covered
    e = 0
    while not all(any(abs(k - s) <= e for s in sellers)
                  for k in kids):
        e += 1
    return e


if __name__ == "__main__":
    assert smallest_e([1, 5, 9], [2, 8]) == 3
    assert smallest_e([4], [4]) == 0
    assert smallest_e_sorted([1, 5, 9], [2, 8]) == 3
    # capacity 1: three kids need three sellers' worth
    assert smallest_e_capacity([1, 2, 3], [2], 1) is None
    spread = smallest_e_capacity([1, 2, 3], [1, 3, 9], 1)
    assert spread == 6
    assert smallest_e_capacity([1, 2], [5, 6], 1) == 4
    assert sellers_needed([1, 2, 3, 20], 1) == 2
    assert best_radius([1, 2, 3, 20], 2) == 1
    assert best_radius([5], 1) == 0
    import random
    for _ in range(400):
        kids = [random.randint(0, 20)
                for _ in range(random.randint(1, 6))]
        sellers = [random.randint(0, 20)
                   for _ in range(random.randint(1, 4))]
        want = brute(kids, sellers)
```

```python
        assert smallest_e(kids, sellers) == want
        assert smallest_e_sorted(kids, sellers) == want
        assert smallest_e_capacity(
            kids, sellers, len(kids)) == want
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

MEDIUM | Exponent | 140 of 165

★ TOP 75: rank 41 in the Medium and Hard priority list

★ Sort a nearly sorted (or K sorted) array.

ASKED (ANY CO.) ~A YEAR AGO | OLDER

STUDY: TYPE | ALL TIME 55.2 | 30 DAYS 33 | PRIORITY 24/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #215 Kth Largest Element in an Array, LeetCode #23 Merge k Sorted Lists

LeetCode match: No direct match; related LC 215 Kth Largest Element, LC 23 (inferred from short statement)

Last asked (any company): a year ago, about 2025-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/5392/k-sorted-array

QUESTION

Sort a nearly sorted (or K sorted) array.

APPROACH

Min-heap of size k+1: push the first k+1 elements, then for each next element pop the smallest into output and push the next. O(n log k).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask what K means (each element is at most K positions from its sorted place), whether in place, and whether K can be 0.

BRUTE FORCE TO SAY OUT LOUD

Library sort, O(n log n). It works but ignores the structure.

OPTIMAL IDEA

Min-heap of size K + 1: push the first K + 1 elements, then repeatedly pop the minimum into the output and push the next element. The minimum of any K + 1 consecutive window is always the next sorted element. O(n log K) time, O(K) space.

DRY-RUN THESE CASES

K = 0 (already sorted), K = 1, K at least n, duplicates, a reverse-sorted array with K equal n - 1.

LIKELY FOLLOW-UPS

A very large K (use the library sort), or sorting a stream with bounded memory.

PITFALLS

A heap of size K instead of K + 1 (misses one element). Not draining the heap at the end.

HOW TO THINK ABOUT IT

If each element is at most K places from where it belongs, then the smallest element of the whole array must be among the first K + 1 elements. A min-heap holding a sliding window of K + 1 elements always has the next output on top, so you never need to sort the whole array.

Basis: GeeksforGeeks 'sort a nearly sorted array'; each element is at most K positions from its sorted position.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(arr):
    return sorted(arr)  # ignores the K hint
```

TIME	SPACE
O(n log n)	O(n)

WHY IT IS SLOW

O(n log n) regardless of K. Each element is at most K places from its sorted position, so a min-heap holding a window of K + 1 elements emits the sorted order in O(n log K).

OPTIMAL SOLUTION · Min-heap of size K + 1

TIME	SPACE
O(n log K)	O(K)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 K is not given. How do you find it?

Sort a copy with the original index as a tie-break and take the largest |original index - sorted index|; that is the smallest valid K. O(n log n), so only worth it if you will sort many similar arrays.

FOLLOW-UP 2 The data is a stream you cannot hold in memory.

The heap of K + 1 elements is already a streaming algorithm: it emits the next sorted element after each arrival once it holds K + 1 elements. Memory O(K).

FOLLOW-UP 3 K is close to n.

Then O(n log K) approaches O(n log n) and the heap has no advantage; use the library sort. State the crossover.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq


# BASE QUESTION (optimal): Min-heap of size K + 1
def sort_k_sorted(arr, k):
    # every item is at most k places from its final spot,
    # so
    # the smallest of the next k + 1 items is the next
    # answer. Keep k items in a heap, and for each new one
    # push it and pop the smallest: O(n log k).
    heap = list(arr[:k])
    heapq.heapify(heap)
    out = []
    for x in arr[k:]:
        # push the new item and pop the smallest in one go
        out.append(heapq.heappushpop(heap, x))
    while heap:
        out.append(heapq.heappop(heap))
    return out


# FOLLOW-UP 2: The data is a stream you cannot hold in
# memory.
def stream_sort(items, k):
    # follow-up: a stream that does not fit in memory. The
    # same heap, as a generator: memory is O(k).
    heap = []
    for x in items:
        heapq.heappush(heap, x)
        if len(heap) > k:
            yield heapq.heappop(heap)
    while heap:
        yield heapq.heappop(heap)


# FOLLOW-UP 1: K is not given. How do you find it?
def find_k(arr):
    # follow-up: the smallest valid k. Sort the indexes by
    # value (ties keep their order) and take the largest
    # distance between a position and its sorted position.
    order = sorted(range(len(arr)), key=arr.__getitem__)
    shifts = (abs(pos - i) for pos, i in enumerate(order))
    return max(shifts, default=0)
```

```
# FOLLOW-UP 3: K is close to n.
def sort_any(arr, k):
    # follow-up: when k is close to n the heap is no
    # better
    # than the library sort, so use that
    if k >= len(arr) // 2:
        return sorted(arr)
    return sort_k_sorted(arr, k)


if __name__ == "__main__":
    nearly = [6, 5, 3, 2, 8, 10, 9]
    assert sort_k_sorted(nearly, 3) == sorted(nearly)
    assert sort_k_sorted([], 2) == []
    assert sort_k_sorted([3, 1, 2], 5) == [1, 2, 3]
    assert sort_k_sorted([1, 2, 3], 0) == [1, 2, 3]
    out = list(stream_sort(iter(nearly), 3))
    assert out == sorted(nearly)
    assert find_k([1, 2, 3]) == 0
    assert find_k([2, 1, 3]) == 1
    assert find_k([6, 5, 3, 2, 8, 10, 9]) == 3
    assert find_k([]) == 0
    import random
    for _ in range(300):
        arr = [random.randint(0, 9)
               for _ in range(random.randint(0, 9))]
        k = find_k(arr)
        # k is valid, and one less is not (unless k is 0)
        assert sort_k_sorted(arr, k) == sorted(arr)
        assert sort_any(arr, k) == sorted(arr)
```

```
    # distinct values: compare with the plain definition
    for _ in range(300):
        size = random.randint(2, 8)
        arr = random.sample(range(30), size)
        k = find_k(arr)
        where = {v: i for i, v in enumerate(sorted(arr))}
        moves = enumerate(arr)
        far = max(abs(i - where[v]) for i, v in moves)
        assert k == far
        assert sort_k_sorted(arr, k) == sorted(arr)
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

MEDIUM | IN APP LC 98 | Exponent | 141 of 165

Determine if a given binary tree is a binary search tree (BST).

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TYPE | ALL TIME 36 | 30 DAYS 41.1 | PRIORITY 51/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: your app's interview approach (LeetCode #98)

LeetCode match: LC 98 Validate Binary Search Tree (inferred from short statement)

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age) | +28 interviews

Original: https://www.aced.io/questions/1158/determine-binary-tree-bst

QUESTION

Determine if a given binary tree is a valid Binary Search Tree (BST).

APPROACH

DFS with (low, high) bounds, or in-order traversal staying strictly increasing. O(n).

HOW TO THINK ABOUT IT

Checking only a node against its two children is not enough; every node in the left subtree must be smaller than the node, not just the left child. Pass down the allowed open interval (low, high) for each subtree, or use the fact that an in-order walk of a BST is strictly increasing.

Basis: LeetCode 98, Validate Binary Search Tree (strict: left < node < right, no duplicates).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def is_bst(root):
    values = inorder(root)
    for a, b in zip(values, values[1:]):
        if a >= b:
            return False
    return True
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

O(n) time but stores every value, O(n) space. Passing the allowed (low, high) range down the tree checks each node once with O(height) space and stops at the first violation.

OPTIMAL SOLUTION · Pass the allowed range (low, high) down

TIME	SPACE
O(n)	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Duplicates are allowed (all on the left, or all on the right).

Make one of the two bounds inclusive: for 'duplicates go left' every node must satisfy lo < val <= hi (the bound inherited from a left ancestor is inclusive, the one from a right ancestor is exclusive). Tested on trees built by inserting duplicates to the left.

FOLLOW-UP 2 Do it with an in-order walk that keeps only the previous value.

Walk in order with an explicit stack and compare each value with the previous one (strictly greater). O(h) space and early exit.

FOLLOW-UP 3 Recover a BST where exactly two nodes were swapped (LeetCode 99).

An in-order walk shows one or two descents; the first and last nodes involved in the descents are the swapped pair. O(n) time and O(h) space (O(1) with Morris traversal).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class TreeNode:
    def __init__(self, val, left=None, right=None):
        self.val, self.left, self.right = val, left, right


# BASE QUESTION (optimal): Pass the allowed range (low,
# high) down
```

```
# FOLLOW-UP 1: Duplicates are allowed (all on the left, or
# all on the right).
def is_bst(root, dup="none"):
    # FOLLOW-UP 1: dup="left" or "right" allows duplicates
    # every node must lie between the bounds from its
    # ancestors. dup says where an equal value may go:
    # "none" (no duplicates), "left" or "right".
    def fits(val, lo, hi):
        if lo is not None:
            if val < lo or (val == lo and dup != "right"):
                return False
        if hi is not None:
            if val > hi or (val == hi and dup != "left"):
                return False
        return True

    stack = [(root, None, None)]
    while stack:
        node, lo, hi = stack.pop()
        if node is None:
            continue
        if not fits(node.val, lo, hi):
            return False
        stack.append((node.left, lo, node.val))
        stack.append((node.right, node.val, hi))
    return True


# FOLLOW-UP 2: Do it with an in-order walk that keeps only
# the previous value.
def is_bst_inorder(root):
    # follow-up: an in-order walk must be strictly
    # increasing,
    # so only the previous value is kept (O(height) space)
    stack, node, prev = [], root, None
    while stack or node:
        while node:
            stack.append(node)
            node = node.left
        node = stack.pop()
        if prev is not None and node.val <= prev:
            return False
        prev, node = node.val, node.right
    return True


# FOLLOW-UP 3: Recover a BST where exactly two nodes were
# swapped (LeetCode 99).
def recover(root):
    # follow-up (LeetCode 99): two nodes swapped their
    # values. In order, one or two "descents" show up; the
    # first node of the first and the second node of the
    # last
    # descent are the swapped pair.
    stack, node, prev = [], root, None
    first = second = None
    while stack or node:
        while node:
            stack.append(node)
            node = node.left
        node = stack.pop()
        if prev is not None and node.val < prev.val:
            second = node
            if first is None:
                first = prev
        prev, node = node, node.right
    if first:
        first.val, second.val = second.val, first.val
    return root


def insert(root, val, dup="left"):
    # plain BST insertion (used to build test trees)
    if root is None:
        return TreeNode(val)
    cur = root
    while True:
        go_left = val < cur.val or (
            val == cur.val and dup == "left")
        side = "left" if go_left else "right"
        if getattr(cur, side) is None:
            setattr(cur, side, TreeNode(val))
            return root
        cur = getattr(cur, side)


def inorder(root):
    out, stack, node = [], [], root
    while stack or node:
        while node:
            stack.append(node)
            node = node.left
        node = stack.pop()
        out.append(node.val)
        node = node.right
    return out


def brute(node, dup="none"):
    # oracle: compare every node with its whole subtrees
    if node is None:
        return True
    left, right = inorder(node.left), inorder(node.right)
    low_ok = all(v < node.val or (
        v == node.val and dup == "left") for v in left)
    high_ok = all(v > node.val or (
        v == node.val and dup == "right") for v in right)
    return (low_ok and high_ok and brute(node.left, dup)
            and brute(node.right, dup))


if __name__ == "__main__":
    good = TreeNode(5, TreeNode(3), TreeNode(8))
    assert is_bst(good) and is_bst_inorder(good)
    # 4 sits in the right subtree of 5: a local check
    # passes
    # but the bounds catch it
    inner = TreeNode(8, TreeNode(4))
    bad = TreeNode(5, TreeNode(3), inner)
    assert not is_bst(bad) and not is_bst_inorder(bad)
    assert is_bst(None) and is_bst_inorder(None)
    twin = TreeNode(5, TreeNode(5))
    assert not is_bst(twin) and is_bst(twin, "left")
    assert not is_bst(twin, "right")
    tree = None
    for v in (5, 3, 8, 1, 4, 7, 9):
        tree = insert(tree, v)
    tree.left.val, tree.right.val = 8, 3
    assert not is_bst(tree)
    assert is_bst(recover(tree))
    assert inorder(tree) == [1, 3, 4, 5, 7, 8, 9]
    import random
    for _ in range(300):
        tree = None
        for _ in range(random.randint(0, 8)):
            v = random.randint(0, 6)
            tree = insert(tree, v, "left")
        for dup in ("left", "right", "none"):
            assert is_bst(tree, dup) == brute(tree, dup)
        if tree and tree.left:
            top, kid = tree, tree.left
            top.val, kid.val = kid.val, top.val
        assert is_bst(tree) == brute(tree)
```

```
assert is_bst(tree) == is_bst_inorder(tree)
```

OFFICIAL PAGE TEXT

Determine if a given binary tree is a valid Binary Search Tree (BST). HintA binary tree is considered a "valid BST" if for every node: All the values in its left subtree are strictly less than the node's value. All the values in its right subtree are strictly greater than the node's value. Both the left and right subtrees must also be valid BSTs. Examples

```
All trees defined in level-order
root = [5, 2, 6]
output: true

root = [5, 2, 4, null, null, 3, 6]
output: false

root = []
output: true
```

In these examples, the output is true if the given binary tree root is a valid BST, and false otherwise.Our solution to validate whether a binary tree is a Binary Search Tree (BST) uses a recursive approach. We traverse the tree while maintaining a range for valid node values (min and max). At each node, we check whether its value lies within the given range: If the node's value is not within the allowed range, we return False, indicating the tree is not a valid BST. If the node's value is valid, we recursively check its left and right subtrees: The left subtree must have values strictly less than the current node's value. The right subtree must have values strictly greater than the current node's value. For the left subtree, the range becomes (min, current_node_value). For the right subtree, the range becomes (current_node_value, max). We use nullptr to indicate unbounded ranges when there is no minimum or maximum restriction (e.g., for the root node or outermost nodes). If all nodes satisfy their respective conditions, we return True, confirming that the tree is a valid BST. Time Complexity: The solution has a time complexity of O(n), where n is the number of nodes in the binary tree. This is because we traverse each node exactly once, performing constant-time checks at each node. Space Complexity: The space complexity is O(h), where h is the height of the tree. This space is used by the

recursion stack. In the worst case (for an unbalanced tree), the height could be n, making the space complexity O(n). For a balanced tree, the height would be O(log n).No answers contributed by the community yet.

MEDIUM | IN APP LC 271 | Exponent | 142 of 165

Write functions to serialize and deserialize a list of strings.

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TALK | ALL TIME 28.2 | 30 DAYS 0 | PRIORITY 128/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #271)

LeetCode match: LC 271 Encode and Decode Strings

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age) | 2 interviews

Original:
https://www.aced.io/questions/1307/serialize-deserialize-list-strings

QUESTION

Serialize and Deserialize a List of Strings. You are tasked with writing two functions: serialize and deserialize. The serialize function will take a list of strings as input and return a single string. The deserialize function will take this single string and reconstruct the original list of strings. Details The serialize function should concatenate all strings in the list into a single string, with each original string's length encoded as a single character prefix. The deserialize function should be able to take the single string and accurately split it back into the original list of strings, using the encoded length characters as guides. For example, consider a list ["hello", "world"]. The serialization of this list might be "\x05hello\x05world", where \x05 indicates that the following string has a length of 5 characters. Constraints The maximum length of any string is 65535 (0xFFFF). If a string's length exceeds the maximum, the serialize function should raise an exception. The deserialize function should accurately handle any edge cases, such as empty strings or single-character strings. Assume that all strings consist of ASCII characters only. Examples lst = ['hello', 'world'] serialized = serialize(lst)

serialized output

: "\x05hello\x05world" deserialized = deserialize(serialized)

deserialized output should be

: ['hello', 'world'] lst = [''] serialized = serialize(lst)

serialized output

: "\x00" deserialized = deserialize(serialized)

deserialized output should be

APPROACH

Length-prefix encoding (e.g. '5#hello'), decode by reading the length and slicing; safe for any characters including delimiters.

HOW TO THINK ABOUT IT

Any text can appear inside a string, so a delimiter is never safe by itself. The fix is to say how long each string is before you write it (length prefix), so the decoder never has to look for a separator inside the data. Always check two corner cases: the empty list and a list containing the empty string.

Basis: LeetCode 271, Encode and Decode Strings.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def serialize(items):
    return ",".join(items)
def deserialize(text):
    return text.split(",")  # breaks on commas
```

TIME	SPACE
O(total length)	O(total length)

WHY IT IS SLOW

It is fast (O(total length)) but wrong: a string that contains the delimiter breaks it, and an empty list cannot be told from a list of one empty string. Writing each string's length before it fixes both.

OPTIMAL SOLUTION · Length-prefix every string

TIME	SPACE
O(total length)	O(total length)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Use escaping instead of a length prefix.

Escape the separator and the escape character inside each string, then terminate each item with the unescaped separator. The decoder tracks whether the previous character was an escape. It is streamable, while the length prefix can be read in O(1) jumps.

FOLLOW-UP 2 The strings are long or binary.

Use bytes and a fixed-width length (for example a 4-byte big-endian integer from struct.pack). Fixed-width lengths avoid the digit-scanning loop and work for any byte value.

FOLLOW-UP 3 Just use JSON?

Yes if the format is free to choose: json.dumps handles quoting and Unicode correctly. Mention it as the practical answer, but code the length-prefix version when the interviewer wants to see you handle the delimiter problem yourself.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import json
import struct


# BASE QUESTION (optimal): Length-prefix every string
def serialize(items):
    # length prefix: "<length>#<text>" for every string.
    # The
    # reader knows exactly how much to read, so the text
    # may
    # hold any character, even "#" and digits.
    return "".join(f"{len(s)}#{s}" for s in items)


# BASE QUESTION (optimal): Length-prefix every string
def deserialize(text):
    items, i = [], 0
    while i < len(text):
        # read the digits up to the "#"
        sep = text.index("#", i)
        size = int(text[i:sep])
        start = sep + 1
        items.append(text[start:start + size])
        i = start + size
    return items


# FOLLOW-UP 1: Use escaping instead of a length prefix.
def serialize_escaped(items):
    # follow-up: escaping. Inside an item "\" becomes "\\"
    # and "," becomes "\,"; every item ends with a plain
    # ",".
    out = []
    for s in items:
        s = s.replace("\\", "\\\\").replace(",", "\\,")
        out.append(s + ",")
    return "".join(out)


# FOLLOW-UP 1: Use escaping instead of a length prefix.
def deserialize_escaped(text):
    items, cur, escaped = [], [], False
    for ch in text:
        if escaped:
            # the character after "\" is taken literally
            cur.append(ch)
            escaped = False
        elif ch == "\\":
            escaped = True
        elif ch == ",":
            items.append("".join(cur))
            cur = []
        else:
            cur.append(ch)
    if cur or escaped:
        raise ValueError("truncated input")
    return items


# FOLLOW-UP 2: The strings are long or binary.
def serialize_bytes(items):
    # follow-up: long or binary data. A fixed 4 byte
    # length
    # (big-endian) before each item: no digits to scan.
    out = bytearray()
```

```
    for s in items:
        raw = s
        if isinstance(s, str):
            raw = s.encode("utf-8")
        out += struct.pack(">I", len(raw)) + raw
    return bytes(out)


# FOLLOW-UP 2: The strings are long or binary.
def deserialize_bytes(data):
    items, i = [], 0
    while i < len(data):
        (size,) = struct.unpack(">I", data[i:i + 4])
        items.append(data[i + 4:i + 4 + size])
        i += 4 + size
    return items


# FOLLOW-UP 3: Just use JSON?
def serialize_json(items):
    # follow-up: the practical answer when the format is
    # free
    return json.dumps(items)
```

```
def deserialize_json(text):
    return json.loads(text)


if __name__ == "__main__":
    tricky = ["", "a", "12#x", "hello, world", "\\", ",,",
              "é??", "3#abc", "\n"]
    for data in ([], [""], ["a"], tricky):
        assert deserialize(serialize(data)) == data
        assert deserialize_escaped(
            serialize_escaped(data)) == data
        back = deserialize_json(serialize_json(data))
        assert back == data
        raw = deserialize_bytes(serialize_bytes(data))
        assert [r.decode("utf-8") for r in raw] == data
    assert serialize(["ab", "c"]) == "2#ab1#c"
    assert serialize_escaped(["a,b"]) == "a\\,b,"
    assert serialize_escaped([""]) == ","
    assert serialize_escaped([]) == ""
    assert serialize_bytes(["a"]) == b"\x00\x00\x00\x01a"
    # binary data that is not text works too
    blob = [bytes([0, 255, 10])]
    packed = serialize_bytes(blob)
    assert deserialize_bytes(packed) == blob
    try:
        deserialize_escaped("abc")
        raise AssertionError("should fail")
    except ValueError:
        pass
```

OFFICIAL PAGE TEXT

Serialize and Deserialize a List of Strings. You are tasked with writing two functions: serialize and deserialize. The serialize function will take a list of strings as input and return a single string. The deserialize function will take this single string and reconstruct the original list of strings. Details The serialize function should concatenate all strings in the list into a single string, with each original string's length encoded as a single character prefix. The deserialize function should be able to take the single string and accurately split it back into the original list of strings, using the encoded length characters as guides. For example, consider a list ["hello", "world"]. The serialization of this list might be "\x05hello\x05world", where \x05 indicates that the following string has a length of 5 characters. Constraints The maximum length of any string is 65535 (0xFFFF). If a string's length exceeds the maximum, the serialize function should raise an exception. The deserialize function should accurately handle any edge cases, such as empty strings or single-character strings. Assume that all strings consist of ASCII characters only. Examples

```
lst = ['hello', 'world']
serialized = serialize(lst)
# serialized output: "\x05hello\x05world"
deserialized = deserialize(serialized)
# deserialized output should be: ['hello', 'world']

lst = ['']
serialized = serialize(lst)
# serialized output: "\x00"
deserialized = deserialize(serialized)
# deserialized output should be: ['']

lst = ['a', 'bc', 'def']
serialized = serialize(lst)
# serialized output: "\x01a\x02bc\x03def"
deserialized = deserialize(serialized)
# deserialized output should be: ['a', 'bc', 'def']
```

OFFICIAL PAGE TEXT

Our solution serializes and deserializes a list of strings by encoding the length of each string as a single character and concatenating it with the original string. The serialize function processes the input list of strings by iterating through each string. For every string, it first encodes the length of the string as a single character using the encodeNumber function. The encoded length is then appended to a result list, followed by the string itself. The result list is ultimately joined into a single string, which represents the serialized form of the list of strings. The deserialize function takes the serialized string and reconstructs the original list of strings. It starts by iterating through the serialized string, decoding the length of each string using the decodeNumber function, then extracting the string of that length from the serialized data. These strings are collected in a list and returned as the final deserialized result. Time Complexity: The time complexity of both serialize and deserialize is O(n), where n is the total number of characters across all strings in the input list. In serialize, we iterate through every string, performing constant-time operations (encoding the length and appending the string) for each string. Similarly, in deserialize, we iterate through the serialized string, decoding lengths and extracting substrings, which are also constant-time operations for each step. Space Complexity:

The space complexity is O(n) for both functions since we store the serialized form of the input list (which has a size proportional to the total number of characters across all strings) and reconstruct the list in deserialize.Daniel answers "Write a pair of functions to serialize and deserialize a list of strings."No answers contributed by the community yet.Related questionsWrite a function to do Excel-style operations.Write a function to check whether a string contains a substring.Given a list of bounding boxes and annotations, write a function to compute Intersection over Union.Related coursesCourseCourseSoftware Engineering Interview PrepLand your dream software engineering role at Google, Amazon, Microsoft, Meta, Apple, and other top companies. Learn from mock interviews, frameworks, and advice from senior candidates—practice data structures, algorithms, system design, people management, behavioral interviews, and more.Start learningCourseCourseSystem Design InterviewsLearn how to answer the latest system design questions across product, infrastructure, and AI domains. Features in-depth video examples, written breakdowns, and helpful reference patterns. Watch senior engineers and managers answer these questions in mock interview videos.Start learningPythonJavaScriptJavaC++PythonEditorShareLoading...OutputTest ResultsConsoleSign up to

run code

MEDIUM | IN APP LC 494 | Exponent | 143 of 165

Explain how to find a target sum in an array.

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TALK ALL TIME 41.1 30 DAYS 0 PRIORITY 88/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #494)

LeetCode match: LC 494 Target Sum

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age) | 3 interviews

Original: https://www.aced.io/questions/1439/find-target-sum-array

QUESTION

Determine the Number of Ways to Assign Symbols to Reach a Target Sum. You are given a list of non-negative integers, a1, a2, ..., an, and a target sum S. Your task is to assign each integer in the list a symbol + or - and calculate how many different ways there are to arrange these symbols such that the sum of the integers equals S after applying the assigned symbols. For example, if you have the list [1, 1, 1, 1, 1] and the target sum 3, one way to reach the target sum is to assign + to three 1s and - to two 1s, like so: +1 +1 +1 +1 -1. Another way could be +1 -1 +1 +1 +1. You need to return the total number of unique arrangements that meet the target sum S. Examples nums = [1, 1, 1, 1, 1] targetSum = 3 output: 5 nums = [1, 2, 1] targetSum = 2 output: 2 nums = [1, 2, 7, 1, 5, 3] targetSum = 8 output: -1 (Explanation: Since the total sum of the numbers plus the target is odd, it's not possible to reach the target sum.)The original problem asks for the number of ways to assign symbols (+ or -) to a list of numbers such that their sum equals a target sum S. This problem can be converted into a problem of finding subsets of the given numbers whose sum equals (totalSum + S) / 2. This is because if we can find subsets whose sum equals (totalSum + S) / 2, the remaining numbers will naturally form the other subset that sums to (totalSum - S) / 2, which effectively gives us the desired configuration of

symbols. NoteWhy (totalSum + S) / 2?Given a list of numbers nums=[a1,a2,...,an]\te

APPROACH

Count assignments: DP on sums (subset-sum transform: P = (total + target) / 2), or memoized DFS on (index, sum). O(n * sum).

HOW TO THINK ABOUT IT

Put a + in front of the numbers in a set P and a - in front of the rest N. Then sum(P) - sum(N) = S and sum(P) + sum(N) = total, so sum(P) = (total + S) / 2. The problem becomes 'count the subsets with this sum', a one-dimensional knapsack count. If (total + S) is odd or negative the answer is 0.

Basis: LeetCode 494, Target Sum: assign + or - to every number and count the assignments that add up to S (the data matches this reading; a Two Sum reading is given as a follow-up).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def go(i, total):
    if i == len(nums):
        return 1 if total == S else 0
    plus = go(i + 1, total + nums[i])
    minus = go(i + 1, total - nums[i])
    return plus + minus
answer = go(0, 0)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

Two branches per number: O(2^n). The numbers with a + sign form a subset with sum (total + S) / 2, so a subset-sum counting table is O(n * sum).

OPTIMAL SOLUTION · Subset-sum counting: choose P with sum (total + S) / 2

TIME	SPACE
O(n * sum)	O(sum)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The question was really 'find two numbers that add up to the target' (Two Sum).

One pass with a dictionary from value to index: for each x look for target - x among earlier values. O(n) time, O(n) space; with a sorted array use two pointers in O(1) space.

FOLLOW-UP 2 Only the existence of a subset with the target sum.

The same subset-sum table with booleans (or a bitset: reach |= reach << x) answers existence in O(n * sum / word size).

FOLLOW-UP 3 Negative numbers or a huge sum.

With negatives shift all values to be non-negative, or use a dictionary from reachable sum to count (memoised DFS on (index, sum)); with a huge sum the dictionary is only as large as the number of distinct reachable sums. **Cost:** O(n * R) with a dictionary over R reachable sums; shifting for negatives adds O(n).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


# BASE QUESTION (optimal): Subset-sum counting: choose P
# with sum (total + S) / 2
def count_signs(nums, target):
    # +/- signs reaching `target` equal a subset with sum
    # (total + target) / 2 that gets the plus signs. So
    # the
    # question becomes: how many subsets have that sum?
    total = sum(nums)
    if abs(target) > total or (total + target) % 2:
        return -1
    goal = (total + target) // 2
    ways = [1] + [0] * goal
    for x in nums:
        # go downward so every number is used at most once
        for s in range(goal, x - 1, -1):
            ways[s] += ways[s - x]
    return ways[goal]


# FOLLOW-UP 3: Negative numbers or a huge sum.
def count_signs_dict(nums, target):
    # follow-up: negative numbers or a huge sum. A
    # dictionary
    # from "reachable sum" to "number of ways" holds only
    # the
    # sums that really occur.
    seen = Counter({0: 1})
    for x in nums:
        nxt = Counter()
        for s, ways in seen.items():
            nxt[s + x] += ways
            nxt[s - x] += ways
        seen = nxt
    return seen[target]


# FOLLOW-UP 2: Only the existence of a subset with the
# target sum.
def subset_exists(nums, goal):
    # follow-up: only whether a subset reaches the sum.
    # The
    # set of reachable sums is one integer used as a
    # bitset.
    reach = 1
    for x in nums:
        reach |= reach << x
    return bool(reach >> goal & 1)


# FOLLOW-UP 1: The question was really 'find two numbers
# that add up to the target' ...
```

```python
def two_sum(nums, target):
    # the question may have meant Two Sum: one pass, a
    # dictionary from value to index of earlier numbers
    seen = {}
    for i, x in enumerate(nums):
        if target - x in seen:
            return seen[target - x], i
        seen[x] = i
    return None


# FOLLOW-UP 1: The question was really 'find two numbers
# that add up to the target' ...
def two_sum_sorted(nums, target):
    # sorted input: two pointers, O(1) extra space
    lo, hi = 0, len(nums) - 1
    while lo < hi:
        total = nums[lo] + nums[hi]
        if total == target:
            return lo, hi
        if total < target:
            lo += 1
        else:
            hi -= 1
    return None


if __name__ == "__main__":
    assert count_signs([1, 1, 1, 1, 1], 3) == 5
    assert count_signs([1, 2, 1], 2) == 2
    assert count_signs([1, 2, 7, 1, 5, 3], 8) == -1
    assert count_signs([1], 5) == -1
    assert count_signs([0, 0, 1], 1) == 4
    assert count_signs([], 0) == 1
    assert count_signs_dict([1, 1, 1, 1, 1], 3) == 5
    # negative numbers work with the dictionary version
```

```python
    assert count_signs_dict([-1, 2, 1], 2) == 2
    assert subset_exists([3, 34, 4, 12, 5, 2], 9)
    assert not subset_exists([3, 34, 4], 8)
    assert two_sum([2, 7, 11, 15], 9) == (0, 1)
    assert two_sum([1, 2], 7) is None
    assert two_sum_sorted([1, 3, 4, 8], 11) == (1, 3)
    import random
    for _ in range(300):
        nums = [random.randint(0, 4)
                for _ in range(random.randint(0, 7))]
        target = random.randint(-8, 12)
        want = count_signs_dict(nums, target)
        got = count_signs(nums, target)
        assert got == want or (got == -1 and want == 0)
```

OFFICIAL PAGE TEXT

Determine the Number of Ways to Assign Symbols to Reach a Target Sum. You are given a list of non-negative integers, a1, a2, ..., an, and a target sum S. Your task is to assign each integer in the list a symbol + or - and calculate how many different ways there are to arrange these symbols such that the sum of the integers equals S after applying the assigned symbols. For example, if you have the list [1, 1, 1, 1, 1] and the target sum 3, one way to reach the target sum is to assign + to three 1s and - to two 1s, like so: +1 +1 +1 +1 -1. Another way could be +1 -1 +1 +1 +1. You need to return the total number of unique arrangements that meet the target sum S. Examples

OFFICIAL PAGE TEXT

```
nums = [1, 1, 1, 1, 1]
targetSum = 3
output: 5

nums = [1, 2, 1]
targetSum = 2
output: 2

nums = [1, 2, 7, 1, 5, 3]
targetSum = 8
output: -1 (Explanation: Since the total sum of the nu
mbers plus the target is odd, it's not possible to rea
ch the target sum.)
```

The original problem asks for the number of ways to assign symbols (+ or -) to a list of numbers such that their sum equals a target sum S. This problem can be converted into a problem of finding subsets of the given numbers whose sum equals (totalSum + S) / 2. This is because if we can find subsets whose sum equals (totalSum + S) / 2, the remaining numbers will naturally form the other subset that sums to (totalSum - S) / 2, which effectively gives us the desired configuration of symbols. NoteWhy (totalSum + S) / 2?Given a list of numbers nums=[a1,a2,...,an]\text{nums} = [a_1, a_2, ..., a_n]nums=[a1,a2,...,an], we need to assign either a +++ or a --- to each number so that the total sum equals a target SSS.Let's denote the sum of the entire list as sum(nums)=totalSum\text{sum(nums)} = \text{totalSum}sum(nums)=totalSum.The problem can be rephrased as finding subsets of nums\text{nums}nums such that the difference between the sum of elements in the subset and the sum of elements not in the subset equals SSS.Formulating the Equation: Let PPP be the sum of elements with a +++ sign and NNN be the sum of elements with a --- sign. We need P-N=SP - N = SP-N=S. We also know that P+N=totalSumP + N = \text{totalSum}P+N=totalSum, where totalSum\text{totalSum}totalSum is the sum of all

OFFICIAL PAGE TEXT

elements in nums\text{nums}nums. Combining the Equations: Adding these two equations:P-N+P+N=S+totalSum2P=S+totalSumP - N + P + N = S + \text{totalSum}\\ 2P = S + \text{totalSum} P-N+P+N=S+totalSum2P=S+totalSumTherefore, P=S+totalSum2P = \frac{S + \text{totalSum}}{2}P=2S+totalSum.The problem now reduces to finding subsets of nums\text{nums}nums whose sum equals S+totalSum2\frac{S + \text{totalSum}}{2}2S+totalSum. Approach We define a recursive function find_subset that takes an index, the list of numbers, the target subset sum, and a memoization table (dp). The function recursively explores two possibilities at each step: Include the current number in the subset. Exclude the current number from the subset. The base cases for the recursion are: If the target subset sum (s) is zero, it means we found a valid subset, so we return 1. If we reach the end of the list without finding the subset sum, we return 0. If we have already computed the value for the current state (index and subset sum), we return the stored value from the memoization table to avoid redundant calculations. The changeSigns function calculates the total sum of the numbers and checks if it is possible to partition them to meet the required target sum S. If it is possible, it initializes the memoization table and

calls the find_subset function to compute the number of ways to achieve the target sum. Solution Time Complexity: The time complexity of this solution is O(n x (totalSum + S)) / 2, where n is the number of elements in the input list. This is because each state in the memoization table can be computed in constant time, and there are n x (totalSum + S) / 2 states to fill. Space Complexity: The space complexity of this solution is O(n x (totalSum + S) / 2) due to the memoization table used to store intermediate results. Additionally, the recursive call stack can go up to O(n) in the worst case, but this is dominated by the space required for the memoization table.Watch our mock Flipkart SWE (software engineering) interview. Neamah asks Rohan (Flipkart SWE) the Target Sum leetcode question.No answers contributed by the community yet.Related questionsFind a triplet in an array with a given sum.Given an array, find the two sum.Find quadruplets in an array with a given sum.Related coursesCourseCourseSoftware Engineering Interview PrepLand your dream software engineering role at Google, Amazon, Microsoft, Meta, Apple, and other top companies. Learn from mock interviews, frameworks, and advice from senior candidates—practice data structures, algorithms, system design, people management, behavioral interviews, and more.Start

OFFICIAL PAGE TEXT

learningCourseCourseSystem Design InterviewsLearn how to answer the latest system design questions across product, infrastructure, and AI domains. Features in-depth video examples, written breakdowns, and helpful reference patterns. Watch senior engineers and managers answer these questions in mock interview videos.Start learningPythonJavaScriptJavaC++PythonEditorShareLoading...OutputTest ResultsConsoleSign up to run code

MEDIUM | Exponent | 144 of 165

Count the number of ways to split a string.

ASKED (ANY CO.) ~3 YEARS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 177/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 1573 Number of Ways to Split a String (likely) (inferred from short statement)

Last asked (any company): 3 years ago, about 2023-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/3256/count-ways-to-split-string

QUESTION

Count the number of ways to split a string.

APPROACH

Count the target character; split positions are products of the gaps between required groups. If it is a generic split count, use DP on prefixes. Clarify the problem first.

INTERVIEW-DAY PLAN

CLARIFY FIRST

This prompt is vague, so ask first. The common version is LeetCode 1573: split a binary string into three non-empty parts with the same number of ones. Others are splits into equal parts, or splits into palindromes. State which you are solving.

BRUTE FORCE TO SAY OUT LOUD

Try every pair of cut positions and count ones in each part. O(n^3), or O(n^2) with prefix sums.

OPTIMAL IDEA

For the three-part binary version count the total ones. If it is not divisible by 3 the answer is 0; if there are none the answer is C(n - 1, 2). Otherwise let k be ones per part; the number of zeros between the k-th and (k+1)-th one (gap1) and between the 2k-th and (2k+1)-th one (gap2) give (gap1 + 1) * (gap2 + 1) ways, taken modulo 10^9 + 7. O(n).

INTERVIEW-DAY PLAN

DRY-RUN THESE CASES

All zeros of length 3, 4 and 5. A string with 3 ones. Ones not divisible by 3. Large n for modulo.

LIKELY FOLLOW-UPS

Split into k parts, or count palindromic splits with DP.

PITFALLS

Forgetting the all-zeros special case. Not applying the modulus to the product.

HOW TO THINK ABOUT IT

Ask which split question it is before solving. For 'equal ones' the answer depends only on where the ones are: the cuts have to fall inside the stretches of zeros that separate the groups of ones, so the count is a product of (zeros in the gap + 1). All-zero strings are a special case (choose any two cut points).

Basis: The prompt is vague; the usual version is LeetCode 1573, Number of Ways to Split a String (a binary string into three non-empty parts with equal numbers of ones, modulo 10^9 + 7).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s):
    n, count = len(s), 0
    for a in range(1, n - 1):
        for b in range(a + 1, n):
            parts = (s[:a], s[a:b], s[b:])
            ones = {p.count("1") for p in parts}
            if len(ones) == 1:
                count += 1
    return count
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

O(n^2) pairs. The cuts only depend on where the ones are, so the answer is a product of two gap sizes, computed in O(n).

OPTIMAL SOLUTION · Count the ones, multiply the gap sizes

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Split into m parts with equal ones.

The same argument: each of the m - 1 cut points sits in the gap after a multiple of k ones, so multiply the gap sizes; with no ones at all it is C(n - 1, m - 1).

FOLLOW-UP 2 Count ways to split into palindromes.

That is a different problem: dp[i] counts splits of the prefix, adding dp[j] for every palindromic s[j:i]; precompute the palindromic substrings with expand-around-center or a DP table in O(n^2).

FOLLOW-UP 3 The numbers get huge.

Return the answer modulo 10^9 + 7 and apply the modulus after every multiplication; in languages with fixed-width integers use 64-bit intermediates. **Cost:** O(n) with modular arithmetic; no big integers are needed.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from itertools import combinations
from math import comb

MOD = 10 ** 9 + 7


# BASE QUESTION (optimal): Count the ones, multiply the
# gap sizes
# FOLLOW-UP 1, 3: Split into m parts with equal ones.
def ways_to_split(s, parts=3, mod=MOD):
    # a binary string cut into `parts` non-empty pieces
    # that
    # hold the same number of 1s (LeetCode 1573 for
    # parts=3)
    n = len(s)
    if n < parts:
        return 0
    # FOLLOW-UP 1: parts=m: m pieces with equal ones
    ones = [i for i, ch in enumerate(s) if ch == "1"]
    if len(ones) % parts:
        return 0
    if not ones:
        # no ones: any choice of parts - 1 cut points
        # works
        total = comb(n - 1, parts - 1)
        return total % mod if mod else total
    each = len(ones) // parts
    answer = 1
    for cut in range(1, parts):
        # the cut lies in the run of zeros between the
        # last
        # 1 of piece `cut` and the first 1 of the next
        # piece
        gap = ones[cut * each] - ones[cut * each - 1]
        answer *= gap
        # FOLLOW-UP 3: huge counts: answer modulo 10^9 + 7
        if mod:
            answer %= mod
    return answer


# CHECKER (brute force)
def brute(s, parts):
    # oracle: try every choice of cut points
    count = 0
```

```
    for cuts in combinations(range(1, len(s)), parts - 1):
        edges = [0, *cuts, len(s)]
        spans = zip(edges, edges[1:])
        pieces = [s[a:b] for a, b in spans]
```

```
        if len({p.count("1") for p in pieces}) == 1:
            count += 1
    return count


# FOLLOW-UP 2: Count ways to split into palindromes.
def count_palindrome_splits(s):
    # follow-up: split into palindromes. dp[i] = ways to
    # cut
    # the first i letters; add dp[j] for every palindrome
    # s[j:i]. The table of palindromes is built first.
    n = len(s)
    pal = [[False] * n for _ in range(n)]
    for i in range(n - 1, -1, -1):
        for j in range(i, n):
            inner = j - i < 2 or pal[i + 1][j - 1]
            pal[i][j] = s[i] == s[j] and inner
    dp = [1] + [0] * n
    for i in range(1, n + 1):
        for j in range(i):
            if pal[j][i - 1]:
                dp[i] += dp[j]
    return dp[n]


def brute_palindromes(s):
    # oracle: try every set of cut points
    count = 0
    for size in range(len(s)):
        for cuts in combinations(range(1, len(s)), size):
            edges = [0, *cuts, len(s)]
            spans = zip(edges, edges[1:])
            pieces = [s[a:b] for a, b in spans]
            if all(p == p[::-1] for p in pieces):
                count += 1
    return count


if __name__ == "__main__":
    assert ways_to_split("10101") == 4
    assert ways_to_split("1001") == 0
```

```
    assert ways_to_split("0000") == 3
    assert ways_to_split("100100010100110") == 12
    assert ways_to_split("1100", parts=2) == 1
    assert ways_to_split("0000", parts=2) == 3
    assert ways_to_split("", parts=3) == 0
    # the modulus keeps the answer small for long strings
    big = "0" * 5000
    assert ways_to_split(big) == comb(4999, 2) % MOD
    assert ways_to_split(big, mod=None) == comb(4999, 2)
    assert count_palindrome_splits("aab") == 2
    assert count_palindrome_splits("aaa") == 4
    assert count_palindrome_splits("") == 1
    import random
    for _ in range(300):
        s = "".join(random.choice("0011")
                    for _ in range(random.randint(3, 10)))
        for parts in (2, 3, 4):
            want = brute(s, parts)
            got = ways_to_split(s, parts, mod=None)
            assert got == want
        t = "".join(random.choice("ab")
                    for _ in range(random.randint(1, 8)))
        want = brute_palindromes(t)
        assert count_palindrome_splits(t) == want
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

MEDIUM | IN APP LC 1376 | Exponent | 145 of 165

Given a large n-ary tree where the root node can pass information to one child per iteration, and in subsequent iterations, nodes can pass information to one child while the root continues with others, find the minimum number of iterations to reach all nodes.

ASKED (ANY CO.) ~4 YEARS AGO | OLDER

STUDY: TALK | ALL TIME 25.5 | 30 DAYS 0 | PRIORITY 137/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: your app's interview approach (LeetCode #1376)

LeetCode match: LC 1376 Time Needed to Inform All Employees

Last asked (any company): 4 years ago, about 2022-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/2411/minimum-iterations-information-distribution-n-ary-tree

QUESTION

Given a large n-ary tree where the root node can pass information to one child per iteration, and in subsequent iterations, nodes can pass information to one child while the root continues with others, find the minimum number of iterations to reach all nodes.

APPROACH

DFS/BFS from the root computing the max time along any root-to-leaf path (each node passes the info with its own delay); iterative to avoid recursion depth on large trees.

HOW TO THINK ABOUT IT

Each node can call one child per round, so a node with several children must choose an order. The subtree that needs the most rounds should be called first, because it starts earliest and the others can wait. That makes the time at a node the maximum over children of (position in the calling order + the child's own time), a bottom-up computation.

Basis: Tree broadcasting (minimum rounds). Not LeetCode 1376, which uses per-employee delays; here every node can inform one child per iteration.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def T(v):
    kids = children[v]
    if not kids:
        return 0
    best = INF
    for order in permutations(kids):
        finish = 0
        for i, c in enumerate(order, 1):
            finish = max(finish, i + T(c))
        best = min(best, finish)
    return best
```

TIME	SPACE
O(product of d! over nodes)	O(n)

WHY IT IS SLOW

A node with d children has d! orderings, so the cost is the product of d! over all nodes. Sorting the children by decreasing T gives the same answer in O(d log d).

OPTIMAL SOLUTION · Post-order DP: serve the slowest subtree first

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why is it optimal to serve the child with the largest subtree time first?

Exchange argument: if a child with time a is served in round i and one with time b >= a in round i + 1, swapping them changes the finish times from max(i + a, i + 1 + b) to max(i + b, i + 1 + a), and the second is never larger because b >= a. So sorting by decreasing T minimizes the maximum. **Cost:** sorting the children at each node makes the whole computation O(n log n); the exchange argument adds nothing.

FOLLOW-UP 2 What if each edge has a different transmission cost?

Replace the unit step by the cost: the child served in order position i can only start after the sum of the costs of the edges before it, so T(v) = max over i of (prefix cost up to child_i + T(child_i)). The best order is still decreasing (cost + T) only when costs are equal; in general it becomes a scheduling problem solved by sorting on T(child) - cost, i.e. Smith's rule.

FOLLOW-UP 3 Each call takes a different time per child.

The order still matters, and the right rule is Jackson's: serve children in decreasing order of their own finishing time T, whatever each call costs, because the finish of the child served at prefix cost P is P + T and the largest tail should start earliest. Checked against trying every order on random trees.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from itertools import permutations


def order_children(tree, node):
    # children of `node` as (child, cost) pairs
    return tree.get(node, [])


# FOLLOW-UP 2, 3: What if each edge has a different
# transmission cost?
def finish_times(tree, root):
    # time[v] = rounds until v and everything below has
    # the
    # news, once v has it. v calls its children one after
    # another; the call to the i-th child costs the edges
    # so
    # far, and that child then needs time[child] more.
    # Best order (Jackson's rule): the child with the
    # LARGEST time[child] first.
    order, stack = [], [root]
    while stack:
        node = stack.pop()
        order.append(node)
        kids = order_children(tree, node)
        stack.extend(c for c, _ in kids)
    time, plan = {}, {}
    # process children before parents
    for node in reversed(order):
        kids = sorted(order_children(tree, node),
                      key=lambda kc: -time[kc[0]])
        spent, worst = 0, 0
        for child, cost in kids:
            spent += cost
            worst = max(worst, spent + time[child])
        time[node] = worst
        plan[node] = [c for c, _ in kids]
    return time, plan


# BASE QUESTION (optimal): Post-order DP: serve the
# slowest subtree first
def min_rounds(tree, root):
    return finish_times(tree, root)[0][root]
```

```
# UNIT cost helper (every call takes 1 round)
def unit_tree(children):
    # every call takes one round
    return {v: [(c, 1) for c in kids]
            for v, kids in children.items()}


# CHECKER (brute force)
def brute(tree, node):
    # oracle: try every order of calls at every node
    kids = order_children(tree, node)
```

```
    if not kids:
        return 0
    best = float("inf")
    for perm in permutations(kids):
        spent, worst = 0, 0
        for child, cost in perm:
            spent += cost
            worst = max(worst, spent + brute(tree, child))
        best = min(best, worst)
    return best


if __name__ == "__main__":
    # a root with three leaves needs 3 rounds
    star = unit_tree({"r": ["a", "b", "c"]})
    assert min_rounds(star, "r") == 3
    assert min_rounds({}, "r") == 0
    # serve the child with the deeper subtree first
    deep = unit_tree({"r": ["a", "b"], "b": ["c", "d"]})
    assert min_rounds(deep, "r") == 3
    # the plan: b (the slow subtree) is called before a
    plan = finish_times(deep, "r")[1]
    assert plan["r"] == ["b", "a"]
    # calls with different costs: (child, cost)
    costly = {"r": [("a", 5), ("b", 1)], "b": [("c", 1)]}
    assert min_rounds(costly, "r") == 6
    import random
    for _ in range(200):
        tree, nodes = {}, [0]
        for v in range(1, random.randint(1, 7)):
            parent = random.choice(nodes)
            cost = random.randint(1, 4)
            tree.setdefault(parent, []).append((v, cost))
            nodes.append(v)
```

```
        assert min_rounds(tree, 0) == brute(tree, 0)
    # a very deep tree does not need recursion
    chain = {i: [(i + 1, 1)] for i in range(20000)}
    assert min_rounds(chain, 0) == 20000
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

MEDIUM | Exponent | 146 of 165

Determine if two sentences are similar.

ASKED (ANY CO.) ~4 YEARS AGO | OLDER

STUDY: TALK | ALL TIME 21 | 30 DAYS 0 | PRIORITY 143/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 1813 Sentence Similarity III

Last asked (any company): 4 years ago, about 2022-10 (Exponent shows only a rough age) | 1 interview

Original: https://www.aced.io/questions/2280/determine-similar-sentences

QUESTION

Determine if Two Sentences Are Similar. Two sentences are similar if they have the same length and each pair of corresponding words in the two sentences is similar. The similarity between words is defined by the provided list of similar word pairs. A word is always similar to itself. For example, if we have the list of similar word pairs as [("great", "good"), ("acting","drama"), ("skills","talent")], then the sentences "You have great acting skills" and "You have good drama talent" are similar. Examples sentence1 = ["Let's", "code", "in", "Python"] sentence2 = ["Let's", "program", "in", "Python"] similarPairs = [("code", "program"),] output: true sentence1 = ["I", "love", "to", "play", "football"] sentence2 = ["I", "love", "playing", "soccer"] similarPairs = [("play", "playing"), ("football", "soccer")] output: false, different sentence lengths sentence1 = ["Do", "you", "like", "coffee"] sentence2 = ["Do", "you", "love", "coffee"] similarPairs = [("like", "enjoy"), ("coffee", "tea"),] output: false

"like" is not similar to

"love" based on the given pairs. sentence1 = ["I", "really", "love", "leetcode", "and", "apples"] sentence2 = ["I", "so", "like", "codesignal", "and", "oranges"] similarPairs = [("very", "so"), ("love", "adore"), ("really", "very"), ("leetcode", "codesignal"), ("apples", "oranges"), ("like", "adore"),] output: trueThe provided solution checks if two given sentences are similar by using a graph-based approach. It constructs a graph where words are c

APPROACH

Two pointers: match the longest common prefix and suffix of the word lists; similar iff the shorter sentence is fully covered by prefix + suffix.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask which version: similarity from a list of word pairs (LeetCode 734 or 737), and whether similarity is transitive (737) or not (734). If instead one sentence is the other with a block inserted in the middle (LeetCode 1813), say so and solve that. Ask about case and equal length.

BRUTE FORCE TO SAY OUT LOUD

For each position check the pair against the list by scanning it. O(n * P).

OPTIMAL IDEA

Put the pairs in a set (both directions) for the non-transitive version: lengths must match and each word pair is equal or in the set, O(n + P). For the transitive version build a union-find over words and compare roots. For the insert-a-block version use two pointers to match the common prefix and the common suffix; the sentences are similar if the shorter one is fully covered.

DRY-RUN THESE CASES

INTERVIEW-DAY PLAN

Different lengths, identical sentences, a pair that is only transitively similar (decides the version), duplicate pairs.

LIKELY FOLLOW-UPS

Make similarity transitive, add weights, or allow at most one unmatched word.

PITFALLS

Assuming similarity is symmetric when the pairs are one-directional. Using lists instead of sets.

HOW TO THINK ABOUT IT

Ask which similarity you have: from a pair list, transitive or not. Without transitivity it is a set lookup per word pair. With transitivity, similar words form groups, which is union-find (or BFS on a word graph). The variant where a block is inserted is a different problem: match the common prefix and suffix of the word lists.

Basis: LeetCode 734 (similarity from a list of word pairs), 737 (the same with transitive similarity) and 1813 (one sentence is the other with a block inserted); the question text matches 734/737.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s1, s2, pairs):
    if len(s1) != len(s2):
        return False
    for a, b in zip(s1, s2):
        if a == b:
            continue
        if [a, b] in pairs or [b, a] in pairs:
            continue
        return False
    return True
```

TIME	SPACE
O(n * P)	O(1)

WHY IT IS SLOW

Each word pair scans the whole pair list, O(n * P). Putting the pairs into a set makes each check O(1).

OPTIMAL SOLUTION · Set of pairs (not transitive)

TIME	SPACE
O(n + P)	O(P)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Similarity is transitive (a ~ b and b ~ c means a ~ c).

Union-find over the words: union each pair, then two words are similar if they are equal or have the same root. Path compression keeps it near O(n + P).

FOLLOW-UP 2 One sentence is the other with a sentence of words inserted somewhere (LeetCode 1813).

Match the longest common prefix and the longest common suffix of the word lists; the shorter list must be covered by prefix plus suffix.

FOLLOW-UP 3 Case should not matter, or words can have synonyms with scores.

Normalise with casefold before hashing. For scores, a graph with weighted edges and a threshold query turns it into reachability along strong edges.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict, deque


# BASE QUESTION (optimal): Set of pairs (not transitive)
def similar_direct(s1, s2, pairs):
    # same length, and every pair of words is equal or a
    # listed pair (in either direction)
    if len(s1) != len(s2):
        return False
    allowed = {frozenset(p) for p in pairs}
    return all(a == b or frozenset((a, b)) in allowed
               for a, b in zip(s1, s2))


class DisjointSet:
    def __init__(self):
        self.parent = {}

    def find(self, x):
        self.parent.setdefault(x, x)
        root = x
        while self.parent[root] != root:
            root = self.parent[root]
        # path compression: point everything on the way up
        # straight at the root
        while self.parent[x] != root:
            self.parent[x], x = root, self.parent[x]
        return root

    def union(self, a, b):
        self.parent[self.find(a)] = self.find(b)


# FOLLOW-UP 1: Similarity is transitive (a ~ b and b ~ c
# means a ~ c).
def similar_transitive(s1, s2, pairs):
    # follow-up: a ~ b and b ~ c means a ~ c, so words are
    # grouped with union-find
    if len(s1) != len(s2):
        return False
    groups = DisjointSet()
    for a, b in pairs:
        groups.union(a, b)
    return all(a == b or groups.find(a) == groups.find(b)
               for a, b in zip(s1, s2))
```

```
# FOLLOW-UP 2: One sentence is the other with a sentence
```

```
# of words inserted somewhere ...
def similar_insertion(s1, s2):
    # follow-up (LeetCode 1813): one sentence is the other
    # with a block of words inserted somewhere. The
    # shorter
    # one must be covered by a common prefix plus a common
    # suffix of the two.
    if len(s1) > len(s2):
        s1, s2 = s2, s1
    head = 0
    while head < len(s1) and s1[head] == s2[head]:
        head += 1
    tail = 0
    room = len(s1) - head
    while tail < room and s1[-1 - tail] == s2[-1 - tail]:
        tail += 1
    return head + tail == len(s1)


# FOLLOW-UP 3: Case should not matter, or words can have
# synonyms with scores.
def normalise(words):
    # follow-up: case does not matter
    return [w.casefold() for w in words]


# CHECKER (brute force)
def reachable(a, b, pairs):
    # oracle: breadth first search over the similarity
    # graph
    graph = defaultdict(set)
    for x, y in pairs:
        graph[x].add(y)
        graph[y].add(x)
    seen, queue = {a}, deque([a])
    while queue:
        cur = queue.popleft()
        if cur == b:
            return True
        for nxt in graph[cur] - seen:
            seen.add(nxt)
            queue.append(nxt)
```

```
    return False


if __name__ == "__main__":
    pairs = [("great", "good"), ("acting", "drama"),
             ("skills", "talent")]
    a = "You have great acting skills".split()
    b = "You have good drama talent".split()
    assert similar_direct(a, b, pairs)
    assert not similar_direct(a, b[:-1], pairs)
    assert not similar_direct(["a"], ["b"], [])
    assert similar_direct(["a"], ["a"], [])
    # chain: good ~ fine and fine ~ okay, so good ~ okay
    chain = [("good", "fine"), ("fine", "okay")]
    assert not similar_direct(["good"], ["okay"], chain)
    assert similar_transitive(["good"], ["okay"], chain)
    assert similar_insertion("My name is Haley".split(),
                             "My Haley".split())
    assert similar_insertion(["of"], ["A", "lot", "of"])
    eating = "Eating right now".split()
    assert similar_insertion(eating, ["Eating"])
    assert not similar_insertion(["a", "b"], ["c", "d"])
    assert normalise(["Great"]) == ["great"]
    import random
    for _ in range(300):
        words = "abcde"
        pr = [tuple(random.sample(words, 2))
              for _ in range(random.randint(0, 4))]
        x, y = random.choice(words), random.choice(words)
        want = reachable(x, y, pr)
```

```
        assert similar_transitive([x], [y], pr) == want
```

OFFICIAL PAGE TEXT

Determine if Two Sentences Are Similar. Two sentences are similar if they have the same length and each pair of corresponding words in the two sentences is similar. The similarity between words is defined by the provided list of similar word pairs. A word is always similar to itself. For example, if we have the list of similar word pairs as [("great", "good"), ("acting","drama"), ("skills","talent")], then the sentences "You have great acting skills" and "You have good drama talent" are similar. Examples

```
sentence1 = ["Let's", "code", "in", "Python"]
sentence2 = ["Let's", "program", "in", "Python"]
similarPairs = [
    ("code", "program"),
]
output: true

sentence1 = ["I", "love", "to", "play", "football"]
sentence2 = ["I", "love", "playing", "soccer"]
similarPairs = [("play", "playing"), ("football", "soc
cer")]
output: false, different sentence lengths

sentence1 = ["Do", "you", "like", "coffee"]
sentence2 = ["Do", "you", "love", "coffee"]
similarPairs = [
    ("like", "enjoy"),
    ("coffee", "tea"),
]
output: false  # "like" is not similar to "love" based
 on the given pairs.

sentence1 = ["I", "really", "love", "leetcode", "and",
 "apples"]
sentence2 = ["I", "so", "like", "codesignal", "and", "
oranges"]
similarPairs = [
    ("very", "so"),
    ("love", "adore"),
    ("really", "very"),
    ("leetcode", "codesignal"),
```

```
    ("apples", "oranges"),
    ("like", "adore"),
]
output: true
```

OFFICIAL PAGE TEXT

The provided solution checks if two given sentences are similar by using a graph-based approach. It constructs a graph where words are connected if they are similar according to the provided pairs. Then, it performs a depth-first search (DFS) to check if each pair of corresponding words from the two sentences are connected in the graph. The Depth-First Search (DFS) algorithm is well-suited for this question as it efficiently explores the graph structure created from the similar word pairs. DFS is ideal for checking connectivity between words, which aligns with the task of determining if two words are similar based on the provided pairs. Its memory efficiency is beneficial for handling potentially large sets of sentences and word pairs. Additionally, DFS offers a simple implementation, either through recursion or using a stack, which aids in writing clean and understandable code. Its flexibility allows for easy modification to incorporate additional constraints or optimizations if needed. Therefore, DFS provides an elegant and effective solution for traversing the graph and determining sentence similarity. Remember to handle potential off-by-one errors when implementing this solution due to index-based iteration over the sentences. Time Complexity: Let n be the maximum number of words in the sentences, and m be the number of similar word pairs. Constructing the

graph takes O(m) time. Then, for each word pair, the DFS takes O(n) time in the worst case, resulting in a total time complexity of O(n + m). Space Complexity: In the worst case, the graph can contain O(m) edges. Additionally, in the DFS, the space complexity is O(n) due to the recursion stack or auxiliary data structures to track visited nodes. Therefore, the overall space complexity is O(n + m).Watch Simon, software engineer at Google, answer the question "determine if two sentences are similar."No answers contributed by the community yet.Related questionsDetermine if a number is a power of two.Determine if two words are sorted in lexicographic order.Related coursesCourseCourseSoftware Engineering Interview PrepLand your dream software engineering role at Google, Amazon, Microsoft, Meta, Apple, and other top companies. Learn from mock interviews, frameworks, and advice from senior candidates—practice data structures, algorithms, system design, people management, behavioral interviews, and more.Start learningCourseCourseSystem Design InterviewsLearn how to answer the latest system design questions across product, infrastructure, and AI domains. Features in-depth video examples, written breakdowns, and helpful reference patterns. Watch senior engineers and managers answer these questions in mock interview videos.Start lea

rningPythonJavaScriptJavaC++PythonEditorShareLoading...OutputTest ResultsConsoleSign up to run code

Easy (8)

EASY | IN APP LC 125 | Exponent | 147 of 165

Is this a valid palindrome?

ASKED (ANY CO.) ~6 MONTHS AGO | OLDER

STUDY: TYPE | ALL TIME 52.8 | 30 DAYS 51.4 | PRIORITY 21/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #125)

LeetCode match: LC 125 Valid Palindrome

Last asked (any company): 6 months ago, about 2026-04 (Exponent shows only a rough age) | +612 interviews

Original: https://www.aced.io/questions/4056/validate-palindrome-check

QUESTION

Given a string s, return true if it is a palindrome, and false otherwise. A string is considered a palindrome if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Write a function isPalindrome that implements this logic. Examples Input: s = "H123!@321h" Output: true Input: s = "race a car" Output: false Constraints 1 <= s.length <= 2 * 10^5 The input string s can include any printable ASCII characters. Challenge 1Can you come up with a solution that achieves O(n) time complexity?Challenge 2Can you come up with a solution that achieves O(1) space complexity?Solution 1: Filtering and Reversing Approach This solution processes the input string by first filtering out non-alphanumeric characters and converting all remaining characters to lowercase. It then checks if this filtered string reads the same forward and backward. Filtering: Iterate through the string and collect alphanumeric characters while converting them to lowercase. Reversing and Comparing: Create a reversed version of the filtered string and compare it with the original filtered string to check for palindrome properties. Time Complexity: The time complexity is O(n), where n is the length of the input string. This is because filtering the characters and creating the reversed string both require iterating through the input

once. Space Complexity: The space complexity is O(n) for storing the filtered characters and their

APPROACH

Two pointers from both ends skipping non-alphanumerics and comparing case-insensitively. O(n), O(1).

HOW TO THINK ABOUT IT

A palindrome is symmetric, so compare the two ends and move inward; there is no need to build the reversed string. Decide what to ignore (non-alphanumerics, case) and skip those characters with the pointers instead of copying a cleaned string.

Basis: LeetCode 125, Valid Palindrome, and 680 (Valid Palindrome II).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def is_palindrome(s):
    t = [c.lower() for c in s if c.isalnum()]
    return t == t[::-1]
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

O(n) time but two extra copies of the string, O(n) space. Two pointers moving inward, skipping punctuation, need O(1) space and stop at the first mismatch.

OPTIMAL SOLUTION · Two pointers that skip ignored characters

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 You may delete at most one character (LeetCode 680).

Move inward until the first mismatch, then the answer is whether skipping the left character or skipping the right character leaves a palindrome. That is two more linear checks, so O(n) overall.

FOLLOW-UP 2 Unicode, accents, or locale-specific case.

Normalise first (unicodedata.normalize and casefold) and decide what counts as a letter. str.isalnum handles many scripts, but combining marks need normalisation.

FOLLOW-UP 3 Longest palindromic substring.

Expand around each of the 2n - 1 centers in O(n^2), or use Manacher's algorithm in O(n). The two-pointer comparison is the building block.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import unicodedata


# FOLLOW-UP 2: Unicode, accents, or locale-specific case.
def clean(s):
    # follow-up: unicode. Decompose accents, drop the
    # combining marks, fold case, keep letters and digits.
    text = unicodedata.normalize("NFKD", s)
    text = "".join(ch for ch in text
                   if not unicodedata.combining(ch))
    return [ch for ch in text.casefold() if ch.isalnum()]


# BASE QUESTION (optimal): Two pointers that skip ignored
# characters
def is_palindrome(s):
    # compare the cleaned characters from both ends inward
    chars = clean(s)
    lo, hi = 0, len(chars) - 1
    while lo < hi:
        if chars[lo] != chars[hi]:
            return False
        lo += 1
        hi -= 1
    return True


# SAME check without a cleaned copy
def is_palindrome_in_place(s):
    # the same without building a cleaned copy: two
    # pointers
    # on the original string skip non-alphanumeric
    # characters
    lo, hi = 0, len(s) - 1
    while lo < hi:
        if not s[lo].isalnum():
            lo += 1
        elif not s[hi].isalnum():
            hi -= 1
        elif s[lo].lower() != s[hi].lower():
            return False
        else:
            lo += 1
            hi -= 1
    return True
```

```
# FOLLOW-UP 1: You may delete at most one character
# (LeetCode 680).
def almost_palindrome(s):
    # follow-up (LeetCode 680): at most one deletion. At
    # the
    # first mismatch try skipping the left or the right
    # character; each is one more linear check.
    chars = clean(s)

    def straight(lo, hi):
        while lo < hi:
            if chars[lo] != chars[hi]:
                return False
            lo += 1
            hi -= 1
        return True

    lo, hi = 0, len(chars) - 1
    while lo < hi:
        if chars[lo] != chars[hi]:
            skip_left = straight(lo + 1, hi)
            return skip_left or straight(lo, hi - 1)
        lo += 1
        hi -= 1
    return True
```

```
# FOLLOW-UP 3: Longest palindromic substring.
def longest_palindromic_substring(s):
    # follow-up: expand around each of the 2n - 1 centres
    best = ""
    for centre in range(2 * len(s) - 1):
        i = centre // 2
        j = i + centre % 2
        while i >= 0 and j < len(s) and s[i] == s[j]:
            i -= 1
            j += 1
        if j - i - 1 > len(best):
            best = s[i + 1:j]
    return best


if __name__ == "__main__":
```

```
    assert is_palindrome("H123!@321h")
    assert not is_palindrome("race a car")
    assert is_palindrome("A man, a plan, a canal: Panama")
    assert is_palindrome("")
    assert is_palindrome(".,")
    assert is_palindrome("Été")
    assert is_palindrome_in_place("H123!@321h")
    assert not is_palindrome_in_place("race a car")
    assert almost_palindrome("abca")
    assert almost_palindrome("raceacar")
    assert not almost_palindrome("abcdef")
    assert almost_palindrome("a")
    assert longest_palindromic_substring("babad") in (
        "bab", "aba")
    assert longest_palindromic_substring("cbbd") == "bb"
    import random
    for _ in range(300):
        s = "".join(random.choice("aB,c ")
                    for _ in range(random.randint(0, 9)))
        kept = "".join(clean(s))
        assert is_palindrome(s) == (kept == kept[::-1])
        quick = is_palindrome_in_place(s)
        assert quick == is_palindrome(s)
        near = kept == kept[::-1]
        for i in range(len(kept)):
            rest = kept[:i] + kept[i + 1:]
            near = near or rest == rest[::-1]
        assert almost_palindrome(s) == near
```

OFFICIAL PAGE TEXT

Given a string s, return true if it is a palindrome, and false otherwise. A string is considered a palindrome if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Write a function isPalindrome that implements this logic. Examples

```
Input: s = "H123!@321h"
Output: true

Input: s = "race a car"
Output: false
```

OFFICIAL PAGE TEXT

Constraints 1 <= s.length <= 2 * 10^5 The input string s can include any printable ASCII characters. Challenge 1Can you come up with a solution that achieves O(n) time complexity?Challenge 2Can you come up with a solution that achieves O(1) space complexity?Solution 1: Filtering and Reversing Approach This solution processes the input string by first filtering out non-alphanumeric characters and converting all remaining characters to lowercase. It then checks if this filtered string reads the same forward and backward. Filtering: Iterate through the string and collect alphanumeric characters while converting them to lowercase. Reversing and Comparing: Create a reversed version of the filtered string and compare it with the original filtered string to check for palindrome properties. Time Complexity: The time complexity is O(n), where n is the length of the input string. This is because filtering the characters and creating the reversed string both require iterating through the input once. Space Complexity: The space complexity is O(n) for storing the filtered characters and their reversed copy. This space is needed to hold the filtered string and its reversed version. Solution 2: Two-Pointer Approach This solution uses a two-pointer technique to efficiently check if the string is a palindrome. The idea is to use one pointer starting from the beginning of the string (left) and another pointer from the end (right).

The pointers move towards each other, skipping non-alphanumeric characters and comparing characters that are alphanumeric. Pointer Initialization: Set two pointers: left at the beginning and right at the end of the string. Skipping Non-Alphanumeric Characters: Move the left pointer to the right while skipping non-alphanumeric characters, and similarly move the right pointer to the left. Comparison: Compare the characters at left and right in a case-insensitive manner. If characters do not match, the string is not a palindrome. Update Pointers: Move the pointers closer to each other and repeat until the pointers meet or cross. Time Complexity: The time complexity is O(n), where n is the length of the string. Each character is processed at most twice (once by each pointer). Space Complexity: The space complexity is O(1) as it only uses a constant amount of extra space for the two pointers, regardless of the size of the input string. NoteCheck out our lesson on the two-pointer approach to learn more about it and its applications!No answers contributed by the community yet.

EASY | Exponent | 148 of 165

Return all unique substrings of a given string.

ASKED (ANY CO.) ~6 MONTHS AGO | OLDER

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 215/224

ABOUT THIS QUESTION

Topic: Trie and Prefix Indexing

Optimal answer from: written and tested here for this exact question

LeetCode match: No direct match (substring enumeration) (inferred from short statement)

Last asked (any company): 6 months ago, about 2026-04 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/1223/unique-substrings-given-string

QUESTION

Return all unique substrings of a given string.

APPROACH

Double loop adding s[i:j] to a set, O(n^2) substrings (O(n^3) chars). Mention a suffix automaton/trie for large n.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether to return the substrings or just count them, whether the empty string counts, the maximum length of the string, and whether order matters.

BRUTE FORCE TO SAY OUT LOUD

Double loop adding s[i:j] to a set. O(n^2) substrings and up to O(n^3) characters in total.

OPTIMAL IDEA

For small n the set is fine. To count without storing, build a suffix automaton or a suffix array with LCP: the number of distinct substrings is the sum of (n - suffix_start) minus the LCP values, O(n log n). A trie over all suffixes also works at O(n^2).

DRY-RUN THESE CASES

Empty string, a single character, all equal characters (n substrings), a string with no repeats (n(n + 1) / 2).

LIKELY FOLLOW-UPS

Count only, the k-th lexicographic substring, or the longest repeated substring.

PITFALLS

Counting the empty string by accident. Using a list instead of a set and returning duplicates.

HOW TO THINK ABOUT IT

If the output must list the substrings, its size already is quadratic, so a set over all slices is the honest answer. If only the count is needed, nothing needs to be stored: distinct substrings equal total suffix lengths minus the sum of longest-common-prefixes between adjacent sorted suffixes.

Basis: Written; counting distinct substrings is a classic (suffix array with LCP, suffix automaton).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(s):
    result = set()
    for i in range(len(s)):
        for j in range(i + 1, len(s) + 1):
            result.add(s[i:j])
    return result
```

TIME	SPACE
O(n^3)	O(n^3)

WHY IT IS SLOW

There are about n^2 / 2 substrings and each slice copies up to n characters: O(n^3) time and space. If only the count is needed, a suffix array with LCP counts them in O(n log n) without storing any.

OPTIMAL SOLUTION · Count with a suffix array and LCP

TIME	SPACE
O(n^2 log n) with naive sorting (O(n log n) with a real suffix array)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 List them without building duplicates first.

Insert every suffix into a trie; a substring is new exactly when its trie node is created. O(n^2) time and nodes, and the substrings appear without duplicates.

FOLLOW-UP 2 Return the k-th lexicographic distinct substring, or the longest repeated substring.

Both use the suffix array with LCP: the longest repeated substring is the maximum LCP value, and the k-th substring is found by walking the sorted suffixes and subtracting the new prefixes each one contributes.

FOLLOW-UP 3 The string has a million characters.

Quadratic is out. Build a suffix automaton (O(n)) and count distinct substrings as the sum of len(v) - len(link(v)) over states, or use a suffix array with O(n log n) construction.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Count with a suffix array and
# LCP
def unique_substrings(s):
    # simplest: every slice into a set, then sort. O(n^3).
    return sorted({s[i:j] for i in range(len(s))
                   for j in range(i + 1, len(s) + 1)})


# FOLLOW-UP 1: List them without building duplicates
# first.
def trie_substrings(s):
    # follow-up: no duplicates built first. Insert every
    # suffix into a trie; a substring is new exactly when
    # its
    # node is created while inserting.
    root = {}
    for start in range(len(s)):
        node = root
        for end in range(start, len(s)):
            ch = s[end]
            if ch not in node:
                node[ch] = {}
                yield s[start:end + 1]
            node = node[ch]


def suffix_array(s):
    # start positions of all suffixes in sorted order
    return sorted(range(len(s)), key=lambda i: s[i:])


def lcp_array(s, sa):
    # Kasai: lcp[i] = common prefix of suffix sa[i] and
    # the
    # one before it, found in O(n) in total
    n = len(s)
    rank = [0] * n
    for i, start in enumerate(sa):
        rank[start] = i
    lcp, h = [0] * n, 0
    for start in range(n):
        if rank[start] > 0:
            prev = sa[rank[start] - 1]
            while (start + h < n and prev + h < n
                   and s[start + h] == s[prev + h]):
                h += 1
            lcp[rank[start]] = h
            h = max(h - 1, 0)
        else:
            h = 0
    return lcp


# FOLLOW-UP 2: Return the k-th lexicographic distinct
# substring, or the longest ...
def kth_substring(s, k):
    # follow-up: the k-th distinct substring in dictionary
    # order. Walk the sorted suffixes: each one brings
    # n - start - lcp new prefixes.
    sa = suffix_array(s)
    lcp = lcp_array(s, sa)
    for i, start in enumerate(sa):
        fresh = len(s) - start - lcp[i]
        if k <= fresh:
            return s[start:start + lcp[i] + k]
        k -= fresh
    return None


# FOLLOW-UP 2: Return the k-th lexicographic distinct
# substring, or the longest ...
def longest_repeated(s):
    # follow-up: the biggest lcp value is the longest
    # substring that occurs at least twice
    sa = suffix_array(s)
    lcp = lcp_array(s, sa)
    if not s or max(lcp) == 0:
        return ""
    best = max(range(len(s)), key=lcp.__getitem__)
    return s[sa[best]:sa[best] + lcp[best]]


# FOLLOW-UP 3: The string has a million characters.
def count_distinct(s):
    # follow-up: a million characters. A suffix automaton
    # is
    # built in O(n); the distinct substrings number
    # sum(len[v] - len[link[v]]) over its states.
    length, link, nxt = [0], [-1], [{}]
    last = 0
    for ch in s:
        cur = len(length)
        length.append(length[last] + 1)
        link.append(0)
        nxt.append({})
        p = last
        while p != -1 and ch not in nxt[p]:
            nxt[p][ch] = cur
            p = link[p]
        if p != -1:
            q = nxt[p][ch]
            if length[p] + 1 == length[q]:
                link[cur] = q
            else:
                # split q: a clone with the shorter length
                clone = len(length)
                length.append(length[p] + 1)
                link.append(link[q])
                nxt.append(dict(nxt[q]))
                while p != -1 and nxt[p].get(ch) == q:
                    nxt[p][ch] = clone
                    p = link[p]
                link[q] = link[cur] = clone
        last = cur
    return sum(length[v] - length[link[v]]
               for v in range(1, len(length)))


if __name__ == "__main__":
    assert unique_substrings("abc") == [
        "a", "ab", "abc", "b", "bc", "c"]
    assert unique_substrings("aaa") == ["a", "aa", "aaa"]
    assert unique_substrings("") == []
    three = sorted(trie_substrings("aaa"))
    assert three == ["a", "aa", "aaa"]
    assert kth_substring("abc", 4) == "b"
    assert kth_substring("abc", 7) is None
    assert longest_repeated("banana") == "ana"
    assert longest_repeated("abcd") == ""
    assert count_distinct("aaa") == 3
```

```
assert count_distinct("") == 0
import random
for _ in range(300):
    s = "".join(random.choice("abc")
                for _ in range(random.randint(0, 9)))
```

```
        want = unique_substrings(s)
        assert sorted(trie_substrings(s)) == want
        assert len(list(trie_substrings(s))) == len(want)
        assert count_distinct(s) == len(want)
        for k, sub in enumerate(want, 1):
            assert kth_substring(s, k) == sub
```

EASY | Exponent | 149 of 165

Find the Duplicates

ASKED (ANY CO.) ~7 MONTHS AGO | OLDER

STUDY: TALK | ALL TIME 28.2 | 30 DAYS 0 | PRIORITY 129/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Related in your app (a neighbouring problem, not this exact question): LeetCode #350 Intersection of Two Arrays II

LeetCode match: LC 350 Intersection of Two Arrays II

Last asked (any company): 7 months ago, about 2026-03 (Exponent shows only a rough age) | +15 interviews

Original: https://www.aced.io/questions/3056/find-the-duplicates

QUESTION

Given two sorted arrays arr1 and arr2 of passport numbers, implement a function findDuplicates that returns an array of all passport numbers that are both arrays. Note that the output array should be sorted in ascending order. Let N and M be the lengths of arr1 and arr2, respectively. Solve for two cases and analyze the time & space complexities of your solutions: M ~ N - the array lengths are approximately the same M >> N - arr2 is much bigger than arr1. Example input: arr1 = [1, 2, 3, 5, 6, 7], arr2 = [3, 6, 7, 8, 20] output: [3, 6, 7]

since only these three values

QUESTION

are both in arr1 and arr2Hint 1Start with a brute force solution and optimize from there.Hint 2Note that the question asks for a sorted array. What techniques work well on sorted arrays?Hint 3If M >> N (case #2) is giving you trouble, consider how you might use the values of N, the shorter array, to increase the efficiency of your answer.Challenge 1Have you taken care to avoid array out-of-bound runtime errors?First, the brute force solution. Try two nested loops. For every value arr1[i] in the outer loop, we look it up in arr2 in the inner loop. The time complexity of this algorithm in the worst case scenario is O(N*M). Not very efficient. We can do better than that. Case 1 (M ~ N) We can use the fact the arrays are sorted to traverse both of them in an in-order manner at the same time. The general idea of the algorithm is to use two indices, i and j, for arr1 and arr2, respectively. Every time one of indices,

APPROACH

Two pointers when sizes are similar (O(N+M), O(1) space). When one array is much smaller, binary search each element of the small array in the large one (O(M log N)). Skip repeats to keep output unique.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether duplicates within one array count once in the output, whether the output must be sorted (yes), the relative sizes N and M (the statement asks for two cases), and the value range.

BRUTE FORCE TO SAY OUT LOUD

Put one array in a set and scan the other. O(N + M) time, O(min(N, M)) space, fine but ignores the sorted input.

OPTIMAL IDEA

Similar sizes: two pointers, advancing the smaller value, collecting equal values and skipping repeats. O(N + M) time, O(1) extra space. M much bigger than N: for each element of the small array binary search the large one, O(N log M), which beats O(N + M) when N is small. Exponential (galloping) search from the previous position gives O(N log(M / N)).

DRY-RUN THESE CASES

No common values, all common, repeated values in one array, an empty array, one array a single element.

LIKELY FOLLOW-UPS

Three arrays, unsorted arrays, or arrays too big for memory (merge from files).

PITFALLS

Using O(M log N) for the second case: you search the large array N times, so it is O(N log M). Returning the same value twice.

HOW TO THINK ABOUT IT

Both arrays are sorted, so the question is how the two sizes compare. If they are about the same size, walk both with two pointers and advance the smaller one. If one is much smaller, do not walk the big one: binary search each element of the small array in the big array. Always say the cost in terms of both sizes N and M.

Basis: Intersection of two sorted arrays (LeetCode 349 / 350). Output: values present in both arrays, sorted, each once.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(arr1, arr2):
    found = []
    for x in arr1:
        for y in arr2:
            if x == y and x not in found:
                found.append(x)
    return sorted(found)
```

TIME	SPACE
O(N * M)	O(1) extra

WHY IT IS SLOW

N * M comparisons. Two pointers on the sorted arrays are O(N + M), and binary searching the big array for each element of the small one is O(N log M).

OPTIMAL SOLUTION · Case 1 (M close to N): two pointers

TIME	SPACE
O(N + M)	O(1) extra

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Case 2 (M much bigger than N): binary search the big array

TIME	SPACE
O(N log M)	O(1) extra

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Three or more arrays.

Intersect pairwise, smallest arrays first so the running result shrinks quickly: O(total size). With K arrays you can also keep K pointers and advance the smallest.

FOLLOW-UP 2 The arrays are too big for memory.

Read both as streams (two pointers need only the current element of each), or partition both by value range into files that fit in memory and intersect partition by partition. **Cost:** O(N + M) time and O(1) memory with two streaming pointers; partitioning by value range multiplies the disk passes by the number of partitions.

FOLLOW-UP 3 Which one do you choose when N = 1,000 and M = 10^9?

Binary search: N log M is about 30,000 steps while two pointers need 10^9. The break-even is when N log M is around M.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from bisect import bisect_left
from math import log2


# CASE 1: M close to N (two pointers)
def common_two_pointers(a, b):
    # M close to N: walk both sorted arrays together and
    # advance the smaller side. O(N + M) time, O(1) space
    # besides the output.
    out, i, j = [], 0, 0
    while i < len(a) and j < len(b):
        if a[i] < b[j]:
            i += 1
        elif a[i] > b[j]:
            j += 1
        else:
            if not out or out[-1] != a[i]:
                out.append(a[i])
            i += 1
            j += 1
    return out


# CASE 2: M much bigger than N (binary search)
def common_binary_search(small, big):
    # M much bigger than N: binary search every item of
    # the
    # short array in the long one. O(N log M); the search
    # starts where the previous one stopped.
    out, lo = [], 0
    for x in small:
        lo = bisect_left(big, x, lo)
        if lo == len(big):
            break
        if big[lo] == x and (not out or out[-1] != x):
            out.append(x)
    return out


# BASE QUESTION (optimal): Case 1 (M close to N): two
# pointers
def common(a, b):
    # choose by cost: N log M against N + M
    small, big = (a, b) if len(a) <= len(b) else (b, a)
    if len(small) * log2(len(big) + 2) < len(a) + len(b):
        return common_binary_search(small, big)
    return common_two_pointers(a, b)
```

```
# FOLLOW-UP 1: Three or more arrays.
def common_many(arrays):
    # follow-up: three or more arrays. Intersect pairwise,
    # smallest first, so the running result shrinks fast.
    ordered = sorted(arrays, key=len)
    result = ordered[0]
    for arr in ordered[1:]:
        result = common(result, arr)
        if not result:
            break
    return result


# FOLLOW-UP 2: The arrays are too big for memory.
def common_stream(a_iter, b_iter):
    # follow-up: arrays too big for memory. Only the
    # current
    # item of each stream is held.
    a_iter, b_iter = iter(a_iter), iter(b_iter)
    x, y = next(a_iter, None), next(b_iter, None)
    last = None
    while x is not None and y is not None:
        if x < y:
            x = next(a_iter, None)
        elif x > y:
            y = next(b_iter, None)
        else:
            if x != last:
                yield x
                last = x
            x, y = next(a_iter, None), next(b_iter, None)


if __name__ == "__main__":
    a = [1, 2, 3, 5, 6, 7]
    b = [3, 6, 7, 8, 20]
    assert common_two_pointers(a, b) == [3, 6, 7]
    assert common_binary_search(b, a) == [3, 6, 7]
    assert common(a, b) == [3, 6, 7]
    assert common([], [1]) == []
```

```
    assert common([1, 1, 2], [1, 1, 3]) == [1]
    assert common_many([[1, 2, 3], [7, 8], [3]]) == []
    assert common_many([[1, 2, 3, 4], [2, 3, 9],
                        [2, 3, 5, 6, 7]]) == [2, 3]
    streamed = list(common_stream(iter(a), iter(b)))
    assert streamed == [3, 6, 7]
    import random
    for _ in range(300):
        nx = random.randint(0, 9)
        ny = random.randint(0, 9)
        x = sorted(random.sample(range(40), nx))
        y = sorted(random.sample(range(40), ny))
        want = sorted(set(x) & set(y))
        assert common_two_pointers(x, y) == want
        assert common_binary_search(x, y) == want
        assert common(x, y) == want
        assert list(common_stream(x, y)) == want
    # one short array against a very long one
    tiny, huge = [5, 999999], list(range(0, 1000000, 3))
    assert common(tiny, huge) == [999999]
```

OFFICIAL PAGE TEXT

Given two sorted arrays arr1 and arr2 of passport numbers, implement a function findDuplicates that returns an array of all passport numbers that are both arrays. Note that the output array should be sorted in ascending order. Let N and M be the lengths of arr1 and arr2, respectively. Solve for two cases and analyze the time & space complexities of your solutions: M ~ N - the array lengths are approximately the same M >> N - arr2 is much bigger than arr1. Example

```
input:  arr1 = [1, 2, 3, 5, 6, 7], arr2 = [3, 6, 7, 8,
 20]

output: [3, 6, 7] # since only these three values are
both in arr1 and arr2
```

Hint 1Start with a brute force solution and optimize from there.Hint 2Note that the question asks for a sorted array. What techniques work well on sorted arrays?Hint 3If M >> N (case #2) is giving you trouble, consider how you might use the values of N, the shorter array, to increase the efficiency of your answer.Challenge 1Have you taken care to avoid array out-of-bound runtime errors?First, the brute force solution. Try two nested loops. For every value arr1[i] in the outer loop, we look it up in arr2 in the inner loop. The time complexity of this algorithm in the worst case scenario is O(N*M). Not very efficient. We can do better than that. Case 1 (M ~ N) We can use the fact the arrays are sorted to traverse both of them in an in-order manner at the same time. The general idea of the algorithm is to use two indices, i and j, for arr1 and arr2, respectively. Every time one of indices, let's say i without any loss of generality, points to a value that is smaller than the value pointed by other index, we increment i. If arr1[i] == arr2[j], we add the value to the output array and increment both indices. Pseudocode:

```
function findDuplicates(arr1, arr2):
   duplicates = []
   i = 0
   j = 0

   while (i < arr1.length AND j < arr2.length):
      if (arr1[i] == arr2[j]):
         duplicates.push(arr1[i])
         i = i + 1
         j = j + 1
      else if (arr1[i] < arr2[j]):
         i = i + 1
      else:
         j = j + 1

   return duplicates
```

OFFICIAL PAGE TEXT

Time Complexity: O(N+M) since in the worst case scenario we traverse both arrays once. Note that O(N+M) is a linear time complexity because the input size is O(N+M) as well. Space Complexity: the variable duplicates is the only dynamic auxiliary space we're using in the algorithm. In the worst case scenario, the size of duplicates is going to be as big as big as the smaller input array. For instance, when the smaller array is fully contained within the bigger one. The space complexity is therefore O(N), where N <= M. Case 2 (M >> N) When one array is substantially longer than the other, we should try to avoid traversing the longer one. Instead, we can traverse the shorter array and look up its values in the longer array by using the binary search algorithm. We explain why this approach is superior in this case to the previous one in the complexity analysis section. Pseudocode:

```
function findDuplicates(arr1, arr2):
    duplicates = []

    for number in arr1:
        if binarySearch(arr2, number) != -1:
            duplicates.push(number);

    return duplicates

function binarySearch(arr, num):
    begin = 0
    end = arr.length - 1

    while (begin <= end):
        mid = begin + floor((end-begin)/2)
        if arr[mid] < num:
            begin = mid + 1
        else if arr[mid] == num:
            return mid
        else:
            end = mid - 1

    return -1
```

Time Complexity: we running a binary search on arr2 N times. Hence the time complexity is O(N*log(M)). So why is this algorithm better than the previous one when M >> N? To demonstrate that let's analyze the case that M = N^C, where C is a constant such that C >= 2. In this case, the time complexity of the second algorithm is:

```
O(N*log(M)) = O(N*log(N^C)) = O(C*N*log(N)) = O(N*log(N))
```

And the time complexity of the first algorithm is:

```
O(N + M) = O(N + N^C) = O(N^C)
```

As we all know O(N^C) > O(N*log(N)). Space Complexity: the variable duplicates is the only dynamic auxiliary space we're using in the algorithm. In the worst case scenario, the size of duplicates is going to be as big as big as the smaller input array. For instance, when the smaller array is fully contained within the bigger one. The space complexity is therefore O(N), where N <= M. No answers contributed by the community yet.

EASY | IN APP LC 509 | Exponent | 150 of 165

Fibonacci Numbers

ASKED (ANY CO.) ~9 MONTHS AGO | OLDER

STUDY: TYPE | ALL TIME 46.3 | 30 DAYS 0 | PRIORITY 75/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: your app's interview approach (LeetCode #509)

LeetCode match: LC 509 Fibonacci Number

Last asked (any company): 9 months ago, about 2026-01 (Exponent shows only a rough age) | +26 interviews

Original: https://www.aced.io/questions/3631/fibonacci

QUESTION

Write a function fib(n) that returns the nth Fibonacci number. The Fibonacci sequence is defined as F(n) = F(n-1) + F(n-2) with F(0) = 1 and F(1) = 1, which produces the following pattern: 1, 1, 2, 3, 5, 8, 13 ... Examples Pythonfib(0)

=> 1 fib(1)

=> 1 fib(2)

=> 2 fib(3)

=> 3 ... fib(10)

=> 89 fib(20)

=> 10946Hint 1The Fibonacci sequence

is defined recursively since it refers to itself.Hint 2We can start with a recursive implementation and optimize it.Hint 3Each call to F(n) has two subproblems: F(n-1) and F(n-2). Can we memoize these calculations?Challenge 1Does your solution work in O(n) time?This question is a classic example of how dynamic programming, or memoization, can help us solve problems faster by reducing repetitive computations. In this first version, we recursively call the fib function twice, and then we call it twice more in every subsequent recursive call, so the total number of operations expands to O(2^n)! To improve the runtime of our program, let's save our prior calculations in a dictionary called memo and pass it into our function. Now, if we've already found fib(n) before, our function will use this stored value instead of recursing again. Time Complexity: The time complexity of the memoized version is O(n). This is because each Fibonacci number from 0 to n is computed only once and then stored in the memo dictionary. The recursive calls will now simply look up the value in the dictionary if it has already been computed, reducing redundant

APPROACH

Iterative two-variable loop O(n), O(1) space; mention memoization and matrix exponentiation / fast doubling for O(log n).

HOW TO THINK ABOUT IT

Each term needs only the previous two, so a loop with two variables is O(n) time and O(1) space; the naive recursion does exponential repeated work. Since the recurrence is linear it can also be turned into a matrix power, or into the fast doubling identities, for O(log n).

Basis: LeetCode 509, Fibonacci Number (F(0) = 0, F(1) = 1).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def fib(n):
    if n < 2:
        return 1  # fib(0) = fib(1) = 1
    return fib(n - 1) + fib(n - 2)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

The call tree has about 1.6^n nodes because the same values are recomputed. A loop with two variables is O(n) time and O(1) space; fast doubling is O(log n).

OPTIMAL SOLUTION · Iteration with two variables

TIME	SPACE
O(n)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 n is up to 10^18 and the answer is needed modulo a prime.

Fast doubling (or matrix power) with every multiplication reduced modulo the prime: O(log n) steps with small numbers.

FOLLOW-UP 2 Why is the recursive version slow, and how do you fix it without changing the structure?

It recomputes the same values exponentially often (the call tree has about phi^n nodes). Memoisation (lru_cache) makes each value computed once, so O(n) time with O(n) memory; bottom-up with two variables drops the memory to O(1).

FOLLOW-UP 3 Closed form (Binet's formula).

F(n) = round(phi^n / sqrt(5)) is exact only while floating point has enough precision (up to about n = 70); beyond that it gives wrong digits, so use the integer methods.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from functools import lru_cache
from math import sqrt

# this problem starts at fib(0) = 1, fib(1) = 1
MOD = 10 ** 9 + 7


# THE DEFINITION (slow, say it first)
def fib_slow(n):
    # the definition: correct but about 1.6 ** n calls
    if n < 2:
        return 1
    return fib_slow(n - 1) + fib_slow(n - 2)


@lru_cache(maxsize=None)
# FOLLOW-UP 2: Why is the recursive version slow, and how
# do you fix it without ...
def fib_memo(n):
    # follow-up: the same structure with a cache, so every
    # value is computed once: O(n) time and memory
    if n < 2:
        return 1
    return fib_memo(n - 1) + fib_memo(n - 2)


# BASE QUESTION (optimal): Iteration with two variables
def fib(n):
    # bottom-up with two variables: O(n) time, O(1) memory
    a, b = 1, 1
    for _ in range(n):
        a, b = b, a + b
    return a


def pair(n, mod):
    # follow-up: fast doubling. Returns (F(n), F(n + 1))
    # of
    # the standard sequence 0, 1, 1, 2 using
    #   F(2k)     = F(k) * (2 * F(k + 1) - F(k))
    #   F(2k + 1) = F(k) ** 2 + F(k + 1) ** 2
    if n == 0:
        return 0, 1
    a, b = pair(n // 2, mod)
    c = a * (2 * b - a) % mod
    d = (a * a + b * b) % mod
    return (d, c + d) if n % 2 else (c, d)


# FOLLOW-UP 1: n is up to 10^18 and the answer is needed
# modulo a prime.
def fib_mod(n, mod=MOD):
    # fib(n) here is the standard F(n + 1): O(log n) steps
    # with small numbers, so n = 10 ** 18 is easy
    return pair(n + 1, mod)[0] % mod


# FOLLOW-UP 3: Closed form (Binet's formula).
def fib_binet(n):
    # follow-up: closed form. Floats run out of precision.
    phi = (1 + sqrt(5)) / 2
    return round(phi ** (n + 1) / sqrt(5))


if __name__ == "__main__":
```

```
first = [fib(n) for n in range(7)]
assert first == [1, 1, 2, 3, 5, 8, 13]
assert fib(10) == 89 and fib(20) == 10946
assert fib_slow(10) == 89
assert fib_memo(20) == 10946
assert fib(0) == 1 and fib(1) == 1
for n in range(0, 200):
    assert fib_mod(n, MOD) == fib(n) % MOD
    big = 10 ** 18 + 9
    assert fib_mod(n, big) == fib(n) % big
# a huge n finishes at once
assert 0 <= fib_mod(10 ** 18) < MOD
# Binet is exact for a while, then floating point
# fails
assert all(fib_binet(n) == fib(n) for n in range(60))
late = range(60, 200)
bad = [n for n in late if fib_binet(n) != fib(n)]
assert bad and bad[0] < 100
```

OFFICIAL PAGE TEXT

Write a function fib(n) that returns the nth Fibonacci number. The Fibonacci sequence is defined as F(n) = F(n-1) + F(n-2) with F(0) = 1 and F(1) = 1, which produces the following pattern:

```
1, 1, 2, 3, 5, 8, 13 ...
```

Examples

```
Pythonfib(0)  # => 1
fib(1)  # => 1
fib(2)  # => 2
fib(3)  # => 3
...
fib(10) # => 89
fib(20) # => 10946
```

Hint 1The Fibonacci sequence is defined recursively since it refers to itself.Hint 2We can start with a recursive implementation and optimize it.Hint 3Each call to F(n) has two subproblems: F(n-1) and F(n-2). Can we memoize these calculations?Challenge 1Does your solution work in O(n) time?This question is a classic example of how dynamic programming, or memoization, can help us solve problems faster by reducing repetitive computations. In this first version, we recursively call the fib function twice, and then we call it twice more in every subsequent recursive call, so the total number of operations expands to O(2^n)! To improve the runtime of our program, let's save our prior calculations in a dictionary called memo and pass it into our function. Now, if we've already found fib(n) before, our function will use this stored value instead of recursing again. Time Complexity: The time complexity of the memoized version is O(n). This is because each Fibonacci number from 0 to n is computed only once and then stored in the memo dictionary. The recursive calls will now simply look up the value in the dictionary if it has already been computed, reducing redundant calculations. Space Complexity: The memo dictionary stores each Fibonacci number from 0 to n, which requires O(n) space.No answers contributed by the community yet.

EASY | Exponent | 151 of 165

Given two trees, determine if the pre-order traversals of two trees are same or not.

ASKED (ANY CO.) ~A YEAR AGO | OLDER

STUDY: TYPE | ALL TIME 45.8 | 30 DAYS 0 | PRIORITY 77/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #100 Same Tree

LeetCode match: LC 100 Same Tree (related: traversal comparison) (inferred from short statement)

Last asked (any company): a year ago, about 2025-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/7182/compare-preorder-traversals-two-trees

QUESTION

Given two trees, determine if the pre-order traversals of two trees are same or not.

APPROACH

Generate both pre-order sequences (with null markers) and compare, or walk both trees together with recursion. O(n).

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether they mean the same sequence of values or the same tree. Two different trees can have the same pre-order values.

BRUTE FORCE TO SAY OUT LOUD

Generate both pre-order lists and compare them. O(n) time and space.

OPTIMAL IDEA

Generate each pre-order lazily with an explicit stack and compare the two streams in lockstep with zip_longest, so the first mismatch stops the work. O(min(n, m)) with early exit, O(h) space. For the structural version walk both trees together, or serialize pre-order with null markers.

DRY-RUN THESE CASES

Same shape, different shape with the same pre-order, different lengths, empty trees, one empty.

LIKELY FOLLOW-UPS

Same tree (structure and values), or O(1) space with a Morris traversal.

PITFALLS

Comparing without null markers when the structure matters.

HOW TO THINK ABOUT IT

Ask whether they want identical pre-order value sequences or identical trees; different trees can share a pre-order. For sequences, compare lazily so the first difference ends the work, instead of building two full lists.

Basis: LeetCode 100, Same Tree, is the structural version; this question asks only whether the pre-order sequences match.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def preorder(node):
    if node is None:
        return []
    left = preorder(node.left)
    right = preorder(node.right)
    return [node.val] + left + right
same = preorder(a) == preorder(b)
```

TIME	SPACE
O(n + m)	O(n + m)

WHY IT IS SLOW

It always visits and stores both trees completely, O(n + m) time and space. Walking both pre-orders lazily in lockstep stops at the first difference with O(h) space.

OPTIMAL SOLUTION · Lazy pre-order generators compared in lockstep

TIME	SPACE
O(min(n, m)) with early exit, O(n + m) worst case	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if the interviewer meant the trees must be identical?

Then compare structure as well as values: same_tree above walks both trees together and treats two missing nodes as equal. Equivalently, serialize pre-order with null markers and compare the strings, since pre-order with nulls is unique. Ask which definition they mean before coding.

FOLLOW-UP 2 Do it with O(1) extra space.

Morris traversal visits pre-order using temporary threads on right pointers, giving O(1) space, but it mutates the tree while running (restoring it after), so it is not safe for concurrent readers. Mention that trade-off.

FOLLOW-UP 3 They want identical trees, not just sequences.

Compare structure as well: walk both trees together and treat a missing child on one side only as a mismatch, or serialise pre-order with null markers and compare the strings.

FOLLOW-UP 4 They want identical trees (structure and values), not just the same pre-order values.

Compare the two trees together: a node must match in value and both children must match; two missing children match. Equivalently compare the pre-order serialisation with null markers (which is unique). O(min(n, m)) with early exit.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from itertools import zip_longest


class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


MISSING = object()


def preorder(root):
    # root, then left, then right; iterative with a stack
    stack = [root] if root else []
    while stack:
        node = stack.pop()
        yield node.val
        # right goes first so the left child comes out
        # first
        if node.right:
            stack.append(node.right)
        if node.left:
            stack.append(node.left)


# BASE QUESTION (optimal): Lazy pre-order generators
# compared in lockstep
def same_preorder(a, b):
    # lazily compare the two sequences value by value; a
    # shorter sequence is padded with MISSING and so
    # differs
    pairs = zip_longest(preorder(a), preorder(b),
                        fillvalue=MISSING)
    return all(x == y for x, y in pairs)


# FOLLOW-UP 1, 3, 4: What if the interviewer meant the
# trees must be identical?
def same_tree(a, b):
    # follow-up: truly identical trees (shape and values).
    # Walk both together; one missing child is a mismatch.
    stack = [(a, b)]
    while stack:
        x, y = stack.pop()
        if x is None and y is None:
            continue
        if x is None or y is None or x.val != y.val:
            return False
```

```
        stack.append((x.left, y.left))
        stack.append((x.right, y.right))
    return True


# FOLLOW-UP 1, 3, 4: What if the interviewer meant the
# trees must be identical?
def serialise(root):
    # follow-up: pre-order with null markers is unique, so
    # equal strings mean identical trees
    out, stack = [], [root]
    while stack:
        node = stack.pop()
        if node is None:
            out.append("#")
            continue
        out.append(str(node.val))
        stack.append(node.right)
        stack.append(node.left)
    return ",".join(out)


# FOLLOW-UP 2: Do it with O(1) extra space.
def morris_preorder(root):
    # follow-up: O(1) extra space. A temporary link from
    # the
    # rightmost node of the left subtree back to the node
    # lets the walk climb up again. The tree is mutated
    # while
    # running, so the generator must be run to the end (it
    # removes every link on the way).
    node = root
    while node:
        if node.left is None:
            yield node.val
            node = node.right
            continue
        pred = node.left
        while pred.right and pred.right is not node:
            pred = pred.right
        if pred.right is None:
            yield node.val
```

```
            pred.right = node
            node = node.left
        else:
            pred.right = None
            node = node.right


def same_preorder_constant_space(a, b):
    # never stop early: that would leave links in the
    # trees
    same = True
    one, two = morris_preorder(a), morris_preorder(b)
    pairs = zip_longest(one, two, fillvalue=MISSING)
    for x, y in pairs:
        if x != y:
            same = False
    return same


if __name__ == "__main__":
    t1 = TreeNode(1, TreeNode(2), TreeNode(3))
    # a different shape with the same pre-order: 1, 2, 3
    t2 = TreeNode(1, TreeNode(2, None, TreeNode(3)))
    assert same_preorder(t1, t2)
    assert not same_tree(t1, t2)
    assert serialise(t1) != serialise(t2)
    copy = TreeNode(1, TreeNode(2), TreeNode(3))
    assert same_tree(t1, copy)
    assert same_preorder(None, None)
    assert same_tree(None, None)
```

```
    assert not same_preorder(t1, None)
    assert not same_preorder(t1, TreeNode(1, TreeNode(2)))
    assert same_preorder_constant_space(t1, t2)
    # the trees are left exactly as they were
    assert t1.left.right is None and t1.right.left is None
    assert serialise(t1) == "1,2,#,#,3,#,#"
    assert list(morris_preorder(t2)) == [1, 2, 3]
    assert not same_preorder_constant_space(
        t1, TreeNode(1, TreeNode(9), TreeNode(3)))
```

EASY | IN APP LC 104 | Exponent | 152 of 165

Calculate the height of a binary tree.

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TYPE | ALL TIME 40 | 30 DAYS 33 | PRIORITY 55/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: your app's interview approach (LeetCode #104)

LeetCode match: LC 104 Maximum Depth of Binary Tree (inferred from short statement)

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/1153/calculate-height-binary-tree

QUESTION

Calculate the height of a binary tree.

APPROACH

Recursive 1 + max(h(left), h(right)), or level-order BFS count. O(n).

HOW TO THINK ABOUT IT

Height is defined recursively: 1 plus the larger child height, and 0 for an empty tree. Say whether you count nodes or edges. A level-order traversal gives the same number without recursion, which is the safe choice for a very deep tree.

Basis: LeetCode 104, Maximum Depth of Binary Tree (and 543, 110 for the follow-ups).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def height(node):
    if node is None:
        return 0
    left = height(node.left)
    right = height(node.right)
    return 1 + max(left, right)
```

TIME	SPACE
O(n)	O(h) call stack

BRUTE FORCE

WHY IT IS SLOW

Linear time, which is optimal; the call stack is as deep as the tree, so a chain of 100,000 nodes can overflow. Counting levels with a queue avoids recursion.

OPTIMAL SOLUTION · Level-order traversal counting levels

TIME	SPACE
O(n)	O(width)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Nodes or edges?

Height in nodes is what the code returns; in edges subtract one (an empty tree is -1 and a single node is 0). Say which you use before you code.

FOLLOW-UP 2 Diameter (the longest path between any two nodes).

Return the height from the recursion and update a global best with left + right at each node: one pass, O(n).

FOLLOW-UP 3 Is the tree balanced?

Return the height, or -1 as soon as a subtree is unbalanced or the heights differ by more than one, so the whole check is one O(n) pass.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
from collections import deque


class TreeNode:
    def __init__(self, val=0, left=None, right=None):
        self.val, self.left, self.right = val, left, right


# BASE QUESTION (optimal): Level-order traversal counting
# levels
def height(root):
    # height in NODES: level order, count the levels. An
    # empty tree is 0 and a single node is 1. (In edges,
    # subtract one: empty is -1, single node is 0.)
    levels, queue = 0, deque([root] if root else [])
    while queue:
        levels += 1
        for _ in range(len(queue)):
            node = queue.popleft()
            if node.left:
                queue.append(node.left)
            if node.right:
                queue.append(node.right)
    return levels


# FOLLOW-UP 1: Nodes or edges?
def height_edges(root):
    return height(root) - 1


# FOLLOW-UP 2: Diameter (the longest path between any two
# nodes).
def diameter(root):
    # follow-up: the longest path between any two nodes,
    # in
    # edges. At every node the best path through it is
    # left + right; the recursion returns the node height.
    best = 0

    def depth(node):
        nonlocal best
        if node is None:
            return 0
        left, right = depth(node.left), depth(node.right)
        best = max(best, left + right)
        return 1 + max(left, right)

    depth(root)
    return best


# FOLLOW-UP 3: Is the tree balanced?
def is_balanced(root):
    # follow-up: heights of the two sides differ by at
    # most
    # one at EVERY node. Return -1 as soon as a subtree is
    # unbalanced, so the whole check is one pass.
    def depth(node):
        if node is None:
            return 0
        left = depth(node.left)
        if left == -1:
            return -1
        right = depth(node.right)
        if right == -1 or abs(left - right) > 1:
            return -1
        return 1 + max(left, right)

    return depth(root) != -1


def slow_height(node):
    # oracle: the textbook recursion
    if node is None:
        return 0
    left = slow_height(node.left)
    right = slow_height(node.right)
    return 1 + max(left, right)


def build(depth_left):
    # a random small tree for the tests
    import random
    if depth_left == 0 or random.random() < 0.2:
        return None
    below = depth_left - 1
    return TreeNode(0, build(below), build(below))


if __name__ == "__main__":
    assert height(None) == 0
    assert height(TreeNode(1)) == 1
    assert height_edges(None) == -1
    assert height_edges(TreeNode(1)) == 0
    left = TreeNode(2, TreeNode(4), TreeNode(5))
    tree = TreeNode(1, left, TreeNode(3))
```

```
assert height(tree) == 3 and diameter(tree) == 3
assert is_balanced(tree)
low = TreeNode(3, TreeNode(4))
lopsided = TreeNode(1, TreeNode(2, low))
assert not is_balanced(lopsided)
assert diameter(None) == 0
# the diameter need not pass through the root
a = TreeNode(3, TreeNode(5))
b = TreeNode(4, TreeNode(6))
side = TreeNode(1, TreeNode(2, a, b))
assert diameter(side) == 4
# a very deep chain: the level order version has no
# limit
chain = TreeNode(0)
cur = chain
for i in range(1, 50000):
    cur.left = TreeNode(i)
    cur = cur.left
assert height(chain) == 50000
import random
for _ in range(200):
    t = build(random.randint(0, 6))
    assert height(t) == slow_height(t)
```

OFFICIAL PAGE TEXT

Log in or sign up to answer this question.

EASY | IN APP LC 186 | Exponent | 153 of 165

Reverse a Sentence

ASKED (ANY CO.) ~2 YEARS AGO | OLDER

STUDY: TALK NO LEETCODE FREQUENCY PRIORITY 179/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #186)

LeetCode match: LC 186 Reverse Words in a String II

Last asked (any company): 2 years ago, about 2024-10 (Exponent shows only a rough age) | +38 interviews

Original: https://www.aced.io/questions/3062/reverse-a-sentence

QUESTION

You are given an array of characters arrthat consists of sequences of characters separated by space characters. Each space-delimited sequence of characters defines a word. Implement a function reverseWords that reverses the order of the words in the array in the most efficient manner. Explain your solution and analyze its time and space complexities. Example input: arr = ['p', 'e', 'r', 'f', 'e', 'c', 't', ' ', 'm', 'a', 'k', 'e', 's', ' ', 'p', 'r', 'a', 'c', 't', 'i', 'c', 'e'] output: ['p', 'r', 'a', 'c', 't', 'i', 'c', 'e', ' ', 'm', 'a', 'k', 'e', 's', ' ', 'p', 'e', 'r', 'f', 'e', 'c', 't']Hint 1Even if your language of choice enables this, don't be tempted to use standard functions. Consider how inefficient it is to separately create a string, split the words, and reverse the split.Challenge 1As a general rule, if you're tempted to use a standard or library function, be sure to explain that function's time and space complexity before committing to that solution. You may find a more efficient way to solve the problem yourself. Oftentimes in coding interviews, this is the whole point of the exercise.Challenge 2How have you handled edge cases? For example, empty arrays, arrays with nothing but spaces, arrays with single words only, or with multiple spaces between words, etc.Challenge 3Were you able to achieve a linear time complexity and a constant space complexity?Challenge 4Bonus: how might the mirrorReverse function be implemented with a single index?One possible s

APPROACH

Reverse the whole char array, then reverse each word in place. O(n) time, O(1) space.

HOW TO THINK ABOUT IT

Reversing the order of words but not the letters is the same as reversing everything and then reversing each word back. That is two passes of the same helper and needs no extra memory when the sentence is a mutable character array. First decide how to treat repeated spaces.

Basis: LeetCode 151 (Reverse Words in a String) and 557; the in-place version is the classic array trick.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def reverse_words(arr):
    sentence = "".join(arr)
    words = sentence.split()
    return list(" ".join(reversed(words)))
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

BRUTE FORCE

O(n) time but extra space for the word list, and it collapses repeated spaces. Reversing the whole character array and then each word in place needs O(1) extra space.

OPTIMAL SOLUTION · Reverse the whole array, then reverse each word in place

TIME	SPACE
O(n)	O(1) extra on the character array

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The input may have leading, trailing or repeated spaces.

The split-based version already normalises them; the in-place version keeps them, so say which you want. To normalise in place add a two-pointer pass that writes single spaces.

FOLLOW-UP 2 Reverse the letters of each word but keep the word order (LeetCode 557).

Split on single spaces and reverse each word, or reverse each run in place without the first full reversal.

FOLLOW-UP 3 The sentence is a linked list of characters.

Reverse each word segment, then reverse the whole list, using the pointer-flip routine for linked lists.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def reverse_range(arr, lo, hi):
    # reverse arr[lo..hi] in place with two pointers
    while lo < hi:
        arr[lo], arr[hi] = arr[hi], arr[lo]
        lo += 1
        hi -= 1


def each_word(arr):
    # yield the (start, end) of every word: a run of
    # characters without a space
    i = 0
    while i < len(arr):
        if arr[i] == " ":
            i += 1
            continue
        j = i
        while j + 1 < len(arr) and arr[j + 1] != " ":
            j += 1
        yield i, j
        i = j + 1


# BASE QUESTION (optimal): Reverse the whole array, then
# reverse each word in place
def reverse_words(arr):
    # reverse the whole array, so the words are in the
    # right
    # order but spelled backwards; then reverse each word
    # back. O(n) time and O(1) extra space.
    reverse_range(arr, 0, len(arr) - 1)
    for start, end in list(each_word(arr)):
        reverse_range(arr, start, end)
    return arr


# FOLLOW-UP 2: Reverse the letters of each word but keep
# the word order (LeetCode ...
def reverse_each_word(arr):
    # follow-up (LeetCode 557): keep the word order,
    # reverse
    # the letters of every word
    for start, end in list(each_word(arr)):
        reverse_range(arr, start, end)
    return arr


# FOLLOW-UP 1: The input may have leading, trailing or
# repeated spaces.
def normalise_spaces(arr):
    # follow-up: leading, trailing and repeated spaces. A
    # second pointer writes the words with single spaces;
    # the array is cut to the new length.
    write = 0
    for read in range(len(arr)):
        if arr[read] != " ":
            arr[write] = arr[read]
            write += 1
        elif write and arr[write - 1] != " ":
            arr[write] = " "
            write += 1
    if write and arr[write - 1] == " ":
        write -= 1
    del arr[write:]
    return arr


if __name__ == "__main__":
    text = list("perfect makes practice")
    flipped = "".join(reverse_words(text))
    assert flipped == "practice makes perfect"
    assert reverse_words([]) == []
    assert reverse_words(list("one")) == list("one")
    # spaces stay where they are in the in-place version
    spaced = reverse_words(list(" a  bc "))
    assert "".join(spaced) == " bc  a "
    letters = reverse_each_word(list("let's code"))
    assert "".join(letters) == "s'tel edoc"
    neat = normalise_spaces(list("  a   bc  "))
    assert "".join(neat) == "a bc"
    assert normalise_spaces(list("   ")) == []
    assert normalise_spaces(list("x")) == ["x"]
    messy = list("  one   two three ")
    tidy = reverse_words(normalise_spaces(messy))
    assert "".join(tidy) == "three two one"
    import random
    for _ in range(300):
        s = "".join(random.choice("ab c")
                    for _ in range(random.randint(0, 12)))
        parts = s.split(" ")
        got = "".join(reverse_words(list(s)))
        assert got == " ".join(reversed(parts))
```

OFFICIAL PAGE TEXT

You are given an array of characters arrthat consists of sequences of characters separated by space characters. Each space-delimited sequence of characters defines a word. Implement a function reverseWords that reverses the order of the words in the array in the most efficient manner. Explain your solution and analyze its time and space complexities. Example

```
input:  arr = [ 'p', 'e', 'r', 'f', 'e', 'c', 't', '
',
               'm', 'a', 'k', 'e', 's', '  ',
               'p', 'r', 'a', 'c', 't', 'i', 'c', 'e'
 ]

output: [ 'p', 'r', 'a', 'c', 't', 'i', 'c', 'e', '  '
,
          'm', 'a', 'k', 'e', 's', '  ',
          'p', 'e', 'r', 'f', 'e', 'c', 't' ]
```

Hint 1Even if your language of choice enables this, don't be tempted to use standard functions. Consider how inefficient it is to separately create a string, split the words, and reverse the split.Challenge 1As a general rule, if you're tempted to use a standard or library function, be sure to explain that function's time and space complexity before committing to that solution. You may find a more efficient way to solve the problem yourself. Oftentimes in coding interviews, this is the whole point of the exercise.Challenge 2How have you handled edge cases? For example, empty arrays, arrays with nothing but spaces, arrays with single words only, or with multiple spaces between words, etc.Challenge 3Were you able to achieve a linear time complexity and a constant space complexity?Challenge 4Bonus: how might the mirrorReverse function be implemented with a single index?One possible solution is doing a linear iteration on arr while pushing a copy of every word to a stack and then pulling them in reverse order while copying the words back into arr. Another approach is initializing a new array at the same length, iterating over arr from right to left, and copying any sequence of characters to the new array from left to right. Both approaches take O(N) time and at least O(N) space. A more elegant and efficient approach is to reverse all the characters in arr and then reverse the

characters in each word separately. While the first reverse gives us the words in the reverse order as we wanted, it also reverses the characters of each word. To fix that, we do the second reverse, which reverses each word separately. Reversing items in an array is done by a 'mirror' function, that swaps the items of every 2 indices with the same distance from the middle. Pseudocode:

OFFICIAL PAGE TEXT

```
function reverseWords(arr):
    # reverse all characters:
    n = arr.length
    mirrorReverse(arr, 0, n-1)

    # reverse each word:
    wordStart = null
    for i from 0 to n-1:
        if (arr[i] == ' '):
            if (wordStart != null):
                mirrorReverse(arr, wordStart, i-1)
                wordStart = null
        else if (i == n-1):
            if (wordStart != null):
                mirrorReverse(arr, wordStart, i)
        else:
            if (wordStart == null):
                wordStart = i

    return arr

# helper function - reverses the order of items in arr
# please note that this is language dependent:
# if are arrays sent by value, reversing should be don
e in place

function mirrorReverse(arr, start, end):
    tmp = null
    while (start < end):
        tmp = arr[start]
```

```
        arr[start] = arr[end]
        arr[end] = tmp
        start++
        end--
```

Time Complexity: traversing the array twice with a constant number of actions for each item is linear O(N). Space Complexity: using iteration indices and one temp variable takes constant O(1) memory. Answer to bonus question: The mirrorReverse function could be implemented with a single index with left to right linear iteration and swapping arr[i] and arr[n-1-i] as long as i < n-1-i. No answers contributed by the community yet.Related questionsReverse a linked list.Related coursesCourseCourseMachine Learning Engineer Interview PrepLand your dream machine learning role at Meta, Google, Amazon, Apple, Microsoft, Nvidia, and other top companies. Learn from mock interviews, frameworks, and advice from senior candidates. Explore ML system design, core concepts, coding, behavioral interviews, and more.Start learningCourseCourseData Science Interview PrepLand your dream data science role at Google, Amazon, Microsoft, Meta, Apple, and other top companies. Learn from mock interviews, frameworks, and advice from senior candidates. Practice statistics, experimentation, coding, SQL, machine learning, behavioral interviews, and more.Start learningPythonJavaScript C#JavaC++CGoRubySwiftPythonEditorShareLoading...OutputTest ResultsConsoleSign up to run code

EASY | IN APP LC 953 | Exponent | 154 of 165

Determine if two words are sorted in lexicographic order.

ASKED (ANY CO.) ~3 YEARS AGO | OLDER

STUDY: TALK | ALL TIME 8.1 | 30 DAYS 0 | PRIORITY 167/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: your app's interview approach (LeetCode #953)

LeetCode match: LC 953 Verifying an Alien Dictionary (inferred from short statement)

Last asked (any company): 3 years ago, about 2023-10 (Exponent shows only a rough age)

Original: https://www.aced.io/questions/3431/check-lexicographic-order-two-words

QUESTION

Determine if two words are sorted in lexicographic order.

APPROACH

Compare the two words character by character using the given order map; shorter prefix sorts first. O(L).

HOW TO THINK ABOUT IT

Compare character by character until the first difference; whichever character comes first in the alphabet decides, and if one word is a prefix of the other the shorter word comes first. A custom alphabet is just a lookup table from letter to rank.

Basis: LeetCode 953, Verifying an Alien Dictionary (a custom alphabet makes it the general case).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def sorted_pair(a, b, order):
    rank = {c: i for i, c in enumerate(order)}
    ranks_a = [rank[c] for c in a]
    ranks_b = [rank[c] for c in b]
    return ranks_a <= ranks_b
```

TIME	SPACE
O(L)	O(L)

WHY IT IS SLOW

It builds both full rank lists even when the first letters already decide the answer. Comparing character by character and stopping at the first difference is O(min(len a, len b)) with O(1) extra space.

OPTIMAL SOLUTION · Compare character by character, optionally with a custom alphabet

TIME	SPACE
O(min(len a, len b))	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What about uppercase, accents, or case-insensitive order?

Normalize first (casefold, unicode normalization) or give the rank map entries for the extra characters. Python's own string comparison orders by code point, which is not locale order, so use locale.strxfrm or a collation library when real language order matters.

FOLLOW-UP 2 A whole list of words in an alien alphabet (LeetCode 953).

Check each adjacent pair; sortedness of a list is the AND of its adjacent pairs. Build the rank table once.

FOLLOW-UP 3 Case-insensitive or accented comparison.

Normalise (casefold, unicode normalisation) before building ranks, or use locale-aware collation keys; plain code-point order is not language order.

FOLLOW-UP 4 Prefix rule.

'app' comes before 'apple' but 'apple' does not come before 'app': compare lengths only after all shared positions are equal.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import unicodedata

ALPHABET = "abcdefghijklmnopqrstuvwxyz"


# RANKS of the alphabet
def make_rank(order=ALPHABET):
    # the position of every letter in the alphabet
    return {ch: i for i, ch in enumerate(order)}


# FOLLOW-UP 1: What about uppercase, accents, or case-
# insensitive order?
def fold(word):
    # follow-up: ignore case and accents before comparing
    text = unicodedata.normalize("NFKD", word.casefold())
    return "".join(ch for ch in text
                   if not unicodedata.combining(ch))


# BASE QUESTION (optimal): Compare character by character,
# optionally with a custom ...
def in_order(a, b, rank):
```

```
    # compare letter by letter by rank; the first
    # difference
    # decides. If one word is a prefix of the other, the
    # shorter one comes first. A character outside the
    # alphabet is ranked after all the known ones.
    def key(ch):
        return rank.get(ch, len(rank) + ord(ch))

    for x, y in zip(a, b):
        if x != y:
            return key(x) < key(y)
    return len(a) <= len(b)


# FOLLOW-UP 2: A whole list of words in an alien alphabet
# (LeetCode 953).
def words_sorted(words, order=ALPHABET, fold_case=False):
    # follow-up (LeetCode 953): a whole list in an alien
    # alphabet is sorted when every adjacent pair is
    rank = make_rank(order)
    if fold_case:
        words = [fold(w) for w in words]
```

```
    return all(in_order(a, b, rank)
               for a, b in zip(words, words[1:]))


if __name__ == "__main__":
    rank = make_rank()
    assert in_order("apple", "banana", rank)
    assert not in_order("banana", "apple", rank)
    # the prefix rule
    assert in_order("app", "apple", rank)
    assert not in_order("apple", "app", rank)
    assert in_order("same", "same", rank)
    assert in_order("", "a", rank)
    alien = "hlabcdefgijkmnopqrstuvwxyz"
    assert words_sorted(["hello", "leetcode"], alien)
    alien = "worldabcefghijkmnpqstuvxyz"
    mixed = ["word", "world", "row"]
    assert not words_sorted(mixed, alien)
    assert not words_sorted(["apple", "app"], ALPHABET)
    assert words_sorted([], ALPHABET)
    assert words_sorted(["x"], ALPHABET)
    # case and accents only matter when asked for
    assert not words_sorted(["A", "b"], ALPHABET)
    assert words_sorted(["A", "b"], fold_case=True)
    accents = ["éclair", "ecole"]
    assert words_sorted(accents, fold_case=True)
    import random
    for _ in range(500):
        a = "".join(random.choice("abc")
                    for _ in range(random.randint(0, 4)))
        b = "".join(random.choice("abc")
                    for _ in range(random.randint(0, 4)))
        assert in_order(a, b, rank) == (a <= b)
```

HACKTHEROUNDS

11 questions | Hard 1, Medium 9, Easy 1 | topics: BFS/DFS and trees first

HackTheRounds - Hard (1)

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns 1 questions

HARD | IN APP LC 315 | HackTheRounds | Phone Screen | 155 of 165

Count of Smaller Numbers After Self

STUDY: TALK ALL TIME 33.2 30 DAYS 0 PRIORITY 113/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #315 Count of Smaller Numbers After Self

LeetCode match: LC 315

QUESTION

Given an integer array nums, return an array counts where counts[i] is the number of smaller elements to the right of nums[i].

EXAMPLES

Example 1

Input	`nums = [5, 2, 6, 1]`
Output	`[2, 1, 1, 0]`
Why	`To the right of 5 there are 2 smaller: [2, 1]. To the right of 2 there is 1 smaller: [1]. To the right of 6 there is 1 smaller: [1]. To the right of 1 there are 0 smaller.`

Example 2

Input	`nums = [1, 2, 3, 4]`
Output	`[0, 0, 0, 0]`

Example 3

Input	`nums = [4, 3, 2, 1]`
Output	`[3, 2, 1, 0]`

CONSTRAINTS

- 1 <= nums.length <= 10^5
- -10^4 <= nums[i] <= 10^4

APPROACH

Merge sort, binary indexed tree, or segment tree

HOW TO THINK ABOUT IT

For each element you want the count of smaller elements to its right: an order-statistics query on the elements seen so far if you scan right to left. A Fenwick tree over compressed values gives rank counts in O(log n). The same count falls out of merge sort: when a left element is placed after right elements that are smaller, those right elements are exactly the smaller numbers after it.

Basis: LeetCode 315, Count of Smaller Numbers After Self.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(nums):
    counts = []
    for i in range(len(nums)):
        smaller = 0
        for j in range(i + 1, len(nums)):
            if nums[j] < nums[i]:
                smaller += 1
        counts.append(smaller)
    return counts
```

TIME	SPACE
O(n^2)	O(1) extra

WHY IT IS SLOW

Two nested loops, O(n^2): too slow at n = 10^5. A Fenwick tree over ranks scanned right to left (or merge sort) is O(n log n).

OPTIMAL SOLUTION · Fenwick tree over compressed values, scanning right to left

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Do it with merge sort instead of a Fenwick tree.

Sort indices by value with merge sort; whenever you place an element from the left half, add the number of right-half elements already placed (they are smaller). Same O(n log n), and it avoids coordinate compression.

FOLLOW-UP 2 Count larger numbers after self, or smaller numbers before self.

Larger after: query the suffix instead of the prefix of the Fenwick tree. Smaller before: scan left to right instead of right to left. **Cost:** still O(n log n) with the Fenwick tree.

FOLLOW-UP 3 Count inversions in an array.

The sum of the answers above is the number of inversions; merge sort counts them directly in O(n log n).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class Fenwick:
    """Counts of seen values; prefix(i) = how many seen
    values have a rank below i."""

    def __init__(self, size):
        self.size = size
        self.tree = [0] * (size + 1)

    def add(self, i):
        i += 1
        while i <= self.size:
            self.tree[i] += 1
            i += i & -i

    def prefix(self, i):
        total = 0
        while i > 0:
            total += self.tree[i]
            i -= i & -i
        return total


def ranks(nums):
    # coordinate compression: value -> 0, 1, 2 ... by size
    return {v: i for i, v in enumerate(sorted(set(nums)))}


# BASE QUESTION (optimal): Fenwick tree over compressed
# values, scanning right to left
def count_smaller_after(nums):
    # go from the right; before inserting x ask how many
    # already-seen values are strictly smaller than x
    rank = ranks(nums)
    tree = Fenwick(len(rank))
    out = []
    for x in reversed(nums):
        out.append(tree.prefix(rank[x]))
        tree.add(rank[x])
    return out[::-1]


# FOLLOW-UP 2: Count larger numbers after self, or smaller
# numbers before self.
def count_larger_after(nums):
    # follow-up: the suffix of the tree instead of the
    # prefix
    rank = ranks(nums)
    tree = Fenwick(len(rank))
    out, seen = [], 0
    for x in reversed(nums):
        out.append(seen - tree.prefix(rank[x] + 1))
        tree.add(rank[x])
        seen += 1
    return out[::-1]


# FOLLOW-UP 2: Count larger numbers after self, or smaller
# numbers before self.
def count_smaller_before(nums):
    # follow-up: scan from the left instead
    rank = ranks(nums)
    tree = Fenwick(len(rank))
    out = []
    for x in nums:
        out.append(tree.prefix(rank[x]))
        tree.add(rank[x])
    return out


# FOLLOW-UP 1: Do it with merge sort instead of a Fenwick
# tree.
def count_smaller_merge(nums):
    # follow-up: merge sort on indexes. When a left item
    # is
    # placed, every right item already placed is smaller.
    counts = [0] * len(nums)
    order = list(range(len(nums)))

    def sort(lo, hi):
        if hi - lo <= 1:
            return
        mid = (lo + hi) // 2
        sort(lo, mid)
        sort(mid, hi)
        merged, i, j = [], lo, mid
        while i < mid or j < hi:
            left_first = False
            if i < mid and j < hi:
                a, b = nums[order[i]], nums[order[j]]
                left_first = a <= b
            if j >= hi or left_first:
                counts[order[i]] += j - mid
                merged.append(order[i])
                i += 1
            else:
                merged.append(order[j])
                j += 1
        order[lo:hi] = merged

    sort(0, len(nums))
    return counts


# FOLLOW-UP 3: Count inversions in an array.
def inversions(nums):
    # follow-up: the answers added up are the inversions
    return sum(count_smaller_merge(nums))


def brute(nums):
    return [sum(y < x for y in nums[i + 1:])
            for i, x in enumerate(nums)]


if __name__ == "__main__":
    sample = [5, 2, 6, 1]
    assert count_smaller_after(sample) == [2, 1, 1, 0]
    assert count_smaller_after([-1]) == [0]
    assert count_smaller_after([-1, -1]) == [0, 0]
    assert count_smaller_after([]) == []
    assert count_larger_after(sample) == [1, 1, 0, 0]
    assert count_smaller_before(sample) == [0, 0, 2, 0]
    assert inversions([2, 4, 1, 3, 5]) == 3
    assert inversions([3, 2, 1]) == 3
    import random
    for _ in range(300):
        nums = [random.randint(-5, 5)
                for _ in range(random.randint(0, 12))]
        want = brute(nums)
        assert count_smaller_after(nums) == want
        assert count_smaller_merge(nums) == want
```

```
    assert inversions(nums) == sum(want)
    bigger = [sum(y > x for y in nums[i + 1:])
              for i, x in enumerate(nums)]
    assert count_larger_after(nums) == bigger
```

```
    before = [sum(y < x for y in nums[:i])
              for i, x in enumerate(nums)]
    assert count_smaller_before(nums) == before
```

HackTheRounds - Medium (9)

BFS/DFS Graph and Tree Traversal and Shortest Paths 2 questions

MEDIUM | IN APP LC 1650 | HackTheRounds | Phone Screen | 156 of 165

Lowest Common Ancestor of a Binary Tree III

STUDY: TALK | ALL TIME 14.7 | 30 DAYS 0 | PRIORITY 162/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #1650 Lowest Common Ancestor of a Binary Tree III

LeetCode match: LC 1650

QUESTION

Given two nodes of a binary tree p and q, return their lowest common ancestor (LCA). Each node has a parent pointer.

EXAMPLES

Example 1	
Input	root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 1
Output	3
Why	The LCA of nodes 5 and 1 is 3.

Example 2	
Input	root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 4
Output	5
Why	The LCA of nodes 5 and 4 is 5.

Example 3	
Input	root = [1,2], p = 1, q = 2
Output	1
Why	Node 1 is ancestor of node 2.

CONSTRAINTS

- Number of nodes: [2, 10^5]
- -10^9 <= Node.val <= 10^9

QUESTION

- All node values are unique
- p != q
- p and q exist in the tree

APPROACH

Parent pointers: two-pointer swap trick, or a set of ancestors

HOW TO THINK ABOUT IT

With parent pointers each node is the head of a linked list that ends at the root, so the question is where two linked lists meet. If the lists have different lengths, walk each pointer to the end and then restart it on the other node: both pointers then travel the same total distance and arrive at the meeting node together.

Basis: LeetCode 1650, Lowest Common Ancestor of a Binary Tree III (every node has a parent pointer).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def lca(p, q):
    ancestors = set()
    node = p
    while node:
        ancestors.add(node)
        node = node.parent
    node = q
    while node:
        if node in ancestors:
            return node
        node = node.parent
    return None
```

TIME	SPACE
O(h)	O(h)

WHY IT IS SLOW

Uses O(h) extra space for the set. Two pointers that switch to the other node's start when they fall off the root meet at the answer with O(1) space.

OPTIMAL SOLUTION · Two pointers that switch to the other node at the end

TIME	SPACE
O(h)	O(1)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Do it without the swap trick (it feels like magic).

Compute the depth of each node by walking up, lift the deeper one by the difference, then step both up together until they meet. Same O(h) time and O(1) space and easier to justify.

FOLLOW-UP 2 Many LCA queries on the same tree.

Preprocess with binary lifting (up[k][v] is the 2^k-th ancestor): O(n log n) to build, O(log n) per query. Or an Euler tour with a range-minimum structure for O(1) queries.

FOLLOW-UP 3 The nodes might not be in the same tree.

Then the two pointers both end as None after two passes, and None is the correct answer. The loop terminates because both pointers reach None at the same step.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class Node:
    def __init__(self, val, parent=None):
        self.val, self.parent = val, parent
        self.left = self.right = None


def attach(parent, val, side):
    # create a child and link it both ways
    child = Node(val, parent)
    setattr(parent, side, child)
    return child


# BASE QUESTION (optimal): Two pointers that switch to the
# other node at the end
def lca_swap(p, q):
    # two pointers climb to the root; at the top each one
    # jumps to the other node's start. Both walk the same
    # total distance, so they meet at the LCA (or both
    # reach
    # None together when the nodes are in different
    # trees).
    a, b = p, q
    while a is not b:
        a = a.parent if a else q
        b = b.parent if b else p
    return a


def depth(node):
    d = 0
    while node.parent:
        node = node.parent
        d += 1
    return d


# FOLLOW-UP 1: Do it without the swap trick (it feels like
# magic).
def lca_by_depth(p, q):
    # follow-up: no trick. Lift the deeper node by the
    # difference in depth, then climb both until they
    # meet.
    dp, dq = depth(p), depth(q)
    while dp > dq:
        p, dp = p.parent, dp - 1
    while dq > dp:
        q, dq = q.parent, dq - 1
    while p is not q:
        p, q = p.parent, q.parent
    if p is None or q is None:
        return None
    return p


# FOLLOW-UP 2: Many LCA queries on the same tree.
class LiftingLCA:
    """Follow-up: many queries on one tree.
    up[k][i] is the 2**k-th ancestor of node i: O(n log n)
    to build and O(log n) per query."""

    def __init__(self, root):
        self.ids = {root: 0}
        self.nodes = [root]
        parent, self.depth = [0], [0]
        # the list grows while we walk it: a BFS order
        for node in self.nodes:
            at = self.ids[node]
            for child in (node.left, node.right):
                if child:
                    self.ids[child] = len(self.nodes)
                    self.nodes.append(child)
                    parent.append(at)
                    self.depth.append(self.depth[at] + 1)
        self.up = [parent]
        count = len(self.nodes)
        while (1 << len(self.up)) < count:
            prev = self.up[-1]
            row = [prev[prev[i]] for i in range(count)]
            self.up.append(row)

    def query(self, p, q):
        a, b = self.ids[p], self.ids[q]
        if self.depth[a] < self.depth[b]:
            a, b = b, a
        # lift the deeper node to the same depth
        diff = self.depth[a] - self.depth[b]
        for k, row in enumerate(self.up):
            if diff >> k & 1:
                a = row[a]
        if a == b:
            return self.nodes[a]
        # lift both as high as possible while they differ
        for row in reversed(self.up):
            if row[a] != row[b]:
                a, b = row[a], row[b]
        return self.nodes[self.up[0][a]]


def brute(p, q):
    # oracle: the first ancestor of q that is also one of
    # p
    above = set()
    while p:
        above.add(p)
        p = p.parent
    while q and q not in above:
        q = q.parent
    return q


def random_tree(size):
    import random
    root = Node(0)
    nodes = [root]
    while len(nodes) < size:
        parent = random.choice(nodes)
        side = random.choice(["left", "right"])
        if getattr(parent, side) is None:
            nodes.append(attach(parent, len(nodes), side))
    return nodes
```

```
if __name__ == "__main__":
    root = Node(3)
    five = attach(root, 5, "left")
    one = attach(root, 1, "right")
    six = attach(five, 6, "left")
    two = attach(five, 2, "right")
    four = attach(two, 4, "left")
    assert lca_swap(six, four) is five
    assert lca_swap(five, four) is five
    assert lca_swap(six, one) is root
    assert lca_swap(root, root) is root
    other = Node(99)
```

```
    assert lca_swap(six, other) is None
    assert lca_by_depth(six, other) is None
    assert lca_by_depth(four, one) is root
    index = LiftingLCA(root)
    assert index.query(six, four) is five
    assert index.query(root, four) is root
    import random
    for _ in range(100):
        nodes = random_tree(random.randint(1, 12))
        index = LiftingLCA(nodes[0])
        for _ in range(20):
            p = random.choice(nodes)
            q = random.choice(nodes)
            want = brute(p, q)
            assert lca_swap(p, q) is want
            assert lca_by_depth(p, q) is want
            assert index.query(p, q) is want
```

MEDIUM | IN APP LC 236 | HackTheRounds | Onsite | 157 of 165

Lowest Common Ancestor

STUDY: TALK | ALL TIME 41.5 | 30 DAYS 0 | PRIORITY 87/224

ABOUT THIS QUESTION

Topic: BFS/DFS Graph and Tree Traversal and Shortest Paths

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #236 Lowest Common Ancestor of a Binary Tree

LeetCode match: LC 236

QUESTION

Given a binary tree and two nodes p and q, find their lowest common ancestor (LCA): the lowest node that has both p and q as descendants (a node can be a descendant of itself). Follow-up: what if it is an n-ary tree?

EXAMPLES

Example 1

Input	`root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 1`
Output	`3`
Why	`LCA of 5 and 1 is 3.`

QUESTION

Example 2

Input	`root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 4`
Output	`5`
Why	`A node can be its own ancestor.`

CONSTRAINTS

- Number of nodes in tree: [2, 10^5]
- -10^9 <= Node.val <= 10^9
- All node values are unique
- p != q
- p and q exist in the tree

APPROACH

Recursive DFS; follow-up: n-ary tree

HOW TO THINK ABOUT IT

Ask each subtree 'do you contain p or q?'. The first node where both subtrees report a hit (or the node is p or q itself and a subtree has the other) is the answer. One pass returns the answer upward: a node returns itself if p or q, the child result if only one side found something, and itself if both sides did.

Basis: LeetCode 236, Lowest Common Ancestor of a Binary Tree (and its n-ary follow-up).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def path_to(root, target):
    if root is None:
        return None
    if root is target:
        return [root]
    for child in root.children:
        sub = path_to(child, target)
        if sub:
            return [root] + sub
    return None
def lca(root, p, q):
    path_p = path_to(root, p)
    path_q = path_to(root, q)
    answer = None
    for a, b in zip(path_p, path_q):
        if a is not b:
            break
        answer = a
    return answer
```

TIME	SPACE
O(n)	O(n)

WHY IT IS SLOW

Two full paths stored, O(n) space, and two traversals. One recursive pass that reports whether each subtree contains p or q finds the answer in O(n) time and O(h) space.

OPTIMAL SOLUTION · One recursive pass

TIME	SPACE
O(n)	O(h)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The tree is n-ary.

The same recursion: collect the non-empty results from all children; if two or more children reported a hit this node is the answer, otherwise pass the single result (or None) up.

FOLLOW-UP 2 A very deep tree, or no recursion allowed.

Do one traversal that records each node's parent (a dict), then use the ancestor-set method from the parent-pointer version. O(n) time and space, no recursion.

FOLLOW-UP 3 p or q might not be in the tree.

The recursive answer is wrong in that case (it returns the one that exists). Count how many of p and q were seen during the DFS, or first check both exist, and return None if not.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
class Node:
    def __init__(self, val, children=None):
        self.val = val
        # two children for a binary tree, any number for
        # n-ary
        self.children = children or []


# BASE QUESTION (optimal): One recursive pass
# FOLLOW-UP 1: The tree is n-ary.
def lca(root, p, q):
    # each call reports where p or q was found below. A
    # node
    # with hits from two different children (or that is p
    # or
    # q itself) is the answer; a single hit is passed up.
    def find(node):
        if node is None:
            return None
        if node is p or node is q:
            return node
        # FOLLOW-UP 1: n-ary: collect hits from every
        # child
        hits = [r for r in map(find, node.children) if r]
        if len(hits) >= 2:
            return node
        return hits[0] if hits else None

    return find(root)


# FOLLOW-UP 2: A very deep tree, or no recursion allowed.
def parents_of(root):
    # follow-up: one traversal with a stack (no recursion)
    # that records every node's parent
    parent, stack = {root: None}, [root]
    while stack:
        node = stack.pop()
        for child in node.children:
            parent[child] = node
            stack.append(child)
    return parent


# FOLLOW-UP 2: A very deep tree, or no recursion allowed.
def lca_iterative(root, p, q):
    # climb from p collecting its ancestors, then climb
    # from
    # q until we meet one of them: O(n) time and space
    parent = parents_of(root)
    above = set()
    node = p
    while node:
        above.add(node)
        node = parent[node]
    node = q
    while node not in above:
        node = parent[node]
    return node


# FOLLOW-UP 3: p or q might not be in the tree.
def lca_checked(root, p, q):
    # follow-up: p or q may be missing from the tree. The
    # plain recursion would return the one that exists, so
    # first check that both are really in the tree.
    parent = parents_of(root)
    if p not in parent or q not in parent:
        return None
    return lca_iterative(root, p, q)


def brute(root, p, q):
    # oracle: the deepest node whose subtree holds both
    def holds(node, target):
        return node is target or any(
            holds(c, target) for c in node.children)

    best, stack = None, [root]
    while stack:
        node = stack.pop()
        if holds(node, p) and holds(node, q):
            best = node
            stack.extend(node.children)
    return best


if __name__ == "__main__":
    six, four = Node(6), Node(4)
    two = Node(2, [Node(7), four])
    five = Node(5, [six, two])
    one = Node(1, [Node(0), Node(8)])
    root = Node(3, [five, one])
    assert lca(root, six, four) is five
    assert lca(root, five, four) is five
    assert lca(root, six, one) is root
    # an n-ary tree: three children under one node
    kids = [Node(i) for i in range(3)]
    top = Node("top", [Node("mid", kids), Node("side")])
    assert lca(top, kids[0], kids[2]).val == "mid"
    found = lca_iterative(top, kids[0], kids[2])
    assert found.val == "mid"
    stranger = Node(404)
    assert lca_checked(root, six, stranger) is None
    assert lca_checked(root, six, four) is five
```

```
    # a very deep tree: the iterative version has no limit
    chain = Node(0)
    cur = chain
    for i in range(1, 5000):
        child = Node(i)
        cur.children.append(child)
        cur = child
    assert lca_iterative(chain, cur, chain) is chain
    import random
    for _ in range(100):
        # a random tree: every new node gets a random
        # parent
        nodes = [Node(0)]
        for i in range(1, random.randint(1, 10)):
            child = Node(i)
            random.choice(nodes).children.append(child)
            nodes.append(child)
        p, q = random.choice(nodes), random.choice(nodes)
        want = brute(nodes[0], p, q)
        assert lca(nodes[0], p, q) is want
        assert lca_iterative(nodes[0], p, q) is want
```

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns 3 questions

MEDIUM | HackTheRounds | Onsite | 158 of 165

★ TOP 75: rank 66 in the Medium and Hard priority list

★ Shortest Subarray with K Distinct Integers

STUDY: TYPE | ALL TIME 42.5 | 30 DAYS 33 | PRIORITY 37/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #992 Subarrays with K Different Integers, LeetCode #76 Minimum Window Substring

LeetCode match: LC 992 / LC 76 flavor

QUESTION

Given an array nums and an integer k, find the length of the shortest contiguous subarray that contains at least k distinct integers. If no such subarray exists, return -1.

EXAMPLES

Example 1	
Input	`nums = [1, 2, 1, 2, 3], k = 3`
Output	`3`
Why	`The shortest contiguous subarray with 3 distinct integers is [1, 2, 3].`

Example 2	
Input	`nums = [1, 1, 1, 1], k = 2`
Output	`-1`
Why	`Only 1 distinct integer exists.`

QUESTION

Example 3	
Input	`nums = [1, 2, 3, 4, 5], k = 3`
Output	`3`
Why	`Any 3 consecutive elements give 3 distinct integers.`

CONSTRAINTS

- 1 <= nums.length <= 10^5
- 1 <= nums[i] <= 10^9
- 1 <= k <= nums.length

APPROACH

Sliding window with a frequency hash map, O(n); shrink while distinct >= k

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the output if none exists (-1), whether k can exceed the number of distinct values, and whether the subarray must be contiguous (yes).

BRUTE FORCE TO SAY OUT LOUD

Check every subarray and count distinct values. O(n^3), or O(n^2) with a running set.

OPTIMAL IDEA

Sliding window with a count dict. Move right to add elements; whenever the window has at least k distinct values, record its length and then shrink from the left while it still has at least k distinct, updating the answer each time. Each index enters and leaves once, so O(n).

DRY-RUN THESE CASES

k = 1 (answer 1), k larger than distinct values (-1), all equal values, the shortest window in the middle, k = 0.

LIKELY FOLLOW-UPS

Longest subarray with at most k distinct, count of subarrays with exactly k distinct (LeetCode 992 using at-most minus at-most).

PITFALLS

Shrinking the window before recording the answer. Not deleting keys when counts reach zero.

HOW TO THINK ABOUT IT

Once a window has at least k distinct values, shrinking it from the left can only keep or lose distinct values, so the shortest valid window ending at each right end is found by shrinking as far as possible. A frequency map tells you when a value leaves the window, so each index enters and leaves once.

Basis: Sliding window (compare LeetCode 992 and 340). Shortest contiguous subarray with at least k distinct values; -1 if none.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(nums, k):
    best = -1
    for i in range(len(nums)):
        seen = set()
        for j in range(i, len(nums)):
            seen.add(nums[j])
            if len(seen) >= k:
                size = j - i + 1
                if best == -1 or size < best:
                    best = size
                break
    return best
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

O(n^2) in the worst case. A sliding window with a count map expands on the right and shrinks on the left, so each element is handled twice: O(n).

OPTIMAL SOLUTION · Sliding window with a frequency map

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Count the subarrays with exactly k distinct values (LeetCode 992).

exactly(k) = atMost(k) - atMost(k - 1), where atMost is a sliding window that shrinks while the distinct count exceeds the limit. Both are O(n).

FOLLOW-UP 2 Longest subarray with at most k distinct values.

The same window, but keep the longest window whose distinct count never exceeds k (shrink while it does). O(n).

FOLLOW-UP 3 The values are strings or large objects.

The frequency map works on any hashable value; for huge objects hash them first or map them to integer ids so the window comparisons stay cheap. **Cost:** O(n) plus hashing each element; mapping values to integer ids costs O(n) once.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter


# BASE QUESTION (optimal): Sliding window with a frequency
# map
def shortest_k_distinct(nums, k):
    # a window grows on the right; whenever it holds at
    # least k distinct values, record it and shrink from
    # the
    # left as far as it stays valid
    seen, left, best = Counter(), 0, None
    for right, x in enumerate(nums):
        seen[x] += 1
        while len(seen) >= k:
            size = right - left + 1
            if best is None or size < best:
                best = size
            seen[nums[left]] -= 1
            if seen[nums[left]] == 0:
                del seen[nums[left]]
            left += 1
    return -1 if best is None else best


def at_most(nums, k):
    # the number of subarrays with at most k distinct
    # values:
    # for every right end, all windows starting in
    # [left, right] qualify
    seen, left, total = Counter(), 0, 0
    for right, x in enumerate(nums):
        seen[x] += 1
        while len(seen) > k:
            seen[nums[left]] -= 1
            if seen[nums[left]] == 0:
                del seen[nums[left]]
            left += 1
        total += right - left + 1
    return total


# FOLLOW-UP 1: Count the subarrays with exactly k distinct
# values (LeetCode 992).
def exactly(nums, k):
    # follow-up (LeetCode 992): exactly k distinct values
    return at_most(nums, k) - at_most(nums, k - 1)


# FOLLOW-UP 2: Longest subarray with at most k distinct
# values.
def longest_at_most(nums, k):
    # follow-up: the longest window with at most k
    # distinct
    seen, left, best = Counter(), 0, 0
    for right, x in enumerate(nums):
        seen[x] += 1
        while len(seen) > k:
            seen[nums[left]] -= 1
            if seen[nums[left]] == 0:
                del seen[nums[left]]
            left += 1
        best = max(best, right - left + 1)
    return best


# FOLLOW-UP 3: The values are strings or large objects.
def to_ids(items):
    # follow-up: strings or big objects. Map each distinct
    # value to a small integer once, then reuse the same
    # code.
    ids = {}
    return [ids.setdefault(x, len(ids)) for x in items]


def brute_shortest(nums, k):
```

```
    best = None
    for i in range(len(nums)):
        for j in range(i, len(nums)):
            if len(set(nums[i:j + 1])) >= k:
                size = j - i + 1
                if best is None or size < best:
                    best = size
    return -1 if best is None else best


if __name__ == "__main__":
    assert shortest_k_distinct([1, 2, 1, 3, 4], 3) == 3
    assert shortest_k_distinct([1, 1, 1], 2) == -1
    assert shortest_k_distinct([5], 1) == 1
    assert shortest_k_distinct([], 1) == -1
```

```
    assert exactly([1, 2, 1, 2, 3], 2) == 7
    assert exactly([1, 2, 1, 3, 4], 3) == 3
    assert longest_at_most([1, 2, 1, 2, 3], 2) == 4
    words = ["a", "b", "a", "c"]
    assert shortest_k_distinct(to_ids(words), 3) == 3
    assert to_ids(["x", "y", "x"]) == [0, 1, 0]
    import random
    for _ in range(400):
        nums = [random.randint(1, 4)
                for _ in range(random.randint(0, 10))]
        k = random.randint(1, 5)
        want = brute_shortest(nums, k)
        assert shortest_k_distinct(nums, k) == want
        count = sum(len(set(nums[i:j + 1])) == k
                    for i in range(len(nums))
                    for j in range(i, len(nums)))
        assert exactly(nums, k) == count
```

ALSO REPORTED · 2 more

Find shortest subarray with at least k distinct | PracHub | Technical Screen

https://prachub.com/coding-questions/find-shortest-subarray-with-at-least-k-distinct

Find shortest subarray with >=k distinct integers | PracHub | Technical Screen

https://prachub.com/coding-questions/find-shortest-subarray-with-k-distinct-integers

---

MEDIUM | HackTheRounds | Onsite | 159 of 165

Sum of Two Squares in Two Ways

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 202/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

QUESTION

Given an integer n, find all integers s < n such that s can be expressed as the sum of two squares in exactly two distinct unordered ways. For example: 50 = 1^2 + 7^2 = 5^2 + 5^2.

EXAMPLES

Example 1

Input	n = 100
Output	[50, 65, 85]
Why	50 = 1^2 + 7^2 = 5^2 + 5^2, 65 = 1^2 + 8^2 = 4^2 + 7^2, 85 = 2^2 + 9^2 = 6^2 + 7^2

Example 2

Input	n = 50
Output	[]
Why	No number less than 50 has exactly two representations.

CONSTRAINTS

- 1 <= n <= 2^31 - 1

APPROACH

Taxicab-number style: count a^2 + b^2 over a <= b with a hash map, keep sums with exactly two representations

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether pairs are unordered with a <= b, whether zero is allowed, and whether the bound is strict (s < n).

BRUTE FORCE TO SAY OUT LOUD

For each s below n try every a and b. O(n * sqrt(n)).

OPTIMAL IDEA

Loop over a <= b with a^2 + b^2 < n and count each sum in a hash map. Return the sums whose count is exactly two. There are about pi * n / 8 such pairs, so O(n) time and space. For the example, 50 = 1^2 + 7^2 = 5^2 + 5^2, so 50 qualifies when n > 50.

DRY-RUN THESE CASES

n = 50 (50 itself is excluded because the bound is strict), a small n with no answers, a sum with three representations (excluded), a perfect square such as 25 = 0 + 25 = 9 + 16 if zero is allowed.

LIKELY FOLLOW-UPS

Exactly k ways, or counting without a dictionary using a sieve.

PITFALLS

Counting (a, b) and (b, a) as different. Including s equal to n.

HOW TO THINK ABOUT IT

Do not test each s separately. Generate every pair (a, b) once, add its sum to a counter, and read the answer from the counter. The loop is bounded by a^2 + b^2 < n, so a and b are at most sqrt(n); a <= b removes order duplicates.

Basis: Taxicab-number style counting. The examples fix the rule: a and b are positive integers with a <= b, so 25 = 3^2 + 4^2 has only one representation (0^2 + 5^2 is not allowed).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(n):
    result = []
    for s in range(1, n):
        ways = 0
        for a in range(1, isqrt(s) + 1):
            rest = s - a * a
            b = isqrt(rest)
            if b >= a and b * b == rest:
                ways += 1
        if ways == 2:
            result.append(s)
    return result
```

TIME	SPACE
O(n * sqrt(n))	O(1)

WHY IT IS SLOW

Every s searches all pairs again, O(n * sqrt(n)). Generating each pair once and counting sums in a hash map is O(n).

OPTIMAL SOLUTION · Count every pair once in a hash map

TIME	SPACE
O(n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Exactly k ways instead of two.

Change the comparison from == 2 to == k; the counting loop is the same. For k = 3 the smallest is 325.

FOLLOW-UP 2 Allow zero (0^2 + b^2).

Start a at 0; then perfect squares like 25 gain a representation, so some answers appear or disappear. Check against the examples to see which convention the question uses (here, positive only).

FOLLOW-UP 3 n is huge (10^12) and you only need to test one number.

Factorise the number: the count of representations as a sum of two squares depends only on the primes congruent to 1 mod 4 (Jacobi's formula), so a factorisation answers it in sublinear time.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import Counter
from math import isqrt


# BASE QUESTION (optimal): Count every pair once in a hash
# map


# FOLLOW-UP 1, 2: Exactly k ways instead of two.
def sums_in_k_ways(n, k=2, zero=False):
    # every s < n is counted once per pair a <= b with
    # a*a + b*b = s. Keep the sums seen exactly k times.
    ways = Counter()
    # FOLLOW-UP 2: zero=True allows 0^2 + b^2
    a = 0 if zero else 1
    while 2 * a * a < n:
        b = a
        while a * a + b * b < n:
            ways[a * a + b * b] += 1
            b += 1
        a += 1
    # FOLLOW-UP 1: k ways instead of exactly two
    return sorted(s for s, c in ways.items()
                  if c == k and s > 0)


def factorise(m):
    # trial division: fine up to about 10 ** 12
    out, p = {}, 2
    while p * p <= m:
        while m % p == 0:
            out[p] = out.get(p, 0) + 1
            m //= p
        p += 1
    if m > 1:
        out[m] = out.get(m, 0) + 1
    return out


# FOLLOW-UP 3: n is huge (10^12) and you only need to test
# one number.
def representations(m, zero=False):
    # follow-up: ONE huge number. The number of ways
    # depends
    # only on the primes that are 1 mod 4 (Jacobi): with
    # B = product of (exponent + 1) there are 4B ordered
    # signed pairs. Remove the special shapes a == 0 and
    # a == b, then every other unordered pair is counted 8
    # times.
    if m <= 0:
        return 0
    boost = 1
    for p, e in factorise(m).items():
        if p % 4 == 3 and e % 2:
            return 0
        if p % 4 == 1:
            boost *= e + 1
    is_square = isqrt(m) ** 2 == m
    half = m % 2 == 0 and isqrt(m // 2) ** 2 == m // 2
    plain = (4 * boost - 4 * is_square - 4 * half) // 8
    return plain + half + (is_square if zero else 0)


def brute_count(m, zero=False):
    a = 0 if zero else 1
    count = 0
    while 2 * a * a <= m:
        rest = m - a * a
        b = isqrt(rest)
        if b * b == rest and rest > 0 and b >= a:
            count += 1
        a += 1
    return count


if __name__ == "__main__":
    assert sums_in_k_ways(100) == [50, 65, 85]
    assert sums_in_k_ways(10) == []
    assert sums_in_k_ways(1000, 3)[0] == 325
    # with zero allowed, perfect squares gain a way
```

```
assert 25 not in sums_in_k_ways(100)
assert 25 in sums_in_k_ways(100, 2, zero=True)
assert representations(50) == 2
assert representations(325) == 3
assert representations(3) == 0
assert representations(25) == 1
assert representations(25, zero=True) == 2
# a 12 digit number in a moment (13 * 5 * 5 * ...)
assert representations(5 ** 5 * 13 * 17 * 29) > 10
for m in range(1, 600):
    assert representations(m) == brute_count(m), m
    both = representations(m, True)
```

```
    assert both == brute_count(m, True)
    if m < 100:
        two = representations(m) == 2
        assert (m in sums_in_k_ways(100)) == two
```

ALSO REPORTED · 1 more

Find numbers with exactly two sum-of-squares forms | PracHub | Technical Screen

https://prachub.com/coding-questions/find-numbers-with-exactly-two-sum-of-squares-forms

---

MEDIUM | IN APP LC 362 | DESIGN-STYLE (skippable) | HackTheRounds | Phone Screen | 160 of 165

Hit Counter

STUDY: TALK | ALL TIME 33.2 | 30 DAYS 0 | PRIORITY 114/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #362 Design Hit Counter

LeetCode match: LC 362

QUESTION

Design a hit counter that counts the number of hits received in the past 5 minutes (300 seconds). hit(timestamp) records a hit; getHits(timestamp) returns the number of hits in the past 300 seconds.

EXAMPLES

Example 1	
Input	`hit(1), hit(2), hit(3), getHits(4), hit(300), getHits(300), getHits(301)`
Output	`[null, null, null, 3, null, 4, 3]`
Why	`At 301, hit at timestamp 1 expires.`

CONSTRAINTS

- 1 <= timestamp <= 2 * 10^9
- Timestamps are monotonically increasing

APPROACH

Queue/deque of timestamps; evict entries older than 300 seconds

HOW TO THINK ABOUT IT

Only the last 300 seconds matter, so anything older is dead weight: evict from the front of a queue of timestamps. If hits arrive at very high rates, store counts per second in a circular array of 300 buckets so memory does not depend on the number of hits.

Basis: LeetCode 362, Design Hit Counter.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
hits = []
def hit(t):
    hits.append(t)
def get_hits(t):
    return sum(1 for x in hits if x > t - 300)
```

TIME	SPACE
O(n) per getHits	O(n)

WHY IT IS SLOW

Memory grows with every hit forever, and each query scans them all, O(n). A queue that drops timestamps older than 300 seconds (or 300 per-second buckets) keeps both bounded.

OPTIMAL SOLUTION · Queue of timestamps with eviction

TIME	SPACE
O(1) amortized	O(hits in the window)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Millions of hits per second.

Use 300 buckets (one per second) instead of one entry per hit: hit is O(1), getHits is O(300) = O(1), and memory is constant. A bucket whose stored second is older than the window is reset on reuse.

FOLLOW-UP 2 Timestamps can arrive out of order.

A deque no longer works. Keep a sorted structure (a sorted list with bisect or a balanced tree) and count with two binary searches, or use the buckets, which are order-insensitive within the window.

FOLLOW-UP 3 Thread safety.

Guard the queue with a lock (or use per-thread counters merged on read). The bucket version needs the compare-then-reset of a slot to be atomic. **Cost:** one lock per call, O(1) extra; contention rather than complexity is the concern.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import threading
from bisect import bisect_right, insort
from collections import deque

WINDOW = 300   # seconds


# BASE QUESTION (optimal): Queue of timestamps with
# eviction
class QueueCounter:
    """One entry per hit; old entries are dropped when
    asked. Timestamps must not go backwards."""

    def __init__(self):
        self.hits = deque()

    def hit(self, ts):
        self.hits.append(ts)

    def get_hits(self, ts):
        # keep only the hits in (ts - 300, ts]
        while self.hits and self.hits[0] <= ts - WINDOW:
            self.hits.popleft()
        return len(self.hits)


# FOLLOW-UP 1: Millions of hits per second.
class BucketCounter:
    """Follow-up: millions of hits per second. One bucket
    per second of the window: constant memory and time."""

    def __init__(self):
        self.stamp = [0] * WINDOW
        self.count = [0] * WINDOW

    def hit(self, ts):
        slot = ts % WINDOW
        if self.stamp[slot] != ts:
            # the slot still holds an old second: reuse it
            self.stamp[slot], self.count[slot] = ts, 0
        self.count[slot] += 1

    def get_hits(self, ts):
        slots = zip(self.stamp, self.count)
        return sum(c for t, c in slots
                   if 0 <= ts - t < WINDOW)


# FOLLOW-UP 2: Timestamps can arrive out of order.
class SortedCounter:
    """Follow-up: timestamps can arrive out of order.
    A sorted list and two binary searches count the
    window."""

    def __init__(self):
        self.hits = []

    def hit(self, ts):
        insort(self.hits, ts)

    def get_hits(self, ts):
        newest = bisect_right(self.hits, ts)
        oldest = bisect_right(self.hits, ts - WINDOW)
        return newest - oldest


# FOLLOW-UP 3: Thread safety.
class Locked:
    """Follow-up: thread safety. One lock around every
    call keeps check-then-update steps atomic."""

    def __init__(self, counter):
        self.counter = counter
        self.lock = threading.Lock()

    def hit(self, ts):
        with self.lock:
            self.counter.hit(ts)

    def get_hits(self, ts):
        with self.lock:
            return self.counter.get_hits(ts)


def brute(hits, ts):
    return sum(1 for t in hits if ts - WINDOW < t <= ts)


if __name__ == "__main__":
    kinds = (QueueCounter, BucketCounter, SortedCounter)
    for make in kinds:
        c = make()
        for ts in (1, 2, 3, 300):
            c.hit(ts)
        assert c.get_hits(300) == 4
        # the hit at second 1 is 300 seconds old: it is
        # out
        assert c.get_hits(301) == 3
        assert c.get_hits(599) == 1
        assert c.get_hits(600) == 0
        assert c.get_hits(1000) == 0
    import random
    for make in kinds:
        c, log, now = make(), [], 0
        for _ in range(500):
            now += random.randint(0, 40)
            if random.random() < 0.6:
                c.hit(now)
                log.append(now)
            else:
                assert c.get_hits(now) == brute(log, now)
    # out of order input only works with the sorted
    # version
    late = SortedCounter()
    for ts in (50, 10, 400, 30):
        late.hit(ts)
    assert late.get_hits(400) == 1
    assert late.get_hits(310) == 2
    shared = Locked(BucketCounter())
    def spam():
        for _ in range(1000):
            shared.hit(7)

    workers = [threading.Thread(target=spam)
               for _ in range(4)]
    for w in workers:
        w.start()
    for w in workers:
        w.join()
```

```
assert shared.get_hits(7) == 4000
```

ALSO REPORTED · 1 more

Design a rolling hit counter API | PracHub | Technical Screen
https://prachub.com/coding-questions/design-a-rolling-hit-counter-api

---

Dynamic Programming and State-Space Optimization 2 questions

MEDIUM | IN APP LC 465 | HackTheRounds | Onsite | 161 of 165

Trip Expense Settlement

STUDY: TALK | ALL TIME 25.5 | 30 DAYS 0 | PRIORITY 139/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization
Optimal answer from: the interview site's own solution
Also in your app: LeetCode #465 Optimal Account Balancing
LeetCode match: LC 465 (Optimal Account Balancing)

QUESTION

A group of friends go on a trip. Each friend may pay for others. Given payment records, compute minimal payments required to settle all debts.

EXAMPLES

Example 1

Input	`[{"payer": "alice", "amount": 4000, "payees": ["bob", "jess", "alice", "sam"]}, {"payer": "jess", "amount": 2000, "payees": ["jess", "alice"]}]`
Output	`[{"payer": "bob", "amount": 1000, "payee": "alice"}, {"payer": "sam", "amount": 1000, "payee": "alice"}]`
Why	`Calculate net balance for each person, then settle with minimum transactions.`

Example 2

Input	`expenses = [{"payer": "Alice", "amount": 40, "participants": ["Alice", "Bob"]}, {"payer": "Bob", "amount": 20, "participants": ["Alice", "Bob"]}]`
Output	`["Bob pays Alice 10.00"]`

CONSTRAINTS

- 1 <= payments.length <= 1000
- 1 <= amount <= 10^6
- 1 <= payees.length <= 100

APPROACH

Compute each person's net balance, then match debtors and creditors with heaps

HOW TO THINK ABOUT IT

First reduce the records to one number per person: net balance = paid - owed. Only that matters; who owed whom originally is irrelevant. Then settling is moving money between people with positive and negative balances. Matching largest creditor with largest debtor is quick and uses at most n - 1 payments, but only searching groups of people who sum to zero gives the true minimum.

Basis: LeetCode 465, Optimal Account Balancing. Each record is split equally among the listed payees (the payer may be one of them).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def settle(i):
    while i < n and net[i] == 0:
        i += 1  # already settled
    if i == n:
        return 0
    best = INF
    for j in range(i + 1, n):
        if net[j] * net[i] < 0:  # opposite sign
            net[j] += net[i]  # move balance i
            best = min(best, 1 + settle(i + 1))
            net[j] -= net[i]  # undo
    return best
```

TIME	SPACE
O(n!) worst case	O(n)

WHY IT IS SLOW

It tries every pairing, up to n! in the worst case. Matching the largest creditor with the largest debtor (heaps) is O(n log n) and uses at most n - 1 payments, though not always the minimum.

OPTIMAL SOLUTION · Heaps: match the largest debtor with the largest creditor

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Do you need the true minimum number of payments?

That is NP-hard in general (it is the zero-sum partition problem). The greedy answer is at most n - 1 payments and is usually accepted; for exact answers use the bitmask DP above (about 20 people) or backtracking with pruning.

FOLLOW-UP 2 Amounts that do not divide evenly (cents).

Work in integer cents and decide where the remainder goes (to the payer, or round-robin among payees). Never use floats for money, and make the rule deterministic.

FOLLOW-UP 3 Different shares per person instead of equal split.

Replace the equal share with an explicit amount per payee in each record; the net balance per person is computed the same way.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
from itertools import combinations


# FOLLOW-UP 2: Amounts that do not divide evenly (cents).
def split_equally(amount, people):
    # follow-up: cents that do not divide evenly. Work in
    # whole cents; the leftover cents go to the first
    # people
    # in sorted order, so the rule is always the same.
    people = sorted(people)
    base, extra = divmod(amount, len(people))
    return {p: base + (1 if i < extra else 0)
            for i, p in enumerate(people)}


# FOLLOW-UP 3: Different shares per person instead of
# equal split.
def shares_of(record):
    # follow-up: explicit shares per person instead of
    # equal
    payees = record["payees"]
    if isinstance(payees, dict):
        if sum(payees.values()) != record["amount"]:
            raise ValueError("shares do not add up")
        return payees
    return split_equally(record["amount"], payees)


def balances(records):
    # net balance per person: what they paid minus what
    # they
    # owe. Positive: the group owes them. All sum to zero.
    net = {}
    for rec in records:
        payer = rec["payer"]
        net[payer] = net.get(payer, 0) + rec["amount"]
        for person, share in shares_of(rec).items():
            net[person] = net.get(person, 0) - share
    return {p: v for p, v in net.items() if v}


# BASE QUESTION (optimal): Heaps: match the largest debtor
# with the largest creditor
def settle_greedy(records):
```

```
    # the biggest debtor pays the biggest creditor, as
    # much
    # as one side can: at most n - 1 payments
    net = balances(records)
    owed = [(-v, p) for p, v in net.items() if v > 0]
    debt = [(v, p) for p, v in net.items() if v < 0]
    heapq.heapify(owed)
    heapq.heapify(debt)
    out = []
    while owed and debt:
        o_amt, creditor = heapq.heappop(owed)
        d_amt, debtor = heapq.heappop(debt)
        pay = min(-o_amt, -d_amt)
        out.append({"payer": debtor, "amount": pay,
                    "payee": creditor})
        if -o_amt > pay:
            heapq.heappush(owed, (o_amt + pay, creditor))
        if -d_amt > pay:
            heapq.heappush(debt, (d_amt + pay, debtor))
    return out


# FOLLOW-UP 1: Do you need the true minimum number of
# payments?
def min_payments_exact(values):
    # follow-up: the true minimum. People split into
    # groups
    # that settle among themselves (sum zero); a group of
    # g
    # people needs g - 1 payments. So find the most
    # groups:
    # a DP over subsets of people.
    n = len(values)
    total = [0] * (1 << n)
    best = [0] * (1 << n)
    for mask in range(1, 1 << n):
        low = (mask & -mask).bit_length() - 1
        rest = mask & (mask - 1)
        total[mask] = total[rest] + values[low]
        top = max((best[mask ^ (1 << i)]
                   for i in range(n) if mask >> i & 1))
        best[mask] = top + (1 if total[mask] == 0 else 0)
    return n - best[(1 << n) - 1]
```

```
# FOLLOW-UP 1: Do you need the true minimum number of
# payments?
def min_payments_search(values):
    # the same answer by backtracking: settle the first
    # open
    # debt against every opposite one
    values = [v for v in values if v]

    def go(start):
        while start < len(values) and values[start] == 0:
            start += 1
        if start == len(values):
            return 0
        best = float("inf")
        seen = set()
        for j in range(start + 1, len(values)):
            if values[j] * values[start] < 0 and (
                    values[j] not in seen):
                seen.add(values[j])
                values[j] += values[start]
                best = min(best, 1 + go(start + 1))
                values[j] -= values[start]
        return best

    return go(0)


def apply(payments, net):
    # check: after the payments every balance is zero
    left = dict(net)
    for pay in payments:
        who, whom = pay["payer"], pay["payee"]
        left[who] = left.get(who, 0) + pay["amount"]
```

```
        left[whom] = left.get(whom, 0) - pay["amount"]
    return all(v == 0 for v in left.values())


if __name__ == "__main__":
    trip = [{"payer": "alice", "amount": 4000,
             "payees": ["bob", "jess", "alice", "sam"]},
            {"payer": "jess", "amount": 2000,
             "payees": ["jess", "alice"]}]
    got = settle_greedy(trip)
    want = [
        {"payer": "bob", "amount": 1000,
         "payee": "alice"},
        {"payer": "sam", "amount": 1000,
         "payee": "alice"}]
    assert sorted(got, key=lambda p: p["payer"]) == want
    assert balances(trip) == {"alice": 2000, "bob": -1000,
                              "sam": -1000}
    # 10.00 split three ways: 3.34 + 3.33 + 3.33
    assert split_equally(1000, ["c", "a", "b"]) == {
        "a": 334, "b": 333, "c": 333}
    custom = [{"payer": "x", "amount": 90,
               "payees": {"x": 10, "y": 30, "z": 50}}]
    owed = {"x": 80, "y": -30, "z": -50}
    assert balances(custom) == owed
    assert min_payments_exact([5, -5]) == 1
    assert min_payments_exact([3, -3, 2, -2]) == 2
    assert min_payments_search([3, -3, 2, -2]) == 2
    import random
    for _ in range(100):
        names = "abcdef"
        records = []
        for _ in range(random.randint(1, 5)):
            count = random.randint(1, 4)
            who = random.sample(names, count)
            cents = random.randint(1, 500)
            records.append({"payer": random.choice(names),
                            "amount": cents,
                            "payees": who})
        net = balances(records)
        assert sum(net.values()) == 0
        pays = settle_greedy(records)
        assert apply(pays, net)
        assert len(pays) <= max(len(net) - 1, 0)
        values = list(net.values())
        exact = min_payments_exact(values)
        assert exact == min_payments_search(values)
        assert exact <= len(pays)
```

ALSO REPORTED · 1 more

Compute minimal transfers to settle group expenses | PracHub | Technical Screen

https://prachub.com/coding-questions/compute-minimal-transfers-to-settle-group-expenses

MEDIUM | HackTheRounds | Onsite | 162 of 165

Reverse Coin Change

STUDY: TALK | ALL TIME 37.9 | 30 DAYS 0 | PRIORITY 99/224

ABOUT THIS QUESTION

Topic: Dynamic Programming and State-Space Optimization

Optimal answer from: the interview site's own solution

Also in your app: LeetCode #518 Coin Change II

LeetCode match: Inverse of LC 518

QUESTION

In standard coin change, given a coins array, we build dp where dp[i] = number of ways to make amount i. Reverse problem: given a dp array, find the original coins array that produced it.

EXAMPLES

Example 1	
Input	`dp = [1, 1, 2, 2, 3]`
Output	`[1, 2]`
Why	`Coins [1, 2] produce this dp array.`

Example 2	
Input	`dp = [1, 1, 1, 2, 2, 2, 3]`
Output	`[1, 3]`

CONSTRAINTS

- 1 <= dp.length <= 1000
- dp[0] = 1

APPROACH

Rebuild coins left to right: the first amount whose dp exceeds the dp built from coins so far is a new coin

HOW TO THINK ABOUT IT

Think of building the ways table forward: adding a coin c changes dp[c] by exactly one (the single coin c). So scanning amounts upward, the first amount where the target has more ways than your table can only be explained by a new coin of exactly that value. Add it, rebuild, and continue; at the end compare with the target to detect an impossible input.

Basis: The inverse of LeetCode 518, Coin Change II (number of ways to make each amount with unlimited coins).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def brute(dp):
    n = len(dp) - 1
    for k in range(n + 1):
        values = range(1, n + 1)
        for coins in combinations(values, k):
            if ways_table(coins, n) == dp:
                return list(coins)
    return None
```

TIME	SPACE
O(2^n * n * coins)	O(n)

WHY IT IS SLOW

2^n candidate sets, each with an O(n * coins) table. Scanning amounts upward and adding a coin whenever the target has one more way than the table is O(n^2).

OPTIMAL SOLUTION · Scan upward and add a coin whenever the table falls short

TIME	SPACE
O(n * coins) = O(n^2) worst case	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The array might not come from any set of coins.

Return None (or raise) when dp[0] != 1, when an amount needs more than one extra way, or when the rebuilt table differs from the input at the end; the code does all three checks.

FOLLOW-UP 2 Order of the coins matters (the dp counts permutations, not combinations).

That is a different recurrence: dp[a] = sum of dp[a - c] over coins. Inverting it is a linear-algebra style problem: at each amount the new coins explain the excess; ask which counting is used.

FOLLOW-UP 3 Each coin may be used at most once.

The forward recurrence iterates amounts downward. The inverse still scans upward adding a coin when the target exceeds the table, but the table update must use the 0/1 form.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
def ways_table(coins, n):
    # forward: dp[a] = number of combinations making a
    dp = [1] + [0] * n
    for c in coins:
        for a in range(c, n + 1):
            dp[a] += dp[a - c]
    return dp


# BASE QUESTION (optimal): Scan upward and add a coin
# whenever the table falls short
# FOLLOW-UP 1: The array might not come from any set of
# coins.
def coins_from_dp(dp):
    # backward: rebuild the table with the coins found so
    # far. The first amount where the real dp is exactly
    # one
    # bigger must be a new coin (it adds the single way
    # "just that coin"). Anything else is impossible.
    n = len(dp) - 1
    if not dp or dp[0] != 1:
        return None
    cur, coins = [1] + [0] * n, []
    for a in range(1, n + 1):
        if dp[a] == cur[a]:
            continue
        if dp[a] != cur[a] + 1:
            return None
        coins.append(a)
        for x in range(a, n + 1):
            cur[x] += cur[x - a]
    # the table rebuilt from the coins must equal the
    # input
    return coins if cur == list(dp) else None


# FOLLOW-UP 2: Order of the coins matters (the dp counts
# permutations, not ...
def ordered_table(coins, n):
    # follow-up: the order of coins matters
    # (permutations):
    # dp[a] = sum of dp[a - c] over the coins
    dp = [1] + [0] * n
    for a in range(1, n + 1):
        dp[a] = sum(dp[a - c] for c in coins if c <= a)
    return dp


# FOLLOW-UP 2: Order of the coins matters (the dp counts
# permutations, not ...
def coins_from_ordered(dp):
    n = len(dp) - 1
    if not dp or dp[0] != 1:
        return None
    coins = []
    for a in range(1, n + 1):
        # what the known coins already explain at amount a
        known = sum(dp[a - c] for c in coins)
        if dp[a] == known + 1:
            coins.append(a)
        elif dp[a] != known:
            return None
    again = ordered_table(coins, n)
    return coins if again == list(dp) else None


# FOLLOW-UP 3: Each coin may be used at most once.
def once_table(coins, n):
    # follow-up: each coin used at most once; amounts are
    # visited downward in the forward step
    dp = [1] + [0] * n
    for c in coins:
        for a in range(n, c - 1, -1):
            dp[a] += dp[a - c]
    return dp


# FOLLOW-UP 3: Each coin may be used at most once.
def coins_from_once(dp):
```

```
    n = len(dp) - 1
    if not dp or dp[0] != 1:
        return None
    cur, coins = [1] + [0] * n, []
    for a in range(1, n + 1):
        if dp[a] == cur[a]:
            continue
        if dp[a] != cur[a] + 1:
            return None
        coins.append(a)
        for x in range(n, a - 1, -1):
            cur[x] += cur[x - a]
    return coins if cur == list(dp) else None


if __name__ == "__main__":
    assert coins_from_dp([1, 1, 2, 2, 3]) == [1, 2]
    assert coins_from_dp([1, 1, 1, 2, 2, 2, 3]) == [1, 3]
    assert coins_from_dp([1]) == []
    assert coins_from_dp([]) is None
    # not a table: dp[0] must be 1
    assert coins_from_dp([2, 1]) is None
    # an amount that jumps by more than one new way
    assert coins_from_dp([1, 3]) is None
    # looks fine early, but the whole table does not match
    assert coins_from_dp([1, 1, 2, 2, 5]) is None
    table = ordered_table([1, 2], 6)
    assert coins_from_ordered(table) == [1, 2]
    assert coins_from_ordered([1, 1, 2, 3, 5]) == [1, 2]
    table = once_table([1, 2, 3], 6)
    assert coins_from_once(table) == [1, 2, 3]
    import random
    for _ in range(300):
        size = random.randint(0, 4)
        coins = sorted(random.sample(range(1, 10), size))
        n = random.randint(0, 14)
        small = [c for c in coins if c <= n]
        table = ways_table(coins, n)
        assert coins_from_dp(table) == small
        table = ordered_table(coins, n)
        assert coins_from_ordered(table) == small
        table = once_table(coins, n)
        assert coins_from_once(table) == small
        junk = [1]
        junk += [random.randint(0, 3) for _ in range(n)]
        found = coins_from_dp(junk)
        if found is not None:
            assert ways_table(found, n) == junk
```

Other: Design, Heaps, Intervals and Misc 2 questions

MEDIUM | HackTheRounds | Phone Screen | 163 of 165

★ TOP 75: rank 59 in the Medium and Hard priority list

★ Meeting Rooms III Variant

STUDY: TYPE | ALL TIME 58 | 30 DAYS 0 | PRIORITY 38/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #253 Meeting Rooms II

LeetCode match: LC 253 (cyclic variant)

QUESTION

Given an array of meeting time intervals where each interval is [start, end], determine the minimum number of conference rooms required to hold all meetings without overlap. Variant: times are cyclic within a 24-hour period (meetings can wrap around midnight).

EXAMPLES

Example 1

Input	`intervals = [[0, 30], [5, 10], [15, 20]]`
Output	`2`
Why	`Meeting [0,30] overlaps with [5,10] and [15,20], so we need 2 rooms.`

Example 2

Input	`intervals = [[7, 10], [2, 4]]`
Output	`1`
Why	`No overlap, 1 room is sufficient.`

Example 3

Input	`intervals = [[22, 2], [23, 1], [0, 3]]`
Output	`3`
Why	`All three meetings overlap around midnight.`

CONSTRAINTS

- 1 <= intervals.length <= 10^4
- 0 <= start < end <= 24 * 60 (minutes in a day)
- Meetings may wrap around (e.g., [23:00, 01:00])

APPROACH

Sweep line; split intervals that wrap past midnight

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the 24-hour day repeats cyclically, whether a meeting that wraps midnight must stay in one room the whole time, and whether a meeting ending exactly when another starts conflicts (usually not).

BRUTE FORCE TO SAY OUT LOUD

Try assigning meetings to rooms one by one with backtracking. Exponential.

OPTIMAL IDEA

Split a wrapping meeting [s, e] with e < s into [s, 24h] and [0, e] and run a sweep line over the events: sort start and end events, +1 at a start, -1 at an end (process ends first at equal times), and take the maximum running count. That gives the minimum number of rooms when pieces may use different rooms. If a wrapping meeting must stay in a single room the exact answer is circular-arc coloring, which can be larger than the maximum overlap (five arcs forming an odd cycle need three rooms with overlap two) and is hard in general, so state the assumption and mention a heuristic.

DRY-RUN THESE CASES

No wrap, one wrapping meeting, a wrap that overlaps the beginning of the day, back-to-back meetings, all meetings the same.

LIKELY FOLLOW-UPS

Return which room each meeting uses, or check feasibility with a given number of rooms.

PITFALLS

Counting back-to-back meetings as overlapping. Splitting a wrap but treating the two pieces as two meetings in the output.

HOW TO THINK ABOUT IT

Split a wrapped meeting into two pieces (from start to the end of the day, and from midnight to its end) and run the normal sweep line: the largest number of meetings active at once is the number of rooms needed. That is exact when pieces may sit in different rooms; if a meeting must keep one room, the arcs form a circular-arc graph and the true minimum can exceed the maximum overlap (five overlapping arcs around a circle need 3 rooms with overlap 2). Say which reading you assume.

Basis: LeetCode 253 (Meeting Rooms II) on a circular day. Meetings are half-open [start, end) in minutes; a meeting with end < start wraps past midnight. Two readings: the usual interview answer (split the wrapped meeting and take the maximum overlap) and the exact answer when a wrapped meeting must keep one room.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def rooms_needed(meetings):
    slots = [minutes_used(m) for m in meetings]
    for k in range(1, len(meetings) + 1):
        rooms = [set() for _ in range(k)]
        if assign(0, rooms, slots):
            return k
def assign(i, rooms, slots):
    if i == len(slots):
        return True
    for room in rooms:
        busy = slots[i]
        if not room & busy:  # no shared minute
            room |= busy
            if assign(i + 1, rooms, slots):
                return True
            room -= busy
    return False
```

BRUTE FORCE

TIME	SPACE
exponential	O(n)

WHY IT IS SLOW

Backtracking over room assignments is exponential. Splitting wrapped meetings and sweeping start and end events gives the maximum overlap in O(n log n); that equals the exact answer when meetings do not wrap.

OPTIMAL SOLUTION · Split wrapped meetings and sweep (maximum overlap)

TIME	SPACE
O(n log n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 A wrapped meeting must stay in a single room.

Then it is circular-arc colouring, NP-hard in general. A common practical method: cut the circle at the minute with the fewest active meetings; the meetings crossing the cut use fixed rooms, and the rest are scheduled greedily with a heap. It can use more rooms than the maximum overlap, and the five-arc example shows why.

FOLLOW-UP 2 Return which room each meeting uses.

Sort by start and keep a min-heap of (end time, room id); reuse the earliest-ending room if it is free, otherwise open a new one. For wrapped meetings schedule them first so their rooms are fixed.

FOLLOW-UP 3 Days can repeat (a wrapped meeting recurs every day).

A recurring meeting occupies its slots every day, so the circle model above is exactly right, and the no-wrap shortcut of ordering by start time is not.

FOLLOW-UP 4 Return which room each meeting uses.

Sort by start and keep a heap of (end time, room): reuse the earliest-ending room if it is free, otherwise open a new one. For meetings that do not wrap this uses exactly the minimum number of rooms (verified against the sweep); wrapped meetings need the cut-the-circle method.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq

DAY = 24


def pieces(meetings, day=DAY):
    # a meeting whose end is before its start wraps past
    # midnight: split it into the part before midnight and
    # the part after it
    for s, e in meetings:
        if e < s:
            yield s, day
            yield 0, e
        else:
            yield s, e


# BASE QUESTION (optimal): Split wrapped meetings and
# sweep (maximum overlap)
def min_rooms_sweep(meetings, day=DAY):
    # sweep the time line: +1 at a start, -1 at an end. At
    # equal times an end comes first (a meeting ending at
    # 5
    # and one starting at 5 can share a room).
    events = []
    for s, e in pieces(meetings, day):
        events.append((s, 1))
        events.append((e, -1))
    events.sort()
    cur = best = 0
    for _, step in events:
        cur += step
        best = max(best, cur)
    return best


# FOLLOW-UP 2, 4: Return which room each meeting uses.
def assign_rooms(meetings):
    # follow-up: which room for each meeting (no
    # wrapping).
    # Sort by start; a heap of (end, room) gives the room
    # that
    # frees up first; reuse it if it is free, else open
    # one.
    order = sorted(range(len(meetings)),
                   key=lambda i: meetings[i][0])
    heap, room_of, rooms = [], {}, 0
    for i in order:
        s, e = meetings[i]
        if heap and heap[0][0] <= s:
            _, room = heapq.heappop(heap)
        else:
            room, rooms = rooms, rooms + 1
        room_of[i] = room
        heapq.heappush(heap, (e, room))
    return [room_of[i] for i in range(len(meetings))]


def hours(meeting, day=DAY):
    # the hours a meeting occupies on the 24 hour circle
    s, e = meeting
    length = (e - s) % day or day
    return {(s + k) % day for k in range(length)}


# FOLLOW-UP 1: A wrapped meeting must stay in a single
# room.
def assign_single_rooms(meetings, day=DAY):
    # follow-up: a meeting that wraps must stay in ONE
    # room.
    # That is circular-arc colouring (NP-hard), so use the
    # practical method: cut the circle at the hour where
    # the
    # fewest meetings are running, give those meetings
    # their
    # own rooms, and place the rest greedily.
    busy = [sum(1 for m in meetings
                if cut in hours(m, day))
            for cut in range(day)]
    cut = busy.index(min(busy))
    # rotate so that the cut is time 0: (start, end) on a
    # line
    line = []
    for s, e in meetings:
        start = (s - cut) % day
        length = (e - s) % day or day
        line.append((start, start + length))
    free_at, deadline = [], []     # per room
    room_of = {}
    for i, (s, e) in enumerate(line):
        if e > day:
            # crosses the cut: busy until e - day, and
            # again
            # from s on, so the room is blocked after s
            room_of[i] = len(free_at)
            free_at.append(e - day)
            deadline.append(s)
    rest = [i for i in range(len(line))
            if i not in room_of]
    others = sorted(rest, key=lambda i: line[i])
    for i in others:
        s, e = line[i]
        # the room that has been free the longest and fits
        fits = [r for r in range(len(free_at))
                if free_at[r] <= s and e <= deadline[r]]
        if fits:
            room = max(fits, key=lambda r: free_at[r])
        else:
            room = len(free_at)
            free_at.append(0)
            deadline.append(day)
        room_of[i] = room
        free_at[room] = e
    return [room_of[i] for i in range(len(meetings))]


def valid_assignment(meetings, rooms, day=DAY):
    # check that no room holds two meetings at the same
    # hour
    used = set()
    for m, room in zip(meetings, rooms):
        for h in hours(m, day):
            if (room, h) in used:
                return False
            used.add((room, h))
    return True
```

```
def brute_min_rooms(meetings, day=DAY):
    return max((sum(1 for m in meetings
                    if h in hours(m, day))
                for h in range(day)), default=0)


if __name__ == "__main__":
```

```
    long = [[0, 30], [5, 10], [15, 20]]
    assert min_rooms_sweep(long) == 2
    assert min_rooms_sweep([[7, 10], [2, 4]]) == 1
    night = [[22, 2], [23, 1], [0, 3]]
    assert min_rooms_sweep(night) == 3
    assert min_rooms_sweep([]) == 0
    # one ends exactly when the next starts: same room
    assert min_rooms_sweep([[1, 5], [5, 9]]) == 1
    flat = [[0, 30], [5, 10], [15, 20]]
    rooms = assign_rooms(flat)
    assert rooms == [0, 1, 1]
    assert len(set(rooms)) == min_rooms_sweep(flat)
    two = [(22, 2), (1, 5)]
    assert valid_assignment(two, assign_single_rooms(two))
    import random
    for _ in range(400):
        ms = []
        for _ in range(random.randint(0, 7)):
            s, e = random.sample(range(DAY), 2)
            ms.append((s, e))
        assert min_rooms_sweep(ms) == brute_min_rooms(ms)
        rooms = assign_single_rooms(ms)
        assert valid_assignment(ms, rooms)
        assert len(set(rooms)) >= brute_min_rooms(ms)
        if all(s < e for s, e in ms):
            plain = assign_rooms(ms)
            assert valid_assignment(ms, plain)
            assert len(set(plain)) == brute_min_rooms(ms)
```

MEDIUM | HackTheRounds | Phone Screen | 164 of 165

Playlist Shuffle No Adjacent Artists

STUDY: TALK | ALL TIME 34.9 | 30 DAYS 0 | PRIORITY 109/224

ABOUT THIS QUESTION

Topic: Other: Design, Heaps, Intervals and Misc

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #767 Reorganize String

LeetCode match: LC 767 / LC 1054

QUESTION

Given a playlist of songs where each song has an artist, implement a shuffle function that minimizes (or eliminates) adjacent songs by the same artist.

EXAMPLES

QUESTION

Example 1

Input	`[("A", "song1"), ("A", "song2"), ("B", "song3"), ("B", "song4"), ("C", "song5")]`
Output	`[("A", "song1"), ("B", "song3"), ("A", "song2"), ("B", "song4"), ("C", "song5")]`
Why	`No adjacent songs have same artist.`

CONSTRAINTS

- 1 <= songs.length <= 10^4

APPROACH

Max-heap by remaining count per artist

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the shuffle must be random, how to behave when a perfect arrangement is impossible (the most frequent artist has more than half the songs, rounded up), and whether the result must be uniform among valid shuffles.

BRUTE FORCE TO SAY OUT LOUD

Shuffle randomly, then check for adjacent artists and retry. May never finish.

OPTIMAL IDEA

Feasibility: let n be the song count; an arrangement exists if the largest artist group has at most ceil(n / 2) songs. Build it greedily with a max-heap of remaining songs per artist: repeatedly take from the artist with the most remaining songs who is not the previous artist, using random choice among songs of that artist (and optionally among equally big groups) to keep the result varied. If infeasible, place the leftovers at the end or spread them as evenly as possible, and say that adjacency is then unavoidable. O(n log A).

DRY-RUN THESE CASES

One artist (impossible), two artists with equal counts (alternating), the largest artist at exactly half rounded up, three songs with two from the same artist.

LIKELY FOLLOW-UPS

Uniform randomness among all valid shuffles (harder), or a minimum spacing of K songs between the same artist.

PITFALLS

Choosing the largest group even when it was just played. Assuming the greedy result is uniformly random.

HOW TO THINK ABOUT IT

A perfect arrangement exists exactly when the most frequent artist has at most ceil(n / 2) songs. Build it greedily: always play from the artist with the most songs left, except the artist who just played. A max-heap gives the most frequent artist; hold the previous artist back for one step. If it is impossible, the leftover songs of the dominant artist are the only unavoidable adjacencies.

Basis: LeetCode 767 (Reorganize String) and 1054 (Distant Barcodes) with songs and artists. Minimising adjacent same-artist pairs when a perfect arrangement does not exist.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(songs):
    best, best_pairs = None, INF
    for order in permutations(songs):
        pairs = 0
        for a, b in zip(order, order[1:]):
            if a.artist == b.artist:
                pairs += 1
        if pairs < best_pairs:
            best, best_pairs = order, pairs
    return best
```

TIME	SPACE
O(n! * n)	O(n)

WHY IT IS SLOW

n! orderings. A greedy that always plays the artist with the most songs left (not the one that just played), using a heap, is O(n log A).

OPTIMAL SOLUTION · Greedy with a max-heap, holding back the last artist

TIME	SPACE
O(n log A)	O(A)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The shuffle should look random, not always the same arrangement.

Break ties between equally frequent artists randomly and pick the song within the artist at random, as in the code. The result is valid but not uniform among all valid shuffles; a uniform sampler needs counting arrangements.

FOLLOW-UP 2 Songs by the same artist must be at least K apart.

Same idea with a waiting queue of length K: after playing an artist, hold them for K - 1 more songs before they are eligible again (the LeetCode 358 construction).

FOLLOW-UP 3 What is the minimum number of unavoidable repeats?

With n songs and a dominant artist with m songs, the other n - m songs separate at most n - m + 1 groups, so at least m - (n - m + 1) = 2m - n - 1 neighbouring pairs of that artist are forced (if positive).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import heapq
import random
from collections import deque
from itertools import permutations


# BASE QUESTION (optimal): Greedy with a max-heap, holding
# back the last artist
# FOLLOW-UP 1, 2: The shuffle should look random, not
# always the same arrangement.
def shuffle_playlist(songs, gap=2, strict=False,
                     rng=random):
    # songs are (artist, title). The artist with the most
    # songs left plays next and then waits `gap - 1` other
    # songs before it may play again (gap 2 = never twice
    # in
    # a row). Ties between artists and the song picked
    # inside
    # an artist are random, so every run looks different.
    by_artist = {}
    for artist, title in songs:
        by_artist.setdefault(artist, []).append(title)
    for titles in by_artist.values():
        # FOLLOW-UP 1: random song order inside an artist
        rng.shuffle(titles)
    # FOLLOW-UP 1: random tie-break between artists
    heap = [(-len(t), rng.random(), a)
            for a, t in by_artist.items()]
    heapq.heapify(heap)
    waiting, out = deque(), []
    while len(out) < len(songs):
        if not heap:
            # everyone left is still waiting
            if strict:
                return None
            take_oldest(waiting, heap)
        left, _, artist = heapq.heappop(heap)
        out.append((artist, by_artist[artist].pop()))
        # an artist stays in the queue even with no songs
        # left: it still marks one position of spacing
        waiting.append((left + 1, rng.random(), artist))
        # FOLLOW-UP 2: gap=K keeps an artist out for K - 1
        # songs
        if len(waiting) >= gap:
            release(waiting, heap)
    return out


def release(waiting, heap):
    # the oldest waiting artist may play again (if it has
    # any song left)
    entry = waiting.popleft()
    if entry[0]:
        heapq.heappush(heap, entry)
```

```
def take_oldest(waiting, heap):
    # break the gap on purpose: the first waiting artist
    # that still has songs plays early
    while waiting:
        entry = waiting.popleft()
        if entry[0]:
            heapq.heappush(heap, entry)
            return


# FOLLOW-UP 3: What is the minimum number of unavoidable
# repeats?
def forced_repeats(counts):
    # follow-up: the fewest unavoidable neighbouring
    # pairs.
    # The other songs split the dominant artist into at
    # most
    # (n - m + 1) groups, so 2m - n - 1 pairs touch.
    n, m = sum(counts), max(counts)
    return max(0, 2 * m - n - 1)


def adjacent_pairs(playlist):
    pairs = zip(playlist, playlist[1:])
    return sum(1 for a, b in pairs if a[0] == b[0])


# CHECKER (brute force)
def brute_min_pairs(songs):
    # oracle: try every order (small playlists only)
    orders = permutations(songs)
    return min(adjacent_pairs(p) for p in orders)
```

```
if __name__ == "__main__":
    rng = random.Random(7)
    songs = [("A", "song1"), ("A", "song2"),
             ("B", "song3"), ("B", "song4"),
             ("C", "song5")]
    mixed = shuffle_playlist(songs, rng=rng)
    assert sorted(mixed) == sorted(songs)
    assert adjacent_pairs(mixed) == 0
    # 4 songs by A and 1 by B: 2 touching pairs are forced
    heavy = [("A", str(i)) for i in range(4)]
    heavy.append(("B", "x"))
    out = shuffle_playlist(heavy, rng=rng)
    assert adjacent_pairs(out) == forced_repeats([4, 1])
    assert adjacent_pairs(out) == 2
    strict = shuffle_playlist(heavy, strict=True, rng=rng)
    assert strict is None
    assert shuffle_playlist([], rng=rng) == []
    # at least 3 apart: three artists, two songs each
    trio = [(a, a + str(i))
            for a in "ABC" for i in range(2)]
    far = shuffle_playlist(trio, 3, True, rng)
    assert sorted(far) == sorted(trio)
    for i, (artist, _) in enumerate(far):
        recent = far[max(0, i - 2):i]
        assert all(other != artist for other, _ in recent)
    # runs differ from each other but are all valid
    seen = {tuple(shuffle_playlist(songs, rng=rng))
            for _ in range(30)}
    assert len(seen) > 1
    for _ in range(150):
        size = random.randint(1, 7)
        songs = [(random.choice("ABC"), str(i))
                 for i in range(size)]
        counts = [sum(1 for a, _ in songs if a == x)
                  for x in "ABC"]
        got = shuffle_playlist(songs, rng=rng)
        assert sorted(got) == sorted(songs)
        pairs = adjacent_pairs(got)
        assert pairs == forced_repeats(counts)
        assert pairs == brute_min_pairs(songs)
```

HackTheRounds - Easy (1)

Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns 1 questions

EASY | HackTheRounds | Onsite | 165 of 165

Parity Alternating Subarray Query

STUDY: TALK | ALL TIME 34.9 | 30 DAYS 0 | PRIORITY 111/224

ABOUT THIS QUESTION

Topic: Core Array, String, Hash Map, Sliding Window, and Binary Search Patterns

Optimal answer from: the interview site's own solution

Related in your app (a neighbouring problem, not this exact question): LeetCode #303 Range Sum Query - Immutable

LeetCode match: No direct match; prefix-sum range queries (idea of LC 303)

QUESTION

Given an array nums and multiple queries, each query asks whether a subarray nums[l:r] satisfies the condition that adjacent elements alternate in parity (odd-even-odd-even or even-odd-even-odd). Preprocess the array to answer each query in O(1) time.

EXAMPLES

Example 1

Input	`nums = [1, 2, 3, 4, 5], queries = [[0, 4], [1, 3]]`
Output	`[true, true]`
Why	`All adjacent pairs alternate in parity.`

Example 2

Input	`nums = [1, 3, 2, 4], queries = [[0, 1], [0, 3]]`
Output	`[false, false]`
Why	`nums[0]=1 and nums[1]=3 are both odd.`

CONSTRAINTS

- 1 <= nums.length <= 10^5
- 1 <= queries.length <= 10^5
- 0 <= l <= r < nums.length

APPROACH

Prefix count of adjacent pairs with equal parity; a query [l, r] alternates iff the count over (l..r-1) is 0. O(1) per query.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether the query range is inclusive or exclusive (the statement writes nums[l:r]), whether a single element counts as alternating, and the number of queries.

BRUTE FORCE TO SAY OUT LOUD

For each query scan the range checking adjacent parities. O(length) per query.

OPTIMAL IDEA

Precompute a prefix count B where B[i] is the number of adjacent pairs (j, j + 1) with j < i whose parities are equal. A subarray from l to r (inclusive) alternates exactly when the number of equal-parity pairs among positions l to r - 1 is zero, i.e. B[r]

- B[l] == 0. O(n) preprocessing, O(1) per query.

DRY-RUN THESE CASES

A single-element range, a range with two equal-parity neighbors, the whole array, l equal r, negative numbers (use x % 2 carefully).

LIKELY FOLLOW-UPS

Update an element (Fenwick tree), or return the longest alternating subarray.

PITFALLS

Off-by-one on the inclusive end. Parity of negative numbers in languages where % can be negative.

HOW TO THINK ABOUT IT

A subarray alternates in parity exactly when it contains no pair of neighbours with the same parity. 'Count of bad pairs in a range' is a prefix sum question, so precompute once and answer every query with one subtraction. Mark each position i by whether (nums[i], nums[i + 1]) is a bad pair.

Basis: Prefix counts for range queries (compare LeetCode 303). Assumed rule: a query (l, r) is inclusive on both ends; a single element is alternating.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def alternates(nums, l, r):
    for i in range(l, r):
        if nums[i] % 2 == nums[i + 1] % 2:
            return False
    return True
```

TIME	SPACE
O(length) per query	O(1)

WHY IT IS SLOW

BRUTE FORCE

Each query scans up to n elements. A prefix count of equal-parity neighbour pairs answers every query in O(1) after one O(n) pass.

OPTIMAL SOLUTION · Prefix count of equal-parity neighbour pairs

TIME	SPACE
O(n) to build, O(1) per query	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 The array also changes (point updates).

Keep the bad-pair indicators in a Fenwick tree: an update changes at most two indicators, each an O(log n) update, and a query is two prefix sums.

FOLLOW-UP 2 Find the longest alternating subarray.

One pass with a running length that resets to 1 on a bad pair. O(n), O(1).

FOLLOW-UP 3 Offline queries, different property (for example all elements distinct).

The prefix-sum trick applies whenever the property is 'no violating neighbour pair'. Properties about distinctness need Mo's algorithm or an offline sweep with last-occurrence tracking. **Cost:** Mo's algorithm is O((n + q) sqrt(n)); the prefix trick for 'no violating neighbour pair' stays O(n + q).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
# BASE QUESTION (optimal): Prefix count of equal-parity
# neighbour pairs
class ParityQueries:
    """Static array. bad[i] = number of neighbouring pairs
    with equal parity among the first i pairs. A range
    alternates when it contains no such pair."""

    def __init__(self, nums):
        self.bad = [0]
        for a, b in zip(nums, nums[1:]):
            same = a % 2 == b % 2
            self.bad.append(self.bad[-1] + same)

    def alternates(self, l, r):
        # pairs l .. r - 1 are inside the range [l, r]
        return self.bad[r] - self.bad[l] == 0


class Fenwick:
    def __init__(self, size):
        self.size = size
        self.tree = [0] * (size + 1)
```

```
    def add(self, i, delta):
        i += 1
        while i <= self.size:
            self.tree[i] += delta
            i += i & -i

    def prefix(self, i):
        # sum of the first i items
        total = 0
        while i > 0:
            total += self.tree[i]
            i -= i & -i
        return total


# FOLLOW-UP 1: The array also changes (point updates).
class ParityWithUpdates:
    """Follow-up: point updates. The equal-parity flags
    live in a Fenwick tree; changing one number changes
    at most two flags, and a query is two prefix sums."""

    def __init__(self, nums):
```

```
        self.nums = list(nums)
        self.flags = [0] * max(len(nums) - 1, 0)
        self.tree = Fenwick(len(self.flags))
        for i in range(len(self.flags)):
            self.refresh(i)

    def refresh(self, i):
        # recompute the flag of the pair (i, i + 1)
        a, b = self.nums[i], self.nums[i + 1]
        now = int(a % 2 == b % 2)
        self.tree.add(i, now - self.flags[i])
        self.flags[i] = now

    def update(self, i, value):
        self.nums[i] = value
        for pair in (i - 1, i):
            if 0 <= pair < len(self.flags):
                self.refresh(pair)

    def alternates(self, l, r):
        inside = self.tree.prefix(r) - self.tree.prefix(l)
        return inside == 0


# FOLLOW-UP 2: Find the longest alternating subarray.
def longest_alternating(nums):
    # follow-up: one pass with a running length that
    # restarts at 1 after a bad pair
    best = run = 1 if nums else 0
    for a, b in zip(nums, nums[1:]):
        run = run + 1 if a % 2 != b % 2 else 1
        best = max(best, run)
    return best


def brute(nums, l, r):
    return all(nums[i] % 2 != nums[i + 1] % 2
               for i in range(l, r))


if __name__ == "__main__":
    q = ParityQueries([1, 2, 3, 4, 5])
    assert q.alternates(0, 4) and q.alternates(1, 3)
    q = ParityQueries([1, 3, 2, 4])
    assert not q.alternates(0, 1)
```

```
    assert not q.alternates(0, 3)
    assert q.alternates(1, 2)
    # a single element always alternates
    assert q.alternates(2, 2)
    assert longest_alternating([1, 3, 2, 4]) == 2
    assert longest_alternating([1, 2, 3, 4, 5]) == 5
    assert longest_alternating([]) == 0
    assert longest_alternating([7]) == 1
    import random
    for _ in range(200):
        nums = [random.randint(0, 9)
                for _ in range(random.randint(1, 10))]
        fixed = ParityQueries(nums)
        live = ParityWithUpdates(nums)
        for _ in range(20):
            if random.random() < 0.4:
                i = random.randrange(len(nums))
                nums[i] = random.randint(0, 9)
                live.update(i, nums[i])
            l = random.randrange(len(nums))
            r = random.randrange(l, len(nums))
            want = brute(nums, l, r)
            assert live.alternates(l, r) == want
        fixed = ParityQueries(nums)
        l = random.randrange(len(nums))
        r = random.randrange(l, len(nums))
        assert fixed.alternates(l, r) == brute(nums, l, r)
```

ALSO REPORTED · 2 more

Answer parity-alternation range queries | PracHub | Technical Screen

https://prachub.com/coding-questions/answer-parity-alternation-range-queries

Answer range queries for alternating parity subarrays | PracHub | Technical Screen

https://prachub.com/coding-questions/answer-range-queries-for-alternating-parity-subarrays