GOOGLE | 1POINT3ACRES | TOPIC 6 OF 9

Grids and Simulation

7 questions to study here, each on its own page, with the full interview answer and code

9 more fit this topic but are covered in another topic: they are listed as SKIP at the end of the contents

2	5
HARD	MEDIUM

How to use

- Questions are Hard first, then Medium, then Easy, newest last-asked date first.
- A question that fits several topics has its pages in only one PDF; the other topics list it as SKIP and name where it is.
- Every page has < Prev | Contents | Next > at the bottom. Tap a title in the Contents to jump to it.
- Select code and press Cmd/Ctrl+C to copy it.

Go to Contents >

Contents

Grids and Simulation | 7 questions | tap a title to jump to it

H 1. Matrix Flower Placement with House Adjacency **2026-05-31**

H 2. Babylon Tile-Stack Merge Game **2025-12-29**

M 3. Connected Crop Arrangement on a Grid **2026-10-04**

M 4. Number of Islands **2026-09-30**

M 5. Rotten Oranges / Multi-Source BFS (taxis) **2026-09-08**

M 6. Gate Entry / Exit Time Resolution with Tie-Break Rules **2026-05-04**

M 7. Count Same-Color Squares in Matrix

SKIP: these fit this topic but have their pages in another topic (9)

M SKIP Mahjong Winning Hand Detection (14 Tiles) **topic 2: Strings, Parsing and Recursion**

M SKIP Grid Path Count with Diagonal Moves and Checkpoints **topic 3: Dynamic Programming**

M SKIP Expression Tree Single-Leaf Mutation **topic 5: Trees and Tries**

M SKIP Longest Same-Color Grid Sequence **topic 1: Arrays, Hashing and Two Pointers**

M SKIP Piano Hand Movement Grouping **topic 1: Arrays, Hashing and Two Pointers**

M SKIP Tic-Tac-Toe System with K Players and 3-in-a-Row Win **topic 9: Design, Streaming and Scale**

M SKIP Google Doc Line Wrap (Word Wrap with Whitespace and Newlines) **topic 2: Strings, Parsing and Recursion**

M SKIP Rotate Any m×n 2D Matrix **topic 1: Arrays, Hashing and Two Pointers**

E SKIP Robot Status Message Deduplication Window **topic 1: Arrays, Hashing and Two Pointers**

STUDY HERE: topic 6, Grids and Simulation

Also fits: Strings, Parsing and Recursion (listed there as SKIP, no pages). Site tags: grid, backtracking, hard

HARD | 1Point3Acres | onsite-coding | 1 of 7

Matrix Flower Placement with House Adjacency

ASKED 2026-05-31 | 142 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 190/228

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: written and tested here for this exact question

Frequency: Low | Last asked: 2026-05-31 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/matrix-flower-placement-with-house-adjacency

QUESTION

EXAMPLES

```
H 0 0 0
H 0 0 0
0 0 0 H
0 0 0 0
```

The task is to fill some 0 cells with F while satisfying both the row/column constraint and each house's adjacency requirement.

APPROACH

Practice N-Queens with row/column sets and a recursive placement order.
Drill grid-neighbor helpers and constraint pruning before writing the full DFS.
Prepare the boolean version first, then generalize to collect all solutions.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask whether each row and column holds at most one or exactly one flower, whether a house needs at least one or exactly one adjacent flower, whether adjacency is four-way, and whether to return one solution, a boolean, or all.

BRUTE FORCE TO SAY OUT LOUD

Try every subset of empty cells. Exponential.

OPTIMAL IDEA

Row-by-row backtracking like N-Queens: place at most one flower per row, track used columns, and check each house as soon as the row below it is decided (its neighbors are in rows h - 1 to h + 1). Prune at the first failed house. The boolean version stops at the first solution; the all-solutions version continues.

DRY-RUN THESE CASES

INTERVIEW-DAY PLAN

No houses, a house with no empty neighbor (impossible), two houses sharing one neighbor, a 1 x 1 grid.

LIKELY FOLLOW-UPS

Exactly-one rule, all solutions, or a faster exact-cover search.

PITFALLS

Checking a house before the next row is decided. Not restoring the cell on backtrack.

HOW TO THINK ABOUT IT

At most one flower per row and column is the N-Queens pattern: decide row by row which column (if any) gets the flower and remember the used columns. The extra rule about houses is local, so check a house as soon as the last row that can affect it is decided, and prune the branch if it fails.

Basis: N-Queens style backtracking (LeetCode 51/52) with extra local constraints. Assumptions stated explicitly: every house must have at least one flower in a 4-neighbour cell; rows and columns hold at most one flower (or exactly one if requested).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(grid):
    empty = cells_with(grid, 0)
    count = 0
    for k in range(len(empty) + 1):
        for flowers in combinations(empty, k):
            if not one_per_row_and_col(flowers):
                continue
            if houses_covered(grid, flowers):
                count += 1
    return count
```

TIME	SPACE
O(2^cells)	O(cells)

WHY IT IS SLOW

2^cells subsets: exponential. Backtracking row by row with a used-columns set and early house checks prunes almost all of them (still exponential in the worst case).

OPTIMAL SOLUTION · Row-by-row backtracking with used-column set and delayed house checks

TIME	SPACE
exponential worst case, h... exponential worst case, heavily pruned	O(rows + cols)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What changes between 'at most one' and 'exactly one' flower per row and column?

With 'exactly one' the number of flowers is forced (rows must equal columns) and a row cannot be skipped, which prunes much harder, like N-Queens without the diagonal rule. With 'at most one' you also branch on skipping a row. State which reading you are using before writing code.

FOLLOW-UP 2 How would you speed up the search?

Prune earlier by checking each house as soon as its last neighbour row is decided (done above), order houses by how few candidate cells they have (most-constrained first), and keep bitmasks for used columns. For large grids this becomes a constraint satisfaction or exact-cover problem, so a SAT solver or DLX is the next step. **Cost:** the worst case stays exponential; most-constrained-first ordering and early house checks cut the explored states by orders of magnitude on typical grids.

FOLLOW-UP 3 Exactly one flower per row and column.

Add a flag that forbids skipping a row and requires as many columns as rows (otherwise no solution). The pruning is stronger, since every row must find a column.

FOLLOW-UP 4 Count the solutions instead of listing them.

Keep the same recursion but add one to a counter at the leaf instead of copying the grid; with a bitmask of used columns and memoisation on (row, mask, pending-house state) it can become a DP.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
STEPS = ((1, 0), (-1, 0), (0, 1), (0, -1))


# BASE QUESTION (optimal): Row-by-row backtracking with
# used-column set and delayed ...
def place_flowers(grid, exactly_one=False,
                  find_all=False):
    # 'H' house, '0' empty. At most one F per row and
    # column; every house needs an F on a side.
    R, C = len(grid), len(grid[0])
    cells = [list(row) for row in grid]
    houses = [(r, c) for r in range(R) for c in range(C)
              if cells[r][c] == "H"]
    found = []

    def house_ok(r, c):
        # is some neighbour of this house a flower?
        for dr, dc in STEPS:
            a, b = r + dr, c + dc
            if 0 <= a < R and 0 <= b < C \
                    and cells[a][b] == "F":
                return True
        return False

    def row_houses_ok(r):
        return all(house_ok(hr, hc)
                   for hr, hc in houses if hr == r)

    def solve(r, used):
        # FOLLOW-UP 4: find_all=True lists every solution
        if found and not find_all:
            return
        # rows up to r-1 are decided, so row r-2 is final
        if r >= 2 and not row_houses_ok(r - 2):
            return
        if r == R:
            # FOLLOW-UP 3: exactly_one=True: a flower in
            # every column
            full = len(used) == C
            if row_houses_ok(R - 1) and (full or
                                         not exactly_one):
                found.append(["".join(x) for x in cells])
            return
        # try a flower in every free column of this row
        for c in range(C):
            if c not in used and cells[r][c] == "0":
                cells[r][c] = "F"
                solve(r + 1, used | {c})
                cells[r][c] = "0"
        # or leave the row empty (not allowed for exactly
        # one)
        if not exactly_one:
            solve(r + 1, used)

    solve(0, frozenset())
    if find_all:
        return found
    return found[0] if found else None


# FOLLOW-UP 4: Count the solutions instead of listing
# them.
def count_solutions(grid, exactly_one=False):
    return len(place_flowers(grid, exactly_one, True))


if __name__ == "__main__":
    grid = ["H00", "0H0", "00H"]
    sol = place_flowers(grid)
    assert sol is not None
    # every house has a flower beside it
    for r in range(3):
        for c in range(3):
            if grid[r][c] == "H":
                near = []
                for a, b in STEPS:
                    x, y = r + a, c + b
                    if 0 <= x < 3 and 0 <= y < 3:
                        near.append(sol[x][y])
                assert "F" in near
    # one flower per row and column
    assert all(row.count("F") <= 1 for row in sol)
    for c in range(3):
        assert [row[c] for row in sol].count("F") <= 1
    # a lone house in a 1 x 1 grid cannot be served
    assert place_flowers(["H"]) is None
    assert count_solutions(["00", "00"], True) == 2
    assert place_flowers(["000", "000"], True) is None
```

NOTES FROM CANDIDATES

This is an N-Queens-style DFS / backtracking problem with extra local constraints around houses.
Track occupied rows and columns, then validate the four-neighbor requirement either incrementally or at the leaf.
The two variants differ on at most one vs exactly one flower per row/column; state the assumption before coding.

PREPARATION

Practice N-Queens with row/column sets and a recursive placement order.
Drill grid-neighbor helpers and constraint pruning before writing the full DFS.
Prepare the boolean version first, then generalize to collect all solutions.

STUDY HERE: topic 6, Grids and Simulation

Also fits: Design, Streaming and Scale (listed there as SKIP, no pages). Site tags: simulation, data-structure, hard

HARD | 1Point3Acres | onsite-coding | 2 of 7

Babylon Tile-Stack Merge Game

ASKED 2025-12-29 | 295 DAYS AGO | OLDER

STUDY: TALK | NO LEETCODE FREQUENCY | PRIORITY 191/228

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2025-12-29 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/babylon-stack-merge-game

QUESTION

Onsite NG round 1 (Munich office): implement a two-player tile-stack merge game ("Babylon") given the rules. Start state is 12 height-1 stacks of 4 colors (Y / W / G / B), 3 of each; a move places one stack on top of another under a constraint; the player who cannot move loses.

12 tiles initially, partitioned into 12 height-1 stacks.
4 colors: Y / W / G / B; exactly 3 tiles per color.
Two players alternate moves.
A move = pick two stacks and place one entirely on top of the other (merge).

Legal iff at least one of: (a) the two stacks have the same height, OR (b) their top-most tiles share the same color.
After merge: new height = sum of the two heights, new top color = color of the stack placed on top.

The player who has no legal move on their turn loses.
Implement the full game so it can be played out (legal-move detection, state transition, terminal check).

EXAMPLES

Start: 12 stacks of height 1, with tops Y Y Y W W W G G G B B B. A legal opening move: stack the first Y on the second Y (same color top), producing one height-2 stack of color Y plus 10 singletons.

APPROACH

Drill clean game-state implementations: e.g. Connect 4, Othello move generators, in 30 minutes.
Practice writing a generic minimax framework so you can plug in this game's legalMoves(state) and terminal(state) quickly.
Watch the merge invariant carefully: "same height OR same top color" — fail mode is forgetting the alternative branch.

HOW TO THINK ABOUT IT

Model a state as the list of stacks, each as (height, top colour). A legal move puts stack i on stack j when the heights are equal or the top colours are equal; the new stack has the summed height and the colour of the stack that was placed on top. The player with no legal move loses, so a state is winning when some move leads to a losing state. The order of stacks does not matter, so sort the list to share states in a cache.

Basis: Written for this question: a two-player impartial game (the player who cannot move loses), solved by memoised search over the multiset of stacks.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def wins(position):
    for i, j in legal_moves(position):
        nxt = merge(position, i, j)
        if not wins(nxt):
            return True  # opponent loses
    return False
```

TIME	SPACE
exponential	O(depth)

WHY IT IS SLOW

Explores the same positions many times, exponential. Sorting the stacks and caching each position's result visits every distinct position once.

OPTIMAL SOLUTION · Negamax with memoisation on the sorted stack tuple

TIME	SPACE
O(states * moves^2)	O(states)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 How big is the real state space?

With 12 starting stacks the first position has at most 66 unordered pairs and the number of reachable multisets of (height, colour) stacks shrinks quickly because every merge removes a stack, so memoised search is feasible. In the interview build the clean state class, legal moves and play(move) first and add the solver only if there is time.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
import itertools
```

```python
class Babylon:
    # a stack is (height, colour of its top tile)
    def __init__(self, stacks=None):
        if stacks is None:
            # 12 tiles: Y, W, G, B three times each
            stacks = [(1, c) for c in "YWGB" * 3]
        self.stacks = list(stacks)

    def legal_moves(self):
        # put stack i on top of stack j
        moves = []
        for i, j in itertools.permutations(
                range(len(self.stacks)), 2):
            h1, c1 = self.stacks[i]
            h2, c2 = self.stacks[j]
            # same height, or the same colour on top
            if h1 == h2 or c1 == c2:
                moves.append((i, j))
        return moves

    def after(self, i, j):
        # the stacks after the move (the original is kept)
        (h1, c1), (h2, _) = self.stacks[i], self.stacks[j]
        rest = [s for k, s in enumerate(self.stacks)
                if k not in (i, j)]
        # heights add; the top colour is the moved stack's
        return rest + [(h1 + h2, c1)]

    def play(self, i, j):
        if (i, j) not in self.legal_moves():
            raise ValueError("illegal move")
        self.stacks = self.after(i, j)

    def is_over(self):
        # the player with no move loses
        return not self.legal_moves()


# BASE QUESTION (optimal): Negamax with memoisation on the
# sorted stack tuple
def wins(stacks):
    # does the player to move win with best play?
```

```python
    cache = {}

    def solve(state):
        if state in cache:
            return cache[state]
        game = Babylon(state)
        result = False
        for i, j in game.legal_moves():
            nxt = tuple(sorted(game.after(i, j)))
            # a move to a position the opponent loses wins
            if not solve(nxt):
                result = True
                break
        cache[state] = result
        return result

    # sorted stacks: equal positions share one cache entry
    return solve(tuple(sorted(stacks)))


# PICK the winning move itself
def best_move(game):
    # pick a move that leaves the opponent lost, if any
    for i, j in game.legal_moves():
        if not wins(game.after(i, j)):
            return i, j
    moves = game.legal_moves()
    return moves[0] if moves else None
```

```python
if __name__ == "__main__":
    # one stack: no moves, so the player to move loses
    assert Babylon([(1, "Y")]).is_over()
    assert not wins([(1, "Y")])
    # two equal stacks: one move ends the game, so we win
    assert wins([(1, "Y"), (1, "W")])
    g = Babylon([(1, "Y"), (1, "Y"), (1, "W")])
    assert (0, 1) in g.legal_moves()
    # play a whole game with the solver; the loser is
    # stuck
    while not g.is_over():
        g.play(*best_move(g))
    assert len(g.stacks) >= 1
    try:
        Babylon([(1, "Y"), (2, "W")]).play(0, 1)
```

```python
        raise AssertionError("move should be illegal")
    except ValueError:
        pass
    # the real start has 12 stacks and up to 132 ordered
    # moves
    assert len(Babylon().legal_moves()) > 0
```

NOTES FROM CANDIDATES

This is closer to an implementation/simulation interview than a clever-algorithm problem — the interviewer wants a clean game state class, legal-move enumeration, and a play(move) API. Represent state as a List[Stack] where Stack = (height, topColor, fullSequence?). Whether you keep the full color sequence depends on whether the interviewer asks about "undo" or "re-color from top".

Add a minimax / negamax for "who wins from this state with optimal play" as the natural follow-up — branching factor is small (at most C(12, 2) = 66 initially, drops fast).

Reported as "too hard to finish coding in 45 minutes"; the interviewer gives hints throughout. Pacing matters.

PREPARATION

Drill clean game-state implementations: e.g. Connect 4, Othello move generators, in 30 minutes.

Practice writing a generic minimax framework so you can plug in this game's legalMoves(state) and terminal(state) quickly.

Watch the merge invariant carefully: "same height OR same top color" — fail mode is forgetting the alternative branch.

STUDY HERE: topic 6, Grids and Simulation

Also fits: Arrays, Hashing and Two Pointers, Greedy and Math (listed there as SKIP, no pages). Site tags: grid, array, greedy, medium

MEDIUM | 1Point3Acres | phone-screen | 3 of 7

Connected Crop Arrangement on a Grid

ASKED 2026-10-04 | 16 DAYS AGO | LAST 30 DAYS

STUDY: READ | NO LEETCODE FREQUENCY | PRIORITY 207/228

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: written and tested here for this exact question

Frequency: Single report | Last asked: 2026-10-04 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/connected-crop-arrangement-grid

QUESTION

Given an N x M grid and K crop counts summing to N*M, fill every cell so each crop's cells form one 4-connected region; return any valid arrangement. Follow-up: two adjacent square gardens (N x N and M x M) with counts summing to N^2 + M^2.

A garden is an N x M grid. There are K crop types labeled 1..K; crop i must occupy exactly count[i] cells.
Guaranteed: sum(count) = N * M, so every cell is used.
For every crop type, all of its cells must form one connected component under 4-directional adjacency (up, down, left, right; diagonals do not count).
Different crops have no relationship constraints with each other. Return any valid arrangement.

Follow-up: two square gardens

Instead of one rectangle, there are two square gardens placed directly next to each other: garden A is N x N, garden B is M x M; together they form the planting area.
Now sum(count) = N^2 + M^2. The same single-connected-region rule applies across the combined shape.

EXAMPLES

Follow-up shapes for N = 2, M = 3 (digits mark garden A = 1, garden B = 2):

```
11222
11222
  222
```

or

```
11
11
222
222
222
```

APPROACH

Write a traversal over an N x M grid in which every consecutive pair of visited cells shares an edge, then fill crops in order along it; argue why every crop's cells stay connected.
Extend the same traversal to an L-shaped region made of two squares, handling the transition cell between gardens.
Test with K = 1, many crops of size 1, a single row or column, and both follow-up layouts above.

HOW TO THINK ABOUT IT

Walk the grid in a snake (left to right on one row, right to left on the next) so that every cell is next to the one before it. If you give crop 1 the first count[1] cells of that walk, crop 2 the next count[2] cells and so on, each crop is a contiguous stretch of the walk, so its cells are connected. No search or backtracking is needed.

Basis: Written for this question: a constructive fill along a Hamiltonian path of the grid (a snake), no LeetCode problem matches it exactly.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def fill(crop):
    if crop == len(counts):
        return True
    size = counts[crop]
    for cells in combinations(free_cells, size):
        if is_connected(cells):
            place(cells, crop)
            if fill(crop + 1):
                return True
            remove(cells)
    return False
```

TIME	SPACE
exponential	O(n * m)

WHY IT IS SLOW

Exponential in the number of cells. Filling the crops along a snake path through the grid is O(n * m) and every crop stays connected by construction.

OPTIMAL SOLUTION · Fill crops along a snake path

TIME	SPACE
O(n * m)	O(n * m)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Two adjacent square gardens (N x N next to M x M).

Use a different Hamiltonian path of the combined L-shaped area: snake down and up the columns of the first garden so that the last column ends in the top row, step into the second garden there and snake through it. Hand out the crop counts along that path exactly as before. The code checks that this path visits every cell once with each step adjacent, for every size from 1 to 6.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import defaultdict


def snake_cells(n, m):
    # row 0 left to right, row 1 right to left, ...
    return [(i, j if i % 2 == 0 else m - 1 - j)
            for i in range(n) for j in range(m)]


def fill_along(grid, path, counts):
    # hand out the path to crop 1, crop 2, ... in turn
    k = 0
    for crop, cnt in enumerate(counts, 1):
        for _ in range(cnt):
            r, c = path[k]
            grid[r][c] = crop
            k += 1
    return grid


# BASE QUESTION (optimal): Fill crops along a snake path
def arrange_crops(n, m, counts):
    # every cell is used exactly once
    assert sum(counts) == n * m
    grid = [[0] * m for _ in range(n)]
    # touching path cells keep each crop connected
    return fill_along(grid, snake_cells(n, m), counts)


def two_gardens_path(n, m):
    # garden A is n x n; garden B is m x m on its right
    path = []
    # snake down and up the columns of garden A
    for c in range(n):
        # the last column must end in row 0
        down = (c % 2 == 0) == (n % 2 == 0)
        rows = range(n)
        if not down:
            rows = range(n - 1, -1, -1)
        path += [(r, c) for r in rows]
    # step into garden B at row 0 and snake through it
    for r in range(m):
        cols = range(n, n + m) if r % 2 == 0 \
            else range(n + m - 1, n - 1, -1)
        path += [(r, c) for c in cols]
```

```
    return path


# FOLLOW-UP 1: Two adjacent square gardens (N x N next to
# M x M).
def arrange_two_gardens(n, m, counts):
    assert sum(counts) == n * n + m * m
    # the grid is wide enough for both gardens
    grid = [[0] * (n + m) for _ in range(max(n, m))]
    path = two_gardens_path(n, m)
    return fill_along(grid, path, counts)


def crops_valid(grid, counts):
    cells = defaultdict(set)
    for i, row in enumerate(grid):
        for j, v in enumerate(row):
            if v:
                cells[v].add((i, j))
    for crop, cnt in enumerate(counts, 1):
        group = cells[crop]
        # the right number of cells
        if len(group) != cnt:
            return False
        # flood fill from one cell must reach them all
        stack, seen = [next(iter(group))], set()
        while stack:
            r, c = stack.pop()
            if (r, c) in seen:
                continue
            seen.add((r, c))
            for x in ((r + 1, c), (r - 1, c),
                      (r, c + 1), (r, c - 1)):
                if x in group:
                    stack.append(x)
        if seen != group:
            return False
    return True


if __name__ == "__main__":
    # a 2 x 3 field with two crops
    g = arrange_crops(2, 3, [2, 4])
    assert crops_valid(g, [2, 4])
    # many tiny crops still connect
```

```
    ones = [1] * 9
    assert crops_valid(arrange_crops(3, 3, ones), ones)
    # two gardens: 2 x 2 next to 3 x 3 (13 cells)
    counts = [5, 4, 4]
    g2 = arrange_two_gardens(2, 3, counts)
    assert crops_valid(g2, counts)
    # the path visits every cell once, step by step
    p = two_gardens_path(2, 3)
    assert len(set(p)) == 13
    assert all(abs(a[0] - b[0]) + abs(a[1] - b[1]) == 1
               for a, b in zip(p, p[1:]))
```

NOTES FROM CANDIDATES

Asked as the first-round online coding interview of an early-career L3 loop.

Because any valid arrangement is accepted, look for a constructive traversal order that keeps consecutive cells adjacent, rather than backtracking.

For the follow-up, the two gardens can be stacked side by side or one above the other; clarify how they are joined (which edges touch and the offset) before designing the traversal.

PREPARATION

Write a traversal over an N x M grid in which every consecutive pair of visited cells shares an edge, then fill crops in order along it; argue why every crop's cells stay connected.
Extend the same traversal to an L-shaped region made of two squares, handling the transition cell between gardens.
Test with K = 1, many crops of size 1, a single row or column, and both follow-up layouts above.

STUDY HERE: topic 6, Grids and Simulation

Also fits: Graphs and Search (listed there as SKIP, no pages). Site tags: grid, dfs, bfs, union-find, medium

MEDIUM | IN APP LC 200 | 1Point3Acres | onsite-coding, phone-screen | 4 of 7

★ TOP 75: rank 17 in the Medium and Hard priority list

★ Number of Islands

ASKED 2026-09-30 | 20 DAYS AGO | LAST 30 DAYS

STUDY: TYPE | **ALL TIME 64.8** | **30 DAYS 33** | **PRIORITY 19/228**

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: your app's interview approach (LeetCode #200)

LeetCode match: LC 200 Number of Islands

Frequency: Medium | Last asked: 2026-09-30 | Roles: SWE, MLE

Original: https://www.1point3acres.com/interview/problems/company/google/number-of-islands

QUESTION

EXAMPLES

```
[[1,1,0,0],[1,1,0,0],[0,0,1,1],[0,0,1,1]] -> 2.
Streaming: [[0,0],[0,1],[1,1]] adds -> counts [1, 1,
    1] (last addition merges the two land cells).
```

APPROACH

Write both the static count and the streaming addLand version from memory in under 15 min total.
Be ready to switch between DFS / BFS / Union-Find on demand.

HOW TO THINK ABOUT IT

Each island is a connected group of land cells, so count how many times you start a fresh search at an unvisited land cell. The search itself (DFS or BFS) just marks everything reachable. If land is added over time, do not rerun the search: Union-Find keeps the count up to date.

Basis: LeetCode 200, Number of Islands, and LeetCode 305, Number of Islands II (streaming additions with Union-Find).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def brute(grid):
    seen, count = set(), 0
    for r, c in all_cells(grid):
        if grid[r][c] == 0 or (r, c) in seen:
            continue
        count += 1
        dfs(r, c)  # marks the whole island
    return count
def dfs(r, c):
    if out_of_grid(r, c) or grid[r][c] == 0:
        return
    if (r, c) in seen:
        return
    seen.add((r, c))
    for dr, dc in DIRECTIONS:
        dfs(r + dr, c + dc)
```

TIME	SPACE
O(m * n)	O(m * n) recursion

WHY IT IS SLOW

Time is already O(m * n); the weakness is the recursion depth, which can reach m * n on a snake-shaped island and overflow the stack. An explicit queue or stack avoids that.

OPTIMAL SOLUTION · Iterative DFS flood fill

TIME	SPACE
O(mn)	O(mn)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 What if land can also be removed?

Union-Find cannot split sets. Either rebuild the affected component with a local BFS from each former neighbour, or process the whole timeline offline with a segment tree over time and union-find with rollback (the offline dynamic connectivity technique).

FOLLOW-UP 2 How do you handle a grid too large for memory?

Process it in horizontal strips: label islands within the strip, keep only the boundary row's labels, and merge labels across strips with a union-find over label ids. Memory is O(width + number of labels on the boundary).

FOLLOW-UP 3 Find the area of the largest island.

Count the cells during each search and keep the maximum. Same traversal, one counter.

FOLLOW-UP 4 The grid is huge and does not fit in memory.

Process it in strips of rows, label islands in each strip, and merge labels across strip boundaries with a Union-Find over the labels on the boundary row. **Cost:** O(m * n) time overall and O(width + labels on the boundary row) memory per strip.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
DIRS = ((1, 0), (-1, 0), (0, 1), (0, -1))


def neighbors(r, c, rows, cols):
    # the cells beside (r, c) that are inside the grid
    for dr, dc in DIRS:
        nr, nc = r + dr, c + dc
        if 0 <= nr < rows and 0 <= nc < cols:
            yield nr, nc


def flood(grid, start, seen):
    # visit all land joined to start; return the count
    rows, cols = len(grid), len(grid[0])
    seen.add(start)
    stack, size = [start], 0
    # a stack instead of recursion: no recursion limit
    while stack:
        r, c = stack.pop()
        size += 1
        for nb in neighbors(r, c, rows, cols):
            if grid[nb[0]][nb[1]] == 1 and nb not in seen:
                seen.add(nb)
                stack.append(nb)
    return size


def island_sizes(grid):
    if not grid:
        return []
    seen, sizes = set(), []
    for r in range(len(grid)):
        for c in range(len(grid[0])):
            # an island starts at land not visited yet
            if grid[r][c] == 1 and (r, c) not in seen:
                sizes.append(flood(grid, (r, c), seen))
    return sizes


# BASE QUESTION (optimal): Iterative DFS flood fill
def num_islands(grid):
    # one entry per island
    return len(island_sizes(grid))
```

```
# FOLLOW-UP 3: Find the area of the largest island.
def largest_island(grid):
    # follow-up: the area of the biggest island
    return max(island_sizes(grid), default=0)


# VARIANT: land cells arrive one at a time
class IslandCounter:
    """Follow-up: land cells arrive one at a time."""

    def __init__(self, rows, cols):
        self.rows, self.cols = rows, cols
        # land cell -> parent cell (union-find)
        self.parent = {}
        self.count = 0

    def find(self, x):
        # path halving keeps the trees flat
        while self.parent[x] != x:
            self.parent[x] = self.parent[self.parent[x]]
            x = self.parent[x]
        return x

    def add_land(self, r, c):
        # adding the same cell twice changes nothing
        if (r, c) in self.parent:
            return self.count
        self.parent[(r, c)] = (r, c)
        self.count += 1
        # join with every land neighbour
        for nb in neighbors(r, c, self.rows, self.cols):
            if nb in self.parent:
                a, b = self.find((r, c)), self.find(nb)
                if a != b:
                    self.parent[a] = b
                    # two islands merged into one
                    self.count -= 1
        return self.count


if __name__ == "__main__":
    g = [[1, 1, 0, 0], [1, 1, 0, 0],
         [0, 0, 1, 1], [0, 0, 1, 1]]
    assert num_islands(g) == 2
    assert largest_island(g) == 4
```

```
    assert num_islands([]) == 0
    # streaming adds: counts stay 1, 1, 1
    ic = IslandCounter(2, 2)
    adds = [(0, 0), (0, 1), (1, 1)]
    counts = [ic.add_land(r, c) for r, c in adds]
    assert counts == [1, 1, 1]
    # two separate cells make two islands
    ic = IslandCounter(3, 3)
    assert ic.add_land(0, 0) == 1
    assert ic.add_land(2, 2) == 2
    assert ic.add_land(1, 1) == 3
```

NOTES FROM CANDIDATES

For streaming, Union-Find with path compression is the natural choice — each addLand is amortized alpha(n).
In one onsite, the follow-up arrived after a working BFS solution and explicitly required a Union-Find rewrite; retrofitting the original traversal consumed the remaining time.
Common edge cases: diagonal connectivity (some prompts use 8-connectivity), grid with no land.

PREPARATION

Write both the static count and the streaming addLand version from memory in under 15 min total.
Be ready to switch between DFS / BFS / Union-Find on demand.

STUDY HERE: topic 6, Grids and Simulation

Also fits: Graphs and Search (listed there as SKIP, no pages). Site tags: grid, bfs, medium

MEDIUM | IN APP LC 994 | 1Point3Acres | onsite-coding, phone-screen | 5 of 7

Rotten Oranges / Multi-Source BFS (taxis)

ASKED 2026-09-08 | 42 DAYS AGO | LAST 90 DAYS

STUDY: TYPE | ALL TIME 51.2 | 30 DAYS 0 | PRIORITY 67/228

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: written and tested here for this exact question

This question has several parts, so each part has its own answer below.

Also in your app: LeetCode #994 Rotting Oranges

LeetCode match: LC 994 Rotting Oranges

Frequency: Low | Last asked: 2026-09-08 | Roles: SWE, MLE

Original: https://www.1point3acres.com/interview/problems/company/google/rotten-oranges-multi-source-bfs-taxis

QUESTION

EXAMPLES

```
Grid [[2,1,1],[1,1,0],[0,1,1]] (rotting-oranges
    variant): return number of minutes until all
    reachable 1s become 2 (4).
```

Taxi variant: for each empty cell, distance to nearest taxi.

APPROACH

Drill multi-source BFS from memory in under 10 min.
Prep a 2-minute pitch on incremental-vs-rebuild trade-off for the moving-source follow-up.
Practice the rotting-oranges / walls-and-gates / 01-matrix triplet — all share the multi-source BFS skeleton.

HOW TO THINK ABOUT IT

'Spread outward from several starting points at the same time and count the rounds' is multi-source BFS: put every source in the queue before you start, and process the queue one round at a time. Rounds are minutes. Always count the fresh ones first so that unreachable oranges are detected at the end.

Basis: LeetCode 994, Rotting Oranges, and the same multi-source BFS skeleton as LeetCode 542 and 286.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

BRUTE FORCE

```
def brute(grid):
    minutes = 0
    while True:
        fresh = fresh_next_to_rotten(grid)
        if not fresh:
            break
        for r, c in fresh:
            grid[r][c] = 2
        minutes += 1
    return -1 if any_fresh(grid) else minutes
```

TIME	SPACE
O(minutes * m * n)	O(m * n)

WHY IT IS SLOW

Each minute scans the entire grid, O(minutes * m * n). A queue of the newly rotten oranges touches each cell only once, O(m * n).

OPTIMAL SOLUTION · Multi-source BFS by minute

TIME	SPACE
O(mn)	O(mn)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

OPTIMAL SOLUTION · Taxi variant: distance from every empty cell to the nearest taxi

TIME	SPACE
O(mn)	O(mn)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Sources move or new taxis appear. How do you keep the distances fresh?

Adding a source is cheap: push it at distance 0 and run a BFS that only continues into cells where it beats the stored distance (a decrease-only update, amortized small). Removing or moving a source is hard because distances can increase; either rebuild from scratch with a multi-source BFS, or rebuild periodically and accept bounded staleness in between.

FOLLOW-UP 2 Why is multi-source BFS the same cost as single-source BFS?

A virtual super-source connected to all sources by zero-length edges turns the problem into one BFS. Each cell enters the queue once, so it is O(mn) no matter how many sources exist.

FOLLOW-UP 3 Signal variant: a signal spreads from sources, how long until every target gets it?

Run the BFS and take the maximum distance over the target cells. If any target is unreachable the answer is infeasible (-1); with no targets it is 0. To allow destroying at most one blocker, compute distances from the sources and also from the targets and test each blocker cell as a bridge.

FOLLOW-UP 4 A signal spreads from sources to targets: how long until every target is reached?

One multi-source BFS from the sources, then the answer is the largest distance over the targets (-1 if any target is unreachable, 0 if there are no targets). Per-source BFS would cost O(mn * sources).

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


def multi_source_bfs(rows, cols, sources, open_cell):
    # distance from the nearest source to every cell
    dist = {s: 0 for s in sources}
    queue = deque(sources)
    while queue:
        r, c = queue.popleft()
        for nr, nc in ((r + 1, c), (r - 1, c),
                       (r, c + 1), (r, c - 1)):
            inside = 0 <= nr < rows and 0 <= nc < cols
            if inside and (nr, nc) not in dist:
                if open_cell(nr, nc):
                    dist[(nr, nc)] = dist[(r, c)] + 1
                    queue.append((nr, nc))
    return dist


# BASE QUESTION (optimal): Multi-source BFS by minute
def rotting_minutes(grid):
    rows, cols = len(grid), len(grid[0])
    cells = [(r, c) for r in range(rows)
             for c in range(cols)]
    rotten = [x for x in cells if grid[x[0]][x[1]] == 2]
    fresh = [x for x in cells if grid[x[0]][x[1]] == 1]
    # rot spreads through any non-empty cell
    dist = multi_source_bfs(
        rows, cols, rotten, lambda r, c: grid[r][c] != 0)
    # a fresh orange that is never reached means -1
    if any(x not in dist for x in fresh):
        return -1
    return max((dist[x] for x in fresh), default=0)


# TAXI VARIANT: distance to the nearest taxi
def nearest_taxi(grid):
    # 'T' = taxi, '.' = empty, '#' = blocked
    rows, cols = len(grid), len(grid[0])
    taxis = [(r, c) for r in range(rows)
             for c in range(cols) if grid[r][c] == "T"]
    dist = multi_source_bfs(
        rows, cols, taxis, lambda r, c: grid[r][c] != "#")
    # None where no taxi can reach the cell
    return [[dist.get((r, c)) for c in range(cols)]
            for r in range(rows)]


# FOLLOW-UP 4: A signal spreads from sources to targets:
# how long until every target ...
def signal_time(rows, cols, sources, targets, blocked=()):
    # how long until every target hears the signal?
    dist = multi_source_bfs(
        rows, cols, list(sources),
        lambda r, c: (r, c) not in blocked)
    if any(t not in dist for t in targets):
        return -1
    # no targets means no waiting
    return max((dist[t] for t in targets), default=0)


if __name__ == "__main__":
    assert rotting_minutes([[2, 1, 1], [1, 1, 0],
                            [0, 1, 1]]) == 4
    # a fresh orange walled off by an empty cell
    assert rotting_minutes([[2, 0, 1]]) == -1
    assert rotting_minutes([[0, 2]]) == 0
    assert nearest_taxi(["T.#", "..."]) == [
        [0, 1, None], [1, 2, 3]]
    # signal from two sources to two targets
    assert signal_time(1, 5, [(0, 0), (0, 4)],
                       [(0, 1), (0, 2)]) == 2
    assert signal_time(1, 3, [(0, 0)], [(0, 2)],
                       blocked={(0, 1)}) == -1
    assert signal_time(1, 3, [(0, 0)], []) == 0
```

NOTES FROM CANDIDATES

BFS from all sources simultaneously is O(mn); per-source BFS is O(mn × #sources).
The moving-source follow-up trades exactness for amortized cost — common answer is periodic rebuild with bounded staleness.
For the signal variant, use the maximum source-distance over targets as the completion time; an unreachable target makes that candidate infeasible. Agree that no targets requires zero time. A correct baseline for destroying at most one blocker is to run multi-source BFS with no deletion, then once with each blocker made traversable, restoring it before the next trial. Minimize the completion time across feasible trials; return -1 if none is feasible. With B blockers on an R by C grid, this takes O((B + 1) * R * C) time and O(R * C) reusable auxiliary space. A BFS state that allows each path to break its own blocker does not enforce one shared destroyed blocker for all targets.

PREPARATION

Drill multi-source BFS from memory in under 10 min.
Prep a 2-minute pitch on incremental-vs-rebuild trade-off for the moving-source follow-up.
Practice the rotting-oranges / walls-and-gates / 01-matrix triplet — all share the multi-source BFS skeleton.

STUDY HERE: topic 6, Grids and Simulation

Also fits: Greedy and Math (listed there as SKIP, no pages). Site tags: simulation, algorithm, medium

MEDIUM | 1Point3Acres | onsite-coding | 6 of 7

Gate Entry / Exit Time Resolution with Tie-Break Rules

ASKED 2026-05-04 | 169 DAYS AGO | LAST 6 MONTHS

STUDY: TALK | ALL TIME 27.4 | 30 DAYS 0 | PRIORITY 131/228

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: written and tested here for this exact question

LeetCode match: LC 2534 Time Taken to Cross the Door

Frequency: Single report | Last asked: 2026-05-04 | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/gate-entry-exit-scheduler

QUESTION

Onsite coding round 2: given an array indexed by person id, each containing **`(timestamp, action in {enter, exit})`**, return per-person the actual time they passed through the gate after applying tie-break rules between simultaneous enters and exits.SWEsimulationalgorithmmediumFrequencySingle reportLast asked2026-05-04Stageonsite-coding

APPROACH

Translate the four priority rules into an explicit state machine (prev_state in {enter, exit, none}) before writing any code.
Practice scheduling problems that pair a per-tick simulation with an event-driven optimization (CPU scheduler, traffic light, calendar conflict resolver).
Stress-test corner cases: same timestamp containing both an enter and an exit for the same person, all-enters or all-exits batches, and very large gaps between two events.

INTERVIEW-DAY PLAN

CLARIFY FIRST

Ask for the exact tie-break rules in the four cases (previous second unused, entered, exited, and which wins), whether one person passes per second, and how ties between equal arrival times break (by id).

BRUTE FORCE TO SAY OUT LOUD

Simulate every second between the first and last timestamp. Works, but its cost grows with the size of the timestamps.

OPTIMAL IDEA

Sort people by (time, id) and keep two queues. At each step apply the previous-state rule to choose a queue. When both queues are empty jump to the next arrival time and reset the previous state to idle if at least one second was skipped. Linear after the sort.

DRY-RUN THESE CASES

Same-time enter and exit, an idle gap of exactly one second and of many seconds, all enters, all exits.

LIKELY FOLLOW-UPS

Several gates, priority classes, or answering online.

PITFALLS

Forgetting to reset the state across an idle gap. Letting the clock go backward.

HOW TO THINK ABOUT IT

Write the rule as a small state machine first: the state is what the gate did in the previous second (entered, exited or idle), and the rule picks who goes next from that state. Then replace the second-by-second loop with a loop over people: when nobody is waiting jump the clock forward, and remember that an idle gap resets the state to idle.

Basis: LeetCode 2534, Time Taken to Cross the Door. Assumption: one person passes per second; if an enter and an exit compete, the door's previous-second use decides (enter if it was an enter, otherwise exit, and exit if the door was idle).

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
def brute(arrivals):
    t, prev = 0, None
    enter_q, exit_q = deque(), deque()
    while pending(arrivals, enter_q, exit_q):
        add_arrivals(t, arrivals, enter_q,
                     exit_q)
        queue = choose(prev, enter_q, exit_q)
        if queue:
            person = queue.popleft()
            passed[person] = t
            prev = name_of(queue)
        t += 1
    return passed
```

TIME	SPACE
O(T + n)	O(n)
where T is the last timestamp	

WHY IT IS SLOW

It runs through every second between the first and last timestamp, so a timestamp of 10^9 means a billion iterations. Jumping to the next arrival when the queues are empty makes it O(n log n).

OPTIMAL SOLUTION · Event-driven simulation with two queues

TIME	SPACE
O(n log n)	O(n)
for the sort, O(n) simulation	

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Why does the optimization need care across an empty gap?

If the door sits idle for even one second the previous state becomes 'none', which favours exits again. Jumping time forward without resetting the state would wrongly keep 'enter' priority from before the gap. Compare t with last_used + 1 to know whether the gap really was idle.

FOLLOW-UP 2 What is the complexity, and what if events come online?

Offline it is O(n log n) for the sort, then O(n) for the simulation, independent of how large the timestamps are. Online, keep the two queues and the previous-state variable and advance the clock on every arrival or tick; the work per person stays O(1).

FOLLOW-UP 3 Timestamps go up to 10^9.

That is why the event-driven loop jumps to the next arrival: its running time is O(n log n) and does not depend on the size of the timestamps. Remember to reset the previous state to idle across a gap.

FOLLOW-UP 4 The tie-break when the gate was idle differs in this version of the question.

Keep the simulation and make the idle winner a parameter: only the line that picks the queue changes. With 'exit first' it equals the standard rule; with 'enter first' an enter and an exit arriving together swap places.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```
from collections import deque


# BASE QUESTION (optimal): Event-driven simulation with
# two queues
# FOLLOW-UP 4: The tie-break when the gate was idle
# differs in this version of the ...
def gate_pass_times(events, idle_first="exit"):
    # events[i] = (arrival time, "enter" or "exit")
    n = len(events)
    # people sorted by arrival, then by id
    order = sorted(range(n),
                   key=lambda i: (events[i][0], i))
    queues = {"enter": deque(), "exit": deque()}
    result = [0] * n
    t, i, prev, last_used = 0, 0, None, -10
    while i < n or queues["enter"] or queues["exit"]:
        if not queues["enter"] and not queues["exit"]:
            # nobody waits: jump the clock to the next
            # arrival
            t = max(t, events[order[i]][0])
            # a gap of idle time forgets the previous
            # action
            if t > last_used + 1:
                prev = None
        # everyone who arrived by now joins their line
        while i < n and events[order[i]][0] <= t:
            person = order[i]
            queues[events[person][1]].append(person)
            i += 1
        both = queues["enter"] and queues["exit"]
        if both:
            # FOLLOW-UP 4: idle tie-break set by
            # idle_first
            # tie: continue the direction used last second
            # (when idle, use idle_first)
            want = prev or idle_first
        else:
            want = "enter" if queues["enter"] else "exit"
        person = queues[want].popleft()
        result[person] = t
        prev, last_used = want, t
        t += 1
    return result
```

```
if __name__ == "__main__":
    # one enter and one exit arrive together: exit first
    ev = [(0, "enter"), (0, "exit")]
    assert gate_pass_times(ev) == [1, 0]
    # with "enter" winning the idle tie it swaps
    assert gate_pass_times(ev, "enter") == [0, 1]
    # the same direction continues while people keep
    # coming
    ev2 = [(0, "enter"), (0, "enter"), (1, "exit")]
    assert gate_pass_times(ev2) == [0, 1, 2]
    # a long idle gap resets the state
    ev3 = [(0, "enter"), (10, "enter"), (10, "exit")]
    assert gate_pass_times(ev3) == [0, 11, 10]
    # huge timestamps cost nothing extra
    far = [(10 ** 9, "enter"), (10 ** 9, "exit")]
    assert gate_pass_times(far) == [10 ** 9 + 1, 10 ** 9]
```

NOTES FROM CANDIDATES

The clean implementation uses two queues (pending enters, pending exits) plus a prev_state variable; at each tick peek both queues, apply the four rules, advance, and update prev_state.
A naive tick-by-tick simulation walks every integer time unit from min to max timestamp; the expected optimization is to jump directly to the next event timestamp in the input, dropping complexity to O(n).
The optimization has to carry the "prior moment" state across empty gaps correctly (a 100-tick gap still counts as prev_state = none).
Walk through one or two examples on the whiteboard before coding — interviewers in this family prefer candidates who fully verbalize the precedence rules before writing.

PREPARATION

Translate the four priority rules into an explicit state machine (prev_state in {enter, exit, none}) before writing any code.
Practice scheduling problems that pair a per-tick simulation with an event-driven optimization (CPU scheduler, traffic light, calendar conflict resolver).
Stress-test corner cases: same timestamp containing both an enter and an exit for the same person, all-enters or all-exits batches, and very large gaps between two events.

STUDY HERE: topic 6, Grids and Simulation

Also fits: Dynamic Programming (listed there as SKIP, no pages). Site tags: grid, dp, medium

MEDIUM | 1Point3Acres | onsite-coding | 7 of 7

Count Same-Color Squares in Matrix

STUDY: TYPE | **ALL TIME 51.2** | **30 DAYS 0** | **PRIORITY 68/228**

ABOUT THIS QUESTION

Topic: Grids and Simulation

Optimal answer from: written and tested here for this exact question

Related in your app (a neighbouring problem, not this exact question): LeetCode #221 Maximal Square

LeetCode match: LC 221 Maximal Square (related)

Frequency: Low | Roles: SWE

Original: https://www.1point3acres.com/interview/problems/company/google/count-same-color-squares

QUESTION

LeetCode 221 variant — count maximal same-color square sub-grids. DP on each cell as the bottom-right corner.

Input: m × n grid of colored cells.
Output: count of square sub-grids whose cells are all the same color (or maximum side length, depending on prompt).
DP: dp[i][j] = 1 + min(dp[i-1][j], dp[i][j-1], dp[i-1][j-1]) if grid[i][j] == grid[i-1][j] == grid[i][j-1] == grid[i-1][j-1] else 1.
Sum dp[i][j] across the grid for the count variant; max for the side variant.

EXAMPLES

The plain "count all-1 squares" DP generalizes to same-color directly.

APPROACH

Write the all-1-squares DP from memory in under 8 min. Generalize to multi-color in <2 min — only the equality check changes.

HOW TO THINK ABOUT IT

Let dp[i][j] be the side of the largest same-colour square whose bottom-right corner is (i, j). That square exists only if the three neighbours above, left and above-left have the same colour as the cell and can themselves carry a square, so dp is 1 plus the smallest of their dp values. Summing dp over all cells counts every square once (each cell contributes one square per side length up to dp).

Basis: LeetCode 221, Maximal Square, and LeetCode 1277, Count Square Submatrices with All Ones, generalised from 1s to any one colour.

BRUTE FORCE

BRUTE FORCE · PSEUDO-CODE

```
count = 0
for i, j in all_cells(grid):
    for k in range(1, min(m - i, n - j) + 1):
        cells = square(grid, i, j, k)
        if all(c == grid[i][j] for c in cells):
            count += 1
```

TIME	SPACE
O(m * n * min(m, n)^3)	O(1)

WHY IT IS SLOW

Re-checks the same cells again and again, O(m * n * min(m, n)^3). A dp on the bottom-right corner reuses the neighbours' results in O(m * n).

OPTIMAL SOLUTION · dp on the bottom-right corner

TIME	SPACE
O(m * n)	O(n)

Code: see FULL INTERVIEW CODE below (the optimal solution is its main function).

FOLLOW-UP 1 Return only the largest side instead of the count.

Keep the same dp and take the maximum instead of adding. The common bug is checking only the diagonal neighbour: the up and left neighbours must also match, otherwise a different colour can sit inside the square.

FULL INTERVIEW CODE · base question + every follow-up

One program for the whole question: the base answer and every follow-up above, built from small helper functions, with a comment above each step. Type it top to bottom in the interview; the demo at the bottom runs it.

```python
def square_sides(g):
    # side[i][j]: the biggest same-colour square whose
    # bottom-right corner is (i, j); one row at a time
    if not g:
        return []
    prev, out = [0] * len(g[0]), []
    for i, row in enumerate(g):
        cur = [1] * len(row)
        for j, c in enumerate(row):
            # all three neighbours must match this cell
            if i and j and g[i - 1][j] == c \
                    and g[i][j - 1] == c \
                    and g[i - 1][j - 1] == c:
                cur[j] = 1 + min(prev[j], cur[j - 1],
                                 prev[j - 1])
        out.append(cur)
        prev = cur
    return out


# BASE QUESTION (optimal): dp on the bottom-right corner
def count_same_color_squares(g):
```

```
    # every cell contributes one square per side up to its
    # side
    return sum(sum(row) for row in square_sides(g))


# FOLLOW-UP 1: Return only the largest side instead of the
# count.
def largest_side(g):
    # the variant that asks for the biggest square only
    return max((max(row) for row in square_sides(g)),
               default=0)


if __name__ == "__main__":
    # a 3 x 3 block of one colour: 9 + 4 + 1 squares
    block = ["RRR", "RRR", "RRR"]
    assert count_same_color_squares(block) == 14
    assert largest_side(block) == 3
    # a different colour inside blocks the bigger squares
    holes = ["RRR", "RGR", "RRR"]
    assert largest_side(holes) == 1
    assert count_same_color_squares(holes) == 9
    assert count_same_color_squares([]) == 0
```

```
    assert largest_side([]) == 0
```

NOTES FROM CANDIDATES

Variant reported in both intern VO and an additional NG round. Common bug: assuming all four corners equal is sufficient — need all three neighbors (top, left, top-left) to match the current cell.

PREPARATION

Write the all-1-squares DP from memory in under 8 min. Generalize to multi-color in <2 min — only the equality check changes.