Dynamic Programming

Topic 5 of 10

23 questions | skeleton and writing space only

Each question: the prompt, the function or class signature, and ruled lines to write your own solution.

1. Count Perfect Wake Numbers up to N

HARD | asked 2026-05-07 | dp, bit-manipulation

Examples: 196 -> perfect (digits 1,9,6 all distinct, no 0, 9 is not a valley) 23 -> perfect 12463 -> perfect (1<2, 2<4, 4>6? No, 4<6, 6>3 -- 6 is not a valley because its right neighbor 3 is smaller) 1546 -> not perfect (4 is adjacent to 5 and 6, both strictly larger) 320 -> not perfect (contains 0) 34321 -> not perfect (digit 3 repeats)

```
def is_perfect(n):
```

2. Tree Distance Sum (Re-root DP)

HARD | asked 2026-01-19 | tree, dp, dfs

Onsite coding round 1: given an undirected tree on N nodes, return for every node the sum of distances to all other nodes. Equivalent to LC 834. Input: undirected tree with N nodes and N-1 edges. Output: array ans where ans[u] is the sum of shortest-path distances from u to every other node. Examples: Edges: [[0,1],[0,2],[2,3],[2,4],[2,5]] ans: [8, 12, 6, 10, 10, 10]

```
def tree_distance_sums(n, edges):
```

3. Determine winner in stack-merging game

HARD | asked 2026-01-06 |

Overview: This question evaluates understanding of combinatorial game theory, impartial game analysis, state-space encoding, and efficient state-space search techniques.

```
def first_player_wins(stacks, cap, misere=False
  ):
```

4. Bounded Knapsack Variant

MEDIUM | asked 2026-10-16 | greedy, dp, quickselect, sorting

Each item type has a value and an available count; every item weighs 1. Given capacity W, maximize total value. DP or DFS + memo works at O(n·W), greedy by value after sorting is O(n log n), and the best answer uses quickselect for O(n). Input: for each item type, its value and the number of copies available. Every item has weight 1. Input: a maximum total weight W. Output: the maximum total value achievable without exceeding W.

```
def max_value_sorted(items, W):
```

5. Longest Non-Decreasing Subarray with One Replacement

MEDIUM | asked 2026-10-04 | array, dp, two-pointer

Find the maximum length of a contiguous non-decreasing subarray if at most one element may be changed to any value. Input: an integer array nums. You may change at most one element to any value. Return the maximum length of a contiguous subarray that is non-decreasing (nums[i] <= nums[i + 1] for every adjacent pair inside it) after the change.

```
def longest_with_one_change(a, strict=False):
```

6. Grid Path Count with Diagonal Moves and Checkpoints

MEDIUM | asked 2026-09-29 | dp, grid

Count paths in an n x m matrix from (n-1, 0) to (n-1, m-1) moving up-right, right, or down-right. Matrix of size n x m. Start at (n-1, 0), end at (n-1, m-1). Allowed moves from (r, c): up-right (r-1, c+1), right (r, c+1), down-right (r+1, c+1); stay inside the matrix. Return the total number of distinct paths from start to end. Since every move changes the column, each column can contain at most one visited checkpoint.

```
def count_paths(n, m, checkpoints=(), ordered=F
  alse):
```

7. Minimum-Cost Tree Disconnection

MEDIUM | asked 2026-09-09 | tree, dp

Examples: Negative-weight follow-up: A --(-1)--> B --(-1)--> C Minimum total cut cost: -2 Cutting both edges costs -2, even though cutting just the first edge already separates the root from the original leaf.

```
def disconnect_cost(n, edges):
```

8. Target Expressions from Ordered Digits

MEDIUM | asked 2026-08-13 | array, backtracking, dp, math

Examples: For digits [2, 3, 4] and target 14, valid outputs include: 2 * (3 + 4) 2 + 3 * 4

```
def expressions_for_target(digits, target):
```

9. Count Word Decompositions into Chemical Element Symbols

MEDIUM | asked 2026-07-14 | string, dp

Examples: Physics has four stated decompositions: P - H - Y - Si - C - S P - H - Y - Si - Cs P - H - Y - S - I - C - S P - H - Y - S - I - Cs The returned count is 4.

```
def count_decompositions(word, symbols=ELEMENTS
  , mod=None):
```

10. Fence Painting Minimum Operations (Gemini Team)

MEDIUM | asked 2026-04-27 | dp, recursion

Examples: n = 5, a = [2, 2, 1, 2, 1] Optimal: 1) Horizontal stroke at h=1 across [1..5] (covers row 1 across whole fence) 2) Horizontal stroke at h=2 across [1..2] 3) Vertical stroke at plank 4 (height 2 still missing row 2) Optimal answer: 3.

```
def paint(a, width=None):
```

11. Maximize sum without choosing adjacent elements

MEDIUM | asked 2026-01-06 |

Overview: This question evaluates a candidate's understanding of array-based optimization and dynamic programming concepts for computing a maximum sum under non-adjacent selection constraints.

```
def rob_line(nums):
```

12. Jump Game with Profit

MEDIUM | asked n/a | array, dp

Examples: Variant-dependent; the principal recurrence is the one above.

```
def max_profit_fast(arr, profit):
```

13. Count Same-Color Squares in Matrix

MEDIUM | asked n/a | grid, dp

LeetCode 221 variant -- count maximal same-color square sub-grids. DP on each cell as the bottom-right corner. Input: m x n grid of colored cells. Output: count of square sub-grids whose cells are all the same color (or maximum side length, depending on prompt). DP: dp[i][j] = 1 + min(dp[i-1][j], dp[i][j-1], dp[i-1][j-1]) if grid[i][j] == grid[i-1][j] == grid[i][j-1] == grid[i-1][j-1] else 1. Sum dp[i][j] across the grid for the count variant; max for the side variant.

```
def count_same_color_squares(g):
```

14. Russian Doll Envelopes

MEDIUM | asked n/a | array, dp, binary-search, sorting

LeetCode 354. Maximum chain of envelopes that strictly fit inside each other. Sort + LIS reduction. Input: list of (width, height) envelopes. Output: longest chain where each envelope strictly fits in the next. Trick: sort by width ascending, height descending (when widths tie); run LIS (Longest Increasing Subsequence) on heights. LIS with patience-sort gives O(n log n). Examples: [[5,4],[6,4],[6,7],[2,3]] -> 3.

```
def max_envelopes(envelopes):
```

15. Find the maximum subarray sum.

MEDIUM | asked n/a |

Given an array of integers nums, write a function maxSubarraySum to find the maximum sum of a contiguous subarray within the array and return that maximum sum. The subarray must be contiguous, meaning that the elements must appear consecutively in the original array. Examples Input: nums = [2, 3, -2, 4] Output: 7 Explanation: Maximum sum is 2 + 3 + (-2) + 4 = 7.

```
def max_subarray(nums):
```

16. Partition an array into two sub-arrays with equal sum.

MEDIUM | asked n/a |

Given an array of integers, determine if it can be partitioned into two subsets such that the sum of the elements in each subset is equal. A partition is considered valid if it divides the array into two subsets where both subsets have the same sum. Examples Input: [2, 4, 11, 5] Output: True Explanation: The array can be partitioned into two subsets [2, 4, 5] and [11] with equal sum.

```
def can_partition(nums):
```

17. Given n houses in a line with money in each, find the maximum amount a robber can steal, without stealing from two adjacent houses.

MEDIUM | asked n/a |

Given n houses in a line with money in each, find the maximum amount a robber can steal, without stealing from two adjacent houses.

```
def rob_line(nums):
```

18. Find the longest palindromic subsequence using dynamic programming.

MEDIUM | asked n/a |

Given a string s, determine the longest palindromic substring in s. A substring is considered a palindrome if it reads the same forward and backward. A substring is a contiguous sequence of characters within a string. The longest palindromic substring is the substring with the maximum length that satisfies this condition. Examples Input: "abacc" Output: "aba" Explanation: "aba" is longer than "cc"

```
def lps_length(s):
```

19. Count the number of ways to split a string.

MEDIUM | asked n/a |

Count the number of ways to split a string.

```
def ways_to_split(s, parts=3, mod=MOD):
```

20. Reverse Coin Change

MEDIUM | asked n/a |

In standard coin change, given a coins array, we build dp where dp[i] = number of ways to make amount i. Reverse problem: given a dp array, find the original coins array that produced it.

```
def coins_from_dp(dp):
```

21. Maximum Profit

EASY | asked n/a |

You and your friend have decided to start an international trading business. You want to earn a profit through some ol' fashioned arbitrage: You'll buy widgets in one country and sell them in another at a higher price. Your friend has already found the current market prices for widgets in cities around the world, and you'd like to use this data to pick which cities to buy and sell widgets in.

```
def max_profit_prices(prices):
```

22. Climbing Stairs

EASY | asked n/a |

Given an integer n, representing the number of steps in a staircase, write a function climbStairs that returns the number of distinct ways to climb to the top of the staircase. Each time you can either climb 1 step or 2 steps. You may assume that n is a non-negative integer. Examples Input: n = 1 Output: 1 Explanation: There is only 1 way to climb a staircase with 1 step. Input: n = 2 Output: 2 Explanation: There are 2 ways to climb a staircase with 2 steps: 1.

```
def climb(n):
```

23. Fibonacci Numbers

EASY | asked n/a |

Write a function fib(n) that returns the nth Fibonacci number. The Fibonacci sequence is defined as F(n) = F(n-1) + F(n-2) with F(0) = 1 and F(1) = 1, which produces the following pattern: 1, 1, 2, 3, 5, 8, 13 ... Examples Pythonfib(0) # => 1 fib(1) # => 1 fib(2) # => 2 fib(3) # => 3 ... In this first version, we recursively call the fib function twice, and then we call it twice more in every subsequent recursive call, so the total number of operations expands to O(2^n)!

```
def fib(n):
```