LeetCode Practice

24 Hard: Heap

Question, examples, then the six-phase interview approach with the brute force in phase 2

A split copy of the full All Questions book; every feature and link works the same

24
HARD

Patterns (in order)

1. Heap (24)

How to use

- Tap any title in the Contents to jump to it. A topic name opens that topic's own divider page.
- Every page has < Prev | Contents | Next > at the top.
- Prev and Next move one question at a time; Contents returns here. Each topic starts on its own page.
- Select code and press Cmd/Ctrl+C to copy it.

Go to Contents >

Contents

24 questions | tap a title to jump to it

Hard questions (24) Go >

Heap (24) Go >

H 1. Merge k Sorted Lists LC 23
H 2. The Skyline Problem LC 218
H 3. Closest Binary Search Tree Value II LC 272
H 4. Find Median from Data Stream LC 295
H 5. Reconstruct Itinerary LC 332
H 6. Rearrange String k Distance Apart LC 358
H 7. Sliding Window Median LC 480
H 8. The Maze III LC 499
H 9. IPO LC 502
H 10. Smallest Range Covering Elements from K Lists LC 632
H 11. Employee Free Time LC 759
H 12. Swim in Rising Water LC 778
H 13. Minimum Cost to Hire K Workers LC 857
H 14. Shortest Subarray with Sum at Least K LC 862
H 15. Minimum Number of Refueling Stops LC 871
H 16. Optimize Water Distribution in a Village LC 1168
H 17. Minimum Cost to Make at Least One Valid Path in a Grid LC 1368
H 18. Maximum Performance of a Team LC 1383
H 19. Constrained Subsequence Sum LC 1425
H 20. Max Value of Equation LC 1499
H 21. Minimum Interval to Include Each Query LC 1851
H 22. Minimum Weighted Subgraph With the Required Paths LC 2203
H 23. Minimum Obstacle Removal to Reach Corner LC 2290
H 24. Meeting Rooms III LC 2402

Hard questions (24)

HARD | TOPIC 1 OF 1

Heap

24 Hard questions start on the next page

Before this: this is the first topic
After this: this is the last topic

IN THIS TOPIC

1. Merge k Sorted Lists LC 23
2. The Skyline Problem LC 218
3. Closest Binary Search Tree Value II LC 272
4. Find Median from Data Stream LC 295
5. Reconstruct Itinerary LC 332
6. Rearrange String k Distance Apart LC 358
7. Sliding Window Median LC 480
8. The Maze III LC 499
9. IPO LC 502
10. Smallest Range Covering Elements from K Lists LC 632
11. Employee Free Time LC 759
12. Swim in Rising Water LC 778
13. Minimum Cost to Hire K Workers LC 857
14. Shortest Subarray with Sum at Least K LC 862
15. Minimum Number of Refueling Stops LC 871
16. Optimize Water Distribution in a Village LC 1168
17. Minimum Cost to Make at Least One Valid Path in a Grid LC 1368
18. Maximum Performance of a Team LC 1383
19. Constrained Subsequence Sum LC 1425
20. Max Value of Equation LC 1499
21. Minimum Interval to Include Each Query LC 1851
22. Minimum Weighted Subgraph With the Required Paths LC 2203
23. Minimum Obstacle Removal to Reach Corner LC 2290
24. Meeting Rooms III LC 2402

HARD | Heap | LeetCode #23 | 1 of 24 | 1/24

Merge k Sorted Lists

QUESTION

You are given an array of k linked-lists lists, each linked-list is sorted in ascending order.

Merge all the linked-lists into one sorted linked-list and return it.

Example 1

Input	`lists = [[1,4,5],[1,3,4],[2,6]]`
Output	`[1,1,2,3,4,4,5,6]`
Explanation	*The linked-lists are:* *[* *1->4->5,* *1->3->4,* *2->6* *]* *merging them into one sorted linked list:* *1->1->2->3->4->4->5->6*

Example 2

Input	`lists = []`
Output	`[]`

Example 3

Input	`lists = [[]]`
Output	`[]`

CONSTRAINTS

- k == lists.length
- 0 <= k <= 10^4
- 0 <= lists[i].length <= 500
- 10^4 <= lists[i][j] <= 10^4
- lists[i] is sorted in ascending order.
- The sum of lists[i].length will not exceed 10^4.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Given k sorted linked lists, merge them into one sorted linked list. Right?"

"A few quick questions:

k can be 0 (empty input)? Yes — return None. Lists can be empty? Yes."

"Let me walk: lists=[[1,4,5],[1,3,4],[2,6]] -> [1,1,2,3,4,4,5,6] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
values = every value from every list
sort the values and build a new list from them
```

TIME	SPACE
O(N log N)	O(N)

WHY IT IS SLOW

O(N log N) time and O(N) memory, ignoring that each list is already sorted. A min-heap of the k current heads gives O(N log k).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is building all values then sorting — we discard the sorted structure.

Min-heap of (value, list_index, node): always extract the globally smallest node.

Push each list's head. Pop min, add to result, push its next.

Time: O(n log k): n nodes, heap of size k for log k per pop/push.

Space: O(k) heap + O(n) output."

Key insight: the min-heap preserves the sorted order across all k lists — each node is pushed and popped exactly once for O(n log k) total.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _23_MergeKSortedLists:
    def mergeKLists(self, lists):
        heap = []
        for i, node in enumerate(lists):
            if node:
                heapq.heappush(heap, (node.val, i, node))
        dummy = cur = ListNode(0)
        while heap:
            val, i, node = heapq.heappop(heap)
            cur.next = node; cur = cur.next
            if node.next:
                heapq.heappush(heap, (node.next.val, i, no
de.next))
        return dummy.next
```

PHASE 5 TEST & DEBUG

"Let me trace mergeKLists([[1,4,5],[1,3,4],[2,6]])."

Min-heap of (val, list_id, node). Initial: [(1,0,node1),(1,1,node1),(2,2,node2)].

Pop (1,0,node(1)): curr.next=node(1). Push (4,0,node(4)). heap:[(1,1,node(1)),(4,0),(2,2)].

PHASE 5 TEST & DEBUG

Pop (1,1,node(1)): curr.next=node(1). Push (3,1,node(3)). heap:[(2,2),(3,1),(4,0)].

Pop (2,2,node(2)): curr.next=node(2). Push (6,2,node(6)).

Pop (3,1): Push (4,1). Pop (4,0): Push (5,0). Pop (4,1). Pop (5,0). Pop (6,2).

Result: 1->1->2->3->4->4->5->6 ok

WHY min-heap: each pop gives the globally smallest node across all k lists in O(log k) — heap size stays k so it never grows with n.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log k)	**O(k)**
each of n nodes pushed/popped, heap stays at size k	heap — far better than O(n) from the brute sort

Divide-and-conquer: pair lists and merge pairs repeatedly — also O(n log k).

Follow-up: k=2 reduces to LC 21 Merge Two Sorted Lists.

Follow-up: merge k sorted ARRAYS — same heap approach with (val, list_idx, elem_idx).

HARD | Heap | LeetCode #218 | 2 of 24 | 2/24

The Skyline Problem

QUESTION

A city's skyline is the outer contour of the silhouette formed by all the buildings in that city when viewed from a distance. Given the locations and heights of all the buildings, return the skyline formed by these buildings collectively.

The geometric information of each building is given in the array buildings where buildings[i] = [$left_i$, $right_i$, $height_i$]:

CONSTRAINTS

- $left_i$ is the x coordinate of the left edge of the ith building.
- $right_i$ is the x coordinate of the right edge of the ith building.
- $height_i$ is the height of the ith building.


You may assume all buildings are perfect rectangles grounded on an absolutely flat surface at height 0.

The skyline should be represented as a list of "key points" sorted by their x-coordinate in the form [[x_1,y_1],[x_2,y_2],...]. Each key point is the left endpoint of some horizontal segment in the skyline except the last point in the list, which always has a y-coordinate 0 and is used to mark the skyline's termination where the rightmost building ends. Any ground between the leftmost and rightmost buildings should be part of the skyline's contour.

Note: There must be no consecutive horizontal lines of equal height in the output skyline. For instance, [...,[2^3],[4^5],[7^5],[11^5],[12^7],...] is not acceptable; the three lines of height 5 should be merged into one in the final output as such: [...,[2^3],[4^5],[12^7],...]

Example 1

Input	`buildings = [[2,9,10],[3,7,15],[5,12,12],[15,20,10],[19,24,8]]`
Output	`[[2,10],[3,15],[7,12],[12,0],[15,10],[20,8],[24,0]]`
Explanation	*Figure A shows the buildings of the input. Figure B shows the skyline formed by those buildings. The red points in figure B represent the key points in the output list.*



Example 2

Input	`buildings = [[0,2,3],[2,5,3]]`
Output	`[[0,3],[5,0]]`

- 1 <= buildings.length <= 10^4

QUESTION

- 0 <= $left_i$ < $right_i$ <= 2^{31} - 1
- 1 <= $height_i$ <= 2^{31} - 1
- buildings is sorted by $left_i$ in non-decreasing order.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Given buildings as [left, right, height], output the skyline as [x, height] points

marking where the maximum height changes. Last point always at height 0. Right?"

"A few quick questions:

Can buildings overlap completely or partially? Yes — both cases are valid.

Consecutive same-height segments should be merged? Yes."

"Let me walk:
buildings=[[2,9,10],[3,7,15],[5,12,12],[15,20,10],[19,24,8]].

-> [[2,10],[3,15],[7,12],[12,0],[15,10],[20,8],[24,0]] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
xs = all building edges, sorted
for x in xes:
    height = the largest height among buildings
        with left <= x < right
output [x, height] whenever the height changes
```

TIME	SPACE
O(n^2)	O(n)

WHY IT IS SLOW

Scans every building for every edge. A sweep over sorted edges with a max-heap of active heights (lazy deletion) is O(n log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is iterating over potentially billions of x-coordinates.

Event-based sweep with a max-heap:

Events: building start -> add (-height, right) to heap; building end -> lazy-delete.

At each event x: remove expired buildings from heap top, check new max height.

Record x if height changes.

Time: O(n log n). Space: O(n)."

PHASE 3 OPTIMIZE

Key insight: a lazy-deletion max-heap processes only the unique x-coordinates of building edges — expired buildings are removed from the heap top on demand, not eagerly.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _218_SkylineProblem:
    def getSkyline(self, buildings):
        events = []
        for left, right, h in buildings:
            events.append((left, -h, right))
            events.append((right, 0, 0))
        events.sort()
        result = []
        heap = [(0, float('inf'))]
        prev_max = 0
        for x, neg_h, right in events:
            if neg_h != 0:
                heapq.heappush(heap, (neg_h, right))
            while heap[0][1] <= x:
                heapq.heappop(heap)
            curr_max = -heap[0][0]
            if curr_max != prev_max:
                result.append([x, curr_max])
                prev_max = curr_max
        return result
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

buildings=[[2,9,10],[3,7,15],[5,12,12],[15,20,10],[19,24,8]]:

x=2: push(-10,9). top=(-10,9). h=10->record[2,10].

x=3: push(-15,7). top=(-15,7). h=15->record[3,15].

x=7: evict expired: pop(-15,7). top=(-12,12)? No push yet. top=(-10,9). h=12 not yet.

... builds up to correct output ok

Lazy deletion (check expiry only when needed) handles overlapping buildings

WHY sorted-event max-heap: when a building's right edge fires, lazy-remove its height; the new heap max IS the new skyline peak — O(n log n).

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log n)	**O(n)**
n events, each heap op O(log n)	heap

Follow-up: streaming buildings — same sweep, process events as they arrive.

Follow-up: 3D skyline — project to 2D slices, solve per slice.

HARD | Heap | LeetCode #272 | 3 of 24 | 3/24

Closest Binary Search Tree Value II


QUESTION

Given the root of a binary search tree, a target value, and an integer k, return the k values in the BST that are closest to the target. You may return the answer in any order.

You are guaranteed to have only one unique set of k values in the BST that are closest to the target.

Example 1

Input	`root = [4,2,5,1,3], target = 3.714286, k = 2`
Output	`[4,3]`



Example 2

Input	`root = [1], target = 0.000000, k = 1`
Output	`[1]`

CONSTRAINTS

- The number of nodes in the tree is n.
- $1 <= k <= n <= 10^4$.
- $0 <= Node.val <= 10^9$
- $10^9 <= target <= 10^9$
- Follow up: Assume that the BST is balanced. Could you solve it in less than O(n) runtime (where n = total nodes)?

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Given a BST root, a target (float), and integer k, return the k values

in the BST that are closest to target. Return in any order. Right?"

"A few quick questions:

Guaranteed unique answer (no ambiguity in which k to pick)? Yes.

Tree can be empty? No — at least k nodes exist."

"Let me walk: root=[4,2,5,1,3], target=3.714, k=2 -> [4,3] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
collect every value in a list
sort the list by distance to the target
return the first k
```

TIME	SPACE
O(n log n)	O(n)

WHY IT IS SLOW

Sorts all n values to keep k. In-order traversal gives sorted values, so a sliding window of k (drop the farther end) is O(n); two stacks of predecessors and successors give O(h + k).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the full traversal + sort.

Two-iterator approach using BST inorder stacks — O(log n + k) time, O(log n) space:

lo_stack: ascending iterator (values <= target, largest first from stack).

hi_stack: descending iterator (values > target, smallest first from stack).

Pick the k closest values by comparing lo_stack.top and hi_stack.top each step.

Time: O(log n + k). Space: O(log n) for the two stacks."

Key insight: two lazy BST inorder iterators (one ascending, one descending) converge from opposite ends, examining at most O(log n + k) nodes instead of materialising the full traversal.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
class _272_ClosestBSTValueII:
    def closestKValues(self, root, target, k):
        def push_left_up_to(node, stack):
            while node:
                stack.append(node)
                if node.val <= target: node = node.right
                else: node = node.left

        def push_right_up_to(node, stack):
            while node:
                stack.append(node)
                if node.val > target: node = node.left
                else: node = node.right

        def next_lo(stack):
            node = stack.pop()
            push_left_up_to(node.left, stack)
            return node.val

        def next_hi(stack):
            node = stack.pop()
```

```
            push_right_up_to(node.right, stack)
            return node.val

        lo, hi = [], []
        push_left_up_to(root, lo)
        push_right_up_to(root, hi)
        result = []
        while len(result) < k:
            use_lo = lo and (not hi or target - lo[-1].val
<= hi[-1].val - target)
            if use_lo: result.append(next_lo(lo))
            elif hi: result.append(next_hi(hi))
        return result
```

PHASE 5 TEST & DEBUG

"Let me trace closest k values to target in BST [4,2,5,1,3], target=3.7, k=2."

In-order traversal gives sorted values: [1,2,3,4,5].

Use a deque of size k: slide through sorted values.

Add 1: deque=[1]. Add 2: deque=[1,2]. Add 3: deque=[1,2,3]. Size>k=2? Not yet (k=2, size=3>2).

Wait, maintain size k: when adding 4: |4-3.7|=0.3 < |1-3.7|=2.7 -> remove 1, add 4. deque=[2,3,4].

Adding 5: |5-3.7|=1.3 > |2-3.7|=1.7? 1.3 < 1.7 -> remove 2, add 5. deque=[3,4,5].

Wait: |3-3.7|=0.7. Stop when new element is farther than the one we'd remove.

Final: deque=[3,4] ok (two closest to 3.7). WHY sorted in-order + sliding window: O(n) vs O(n log k) heap.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(log n + k)	**O(log n)**
O(log n) to build both stacks, O(k) to select k values	stacks hold one root-to-leaf path each

Follow-up: Closest BST Value I (#270) — return 1 closest; simple tree walk O(log n).

Follow-up: if tree is unbalanced, worst case degrades to O(n).

HARD | Heap | LeetCode #295 | 4 of 24 | 4/24

Find Median from Data Stream

QUESTION

The median is the middle value in an ordered integer list. If the size of the list is even, there is no middle value, and the median is the mean of the two middle values.

CONSTRAINTS

- For example, for arr = [2,3,4], the median is 3.
- For example, for arr = [2,3], the median is (2 + 3) / 2 = 2.5.

Implement the MedianFinder class:

- MedianFinder() initializes the MedianFinder object.
- void addNum(int num) adds the integer num from the data stream to the data structure.
- double findMedian() returns the median of all elements so far. Answers within 10^{-5} of the actual answer will be accepted.
- 10^5 <= num <= 10^5
- There will be at least one element in the data structure before calling findMedian.
- At most 5 * 10^4 calls will be made to addNum and findMedian.
- Follow up:
- If all integer numbers from the stream are in the range [0, 100], how would you optimize your solution?
- If 99% of all integer numbers from the stream are in the range [0, 100], how would you optimize your solution?

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Design addNum(int) and findMedian()->double. Median of a growing stream. Right?"

"A few quick questions:

For even total elements, median = average of two middle values? Yes.

addNum can be called up to 5*10^4 times — both ops need to be fast."

"Let me walk: addNum(1),addNum(2),findMedian()->1.5. addNum(3),findMedian()->2.0 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
keep all values in a sorted list
def addNum(x):
    insert x at its sorted position (binary search)
def findMedian():
    read the middle one or two
```

PHASE 2 BRUTE FORCE

TIME	SPACE
O(n) per add, O(1) per median	O(n)

WHY IT IS SLOW

Inserting into an array shifts up to n elements. A max-heap for the lower half and a min-heap for the upper half (kept within one element of each other) gives O(log n) add and O(1) median.

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the O(n) insert for the sorted list.

Two heaps — max-heap for lower half, min-heap for upper half:

`max_heap.top() <= min_heap.top() always.`

Sizes differ by at most 1.

addNum: push to max_heap (negated), rebalance.

findMedian: if equal sizes -> average of tops; else -> top of larger heap.

Time: O(log n) addNum, O(1) findMedian. Space: O(n)."

Key insight: two heaps partition numbers into lower and upper halves — the max-heap top and min-heap top are always the two median candidates, rebalanced in O(log n) after each insertion.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
class _295_FindMedianFromDataStream:
    def __init__(self):
        self._lo = []
        self._hi = []

    def addNum(self, num):
        heapq.heappush(self._lo, -num)
        heapq.heappush(self._hi, -heapq.heappop(self._lo))
        if len(self._hi) > len(self._lo):
            heapq.heappush(self._lo, -heapq.heappop(self._
hi))

    def findMedian(self):
        if len(self._lo) > len(self._hi):
            return float(-self._lo[0])
        return (-self._lo[0] + self._hi[0]) / 2.0
```

PHASE 5 TEST & DEBUG

"Let me trace MedianFinder with addNum(1),addNum(2),findMedian(),addNum(3),findMedian()."

Two heaps: max_heap (left half), min_heap (right half). left>=right by 0 or 1.

addNum(1): push to max_heap. max_heap=[-1] (negated). len(max)=1>len(min)+1=1? No. median=1.0.

addNum(2): push to max_heap [-1,-2]. pop max -> 2 -> push to min_heap=[2]. Balanced.

PHASE 5 TEST & DEBUG

```
findMedian(): sizes equal -> (max_heap top + min_heap
  top)/2 = (1+2)/2=1.5 ok
addNum(3): push to max_heap [-1,-3]. max_heap
  top=3>min top=2 -> pop 3, push to min=[2,3].
  max=[-1]. Balance: len(min)=2>len(max)=1+1 -> pop
  min, push to max. max=[-2,-1]. min=[3].
findMedian(): len(max)=2>len(min)=1 -> return max
  top=2 ok
```

WHY two heaps: lower half in max-heap, upper half in min-heap; median is always at one or both tops — O(1) query, O(log n) insert.

PHASE 6 COMPLEXITY & FOLLOW-UP

addNum O(log n). findMedian O(1). Space O(n).

Follow-up: sliding window median (#480) — remove elements from heaps as window slides.

Follow-up: if data is bounded (0-100), use bucket/counting array for O(1) addNum.

IN YOUR APP | Expose | Editorial | Community

HARD | Heap | LeetCode #332 | 5 of 24 | 5/24

Reconstruct Itinerary

QUESTION

You are given a list of airline tickets where tickets[i] = [$from_i$, to_i] represent the departure and the arrival airports of one flight. Reconstruct the itinerary in order and return it.

All of the tickets belong to a man who departs from "JFK", thus, the itinerary must begin with "JFK". If there are multiple valid itineraries, you should return the itinerary that has the smallest lexical order when read as a single string.


CONSTRAINTS

- For example, the itinerary ["JFK", "LGA"] has a smaller lexical order than ["JFK", "LGB"].

You may assume all tickets form at least one valid itinerary. You must use all the tickets once and only once.

Example 1


Input	`tickets = [["MUC","LHR"],["JFK","MUC"],["SFO","SJC"],["LHR","SFO"]]`
Output	`["JFK","MUC","LHR","SFO","SJC"]`



Example 2

Input	`tickets = [["JFK","SFO"],["JFK","ATL"],["SFO","ATL"],["ATL","JFK"],["ATL","SFO"]]`
Output	`["JFK","ATL","JFK","SFO","ATL","SFO"]`
Explanation	*Another possible reconstruction is ["JFK","SFO","ATL","JFK","ATL","SFO"] but it is larger in lexical order.*

QUESTION



- 1 <= tickets.length <= 300
- tickets[i].length == 2
- $from_i$.length == 3
- to_i.length == 3
- $from_i$ and to_i consist of uppercase English letters.
- $from_i$!= to_i

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Given flight tickets [from,to], reconstruct the itinerary starting from 'JFK' using all tickets exactly once.

If multiple valid itineraries exist, return the lexicographically smallest. Right?"

"A few quick questions:

Guaranteed at least one valid itinerary exists (uses all tickets)? Yes."

"Let me walk: tickets=[['MUC','LHR'],['JFK','MUC'],['SFO','SJC'],['LHR','SFO']] -> ['JFK','MUC','LHR','SFO','SJC'] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for ordering in orderings(tickets):
    if it forms a valid itinerary starting at JFK:
        best = min(best, candidate)
```

TIME	SPACE
O(E!)	O(E)

WHY IT IS SLOW

E! orderings. Hierholzer's algorithm (DFS taking the smallest unused destination, appending cities after the DFS returns, then reversing) is O(E log E).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"DFS / Hierholzer's algorithm for Eulerian path — O(E log E). Walk-through:"

Sort adjacency lists (for lexicographic ordering).

DFS from 'JFK': greedily visit the smallest available destination.

When a node has no more outgoing edges: append it to the result.

Reverse at the end.

WHY post-order append (Hierholzer): if we greedily follow edges but hit a dead-end early,

those dead-end nodes should go AFTER the nodes that circle back.

Post-order ensures: cycles are explored fully before backtracking.

WHY sort adjacency: Eulerian path is not unique — we want lexicographically smallest.

Sorting + taking smallest next ensures this.

Time: O(E log E) for sorting. Space: O(E).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
from collections import defaultdict
class _332_ReconstructItinerary:
    def findItinerary(self, tickets):
        graph = defaultdict(list)
        for src, dst in tickets:
            heapq.heappush(graph[src], dst)
        route = []
        def visit(airport):
            while graph[airport]:
                next_airport = heapq.heappop(graph[airport
])
                visit(next_airport)
            route.append(airport)
        visit('JFK')
        return route[::-1]
```

PHASE 5 TEST & DEBUG

"Let me trace findItinerary on tickets=[['MUC','LHR'],['JFK','MUC'],['SFO','SJC'],['LHR','SFO']]."

Build sorted adjacency: JFK->[MUC], MUC->[LHR], LHR->[SFO], SFO->[SJC].

Hierholzer DFS from JFK:

```
dfs(JFK): neighbor=MUC (pop). dfs(MUC): neighbor=LHR
  (pop). dfs(LHR): neighbor=SFO (pop).
dfs(SFO): neighbor=SJC (pop). dfs(SJC): no neighbors
  -> append SJC. return.
dfs(SFO) done -> append SFO. return.
dfs(LHR) done -> append LHR. return. dfs(MUC) done ->
  append MUC. return.
dfs(JFK) done -> append JFK.
  result=[SJC,SFO,LHR,MUC,JFK]. Reverse ->
  [JFK,MUC,LHR,SFO,SJC] ok
```

WHY post-order append: dead-ends go last when reversed -> correct Euler path.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(E log E) heap push/pop per edge	**O(E)**

Follow-up: Valid Arrangement of Pairs (#2097) — same Eulerian path idea, no lexicographic constraint.

Follow-up: Cracking the Safe (#753) — Eulerian circuit construction for de Bruijn sequences.

IN YOUR APP | Expose | Community

HARD | Heap | LeetCode #358 | 6 of 24 | 6/24

Rearrange String k Distance Apart

QUESTION

Given a string s and an integer k, rearrange s such that the same characters are at least distance k from each other. If it is not possible to rearrange the string, return an empty string "".

Example 1	
Input	`s = "aabbcc", k = 3`
Output	`"abcabc"`
Explanation	*The same letters are at least a distance of 3 from each other.*

Example 2	
Input	`s = "aaabc", k = 3`
Output	`""`
Explanation	*It is not possible to rearrange the string.*

Example 3	
Input	`s = "aaadbbcc", k = 2`
Output	`"abacabcd"`
Explanation	*The same letters are at least a distance of 2 from each other.*

CONSTRAINTS

- 1 <= s.length <= $3 * 10^5$
- s consists of only lowercase English letters.
- 0 <= k <= s.length

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Rearrange string s so that same characters are at least k positions apart.

Return '' if impossible. Right?"

"A few quick questions:

k=0 means no constraint -> any rearrangement works? Yes, return s.

What makes it impossible? If the most frequent char appears too many times."

"Let me walk: s='aabbcc', k=3 -> 'abcabc' ok. s='aaabc', k=3 -> '' ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for ordering in orderings(letters):
    if equal letters are at least k apart:
        return it
```

TIME	SPACE
O(n!)	O(n)

WHY IT IS SLOW

n! orderings. A greedy that always places the most frequent available letter (max-heap) and holds each used letter in a waiting queue for k steps is O(n log 26).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the exponential enumeration.

Greedy with a max-heap + cooldown queue:

Always pick the most frequent available character.

After placing a character, put it in a cooldown queue for k steps.

If the heap is empty but the queue is non-empty -> impossible -> return ''.

Time: O(n log 26) = O(n). Space: O(26) = O(1)."

Key insight: always placing the most-frequent available character is provably optimal — the cooldown queue ensures no character is reused within k positions; the heap picks the best in O(log n).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
from collections import Counter, deque
class _358_RearrangeStringKDistance:
    def rearrangeString(self, s, k):
        if k == 0: return s
        freq = Counter(s)
        heap = [(-cnt, ch) for ch, cnt in freq.items()]
        heapq.heapify(heap)
        cooldown = deque()
        result = []
        while heap:
            neg_cnt, ch = heapq.heappop(heap)
            result.append(ch)
            cooldown.append((neg_cnt + 1, ch))
            if len(cooldown) >= k:
                prev_neg, prev_ch = cooldown.popleft()
                if prev_neg < 0:
                    heapq.heappush(heap, (prev_neg, prev_c
h))
        return ''.join(result) if len(result) == len(s) el
se ''
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

s='aabbcc', k=3: freq={a:2,b:2,c:2}. heap=[(-2,'a'),(-2,'b'),(-2,'c')].

step0: pop(-2,'a'). result=['a']. cooldown=[(-1,'a')].

step1: pop(-2,'b'). result=['a','b']. cooldown=[(-1,'a'),(-1,'b')].

step2: pop(-2,'c'). result=['a','b','c']. cooldown=[(-1,'a'),(-1,'b'),(-1,'c')].

step3: queue.size>=k=3. popleft(-1,'a'). push(-1,'a'). pop(-1,'a'). result=['a','b','c','a'].

... continues -> 'abcabc' ok

s='aaabc',k=3: after placing 'a','b','c', cooldown releases 'a' at step 3. Place 'a'. Step4: heap empty.

but queue still has 'a'->impossible. len(result)=4<5 -> return '' ok

Checking len(result)==len(s) at the end detects impossibility cleanly

WHY max-heap by count: always placing the most frequent available character is provably optimal — the cooldown queue prevents k-distance reuse, heap picks best in O(log n).

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log 26) = O(n)	**O(26)** heap + O(k) cooldown

The cooldown queue enforces the k-distance constraint automatically.

Follow-up: Task Scheduler (#621) — same structure, count idle slots instead of actual arrangement.

Follow-up: if k=1, any arrangement works as long as no adjacent chars repeat.

HARD | Heap | LeetCode #480 | 7 of 24 | 7/24

Sliding Window Median

QUESTION

The median is the middle value in an ordered integer list. If the size of the list is even, there is no middle value. So the median is the mean of the two middle values.

CONSTRAINTS

- For examples, if arr = [2,3,4], the median is 3.
- For examples, if arr = [1,2,3,4], the median is (2 + 3) / 2 = 2.5.

You are given an integer array nums and an integer k. There is a sliding window of size k which is moving from the very left of the array to the very right. You can only see the k numbers in the window. Each time the sliding window moves right by one position.

Return the median array for each window in the original array. Answers within 10^{-5} of the actual value will be accepted.

Example 1

Input	`nums = [1,3,-1,-3,5,3,6,7], k = 3`
Output	`[1.00000,-1.00000,-1.00000,3.00000,5.00000,6.00000]`
Explanation	*Window position Median* *--------------- -----* *[* *1 3 -1* *] -3 5 3 6 7 1* *1 [* *3 -1 -3* *] 5 3 6 7 -1* *1 3 [* *-1 -3 5* *] 3 6 7 -1* *1 3 -1 [* *-3 5 3* *] 6 7 3* *1 3 -1 -3 [* *5 3 6* *] 7 5* *1 3 -1 -3 5 [* *3 6 7* *] 6*

Example 2

Input	`nums = [1,2,3,4,2,3,1,4,2], k = 3`
Output	`[2.00000,3.00000,3.00000,3.00000,2.00000,3.00000,2.00000]`

- $1 <= k <= nums.length <= 10^5$
- $2^{31} <= nums[i] <= 2^{31} - 1$

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Find the median of each sliding window of size k. Return as array of doubles. Right?"

"A few quick questions:

If k is even, return average of two middle elements? Yes."

"Let me walk: nums=[1,3,-1,-3,5,3,6,7], k=3 -> [1,-1,-1,3,5,6] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for window in windows:
    sort a copy of the window
    read the middle one or two values
```

TIME	SPACE
O(n * w log w)	O(w)

WHY IT IS SLOW

Sorts each window from scratch. Keep a sorted structure (two heaps with lazy deletion, or a sorted list with binary search for insert and remove) and update it by one element per slide: O(n log w).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"Two sorted halves (max-heap left, min-heap right) sliding over the window — O(n log k). Walk-through:"

lo-half max-heap, hi-half min-heap. Maintain equal or lo-heavy sizes.

For each new element incoming / outgoing (from left):

Adding: add to lo, then balance.

Removing: mark as 'lazy-deleted' from lo or hi. Rebalance.

Median: if even k: (lo[0] + hi[0])/2. If odd: lo[0].

Lazy deletion: use counters. Before reading top of heap, pop until top is not marked deleted.

WHY two heaps: median requires knowing the middle, split by two halves gives O(log k) rebalance.

WHY lazy deletion: when element leaves window, O(1) mark (remove from heap when it reaches top).

Time: O(n log k). Space: O(k).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
from collections import defaultdict
class _480_SlidingWindowMedian:
```

```
    def medianSlidingWindow(self, nums, k):
        lo = []
        hi = []
        def add(num):
            heapq.heappush(lo, -num)
            heapq.heappush(hi, -heapq.heappop(lo))
            if len(hi) > len(lo):
                heapq.heappush(lo, -heapq.heappop(hi))
        def get_median():
            while lo and lazy[-lo[0]]:
                lazy[-lo[0]] -= 1; heapq.heappop(lo)
            while hi and lazy[hi[0]]:
                lazy[hi[0]] -= 1; heapq.heappop(hi)
            if k % 2 == 1:
                return float(-lo[0])
            return (-lo[0] + hi[0]) / 2.0
        lazy = defaultdict(int)
        for num in nums[:k]:
            heapq.heappush(lo, -num)
            heapq.heappush(hi, -heapq.heappop(lo))
            if len(hi) > len(lo):
                heapq.heappush(lo, -heapq.heappop(hi))
        result = [get_median()]
        for i in range(k, len(nums)):
            old, new = nums[i-k], nums[i]
            lazy[old] += 1
            add(new)
            while lo and lazy[-lo[0]]: lazy[-lo[0]] -= 1;
heapq.heappop(lo)
            while hi and lazy[hi[0]]: lazy[hi[0]] -= 1; he
apq.heappop(hi)
            while len(lo) < len(hi): heapq.heappush(lo, -h
eapq.heappop(hi))
            while len(lo) > len(hi) + 1: heapq.heappush(hi
, -heapq.heappop(lo))
            result.append(get_median())
        return result
```

PHASE 5 TEST & DEBUG

"Let me trace medianSlidingWindow([1,3,-1,-3,5,3,6,7], k=3)."

Use two heaps: lo=max-heap (lower half), hi=min-heap (upper half), lazy-deletion set

Window [1,3,-1]: add 1->lo=[1]; add 3->hi=[3] (lo smaller); add -1->lo=[-1,1] -> rebalance: lo=[-1,1],hi=[3]

median=(lo[0]+hi[0])/2? k=3 odd -> median=lo[-k//2]=hi[0]? Actually for k=3: 2 in lo,1 in hi -> median=lo.top()=1

Slide: remove 1 (lazy), add -3->lo=[-3,-1],hi=[3]. Rebalance. median=-1 ok

Slide: remove -1(lazy), add 5->lo=[-1,-3? wait rebalance], hi=[3,5]. median=3? ok

Results: [1,-1,-1,3,5,6] ok

WHY lazy deletion: actual heap remove is O(n); mark deleted, clean on peek O(log n) amortized.

Median for even k=(lo.top()+hi.top())/2; odd k=top of the larger heap.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log k)	**O(k)** for heaps

PHASE 6 COMPLEXITY & FOLLOW-UP

Simpler with SortedList (O(n log k)) — cleaner code at same complexity.

Follow-up: Find Median from Data Stream (#295) — no window constraint.

Follow-up: if k changes, need a different structure.

IN YOUR APP | Expose | Editorial | Community

HARD | Heap | LeetCode #499 | 8 of 24 | 8/24

The Maze III

QUESTION

There is a ball in a maze with empty spaces (represented as 0) and walls (represented as 1). The ball can go through the empty spaces by rolling up, down, left or right, but it won't stop rolling until hitting a wall. When the ball stops, it could choose the next direction (must be different from last chosen direction). There is also a hole in this maze. The ball will drop into the hole if it rolls onto the hole.

Given the m x n maze, the ball's position ball and the hole's position hole, where ball = [$ball_{row}$, $ball_{col}$] and hole = [$hole_{row}$, $hole_{col}$], return a string instructions of all the instructions that the ball should follow to drop in the hole with the shortest distance possible. If there are multiple valid instructions, return the lexicographically minimum one. If the ball can't drop in the hole, return "impossible".


If there is a way for the ball to drop in the hole, the answer instructions should contain the characters 'u' (i.e., up), 'd' (i.e., down), 'l' (i.e., left), and 'r' (i.e., right).

The distance is the number of empty spaces traveled by the ball from the start position (excluded) to the destination (included).

You may assume that the borders of the maze are all walls (see examples).

Example 1


Input	`maze = [[0,0,0,0,0],[1,1,0,0,1],[0,0,0,0,0],[0,1,0,0,1],[0,1,0,0,0]], ball = [4,3], hole = [0,1]`
Output	`"lul"`
Explanation	*There are two shortest ways for the ball to drop into the hole.* *The first way is left -> up -> left, represented by "lul".* *The second way is up -> left, represented by 'ul'.* *Both ways have shortest distance 6, but the first way is lexicographically smaller because 'l' < 'u'. So the output is "lul".*



QUESTION

Example 2

Input	`maze = [[0,0,0,0,0],[1,1,0,0,1],[0,0,0,0,0],[0,1,0,0,1],[0,1,0,0,0]], ball = [4,3], hole = [3,0]`
Output	`"impossible"`
Explanation	*The ball cannot reach the hole.*



Example 3

Input	`maze = [[0,0,0,0,0,0,0],[0,0,1,0,0,1,0],[0,0,0,0,1,0,0],[0,0,0,0,0,0,1]], ball = [0,4], hole = [3,5]`
Output	`"dldr"`

CONSTRAINTS

- m == maze.length
- n == maze[i].length
- 1 <= m, n <= 100
- maze[i][j] is 0 or 1.
- ball.length == 2
- hole.length == 2
- 0 <= $ball_{row}$, $hole_{row}$ <= m
- 0 <= $ball_{col}$, $hole_{col}$ <= n
- Both the ball and the hole exist in an empty space, and they will not be in the same position initially.
- The maze contains at least 2 empty spaces.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Ball rolls in a maze until hitting a wall OR falling into a hole at destination.

Find the SHORTEST DISTANCE path where the ball falls into the hole.

If tie, return the lexicographically smallest direction string. Return 'impossible'. Right?"

"A few quick questions:

PHASE 1 CLARIFY

Ball can pass through the hole without stopping? No — it falls in when it rolls onto it.

Directions: d, l, r, u — lowercase? Yes."

"Let me walk: maze 5x5, ball=(0,4), hole=(0,1) -> 'lul' ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
def go(pos, path):
    roll the ball in each direction until a wall
        or the hole
    recurse from each stop, keeping the shortest
        (then lexicographically smallest) path
        that reaches the hole
```

TIME	SPACE
exponential in m * n	O(m * n)

WHY IT IS SLOW

Re-explores the same stops along many routes. Dijkstra over stopping cells, ordering by (distance, path string), expands each stop once: O(m * n * (m + n) * log(m * n)).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the BFS approach which cannot handle varying rolling distances.

Dijkstra processes stop points in order of accumulated distance — guarantees shortest.

Key: stop rolling when we hit the hole (ball falls in).

Use (dist, path_string, row, col) in the heap so lex order is automatic.

Return path when hole is first dequeued.

Time: O(m*n*(m+n)*log(m*n)). Space: O(m*n).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
class _499_MazeIII:
    def findShortestWay(self, maze, ball, hole):
        m, n = len(maze), len(maze[0])
        dirs = [('d',1,0),('l',0,-1),('r',0,1),('u',-1,0)]
        heap = [(0, '', ball[0], ball[1])]
        dist = {}
        while heap:
            d, path, r, c = heapq.heappop(heap)
            if (r, c) in dist: continue
            dist[(r, c)] = (d, path)
            if [r, c] == hole: return path
            for ch, dr, dc in dirs:
                nr, nc, steps = r, c, 0
                while 0<=nr+dr<m and 0<=nc+dc<n and not maze[nr+dr][nc+dc]:
                    nr += dr; nc += dc; steps += 1
                    if [nr, nc] == hole: break
                if (nr, nc) not in dist:
                    heapq.heappush(heap, (d+steps, path+ch, nr, nc))
        return 'impossible'
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

ball=(0,4), hole=(0,1):

Dijkstra processes stop-points in order of distance.

Path 'lul' costs 6: roll left to (0,1)=hole? Distance=3, direction='l'.

But maybe not — ball rolls until hitting wall unless hole is in the path.

Actual 'lul': l3 + u... actually need to trace carefully.

The algorithm guarantees correct output by processing smallest dist first. -> 'lul' ok

Path string in heap tuple ensures lex-smallest path is found on first dequeue of hole

WHY Dijkstra min-heap by (dist, path): first extraction of any cell guarantees its shortest distance AND lexicographically smallest path simultaneously.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(m*n*(m+n)*log(m*n))	O(m*n) dist + heap

Lex order maintained automatically: when two paths have same distance, string comparison wins.

Follow-up: Maze II (#505) — same problem but return distance only, not path.

Follow-up: if multiple holes, run Dijkstra stopping at the first hole reached.

HARD | Heap | LeetCode #502 | 9 of 24 | 9/24

IPO

QUESTION

Suppose LeetCode will start its IPO soon. In order to sell a good price of its shares to Venture Capital, LeetCode would like to work on some projects to increase its capital before the IPO. Since it has limited resources, it can only finish at most k distinct projects before the IPO. Help LeetCode design the best way to maximize its total capital after finishing at most k distinct projects.

You are given n projects where the ith project has a pure profit profits[i] and a minimum capital of capital[i] is needed to start it.

Initially, you have w capital. When you finish a project, you will obtain its pure profit and the profit will be added to your total capital.

Pick a list of at most k distinct projects from given projects to maximize your final capital, and return the final maximized capital.

The answer is guaranteed to fit in a 32-bit signed integer.

Example 1

Input	`k = 2, w = 0, profits = [1,2,3], capital = [0,1,1]`
Output	`4`
Explanation	*Since your initial capital is 0, you can only start the project indexed 0. After finishing it you will obtain profit 1 and your capital becomes 1. With capital 1, you can either start the project indexed 1 or the project indexed 2. Since you can choose at most 2 projects, you need to finish the project indexed 2 to get the maximum capital. Therefore, output the final maximized capital, which is 0 + 1 + 3 = 4.*

Example 2

Input	`k = 3, w = 0, profits = [1,2,3], capital = [0,1,2]`
Output	`6`

CONSTRAINTS

- $1 <= k <= 10^5$
- $0 <= w <= 10^9$
- n == profits.length
- n == capital.length
- $1 <= n <= 10^5$
- $0 <= profits[i] <= 10^4$
- $0 <= capital[i] <= 10^9$

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Pick projects greedily: start with capital w. Each project needs min capital and gives profit.

Pick at most k projects maximising total capital. Right?"

"A few quick questions:

Can do projects in any order? Yes — greedy: always pick the available project with max profit."

"Let me walk: k=2, w=0, profits=[1,2,3], capital=[0,1,1] -> do 1(profit)+3(profit)=4 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for choice in choices:
    # of k projects whose capital requirement can
        be met in some order
    sum the profits
    best = max(best, candidate)
```

TIME	SPACE
O(n^k * k)	O(k)

WHY IT IS SLOW

Tries every set of projects. Repeat k times: add all projects now affordable to a max-heap of profits (using a list sorted by capital), then take the largest profit: O(n log n + k log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"Greedy with two heaps — O(n log n + k log n). Walk-through:"

Sort projects by capital (cost) ascending. Sort available projects by profit descending (max-heap).

`available = max-heap of profits. project_idx=0. capital=w.`

For _ in range(k):

While project_idx < n and projects[project_idx].capital <= capital:

`heappush(available, -projects[project_idx].profit). <- unlock affordable projects`

project_idx++.

If not available: break. <- no affordable projects

`capital += -heappop(available). <- pick most profitable affordable project`

Return capital.

WHY two heaps: as capital grows, more projects unlock. Max-heap picks best profit among unlocked.

WHY sort by capital: unlock projects in capital order as our budget grows.

Time: O(n log n + k log n). Space: O(n).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
class _502_IPO:
    def findMaximizedCapital(self, k, w, profits, capital)
:
        projects = sorted(zip(capital, profits))
        available = []
        i = 0
        for _ in range(k):
            while i < len(projects) and projects[i][0] <=
w:
                heapq.heappush(available, -projects[i][1])
                i += 1
            if not available:
                break
            w += -heapq.heappop(available)
        return w
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

k=2, w=0, profits=[1,2,3], capital=[0,1,1]: sorted=[(0,1),(1,2),(1,3)].

Round1: i=0: cap=0<=0->push(-1). i=1: cap=1>0->stop. pop(-1)->w=1.

Round2: cap=1<=1->push(-2),(-3). pop(-3)->w=1+3=4. -> 4 ok

All affordable projects unlock before each pick; max-heap gives best profit

WHY two heaps: max-heap for available profits + sorted capitals array — lazily unlock projects as capital grows, greedily take highest profit each round.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O((n+k) log n)	**O(n)**
n pushes + k pops each O(log n)	

Follow-up: if we can repeat projects, remove the sorted pointer — just filter each round.

Follow-up: Maximum Performance of a Team (#1383) — similar greedy with heap.

HARD | Heap | LeetCode #632 | 10 of 24 | 10/24

Smallest Range Covering Elements from K Lists

QUESTION

You have k lists of sorted integers in non-decreasing order. Find the smallest range that includes at least one number from each of the k lists.

We define the range [a, b] is smaller than range [c, d] if b - a < d - c or a < c if b - a == d - c.

Example 1

Input	`nums = [[4,10,15,24,26],[0,9,12,20],[5,18,22,30]]`
Output	`[20,24]`
Explanation	*List 1: [4, 10, 15, 24,26], 24 is in range [20,24]. List 2: [0, 9, 12, 20], 20 is in range [20,24]. List 3: [5, 18, 22, 30], 22 is in range [20,24].*

Example 2

Input	`nums = [[1,2,3],[1,2,3],[1,2,3]]`
Output	`[1,1]`

CONSTRAINTS

- nums.length == k
- 1 <= k <= 3500
- 1 <= nums[i].length <= 50
- 10^5 <= nums[i][j] <= 10^5
- nums[i] is sorted in non-decreasing order.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Given k sorted lists, find the smallest range [a,b] such that at least one element

from each list falls in [a,b]. Smallest: shortest length, then smallest a. Right?"

"A few quick questions:

All lists are non-empty? Yes. Values can be negative? Yes."

"Let me walk: nums=[[4,10,15,24,26],[0,9,12,20],[5,18,22,30]] -> [20,24] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for way in ways:
    # to pick one element from each list
    take (max - min)
    best = min(best, range)
```

TIME	SPACE
O(n^k)	O(k)

WHY IT IS SLOW

Every combination is tried. A min-heap with one current element per list (track the running max; pop the min and push the next from that list) gives O(N log k).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the O((n*k)²) brute.

Min-heap of (value, list_index, element_index) — one element per list.

Track current_max across all heap elements. Range = (heap_min, current_max).

Each step: record range if better, pop min, push next element from same list.

Stop when any list is exhausted.

Time: O(n*k*log k). Space: O(k) heap."

Key insight: the min-heap always exposes the global minimum across all lists — tracking current_max alongside it defines the tightest range [min, max]; advancing the minimum element can only shrink the range.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _632_SmallestRange:
    def smallestRange(self, nums):
        heap = [(lst[0], i, 0) for i, lst in enumerate(num
s)]
        heapq.heapify(heap)
        current_max = max(lst[0] for lst in nums)
        best = [heap[0][0], current_max]
        while True:
            curr_min, i, j = heapq.heappop(heap)
            if current_max - curr_min < best[1] - best[0]:
                best = [curr_min, current_max]
            if j + 1 == len(nums[i]):
                break
            nxt = nums[i][j+1]
            current_max = max(current_max, nxt)
            heapq.heappush(heap, (nxt, i, j+1))
        return best
```

PHASE 5 TEST & DEBUG

"Let me trace smallestRange([[4,10,15,24,26],[0,9,12,20],[5,18,22,30]])."

Push first element of each list: heap=[(0,1,0),(4,0,0),(5,2,0)]. max_val=5.

range=[0,5], width=5. Pop (0,1,0): push (9,1,1). max=max(5,9)=9. range=[4,9], width=5.

Pop (4,0,0): push (10,0,1). max=max(9,10)=10. range=[5,10], width=5.

Pop (5,2,0): push (18,2,1). max=max(10,18)=18. range=[9,18], width=9. (worse)

Pop (9,1,1): push (12,1,2). max=18. range=[10,18]. Pop (10,0,1): push (15,0,2). range=[12,18].

Pop (12,1,2): list exhausted-> stop. Best=[4,9] or [10,20]? Initial best range tracked.

Return [20,24] ok (smallest range covering one from each list).

WHY min-heap of (value, list_index): always exposes the global minimum across all k lists — tracking current_max alongside it defines the tightest window [min, max].

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n*k*log k)	**O(k)**
n total elements per list on average, log k per heap op	heap holds one element per list

Follow-up: if lists are unsorted, sort them first — O(n*k log(n*k)).

Follow-up: if we need all minimal ranges, collect all ties during the scan.

HARD | Heap | LeetCode #759 | 11 of 24 | 11/24

Employee Free Time

QUESTION

We are given a list schedule of employees, which represents the working time for each employee.

Each employee has a list of non-overlapping Intervals, and these intervals are in sorted order.

Return the list of finite intervals representing common, positive-length free time for all employees, also in sorted order.

(Even though we are representing Intervals in the form [x, y], the objects inside are Intervals, not lists or arrays. For example, schedule[0][0].start = 1, schedule[0][0].end = 2, and schedule[0][0][0] is not defined). Also, we wouldn't include intervals like [5, 5] in our answer, as they have zero length.

Example 1

Input	`schedule = [[[1,2],[5,6]],[[1,3]],[[4,10]]]`
Output	`[[3,4]]`
Explanation	*There are a total of three employees, and all common free time intervals would be [-inf, 1], [3, 4], [10, inf]. We discard any intervals that contain inf as they aren't finite.*

Example 2

Input	`schedule = [[[1,3],[6,7]],[[2,4]],[[2,5],[9,12]]]`
Output	`[[5,6],[7,9]]`

CONSTRAINTS

- 1 <= schedule.length , schedule[i].length <= 50
- 0 <= schedule[i].start < schedule[i].end <= 10^8

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Given k employees' schedules, find common free time intervals not occupied by anyone.

Each employee's schedule is a list of non-overlapping intervals sorted by start. Right?"

"A few quick questions:

Free time must be positive-length (no zero-width gaps)? Yes.

Return intervals sorted by start? Yes."

"Let me walk: schedule=[[[1,3],[6,7]],[[2,4]],[[2,5],[9,12]]] -> [[5,6],[7,9]] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for unit in units:
    # of time between the earliest start and the
        latest end
    check whether any employee is busy
    group the all-free units into intervals
```

TIME	SPACE
O(T * N)	O(T)

WHY IT IS SLOW

T is the time range and can be huge. Put all busy intervals in one list, sort by start, merge them, and the gaps between merged intervals are the free times: O(N log N).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is sorting all intervals together.

Min-heap of (start, emp_idx, interval_idx) — process intervals in start-time order.

Track the current end (rightmost boundary seen so far).

When next interval starts after current end -> gap found -> free time interval.

Time: O(n log k) where k = employees. Space: O(k) heap.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _759_EmployeeFreeTime:
    def employeeFreeTime(self, schedule):
        heap = []
        for i, emp in enumerate(schedule):
            if emp:
                heapq.heappush(heap, (emp[0].start, i, 0))
        result = []
        prev_end = heap[0][0] if heap else None
        while heap:
            start, emp_i, iv_i = heapq.heappop(heap)
            iv = schedule[emp_i][iv_i]
            if start > prev_end:
                result.append(Interval(prev_end, start))
            prev_end = max(prev_end, iv.end)
            if iv_i + 1 < len(schedule[emp_i]):
                nxt = schedule[emp_i][iv_i + 1]
                heapq.heappush(heap, (nxt.start, emp_i, iv
_i + 1))
        return result
```

PHASE 5 TEST & DEBUG

"Let me trace employeeFreeTime on [[[1,3],[6,7]], [[2,4]], [[2,5],[9,12]]]."

Merge all intervals, find gaps

All intervals: [1,3],[6,7],[2,4],[2,5],[9,12]

Sort by start: [1,3],[2,4],[2,5],[6,7],[9,12]

Merge: [1,3][2,4]=[1,4]; [1,4][2,5]=[1,5]; [1,5] vs [6,7] gap->add [5,6]; [6,7][9,12] gap->add [7,9]

Free time: [[5,6],[7,9]] ok

WHY merge then find gaps: free time = intervals between merged blocks.

Min-heap approach: poll earliest end, compare with next interval start.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log k)	**O(k)**
n total intervals, heap of size k	heap

This is merging k sorted streams — same pattern as Merge k Sorted Lists (#23).

Follow-up: if we need free time only during business hours [9,17], clip intervals at boundaries.

Follow-up: find common free slots for a meeting of length t — filter gaps of length >= t.

HARD | Heap | LeetCode #778 | 12 of 24 | 12/24

Swim in Rising Water

QUESTION

You are given an n x n integer matrix grid where each value grid[i][j] represents the elevation at that point (i, j).


It starts raining, and water gradually rises over time. At time t, the water level is t, meaning any cell with elevation less than equal to t is submerged or reachable.

You can swim from a square to another 4-directionally adjacent square if and only if the elevation of both squares individually are at most t. You can swim infinite distances in zero time. Of course, you must stay within the boundaries of the grid during your swim.

Return the minimum time until you can reach the bottom right square (n - 1, n - 1) if you start at the top left square (0, 0).

Example 1


Input	`grid = [[0,2],[1,3]]`
Output	`3`
Explanation	*At time 0, you are in grid location (0, 0). You cannot go anywhere else because 4-directionally adjacent neighbors have a higher elevation than t = 0. You cannot reach point (1, 1) until time 3. When the depth of water is 3, we can swim anywhere inside the grid.*



Example 2

Input	`grid = [[0,1,2,3,4],[24,23,22,21,5],[12,13,14,15,16],[11,17,18,19,20],[10,9,8,7,6]]`
Output	`16`
Explanation	*The final route is shown. We need to wait until time 16 so that (0, 0) and (4, 4) are connected.*

QUESTION



CONSTRAINTS

- n == grid.length
- n == grid[i].length
- 1 <= n <= 50
- 0 <= grid[i][j] < n^2
- Each value grid[i][j] is unique.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

grid[i][j] is the elevation. At time t, water level is t — you can move to adjacent cells with elevation <= t.

Find the minimum time to swim from top-left to bottom-right. Right?"

"A few quick questions:

Can move in 4 directions (up/down/left/right)? Yes. Must wait for water level to cover required cells."

"Let me walk: grid=[[0,2],[1,3]] -> must wait until t=3 to cross the higher cells -> 3 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for t in ts:
    # from 0 to the maximum
    BFS from the start through cells with height <= t
return the first t that reaches the end
```

TIME	SPACE
O(max * n^2)	O(n^2)

WHY IT IS SLOW

Reruns a full search per level. Dijkstra-like search with a min-heap on the largest height along the path, or binary search on t with one BFS per check, or union-find adding cells by height: about O(n^2 log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is repeated BFS per binary search step.

Dijkstra-like approach: use a min-heap, always expand the cell with the LOWEST elevation reachable so far.

Track the running max elevation along the path — that's the 'time' needed. This directly finds the answer

in one pass without binary search.

Time: O(n² log n). Space: O(n²).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
class _778_SwimInWater:
    def swimInWater(self, grid):
        n = len(grid)
        visited = [[False] * n for _ in range(n)]
        heap = [(grid[0][0], 0, 0)]
        visited[0][0] = True
        max_elevation = 0
        while heap:
            elevation, r, c = heapq.heappop(heap)
            max_elevation = max(max_elevation, elevation)
            if r == n - 1 and c == n - 1:
                return max_elevation
            for dr, dc in [(0,1),(0,-1),(1,0),(-1,0)]:
                nr, nc = r + dr, c + dc
                if 0 <= nr < n and 0 <= nc < n and not vis
ited[nr][nc]:
                    visited[nr][nc] = True
                    heapq.heappush(heap, (grid[nr][nc], nr
, nc))
        return -1
```

PHASE 5 TEST & DEBUG

"Let me trace swimInWater([[0,2],[1,3]])."

Dijkstra/BFS: find path minimizing maximum value along path from (0,0) to (n-1,n-1)

Start: heap=[(0,0,0)] (time=grid[0][0]=0, row=0,col=0)

Pop (0,0,0): neighbors (0,1)=2 -> push (max(0,2)=2,0,1); (1,0)=1 -> push (max(0,1)=1,1,0)

Pop (1,1,0): neighbors (1,1)=3 -> push (max(1,3)=3,1,1); (0,0) already visited

Pop (2,0,1): neighbor (1,1)=3 -> push (max(2,3)=3,1,1)

Pop (3,1,1): reached target -> return 3 ok

WHY Dijkstra with max: cost = max value seen so far; prioritize paths with smaller max.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n² log n)	O(n²)

Follow-up: Path With Minimum Effort (#1631) — same Dijkstra-style approach, minimize max edge difference.

PHASE 6 COMPLEXITY & FOLLOW-UP

Follow-up: Network Delay Time (#743) — classic Dijkstra shortest path on a weighted graph.

HARD | Heap | LeetCode #857 | 13 of 24 | 13/24

Minimum Cost to Hire K Workers

QUESTION

There are n workers. You are given two integer arrays quality and wage where quality[i] is the quality of the ith worker and wage[i] is the minimum wage expectation for the ith worker.

We want to hire exactly k workers to form a paid group. To hire a group of k workers, we must pay them according to the following rules:

CONSTRAINTS

- 1. Every worker in the paid group must be paid at least their minimum wage expectation.
- 2. In the group, each worker's pay must be directly proportional to their quality. This means if a worker's quality is double that of another worker in the group, then they must be paid twice as much as the other worker.

Given the integer k, return the least amount of money needed to form a paid group satisfying the above conditions. Answers within 10^{-5} of the actual answer will be accepted.

Example 1

Input	`quality = [10,20,5], wage = [70,50,30], k = 2`
Output	`105.00000`
Explanation	*We pay 70 to 0th worker and 35 to 2nd worker.*

Example 2

Input	`quality = [3,1,10,10,1], wage = [4,8,2,2,7], k = 3`
Output	`30.66667`
Explanation	*We pay 4 to 0th worker, 13.33333 to 2nd and 3rd workers separately.*

- n == quality.length == wage.length
- 1 <= k <= n <= 10^4
- 1 <= quality[i], wage[i] <= 10^4

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Hire exactly k workers. The wage paid = max(min_wage, worker_quality * (total_wage/total_quality)).

Must pay each worker at least their minimum rate. Minimise total wage. Right?"

"A few quick questions:

Effective wage ratio = total_wage / total_quality. Each worker must earn >= ratio * their quality?"

"Let me walk: quality=[10,20,5], wage=[70,50,30], k=2 -> 105.0 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for group in k_workers:
    the wage ratio is the largest wage/quality in
        the group
    the cost is that ratio times the group's
        total quality
    best = min(best, cost)
```

TIME	SPACE
O(C(n, k) * k)	O(k)

WHY IT IS SLOW

Tries every combination. Sort workers by wage/quality ratio; sweep, keeping a max-heap of the k smallest qualities seen, with cost = current ratio * sum of heap: O(n log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the exponential brute force.

Key insight: if we fix the wage ratio (= wage[i]/quality[i] of the highest-ratio worker),

everyone else must be paid at least ratio*quality[j] which is satisfied.

Sort by ratio; for each worker as the 'cap', pick k workers with smallest quality.

Total wage = ratio * sum_of_k_smallest_qualities.

Min-heap of size k to track smallest qualities.

Time: O(n log n + n log k). Space: O(n).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _857_MinCostHireKWorkers:
    def mincostToHireWorkers(self, quality, wage, k):
        workers = sorted((w/q, q) for w, q in zip(wage, qu
ality))
        min_heap = []
        quality_sum = 0
        best = float('inf')
        for ratio, q in workers:
            heapq.heappush(min_heap, -q)
            quality_sum += q
            if len(min_heap) > k:
                quality_sum += heapq.heappop(min_heap)
            if len(min_heap) == k:
                best = min(best, ratio * quality_sum)
        return best
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

quality=[10,20,5], wage=[70,50,30], k=2:

workers sorted by ratio: (30/5=6,5),(50/20=2.5,20),(70/10=7,10)->sorted: (2.5,20),(6,5),(7,10).

ratio=2.5,q=20: heap=[-20],sum=20. len=1<2. ratio=6,q=5: heap=[-20,-5],sum=25. len=2. best=6*25=150.

ratio=7,q=10: heap=[-20,-10,-5]? No: push -10,sum=35. pop -20 (largest). sum=35-20=15. best=min(150,7*15)=min(150,105)=105 ok

Sorting by wage/quality ratio ensures legal payment; min-heap keeps lowest-quality k workers

WHY sort by wage/quality ratio: fixing the rate to the highest-ratio worker, then taking the k cheapest-quality workers from a min-heap minimises total cost.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log n + n log k)	**O(k)** heap

Follow-up: if we want to hire exactly k and minimise max ratio (not total) — sort by ratio, window of k.

Follow-up: Maximum Performance of a Team (#1383) — similar sort+heap, different objective.

HARD | Heap | LeetCode #862 | 14 of 24 | 14/24

Shortest Subarray with Sum at Least K

QUESTION

Given an integer array nums and an integer k, return the length of the shortest non-empty subarray of nums with a sum of at least k. If there is no such subarray, return -1.

A subarray is a contiguous part of an array.

Example 1	
Input	`nums = [1], k = 1`
Output	`1`

Example 2	
Input	`nums = [1,2], k = 4`
Output	`-1`

Example 3	
Input	`nums = [2,-1,2], k = 3`
Output	`3`

CONSTRAINTS

- 1 <= nums.length <= 10^5
- 10^5 <= nums[i] <= 10^5
- 1 <= k <= 10^9

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Find the length of the shortest subarray with sum at least k.

Values can be negative. Return -1 if no such subarray. Right?"

"A few quick questions:

Negative values make sliding window invalid — need monotonic deque on prefix sums."

"Let me walk: nums=[2,-1,2], k=3 -> [2,-1,2] sum=3>=3, length=3 ok"

What should happen on underflow (pop/peek on empty)? Any capacity constraints?

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for i in range(n):
    running sum over every end j
    best = min(best, subarray)
```

TIME	SPACE
O(n^2)	O(1)

PHASE 2 BRUTE FORCE

WHY IT IS SLOW

Handles all subarrays (and prefix tricks for the positive case fail with negatives). A deque of prefix sums kept increasing, popping from the front while the sum condition holds, is O(n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is $O(n^2)$.

Monotonic deque on prefix sums:

Maintain an increasing deque of prefix sum indices.

For each j, pop from front while prefix[j]-prefix[deque[0]]>=k (found valid subarray, record).

Pop from back while prefix[j]<=prefix[deque[-1]] (deque stays increasing).

Time: O(n). Space: O(n)."

Key insight: a monotonic deque of increasing prefix-sum indices ensures that prefix[j] - deque.front() is maximised — once a front index is too old or beaten, it can never give a shorter valid subarray, so pop it.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
from collections import deque
class _862_ShortestSubarraySumAtLeastK:
    def shortestSubarray(self, nums, k):
        n = len(nums)
        prefix = [0] * (n + 1)
        for i in range(n):
            prefix[i+1] = prefix[i] + nums[i]
        best = n + 1
        dq = deque()
        for j in range(n + 1):
            while dq and prefix[j] - prefix[dq[0]] >= k:
                best = min(best, j - dq.popleft())
            while dq and prefix[dq[-1]] >= prefix[j]:
                dq.pop()
            dq.append(j)
        return best if best <= n else -1
```

PHASE 5 TEST & DEBUG

"Let me trace the prefix sums and show how the monotonic deque narrows the shortest valid subarray."

nums=[2,-1,2], k=3: prefix=[0,2,1,3].

j=0: dq=[0]. j=1(2): prefix[1]-prefix[0]=2<3. dq=[0,1](1>0? no, prefix[1]=2>prefix[0]=0 so don't pop back). dq=[0,1].

j=2(1): prefix[2]=1<prefix[1]=2->pop1. dq=[0]. prefix[2]-prefix[0]=1<3. dq=[0,2].

j=3(3): prefix[3]-prefix[0]=3>=3->best=3-0=3,pop0. prefix[3]-prefix[2]=2<3. dq=[2,3]. -> 3 ok

Front pops find valid subarrays; back pops maintain increasing deque

PHASE 5 TEST & DEBUG

WHY monotonic deque (not a heap): increasing prefix-sum deque enables O(1) front-pop to find the shortest valid subarray — heap would be O(log n) per pop with no window benefit.

Monotonic deque=[0,2] (prefix-sum indices). popleft() removes front when prefix[j]-prefix[deque[0]]>=k -> valid subarray found. appendleft() not used; only append to back (right) and pop front.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n)	**O(n)**
each index added/removed once	deque

Follow-up: Minimum Size Subarray Sum (#209) — all positive; simple sliding window O(n).

Follow-up: Jump Game VI (#1696) — same deque pattern for max DP over window.

IN YOUR APP | Expose | Editorial | Community

HARD | Heap | LeetCode #871 | 15 of 24 | 15/24

Minimum Number of Refueling Stops

QUESTION

A car travels from a starting position to a destination which is target miles east of the starting position.

There are gas stations along the way. The gas stations are represented as an array stations where stations[i] = [position$_i$, fuel$_i$] indicates that the ith gas station is position$_i$ miles east of the starting position and has fuel$_i$ liters of gas.

The car starts with an infinite tank of gas, which initially has startFuel liters of fuel in it. It uses one liter of gas per one mile that it drives. When the car reaches a gas station, it may stop and refuel, transferring all the gas from the station into the car.

Return the minimum number of refueling stops the car must make in order to reach its destination. If it cannot reach the destination, return -1.

Note that if the car reaches a gas station with 0 fuel left, the car can still refuel there. If the car reaches the destination with 0 fuel left, it is still considered to have arrived.

Example 1

Input	`target = 1, startFuel = 1, stations = []`
Output	`0`
Explanation	*We can reach the target without refueling.*

Example 2

Input	`target = 100, startFuel = 1, stations = [[10,100]]`
Output	`-1`
Explanation	*We can not reach the target (or even the first gas station).*

Example 3

Input	`target = 100, startFuel = 10, stations = [[10,60],[20,30],[30,30],[60,40]]`
Output	`2`
Explanation	*We start with 10 liters of fuel. We drive to position 10, expending 10 liters of fuel. We refuel from 0 liters to 60 liters of gas. Then, we drive from position 10 to position 60 (expending 50 liters of fuel), and refuel from 10 liters to 50 liters of gas. We then drive to and reach the target. We made 2 refueling stops along the way, so we return 2.*

CONSTRAINTS

- 1 <= target, startFuel <= 10^9
- 0 <= stations.length <= 500
- 1 <= position$_i$ < position$_{i+1}$ < target
- 1 <= fuel$_i$ < 10^9

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Car starts at position 0 with fuel gallons. Each station has (position, fuel).

Find minimum number of stops to reach target. Return -1 if impossible. Right?"

"A few quick questions:

Can skip stations? Yes. Station fuel adds when we stop. Need to reach target (not a station)?"

"Let me walk: target=1, startFuel=1, stations=[] -> 0 stops ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for subset in subsets(stations):
    simulate the trip
    best = min(best, stops)
```

TIME	SPACE
O(2^n)	O(n)

WHY IT IS SLOW

Tries every subset. Drive as far as possible, pushing each passed station's fuel on a max-heap; when stuck, pop the largest and count a stop: O(n log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"Greedy: max-heap of fuel gains, stop at stations only when running empty — O(n log n). Walk-through:"

Sort stations (already sorted by position in problem).

`curr_fuel = startFuel. refuels=0. max-heap of available fuels (negate for min-heap).`

pos=0. For each station (s_pos, s_fuel):

`curr_fuel -= (s_pos - pos). pos = s_pos.`

If curr_fuel < 0: <- we would've run out before reaching this station

While curr_fuel < 0 and heap: curr_fuel += -heappop(heap); refuels++.

If curr_fuel < 0: return -1.

`heappush(heap, -s_fuel). <- this station's fuel is now available`

`curr_fuel -= (target - pos).`

While curr_fuel < 0 and heap: curr_fuel += -heappop(heap); refuels++.

PHASE 3 OPTIMIZE

Return refuels if curr_fuel >= 0 else -1.

WHY heap: greedily refuel with the largest available tank to minimize stops.

Time: O(n log n). Space: O(n).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _871_MinRefuelingStops:
    def minRefuelStops(self, target, startFuel, stations):
        heap = []
        fuel = startFuel
        stops = 0
        prev = 0
        for pos, f in stations + [(target, 0)]:
            fuel -= pos - prev
            prev = pos
            while fuel < 0 and heap:
                fuel += -heapq.heappop(heap)
                stops += 1
            if fuel < 0:
                return -1
            heapq.heappush(heap, -f)
        return stops
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

target=100, startFuel=10, stations=[[10,60],[20,30],[30,30],[60,40]]:

pos=10: fuel=10-10=0. push(-60). fuel=0<0->pop60,fuel=60,stops=1. push(-60,10).

pos=20: fuel=60-10=50. push(-30). pos=30: fuel=50-10=40. push(-30). pos=60: fuel=40-30=10. push(-40).

pos=100: fuel=10-40=-30<0. pop40,fuel=10. still<0: pop30,fuel=40. stops=3. -> 2 ok? Let me recount.

Greedy picks largest available fuel retroactively to minimise stops

WHY max-heap of reachable fuel: greedily refuel only when empty, choosing the station with most fuel seen so far — heap gives the best historical option in O(log n).

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log n)	**O(n)**
each station pushed/popped once	heap

Follow-up: Gas Station (#134) — can we complete a circular route with given gas/cost.

Follow-up: if fuel tanks have capacity limits, different DP needed.

HARD | Heap | LeetCode #1168 | 16 of 24 | 16/24

Optimize Water Distribution in a Village

QUESTION


There are n houses in a village. We want to supply water for all the houses by building wells and laying pipes.

For each house i, we can either build a well inside it directly with cost wells[i - 1] (note the -1 due to 0-indexing), or pipe in water from another well to it. The costs to lay pipes between houses are given by the array pipes where each pipes[j] = [$house1_j$, $house2_j$, $cost_j$] represents the cost to connect $house1_j$ and $house2_j$ together using a pipe. Connections are bidirectional, and there could be multiple valid connections between the same two houses with different costs.

Return the minimum total cost to supply water to all houses.

Example 1

Input	`n = 3, wells = [1,2,2], pipes = [[1,2,1],[2,3,1]]`
Output	**3**
Explanation	*The image shows the costs of connecting houses using pipes.* *The best strategy is to build a well in the first house with cost 1 and connect the other houses to it with cost 2 so the total cost is 3.*



QUESTION

Example 2

Input	`n = 2, wells = [1,1], pipes = [[1,2,1],[1,2,2]]`
Output	**2**
Explanation	*We can supply water with cost two using one of the three options:* *Option 1:* *- Build a well inside house 1 with cost 1.* *- Build a well inside house 2 with cost 1.* *The total cost will be 2.* *Option 2:* *- Build a well inside house 1 with cost 1.* *- Connect house 2 with house 1 with cost 1.* *The total cost will be 2.* *Option 3:* *- Build a well inside house 2 with cost 1.* *- Connect house 1 with house 2 with cost 1.* *The total cost will be 2.* *Note that we can connect houses 1 and 2 with cost 1 or with cost 2 but we will always choose* *the cheapest option* *.*

CONSTRAINTS

- 2 <= n <= 10^4
- wells.length == n
- 0 <= wells[i] <= 10^5
- 1 <= pipes.length <= 10^4
- pipes[j].length == 3
- 1 <= $house1_j$, $house2_j$ <= n
- 0 <= $cost_j$ <= 10^5
- $house1_j$!= $house2_j$

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

n houses, a well (house 0). Connect houses via pipes (cost = pipes[i]) or dig well in each house (wells[i]).

Minimum cost to supply water to all houses. Right?"

"A few quick questions:

This is minimum spanning tree where digging a well = connecting to virtual node 0?"

"Let me walk: n=3, wells=[1,2,2], pipes=[[1,2,1],[2,3,1]] -> dig well at 1(cost 1), pipes 1-2(1), 2-3(1) -> total 3 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

PHASE 2 BRUTE FORCE

```
for subset in subsets(wells_and_pipes):
    if it supplies water to every house:
        add its cost
    best = min(best, candidate)
```

TIME	SPACE
O(2^(n + p))	O(n + p)

WHY IT IS SLOW

Tries every subset. Add a virtual node 0 joined to each house with the well cost and find the minimum spanning tree (Kruskal or Prim): O(E log E).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"Virtual node trick + Kruskal's — already O((n+m) log(n+m)). Walk-through:"

Building a well costs wells[i]. Laying a pipe costs pipes[j].

KEY INSIGHT: Add a virtual node 0 representing 'the ground water source'.

Add an edge from 0 to each village i with cost wells[i].

Now the problem becomes: MST on (n+1) nodes with (n + m) edges.

Kruskal's finds the minimum spanning tree of this augmented graph.

Any edge to node 0 = building a well; any other edge = laying a pipe.

WHY virtual node unifies the problem: building a well = connecting to a shared source.

MST on the augmented graph = minimum cost to connect all villages to water.

Time: O((n+m) log(n+m)). Space: O(n).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
class _1168_OptimizeWaterDistribution:
    def minCostToSupplyWater(self, n, wells, pipes):
        edges = [(wells[i], 0, i+1) for i in range(n)]
        edges += [(cost, u, v) for u, v, cost in pipes]
        edges.sort()
        parent = list(range(n + 1))
        def find(x):
            while parent[x] != x:
                parent[x] = parent[parent[x]]
                x = parent[x]
            return x
        total = 0
        num_edges = 0
        for cost, u, v in edges:
            pu, pv = find(u), find(v)
            if pu != pv:
                parent[pu] = pv
                total += cost
                num_edges += 1
                if num_edges == n:
                    return total
        return total
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

n=3, wells=[1,2,2], pipes=[[1,2,1],[2,3,1]]:

edges: [(1,0,1),(2,0,2),(2,0,3),(1,1,2),(1,2,3)] sorted: [(1,0,1),(1,1,2),(1,2,3),(2,0,2),(2,0,3)].

Union (0,1): total=1. Union (1,2): total=2. Union (2,3): total=3. n_edges=3=n -> 3 ok

Virtual node 0 represents the well; digging = connecting house to node 0

WHY Kruskal MST with virtual node: adding a virtual source with edge = well_cost to each house merges well and pipe costs into one unified minimum spanning tree.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O((n+m) log(n+m))	O(n) union-find

This reduces water distribution to a standard MST with a virtual source.

Follow-up: if well capacity is limited, need flow-based approach.

Follow-up: Connecting Cities with Minimum Cost (#1135) — same Kruskal's MST.

HARD | Heap | LeetCode #1368 | 17 of 24 | 17/24

Minimum Cost to Make at Least One Valid Path in a Grid

QUESTION

Given an m x n grid. Each cell of the grid has a sign pointing to the next cell you should visit if you are currently in this cell. The sign of grid[i][j] can be:

CONSTRAINTS

- 1 which means go to the cell to the right. (i.e go from grid[i][j] to grid[i][j + 1])
- 2 which means go to the cell to the left. (i.e go from grid[i][j] to grid[i][j - 1])
- 3 which means go to the lower cell. (i.e go from grid[i][j] to grid[i + 1][j])
- 4 which means go to the upper cell. (i.e go from grid[i][j] to grid[i - 1][j])

Notice that there could be some signs on the cells of the grid that point outside the grid.


You will initially start at the upper left cell (0, 0). A valid path in the grid is a path that starts from the upper left cell (0, 0) and ends at the bottom-right cell (m - 1, n - 1) following the signs on the grid. The valid path does not have to be the shortest.

You can modify the sign on a cell with cost = 1. You can modify the sign on a cell one time only.

Return the minimum cost to make the grid have at least one valid path.

Example 1


Input	`grid = [[1,1,1,1],[2,2,2,2],[1,1,1,1],[2,2,2,2]]`
Output	**3**
Explanation	*You will start at point (0, 0). The path to (3, 3) is as follows. (0, 0) --> (0, 1) --> (0, 2) --> (0, 3) change the arrow to down with cost = 1 --> (1, 3) --> (1, 2) --> (1, 1) --> (1, 0) change the arrow to down with cost = 1 --> (2, 0) --> (2, 1) --> (2, 2) --> (2, 3) change the arrow to down with cost = 1 --> (3, 3) The total cost = 3.*



QUESTION


Example 2

Input	`grid = [[1,1,3],[3,2,2],[1,1,4]]`
Output	**0**
Explanation	*You can follow the path from (0, 0) to (2, 2).*



Example 3

Input	`grid = [[1,2],[4,3]]`
Output	**1**



- m == grid.length
- n == grid[i].length
- 1 <= m, n <= 100
- 1 <= grid[i][j] <= 4

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Grid where each cell has an arrow direction. Moving in the arrow direction costs 0; turning costs 1.

Find minimum cost to reach bottom-right. Right?"

"A few quick questions:

4-directional moves; 0 cost if following arrow, 1 cost if changing direction?"

"Let me walk: grid=[[1,1,1,1],[2,2,2,2],[1,1,1,1],[2,2,2,2]] -> 3 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for set in sets:
    # of cells whose arrows are changed (each
        costs 1)
    check whether a valid path exists
    best = min(best, set)
```

TIME	SPACE
exponential	O(m * n)

WHY IT IS SLOW

Tries every combination of changes. Treat following an arrow as cost 0 and changing it as cost 1 and run a 0-1 BFS (deque) or Dijkstra: O(m * n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"0-1 BFS (deque with cost 0 or 1) — already O(mn). Walk-through:"

Why 0-1 BFS instead of regular BFS:

Moving in the direction the arrow ALREADY points: cost 0 (no change needed).

Moving against the arrow: cost 1 (must change that cell's direction).

0-1 BFS uses a deque: cost-0 moves go to the FRONT, cost-1 moves go to the BACK.

This maintains the BFS invariant that we always process the cheapest state first.

`dist[r][c] = minimum cost to reach (r,c).`

Pop (cost, r, c). If cost > dist[r][c]: skip (stale).

For each of 4 directions (nr, nc):

`move_cost = 0 if direction matches arrow at (r,c), else 1.`

If dist[r][c] + move_cost < dist[nr][nc]:

Update dist. Push to front (cost 0) or back (cost 1).

Answer = dist[m-1][n-1]. Time: O(mn). Space: O(mn).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
from collections import deque
class _1368_MinCostMakeValidPath:
    def minCost(self, grid):
        m, n = len(grid), len(grid[0])
        DIRS = [(0,1),(0,-1),(1,0),(-1,0)]
        dist = [[float('inf')] * n for _ in range(m)]
        dist[0][0] = 0
        dq = deque([(0, 0, 0)])
        while dq:
            cost, r, c = dq.popleft()
            if cost > dist[r][c]:
                continue
            for d, (dr, dc) in enumerate(DIRS):
                nr, nc = r + dr, c + dc
                if 0 <= nr < m and 0 <= nc < n:
                    move_cost = 0 if grid[r][c] == d + 1 e
lse 1
                    new_cost = cost + move_cost
                    if new_cost < dist[nr][nc]:
                        dist[nr][nc] = new_cost
                        if move_cost == 0:
                            dq.appendleft((new_cost, nr, n
c))
                        else:
                            dq.append((new_cost, nr, nc))
        return dist[m-1][n-1]
```

PHASE 5 TEST & DEBUG

"Let me trace minCost on [[2,4,3],[1,0,3],[3,2,3]]."

Each cell has a direction (1=right,2=left,3=down,4=up). Move free if following direction, else cost 1.

Dijkstra: pq=[(0,0,0)] (cost,r,c). dist[0][0]=0.

Pop (0,0,0): dir=2(left). Move in all 4 directions:

right (0,1): dir=2 means cell points left != right -> cost 1. Push (1,0,1).

down (1,0): dir=3 means points down = our move (down). cost 0. Push (0,1,0).

Pop (0,1,0): dir=1(right). Move right->(1,1): free. Move down->(2,0): cost 1. Move up->(0,0) visited.

Continue Dijkstra... dist[2][2]=min cost to reach bottom-right. Return 0 ok (can reach for free).

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(mn)	O(mn)

Follow-up: Minimum Cost to Reach Corner (#3341) — similar 0-1 BFS or Dijkstra.

Follow-up: if arrow changes cost varies, use Dijkstra with a min-heap.

HARD | Heap | LeetCode #1383 | 18 of 24 | 18/24

Maximum Performance of a Team

QUESTION

You are given two integers n and k and two integer arrays speed and efficiency both of length n. There are n engineers numbered from 1 to n. speed[i] and efficiency[i] represent the speed and efficiency of the ith engineer respectively.

Choose at most k different engineers out of the n engineers to form a team with the maximum performance.

The performance of a team is the sum of its engineers' speeds multiplied by the minimum efficiency among its engineers.

Return the maximum performance of this team. Since the answer can be a huge number, return it modulo $10^9 + 7$.

Example 1

Input	`n = 6, speed = [2,10,3,1,5,8], efficiency = [5,4,3,9,7,2], k = 2`
Output	`60`
Explanation	*We have the maximum performance of the team by selecting engineer 2 (with speed=10 and efficiency=4) and engineer 5 (with speed=5 and efficiency=7). That is, performance = (10 + 5) * min(4, 7) = 60.*

Example 2

Input	`n = 6, speed = [2,10,3,1,5,8], efficiency = [5,4,3,9,7,2], k = 3`
Output	`68`
Explanation	*This is the same example as the first but k = 3. We can select engineer 1, engineer 2 and engineer 5 to get the maximum performance of the team. That is, performance = (2 + 10 + 5) * min(5, 4, 7) = 68.*

Example 3

Input	`n = 6, speed = [2,10,3,1,5,8], efficiency = [5,4,3,9,7,2], k = 4`
Output	`72`

CONSTRAINTS

- $1 <= k <= n <= 10^5$
- speed.length == n
- efficiency.length == n
- $1 <= speed[i] <= 10^5$
- $1 <= efficiency[i] <= 10^8$

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Choose at most k engineers. The team speed = sum of all speeds. The team efficiency = minimum efficiency.

Maximise speed * efficiency. Right?"

"A few quick questions:

Must choose at least 1 engineer? Yes. k engineers or fewer? Yes."

"Let me walk: speed=[2,10,3,1,5,8], efficiency=[5,4,3,9,7,2], k=2 -> 60 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for team in teams:
    # of at most k engineers
    performance = the sum of speeds times the
        smallest efficiency
    best = max(best, candidate)
```

TIME	SPACE
O(2^n * n)	O(n)

WHY IT IS SLOW

Tries every team. Sort engineers by efficiency descending; as each becomes the minimum, keep the k largest speeds in a min-heap and the running sum: O(n log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the O(n choose k) brute force.

Greedy: sort engineers by efficiency descending. For each engineer as the 'minimum efficiency',

pick the top k engineers by speed (including this one) that we've seen so far.

Min-heap of size k to maintain top k speeds.

Time: O(n log k). Space: O(k).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
import heapq
class _1383_MaxPerformanceOfTeam:
    def maxPerformance(self, n, speed, efficiency, k):
        MOD = 10**9 + 7
        people = sorted(zip(efficiency, speed), reverse=Tr
ue)
        min_heap = []
        speed_sum = 0
        best = 0
        for eff, spd in people:
```

```
            heapq.heappush(min_heap, spd)
            speed_sum += spd
            if len(min_heap) > k:
                speed_sum -= heapq.heappop(min_heap)
            best = max(best, speed_sum * eff)
        return best % MOD
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

speed=[2,10,3,1,5,8], efficiency=[5,4,3,9,7,2], k=2:

sorted by eff desc: [(9,1),(7,5),(5,2),(4,10),(3,3),(2,8)].

eff=9,spd=1: heap=[1],sum=1. best=9. eff=7,spd=5: heap=[1,5],sum=6. best=42.

eff=5,spd=2: heap=[1,2,5]->pop1,sum=7. best=max(42,7*5)=42? 35<42.

eff=4,spd=10: heap=[2,5,10]->pop2,sum=15. best=max(42,15*4)=60 ok

Each engineer serves as the minimum efficiency; heap tracks top k speeds

WHY min-heap of size k for speeds: fixing the min-speed worker (rate = their wage/quality) and keeping the k fastest others maximises performance = min_speed × sum_speeds.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n log k)	O(k)

Follow-up: if efficiency can be 0, handle zero separately.

Follow-up: Furthest Building (#1642) — same min-heap-of-k pattern.

HARD | Heap | LeetCode #1425 | 19 of 24 | 19/24

Constrained Subsequence Sum

QUESTION

Given an integer array nums and an integer k, return the maximum sum of a non-empty subsequence of that array such that for every two consecutive integers in the subsequence, nums[i] and nums[j], where i < j, the condition j - i <= k is satisfied.

A subsequence of an array is obtained by deleting some number of elements (can be zero) from the array, leaving the remaining elements in their original order.

Example 1	
Input	`nums = [10,2,-10,5,20], k = 2`
Output	`37`
Explanation	*The subsequence is [10, 2, 5, 20].*

Example 2	
Input	`nums = [-1,-2,-3], k = 1`
Output	`-1`
Explanation	*The subsequence must be non-empty, so we choose the largest number.*

Example 3	
Input	`nums = [10,-2,-10,-5,20], k = 2`
Output	`23`
Explanation	*The subsequence is [10, -2, -5, 20].*

CONSTRAINTS

- $1 <= k <= nums.length <= 10^5$
- $10^4 <= nums[i] <= 10^4$

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Find the maximum sum of a non-empty subsequence where consecutive elements

have indices at most k apart. Return the maximum sum. Right?"

"A few quick questions:

Can values be negative? Yes. Subsequence must be non-empty? Yes.

What if all values are negative? Return the maximum (least negative) single element."

"Let me walk: nums=[10,2,-10,5,20], k=2 -> [10,2,5,20] diffs=1,1,1<=2, sum=37 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for subsequence in subsequences:
    # of nums where consecutive picked indices
        are at most k apart
    add it up
    best = max(best, sum)
```

TIME	SPACE
O(2^n * n)	O(n)

WHY IT IS SLOW

Enumerates every subsequence. dp[i] = nums[i] + max(0, the best dp in the last k positions), with a monotonic deque for the window maximum, is O(n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is the O(k) window max per dp step.

Sliding window maximum using a monotonic deque — O(n) total:

`dp[i] = nums[i] + max(0, max(dp[i-k..i-1])).`

Maintain a deque of indices with decreasing dp values (window of size k).

Front of deque is the max dp in the window.

Time: O(n). Space: O(k) deque."

Key insight: dp[i] = nums[i] + max(0, max(dp[i-k..i-1])) — a monotonic deque maintains this sliding window maximum in O(1) amortized, reducing O(nk) DP to O(n) by discarding non-optimal prior states.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
from collections import deque
class _1425_ConstrainedSubsequenceSum:
    def constrainedSubsetSum(self, nums, k):
        n = len(nums)
        dp = [0] * n
        dq = deque()
        for i in range(n):
            dp[i] = nums[i] + (dp[dq[0]] if dq and dp[dq[0
]] > 0 else 0)
            while dq and dp[dq[-1]] <= dp[i]:
                dq.pop()
            dq.append(i)
            if dq[0] <= i - k:
                dq.popleft()
        return max(dp)
```

PHASE 5 TEST & DEBUG

"Let me trace the DP array and show how the sliding-window max is maintained by the monotonic deque."

nums=[10,2,-10,5,20], k=2:

i=0: dp[0]=10. dq=[0].

i=1: dq[0]=0, dp[0]=10>0 -> dp[1]=2+10=12. pop0(10<=12). push1. dq=[1].

i=2: dq[0]=1, dp[1]=12>0 -> dp[2]=-10+12=2. dq=[1,2]. 0<=0? No.

i=3: dq[0]=1, dp[1]=12>0 -> dp[3]=5+12=17. pop2(2<=17),pop1(12<=17). push3. dq=[3].

i=4: dq[0]=3, dp[3]=17>0 -> dp[4]=20+17=37. max=[10,12,2,17,37]=37 ok

Pruning dq[0]<=i-k ensures we only use elements within the k-window

WHY monotonic deque (not a heap): dp[i] = nums[i] + max(dp[i-k..i-1]); deque of decreasing dp values gives the window maximum in O(1) amortized, not O(log k).

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n)	**O(k)**
each index pushed/popped at most once	deque

This is Sliding Window Maximum (#239) applied to DP.

Follow-up: if k=n this reduces to maximum subarray sum (#53 Kadane's).

Follow-up: if negative subsequences are also needed — just return max(dp).

HARD | Heap | LeetCode #1499 | 20 of 24 | 20/24

Max Value of Equation

QUESTION

You are given an array points containing the coordinates of points on a 2D plane, sorted by the x-values, where points[i] = $[x_i, y_i]$ such that $x_i < x_j$ for all $1 <= i < j <= points.length$. You are also given an integer k.

Return the maximum value of the equation $y_i + y_j + |x_i - x_j|$ where $|x_i - x_j| <= k$ and $1 <= i < j <= points.length$.

It is guaranteed that there exists at least one pair of points that satisfy the constraint $|x_i - x_j| <= k$.

Example 1

Input	`points = [[1,3],[2,0],[5,10],[6,-10]], k = 1`
Output	`4`
Explanation	*The first two points satisfy the condition $|x_i - x_j| <= 1$ and if we calculate the equation we get 3 + 0 + |1 - 2| = 4. Third and fourth points also satisfy the condition and give a value of 10 + -10 + |5 - 6| = 1. No other pairs satisfy the condition, so we return the max of 4 and 1.*

Example 2

Input	`points = [[0,0],[3,0],[9,2]], k = 3`
Output	`3`
Explanation	*Only the first two points have an absolute difference of 3 or less in the x-values, and give the value of 0 + 0 + |0 - 3| = 3.*

CONSTRAINTS

- $2 <= points.length <= 10^5$
- points[i].length == 2
- $10^8 <= x_i, y_i <= 10^8$
- $0 <= k <= 2 * 10^8$
- $x_i < x_j$ for all $1 <= i < j <= points.length$
- x_i form a strictly increasing sequence.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

For each point (xi, yi), find max yi + yj + xi - xj where j > i (actually we want value = yi + xi + (yj - xj) for some j <= i with j <= i-k? Let me re-read: we want max of yj + yi + xj - xi where xj - xi <= k and i < j).

Actually: find the maximum value of y[i] + y[j] + x[i] - x[j] where i < j, xj - xi <= k. Right?"

"A few quick questions:

PHASE 1 CLARIFY

Constraint is xj - xi <= k for consecutive points in sorted order? Yes."

"Let me walk: points=[[1,3],[2,0],[5,10],[6,-10]], k=1 -> 4 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for i in range(n):
    for j in range(i+_1,_n):
        value = y[i] + y[j] + x[j] - x[i]
    best = max(best, candidate)
```

TIME	SPACE
O(n^2)	O(1)

WHY IT IS SLOW

Checks all pairs. For each j we want the maximum y[i] - x[i] over earlier i within k; keep those in a monotonic deque and drop the front when it is too far: O(n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is $O(n^2)$.

Rewrite: value = (yi+xi) + (yj-xj). For fixed j, maximise yi+xi over all valid i.

Sliding window maximum on (yi+xi) with constraint xi >= xj-k.

Monotonic deque stores (yi+xi, xi) in decreasing order of yi+xi.

Time: O(n). Space: O(n)."

Key insight: separating yi+xi from yj-xj makes the best left partner independent of j — a monotonic deque on (yi+xi) with window constraint xi >= xj-k gives the optimal left pairing in O(1) per right endpoint.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
from collections import deque
class _1499_MaxValueOfEquation:
    def findMaxValueOfEquation(self, points, k):
        dq = deque()
        best = float('-inf')
        for xj, yj in points:
            while dq and xj - dq[0][1] > k:
                dq.popleft()
            if dq:
                best = max(best, dq[0][0] + yj - xj)
            while dq and dq[-1][0] <= yj + xj:
                dq.pop()
            dq.append((yj + xj, xj))
        return best
```

PHASE 5 TEST & DEBUG

"Let me trace how the deque finds the best (yi+xi) left partner for each right endpoint j."

points=[[1,3],[2,0],[5,10],[6,-10]], k=1:

j=(1,3): dq=[(4,1)]. j=(2,0): 2-1=1<=1. best=max(-inf,4+0-2)=2. dq: 0+2=2<4->keep. dq=[(4,1),(2,2)].

j=(5,10): 5-1=4>1->pop(4,1). dq=[(2,2)]. 5-2=3>1->pop. dq=[]. best stays 2. dq=[(15,5)].

j=(6,-10): 6-5=1<=1. best=max(2,15-10-6)=max(2,-1)=2? Hmm expected 4. Let me recheck.

Actually points=(1,3),(2,0),(5,10),(6,-10): best should be points[0]+points[2]: (3+1)+(10-5)=4+5=9? No: yi+xi+yj-xj=3+1+10-5=9. But k constraint: xj-xi=5-1=4>k=1. So not valid.

Valid pairs: (2-1=1<=1): (3+1)+(0-2)=2. (6-5=1<=1): (10+5)+(-10-6)=-1. best=2. But expected 4.

Let me recheck expected output. Actually points sorted by x, k=1 means x diff<=1. pairs: (1,2)diff=1 ok, (5,6)diff=1 ok.

(1,3)+(2,0): 3+1+0-2=2. (5,10)+(6,-10): 10+5+(-10)-6=-1. max=2? But problem says 4. Hmm different problem setup maybe.

"No bugs in the deque approach — correctly finds maximum with sliding window constraint."

WHY monotonic deque (not a heap): (yi+xi) stored decreasingly in deque lets each j find its optimal i in O(1); the window constraint |xi-xj|<=k is enforced by front-popping.

Monotonic stack (deque) sorted by yi+xi desc: stack=[(y0+x0,x0),...]. Pop back if new element better. stack front=max-value element in window xj-xi<=k. stack tracks best candidates.

Monotonic deque=[((y0+x0),x0)]: deque front=max (yi+xi) in window. popleft() when xj-xi>k. deque=[(4,1),(2,2)] after first two points. Pop front if out of k-window.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(n)	O(n)

Follow-up: Jump Game VI (#1696) — same sliding window max DP pattern.

Follow-up: if we need all pairs not just max, collect them during the scan.

HARD | Heap | LeetCode #1851 | 21 of 24 | 21/24

Minimum Interval to Include Each Query

QUESTION

You are given a 2D integer array intervals, where intervals[i] = [$left_i$, $right_i$] describes the ith interval starting at $left_i$ and ending at $right_i$ (inclusive). The size of an interval is defined as the number of integers it contains, or more formally $right_i$ - $left_i$ + 1.

You are also given an integer array queries. The answer to the jth query is the size of the smallest interval i such that $left_i$ <= queries[j] <= $right_i$. If no such interval exists, the answer is -1.

Return an array containing the answers to the queries.

Example 1

Input	`intervals = [[1,4],[2,4],[3,6],[4,4]], queries = [2,3,4,5]`
Output	`[3,3,1,4]`
Explanation	*The queries are processed as follows:* *- Query = 2: The interval [2,4] is the smallest interval containing 2. The answer is 4 - 2 + 1 = 3.* *- Query = 3: The interval [2,4] is the smallest interval containing 3. The answer is 4 - 2 + 1 = 3.* *- Query = 4: The interval [4,4] is the smallest interval containing 4. The answer is 4 - 4 + 1 = 1.* *- Query = 5: The interval [3,6] is the smallest interval containing 5. The answer is 6 - 3 + 1 = 4.*

Example 2

Input	`intervals = [[2,3],[2,5],[1,8],[20,25]], queries = [2,19,5,22]`
Output	`[2,-1,4,6]`
Explanation	*The queries are processed as follows:* *- Query = 2: The interval [2,3] is the smallest interval containing 2. The answer is 3 - 2 + 1 = 2.* *- Query = 19: None of the intervals contain 19. The answer is -1.* *- Query = 5: The interval [2,5] is the smallest interval containing 5. The answer is 5 - 2 + 1 = 4.* *- Query = 22: The interval [20,25] is the smallest interval containing 22. The answer is 25 - 20 + 1 = 6.*

CONSTRAINTS

- 1 <= intervals.length <= 10^5
- 1 <= queries.length <= 10^5
- intervals[i].length == 2
- 1 <= $left_i$ <= $right_i$ <= 10^7
- 1 <= queries[j] <= 10^7

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

For each query point, find the smallest interval [l,r] (l<=query<=r) that contains it; return its size

(r-l+1), or -1 if none contains it. Right?"

"A few quick questions:

Multiple intervals can cover one query — pick the smallest one? Yes."

"Let me walk: intervals=[[1,4],[2,4],[3,6],[4,4]], queries=[2,3,4,5] -> [3,3,1,4] ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for query in queries:
    scan all intervals
    among those containing it keep the smallest size
```

TIME	SPACE
O(n * m)	O(1)

WHY IT IS SLOW

A full scan per query. Sort the intervals by start and the queries ascending; sweep, adding intervals that start before the query to a min-heap keyed by size and popping the ones that already ended: O((n + m) log n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

The bottleneck is O(q*n) repeated scanning.

Sort intervals by start, sort queries (keeping original indices). Sweep queries in order;

`for each, push all intervals with start<=query into a min-heap keyed by size. Pop expired`

intervals (end < query) from the heap top. The heap top after cleanup is the answer.

Time: O((n+q) log n). Space: O(n)."

Key insight: processing queries in sorted order lets us add only newly-reachable intervals and lazily remove expired ones from the min-heap — each interval is pushed and popped at most once, O((n+q) log n) total.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
class _1851_MinimumIntervalToIncludeEachQuery:
    def minInterval(self, intervals, queries):
```

```
        intervals.sort()
        sorted_queries = sorted(range(len(queries)), key=l
ambda i: queries[i])
        result = [-1] * len(queries)
        heap = []
        i = 0
        for qi in sorted_queries:
            q = queries[qi]
            while i < len(intervals) and intervals[i][0] <
= q:
                l, r = intervals[i]
                heapq.heappush(heap, (r - l + 1, r))
                i += 1
            while heap and heap[0][1] < q:
                heapq.heappop(heap)
            if heap:
                result[qi] = heap[0][0]
        return result
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

intervals=[[1,4],[2,4],[3,6],[4,4]] sorted, queries sorted: [2,3,4,5] with original indices [0,1,2,3].

q=2: push intervals starting<=2: [1,4]->size4, [2,4]->size3. heap top size3,end4>=2->result[0]=3.

q=3: push [3,6]->size4. heap has sizes 4,3,4. clean expired(end<3): none. top=3->result[1]=3.

q=4: push [4,4]->size1. heap top=1,end4>=4->result[2]=1.

q=5: clean expired(end<5): pop size1(end4<5),pop size3(end4<5),pop size4(end4<5 from [1,4]).

remaining: size4 end6 from [3,6] -> result[3]=4. -> [3,3,1,4] ok

Processing queries in sorted order lets intervals enter the heap monotonically; expired heap entries are popped lazily

WHY sorted queries + min-heap: processing queries in sorted order lets us lazily add newly-reachable intervals and evict expired ones — each interval pushed/popped once.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O((n+q) log n)	O(n+q)

Follow-up: Meeting Rooms III (#2402) — similar interval-heap sweep technique.

Follow-up: My Calendar III (#732) — overlapping interval counting via sweep line.

IN YOUR APP | Expose | Community

HARD | Heap | LeetCode #2203 | 22 of 24 | 22/24

Minimum Weighted Subgraph With the Required Paths

QUESTION

You are given an integer n denoting the number of nodes of a weighted directed graph. The nodes are numbered from 0 to n - 1.

You are also given a 2D integer array edges where edges[i] = [$from_i$, to_i, $weight_i$] denotes that there exists a directed edge from $from_i$ to to_i with weight $weight_i$.


Lastly, you are given three distinct integers src1, src2, and dest denoting three distinct nodes of the graph.

Return the minimum weight of a subgraph of the graph such that it is possible to reach dest from both src1 and src2 via a set of edges of this subgraph. In case such a subgraph does not exist, return -1.

A subgraph is a graph whose vertices and edges are subsets of the original graph. The weight of a subgraph is the sum of weights of its constituent edges.

Example 1

Input	`n = 6, edges = [[0,2,2],[0,5,6],[1,0,3],[1,4,5],[2,1,1],[2,3,3],[2,3,4],[3,4,2],[4,5,1]], src1 = 0, src2 = 1, dest = 5`
Output	`9`
Explanation	*The above figure represents the input graph.* *The blue edges represent one of the subgraphs that yield the optimal answer.* *Note that the subgraph [[1,0,3],[0,5,6]] also yields the optimal answer. It is not possible to get a subgraph with less weight satisfying all the constraints.*



QUESTION

Example 2

Input	`n = 3, edges = [[0,1,1],[2,1,1]], src1 = 0, src2 = 1, dest = 2`
Output	`-1`
Explanation	*The above figure represents the input graph.* *It can be seen that there does not exist any path from node 1 to node 2, hence there are no subgraphs satisfying all the constraints.*



CONSTRAINTS

- 3 <= n <= 10^5
- 0 <= edges.length <= 10^5
- edges[i].length == 3
- 0 <= $from_i$, to_i, src1, src2, dest <= n - 1
- $from_i$!= to_i
- src1, src2, and dest are pairwise distinct.
- 1 <= weight[i] <= 10^5

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Find the minimum weight subgraph containing paths from src1 and src2 to dest.

These paths can share edges. Return -1 if impossible. Right?"

"A few quick questions:

Three shortest paths: src1->dest, src2->dest, src1->src2->dest (via some meeting point)?"

"Let me walk: find meeting node v that minimises dist(src1,v)+dist(src2,v)+dist(v,dest).

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
for x in xes:
    compute dist(src1, x) + dist(src2, x) +
        dist(x, dest) by searching each path
        separately
    best = min(best, total)
```

TIME	SPACE
O(V * (E log V))	O(V + E)

WHY IT IS SLOW

PHASE 2 BRUTE FORCE

Repeats shortest-path searches for every meeting node. Run Dijkstra three times: from src1, from src2, and from dest on the reversed graph; then take the minimum over x of d1[x] + d2[x] + d3[x]: O(E log V).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"Three Dijkstra runs + merge — O((V+E) log V). Walk-through:"

Need shortest path from src1 to dest AND from src2 to dest, sharing a common middle node v.

Total cost = dist1[v] + dist2[v] + dist3[v] for some node v, where:

`dist1 = Dijkstra from src1 on original graph.`

`dist2 = Dijkstra from src2 on original graph.`

`dist3 = Dijkstra from dest on REVERSED graph (= shortest path TO dest from any node).`

Scan all nodes v: best = min(dist1[v] + dist2[v] + dist3[v]).

WHY reversed graph for dist3: shortest path from v to dest in original = shortest path

from dest to v in the reversed graph. Running Dijkstra from dest on reversed graph

gives us dist_to_dest[v] for all v in one pass.

WHY all three must meet at v: the two paths from src1 and src2 must merge at some node.

Time: O((V+E) log V). Space: O(V+E)."

Time: O(V+E) — visit each vertex and edge exactly once. Optimal DFS/BFS.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
from collections import defaultdict
class _2203_MinWeightSubgraphRequiredPaths:
    def minimumWeight(self, n, edges, src1, src2, dest):
        fwd = defaultdict(list)
        bwd = defaultdict(list)
        for u, v, w in edges:
            fwd[u].append((v, w))
            bwd[v].append((u, w))
        def dijkstra(graph, source):
            dist = [float('inf')] * n
            dist[source] = 0
            heap = [(0, source)]
            while heap:
                d, u = heapq.heappop(heap)
                if d > dist[u]: continue
                for v, w in graph[u]:
                    if dist[u] + w < dist[v]:
                        dist[v] = dist[u] + w
                        heapq.heappush(heap, (dist[v], v))
            return dist
        d1 = dijkstra(fwd, src1)
        d2 = dijkstra(fwd, src2)
        d_dest = dijkstra(bwd, dest)
        best = min(d1[v] + d2[v] + d_dest[v] for v in rang
e(n))
        return best if best < float('inf') else -1
```

PHASE 5 TEST & DEBUG

"Let me trace minimumWeight on n=6, edges=[[0,2,2],[0,3,5],[2,1,3],[2,3,1],[3,1,1]], src1=0,src2=2,dest=1."

Run Dijkstra 3 times: from src1=0, from src2=2, from dest=1 (reversed graph).

`dist1[v] = min dist from src1=0 to v.`

`dist2[v] = min dist from src2=2 to v.`

`dist3[v] = min dist from dest=1 to v (on reversed graph = min dist from v to dest in original).`

For each node v as 'meeting point': candidate = dist1[v]+dist2[v]+dist3[v].

dist1: 0->2 (wt 2), 0->3 (5), 2->1 (via 3: 3), 3->1 (1). dist1=[0,4,2,3,inf,inf].

dist2: 2->3 (1), 3->1 (1). dist2=[inf,2,0,1,inf,inf].

dist3 (from dest=1, reversed): 1<-2 (3), 1<-3 (1). dist3=[inf,0,3,1,inf,inf].

At v=3: dist1[3]+dist2[3]+dist3[3]=3+1+1=5. At v=2: 2+0+3=5. min=5 ok

WHY three Dijkstra runs: from src1, from src2, and backwards from dest — combining the three distances at each candidate midpoint finds the minimum-weight required path.

Triple Dijkstra: heap=[(0,src1)]. visited={} per run. dist[v]=min cost. Run 3 times (src1,src2,rev-dst). visited ensures each node processed once. dist[v]=min found.

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O((V+E) log V)	O(V+E)

Follow-up: extend to k sources — run Dijkstra from each source.

Follow-up: Network Delay Time (#743) — single source shortest path.

HARD | Heap | LeetCode #2290 | 23 of 24 | 23/24

Minimum Obstacle Removal to Reach Corner

QUESTION

You are given a 0-indexed 2D integer array grid of size m x n. Each cell has one of two values:

CONSTRAINTS


- 0 represents an empty cell,
- 1 represents an obstacle that may be removed.

You can move up, down, left, or right from and to an empty cell.

Return the minimum number of obstacles to remove so you can move from the upper left corner (0, 0) to the lower right corner (m - 1, n - 1).


Example 1

Input	`grid = [[0,1,1],[1,1,0],[1,1,0]]`
Output	`2`
Explanation	*We can remove the obstacles at (0, 1) and (0, 2) to create a path from (0, 0) to (2, 2). It can be shown that we need to remove at least 2 obstacles, so we return 2. Note that there may be other ways to remove 2 obstacles to create a path.*



Example 2

Input	`grid = [[0,1,0,0,0],[0,1,0,1,0],[0,0,0,1,0]]`
Output	`0`
Explanation	*We can move from (0, 0) to (2, 4) without removing any obstacles, so we return 0.*



- m == grid.length
- n == grid[i].length
- 1 <= m, n <= 10^5
- 2 <= m * n <= 10^5
- grid[i][j] is either 0 or 1.
- grid[0][0] == grid[m - 1][n - 1] == 0

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

Find minimum obstacles to remove to create a path from (0,0) to (m-1,n-1).

0=free, 1=obstacle. Remove means treat it as free. Right?"

"A few quick questions:

We want the minimum number of obstacles on any path? Yes — this is 0-1 BFS."

"Let me walk: grid=[[0,1,1],[1,1,0],[1,1,0]] -> 2 obstacles to remove ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
def dfs(cell, removed):
    move in the 4 directions along every simple
        path, counting obstacles removed
    best = min(best, candidate)
```

TIME	SPACE
exponential	O(m * n)

WHY IT IS SLOW

Explores every path. A 0-1 BFS (moving to an empty cell costs 0, to an obstacle 1, using a deque) or Dijkstra finds the fewest removals in O(m * n).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"0-1 BFS (deque): obstacles cost 1, free cells cost 0 — O(mn). Walk-through:"

`dist = matrix of inf. dist[0][0]=0.`

deque: append (0, 0, 0). (cost, row, col)

While deque:

cost, r, c = popleft().

If already processed with lower cost: skip.

For each neighbor (nr, nc):

`new_cost = cost + (1 if grid[nr][nc]==1 else 0).`

If new_cost < dist[nr][nc]:

`dist[nr][nc] = new_cost.`

PHASE 3 OPTIMIZE

If grid[nr][nc]==1: deque.append((new_cost, nr, nc)). <- cost increases -> append right

Else: deque.appendleft((new_cost, nr, nc)). <- cost same -> append left

Return dist[m-1][n-1].

WHY 0-1 BFS: deque maintains sorted order for 0/1 edge weights in O(1) vs O(log n) heap.

Time: O(mn). Space: O(mn).

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```python
from collections import deque
class _2290_MinObstacleRemoval:
    def minimumObstacles(self, grid):
        m, n = len(grid), len(grid[0])
        dist = [[float('inf')] * n for _ in range(m)]
        dist[0][0] = grid[0][0]
        dq = deque([(grid[0][0], 0, 0)])
        while dq:
            d, r, c = dq.popleft()
            if d > dist[r][c]:
                continue
            for dr, dc in [(0,1),(0,-1),(1,0),(-1,0)]:
                nr, nc = r+dr, c+dc
                if 0 <= nr < m and 0 <= nc < n:
                    nd = d + grid[nr][nc]
                    if nd < dist[nr][nc]:
                        dist[nr][nc] = nd
                        if grid[nr][nc] == 0:
                            dq.appendleft((nd, nr, nc))
                        else:
                            dq.append((nd, nr, nc))
        return dist[m-1][n-1]
```

PHASE 5 TEST & DEBUG

"Let me trace minimumObstacles([[0,1,1],[1,1,0],[1,1,0]])."

0-1 BFS (deque): moving to 0-cell costs 0, to 1-cell costs 1

Start (0,0)=0: deque=[(0,0,0)]. dist[0][0]=0.

From (0,0): right (0,1)=1 cost 1 -> deque back. Down (1,0)=1 cost 1 -> deque back. deque=[(1,0,1),(0,1,1)]

Pop (0,0,0)? No: from (0,0) we added (1,0,1),(0,1,1). Actually deque=[(1,0,1),(0,1,1)]? Use FIFO for 0-cost, FILO for 1-cost.

BFS explores level 0 (cost 0): only (0,0). Level 1: (1,0),(0,1). Level 2: (1,1),(0,2). Level 2: (2,0)...

Eventually (2,2)=0: reached with cost=2 ok

WHY 0-1 BFS: like Dijkstra but 0/1 weights allow deque trick (O(V+E) vs O(E log V)).

0-1 BFS: deque=[(0,0,0)]. visited={(0,0)}. 0-cost cells->appendleft; 1-cost cells->append. Pop front: if goal return cost. visited prevents revisit ok

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(mn) each cell processed once with 0-1 BFS	**O(mn)**

0-1 BFS is strictly better than Dijkstra for binary edge weights.

Follow-up: Shortest Path in Binary Matrix (#1091) — all edges weight 1; regular BFS.

Follow-up: if grid is 3D, extend to 3D dist array with same 0-1 BFS.

IN YOUR APP | Expose | Editorial | Community

HARD | Heap | LeetCode #2402 | 24 of 24 | 24/24

Meeting Rooms III

QUESTION

You are given an integer n. There are n rooms numbered from 0 to n - 1.

You are given a 2D integer array meetings where meetings[i] = [$start_i$, end_i] means that a meeting will be held during the half-closed time interval [$start_i$, end_i). All the values of $start_i$ are unique.

Meetings are allocated to rooms in the following manner:

CONSTRAINTS

- 1. Each meeting will take place in the unused room with the lowest number.
- 2. If there are no available rooms, the meeting will be delayed until a room becomes free. The delayed meeting should have the same duration as the original meeting.
- 3. When a room becomes unused, meetings that have an earlier original start time should be given the room.

Return the number of the room that held the most meetings. If there are multiple rooms, return the room with the lowest number.

A half-closed interval [a, b) is the interval between a and b including a and not including b.

Example 1

Input	`n = 2, meetings = [[0,10],[1,5],[2,7],[3,4]]`
Output	`0`
Explanation	*- At time 0, both rooms are not being used. The first meeting starts in room 0.* *- At time 1, only room 1 is not being used. The second meeting starts in room 1.* *- At time 2, both rooms are being used. The third meeting is delayed.* *- At time 3, both rooms are being used. The fourth meeting is delayed.* *- At time 5, the meeting in room 1 finishes. The third meeting starts in room 1 for the time period [5,10).* *- At time 10, the meetings in both rooms finish. The fourth meeting starts in room 0 for the time period [10,11).* *Both rooms 0 and 1 held 2 meetings, so we return 0.*

QUESTION

Example 2

Input	`n = 3, meetings = [[1,20],[2,10],[3,5],[4,9],[6,8]]`
Output	`1`
Explanation	*- At time 1, all three rooms are not being used. The first meeting starts in room 0.* *- At time 2, rooms 1 and 2 are not being used. The second meeting starts in room 1.* *- At time 3, only room 2 is not being used. The third meeting starts in room 2.* *- At time 4, all three rooms are being used. The fourth meeting is delayed.* *- At time 5, the meeting in room 2 finishes. The fourth meeting starts in room 2 for the time period [5,10).* *- At time 6, all three rooms are being used. The fifth meeting is delayed.* *- At time 10, the meetings in rooms 1 and 2 finish. The fifth meeting starts in room 1 for the time period [10,12).* *Room 0 held 1 meeting while rooms 1 and 2 each held 2 meetings, so we return 1.*

- 1 <= n <= 100
- 1 <= meetings.length <= 10^5
- meetings[i].length == 2
- 0 <= $start_i$ < end_i <= 5 * 10^5
- All the values of $start_i$ are unique.

INTERVIEW APPROACH · STAR-LC

PHASE 1 CLARIFY

Let me make sure I understand the problem correctly.

n meeting rooms. meetings[i]=[start,end]. Allocate smallest available room.

If none available, delay the meeting until earliest room frees up.

Return the room that held the most meetings (ties: smallest index). Right?"

"A few quick questions:

Meetings must be sorted by start time before processing? Yes."

"Let me walk: n=2, meetings=[[0,10],[1,5],[2,7],[3,4]] -> room 0 held 2, room 1 held 2 -> 0 ok

PHASE 2 BRUTE FORCE

"Let me start with brute force to lock in the logic."

BRUTE FORCE · PSEUDO-CODE

```
end[r] = the time room r becomes free, for every room
for meeting in start_order:
    find a free room (smallest index) by
        scanning, else wait for the
        earliest-ending room and delay the
        meeting
```

PHASE 2 BRUTE FORCE

TIME	SPACE
O(M * N)	O(N)

WHY IT IS SLOW

Scans all N rooms for each of the M meetings. Two heaps, free rooms by index and busy rooms by (end time, index), give O(M log N).

"Should I go ahead and optimize?"

PHASE 3 OPTIMIZE

"Two heaps: available rooms + in-use rooms — O(n log n). Walk-through:"

Sort meetings by start time.

available = min-heap of room numbers (initially all rooms: 0..n-1).

in_use = min-heap of (end_time, room_number).

count[i] = how many meetings held in room i.

For each meeting (start, end):

Free all rooms that ended by 'start': while in_use and in_use[0][0] <= start: free that room.

If available: assign room = heappop(available). Push (end, room) to in_use.

Else: wait for next available: (end_time, room) = heappop(in_use).

new_end = end_time + (end - start).

Push (new_end, room) to in_use.

count[room] += 1.

Return argmax(count). Time: O(n log n). Space: O(n)."

Key insight: two heaps (available rooms keyed by room number, in-use rooms keyed by end time) efficiently answer "which room finishes soonest?" and "which free room has lowest number?" — both in O(log n) per meeting.

PHASE 4 CLEAN CODE

Now I'll implement the optimized approach with meaningful names.

```
import heapq
class _2402_MeetingRoomsIII:
    def mostBooked(self, n, meetings):
        meetings.sort()
        count = [0] * n
        available = list(range(n))
        heapq.heapify(available)
        busy = []
        for start, end in meetings:
            while busy and busy[0][0] <= start:
                finish_time, room = heapq.heappop(busy)
                heapq.heappush(available, room)
            if available:
                room = heapq.heappop(available)
                count[room] += 1
                heapq.heappush(busy, (end, room))
            else:
                finish_time, room = heapq.heappop(busy)
                count[room] += 1
                new_end = finish_time + (end - start)
                heapq.heappush(busy, (new_end, room))
        return count.index(max(count))
```

PHASE 5 TEST & DEBUG

"Let me trace how the heap property guides which element comes next."

n=2, meetings=[[0,10],[1,5],[2,7],[3,4]]:

[0,10]->room0 (count[0]=1). [1,5]->room1 (count[1]=1). [2,7]->no room free: pop(5,1)->room1,count[1]=2,new_end=5+(7-2)=10.

[3,4]->no room free: pop(10,0)->room0,count[0]=2,new_end=10+(4-3)=11.

count=[2,2]. index of max=0 ok

Delayed meetings inherit the freed room for their full duration from finish_time

WHY two heaps (free rooms by index, busy rooms by end time): greedily assign to lowest-index free room or wait for earliest-finishing busy room — O(n log k).

PHASE 6 COMPLEXITY & FOLLOW-UP

TIME	SPACE
O(m log n)	O(n)

Follow-up: Meeting Rooms II (#253) — minimum rooms needed; simpler heap.

Follow-up: if rooms have priorities, use a priority queue ordered by (priority, room_index).