## Test 1: Multiple Choice and Fill in the blanks.

Due No due datePoints 20Questions 10

Available Apr 7 at 6:20pm - Apr 7 at 7:30pm about 1 hour Time Limit 20 Minutes

This quiz was locked Apr 7 at 7:30pm.

## **Attempt History**

	Attempt	Time	Score
LATEST	Attempt 1	17 minutes	14 out of 20

(!) Correct answers are no longer available.

Score for this quiz: **14** out of 20 Submitted Apr 7 at 7:04pm This attempt took 17 minutes.

Question 1	2 / 2 pts
What is the display in the following code snippet?	
<pre>enum usc {     scientia,     virtus,     devotio }e; printf("%d", devotio);</pre>	
2	

Question 2 2 / 2 pts

What is the display in the following code snippet?

```
enum usc {
    scientia,
    virtus,
    devotio
}e[3];
printf("%d", sizeof(e));
```

12

Question 3 2 / 2 pts

```
Given a function: void test(int A[], int SIZE) { printf("%d", sizeof(A));
}
```

What is the output if the function call is as follow?

```
int A[] = {1,2,3,4,5};
test(A, 5);
```

8

Incorrect

Question 4 0 / 2 pts

Given the code snippet below, what is the result of the operations?

```
int x[10] = {1,2,3,4,5,6,7,8,9,10};
int y = 20;
int i = 10;
x[i--] = y;
```

```
    x contains {1,2,3,4,5,6,7,8,9,20}
    x contains {1,2,3,4,5,6,7,8,20,10}
    x contains {20,2,3,4,5,6,7,8,9,10}
    It may overwrite memory beyond the array.
```

```
Question 5

typedef struct {
  int arr[10];
}arrStruct;
arrStruct X, Y;

To copy the contents of X to Y:

a) Y = X;
b) memcpy(Y, X, sizeof(arrStruct));
Which of the following statement is valid?

Both a) and b) are correct.

b) is the only correct answer

a) is the only correct answer

Both a) and b) are incorrect
```

Question 6 2 / 2 pts

Which correctly defines the relationship of q and p?

```
struct {
  char a;
  int b;
}*p;
union {
  char a;
  int b;
}*q;

    cannot be determined

   sizeof(q) > sizeof(p)
   sizeof(q) < sizeof(p)</pre>
   sizeof(q) == sizeof(p)
```

## 2 / 2 pts **Question 7**

How many data type(s) is/are defined in the definition below?

```
typedef struct node{
  char a;
  int b;
}*p, q;
```

3

```
Incorrect
```

```
Question 8
                                                               0 / 2 pts
  struct ex{
    float a;
    union{
```

```
struct {
         int number;
         float decimal[2];
      struct {
         double be[2];
         char ce;
     }c;
    }d;
 };
 struct ex val[5];
 struct ex *p = val + 2;
What is the effect of the following statement?
       (--p)->d.b.number = 10;

    Variable number of array component 0 is set to 10

    Variable number of array component 3 is set to 10
    Variable number of array component 1 is set to 10
    Variable number of array component 2 is set to 10
    Run time Error

    Compile Time error
```

## Incorrect

Question 9 0 / 2 pts

What is the minimum number of bytes allocated to any variable of type struct ex?

```
struct ex{
  float a;
  union{
    struct {
      int number;
      float decimal[2];
  }b;
  struct {
      double be[2];
  }
}
```

```
char ce;
}c;
}d;
};

32
```

Quiz Score: 14 out of 20