Munich University of Applied Sciences
Faculty of Computer Science and Mathematics



Master Thesis
for obtaining the academic degree of
Master of Science
in course of studies Computer Science

Observing an Identity Provider from Within: Design, Implementation and Evaluation of a Security Monitoring System for Shibboleth

---

Author:	Tadashi Toyokawa
Matriculation number:	27740221
Submission Date:	4. November 2026
Supervisor:	Prof. Dr.-Ing. Thomas Schreck
Second Supervisor:	Prof. Dr.-Ing. Erik Krempel
Advisor:	Erwin Kupris

I confirm that this master thesis is my own work and I have documented all sources and material used.

Munich, 4. November 2026 Tadashi Toyokawa

Acknowledgments

I would like to express my deepest gratitude to my advisor, Erwin Kupris, my supervisor Prof. Dr.-Ing. Thomas Schreck, and my second supervisor Prof. Dr.-Ing. Erik Krempel, for their invaluable guidance, insightful feedback and continuous support throughout this research. Furthermore, I extend my appreciation to my family and friends for their encouragement and support during this journey. Their motivation and belief in my abilities have been a constant source of strength.

Abstract

An identity provider (IdP) authenticates the users of an organisation across multiple service providers (SPs), so that a single misconfigured or compromised IdP can affect every service its users access. Existing monitoring approaches for IdPs focus on availability rather than on security. This thesis proposes a security monitoring system that observes the Shibboleth IdP from within its application layer. It combines three data sources from the IdP: the audit log, two interceptors that run inside the authentication flow, and the configuration and metadata of the SPs. The records are pseudonymised at their source, sent to a separate backend, correlated with each other and checked against fifteen detection rules. Thirteen of these rules can be traced to documented vulnerabilities and security recommendations.

The evaluation shows that the records of a login can be linked reliably. Where the audit log records the identifier of the request, every record was linked to the correct login. Without this identifier, a fallback based on the pseudonymised user and address also linked every record correctly in all tested scenarios. All rules behaved as specified in tests against a real database, and eleven of them also detected their condition in tests of the complete pipeline. Legitimate logins raised no false alarms. With asynchronous transmission, the interceptors added no measurable login delay but cost about 28 ms of processor time per login.

The work also shows the limitations of monitoring an IdP from within. Attacks that take place at the SP, in the network or with a stolen signing key remain invisible to the system, and an attacker who controls the IdP can suppress the records about their own actions.

Contents

1 Introduction **1**

2 Background **3**
2.1 Technical Foundation of Federated Identity Management 3
2.2 SAML 4
2.2.1 SAML Assertions 4
2.2.2 XML-Signature and Encryption 4
2.2.3 Web Browser SSO Authentication Process 5
2.2.4 SAML Metadata 7
2.3 Shibboleth 7
2.3.1 Profile Flows and Interception Points 8
2.3.2 The Context Tree 8
2.3.3 Audit Logging 8
2.3.4 Configuration 9

3 Related Work **11**
3.1 Security Analyses of SAML and Shibboleth 11
3.2 Monitoring of Applications and Federations 11
3.3 Log Analysis and Log Integrity 13
3.4 Positioning of This Work 14

4 System Design **17**
4.1 Requirements for the System 17
4.2 Overview 18
4.3 Data Aggregation Layer 19
4.3.1 The Audit Logs 20
4.3.2 Metadata and Relying Party File 21
4.3.3 Interceptor 22
4.4 Transport Layer and Trust Boundary 23
4.5 Correlation and Detection Layer 25
4.5.1 Correlation 25
4.5.2 Detection 26
4.5.3 Derivation of the Rules 27
4.5.4 Severity Classification 29
4.6 Visualisation Layer 30
4.7 Design Decisions and Rejected Alternatives 31

5 Implementation **33**
5.1 Data Aggregation Layer 33
5.2 Transport Layer 35

5.3 Correlation and Detection Layer 36
5.3.1 Storage 36
5.3.2 Correlation 36
5.3.3 Detection 38
5.4 Visualisation Layer 40

6 Evaluation **41**
6.1 Test Setup 41
6.2 Correlation 41
6.2.1 Method and Datasets 42
6.2.2 Results 43
6.3 Detection 46
6.3.1 Method and Scenarios 47
6.3.2 Results 48
6.4 Performance Overhead 50
6.4.1 Method and Measurements 51
6.4.2 Results 52
6.5 Defects Found 54
6.6 Threats to Validity 55

7 Discussion **57**
7.1 Interpretation of the Results 57
7.2 Limitations of the Approach 58
7.3 Implications for Future Research 59

8 Conclusion **61**

Bibliography **63**

List of Figures

2.1 SP-initiated SSO with Redirect and POST bindings [41] 6

4.1 UML deployment diagram of the proposed monitoring system 19

List of Tables

3.1 Comparison of the related work 15

4.1 Assignment of the 15 detection rules to documented vulnerabilities and attack classes 28
4.2 Severity assigned by each rule 30

6.1 Datasets of the correlation measurements 44
6.2 Precision of the heuristic strategies per dataset 45
6.3 Precision of `TIME_WINDOW` by distance to the nearest other login at the same SP 45
6.4 Offset between the reception of a report and the event time of its audit entry 46
6.5 End-to-end coverage per rule 49
6.6 Cost of a login per configuration 53
6.7 Defects uncovered by the evaluation 54

Glossary

ACS Assertion Consumer Service.

FIM Federated Identity Management.

HMAC Hash-based Message Authentication Code.

IdP Identity Provider.

LDAP Lightweight Directory Access Protocol.

MFA Multi-Factor Authentication.

OASIS Organization for the Advancement of Structured Information Standards.
OIDC OpenID Connect.

SAML Security Assertion Markup Language.
SIEM Security Information and Event Management.
SP Service Provider.
SSO Single Sign-On.

XSW XML Signature Wrapping.

1 Introduction

Most online services require users to create an account, so that users have to manage a large number of credentials and often reuse the same password for several services [17]. These accounts can be linked to personal data such as an email address, a phone number or even an official identity document. Attackers exploit password reuse by testing large collections of leaked credentials against other services [17], an attack known as credential stuffing. Verizon's 2026 Data Breach Investigations Report shows that this risk is shifting rather than disappearing. Credential abuse, the most common initial access vector of the previous year, is down to 13% of more than 22,000 confirmed breaches, while the exploitation of vulnerabilities has risen to 31% [61].

Federated Identity Management (FIM) addresses the credential side of this risk. It concentrates authentication behind a single trusted authority, the Identity Provider (IdP), so that users can access several Service Providers (SPs) with one set of credentials. When a user wants to access an SP, the SP redirects the user's browser to the IdP. The user authenticates with the IdP, which then confirms the user's identity to the SP [55].

Shibboleth is one of the most widely deployed open-source implementations of FIM in the research and education sector [53]. Its IdP natively supports the Security Assertion Markup Language (SAML), with which an IdP confirms the identity of a user to an SP through signed statements called assertions [41]. OpenID Connect and some OAuth 2.0 features are available through an official plugin [9].

In research and education, Shibboleth IdPs are usually operated within a national federation, for example DFN-AAI [20]. A federation operator registers the IdPs and SPs of all members and publishes their metadata, on which every member relies [40]. DFN-AAI follows a full-mesh architecture, in which every institution operates its own IdP and exchanges messages directly with the SPs of the federation [56]. The IdP of an institution therefore becomes a single point of trust for every SP that its users access. A compromised, misconfigured or vulnerable IdP thus affects not one SP but all of them.

The Sunburst supply chain attack shows the consequences of such a compromise [19]. As Hartl and Derek note, after the initial compromise the attackers obtained the trusted certificate used for signing SAML assertions and used it to access all services within the targeted enterprise [23]. Since tokens forged with this certificate carry the organisation's own trusted signature, the resulting anomalies may go unnoticed [29]. Beyond targeted attacks, an IdP is itself software that is reachable from the internet, and SAML deployments are exposed to weaknesses in the SAML standard and in its implementations. Somorovsky et al. found XML Signature Wrapping (XSW) vulnerabilities in eleven of fourteen SAML frameworks, including Shibboleth, which allow an attacker to inject forged claims that the SP accepts once the signature has been validated [59], and the attack has since been reproduced in other OpenSAML-based setups [26]. In a formal analysis of Shibboleth, Sommer identified three further attacks, namely Response Injection, Leaked Assertion Artifact and IdP Spoofing, which let an attacker log a victim into an account controlled by the attacker

or reuse a leaked artifact to log in as the victim. The Shibboleth developers attribute the first of these to the SAML standard itself rather than to the implementation [58].

Despite this elevated risk profile, systematic security monitoring at the application layer of Shibboleth IdP deployments remains largely absent. Existing approaches such as AAIEye [60] focus primarily on operational availability, leaving security-relevant aspects unaddressed. The research literature reflects a comparable gap. A survey of security analyses in FIM finds that Shibboleth has received little attention compared with other FIM systems and asks whether Shibboleth is more secure or has simply been examined less [55].

This thesis addresses the missing security monitoring with a system that operates directly within the Shibboleth application layer. It makes application-layer security parameters and authentication workflows visible that tools observing the IdP from outside cannot see. Rather than testing the deployment actively, the system observes it passively. This principle has been applied to the eduroam infrastructure by analysing its network traffic [42], whereas this work applies it inside the application. The system thereby provides the operators of an IdP with a continuous view of its security posture. Three research questions guide this work:

- **RQ1:** Which security-relevant data can be collected at the application layer of a Shibboleth IdP, and through which mechanisms are these data accessible?
- **RQ2:** How can these data be correlated in order to detect configuration weaknesses and anomalies in the authentication process?
- **RQ3:** What measurable overhead does the resulting system impose on the monitored IdP?

To answer these questions, the system combines three sources within the IdP whose records can be related to an individual login. Before the records leave the IdP, user names and IP addresses are pseudonymised. A separate backend links the records of each login through the identifier of the request or through the pseudonymised user, address and time. It then checks them against fifteen detection rules, derived mainly from documented vulnerabilities and security recommendations. In a test environment, this linking proved reliable, all rules behaved as specified and the interceptors added no measurable latency to a login.

The remainder of this thesis is structured as follows. Chapter 2 introduces the technical foundations of FIM, SAML and the Shibboleth IdP. Chapter 3 positions this work within existing research on SAML security, application-level intrusion detection, federation monitoring and log integrity. Chapter 4 derives the requirements and presents the architecture of the system, and Chapter 5 describes its implementation layer by layer. Chapter 6 evaluates the correlation, the detection rules and the overhead of the system. Chapter 7 interprets the results with respect to the research questions and discusses the limitations of the approach, before Chapter 8 concludes the thesis.

2 Background

This chapter explains the key concepts and terminology relevant to this thesis and establishes the technical foundation required for the design of the proposed monitoring tool. It is limited to the aspects on which the later chapters build, and consequently covers neither the full range of the SAML specification nor the complete configuration surface of the Shibboleth IdP.

2.1 Technical Foundation of Federated Identity Management

As introduced in Chapter 1, FIM allows users to access resources with a single digital identity and provides Single Sign-On (SSO) functionality across the applications of an organisation. The immediate benefit is convenience, since users no longer need to create and remember a separate set of credentials for every service. The more consequential benefit lies elsewhere. Because credentials exist in one place rather than in every participating service, the number of systems that store and verify them is reduced, since the SP neither verifies the user's authenticators itself nor needs to issue its own [36]. The strength of authentication is consequently also determined in one place. An SP can require a minimum authentication assurance level, which the IdP fulfils and reports in the assertion [36], and from the second level upwards this requires two distinct authentication factors [35]. Concentrating authentication at one well-managed site also focuses administrative effort. It also makes Multi-Factor Authentication (MFA) more acceptable to users, since with single sign-on they are asked for the second factor once per session at the IdP rather than at every service [21]. Administration follows the same pattern, since accounts are created, modified and revoked centrally rather than in each service individually.

This centralisation introduces a new risk in return. Every SP that accepts the assertions of an IdP relies on it to authenticate users correctly. Concentrating credentials in one place also concentrates the consequences of a compromise, since an attacker who gains control of the IdP can potentially authenticate as any of its users at the services that rely on it [56].

Both the IdP and the SP have to maintain a high level of security [36]. The policies defined for each SP in the IdP must accurately translate to the rules at the corresponding SP. The configuration of the IdP and that of each SP must remain consistent with one another. Certificates, keys and protocol settings are maintained separately on both sides, and a mismatch between them can weaken the security of a transaction without either party noticing. To better understand the interaction within a federated identity system, the roles and responsibilities of the IdP and SP are described in the following.

A federation consists of two kinds of participants. The IdP authenticates users and issues statements about them [41]. The SP offers the resource a user wants to reach and relies on those statements instead of authenticating the user itself. Since it relies on the statements of the IdP, the SP is also referred to as the relying party. Neither role is meaningful without the other, and their interaction follows a fixed pattern.

This division has a consequence for how a federation is configured. Because the IdP serves many SPs, it does not treat them uniformly. It maintains a separate configuration for each partner, specifying for instance whether the statement is to be encrypted, which authentication methods are permitted and which attributes are released. The SP maintains its own configuration in turn, stating what it expects to receive and what it will accept.

Both sides therefore hold configuration that describes the same relationship, and both are maintained independently. What binds them together is the metadata each party publishes about itself. This includes the endpoints at which it can be reached, and the certificates by which its statements can be verified. Trust within a federation rests on this metadata being current and correctly exchanged [16]. Whether the two configurations remain consistent with one another, however, is not something the SAML standard itself verifies.

2.2 SAML

SAML is an XML-based standard developed by the Organization for the Advancement of Structured Information Standards (OASIS) for the exchange of authentication, authorisation and other security-related information between different parties. SAML is a fundamental component of FIM and is widely used to enable SSO across organisational and security boundaries [41]. The current version, SAML 2.0, was published in March 2005 and consolidated earlier approaches, among them the Shibboleth architecture [37].

2.2.1 SAML Assertions

SAML assertions serve as security tokens that convey security-related information about a principal, such as a user, system or service. An assertion contains statements made by an issuer about the principal, which may include authentication, authorisation and attribute information. Since these statements can have security-critical implications, their authenticity and integrity must be ensured [15]. Therefore, the assertion can be protected by a digital signature following the XML Signature standard, allowing a relying party to verify that the assertion was issued by the stated issuer and has not been modified [59].

Each assertion contains metadata that defines its origin and validity. The `Issuer` element identifies the entity that issued the assertion, while the `IssueInstant` attribute specifies the time at which it was issued. Furthermore, every assertion is assigned a unique identifier that must not be reused. Once an assertion has been issued, the issuer has no direct control over its subsequent use. Consequently, a consumer of an assertion is expected to enforce its specified validity conditions, including any validity interval and applicable `OneTimeUse` condition [15].

2.2.2 XML-Signature and Encryption

To protect the integrity and authenticity of SAML assertions, XML signatures can be used to cryptographically bind the assertion to its issuer. The W3C XML Signature standard defines how signatures over XML data are created, encoded and verified [1]. A signature

is defined by the `Signature` element and can be applied to an entire SAML assertion or to selected parts of an XML document [15, 59].

Depending on the location of the signature relative to the signed data, XML signatures can be categorised into three types [1]. An enveloped signature is contained within the XML element that it signs. In contrast, an enveloping signature contains the signed data within the signature itself. A detached signature is kept apart from the signed data, which it neither contains nor is contained in, and refers to that data by reference [1]. In the context of SAML, enveloped signatures are commonly used to sign SAML assertions and protocol messages [15].

XML Encryption provides confidentiality for sensitive information contained in SAML messages. Instead of transmitting the original XML content in plaintext, the protected content is replaced by an `EncryptedData` element containing the resulting ciphertext [25]. The encryption therefore enables selective and persistent confidentiality of individual elements within an XML document. This allows, for example, sensitive attributes contained in a SAML assertion to be encrypted without requiring the entire message to be encrypted.

Although XML Signature and XML Encryption provide important security mechanisms, their use and configuration depend on the respective SAML profile, deployment and implementation. Therefore, SAML is not a security protocol in itself, but rather a framework whose optional features can be combined in various ways. The resulting security properties depend on the chosen combination. Hartl and Derek make this explicit by deriving eight protocol variants from the optional features of a single use case and analysing each separately [23]. Consequently, the security properties of a SAML-based system cannot be derived solely from these standard mechanisms. Incorrect configuration or implementation may result in insufficient protection, such as assertions that are not appropriately signed or sensitive information that is transmitted without encryption.

2.2.3 Web Browser SSO Authentication Process

The SAML Web Browser SSO profile enables a user to authenticate to an IdP and subsequently access a protected service provided by an SP. The process is mediated by the user's web browser, which forwards SAML messages between the SP and IdP.

The process begins when a user requests access to a protected resource at the SP. If the user does not have an established session, the SP generates a SAML authentication request and redirects the user's browser to the IdP. The IdP processes the request and authenticates the user using the configured authentication mechanism. Upon successful authentication, the IdP generates a SAML response containing a SAML assertion with security-related statements about the authenticated principal.

The assertion can be digitally signed by the IdP to provide authenticity and integrity. The SAML response is then returned to the user's browser, which forwards it to the SP. The SP validates the received SAML response and assertion, including the digital signature and the applicable validity conditions. If the assertion is considered valid, the SP evaluates the contained statements and attributes to determine whether the user is authorised to access the requested resource. If the authorisation requirements are satisfied, the SP grants the

user access to the protected service [41]. Figure 2.1 illustrates the described authentication process.




Figure 2.1: *SP-initiated SSO with Redirect and POST bindings [41]*

The use of the user's web browser as an intermediary introduces an important security consideration. SAML messages pass through a communication path that is not directly controlled by either the IdP or the SP. Therefore, neither party can assume that the messages remain unchanged while being forwarded. Consequently, the security of the exchange cannot rely solely on the communication channel. Instead, mechanisms such as digital signatures, message identifiers and validity conditions are used to ensure the authenticity and integrity of SAML messages and to prevent their misuse [24].

An important security property of this process is the prevention of message replay. SAML requests and assertions contain unique identifiers that allow the SP and IdP to assign messages and detect previously processed messages. In particular, an assertion's unique identifier must not be reused, and the recipient is expected to enforce the applicable validity conditions and replay-related constraints.

2.2.4 SAML Metadata

SAML metadata provides a standardised way for SAML entities to describe their configuration and capabilities to other participating entities. It enables IdPs and SPs to obtain information required for establishing communication and processing SAML messages without requiring every configuration parameter to be exchanged manually. The SAML metadata specification organises this information around roles supported by an entity, which are represented using role descriptors within an `EntityDescriptor` element [16].

For an IdP, the `IDPSSODescriptor` describes information relevant to its role as a SAML IdP. Similarly, an SP can be described using an `SPSSODescriptor`. These descriptors contain information such as supported SAML protocols, communication endpoints, supported bindings and cryptographic keys. For example, an SP metadata document can specify its Assertion Consumer Service (ACS) endpoint and the bindings supported for receiving SAML responses, while an IdP can specify its SSO Service endpoints and the corresponding supported bindings. A binding defines how a SAML message is transported over an underlying protocol, for instance in the query string of an HTTP redirect (HTTP-Redirect) or in an HTML form that the browser submits (HTTP-POST) [14].

Cryptographic information contained in metadata is particularly important for the security of SAML communication. Metadata can contain certificates and public keys used by participating entities for verifying digital signatures or encrypting SAML messages. Consequently, the metadata configuration directly influences how SAML messages are validated and which endpoints and cryptographic keys are considered valid by an implementation.

The security of the metadata itself is therefore an important aspect of a SAML deployment. If an entity accepts manipulated metadata, an attacker could potentially influence endpoints, supported bindings or cryptographic keys used during SAML message processing. SAML metadata can itself be protected using digital signatures, allowing an entity to verify the integrity and origin of the metadata before using it for configuration or trust decisions [16].

2.3 Shibboleth

Shibboleth is a free and open-source web single sign-on software suite that implements SAML and other standards for FIM. The Shibboleth Consortium provides separate components for the IdP and the SP [53]. This thesis concerns the IdP, which is implemented as a Java-based web application and is typically deployed using a Java servlet container such as Apache Tomcat. User identities and associated attributes are commonly managed through an external directory service, such as a Lightweight Directory Access Protocol (LDAP) server, which provides the IdP with the information required for authentication and attribute release. The IdP builds on the OpenSAML library for the construction and validation of SAML messages, which is relevant because vulnerabilities reported for OpenSAML can affect Shibboleth deployments as well [21].

2.3.1 Profile Flows and Interception Points

The IdP processes each request as a workflow built on Spring Web Flow, a framework in which a sequence of processing steps is described declaratively rather than in program code. A flow consists of states that are traversed in order, and a state may delegate to a subflow, that is a self-contained flow which performs a defined task and returns control to its caller. Every top-level flow of the IdP implements one of the supported protocol interfaces, referred to as profiles, such as SAML 2.0 Web Browser SSO. Recurring tasks within such a profile, among them the authentication of the user, are carried out by subflows [10].

To allow developers to extend this behaviour without copying or editing the internal flow definitions, the IdP provides a set of defined hooks. A subflow attached to one of these hooks is known as an interceptor, and there are three hooks in total: inbound message processing, post authentication processing and outbound message processing. The first and third are available in any profile flow, whereas the second applies only to profiles that actually authenticate a user [10]. An interceptor is registered as a bean and enabled by adding its flow identifier to the corresponding list property of a profile configuration in `conf/relying-party.xml`. No modification of the IdP source code is required [11].

2.3.2 The Context Tree

While a flow describes the sequence of processing steps, the state of the request being processed is held separately in a structure referred to as the context tree. Its root is the `ProfileRequestContext`, which is created when a request arrives and accompanies it through the entire profile execution. Attached to this root are child contexts, each holding one aspect of the request, so that the state grows as processing advances rather than being assembled in a single object at the outset [4, 49].

Three of these child contexts are relevant in the following. The inbound `MessageContext` holds the message as it was received, the `RelyingPartyContext` identifies the SP the request originates from and records whether that identity could be verified, and the `SubjectContext` holds the authenticated subject once authentication has completed [10]. The last of these illustrates the incremental nature of the structure, since it does not exist before the user has been authenticated.

2.3.3 Audit Logging

The IdP writes one line per completed transaction to `idp-audit.log`. The set of fields is not fixed but defined by the operator in `conf/audit.xml`, so the information available in the log depends on the configuration of the individual deployment. In the default configuration, authentication attempts that do not result in a completed transaction, in particular failed password validations, produce no entry in this log. The IdP can additionally record every authentication attempt, but this feature is disabled by default, and when enabled its records enter the same audit stream unless they are routed to a separate destination [3].

The format of a log line is defined per profile in the *shibboleth.AuditFormattingMap* of `conf/audit.xml`. A format consists of formatting tokens, each of which is replaced by a value from the context tree of the transaction when the line is written, for instance the time of the event, the identifier of the inbound message or the address of the client. Some values are written in an abbreviated form, which the IdP derives from a replacement map, and further tokens can be added by the operator [3].

2.3.4 Configuration

Three configuration files are relevant in the following. `relying-party.xml` holds the per-partner configuration described in Section 2.1, including which profiles are enabled and which security settings apply [12]. `metadata-providers.xml` declares where the IdP obtains metadata for its partners [6]. `attribute-filter.xml` governs which attributes are released to which relying party [2].

The settings of `relying-party.xml` apply to all partners by default and can be overridden for a single partner, so that one partner is configured differently from the others. They include the authentication flows permitted for a partner and whether responses and assertions are signed or encrypted [12].

3 Related Work

Existing research and implementations were examined to identify approaches relevant to the development of a monitoring system for an IdP operating at the application layer. The goal was to find relevant existing solutions and examine their limitations and applicability to this thesis. These related works provide valuable insights and a foundation for this thesis by identifying existing approaches, their areas of coverage and gaps that remain relevant to the considered scenario. The most relevant studies and projects are presented and analysed in the following sections.

3.1 Security Analyses of SAML and Shibboleth

The security of SAML-based federations has been examined from two directions. Empirical studies analyse existing implementations, whereas formal approaches focus on the specification itself.

Somorovsky et al. examined fourteen SAML frameworks and found critical XSW vulnerabilities in eleven of them [59]. Their analysis is confined to the processing of assertions at the SP, and it does not consider what information is available at the IdP during or after such an attack. Kaur and Bansal transferred this line of work to a cloud setting by reproducing an XSW attack in their own OpenSAML-based SSO environment and rating its severity with CVSS, which fell from 6.2 to 2.7 once a mitigation was applied [26].

A second line of work approaches the problem formally. Sommer analyses a model of Shibboleth with respect to authentication, session integrity and logout consistency [58], while Hartl and Derek analyse the SAML specification itself [23]. The latter derive eight protocol variants from the optional features of a single use case and verify or falsify the security properties of each separately. Their premise is that SAML is not a security protocol in itself, but a framework whose optional features can be composed in different ways.

Both formal analyses establish which configurations are secure under a given set of assumptions. Neither verifies whether a deployed system actually satisfies those assumptions. Formal analysis therefore answers which configuration is secure, whereas this work observes which configuration is in effect.

3.2 Monitoring of Applications and Federations

Monitoring approaches differ in the position from which they observe a system. The OWASP AppSensor project describes an approach in which intrusion detection and response capabilities are integrated directly into an application [39]. In contrast to network-based security mechanisms, application-layer monitoring can make use of information about the application's internal state and semantics.

Network-based monitoring observes a system from the outside instead. Rieckers applies the principle of passive observation to the eduroam infrastructure, capturing its RADIUS and EAP-TLS traffic to analyse the TLS parameters that clients offer [42]. In captured traffic, information that exists only inside the application, such as the structure of a SAML assertion or the configuration of an SP, is not visible. This work adopts the principle and applies it inside the Shibboleth IdP itself.

Placing detection inside the application is also the basis of existing application-level approaches. One relevant architectural precedent is BlackWatch by Hall et al. [22]. BlackWatch applies a similar architecture to generic web applications. Detection points are placed directly within the application to identify security-relevant events. These events are collected by the separate BlackWatch application, where they are analysed using rule-based and reputation-based mechanisms. The results are then made available through a web-based reporting interface.

The separation between the monitored application and the analysis component allows the detection and analysis functionality to be decoupled from the application itself. A key challenge identified by Hall et al. is the integration and configuration of detection points within the application. Developers must identify suitable locations where suspicious behaviour can be detected and implement the corresponding detection logic [22].

A domain-specific example is provided by Suvanto's AAIEye, a monitoring system for Shibboleth- and SAML 2.0-based federations [60]. Motivated by the lack of effective monitoring solutions for authentication and authorisation infrastructures, AAIEye deploys probes alongside the monitored IdP and SP components. These probes collect two categories of information that closely resemble the sources used in this work: runtime authentication events and federation metadata.

However, the evaluation applied to this data differs fundamentally. The usage statistics probe records an authentication event only as a data point for a login count, without assessing whether the event itself is suspicious. The metadata probe only verifies whether a metadata file is up to date by comparing its checksum against a reference copy. It does not verify its security-relevant content, such as certificate validity or endpoint configuration. Suvanto notes that problems in federation operation are often caused by configuration mistakes or changes that cannot currently be easily detected [60]. He addresses them with login tests, in which a central server logs in to the monitored SPs with test accounts. Such a test reveals a configuration mistake only once it breaks a login. A configuration that is insecure but still works remains unnoticed. This is precisely the gap addressed in this work. The same categories of data that AAIEye already collects for operational purposes are evaluated here for their security semantics instead.

A complementary perspective is provided by Martín et al., who propose behavioural anomaly detection at the SP rather than the IdP [31]. Their argument is that delegating authentication to an IdP does not transfer the entire security responsibility, and that the relying party can contribute to detection even after authentication has succeeded. The IdP side is explicitly outside their scope, and protocol-level information such as assertion structure, attribute release policies or SP metadata is consequently not considered. Taken together with the present work, the two perspectives address opposite ends of the same federation.

3.3 Log Analysis and Log Integrity

A Security Information and Event Management (SIEM) primarily operates on logs and security-relevant events. Two limitations follow from this principle. First, information that is not represented in an event or log is not available to the SIEM for analysis. Second, the SIEM generally relies on the information provided by its data sources and therefore cannot independently verify information that is incorrect or has been manipulated at the source.

The collection, storage and correlation of log data used in this work correspond to established SIEM functionality [27]. What remains open is the second limitation, namely how the sources underlying the events can be verified. In this context, Wazuh is particularly relevant, as it combines log analysis with file integrity monitoring and security configuration assessment. This addresses both event-based analysis and the verification of the system state [62]. However, these mechanisms mainly focus on configuration and file state rather than the relationship between configuration and individual runtime events. For instance, the security configuration assessment evaluates system configurations against defined policies, while file integrity monitoring detects changes to monitored files. Neither mechanism directly establishes whether a particular runtime event is consistent with the configuration state that was active when the event occurred.

A further concern arises when considering the integrity of the log sources themselves. Graves discusses this concern for Shibboleth under the STRIDE category of repudiation. Prompted by unusual entries reported on the Shibboleth mailing list, he concludes that log entries can be injected that lead the administrator astray, and suggests keeping the Apache logs, which contain the actual browser requests, separate from the Tomcat and IdP logs, which may themselves be subverted [21]. CWE-117 describes the underlying mechanism: input that is written to a log without neutralisation allows an attacker to insert forged entries and thereby mislead subsequent analysis [33]. An attacker who has gained access to the system can go further and alter entries that have already been written. OWASP A09 lists logs that are only stored locally and logs that are not protected against tampering as weaknesses, and recommends audit trails with integrity controls [38]. AppSensor dedicates a detection point to this issue (IE6), which involves modifying an existing log entry [39]. Snodgrass et al. assume such an attacker in their threat model, who after a successful penetration has access to the database, the operating system and the hardware [57].

The possibility of altered log entries makes the correlation of independent event sources more than a technical convenience. It provides an additional means of identifying inconsistencies between records of the same event. A system that relies solely on log analysis can compare multiple log sources, but if all sources are stored as files on the same system, they remain exposed to an attacker with sufficient file-system access.

Cryptographic approaches provide a stronger solution to this problem. Schneier and Kelsey, as well as Snodgrass et al., describe mechanisms that make tampering with stored logs cryptographically detectable [45, 57]. However, these approaches require changes to the logging or storage architecture and may depend on external trusted components. Snodgrass et al. report an overhead of up to 16 percent for their approach [57].

The approach taken in this work is different. Instead of modifying the existing logging infrastructure, two independently generated records of the same event are compared. The detection of tampering therefore does not rest on cryptography, but on the temporal and architectural separation between the records. A log file may remain accessible to an attacker with file-system access for an extended period, whereas a record generated within the application process itself exists only for the duration of the corresponding processing before it is transmitted away. This does not make a record produced inside the application process immutable: an attacker controlling the JVM process could also manipulate it. Its purpose is instead to provide a second, independently generated observation of the same event.

The remaining question is whether such application-level detection is already sufficiently covered by existing frameworks. Of the works considered, AppSensor is conceptually closest to this work. However, its detection model is based on different assumptions about the monitored application [39].

AppSensor detection points primarily monitor the behaviour of a user within an application session. They can detect events such as tampered cookies, modified parameters or injection attempts. The framework therefore asks whether a user's behaviour is suspicious. It does not provide a mechanism for comparing an observed runtime event with a configuration or security state declared by a third party.

This limitation follows from the architectural assumptions of the framework. AppSensor is designed for applications in which the application itself is the primary authority over the user's interaction. An IdP, in contrast, performs authentication and issues identity information on behalf of other entities. Consequently, security-relevant conditions may depend not only on the IdP's own runtime behaviour, but also on configuration and trust relationships involving its federation partners.

This creates a detection category that is not directly represented in the AppSensor model: comparing an observed runtime event against the configuration that should govern that event. One AppSensor detection point, however, is directly applicable. IE6, *Violation of Security Log Integrity*, addresses the integrity of security logs and cites NIST SP 800-92 and Snodgrass et al. as supporting references [27, 39, 57]. The discrepancy-based approach used in this work therefore does not introduce the general concept of detecting log integrity violations. Instead, it applies an established detection principle to the specific domain of federated identity management and extends it with application-level observations from the Shibboleth IdP.

3.4 Positioning of This Work

Table 3.1 compares the related works discussed in this chapter with the approach proposed in this work. The last three columns show the properties that this work combines. This work builds on each of these lines of research in a different way. The analyses of SAML and Shibboleth establish which implementations and configurations are vulnerable, and this work observes whether a running deployment exhibits such a configuration. From Rieckers, it adopts the principle of passive observation but moves it from the network

Table 3.1: *Comparison of the related work*

Work	Observation point	Purpose	Multiple sources	Event vs. declared configuration	Log integrity
Somorovsky et al., Kaur and Bansal [26, 59]	SAML implementations	Vulnerability analysis	—	—	—
Sommer, Hartl and Derek [23, 58]	Shibboleth model, SAML specification	Formal analysis	—	—	—
AppSensor [39]	Inside the application	Intrusion detection	—	—	(✓)
BlackWatch [22]	Inside the web application	Intrusion detection	—	—	—
Rieckers [42]	Network traffic	TLS analysis	—	—	—
AAIEye [60]	Probes at the IdP and the SP	Operational monitoring	✓	—	—
Martín et al. [31]	SP after authentication	Anomaly detection	—	—	—
SIEM [27]	Collected logs	Log analysis	✓	—	—
Wazuh [62]	Host	Log analysis, configuration assessment	✓	—	(✓)
Snodgrass et al. [57]	Stored logs	Tamper detection	—	—	✓
Schneier and Kelsey [45]	Stored logs	Tamper detection	—	—	✓
This work	Inside the IdP	Security monitoring	✓	✓	✓

into the IdP. AppSensor and BlackWatch show that detection points can be placed inside an application. The challenge of integrating them motivates the development of a plugin. AAIEye already collects authentication events and metadata, which this work evaluates for their security rather than for operation. Martín et al. observe users at the SP after authentication and thus complement this work, which observes the IdP.

The aggregation of multiple data sources is established practice, as AAIEye, SIEM systems and Wazuh demonstrate. However, none of the approaches discussed compares the declared configuration of the infrastructure with the events observed at runtime.

Log integrity is addressed in different ways. Schneier and Kelsey, as well as Snodgrass et al., propose cryptographic approaches that make modifications to stored logs detectable. AppSensor defines a detection point for log integrity (IE6) but leaves its realisation to the application. Wazuh detects changes to monitored files through checksum-based file integrity monitoring. If configured, it also records the user and the process that made a change, so that a manual modification by another account can be distinguished from a regular write [62]. A change by the process that writes the log, or an entry injected through

the application, still appears as a regular write. The table therefore marks AppSensor and Wazuh as partial. None of these approaches provides a second, independently generated record of the same event.

This work combines all three properties within the IdP. Its collection, storage and correlation follow established SIEM practice. Its contribution lies in two comparisons that the position inside the IdP makes possible. It compares an observed login with the configuration declared for the SP, and it compares two independently produced records of the same login.

4 System Design

This chapter describes the design of the proposed monitoring system. It first derives the requirements that follow from the research questions and the preceding chapter, and then presents the system along the path that data takes through it. First, the data aggregation inside the IdP. Then, the transport of the collected data across a trust boundary. Finally, storage, correlation and rule-based detection.

The emphasis lies on the collection layer. The remaining layers follow established practice, whereas the question of which data can be obtained from within an IdP, and by which mechanisms, is specific to this work. Design decisions are stated together with the alternatives that were considered and rejected.

4.1 Requirements for the System

The requirements for the monitoring system were derived from the research and analysis of the related work. Section 3.3 showed that AppSensor's detection model provides no mechanism for comparing an observed event against a configuration declared by a third party. Since an IdP authenticates on behalf of other entities, such a comparison requires at least two independent sources, one describing the intended configuration and another describing what actually occurred.

As discussed in Chapter 1, the proposed monitoring system operates directly within the application layer of the Shibboleth IdP. Its objective is to detect attacks based on events and behaviour observable from within the application.

The intended scope of the system can be described with the taxonomy for self-protecting software systems introduced by Yuan and Malek [64]. Two dimensions of this taxonomy are particularly relevant to the scope of this work: the `Architecture Level` and the `Self-Protection Level`. The `Architecture Level` describes the layer at which a security mechanism operates and distinguishes between Network, Host, Software/Application and Services. This dimension allows the observation position of different security mechanisms to be compared. Network-based intrusion detection systems, such as Suricata and Snort, operate primarily at the network level, whereas endpoint detection and response solutions operate at the host level. The proposed system operates at the Software/Application level, as it observes events directly within the Shibboleth IdP. The distinction between these systems therefore lies primarily in the layer at which security-relevant information becomes observable.

While the Architecture Level describes where the system operates, the `Self-Protection Level` describes the degree of self-protection according to the MAPE process of Monitor, Analyze, Plan and Execute. The proposed system fully covers the *Monitor & Detect* level by collecting and detecting security-relevant events within the IdP. The *Analyze & Characterize* level is partially addressed through event correlation and severity classification (Section 4.5). In contrast, *Plan & Prevent* is outside the scope of this work. The system

generates alerts based on detected events but does not autonomously modify the system state or take preventive countermeasures.

This limited level of self-protection is intentional and follows from the principle of passive observation discussed in Section 3.2, in which security-relevant events are made observable without interfering with the operation of the monitored system. An erroneous automated response could affect the availability of the IdP and thereby every SP that relies on it (Section 4.7). The system must therefore report detected security-relevant events without automatically intervening.

As mentioned in Section 3.2, Hall et al. identify the integration of detection points into the application as a central difficulty [22]. The system is therefore implemented as a plugin that uses an extension point provided by Shibboleth (Section 2.3.1), allowing the monitoring functionality to be added without modifying the underlying IdP implementation.

Section 3.3 also showed that log sources stored on the same system share the same attack surface. Records generated by the interceptor are therefore transmitted to a separate system rather than stored locally. This requires the transport to be authenticated and sensitive data to be pseudonymised at the source (Section 4.4).

The detection logic must rest on documented attack classes and security recommendations, so that every finding can be traced back to its origin. The sources used for this purpose are introduced in Section 4.5.3. These considerations result in five requirements:

1. At least two independent sources: the declared configuration and the observed event.
2. Detection and reporting without automated intervention.
3. Realisation as a plugin, without modification of the IdP.
4. Storage outside the monitored system, with authenticated transport and pseudonymisation at the source.
5. Detection rules derived from documented attack classes and security recommendations.

4.2 Overview

The proposed system comprises four layers. The data collection layer gathers security-relevant information from within the Shibboleth IdP, drawing on three sources: the audit log written by the IdP, its static configuration and metadata files, and two custom interceptors that are attached at two points of the profile processing and execute inside the IdP itself. Because the monitoring backend resides outside the trust boundary of the IdP, sensitive attributes such as usernames and IP addresses are pseudonymised before transmission. The transport layer then transfers the collected records to the backend application over an authenticated channel. Within the backend, incoming records are persisted and periodically correlated, so that observations originating from different sources but describing the same authentication event can be linked. The detection layer evaluates the resulting data against the rule catalogue in order to identify configuration weaknesses and anomalies in the authentication process. Finally, the presentation layer

makes the detected findings accessible to the operator through a frontend web application. Figure 4.1 illustrates the UML deployment diagram of the proposed system.




Figure 4.1: *UML deployment diagram of the proposed monitoring system*

Two terms recur throughout this work. An audit entry describes a record that the IdP writes to its audit log and that reaches the monitoring tool through the log shipping stack. A report represents a record that an interceptor produces within the IdP and transmits directly to the monitoring tool. Since two interceptors are used, their reports are called the post authentication report and the outbound report, to distinguish between them. A report and an audit entry may describe the same authentication event, which makes the correlation described in Section 4.5.1 possible.

4.3 Data Aggregation Layer

The design of the collection layer begins with a broader question than the choice of individual data sources. Through which kinds of channel does an application disclose information about itself at all? Applied to the Shibboleth IdP, five such channels can be identified. The application writes log files, it reads static configuration and metadata, it maintains runtime state that is accessible through defined extension points, it exposes status endpoint and it can publish metrics, for instance via Java Management Extensions [8].

Not all of these are suitable for the purpose of this work. The system described here associates every finding to the logins it affects, since a weakness or an attack is only meaningful in the context of the transactions in which it occurs. A channel that cannot be related to a single login therefore cannot contribute to correlation or detection.

Two of the five channels fail this criterion. The status endpoint describes the state of the deployment as a whole in free-form text [13]. It therefore addresses availability rather than the security of individual transactions. The metrics are counters, timers and

gauges [8], and none of them refers to an individual login. A counter reports that a number of logins occurred, not which login was affected. An alert derived from either source could not be related to a single login.

The remaining three channels form the collection layer of this work. These are the audit log, the configuration files and the runtime state accessible through interceptors. Together, they fulfil the first requirement of Section 4.1. The configuration files describe the intended state of an SP, while the audit log and the interceptors record what actually occurred. They are described in the following sections.

4.3.1 The Audit Logs

All logging within the Shibboleth IdP is performed through the abstract logging API SLF4J, with Logback as the default implementation. By default, three classes of log files are produced. The diagnostic logs, *idp-process.log* and *idp-warn.log*, contain messages generated during the normal operation of the software. The general audit log, *idp-audit.log*, records the results of authentication transactions for each SP. Finally, the consent audit log, *idp-consent-audit.log*, contains audit records of user decisions regarding data privacy and terms of use [5].

The amount of information recorded in the diagnostic logs depends on the configured logging level, which determines the severity of messages that are written. The *idp-warn.log* file is a filtered view of *idp-process.log* and contains only messages logged at the `WARN` level or higher. These files are written for a human reader. A line consists of a timestamp, a severity, the originating class and a free-form message whose content depends on the code location that produced it, so that lines of different origin share no common structure.

The audit log differs from the diagnostic logs in that its structure is defined rather than free-form. It records one entry per completed transaction, written once the IdP has finished processing the request, with a fixed sequence of fields that allows every line to be decomposed in the same way. This has two consequences for the information it can provide. On the one hand, the entry reflects the final outcome of a transaction, including properties that are only determined at the end of processing, such as the encryption applied to the outgoing assertion. On the other hand, events that never result in a completed transaction produce no entry. Failed password validations in particular are not recorded in the audit log by default, since no transaction is concluded for them.

As mentioned in Section 2.3.3, the fields that are written to the audit log are not fixed. The audit format is configured per profile in *conf/audit.xml*, where each field is represented by a formatting token, and the set of available tokens can be extended within the IdP [3]. Which information a given deployment records is therefore determined by its operator and may differ between installations.

This property has direct implications for the monitoring system developed in this work. The system cannot assume the presence of a fixed set of audit fields, since the information required by a particular detection rule may simply not be recorded. The detection logic must therefore take the configured audit format into account and determine whether the information a given rule depends on is available at all. The same constraint applies to the correlation between audit entries and interceptor records. Rather than relying on a

fixed set of fields, the correlation must adapt to the information that a given deployment provides, which requires a strategy capable of selecting an appropriate matching approach depending on the fields available for a given audit event.

4.3.2 Metadata and Relying Party File

SAML metadata, introduced in Section 2.2.4, describes the entities that participate in a federation. For an SP, the relevant role descriptor is the `md:SPSSODescriptor` element. It lists among others the supported protocols, the name identifier formats, the cryptographic keys and the `md:AssertionConsumerService` endpoints to which the IdP may send its responses [7].

The Shibboleth IdP consumes metadata through configured metadata providers. These providers define the sources from which SAML metadata is obtained and are configured using `<MetadataProvider>` elements in *conf/metadata-providers.xml* [6]. The metadata therefore forms an essential part of the IdP configuration, as it determines which federation entities are known to the IdP and which endpoints, protocols and cryptographic information are associated with them.

The metadata describes what an SP declares about itself. What the IdP intends to do for that SP is defined in the configuration of the deployment, most notably in *relying-party.xml* (Section 2.3.4). Unlike the audit log, both describe not what happened, but what is supposed to happen.

The file *relying-party.xml* specifies which functional features the IdP supports and allows these settings to be customised based on the identity of a relying party. It determines which profiles are enabled for a given partner and allows security configurations to be attached at various levels. These include whether assertions and other content are encrypted, at which layer signing is performed and which cryptographic algorithms are used [12].

Of particular relevance to this work is that these settings are not global. A deployment defines default behaviour that applies to all partners, and may then override this behaviour for individual relying parties or groups of them. A single IdP therefore enforces a set of independent, per partner policies rather than one uniform policy, and the security properties of a given transaction depend on which policy applies to the SP involved.

Two settings are relevant in the context of this work. The first concerns encryption. A deployment may disable the encryption of assertions for a particular partner, for instance where an SP does not support it, which means that assertions for that partner are transmitted in plain text. The second concerns authentication. A deployment may specify which authentication flows are permitted for a partner, and thereby require multi factor authentication for some SPs while accepting password based authentication for others.

Both settings describe a target state. Whether a given login actually satisfied it is recorded in the audit log, not in the configuration. Neither source is sufficient on its own. A comparison between them is only possible if both are available to the monitoring system, which is the reason why the configuration is treated as an independent data source in this work.

Finally, *relying-party.xml* is also the file in which interceptor flows are enabled for a profile. The extension point used by the collection mechanism described in Section 4.3.3 is therefore configured in the same place as the security settings it observes.

4.3.3 Interceptor

Section 2.3.1 introduced the three hooks at which interceptors can be attached to the profile processing. The following paragraphs examine what each of them can observe and which of them suit the monitoring system.

Inbound interceptors run before the user is authenticated. At this point, the inbound `MessageContext` tree is fully populated. A `RelyingPartyContext` has typically been created as well, together with contexts required for operations such as transport or message authentication [10].

Consequently, an inbound interceptor can observe information associated with the received message and the context in which it is being processed. This makes the interception point particularly suitable for security checks on the incoming request. Shibboleth itself uses inbound interceptors for various security policy checks. An interceptor may also modify the context tree, although such modifications directly influence subsequent profile processing [10]. For the monitoring system, however, this point comes too early, since the outcome of the authentication is not yet known when it is reached.

The post authentication interception point is executed after the user has been authenticated and after the attributes have been resolved and filtered, but before the profile constructs the outgoing message [11]. Unlike the inbound and outbound hooks, this interception point is only available for a subset of profiles, particularly profiles that perform user authentication [10].

The interceptor therefore has access to a later state of the processing context. In particular, information related to the authenticated identity and resolved attributes is available at this stage. The interceptor can also modify the context before the outgoing response is constructed, including changes to the authenticated identity or attributes [10]. Access to this later state makes the post authentication interception point particularly suitable for the monitoring system developed in this work.

Outbound interceptors run shortly before the final stage of profile processing that produces the response to the client. Their input therefore represents the state produced by the preceding profile execution and typically contains a populated outbound `MessageContext`. The message may not yet be in its final form, since operations such as signing can still occur afterwards [10].

The outbound interception point consequently provides access to the information that is about to be returned to the relying party. Interceptors can inspect or modify the outbound context and may also terminate processing [10]. For the monitoring system, this interception point is useful for observing the result of the authentication workflow and properties of the response that is about to be issued by the IdP.

The monitoring system uses two interception points, the post authentication point and the outbound point. The post authentication point is the earliest of the three interception points at which both the incoming message and the authentication result are available

in the context tree, and it serves as the main collection point. The outbound point still has access to both, since its input is the entire state of the tree that the profile execution has produced [10], and it additionally holds the response that is about to be issued. At the post authentication point, in contrast, the outgoing response does not exist yet. The outbound interceptor therefore complements the main collection point with the fields that only the response carries. The outbound point is also reached by error responses, for instance when the IdP cannot provide the authentication context that the SP requested. The post authentication point never sees these responses, since no authentication has succeeded.

What remains outside the view of the post authentication point is the outgoing response, including the response identifier, the final status of the transaction and whether the assertion was encrypted. The outbound interceptor makes these properties observable, with one limit. When the assertion is encrypted, the encryption has already taken place when the outbound hook runs, so that the assertion identifier, the authentication context and the name identifier are no longer readable, and the IdP cannot read them afterwards, since only the SP holds the private key. Reading them before the encryption would require an intervention in the profile flow itself, which the third requirement from Section 4.1 excludes. For encrypted assertions only the response level fields and the encryption state are therefore available to the interceptors, whereas the audit log records all of them, since the IdP extracts them at an earlier point of the processing sequence. The complementarity of the sources described in Section 4.3.1 therefore follows from their position in the processing sequence rather than from a deliberate division of responsibilities.

4.4 Transport Layer and Trust Boundary

After the data has been aggregated on the Shibboleth IdP side, it is transferred to the monitoring tool for further processing and storage. As stated in Section 4.2, this tool is deliberately deployed outside the trust boundary of the IdP. The separation avoids placing the monitoring system under the same security assumptions and access controls as the system it monitors. Together with the authenticated transport and the pseudonymisation described in this section, the separation realises the fourth requirement of Section 4.1.

If the monitoring functionality were deployed entirely within the IdP, an attacker who compromises the IdP could potentially compromise or manipulate the monitoring functionality at the same time. An attacker would then be in a position to influence the recording of their own activity, since collection, storage and analysis would all fall under the same control.

By transferring the collected information to a separate monitoring component, the observation and analysis functions are separated from the monitored application. This creates an additional security boundary and reduces the dependency of the monitoring system on the integrity of the IdP itself. The external component therefore does not exist solely for scalability or architectural convenience. What the separation protects is the data that has already been transmitted. An attacker who gains control of the IdP can influence

which records are produced from that point onward, but not those that have already left the system. The independence is thus temporal rather than absolute.

This design decision has consequences. The collected data leaves the security domain in which the original authentication data is processed and becomes accessible to a separate component with a different trust relationship. Therefore, transmitting original sensitive user information, such as usernames and client IP addresses, would expose more personal information than is necessary for the intended processing purpose. A comparable concern is described by CWE-532 for log files, where the inclusion of sensitive user data provides attackers with an additional and less protected path to obtaining that information [34]. The same reasoning applies to data transferred to a component outside the original security domain.

To reduce this exposure, sensitive identifiers are pseudonymised before they leave the IdP trust boundary. The monitoring functionality does not require the original identity of a user to perform its security analysis. It primarily requires the ability to distinguish and correlate events belonging to the same subject. The monitoring system can therefore preserve the ability to correlate multiple events belonging to the same subject without transmitting the original identifier. Pseudonymisation reduces the risk associated with unauthorised access to the monitoring system, while still allowing the required security analysis to be performed.

To enable this correlation across the different data sources, all components that generate monitoring data must apply the same pseudonymisation algorithm and the same secret salt. Otherwise, identical identifiers would result in different pseudonyms and events originating from different sources could no longer be reliably correlated. The secret salt is therefore treated as a shared cryptographic parameter between the data collection components and must be protected accordingly.

The deployment of the monitoring tool outside the IdP trust boundary introduces an additional security concern. The endpoints of the monitoring tool accept data from collection components that reside outside its own trust boundary. Consequently, the monitoring tool cannot assume that every received message originates from an authorised data collection component.

Without message authentication, an attacker could submit forged or manipulated records to the exposed endpoints. Injected events would not only produce false findings but could also interfere with the correlation of genuine ones, since a fabricated record may be matched against a real audit entry.

The transmitted data must therefore be authenticated before the monitoring tool accepts it. In this work, this is achieved using a Hash-based Message Authentication Code (HMAC) [28]. The collection components and the monitoring tool share a secret key that is used to generate and verify a message authentication code for each transmitted message.

The final design decision concerning the transport layer is whether the collection component should wait for the monitoring tool to confirm receiving the data. The interceptors execute within the authentication flow of the IdP. Any time spent transmitting a record is therefore time added to the login of the user who triggered it. Waiting for a response would make the duration of every authentication dependent on the availability and response time of a component outside the IdP, and a monitoring tool that is slow

or temporarily unreachable would delay the service it observes. The test environment transmits the records over plain HTTP. A production deployment would additionally encrypt the communication with TLS, while the HMAC continues to authenticate the sender.

The records are consequently transmitted asynchronously. Each interceptor dispatches its record and continues without awaiting a response. If a transmission fails, the record is lost, and only a warning in the log of the IdP indicates the failure. The design thus accepts that individual records may be lost in order not to delay the service it observes. In BlackWatch, Hall et al. make a similar choice and retrieve responses separately rather than in reply to the submitted event [22].

4.5 Correlation and Detection Layer

This section explains how the monitoring tool processes the collected data. Records originating from different sources are first linked to the authentication event they describe, then evaluated against the detection rules and finally classified according to the impact of the condition they report.

4.5.1 Correlation

When the collected data arrives at the monitoring tool, it must first be stored for subsequent processing. The different data sources transmit their information through separate endpoints and at different times, which means that information belonging to the same authentication event does not necessarily arrive together. The corresponding records can therefore not always be correlated upon arrival. Instead, they are stored until the required information from the other source becomes available.

This introduces the first challenge for the correlation process. Data collected by the post authentication interceptor within the Shibboleth IdP is transmitted immediately after the collection process has completed, so the corresponding post authentication report reaches the monitoring tool shortly after the authentication event has been processed. The audit entry follows a different path. Audit logs are collected by log shippers that operate periodically, and the corresponding entry therefore reaches the monitoring tool later than the post authentication report. This temporal offset is the reason why the two records cannot be matched by a simple database join at the time of arrival.

A further consequence follows from this. A report may arrive at a point when its counterpart does not yet exist, which means that an unsuccessful correlation attempt does not necessarily indicate that no counterpart will ever arrive. The correlation process must therefore retry over a defined period and, once that period has elapsed, treat the record as permanently uncorrelated. Without this distinction, a record still awaiting its counterpart would be indistinguishable from one that will never receive it, and the proportion of successfully correlated records could not be determined.

The second challenge arises from the dynamic nature of the audit log discussed in Section 4.3.1. Since the audit format is determined by the configuration of the deployment,

the information available in an audit record is not fixed, and the correlation must adapt to the fields that are actually present.

This creates an asymmetric correlation problem. The data collected by the post authentication interceptor is static by design and always contains the same set of fields. The audit data, in contrast, is dynamic and may lack information required by a particular correlation strategy. The static post authentication report, which arrives first, therefore has to be matched against a dynamic audit record that arrives later.

Depending on the fields available in the audit record, different correlation strategies are applicable, and these differ in how reliably they identify the corresponding record. A strategy based on a unique identifier that both sources share establishes the relationship unambiguously, whereas a strategy based on attributes that several transactions may have in common can only approximate it. The correlation process consequently applies the available strategies in a defined priority order, using the strongest applicable strategy first and weaker ones only where the required fields are absent. The strategy used for a given record is recorded alongside the result, since it determines how reliable the resulting correlation is. The precision achieved by each strategy is examined in Chapter 6.

4.5.2 Detection

Once the data has been stored, the detection layer evaluates it against a catalogue of fifteen rules. Each rule describes a condition that indicates a weakness or an attack and reports a finding when this condition is met. Since the conditions are defined explicitly rather than learned from data, every finding can be traced back to its rule and to a documented weakness or requirement (Table 4.1).

The rules do not all operate on the same kind of input. Four input types occur in this system: login events derived from the audit log, the configuration of an SP, its metadata and the post authentication reports produced by the interceptor. These differ not only in structure but also in the rhythm at which they appear. Login events occur continuously during operation, whereas a configuration or a metadata document changes rarely and may remain unchanged for long periods of time.

Evaluating all rules against all data whenever any of it changes would therefore be inefficient and, in the case of configuration data, largely redundant. The detection logic is consequently divided into four engines, each responsible for one input type. An engine evaluates the rules that apply to its input and can be scheduled according to the frequency at which that input actually changes.

A further consideration follows from the dynamic audit format described in Section 4.3.1. A rule may depend on a field that a given deployment does not record, in which case the rule cannot reach a valid conclusion. Evaluating it regardless would produce a result that appears definite but rests on absent information, and a rule that cannot observe a condition must not report its absence as a finding. Each rule therefore checks whether the fields it requires are recorded before it evaluates an input. Where the required information is not recorded, the rule withdraws rather than returning a result. Which rules are active in a given deployment is thus determined by what that deployment logs.

4.5.3 Derivation of the Rules

The rules are derived from two complementary sources. The first is the FIM survey by Simpson and Groß, which identifies 11 vulnerabilities and 14 attack classes based on a systematic literature review [55]. The vulnerabilities are grouped into cross-protocol issues where the same weakness is exploited by the same attack class, results in the same CIA consequence and is documented for at least two different protocols. The survey identifies 14 such issues. Six of them concern SAML (issues 5, 7, 8, 9, 10 and 14 in the numbering of the survey), while one directly concerns Shibboleth (issue 6). Issue 4, weak user credentials exploited by brute force, is reported only for OpenID and OAuth. Since it concerns how the IdP authenticates its users, it applies to SAML as well. For each of these issues, it was examined whether its vulnerability or its attack becomes visible in the audit log, in the reports of the interceptors or in the configuration of an SP (Section 4.3). This is the case for issues 4, 5 and 9, which the rules therefore address. The remaining issues are observable from the IdP only through their preconditions or not at all and are discussed in Section 7.2.

While the survey describes vulnerabilities that have been documented in the literature, the second source, the OASIS SAML Security and Privacy Considerations, provides security recommendations for SAML deployments by specifying security requirements and suggested countermeasures [24]. This allows the detection rules to be derived not only from observed or documented attacks, but also from the security properties that a SAML deployment is expected to enforce. Where the evidence from the survey and the requirements specified by OASIS overlap, the basis for a detection rule is particularly strong. Replay attacks provide an example of such an overlap, as they are documented in the literature and explicitly addressed by the SAML security considerations.

The rules are derived from these two sources and classified with the STRIDE framework [54]. It distinguishes between spoofing, tampering, repudiation, information disclosure, denial of service and elevation of privilege. Graves applies this framework to the analysis of threats against Shibboleth [21]. STRIDE does not derive any rule but characterises the kind of threat that a detected weakness or attack represents.

Table 4.1 shows the resulting assignment. Five rules follow from the survey alone, three from the survey and OASIS and one from OASIS alone. The last column of the table also lists sources that specify the condition of a rule, such as the technical guideline of the BSI, which defines which algorithms count as weak [18], and Graves, who describes threats specific to Shibboleth [21]. Two further rules follow from works discussed in Chapter 3. `SIGNATURE_WRAPPING_SUSPECTED` rests on the analysis by Somorovsky et al. and on Graves [21, 59], since the survey reports message modification through the message format only for other protocols (issue 1). `FAILED_LOGIN` reports an indicator rather than an attack and follows the OWASP guidance on security logging [38]. Two rules, `CORRELATION_DISCREPANCY` and `FIELD_MISMATCH`, compare independently produced records and follow the log integrity argument of Section 3.3. Thirteen of the fifteen rules can thus be traced to documented weaknesses, attacks or recommendations, which meets the fifth requirement of Section 4.1. The remaining two rules are discussed after Table 4.1.

Table 4.1: *Assignment of the 15 detection rules to documented vulnerabilities and attack classes*

Rule	Vulnerability	Attack Class	STRIDE	Sources
WEAK_ENCRYPTION	Unencrypted Communications	Message Modification	I, T	[18, 24, 55]
UNENCRYPTED_ ASSERTION	Unencrypted Communications	Message Modification	I, T	[21, 55]
WEAK_ CONFIGURATION	Unencrypted Communications	Message Modification	I, T	[55]
MISSING_MFA	Weak User Credentials	Enables Brute Force	S, E	[55]
MFA_BYPASS	Weak User Credentials	Enables Brute Force	S, E	[55]
BRUTE_FORCE	Weak User Credentials	Brute Force	S, E	[55]
FAILED_LOGIN	Weak User Credentials	Indicator, not an attack	S	[38]
ASSERTION_REPLAY	Lack of Binding	Replay Attack	S, E	[24, 55]
REQUEST_REPLAY	Lack of Binding	Replay Attack	S, E	[24, 55]
SIGNATURE_ WRAPPING_ SUSPECTED	Message Formatting	Message Modification	S, T, E	[21, 59]
CERTIFICATE_ EXPIRED	Security recommendations	None	S	[24]
CORRELATION_ DISCREPANCY	Log integrity	Log tampering	T, R	[33, 38, 39]
FIELD_MISMATCH	Log integrity	Log tampering	T, R	[33, 38, 39]
SUSPICIOUS_USER_ AGENT	None	None	—	[39]
BEHAVIOUR_ANOMALY	None	Detection method	S	[39]

Two observations follow from this assignment. Lack of binding appears in three of the six cross-protocol issues that concern SAML and is therefore the most frequently documented weakness of SAML in the survey. Both replay rules address it, although only a replayed request passes the IdP, whereas a replayed assertion is presented to the SP (Section 7.2). Furthermore, several rules form pairs in which the same weakness is captured twice, once as a configuration state and once as an event that has occurred. MISSING_MFA examines whether an SP requires multi factor authentication at all, whereas MFA_BYPASS examines whether an actual login circumvented that requirement. This distinction is a direct consequence of the three source architecture described in Section 4.3: the configuration states what is intended, and the audit log records what took place.

Two of the rules do not examine a single record. They compare records that were produced independently of each other for the same event. The first, CORRELATION_ DISCREPANCY, reports a post authentication report for which no audit entry arrived within the retry window of the correlation. The second, FIELD_MISMATCH, compares the fields of the outbound report with those of the audit entry that the post authentication report of

the same login was correlated with, and reports every field in which they disagree. Both follow the detection point IE6 of AppSensor, the violation of security log integrity, and the argument of Section 3.3 that two independent records offer an alternative to protecting a log cryptographically [39]. In addition, input that is written to the audit log without neutralisation can corrupt individual fields of an entry or split it into several lines, which the comparison with an independently produced record reveals as a field mismatch or, if the entry can no longer be correlated, as a discrepancy [33].

The comparison establishes that two records disagree but not which of them was altered, since an attacker who controls the application process can alter the report as well. It also cannot compare fields that only one of the records contains. For encrypted assertions this applies to the fields inside the assertion, which the outbound interceptor cannot read after the encryption, whereas the audit log records them. Unlike the other rules, the comparison does not withdraw as a whole when a field is missing. It compares only the fields that the interceptor observed and that the audit format of the deployment records.

Two rules cannot be assigned to a vulnerability or an attack class. `SUSPICIOUS_USER_AGENT` identifies an indicator for which no documented relation to a specific attack class could be established. It comes closest to the AppSensor detection point RP3, *Suspicious Client-Side Behavior* [39]. `BEHAVIOUR_ANOMALY` is a detection method rather than an attack class, since it may reveal several different attacks indirectly without corresponding to any one of them. It corresponds to the detection point UT1, *Irregular Use of Application* [39]. Both rules are retained in the catalogue, and the absence of a derivation from a vulnerability or an attack class is stated here rather than omitted.

4.5.4 Severity Classification

Each alert detected by the detection layer described in Section 4.5 is assigned a severity level. The severity levels used in this work are based on the high-level risk categories proposed by Graves, which range from R1 to R5. Although Graves does not state an explicit ordering, he identifies the theft or abuse of the signing keys underlying R5 as the worst case. This work treats the categories as increasing in severity. The specific definitions of the risk categories are as follows [21]:

- **R1:** Abuse of system resources
- **R2:** Log on to a specific SP as any user
- **R3:** Log on to a specific SP as a specific user
- **R4:** Steal user passwords
- **R5:** Log on to any SP as any user

These categories describe what an attacker can achieve. The backend, in contrast, uses four levels from low to critical, and the two scales are not mapped one to one. The categories serve as an orientation for the severity of each rule, which is listed in Table 4.2.

A rule is rated critical if its condition directly endangers the authentication of users at an SP, for instance an assertion that is transmitted without encryption. Rules rated high report an attack in progress, such as a series of failed logins for the same subject, a replayed request or a request that shows the traces of a signature wrapping attack. The

attacks examined by Somorovsky et al. target the processing of assertions at the SP [59]. SIGNATURE_WRAPPING_SUSPECTED, in contrast, examines the requests that the IdP receives. In such a request, the traces of a wrapping attack show an attempt but not a compromised login. Rules rated low report indicators that are not harmful on their own, such as a single failed login or the user agent of a script. None of the rules addresses R5, since it presupposes a compromise of the signing key.

The discrepancy rule is classified as medium, since a missing counterpart can also result from operational causes such as a delayed log shipping chain. The mismatch rule is classified as high, since a contradiction between two records of the same event points either to a manipulation or to a defect in the collection, and both undermine the basis on which the other rules operate.

Five rules have no fixed severity, since their impact depends on the context. The two multi factor rules (MISSING_MFA, MFA_BYPASS) depend on whether an SP must use multi factor authentication. The operator can place an SP on a list of providers for which this is required, and for such an SP both rules are rated critical. MFA_BYPASS is also critical if the configuration of the SP permits no flow other than multi factor authentication. In all other cases, both rules are rated medium. WEAK_ENCRYPTION takes its severity from the algorithm policy and CERTIFICATE_EXPIRED from the expiry status of the certificate. BEHAVIOUR_ANOMALY is rated high if at least two independent reasons apply, and medium otherwise.

Table 4.2: *Severity assigned by each rule*

Severity	Rules
Critical	UNENCRYPTED_ASSERTION, WEAK_CONFIGURATION, ASSERTION_REPLAY
High	BRUTE_FORCE, REQUEST_REPLAY, FIELD_MISMATCH, SIGNATURE_WRAPPING_SUSPECTED
Medium	CORRELATION_DISCREPANCY
Low	FAILED_LOGIN, SUSPICIOUS_USER_AGENT
Context	MISSING_MFA, MFA_BYPASS, WEAK_ENCRYPTION, CERTIFICATE_EXPIRED, BEHAVIOUR_ANOMALY

4.6 Visualisation Layer

The primary purpose of the visualisation layer is to present the collected, correlated and detected information to an operator through a user interface. The layer does not generate new information. Instead, it presents the data produced and aggregated by the preceding layers.

The interface provides visibility into detected findings but does not offer any functionality for modifying or controlling the IdP. This is a deliberate design decision rather than an omission and implements the second requirement described in Section 4.1, which follows from the passive monitoring principle adopted in this work.

The interface shows users only by their pseudonyms (Section 4.4), so that the operator can recognise events of the same user without learning who that user is. An operator who

requires the original identity would have to obtain it from the IdP itself. Data protection is thus achieved through the architecture of the system rather than through access control alone.

The interface displays the severity that the detection layer assigns to each finding (Section 4.5.4). This allows the operator to distinguish findings of different importance and to prioritise them.

In addition to the finding itself, the interface indicates which correlation strategy was used to link the underlying records. As described in Section 4.5, the available strategies differ in how reliably they establish the relationship between a post authentication report and an audit entry. Making this information visible allows an operator to judge how well supported a given finding is, rather than presenting all findings as equally certain.

4.7 Design Decisions and Rejected Alternatives

This section presents the main design decisions made for the monitoring tool and the alternatives that were considered but rejected. Each decision involves a trade-off, and the cost of the chosen option is stated alongside its rationale. Two decisions are not repeated here, since they were discussed where they arise, namely the choice of the interception points in Section 4.3.3 and the asynchronous transmission in Section 4.4.

The first alternative was to extend the monitoring tool with the capability to actively intervene in ongoing attacks. In this design, the tool would provide the operator with the option to react to a detected finding by terminating the affected user session or by blocking the corresponding SP. This design was rejected because an incorrect response would not necessarily affect only the service concerned. Since the IdP provides authentication for multiple SPs, an erroneous intervention could disrupt several or even all connected services. The monitoring system is therefore intentionally designed as a passive system. The cost of this decision is that the system cannot prevent an attack that is in progress. It reports the condition it observes and leaves any reaction to the operator.

The second alternative was to incorporate cryptographic mechanisms for detecting log manipulation, following the approaches of Schneier and Kelsey and of Snodgrass et al. discussed in Section 3.3 [45, 57]. Such mechanisms can provide cryptographic evidence of modifications to stored log data. Their integration would, however, require changes to the existing logging and storage infrastructure and would introduce additional processing overhead, which Snodgrass et al. report as up to 16 percent [57].

The proposed system therefore does not provide cryptographic proof of log integrity. Instead, it detects potential inconsistencies by comparing audit log entries with information independently collected by the interceptors. This avoids modifying the existing logging infrastructure while still providing a second observation of the same authentication event. The cost is that an inconsistency indicates a discrepancy between two sources without establishing which of them was altered.

The third alternative was to use machine learning instead of explicitly defined detection rules. In such an approach, the system would learn normal behaviour statistically and identify deviations from it as anomalies. This approach was rejected because the detection

rules developed in this work are explicitly derived from documented vulnerabilities and security requirements. A rule based approach therefore provides direct traceability from a finding to the underlying security rationale, which is a central objective of the derivation described in Section 4.5.3. The cost of this decision is that the system detects only conditions that were anticipated when the rules were formulated. Attack patterns that do not correspond to any defined rule remain unnoticed, whereas a statistical approach could in principle identify previously unknown deviations.

The fourth alternative was to collect all data with a single outbound interceptor. The contexts read by the post authentication interceptor are still part of the context tree at the outbound point, so that one interceptor could collect the data of both and halve the number of transmissions per login. The assertion level fields of encrypted assertions would remain unavailable in either case. This alternative was not examined beyond the request identifier, which the outbound interceptor already reads from the inbound message context. The cost of the chosen design is a second transmission per login.

5 Implementation

This chapter describes the implementation of the proposed monitoring tool and discusses the main challenges encountered during development. It follows the same structure as Chapter 4 by examining each system layer and describing its technical implementation.

5.1 Data Aggregation Layer

As described in Section 4.3, the data aggregation layer uses log shippers to collect and parse log entries and static configuration files, as well as two custom interceptors that operate within the Shibboleth IdP. The log shipping stack consists of Filebeat for reading the source files and Logstash for preprocessing and transmitting the collected data. Both components run as separate containers on the same host as the IdP and access its log files and configuration through mounted directories. This placement is what allows them to share the pseudonymisation salt and the message authentication secret with the interceptor, as described in Section 5.2.

A key aspect of the implementation is the handling of audit log entries. Instead of parsing the audit log according to a fixed format, Logstash processes the audit fields as key-value pairs. This allows the monitoring system to adapt to dynamic changes in the configured audit format.

The monitoring tool handles these dynamic changes by maintaining a field registry. The registry periodically retrieves the most recent audit entries stored in the database and extracts the names of all fields that are currently present. Using only recent entries ensures that fields no longer written by the IdP are eventually removed from the registry. Both the detection rules and the correlation strategies query the registry before they are applied, which is how the withdrawal described in Section 4.5.2 is realised.

The audit log is not the only log file read by the collection layer. As described in Section 4.3.1, authentication attempts that do not result in a completed transaction produce no entry there, which applies in particular to failed password validations. In the deployment used in this work, the authentication flows for password login and for MFA (Section 4.3.2) therefore record every attempt, including failed ones, in separate audit files. Successful password attempts are discarded, since these logins already appear in the general audit log. Filebeat is configured to read these files in addition to the general audit log, and the Logstash pipeline tags the resulting records with their source so that they remain distinguishable in the backend. Without this second source, the rules that evaluate failed authentication attempts would have no data to operate on.

A particular difficulty of this mechanism is that a missing field does not manifest itself as an error. If the audit format of a deployment does not include a field that a rule depends on, no exception is raised and no entry is written to any log. The information is simply absent, and a rule evaluating it would silently operate on incomplete data. The registry therefore also makes this absence detectable.

The static configuration files are collected by the same log shipping stack, but processed differently. Unlike the audit log, which is written continuously and line by line, *relying-party.xml* and the metadata documents change rarely and are read as a whole. Filebeat is therefore configured to aggregate the lines of such a file into a single event before transmitting it, and Logstash forwards the result without field level parsing. The number of lines combined in this way is bounded by configuration, which places an upper limit on the size of a document that can be transmitted as a unit. The interpretation of the XML structure takes place in the monitoring tool itself, where the relevant security settings are extracted and stored per SP. Filebeat monitors these files and transmits them only when their content has changed. The backend therefore does not receive the same configuration repeatedly, but only when a deployment has actually been modified, which is also what makes the detection rules operating on configuration meaningful at all.

Unlike the log shippers, the two interceptors are custom components developed as part of this work. They are registered as described in Section 2.3.1, the post authentication interceptor through the *postAuthenticationFlows* property and the outbound interceptor through the *outboundInterceptorFlows* property [11].

The post authentication interceptor extends the `AbstractProfileAction` API of the Shibboleth IdP and operates on the `ProfileRequestContext`, the root of the context tree described in Section 2.3.2 [46, 49]. From this context it accesses the child contexts that carry the information relevant to the monitoring purpose. The `RelyingPartyContext` identifies the SP for which the authentication is performed, the `SubjectContext` provides the authenticated subject and the inbound `MessageContext` gives access to the raw SAML request as it was received [48, 50, 52]. Further contexts, among them the `AuthenticationContext` and the `SessionContext`, supply information about the authentication flow that was used and the session state at the time of the request [47, 51].

Like the post authentication interceptor, the outbound interceptor consists of an action class and its own Spring Web Flow subflow. The subflow contains a single state that calls the action and then returns control to the profile [11].

The action reads the outbound message context. If it does not contain a SAML 2 response, the action returns without effect. Otherwise it collects the status code, the identifier and the issue time of the response, the identifier of the request that the response answers, and whether the response contains encrypted assertions. If the assertion is not encrypted, it additionally reads the identifier and issue time of the assertion, the authentication instant, the session index, the authentication context class and the format and value of the name identifier, of which the value is pseudonymised before transmission. For encrypted assertions these fields are not collected, since the assertion is only available as ciphertext at this point and the IdP holds no key to decrypt it. The destination attribute of the response is empty at this hook and is therefore not used. The identifier of the original request, which links the outbound report to the post authentication report, is read from the inbound message context.

Both reports are transmitted by the same mechanism, but to separate endpoints. Section 5.2 describes this mechanism in more detail. The backend stores each report in its own index. The separation is necessary because the backend treats a second submission with the same identifier as a resubmission of the request and increments a counter that

the replay rule evaluates. During development, registering the action of the post authentication interceptor at both hooks produced reports with a submission count of two and would have triggered that rule for every login.

Since the audit format is configurable (Section 4.3.1), the deployment used in this work was extended by three tokens: the identifier of the response, the identifier of the request that it answers and the issue time of the response. They allow the response-level fields of the outbound report to be compared with the audit entry, as `FIELD_MISMATCH` requires (Section 4.5.3).

Before any record leaves the IdP, its sensitive identifiers are pseudonymised (Section 4.4). This takes place in two different components. The interceptors pseudonymise the identifiers they collect within the Java application, whereas Logstash pseudonymises the audit fields during preprocessing. If the two produced different values for the same identifier, no error would occur, but the records could no longer be matched through their pseudonyms. Both components therefore apply the same hash function and share the same secret salt. The salt is provided through the deployment configuration rather than embedded in either component, so that it can be rotated without modifying the interceptors or the Logstash pipeline.

5.2 Transport Layer

Before the aggregated data is transmitted, each collecting component computes an HMAC over every record, as outlined in Section 4.4. Both Logstash and the interceptor hold the shared secret, so that the backend can verify that a received record was not altered and originates from an authorised collection component.

The verification is conditional on configuration. If no secret is configured on the sending side, the message is transmitted without an HMAC, and the backend enforces validation only where a secret has been configured there as well. This makes it possible to deploy the system without prior key distribution, for instance in a test environment, at the cost of accepting unauthenticated records in that case. A production deployment is therefore expected to configure the secret on both sides.

The monitoring tool provides a separate endpoint for each type of collected data. A post authentication report, an outbound report and a configuration document differ in structure and in the processing, so that separating them at the interface avoids having to determine the type of a record before it can be handled. The path of audit entries is different, since Logstash writes them directly into Elasticsearch, as described later in Section 5.3.1.

As mentioned in Section 4.4, the interceptors send their payload asynchronously. Neither of them waits for a response from the monitoring tool, and each proceeds with the authentication flow immediately after dispatching its record. If a transmission fails, whether because the backend is unreachable, the request times out or the record is rejected, the interceptor writes a warning in the log of the IdP but does not send the record again.

To quantify the cost of this design decision, the interceptors also support a synchronous mode. In this mode each of them waits for the backend to confirm receipt before the

authentication flow continues, which makes the time spent on transmission visible in the overall duration of a login. The mode is not intended for production use but serves as a reference point against which the asynchronous variant can be compared. The resulting measurements are presented in Section 6.4. The synchronous mode applies to both interceptors and is selected by the same environment variable, so that a login in that mode contains two blocking transmissions.

5.3 Correlation and Detection Layer

This section describes the main technical components of the backend application. It follows the same structure as Section 4.5.

5.3.1 Storage

Elasticsearch serves as the primary data store of the backend application. It was chosen to ease the integration with the log shipping stack described in Section 5.1. The application uses separate indices for the different types of data it handles, namely audit entries, metadata, configuration data and the reports of the two interceptors. These indices differ in how they are created. Audit entries are written by Logstash into time based indices that are rotated daily, whereas post authentication reports and outbound reports are stored in a single index each, maintained by the application itself. Queries that span audit data therefore address an index pattern rather than a concrete index, which restricts the set of Elasticsearch operations available for them.

Elasticsearch does not provide relations between documents. The result of a correlation is therefore stored as a field on the post authentication report, which holds the identifier of the audit entry it was matched with. The strategy that produced the match is stored alongside it, as described in Section 4.5.1, so that the basis of a correlation remains visible after the fact.

5.3.2 Correlation

This section describes how the two challenges of the correlation layer identified in Section 4.5.1 are addressed in the implementation, namely the temporal offset between the arrival of related records and the varying availability of fields in the audit log. The post authentication report is static and always contains the fields required for correlation. The constraint therefore lies entirely on the audit side. The audit logging documentation lists all fields that a deployment may record [3], of which four are usable for establishing a relationship between an audit entry and a post authentication report.

- **I**: the inbound message identifier of the SAML request
- **u**: the username, pseudonymised by Logstash (*usernameHash*)
- **a**: the client IP address, pseudonymised by Logstash (*ipHash*)
- **T**: the timestamp of the event

The audit format records further identifiers that are unique per transaction, but none of them improves the correlation. The `InResponseTo` value of the response repeats the identifier of the inbound request. A strategy built on it would therefore find exactly the same counterpart as the inbound message identifier. The assertion identifier and the outbound message identifier are created only after the post authentication hook has run [3, 10], so that the post authentication report cannot contain them. The outbound interceptor reads them, the assertion identifier only for unencrypted assertions. Both serve the comparison of the two records rather than the correlation. Which identifiers can be used for correlation is thus determined by the observation point rather than by the audit format alone. The remaining fields, among them the entity identifier of the SP, the authentication flow and the released attributes, are identical across many logins of the same SP and narrow the candidates no further than the SP already does.

The four usable fields differ in how precisely they identify a counterpart. The inbound message identifier is unique per request and therefore establishes the relationship unambiguously, since the same value appears in both records. The two pseudonymised identifiers narrow the set of candidates to those belonging to the same subject and origin, but several logins of the same user may share them. The timestamp alone can only indicate temporal proximity. Strategies that rely on the hashes or on time alone additionally restrict the candidates to the SP recorded in the report, since an audit entry for a different SP can never be its counterpart. The inbound message identifier needs no such restriction, since it is unique. Where the inbound message identifier is not recorded, the relationship can therefore only be approximated. If none of the identifiers is available, the timestamp remains the sole criterion.

The three correlation strategies implement a common interface and are applied in a fixed order of precedence. Each strategy first checks in the field registry described in Section 5.1 whether the audit fields it depends on are recorded. Where a required field is not recorded by the deployment, the strategy withdraws and the next one in the chain is attempted.

The first strategy, `INBOUND_MESSAGE_ID`, matches the inbound message identifier of the post authentication report against the corresponding audit field. Since this value is unique per request, a match establishes the relationship without ambiguity. The second strategy, `HASH_AND_TIME_WINDOW`, narrows the candidates by SP, pseudonymised subject and pseudonymised client address, and additionally restricts them to a configurable time window around the event. The third strategy, `TIME_WINDOW`, retains only the SP and the time window. It is therefore used where neither the message identifier nor the pseudonymised identifiers are recorded.

Both time window strategies may return more than one candidate. In this case the entry with the smallest temporal distance to the post authentication report is selected. The strategy that produced a match is stored alongside the result, so that the reliability of a given correlation remains apparent afterwards.

The timestamp used for these windows requires particular attention. The field that Elasticsearch assigns to an audit document by default reflects the point at which Filebeat read the log line, not the point at which the authentication took place. Since Filebeat processes log lines in batches, this value is shared by all entries of a batch and does not

preserve their order. The Logstash pipeline therefore derives a dedicated field from the event timestamp recorded by the IdP, and both time window strategies operate on this field. The effect of this distinction on correlation precision is reported in Section 6.5.

The temporal offset described in Section 4.5.1 is addressed by repeated attempts. A post authentication report that could not be correlated on arrival is retried periodically, with a minimum age before the first attempt to account for the indexing delay of the log shipping stack. After a defined retry window has elapsed without a match, a separate scheduled sweep marks the report as permanently uncorrelated. This marking is what allows an uncorrelated report to be distinguished from one that is still awaiting its counterpart, and thus what makes the proportion of successfully correlated reports determinable at all.

Two mechanisms prevent an audit entry from being claimed twice. Within a single retry run, entries that have already been assigned are excluded from the candidate set of subsequent reports. Across runs, the application verifies against the stored data whether an audit entry has already been referenced by another report before accepting a match.

5.3.3 Detection

The detection logic is divided into four engines, following the separation by input type described in Section 4.5.2. The rule engine evaluates login events derived from audit entries, the configuration rule engine evaluates the security settings of an SP, the metadata rule engine evaluates its metadata and the interceptor rule engine evaluates the post authentication reports produced by the interceptor.

The rules of each engine implement a common interface. A rule receives a single object of the type its engine is responsible for and returns either an alert or nothing. Each rule first checks in the field registry described in Section 5.1 whether the fields it depends on are recorded. Where a required field is not recorded by the deployment, the rule returns no result rather than evaluating incomplete data.

The engines are executed by a scheduler at intervals that reflect the rhythm of their input. Login events and post authentication reports arrive continuously and are therefore evaluated frequently, whereas configuration and metadata change rarely and are checked at longer intervals. To avoid evaluating the same login events repeatedly, the application maintains a marker that records the point up to which audit entries have already been processed. Each run evaluates only entries newer than this marker, and the marker is advanced once the run has completed. A grace period is applied before an entry is considered, so that records still being indexed by the log shipping stack are not skipped.

A further mechanism concerns repeated findings. A weakness in a configuration persists until the operator changes it, and evaluating the same configuration every few minutes would otherwise produce a continuous stream of identical alerts. The engines for the configuration, the metadata and the post authentication reports therefore store at most one alert of a given type per SP and day. The engine for login events stores at most one alert of a given type per audit entry, so that a rule that examines a property of every login, such as an unencrypted assertion, raises an alert for every affected login. Rules that aggregate several logins limit themselves further, `BRUTE_FORCE` to one alert per subject and day and `ASSERTION_REPLAY` to one per assertion and day.

The rules differ in the kind of condition they examine. Three examples illustrate this range. `WEAK_ENCRYPTION` compares the encryption algorithm recorded for a login against a list of algorithms considered insecure, which is maintained in the application and can be adjusted without changing the rule itself. `BRUTE_FORCE` does not evaluate a single event in isolation but counts failed authentication attempts of the same subject within a defined time window, which requires a query across previously stored events. `SIGNATURE_WRAPPING_SUSPECTED` operates on the raw SAML request contained in a post authentication report and examines it for more than one signature element and for signature references to an identifier that occurs more than once. A signature refers to the element it protects through this identifier (Section 2.2.2), so that a second element with the same identifier leaves open which of the two was signed. Signature elements only appear in requests sent with the HTTP-POST binding, since the HTTP-Redirect binding removes the signature from the message and transmits it as a URL parameter [14]. The remaining rules follow one of these patterns or compare an observed event against the configuration declared for the SP involved, as described for `MFA_BYPASS` in Section 4.5.3.

A further difficulty arose with the comparison between configuration and runtime event. The authentication flows permitted for an SP are listed in *relying-party.xml* by their short name, for instance `MFA`, whereas the audit log records the full flow identifier with the prefix `authn/`, for instance `authn/MFA`. A direct string comparison between the two never matches, and the rule would consequently never report a finding. Like the two cases in Section 5.1, this fault would have remained silent, since no exception or log entry would have revealed it. The comparison is therefore performed token by token and accepts both notations. It is implemented in a shared comparison function that is used by all rules evaluating authentication flows.

Two rules operate on pairs of records and are therefore not evaluated by the rule engines. Both are triggered by the correlation service. When a report is marked as permanently uncorrelated, either because the retry loop reaches the end of its window or because the periodic sweep finds it expired, the service raises a `CORRELATION_DISCREPANCY` alert of medium severity. Each report is expired exactly once, so that this alert cannot produce repeated findings.

When a report is correlated with an audit entry, the service loads the outbound report with the same request identifier and passes it together with the audit entry to the consistency service. If no outbound report exists, the check is skipped. Otherwise the service compares the fields that both records contain, namely the status, the identifier of the answered request, the identifier and the issue time of the outbound message and the encryption state. For an unencrypted assertion, it also compares the identifier of the assertion, the authentication instant, the authentication context, the format of the name identifier and the pseudonymised name identifier. A field is compared only if the interceptor observed a value for it and the field registry shows that the audit format of the deployment records it. If the audit entry lacks a value for a field that the registry lists, the field counts as deviating, since a removed field is itself a sign of tampering. On a deviation the service stores a `FIELD_MISMATCH` alert of high severity, whose details list each deviating field with the values of both records.

5.4 Visualisation Layer

The visualisation layer displays the collected, correlated and detected data through an Angular based web application. A generic dashboard such as Kibana was not used, since the views required here are specific to the domain of the monitoring tool. They present findings together with the records from which they were derived and follow the relationships that the correlation layer establishes, neither of which can be expressed through generic index queries alone.

The dashboard provides an overview of the most important data within a specified timeframe. It includes the total number of logins, failed logins, successful logins and detected alerts. In addition, it provides a line chart showing the number of logins over the selected timeframe, an overview of the total number of logins per SP and a detailed table of the individual login events. The login overview for each SP also provides a detailed dialog containing the configuration and metadata defined for the respective SP in the Shibboleth IdP. The SP details also list the misconfigurations that have been detected.

The second major page of the web application is the alert page. As its name suggests, this page displays the recent alerts detected by the monitoring tool. It includes a vertical bar chart showing the alerts detected during the current week, grouped by their respective severity. The page also provides a table of alerts ordered by severity.

Each row in the alert table is interactive and opens a detailed dialog containing information about the selected alert. This dialog also provides access to the audit entry and the post authentication report associated with the alert. Conversely, both the audit entry and the post authentication report dialogs list all alerts detected for the corresponding event. The relationship established by the correlation layer is therefore navigable in both directions, which allows an operator to examine a finding together with the records it was derived from rather than in isolation.

The audit entry view displays only the information that was available in the corresponding audit file of the Shibboleth IdP. Since subjects and client addresses are pseudonymised before leaving the IdP, as described in Section 5.1, the interface presents these values in their hashed form. An operator can therefore recognise that several events originate from the same subject without learning the identity of that subject.

Each alert can also be acknowledged by an operator and marked as a false positive. Acknowledged alerts and false positives are removed from the default alert view, which only displays active alerts.

The third major page displays the collected post authentication reports in a table. Each row contains the most relevant information from the corresponding post authentication report and indicates whether the report was successfully correlated with an audit entry. This makes the state described in Section 5.3.2 visible to the operator, including reports for which no counterpart was found within the retry window. Each row can be expanded to reveal additional details, including the raw SAML request, and a button allows the operator to open the corresponding alert in a detailed dialog.

6 Evaluation

This chapter evaluates the proposed monitoring system. It presents the test setup, evaluates the correlation and detection capabilities, measures the performance overhead introduced by the interceptors, lists the defects that the evaluation uncovered and concludes with a discussion of the threats to validity.

6.1 Test Setup

To facilitate integration with the Java testing framework, the test environment runs in containers. This comprises the Shibboleth IdP, an LDAP directory serving as the user store, the SPs and the log shipping stack. Only the backend application of the monitoring tool and the test code run directly on the host.

Two SPs are deployed, referred to as the weak SP and the clean SP in the following. The weak SP is used for the detection scenarios and is configured to exhibit the weaknesses that the rules are intended to identify. The clean SP encrypts its assertions and serves as the reference for the false positive rate, since no legitimate login against it should raise an alert.

The evaluation distinguishes three levels of testing. Unit tests examine individual components in isolation, with their dependencies replaced by mocks, so that a test result reflects the behaviour of that component alone. Integration tests run against a real Elasticsearch instance, which additionally covers the persistence layer, the index mappings and the queries that a mock cannot represent. End-to-end tests exercise the complete pipeline, from the IdP through the log shipping stack.

Logins are generated in two ways. An HTTP client harness performs the SAML login sequence directly, parsing the forms returned by the IdP and submitting them without rendering the pages. Selenium based tests drive an actual browser through the same sequence. The two differ in the interval between consecutive logins, since the harness proceeds as fast as the server responds whereas a browser adds the time required for page loading and form interaction. This difference is relevant for the correlation measurements in Section 6.2, where the temporal density of logins determines how reliably records can be matched.

The environment is not a production deployment. It comprises a single IdP, two SPs and a small number of test accounts, and all traffic is generated for the purpose of measurement. The implications of this are discussed in Section 6.6.

6.2 Correlation

Section 5.3.2 described the correlation mechanism, which links each post authentication report to the audit entry of the same login. It first tries `INBOUND_MESSAGE_ID` and falls back to two heuristic strategies where the identifier is not available. Both heuristics query the audit entries of the same SP within a time window around the report. `HASH_AND_`

TIME_WINDOW additionally requires the same *usernameHash* and *ipHash*, whereas TIME_WINDOW relies on the time alone. The entries returned by such a query are referred to as candidates in the following, and the strategy selects the candidate with the smallest temporal distance to the report. This section examines how often the selected candidate is the correct one (precision) and how many reports find a counterpart at all (coverage). The exact strategy serves as the reference for the heuristics, and the measurement is repeated on datasets that differ in the number of users and in the login generator.

6.2.1 Method and Datasets

Ground truth. To determine the precision of the heuristic strategies, a reference is required that indicates whether a given correlation was correct. The correlation via INBOUND_MESSAGE_ID establishes a one-to-one relationship, since the identifier is unique per request. Wherever this strategy produced a match, the correct counterpart is therefore known without ambiguity, which allows it to serve as a ground truth for the heuristic strategies. An analysis program in the test sources of the backend proceeds as follows:

- It collects all post authentication reports of a configurable time period that were correlated via INBOUND_MESSAGE_ID.
- For each report and each window size from ±1 to ±60 s, it executes the query of the heuristic strategy unchanged and selects the same candidate as the production system would, namely the one with the smallest temporal distance.
- It compares the selected candidate with the known correct audit entry and classifies the outcome as a hit, an incorrect assignment or no match. Precision is the share of hits among the assigned reports, coverage the share of reports that were assigned at all.
- It records the offset between the reception of the report and the event time of its audit entry, and the distance to the nearest other audit entry of the same SP as a measure of the local login density.

In production, an audit entry that has already been assigned to a report is no longer offered as a candidate for other reports. The analysis has to omit this filter, since every audit entry in the ground truth has already been assigned to its correct report, so that the filter would remove exactly the candidate that is being looked for. Each report is therefore evaluated against all audit entries in its window.

Datasets. The heuristics only take effect when the audit log lacks the inbound message identifier, for instance because an operator does not record it or uses an older audit format. Whether they then select the correct entry depends on two properties of the traffic: how many logins at the same SP fall into the same time window, and whether these logins can be told apart by subject and address. Both vary considerably in production. At the start of a lecture or during an exam registration, many users log in at the same SP within a few seconds, while at night a single login may stand alone. Some users log in from an address of their own, while others share one behind a gateway. The five datasets reproduce

these situations step by step, each adding a condition that the previous ones leave open. Table 6.1 summarises how they were generated. Coverage is additionally determined on the performance series of Section 6.4, which comprises 7,236 reports and is by far the largest dataset.

The starting point is the simplest case, a single user who logs in repeatedly at the same SP (D1). For the heuristics, this case removes every distinguishing feature except time. All candidates share subject, address and SP, so that the hashes exclude nothing and both heuristics behave like `TIME_WINDOW`. The correct entry can only be found if the time recorded for each login is precise enough to keep consecutive logins apart. D1 therefore tests the time base on which both heuristics rest. If it failed here, none of the further scenarios could succeed.

In production, however, the logins within a window rarely stem from one person. In D2, three users log in at the same SP at the same time, so that candidates of different users lie in the same window. This is precisely the situation for which the hashes exist. `HASH_AND_TIME_WINDOW` can discard the entries of other users, whereas `TIME_WINDOW` has to choose among all of them by time alone. D2 is thus the first dataset in which the two heuristics differ, and it shows what an operator loses who records neither the subject nor the address in the audit log.

D1 and D2 are generated by the HTTP harness, which starts the next login as soon as the server has answered. It produces logins at intervals that no user reaches with a browser, since loading pages and filling in forms take time. If the harness is considerably denser than real traffic, D2 overstates how often the time alone fails. D3 therefore repeats D1 with Chrome driven by Selenium, which loads every page and submits the forms as a browser does, and shows how closely spaced the logins of one user are under real browser timing.

D3 still covers only one user. D4 combines the two previous steps: three users log in simultaneously, each through their own browser, which comes closest to several people logging in at the same time. It shows whether the weakness of `TIME_WINDOW` that D2 exposes also occurs under browser timing, and how often. Since every browser runs in its own container, each user also has an address of their own, as users at different devices or in different networks do. This makes it possible to analyse the same data a second time without *usernameHash* and to determine whether *ipHash* alone keeps the users apart.

Separate addresses cannot be taken for granted, however. Behind a gateway with network address translation, for instance in a company network, many users appear under the same address and *ipHash* no longer distinguishes them. The separation then rests on *usernameHash* alone. D5 reproduces this case by running three users as threads of a single process, so that all logins originate from one address.

6.2.2 Results

Table 6.2 summarises the precision of both heuristics in the five datasets. The figures are identical for all window sizes from ±1 to ±60 s, for a reason explained below. The following paragraphs state what the figures show, from the coverage of the correlation to the limits of the heuristics.

Table 6.1: *Datasets of the correlation measurements*

Dataset	Login generator	Users	Logins per user	Reports
D1	HTTP harness	1	200 + 3 warm-up	203
D2	HTTP harness	3	200	600
D3	Selenium	1	200 + 2 warm-up	202
D4	Selenium, one container per user	3	200 + 2 warm-up	606
D5	HTTP harness, threads of one process	3	200	600

Every report finds its counterpart. In the performance series, all 7,236 post authentication reports were correlated with their audit entry through the inbound message identifier, and none expired without a counterpart. The coverage of the exact strategy was therefore 100 percent, with a lower bound of 99.95 percent for the 95 percent Wilson interval [63]. That this figure can be determined at all is due to the sweep described in Section 5.3.2, which marks reports without a counterpart as permanently uncorrelated after a waiting period, so that a lost report can be told apart from one that is still waiting. The heuristics, too, assigned every report in all five datasets, even with the smallest window of ±1 s. This follows from the offsets in Table 6.4: a report arrives at most about 160 ms before or after the event time of its audit entry, so that the correct entry always lies within the window. Where a heuristic fails, it therefore assigns a report to the wrong counterpart rather than to none, which is why the following paragraphs concern precision.

With the hashes, the heuristic is as reliable as the exact strategy. `HASH_AND_TIME_WINDOW` selected the correct entry for every report in all five datasets. This includes D1, where the hashes exclude nothing and the event time alone decides, and D5, where all users share one address. The size of the window does not affect the precision. In D1 the mean number of candidates rises from 6.4 at ±1 s to 197.6 at ±60 s without a single wrong assignment, since a larger window only adds candidates that lie further away and are therefore never selected. The window therefore only has to be large enough to contain the correct entry, and a larger window costs nothing but query effort. In the test environment ±1 s would have sufficed, but in production a report can arrive later, since the interceptors give up a transmission only after 1.5 s, and on separate hosts the clocks may differ. The default of ±10 s covers both with a wide margin, at the price of examining 58.1 instead of 6.4 candidates per report in D1.

Without the hashes, wrong assignments occur only between logins less than 100 ms apart. `TIME_WINDOW` reached 65.0 percent in D2, 73.7 percent in D5 and 89.9 percent in D4. Table 6.3 breaks these figures down by the distance of each login to the nearest other login at the same SP, with the number of logins in each range in parentheses. All wrong assignments concern logins with a distance below 100 ms. At larger distances, `TIME_WINDOW` was correct in every case. Within this zone, it selected the correct entry in 56 to 69 percent of cases, regardless of whether the logins came from the harness or from browsers. The differences between the overall figures therefore do not stem from the

strategy but from how many logins fall into the zone: 87 percent in D2, 84 percent in D5 and 23 percent in D4.

Table 6.2: *Precision of the heuristic strategies per dataset*

Dataset	Scenario	HASH_AND_TIME_WINDOW	TIME_WINDOW
D1	Single user	100%	100%
D2	Several users	100%	65.0%
D3	Real browser	100%	100%
D4	Real browser, several users	100%	89.9%
D5	Shared address	100%	73.7%

Table 6.3: *Precision of TIME_WINDOW by distance to the nearest other login at the same SP*

Distance	D2	D3	D4	D5
< 100 ms	59.7% (521)	— (0)	55.8% (138)	68.7% (504)
100–300 ms	100% (65)	— (0)	100% (132)	100% (96)
300 ms–1 s	100% (14)	— (0)	100% (258)	— (0)
> 1 s	— (0)	100% (202)	100% (78)	— (0)
Share below 100 ms	86.8%	0%	22.8%	84.0%

Real browser traffic reaches this zone far less often. With a single browser user (D3), every login lay more than one second away from the next, and a window of ±1 s contained on average one candidate instead of 6.4 with the harness. Even with three users logging in simultaneously through browsers (D4), less than a quarter of the logins fell below 100 ms. The weakness of TIME_WINDOW is thus not an artefact of the harness, since it is just as pronounced within the zone, but the harness reaches the zone far more often than browser traffic does. How often a production IdP reaches it depends on its load at peak times and cannot be derived from the test environment.

Each hash covers the case in which the other one is uninformative. In D4, every user had an address of their own. Analysed without *usernameHash*, the heuristic found exactly the same candidates as with both hashes, for every window size and including the 138 logins below 100 ms, and thus again reached 100 percent. *ipHash* alone therefore separates users who log in from different devices or networks. In D5, where all users shared one address, the same variant produced exactly the figures of TIME_WINDOW, since a filter on the only address present excludes nothing. HASH_AND_TIME_WINDOW nevertheless remained at 100 percent, because *usernameHash* separated the users on its own. In all tested scenarios, the heuristic thus stays exact as long as at least one of the two identifiers distinguishes the users, and it falls back to the density dependence of TIME_WINDOW only when both are missing or uninformative.

Operating limit of the heuristics. Table 6.4 shows the offset between the reception of a report and the event time of its audit entry. This was not recorded for D2. It is mostly negative, by about 30 ms, because the post authentication interceptor runs in the middle of the profile flow, whereas `%T` marks the completion of the transaction. Since the heuristics select the entry closest to the reception time, a neighbouring login can only be selected instead of the correct one if the two lie closer together than twice the largest absolute offset (last column). Across all datasets, this critical distance is at most 316 ms (D4), which corresponds to about three logins per second. For `HASH_AND_TIME_WINDOW`, the limit applies to logins of the same subject from the same address at the same SP, a rate that interactive users do not reach. For `TIME_WINDOW`, it applies to all logins at an SP, which explains why this strategy fails in dense traffic. The bound is conservative, since wrong assignments were only observed below 100 ms. All offsets were measured on a single host, where the IdP and the backend share one clock. On separate hosts, the difference between the clocks adds to the offset and lowers the limit, so that the offset, which the analysis records, has to be measured again in a different environment.

Table 6.4: *Offset between the reception of a report and the event time of its audit entry*

Dataset	Minimum	Maximum	Critical distance
D1	−98 ms	+75 ms	196 ms
D3	−102 ms	−17 ms	204 ms
D4	−158 ms	+42 ms	316 ms
D5	−50 ms	+110 ms	220 ms

Taken together, the correlation found a counterpart for every report, and with the inbound message identifier or at least one separating hash, it found the correct one in every tested scenario. Only an audit log that records neither the identifier nor the hashes leaves the correlation to time alone, and it then assigns reports to the wrong entry where logins at the same SP follow each other within less than 100 ms. Operators should therefore record `%I` in the audit format or, where that is not possible, at least the subject and the address.

6.3 Detection

Section 5.3.3 described the detection layer, which evaluates the rules in four engines, one for each type of input. Most rules examine a single input for a condition that indicates a weakness or an attack, for instance an assertion that was sent unencrypted or a series of failed logins for the same subject. Two rules compare records that were produced independently of each other (`FIELD_MISMATCH` and `CORRELATION_DISCREPANCY`).

This section examines whether each rule behaves as specified, that is whether it raises an alert when the condition it examines occurs and remains silent when it does not. Since no production logins with a known classification are available, the rules are tested in scenarios whose expected outcome is fixed in advance, on the test levels introduced in

Section 6.1. In addition, series of legitimate logins show whether the rules remain silent when no alert is expected.

6.3.1 Method and Scenarios

Tests. There are two types of tests. A true positive test constructs a scenario in which a rule is supposed to raise an alert and confirms that it does. A true negative test constructs a scenario in which no alert is due and confirms that none is raised. How much a test shows depends on the level at which it runs. In an integration test, the test builds the input of the rule itself, for instance an audit entry or a post authentication report, stores any history the rule requires in Elasticsearch and passes the input directly to the rule engine rather than waiting for the scheduler, so that the result does not depend on its timing. Such a test covers the rule, its queries and the stored documents, but not the way in which Filebeat and Logstash turn a real audit line into such an input. An end-to-end test starts from a real event at the IdP, usually a login in the browser, and covers this path as well, which makes it the only level at which a fault in the log shipping stack can become visible.

Scenarios. In production, the detection layer has to meet two expectations at once. It has to report the weaknesses and attacks that the rules describe, and it has to remain quiet during the vast majority of logins, which are legitimate, since an operator who receives alerts for ordinary logins soon stops reading them. The two comparison rules carry a third expectation, namely to notice when a record has been altered or has gone missing. The scenarios address these expectations in turn and finally repeat the second one under sustained load.

Every rule has at least one scenario at the integration level that contains the condition it is meant to detect. For most rules this is a single prepared input, such as an audit entry that records an unencrypted assertion or a SAML request with two signature elements, a typical trace of a signature wrapping attack, which the rule treats as a possible signature wrapping attempt [59]. Rules that depend on history receive it in the same way.

At the end-to-end level, eight rules are triggered by a login in the browser. Four of them need nothing but the login itself: a login with the user agent of a script, a login with a wrong password, multiple failed logins in quick succession and a login at the weak SP, whose assertions are not encrypted. For `BEHAVIOUR_ANOMALY`, a user first logs in five times with the same browser and then once with a client that the stored profile does not contain. For `WEAK_ENCRYPTION`, the copy of the clean SP metadata that the IdP has loaded is changed so that it offers only Triple DES for encryption. The IdP then encrypts the next assertion for this SP with this algorithm. The scenarios of the two comparison rules are described below with the third expectation. Three further rules are triggered by a changed file. For `WEAK_CONFIGURATION` and `MISSING_MFA`, the test adds an override to `relying-party.xml` that neither encrypts the assertions nor offers an MFA flow. For `CERTIFICATE_EXPIRED`, it adds the metadata of an SP whose certificate has expired. Since the metadata rules are only evaluated at start-up and once a day, this test starts the scheduled check itself once the metadata has arrived. Each of these scenarios has a true

negative counterpart with the same trigger but without the weakness, for instance a further login with the known browser or an override that encrypts and offers an MFA flow. For `MFA_BYPASS` and `SIGNATURE_WRAPPING_SUSPECTED`, no end-to-end scenario was implemented, and the two replay rules have only a true negative test at this level. Table 6.5 states the reasons.

The second expectation is tested with legitimate logins through the browser. At the clean SP, three users log in alternately, 100 times in total, and after a further 100 seconds, in which the scheduler evaluates all entries, none of the logins may have raised an alert. Since every alert in this run would be a false alarm, the run is at the same time a true negative test for every rule that can react to a login. The same run against the weak SP tests the consistency check in the presence of the alerts that the weaknesses of this SP rightly cause, so that there no `FIELD_MISMATCH` alert may arise. In addition, a single legitimate login at the clean SP provides end-to-end true negative tests for eight rules, among them the two replay rules, for which no true positive scenario exists at this level.

The third expectation concerns someone who alters the audit entry of a login after the fact, for instance to conceal which request a response answered. The consistency check is meant to notice this, since the outbound report is produced independently by the IdP and reaches the backend directly. It compares the fields listed in Section 5.3.3 that the audit format records, five for every login and five more for an unencrypted assertion. To produce a manipulation, the test performs a login against the clean SP and waits until its audit entry has reached Elasticsearch. It then replaces the identifier of the answered request with a different value. This happens before the backend correlates the entry, since the backend attempts a correlation only once a report has reached a minimum age (Section 5.3.2).

An audit entry can also go missing, for instance when the log shipping stack fails. `CORRELATION_DISCREPANCY` is meant to notice this, since the post authentication report then has no counterpart. To produce a missing record, the test stops Filebeat before a login, so that the report reaches the backend but the audit entry does not. For this test, the waiting period is shortened from fifteen minutes to one minute by configuration.

Finally, the comparison rules must not raise false alarms when many logins arrive in quick succession, since both rely on the records of every login being matched in time. The performance series of Section 6.4 provides this load with 10,854 logins against the weak SP, in measurements of about 200 logins each. In 7,236 of them the interceptors were active and transmitted both reports. The remaining logins belong to the baseline configuration without interceptors.

6.3.2 Results

Table 6.5 shows which rules are also tested end-to-end and what an end-to-end test of the others would require. The following paragraphs state what the tests establish, from the coverage of the rules to the limits of what the results can show.

Every rule is tested against a real Elasticsearch instance, and thirteen are also tested end-to-end. All fifteen rules have a true positive test on the unit and on the integration

Table 6.5: *End-to-end coverage per rule*

Rule	End-to-end	Trigger or reason
SUSPICIOUS_USER_AGENT	TP, TN	Login with the user agent of a script
FAILED_LOGIN	TP, TN	Login with a wrong password
BRUTE_FORCE	TP, TN	Five failed logins in quick succession
UNENCRYPTED_ASSERTION	TP, TN	Login at the weak SP
BEHAVIOUR_ANOMALY	TP, TN	Login with a client unknown to the profile
WEAK_ENCRYPTION	TP, TN	Login after the SP metadata offers only Triple DES
FIELD_MISMATCH	TP, TN	Login with an altered audit entry
CORRELATION_DISCREPANCY	TP, TN	Login with Filebeat stopped
WEAK_CONFIGURATION	TP, TN	Changed `relying-party.xml`
MISSING_MFA	TP, TN	Changed `relying-party.xml`
CERTIFICATE_EXPIRED	TP, TN	New SP metadata
ASSERTION_REPLAY	TN	A replayed assertion is presented to the SP, not to the IdP
REQUEST_REPLAY	TN	Requires a replay after the replay cache of the IdP has expired
MFA_BYPASS	—	In the test environment, the audit entry does not show whether a second factor was used
SIGNATURE_WRAPPING_SUSPECTED	—	Requires a crafted request that the IdP accepts

level, so that for every rule the queries, the index mapping and the stored documents are covered and not only the detection logic. The test suite comprises 118 unit tests for the rules, 21 integration tests and 18 end-to-end tests. Eleven rules have both a true positive and a true negative test on the end-to-end level, eight of them triggered by a login and three by a changed file. For the two replay rules, the end-to-end level provides only the true negative test, and two rules are not tested end-to-end at all. MFA_BYPASS could be triggered in the test environment, but not tested meaningfully. The SP requests the authentication context for password protected transport, and the audit format does not record the authentication flow. The audit entry of a login with a second factor would therefore look the same as that of a login with a password alone, and the rule would report both. The scenario for WEAK_ENCRYPTION showed in addition that the IdP uses Triple DES as soon as the metadata of an SP offers only this algorithm, although its configuration prefers AES-GCM. The weakness is thus not prevented by the IdP but only made visible by the monitoring. That the end-to-end level is not redundant became apparent when it uncovered a fault in the log shipping stack that no integration test could have found (Section 6.5).

Legitimate logins raise no false alarms. In the 100 logins at the clean SP, none of the logins raised an alert, and in the 100 logins at the weak SP, where the alerts caused by its weaknesses are expected, no FIELD_MISMATCH was raised. In all 200 logins, the post authentication report was correlated with its audit entry through the inbound message identifier, and the consistency check found no mismatch. No false alarm in 100 logins

does not prove that false alarms cannot occur, but it makes a rate above 3.7 percent per SP unlikely, with 95 percent confidence according to the Wilson interval [63]. For both SPs together, the limit is 1.9 percent. At the clean SP this applies to every alert that a login can trigger, at the weak SP to the consistency check. Findings about the configuration of an SP are not triggered by logins. The clean SP, for instance, receives a `MISSING_MFA` alert once per day, since it does not offer an MFA flow. Sustained load did not change this. During the 10,854 logins of the performance series, the detection layer raised 21,712 alerts, all of them expected: one `UNENCRYPTED_ASSERTION` and one `SUSPICIOUS_USER_AGENT` alert per login, since the benchmark addresses the weak SP and is not a browser, and four configuration alerts. Since these two rules report every affected login rather than the condition once, a persistent weakness of an SP produces one alert per login. All 7,236 logins with active interceptors were correlated and passed the consistency check, without a single `FIELD_MISMATCH` or `CORRELATION_DISCREPANCY` alert. These figures apply to the two SP configurations and to the login flow of the test environment.

The comparison rules detect an altered or a missing record. In the manipulation scenario, the backend matched the post authentication report to the altered audit entry through the unchanged inbound message identifier. The consistency check then raised a `FIELD_MISMATCH` alert of high severity that named the altered field. The check thus detects a contradiction between two independently produced records of the same login. Since only one field of a single entry was altered, the test shows that the mechanism works, not how reliably it detects manipulations in general. A manipulation can only become visible in the fields that the check compares, and the check establishes that the two records disagree, not which of them was altered. With Filebeat stopped, the report of the login was marked as expired after the waiting period and raised a `CORRELATION_DISCREPANCY` alert, while the report of a regular login was correlated and raised none. An audit entry that arrives only afterwards, for instance because of a delay in the log shipping stack, is no longer correlated, so that the alert remains although the record exists.

The results establish the fidelity of the implementation, not its detection quality in production. The rules were derived from documented weaknesses and requirements (Section 4.5.3), and the scenarios reproduce the conditions that the rules describe. The results therefore show that the implementation behaves as specified. Specifically, every rule raises its alert when its condition occurs, and legitimate logins remain without false alarms. How often the rules detect real attacks in production, and how many of their alerts would be false for production traffic with its unusual but legitimate configurations, cannot be derived from them. That would require production logins labelled as legitimate or malicious independently of the rules, which no test environment can produce.

6.4 Performance Overhead

The two interceptors run inside the IdP, the post authentication interceptor as a *post AuthenticationFlow* and the outbound interceptor as an *outboundInterceptorFlow*. Both

therefore lie on the critical path of every login, so that any time they take is added to the time a user waits for access to the SP, and any processor time they use is taken from the IdP. The evaluation addresses two questions. The first is how much the interceptors add to a login, in latency and in processor time, in the configuration intended for production. The second concerns the way in which they transmit their records. As described in Section 5.2, they send them without waiting for a response, so that a login does not depend on the backend. A failed transmission is only recorded in the log of the IdP, and the record is not sent again. Waiting for a confirmation would allow the login to react to such a failure, and the second question is what waiting would cost and whether the choice of fire-and-forget transmission is justified.

Three configurations are compared. In *baseline*, neither interceptor is configured for the SP, so that a login runs as in an IdP without monitoring. In *async*, both interceptors are active and transmit their records without waiting, which is the configuration intended for production. In *sync*, both are active but wait for the confirmation of the backend, so that every login contains two blocking transmissions. The comparison of *baseline* and *async* answers the first question, and the comparison of *async* and *sync* the second. Both are measured as the client experiences a login and as processor load of the IdP, in repeated runs that compare all three configurations under the same conditions.

6.4.1 Method and Measurements

Measurements. Three measurements capture the cost of the interceptors from different angles. The internal measurement is recorded by each interceptor itself (*executionTimeMs*) and covers reading the contexts and extracting the fields. It excludes the construction of the payload and the transmission and is therefore a lower bound. Since the value is part of every report, it is available without further instrumentation. The external measurement is the duration of a login as the client observes it, from the first request to the point at which the SP grants access. Since it includes every step of the login, it shows the delay that a user actually experiences. The third measurement records the processor utilisation of the IdP container about every two seconds through `docker stats`, where 100 percent corresponds to one fully used logical processor. Only the samples taken during the measured logins are evaluated, so that the warm-up, in which class loading and compilation in the freshly started IdP raise the utilisation, is excluded. This measurement captures a cost that appears as additional computation rather than as additional waiting time, which the two latency measurements could miss. Since the configurations do not complete the same number of logins per second, the processor time per login is derived by dividing the mean utilisation by the throughput. The mean is used here because, unlike the median, it adds up to the total processor time of a measurement.

Procedure. All logins are generated by the HTTP harness for a single test account against the weak SP. This is the less favourable case for the interceptors, since the outbound interceptor evaluates all fields of the unencrypted assertion and a login of the baseline is cheaper without encryption, so that the relative overhead turns out larger rather than smaller. Each login uses a fresh client with an empty cookie store, so that it passes through

the complete authentication without reusing a session, and the next login starts as soon as the previous one has completed. The series comprises 18 runs, each of which measures all three configurations, which yields 54 measurements. For every measurement, the IdP container is recreated with the settings of the configuration, and a single check login verifies that the configuration is in effect by testing whether the expected reports arrive at the backend. One hundred warm-up logins follow, whose values are discarded, and then the one hundred logins that are measured. The backend runs during all measurements, including the baseline, so that the environment is the same, and a pause of four minutes after each measurement gives it time to process the records. The whole series took about five hours and comprised 10,854 logins.

Within a session, later measurements tended to be slower than earlier ones. In this series, the third position of a run was on average about 10 ms slower than the first, which is of the same order as the effects to be measured, although the difference is not statistically established. As a precaution against attributing such a drift to a configuration, the order of the configurations is rotated between runs, so that each configuration occupies each of the three positions six times.

Analysis. The run, not the individual login, is the unit of the analysis. The hundred logins of a measurement share the same JVM, the same container and the same load, so that they are not independent observations. The medians of different runs differ considerably more than the scatter of the logins within a run would suggest, so that treating the logins as independent would overstate the precision. Each measurement therefore contributes the median of its hundred logins and its processor time per login, which yields 18 values per configuration. The slower logins are described by the 90th percentile of each measurement. The differences between the configurations are estimated with a linear model that accounts for the run and the position within the run besides the configuration, and they are reported with their 95 percent confidence interval. As a simple check, the number of runs in which one configuration was slower than the other is counted as well. With 18 runs, the confidence intervals of the latency differences have a half width of about 11 ms, so that smaller differences cannot be distinguished from zero.

6.4.2 Results

Table 6.6 summarises what a login costs in each configuration, as the mean over the 18 runs. The following paragraphs explain the figures, from the work inside the interceptors to the answers to the two questions.

The work inside the interceptors takes less than half a millisecond. The internal measurement yields a median of 0.415 ms for the post authentication interceptor and 0.039 ms for the outbound interceptor, and 99 percent of the reports stay below 2 ms. Together this is about 0.45 ms, or 0.13 percent of a median login in the baseline. Since the measurement excludes the construction of the payload and the transmission, it is a lower bound, but it shows that collecting the data does not weigh on the login. Any larger

Table 6.6: *Cost of a login per configuration*

	baseline	async	sync
Median login	356.5 ms	362.7 ms	416.1 ms
Difference to baseline	—	+6.2 ms	+59.6 ms
95 % confidence interval	—	[−4.7; +17.1] ms	[+48.7; +70.4] ms
Difference at the 90th percentile	—	+8.1 ms	+92.0 ms
Logins per second	2.77	2.71	2.36
Processor time per login	126 ms	154 ms	166 ms

difference between the configurations must therefore stem from building and sending the reports.

Asynchronous transmission adds no latency that the experiment can distinguish from zero. A median login takes 6.2 ms longer than in the baseline, and the 95 percent confidence interval ranges from −4.7 to +17.1 ms and thus includes zero. In twelve of the 18 runs the asynchronous configuration was the slower one, which is a weak tendency but not an established effect. The slower logins behave in the same way, with a difference of 8.1 ms at the 90th percentile and an upper bound of 22 ms, or 5.2 percent. With 95 percent confidence, the overhead therefore lies below 17.1 ms, or 4.8 percent of a median login. Smaller effects, such as the point estimate suggests, are below the resolution of the experiment.

Synchronous transmission adds about 60 milliseconds to every login. A median login takes 59.6 ms or 16.7 percent longer than in the baseline, with a 95 percent confidence interval from +48.7 to +70.4 ms, and the synchronous configuration was the slower one in all 18 runs. Compared with the asynchronous configuration, the difference is 53.4 ms. Since every login contains two blocking transmissions, each of them costs roughly 27 to 30 ms. The slower logins are affected more strongly, as the difference grows to 92.0 ms or 21.6 percent at the 90th percentile. Since both configurations build and send the same reports, this difference is the time spent waiting, during which the backend validates each report and stores it in Elasticsearch before it answers.

Asynchronous transmission costs processor time, and waiting does not save it. In the asynchronous configuration, the IdP spends 28 ms more processor time on a login than in the baseline, with a 95 percent confidence interval from 19 to 37 ms. This is 22 percent of the 126 ms that a login costs without interceptors. The synchronous configuration shows a lower utilisation than the asynchronous one because it completes fewer logins per second, 2.36 instead of 2.71, since each login waits for the backend. Per login, however, it does not use less processor time than the asynchronous configuration. The additional processor time does not show in the latency of the asynchronous configuration because the transmission runs in background threads. At the load of the test it occupies less than half a percent of the 16 logical processors of the host, but it grows with the number of

logins, so that 50 logins per second at a peak would require about 1.4 additional logical processors.

In the configuration intended for production, the interceptors therefore add no measurable latency and about 28 ms of processor time to a login, which answers the first question. Waiting for a confirmation would add about 60 ms to every login and more to the slow ones, without saving processor time. In the current implementation it would not even improve the delivery, since both modes only log a failed transmission and neither sends the record again. A delivery guarantee would require a local buffer that repeats failed transmissions, and such a buffer works with asynchronous transmission as well. The measurement therefore supports the choice of fire-and-forget transmission described in Section 5.2.

6.5 Defects Found

Besides the results reported above, the evaluation revealed six defects that were not visible while the system was running. In each case the system kept running and produced plausible output, and the defect only became visible when the behaviour was compared with an expectation defined in advance. Table 6.7 lists them together with the consequence they would have had in production. After the missing identifier had been added to the audit format, the exact strategy activated itself while the system was running, without a restart, as intended by the dynamic field adaptation of Section 5.1. All six defects were corrected, and the results in this chapter refer to the corrected system. What this pattern means for the monitoring of an IdP is discussed in Section 7.1.

Table 6.7: *Defects uncovered by the evaluation*

Defect	Consequence if undetected	Uncovered by
Inbound message identifier (`%I`) missing from the audit format	Exact correlation never active, all 3,690 correlations up to then made by the hashed heuristic	Correlation measurement
Heuristics compared against the Filebeat ingest time instead of the IdP event time	2,423 audit entries shared 448 time values, precision of the hashed heuristic 6 to 7 percent	Correlation measurement
Logstash set the field *encrypted* to false for every login	Every encrypted login reported as `UNENCRYPTED_ASSERTION`	End-to-end test against the clean SP
Version field missing from the stored behaviour profile	Profile updates discarded silently, so that `BEHAVIOUR_ANOMALY` compared against outdated profiles, while the unit test with a mocked repository passed	Integration test
Ingest path for the SP configuration inactive	Two rules evaluated an index that was no longer updated	Detection evaluation
Indexing errors in the analysis script of the performance measurement	Plausible but incorrect performance figures	Tracing values back to the raw measurement files

6.6 Threats to Validity

Several limits have already been stated together with the results they concern, for instance the shared clock of the correlation measurements or the resolution of the latency measurement. This section adds the limits that have not been stated there, most of which follow from the test environment and the generated traffic as a whole.

One host. All components ran on a single notebook, the IdP, the SPs and the log shipping stack in containers and the monitoring backend as a process on the host. This reproduces the logical separation of the backend from the IdP, but not the trust boundary that the design derives from it (Section 4.4). That an attacker who gains control of the IdP cannot alter the records that have already left it therefore follows from the design but was not tested.

The shared host also affects the performance measurement. The backend and Elasticsearch processed the reports on the same processor as the IdP, and they had more to process in the configurations with interceptors than in the baseline. This competition was not measured, but where it has an effect, it makes the overhead appear larger rather than smaller. Absolute login durations are specific to this setup and are likely to be longer in production, where the network and the user store contribute. The differences between the configurations transfer better, since every run measured all three under the same conditions. On separate hosts, synchronous transmission would additionally wait for the network on both of its transmissions, so that its distance to asynchronous transmission would grow rather than shrink.

Scripted traffic. All logins were generated by scripts, either by the HTTP harness or by a browser driven by Selenium, with three test accounts, two SPs and a single authentication flow based on a password. Real users log in less regularly, through other flows such as a second factor, and from many different browsers and networks. Since no logins of real users were available, the evaluations show how the system behaves in the situations they reproduce, but not how often these situations arise in production. This concerns how often logins at an SP follow each other closely enough to confuse the time-only correlation, which load a production IdP reaches at its peak and how often the rules detect real attacks or raise false alarms (Section 6.3.2). Single sign-on follow-up requests, which reuse an existing session, were not measured either. Since such requests are faster than a full login, the interceptors would account for a larger share of their duration.

Sequential load. In the performance series, each login started only after the previous one had completed, so that the IdP handled fewer than three logins per second and never two at once. The figures therefore describe the cost of a single login at low load. At a peak with many simultaneous logins, the additional processor time of the interceptors competes with other logins, and the estimate of about 1.4 additional logical processors at 50 logins per second assumes that the processor time per login does not grow with the load. Whether the backend accepts the reports quickly enough at such a peak was not

tested either. Since the asynchronous interceptors give up a transmission after 1.5 s, a backend that falls behind would lose reports rather than slow down the logins.

Rules without an end-to-end test. `MFA_BYPASS` and `SIGNATURE_WRAPPING_SUSPECTED` rest on the integration test, which passes its input directly to the rule engine. In production, the input of `MFA_BYPASS` arrives through the log shipping stack, and that of `SIGNATURE_WRAPPING_SUSPECTED` with the post authentication report. A fault on either path, such as the one in Logstash described in Section 6.5, would remain undetected for these two rules if it only affected fields that none of the rules with an end-to-end test reads. For the two replay rules, the same applies to the true positive case.

7 Discussion

This chapter interprets the results with respect to the research questions. It then discusses the structural limitations of the approach and outlines directions for future work.

7.1 Interpretation of the Results

The results of this study can be read along the three research questions posed in Chapter 1. The first question asked which security relevant data can be collected at the application layer of a Shibboleth IdP and through which mechanisms. Three sources proved usable, namely the audit log, the configuration and metadata of the SPs, and the runtime state accessible through interceptors. The value of this combination does not primarily result from the number of sources but from the positions at which they observe the authentication process. The audit log records the outcome of a completed transaction, the configuration states what was intended for the partner involved, and the interceptors observe the incoming request and the outgoing response while the transaction is being processed. Each source therefore holds information that the others cannot provide, and the complementarity follows from their position in the processing sequence rather than from a deliberate division of responsibilities.

The second question asked how these data can be correlated in order to detect configuration weaknesses and anomalies. The correlation found a counterpart for every report, and with the inbound message identifier or at least one hash that separates the users, it found the correct one in every tested scenario. Only the strategy that relies on time alone (`TIME_WINDOW`) assigned reports to the wrong entry, and only where logins at the same SP followed each other within less than 100 ms. The hashed heuristic (`HASH_AND_TIME_WINDOW`) remains reliable up to about three logins per second for a given combination of subject, address and SP, a rate that interactive users do not reach (Section 6.2.2). The fifteen detection rules behave as intended for the scenarios constructed for them. All of them are verified against a real Elasticsearch instance. Thirteen are also tested through the complete pipeline, eleven of them with a detected condition. Whether they also detect real attacks reliably and without false alarms in production cannot be derived from these tests, since this would require production logins labelled independently of the rules (Section 6.3.2).

The number of alerts deserves attention as well. During the performance series, the detection layer raised 21,712 alerts for 10,854 logins, since the benchmark used a script client against the weak SP and both affected rules report every login (Section 6.3.2). In a production environment, such a high volume of alerts would make it difficult to identify the few that indicate an attack, potentially leading to alert fatigue. The two rules rated low report indicators that are of limited value on their own. In the evaluation, they served to verify the pipeline end to end, but in production they mainly add volume. `FAILED_LOGIN` reports every failed login attempt, although `BRUTE_FORCE` evaluates the same attempts and reports a subject once they accumulate. `SUSPICIOUS_USER_AGENT` alone accounts for

half of the alerts of the performance series. In production, FAILED_LOGIN could therefore be hidden without affecting the detection of brute force attacks, and SUSPICIOUS_USER_AGENT could be shown in condensed form, for instance as a daily count per SP.

The third question asked what overhead the resulting system imposes. With asynchronous transmission, the latency of a login did not differ measurably from a deployment without interceptors. The point estimate is +6.2 ms, and the upper bound of the 95 % confidence interval is 17 ms, which is below five percent of the median login duration. The work inside the two interceptors amounts to about 0.45 ms. The cost appears as processor time instead, about 28 ms per login or 22 percent of the processor time of a login without interceptors, which the IdP spends in background threads. Synchronous transmission adds about 60 ms to every login and was the slower configuration in all 18 runs, without saving processor time. In the current implementation it would not improve the delivery either, since both modes only log a failed transmission (Section 6.4.2). The measurement therefore supports the choice of fire-and-forget transmission.

Beyond the individual research questions, each of the three evaluations uncovered at least one defect, six in total (Table 6.7). None of them caused a visible failure. They became apparent only through a comparison with an expectation defined in advance, such as the ground truth of the correlation or an end-to-end test against the clean SP. Tests at several levels were therefore necessary to establish that the system works as intended.

7.2 Limitations of the Approach

This section discusses the structural limitations of the proposed monitoring system. As the assignment in Table 4.1 shows, the rules address two of the six SAML cross-protocol issues identified by Simpson and Groß [55], namely unencrypted communications exploited by message modification and lack of binding exploited by replay. The second is covered only in part, since a replayed assertion is presented to the SP and does not pass the IdP again, so that only the replay of a request remains observable (Table 6.5).

This limited coverage is not primarily caused by missing implementations but by the observation position of the monitoring system. The four remaining issues lie at a different system layer, at a different party or outside the path that the IdP observes [55]. DNS poisoning concerns name resolution and therefore a layer beneath the application [55]. The IdP processes the request it receives regardless of how the client resolved the corresponding address. Cross-site request forgery describes an implementation vulnerability at the SP [55]. The relevant interaction occurs between the browser and the SP and therefore does not pass through the IdP. The same applies to message modification enabled by a lack of binding, whose mitigation lies in the SP checking the credentials it receives [55]. A man-in-the-middle attack exploits a lack of binding, where a token is not tied to the SP for which it was issued, and the survey names binding the token to its intended SP as the countermeasure [55]. The attack itself takes place on the communication path after the message has left the IdP. The IdP can at most observe whether an outgoing assertion is restricted to its intended recipient. None of the implemented rules currently examines this condition.

Two further attack classes, UI redressing and ACS spoofing, were reported only for SAML and exploit a vulnerable IdP [55]. UI redressing is mitigated by response headers that the web server in front of the IdP sets [21, 32]. These headers lie outside the profile flows that the interceptors observe. ACS spoofing, in contrast, could be detected by comparing the requested endpoint with the endpoints in the metadata of the SP, but the current catalogue contains no such rule [7, 32].

Two cases deserve separate attention. The bogus merchant scenario is the only cross-protocol issue that concerns Shibboleth directly, and it remains uncovered by the monitoring system because a malicious SP is a regular participant registered in the federation metadata. From the perspective of the IdP, such an SP does not differ from any other partner. Monitoring changes to its configuration and metadata would only reveal a provider whose behaviour has changed, not one that was malicious from the start.

The second case is more fundamental. The malicious provider scenario is reported for other protocols, among them Liberty, which builds on SAML [55]. It describes an IdP that abuses its own position within the federation and therefore concerns any IdP, regardless of the protocol. Since the monitoring system is integrated into the IdP, the observer and the potential attacker reside within the same system. An entity that fully controls the IdP therefore also controls the collection layer of the monitoring system, including which records are produced and which are not. This limitation follows directly from the observation point and cannot be overcome by adding further detection rules within the same trust domain. Snodgrass et al. make the same assumption in their threat model, where only services outside the compromised system remain trustworthy once an adversary has gained control of it [57]. Detecting this class of behaviour would require an observation point outside the IdP, for instance at the SPs or at the level of the federation itself.

A final limitation connects back to the motivation of this work. The risk classification used for the severity assignment in Section 4.5.4 distinguishes five levels, of which the highest describes an adversary able to authenticate as any user at any SP. None of the fifteen rules reaches this level, since it presupposes a compromise of the signing key. An adversary in possession of that key produces formally valid assertions that are indistinguishable from legitimate ones by any of the implemented rules. The Sunburst incident described in Chapter 1 is precisely such a case and would therefore not have been detected by this system. What the system can detect are configuration weaknesses that make an attack of this kind more likely to succeed or harder to notice.

7.3 Implications for Future Research

The findings and limitations identified in this study point to several directions for future work in the area of application layer monitoring for federated identity infrastructures. They fall into two categories, namely extensions that would widen the observation point and questions that cannot be answered without a different kind of data.

A primary direction is to extend the detection capabilities beyond the IdP and incorporate observations made at the SP. The approach presented here is inherently limited by its

position, as discussed in Section 7.2, and several of the uncovered attack classes are located precisely where the IdP has no visibility. Martín et al. have proposed behavioural anomaly detection on the relying party side [31], arguing that delegating authentication does not transfer the entire security responsibility. Combining both perspectives would address opposite ends of the same federation. Such an extension would require a suitable and preferably standardised integration mechanism for SPs, which introduces organisational challenges beyond the technical ones, since it presupposes cooperation between parties that are administratively independent.

A second direction concerns the observation point within the IdP itself. The outbound interceptor added in this work makes the response level fields available from a second, independent source, and it enables the comparison with the audit entry described in Section 4.5.3. What it cannot provide are the assertion internal fields of encrypted assertions, since the encryption has already taken place at that hook. An observation point before the encryption would close this gap, but the interception points that Shibboleth offers to developers do not include one, and an intervention in the profile flow would conflict with the third requirement from Section 4.1. Whether the audit extraction points of the IdP could serve this purpose is a question for future work.

A third direction addresses the one Shibboleth specific issue that remains uncovered. The system already receives every changed configuration and metadata document of an SP (Section 5.1), but no rule reports the change itself. Such a rule would provide a partial answer to the bogus merchant scenario, since a change is the only observable signal where no basis for prior trust exists. What such a mechanism could establish and what it could not is discussed in Section 7.2, and the distinction would need to be stated carefully in any implementation.

A fourth direction is the extension of the approach to OpenID Connect (OIDC) [44]. The present work focuses exclusively on SAML and Shibboleth, so that it remains an open question whether the three source architecture developed here transfers to OIDC based infrastructures. The architecture itself appears protocol independent, since an OIDC provider likewise maintains a registration of its clients, writes records of completed transactions and processes incoming requests at runtime. The detection rules, by contrast, are protocol specific and would not transfer, since conditions such as a missing proof key exchange or an implicit flow have no direct counterpart in the rules developed here [30, 43]. Future work could therefore examine which application level sources exist in an OIDC provider, whether they are complementary in the same sense and which rules follow from the documented weaknesses of that protocol.

Finally, one question cannot be addressed by extending the system. Determining how reliably the rules detect genuine attacks requires production traffic in which each authentication is independently labelled, as discussed in Section 6.3.2. Producing such a dataset is a research problem in its own right rather than an implementation task, and it would benefit not only this work but any evaluation of detection systems in federated identity infrastructures, where the same constraint applies.

8 Conclusion

This thesis presented an application layer monitoring tool for the Shibboleth IdP that detects documented vulnerabilities, configuration weaknesses and anomalous authentication behaviour by combining three separate sources of information from within the IdP. These sources are the audit log, two interceptors in the authentication flow, and the configuration and metadata of the SPs. The collected data is transmitted to an external backend, where it is stored, correlated and evaluated against a catalogue of fifteen detection rules.

For the first research question, the IdP discloses security-relevant data through the three channels. What each source can see is defined by its position in the processing sequence, which is why their combination allows comparisons that no single source supports on its own. The configuration describes what is intended for an SP, while the audit log and the interceptors record independently of each other what actually happened. For the second question, the records of a login can be linked reliably as long as the audit log records the identifier of the request or the pseudonymised user and address. Only a correlation by time alone fails when logins at the same SP follow each other within less than 100 ms. The rules correlate observed logins with the declared configuration and compare the records of a login with each other. All of them behaved as specified in the tested scenarios. For the third question, asynchronous transmission introduced no measurable latency overhead. The cost appears as processor time instead.

This thesis also identified limitations that follow from the observation point. Several federation level attack scenarios occur at a different system layer, involve a different party or are observable only through their preconditions. The comparison of independent records shows that two records disagree, but not which of them was altered.

What this thesis contributes is therefore not a new architecture for collecting and correlating security events. It shows that an interceptor inside the authentication flow provides a second record of each login, which is produced and transmitted independently of the audit log. Combined with the audit log and the configuration, this record allows each login to be compared with the declared state of its SP and with the audit entry of the same login. In addition, the thesis analyses which properties are observable from which position and provides an implementation whose overhead was measured. Future work could extend the observation to the SPs, transfer the approach to OpenID Connect and evaluate the rules on labelled production traffic.

Bibliography

[1] M. Bartel, J. Boyer, B. Fox, B. LaMacchia, and E. Simon. *XML Signature Syntax and Processing Version 1.1*. URL: https://www.w3.org/TR/xmldsig-core/ (visited on 09/03/2026).

[2] S. Cantor. *AttributeFilterConfiguration*. Nov. 2023. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199501794/AttributeFilterConfiguration (visited on 09/02/2026).

[3] S. Cantor. *AuditLoggingConfiguration*. June 2026. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199509698/AuditLoggingConfiguration (visited on 09/02/2026).

[4] S. Cantor. *GeneralArchitecture*. Apr. 2024. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199511689/GeneralArchitecture (visited on 10/25/2026).

[5] S. Cantor. *LoggingConfiguration*. May 2026. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199509659/LoggingConfiguration (visited on 09/11/2026).

[6] S. Cantor. *MetadataConfiguration*. Feb. 2024. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199506698/MetadataConfiguration (visited on 09/02/2026).

[7] S. Cantor. *MetadataForSP*. June 2017. URL: https://shibboleth.atlassian.net/wiki/spaces/CONCEPT/pages/928645420/MetadataForSP (visited on 09/11/2026).

[8] S. Cantor. *MetricsConfiguration*. July 2024. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199510278/MetricsConfiguration (visited on 10/25/2026).

[9] S. Cantor. *OIDC OP*. June 2026. URL: https://shibboleth.atlassian.net/wiki/spaces/IDPPLUGINS/pages/1376878976 (visited on 10/21/2026).

[10] S. Cantor. *ProfileHandling*. Nov. 2023. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199511979/ProfileHandling (visited on 09/02/2026).

[11] S. Cantor. *ProfileInterceptConfiguration*. May 2023. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199509815/ProfileInterceptConfiguration (visited on 09/11/2026).

[12] S. Cantor. *RelyingPartyConfiguration*. May 2025. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199508044/RelyingPartyConfiguration (visited on 09/02/2026).

[13] S. Cantor. *Status*. June 2023. URL: https://shibboleth.atlassian.net/wiki/spaces/IDP5/pages/3199511520/Status (visited on 10/25/2026).

[14] S. Cantor, F. Hirsch, J. Kemp, R. Philpott, and E. Maler, eds. *Bindings for the OASIS Security Assertion Markup Language (SAML) V2.0*. OASIS. Mar. 2005. URL: https://docs.oasis-open.org/security/saml/v2.0/saml-bindings-2.0-os.pdf (visited on 09/03/2026).

[15] S. Cantor, J. Kemp, R. Philpott, and E. Maler, eds. *Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V2.0*. OASIS. Mar. 2005. URL: https://docs.oasis-open.org/security/saml/v2.0/saml-core-2.0-os.pdf (visited on 09/03/2026).

[16] S. Cantor, J. Moreh, R. Philpott, and E. Maler, eds. *Metadata for the OASIS Security Assertion Markup Language (SAML) V2.0*. OASIS. Mar. 2005. URL: https://docs.oasis-open.org/security/saml/v2.0/saml-metadata-2.0-os.pdf (visited on 09/03/2026).

[17] A. Das, J. Bonneau, M. Caesar, N. Borisov, and X. Wang. "The Tangled Web of Password Reuse". In: *Proceedings of the Network and Distributed System Security Symposium (NDSS)*. Feb. 2014. ISBN: 1-891562-35-5. DOI: 10.14722/ndss.2014.23357.

[18] Federal Office for Information Security. *Cryptographic Mechanisms: Recommendations and Key Lengths*. Technical Guideline. Bonn, Germany: Federal Office for Information Security. URL: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.pdf (visited on 09/14/2026).

[19] FireEye. *Highly Evasive Attacker Leverages SolarWinds Supply Chain to Compromise Multiple Global Victims With SUNBURST Backdoor*. Dec. 2020. URL: https://cloud.google.com/blog/topics/threat-intelligence/evasive-attacker-leverages-solarwinds-supply-chain-compromises-with-sunburst-backdoor (visited on 09/01/2026).

[20] German National Research and Education Network (DFN). *DFN-AAI portal*. URL: https://www.aai.dfn.de/index.en.html (visited on 09/01/2026).

[21] R. Graves. *Implementing a Shibboleth SSO Infrastructure*. GIAC GWEB Gold Certification. SANS Institute, Sept. 2014. URL: https://www.giac.org/paper/gweb/35/implementing-shibboleth-sso-infrastructure/122593 (visited on 09/01/2026).

[22] C. Hall, L. Shepherd, and N. Coull. "BlackWatch: Increasing Attack Awareness within Web Applications". In: *Future Internet* 2 (Feb. 2019). ISSN: 1999-5903. DOI: 10.3390/fi11020044.

[23] Z. Hartl and A. Derek. "Toward Automated Formal Security Analysis of SAML V2.0 Web Browser SSO Standard—The POST/Artifact Use Case". In: *IEEE Access* (2025). ISSN: 2169-3536. DOI: 10.1109/access.2025.3622379.

[24] F. Hirsch, R. Philpott, and E. Maler, eds. *Security and Privacy Considerations for the OASIS Security Assertion Markup Language (SAML) V2.0*. OASIS. Mar. 2005. URL: https://docs.oasis-open.org/security/saml/v2.0/saml-sec-consider-2.0-os.pdf (visited on 09/03/2026).

[25] T. Imamura, B. Dillaway, E. Simon, K. Yiu, and M. Nyström. *XML Encryption Syntax and Processing Version 1.1*. URL: https://www.w3.org/TR/xmlenc-core/ (visited on 09/03/2026).

[26] K. Kaur and D. Bansal. "Security Vulnerabilities in SAML based Single Sign-On Authentication in Cloud". In: *Proceedings of the 1st International Workshop on Cloud Computing and Information Security*. Atlantis Press, Nov. 2013. ISBN: 978-90-78677-88-8. DOI: 10.2991/ccis-13.2013.69. URL: https://doi.org/10.2991/ccis-13.2013.69.

[27] K. Kent and M. Souppaya. *Guide to Computer Security Log Management*. NIST Special Publication 800-92. Gaithersburg, MD: National Institute of Standards and Technology, Sept. 2006. DOI: 10.6028/NIST.SP.800-92. URL: https://nvlpubs.nist.gov/nistpubs/Legacy/SP/nistspecialpublication800-92.pdf (visited on 09/06/2026).

[28] H. Krawczyk, M. Bellare, and R. Canetti. *HMAC: Keyed-Hashing for Message Authentication*. RFC 2104. RFC Editor, Feb. 1997. DOI: 10.17487/RFC2104. URL: https://www.rfc-editor.org/rfc/rfc2104.html (visited on 10/07/2026).

[29] J. Lambert. *Important steps for customers to protect themselves from recent nation-state cyberattacks*. Dec. 2020. URL: https://blogs.microsoft.com/on-the-issues/2020/12/13/customers-protect-nation-state-cyberattacks (visited on 09/01/2026).

[30] T. Lodderstedt, J. Bradley, A. Labunets, and D. Fett. *Best Current Practice for OAuth 2.0 Security*. RFC 9700. Internet Engineering Task Force, Jan. 2025. DOI: 10.17487/RFC9700. URL: https://www.rfc-editor.org/rfc/rfc9700.html (visited on 10/07/2026).

[31] A. G. Martín, M. Beltrán, A. Fernández-Isabel, and I. Martín de Diego. "An approach to detect user behaviour anomalies within identity federations". In: *Computers & Security* (2021). ISSN: 0167-4048. DOI: 10.1016/j.cose.2021.102356.

[32] A. Mayer, M. Niemietz, V. Mladenov, and J. Schwenk. "Guardians of the Clouds: When Identity Providers Fail". In: *Proceedings of the 6th Edition of the ACM Workshop on Cloud Computing Security*. CCSW '14. Scottsdale, Arizona, USA: Association for Computing Machinery, 2014. ISBN: 9781450332392. DOI: 10.1145/2664168.2664171. URL: https://doi.org/10.1145/2664168.2664171.

[33] MITRE. *CWE-117: Improper Output Neutralization for Logs*. URL: https://cwe.mitre.org/data/definitions/117.html (visited on 09/06/2026).

[34] MITRE. *CWE-532: Insertion of Sensitive Information into Log File*. URL: https://cwe.mitre.org/data/definitions/532.html (visited on 09/12/2026).

[35] National Institute of Standards and Technology (NIST). *NIST Special Publication 800-63B*. URL: https://pages.nist.gov/800-63-4/sp800-63b.html (visited on 09/03/2026).

[36] National Institute of Standards and Technology (NIST). *NIST Special Publication 800-63C*. URL: https://pages.nist.gov/800-63-4/sp800-63c.html (visited on 09/03/2026).

[37] OASIS Open. *Members approve security assertion markup language (SAML) v2.0 as OASIS standard*. Mar. 2005. URL: https://www.oasis-open.org/2005/03/13/members-approve-security-assertion-markup-language-saml-v2-0-as-oasis-standard/ (visited on 09/03/2026).

[38] OWASP. *A09:2025 Security Logging & Alerting Failures*. URL: https://owasp.org/Top10/2025/A09_2025-Security_Logging_and_Alerting_Failures/ (visited on 09/06/2026).

[39] OWASP Foundation. *OWASP AppSensor*. URL: https://owasp.org/www-project-appsensor/ (visited on 09/04/2026).

[40] W. Pempe. *Metadata Registration Practice Statement of the DFN-AAI Federation, Version 1.0*. Mar. 2019. URL: https://www.aai.dfn.de/fileadmin/documents/mrps_dfn-aai_1.0.pdf (visited on 10/21/2026).

[41] N. Ragouzis, J. Hughes, R. Philpott, E. Maler, P. Madsen, et al., eds. *Security Assertion Markup Language (SAML) V2.0 Technical Overview*. OASIS. Mar. 2008. URL: https://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0-cd-02.pdf (visited on 09/03/2026).

[42] J.-F. Rieckers. "Passive Security Analysis of Current TLS Implementations and Configurations in the eduroam EAP-TLS Environment". Bachelor's Thesis. University of Bremen, Faculty 3: Mathematics and Computer Science, Aug. 2021.

[43] N. Sakimura, J. Bradley, and N. Agarwal. *Proof Key for Code Exchange by OAuth Public Clients*. RFC 7636. RFC Editor, Sept. 2015. DOI: 10.17487/RFC7636. URL: https://www.rfc-editor.org/rfc/rfc7636.html (visited on 10/07/2026).

[44] N. Sakimura, J. Bradley, M. B. Jones, B. de Medeiros, and C. Mortimore. *OpenID Connect Core 1.0 incorporating errata set 2*. Dec. 2023. URL: https://openid.net/specs/openid-connect-core-1_0.html (visited on 10/07/2026).

[45] B. Schneier and J. Kelsey. "Cryptographic Support for Secure Logs on Untrusted Machines". In: *7th USENIX Security Symposium (USENIX Security 98)*. San Antonio, TX: USENIX Association, Jan. 1998. URL: https://www.usenix.org/conference/7th-usenix-security-symposium/cryptographic-support-secure-logs-untrusted-machines.

[46] Shibboleth Consortium. *AbstractProfileAction*. URL: https://shibboleth.net/api/java-identity-provider/5.0.0/net/shibboleth/idp/profile/AbstractProfileAction.html (visited on 09/15/2026).

[47] Shibboleth Consortium. *AuthenticationContext*. URL: https://shibboleth.net/api/java-identity-provider/5.1.1/net/shibboleth/idp/authn/context/AuthenticationContext.html (visited on 09/15/2026).

[48] Shibboleth Consortium. *InOutOperationContext*. URL: https://shibboleth.net/api/java-opensaml/5.1.1/org/opensaml/messaging/context/InOutOperationContext.html (visited on 09/15/2026).

[49] Shibboleth Consortium. *ProfileRequestContext*. URL: https://shibboleth.net/api/java-opensaml/5.0.0/org/opensaml/profile/context/ProfileRequestContext.html (visited on 09/15/2026).

[50] Shibboleth Consortium. *RelyingPartyContext*. URL: https://shibboleth.net/api/java-shib-profile/5.1.5/net/shibboleth/profile/context/RelyingPartyContext.html (visited on 09/15/2026).

[51] Shibboleth Consortium. *SessionContext*. URL: https://shibboleth.net/api/java-identity-provider/5.2.0/net/shibboleth/idp/session/context/SessionContext.html (visited on 09/15/2026).

[52] Shibboleth Consortium. *SubjectContext*. URL: https://shibboleth.net/api/java-identity-provider/5.2.0/net/shibboleth/idp/authn/context/SubjectContext.html (visited on 09/15/2026).

[53] Shibboleth Consortium. *The Shibboleth Project*. URL: https://www.shibboleth.net/about-us/the-shibboleth-project/ (visited on 09/01/2026).

[54] A. Shostack. *Threat Modeling: Designing for Security*. 1st ed. Indianapolis, IN, USA: Wiley, 2014. ISBN: 978-1-118-80999-0.

[55] S. Simpson and T. Groß. "A Survey of Security Analysis in Federated Identity Management". In: *Privacy and Identity Management. Facing up to Next Steps*. Ed. by A. Lehmann, D. Whitehouse, S. Fischer-Hübner, L. Fritsch, and C. Raab. IFIP Advances in Information and Communication Technology. Cham: Springer, 2017. DOI: 10.1007/978-3-319-55783-0_16.

[56] A. Šliamin. *Federation Architectures*. Sept. 2017. URL: https://wiki.geant.org/spaces/eduGAIN/pages/121348064/Federation+Architectures (visited on 09/03/2026).

[57] R. T. Snodgrass, S. S. Yao, and C. Collberg. "Tamper Detection in Audit Logs". In: *Proceedings of the Thirtieth International Conference on Very Large Data Bases - Volume 30*. VLDB '04. Toronto, Canada: VLDB Endowment, 2004. ISBN: 0120884690.

[58] D. Sommer. "Formal Security Analysis of the Shibboleth Web Single Sign On System Using a Comprehensive Model of the Web". MA thesis. University of Stuttgart, June 2020. URL: https://elib.uni-stuttgart.de/server/api/core/bitstreams/49a085bf-cbbf-4655-aedb-ef1501dc6388/content.

[59] J. Somorovsky, A. Mayer, J. Schwenk, M. Kampmann, and M. Jensen. "On Breaking SAML: Be Whoever You Want to Be". In: *21st USENIX Security Symposium (USENIX Security 12)*. Bellevue, WA: USENIX Association, Aug. 2012. ISBN: 978-1-931971-95-9. URL: https://www.usenix.org/conference/usenixsecurity12/technical-sessions/presentation/somorovsky.

[60] M. Suvanto. "A Monitoring System for Authentication and Authorisation Infrastructure". MA thesis. Aalto University, Apr. 2010. URL: https://aaltodoc.aalto.fi/server/api/core/bitstreams/38beefb5-9846-433f-921a-aebb7884204c/content.

[61] Verizon Business. *2026 Data Breach Investigations Report*. May 2026. URL: https://www.verizon.com/business/resources/executivebriefs/2026-dbir-executive-summary.pdf (visited on 10/21/2026).

[62] Wazuh. *Wazuh documentation*. URL: https://documentation.wazuh.com/current/index.html (visited on 09/06/2026).

[63] E. B. Wilson. "Probable Inference, the Law of Succession, and Statistical Inference". In: *Journal of the American Statistical Association* 158 (1927). DOI: 10.1080/01621459.1927.10502953.

[64] E. Yuan and S. Malek. "A Taxonomy and Survey of Self-Protecting Software Systems". In: *Proceedings of the 7th International Symposium on Software Engineering for Adaptive and Self-Managing Systems*. SEAMS '12. Zurich, Switzerland: IEEE Press, 2012. ISBN: 9781467317870.