

Create Plots

April 3, 2017

Notebook for creating several Plots

- Sum of Squares plot
- Many numerical fingerprints
- Example tournament and results

```
In [ ]: import string
import numpy as np
import axelrod as axl
import pandas as pd
from tqdm import tqdm
import matplotlib.pyplot as plt
import matplotlib
```

```
In [ ]: def format_filename(s):
    """
    Take a string and return a valid filename constructed from the string.
    Uses a whitelist approach: any characters not present in valid_chars are
    removed. Also spaces are replaced with underscores.
    Note: this method may produce invalid filenames such as ``, ``.`` or ``..``
    When I use this method I prepend a date string like '2009_01_15_19_46_3'
    and append a file extension like '.txt', so I avoid the potential of using
    an invalid filename.
    Borrowed from https://gist.github.com/seanh/93666
    """
    valid_chars = "-_().{}{}".format(string.ascii_letters, string.digits)
    filename = ''.join(c for c in s if c in valid_chars)
    filename = filename.replace(' ', '_')
    return filename
```

```
In [ ]: strats = axl.strategies
```

```
strategies = [s.name for s in strats]
# need access to the fingerprint csv files from Axelrod-fingerprint repo
path = '/Users/James/Projects/Axelrod-fingerprint/assets/'
filenames = [path + format_filename(s) + '.csv' for s in strategies]
dataframes = [pd.read_csv(f) for f in filenames]
```

```

def score_for_df(A, B):
    """
    Compute the sum of squares score for two dataframes, A and B
    """
    result = pd.merge(A, B, on=['x', 'y'], suffixes=('_A', '_B'))
    result['SQ_difference'] = (result['score_A'] - result['score_B'])**2
    result.drop(['score_A', 'score_B'], axis=1, inplace=True)
    return sum(result.SQ_difference)

sum_squares_df = pd.DataFrame(index=strategies, columns=strategies)

for indexA, strategyA in enumerate(tqdm(strategies)):
    A_df = dataframes[indexA]
    for indexB, strategyB in enumerate(strategies):
        B_df = dataframes[indexB]
        similarity_score = score_for_df(A_df, B_df)
        sum_squares_df.set_value(strategyA, strategyB, similarity_score)

sum_squares_df

In [ ]: sum_squares_df = sum_squares_df.apply(pd.to_numeric)
size = len(dataframes[0].index)
mean_squares_df = sum_squares_df.divide(size)
mean_squares_df.head()

In [ ]: plt.figure(figsize=(50, 75))
sns.heatmap(mean_squares_df, cbar_kws={"orientation": "horizontal"})
cbar = ax.figure.colorbar(ax.collections[0])
cbar.set_ticks([0, 1])
cbar.set_ticklabels(["0%", "100%"])
# cbar.set_ticks([0, .2, .75, 1])
# cbar.set_ticklabels(['low', '20%', '75%', '100%'])
# fig.colorbar(ax, orientation="horizontal", fraction=0.07, anchor=(1.0, 0.0))
plt.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/mean_squares.png')
plt.show()

# f, ax = plt.subplots(figsize=(50, 50))
# sns.heatmap(sum_squares_df, cbar=False)

In [ ]:

In [ ]: axl.seed(0) # Set a seed
players = [axl.TitForTat(), axl.Cooperator(), axl.Random(), axl.Gradual()]
tournament = axl.Tournament(players) # Create a tournament
results = tournament.play() # Play the tournament
plot = axl.Plot(results)

```

```

p = plot.boxplot()
q = plot.payoff()

In [ ]: p.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/examples/sm
p

In [ ]: q.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/examples/sm
q

```

1 Analytical Plots

```

In [ ]: def TFT(coord):
    x, y = coord
    numerator = y**2 + 5*x*y + 3*x**2
    denominator = (x + y)**2
    return numerator/denominator

def WSLS(coord):
    x, y = coord
    numerator = (3*x + y)*(x - 1) + 5*y*(y - 1)
    denominator = (x + 2*y)*(x - 1) + y*(y - 1)
    return numerator/denominator

def Psycho(coord):
    x, y = coord
    numerator = 4*(y - 1)*(x - 1) + 5*(y - 1)**2
    denominator = 2*(y - 1)*(x - 1) + (x - 1)**2 + (y - 1)**2
    return numerator/denominator

def Coop(coord):
    x, y = coord
    return 3 - 3*y

def Defect(coord):
    x, y = coord
    return 4*x + 1

In [ ]: from collections import namedtuple

Point = namedtuple('Point', 'x y')

def reshape_data(data, points, size):
    """Shape the data so that it can be plotted easily.
    Parameters
    -----
    data : dictionary
        A dictionary where the keys are Points of the form (x, y) and
        the values are the mean score for the corresponding interactions.

```

```

    points : list
        of Point objects with coordinates (x, y).
    size : int
        The number of Points in every row/column.
    Returns
    -----
    plotting_data : list
        2-D numpy array of the scores, correctly shaped to ensure that the
        score corresponding to Point (0, 0) is in the left hand corner ie.
        the standard origin.
    """
    ordered_data = [data[point] for point in points]
    shaped_data = np.reshape(ordered_data, (size, size), order='F')
    plotting_data = np.flipud(shaped_data)
    return plotting_data

def create_points(step, progress_bar=False):
    """Creates a set of Points over the unit square.
    A Point has coordinates (x, y). This function constructs points that are
    separated by a step equal to `step`. The points are over the unit
    square which implies that the number created will be  $(1/\text{step} + 1)^2$ .
    Parameters
    -----
    step : float
        The separation between each Point. Smaller steps will produce more
        Points with coordinates that will be closer together.
    progress_bar : bool
        Whether or not to create a progress bar which will be updated
    Returns
    -----
    points : list
        of Point objects with coordinates (x, y)
    """
    num = int((1 / step) // 1) + 1

    if progress_bar:
        p_bar = tqdm(total=num ** 2, desc="Generating points")

    points = []
    for x in np.linspace(0, 1, num):
        for y in np.linspace(0, 1, num):
            points.append(Point(x, y))

            if progress_bar:
                p_bar.update()

    if progress_bar:

```

```

        p_bar.close()

    return points

def plot(plotting_data, col_map='seismic', interpolation='none', title=None,
        colorbar=True, labels=True):
    """Plot the results of the spatial tournament.
    Parameters
    -----
    col_map : str, optional
        A matplotlib colour map, full list can be found at
        http://matplotlib.org/examples/color/colormaps\_reference.html
    interpolation : str, optional
        A matplotlib interpolation, full list can be found at
        http://matplotlib.org/examples/images\_contours\_and\_fields/interpolation\_demo.html
    title : str, optional
        A title for the plot
    colorbar : bool, optional
        Choose whether the colorbar should be included or not
    labels : bool, optional
        Choose whether the axis labels and ticks should be included
    Returns
    -----
    figure : matplotlib figure
        A heat plot of the results of the spatial tournament
    """
    fig, ax = plt.subplots()
    cax = ax.imshow(
        plotting_data, cmap=col_map, interpolation=interpolation)

    if colorbar:
        max_score = np.nanmax(plotting_data)
        min_score = np.nanmin(plotting_data)
        ticks = [min_score, (max_score + min_score) / 2, max_score]
        fig.colorbar(cax, ticks=ticks)

    plt.xlabel('$x$')
    plt.ylabel('$y$', rotation=0)
    ax.tick_params(axis='both', which='both', length=0)
    plt.xticks([0, len(plotting_data) - 1], ['0', '1'])
    plt.yticks([0, len(plotting_data) - 1], ['1', '0'])

    if not labels:
        plt.axis('off')

    if title is not None:
        plt.title(title)

```

```

        return fig

In [ ]: step=0.01
        size = int((1 / step) // 1) + 1
        points = create_points(step)

In [ ]: TFT_Data = {p: TFT(p) for p in points}
        WSLS_Data = {p: WSLS(p) for p in points}
        Psycho_Data = {p: Psycho(p) for p in points}
        Coop_Data = {p: Coop(p) for p in points}
        Defect_Data = {p: Defect(p) for p in points}

In [ ]: TFT_Data = reshape_data(TFT_Data, points, size)
        WSLS_Data = reshape_data(WSLS_Data, points, size)
        Psycho_Data = reshape_data(Psycho_Data, points, size)
        Coop_Data = reshape_data(Coop_Data, points, size)
        Defect_Data = reshape_data(Defect_Data, points, size)

In [ ]: np.nanmax(TFT_Data)

In [ ]: TFT_plot = plot(TFT_Data)
        WSLS_plot = plot(WSLS_Data)
        Psycho_plot = plot(Psycho_Data)
        Coop_plot = plot(Coop_Data)
        Defect_plot = plot(Defect_Data)

In [ ]: TFT_plot.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/Ana
        WSLS_plot.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/Ana
        Psycho_plot.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/A
        Coop_plot.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/Ana
        Defect_plot.savefig('/Users/James/Projects/FinalYearReport-Manuscript/img/A

```