Technical Specification

Product Name : LED Power Supply Dimmerbale
Article No : LDX-DS-12V



0-10V

IP20

Electrical Data

Rated Input Voltage: AC 170 – 264 V
Frequency: 50 / 60 Hz
Power Factor: > 0.95
Rated Output Current: 8.3 A
Output Voltage DC 12 V
Dimming Type: 0–10 V
Dimmable: Yes
Power Efficiency: High Efficiency Design
Cooling Method: Passive Cooling with Robust Frame

Mechanical & Environmental

Housing Material: Aluminium
Body Color: Black
Ingress Protection: IP20
Protection Class: Class I
Operating Temperature: −20 °C to +40 °C
Storage Temperature: −40 °C to +80 °C
Indoor Use Only

Installation & Safety

Mounting Type: Surface Mount
Application Range: LED Strips, LED Modules, Linear Lighting
Short Circuit Protection: Yes
Overload Protection: Yes
Over-temperature Protection: Yes

Product Description (Technical)

The LDX-DS-12V is a constant-voltage LED power supply designed for indoor professional lighting systems. It operates within a wide AC input range and delivers stable DC output with high power factor and 0–10 V dimming capability.
The aluminium housing with passive cooling, combined with integrated short-circuit, overload, and over-temperature protection, ensures reliable and compliant operation in accordance with EN / IEC standards.

Rated Output Power

LDX-DS-12V-60	-	60W
LDX-DS-12V-100	-	100W
LDX-DS-12V-150	-	150W
LDX-DS-12V-200	-	200W
LDX-DS-12V-350	-	300W
LDX-DS-12V-300	-	350W

Specifications are subject to change without prior notice.