

# Checking a table for the search of exp in Rocq

What `code/exptable` checks on each line, in the notation of `doc/htr.md`

Paul Zimmermann's search for the hard-to-round cases of exp (`doc/htr.md`) reads a table with one line per subrange of inputs. This note says what a line holds, the six conditions under which the search on that line misses no hard case, and how the Rocq files in `code/exptable/` check them all with one boolean function whose answer `true` is proved to imply the six conditions. Section 7 follows the first line of the table through every step, with its numbers.

## 1 Proof by a checker, for a reader who does not use Rocq

Rocq is a proof assistant: it accepts a theorem only with a proof it can verify step by step. It is also a programming language, and it can run its own programs. The files here use both sides:

- `check_table` is a **program**. It reads the table and answers `true` or `false`. It uses integers only, plus one call to a function of the Interval library that returns two numbers  $L \leq \exp(x) \leq U$ .
- `check_tableP` is a **theorem** about that program: **if `check_table` answers `true` on a table, then every line of the table satisfies the six conditions**. It is proved once, for every possible table.
- To prove that `in_lt` satisfies the six conditions, Rocq runs the program on it, sees `true`, and applies the theorem.

So one does not need to trust the program, or to read it: the theorem is what guarantees that it tests the right thing. What one must read is the statement of the six conditions (section 4), because that is what is proved. The run itself is done by an evaluator built into Rocq (`vm_compute`, or `native_compute`, which compiles the program to machine code first).

Two words used below. The **binade** of a positive number  $y$  is the interval  $[2^e, 2^{e+1})$  that contains it. An **enclosure** of  $y$  is a pair of numbers  $L \leq y \leq U$ , here with  $U - L$  tiny compared with  $y$ .

## 2 The notation of `doc/htr.md`

- $\beta = 2^{64}$  is the machine word basis,  $\ell$  the number of words of a coefficient, so the coefficients are integers modulo  $\beta^\ell$ .
- A subrange is  $[x_0, x_1]$  with  $x_1 = x_0 + nu$ , where  $u = \text{ulp}(x)$  is the same for all  $x$  in  $[x_0, x_1]$ . The search looks at the  $n + 1$  inputs  $x_0 + ju$ ,  $j = 0, \dots, n$ .
- $v = \frac{1}{2} \text{ulp}(\exp x)$ , the same for all  $x$  in  $[x_0, x_1]$ : if  $2^e \leq \exp x < 2^{e+1}$  then  $v = 2^{e-53}$ .
- $a_i = \exp(x_0)u^i/i!$ ,  $0 \leq i < k$ : the Taylor coefficients, so that  $\exp(x_0 + ju) = a_0 + a_1j + \dots + a_{k-1}j^{k-1} + r$  with  $|r| \leq \exp(x_1)(nu)^k/k!$ .
- $A_i$  is an integer with  $0 \leq A_i < \beta^\ell$  and  $|A_i - \beta^\ell \text{frac}(a_i/v)| < 1$ .
- $P(j) = A_0 + A_1j + \dots + A_{k-1}j^{k-1}$ .
- $m$ : an input is hard to round when  $\exp(x)/v$  is within  $2^{-m}$  of an integer.  $E$  is the window of the search:  $x_0 + ju$  is a candidate when  $P(j)$  is within  $E$  of a multiple of  $\beta^\ell$ .

## 3 What a line of the table holds

A line of `in_lt` is  $x_0$  (a double, in hexadecimal), then  $n$ , then  $k$  integers  $B_0, \dots, B_{k-1}$  of  $\ell$  words each, the least significant word first:

$$B_i = P(i) \bmod \beta^\ell, \quad 0 \leq i < k.$$

This is the output of step 3 of the search in `doc/htr.md`, before the differences of step 4. It is  $P$  at  $0, 1, \dots, k-1$ , **not** the  $A_i$ : only  $B_0 = A_0$ . For `in_lt`,  $k = 8$ ,  $\ell = 5$ , every  $x_0$  is in  $[2^9, 2^{10})$  so  $u = 2^{-43}$ , and there are 67 486 lines. On line 1,  $x_0 = 0x1.4678ea18f304cp+9$ ,  $n = 7412951889$ ,  $2^{942} \leq \exp x_0 < 2^{943}$  so  $v = 2^{889}$ .

## 4 The six conditions

For one line, the search misses no hard case when:

1.  **$u$  is constant:**  $x_0$  and  $x_1$  are in the same binade  $[2^9, 2^{10})$ ;
2.  **$v$  is constant:**  $\exp x_0$  and  $\exp x_1$  are in the same binade  $[2^e, 2^{e+1})$ ;
3. **(H\_A):** there are  $A_0, \dots, A_{k-1}$  with  $0 \leq A_i < \beta^\ell$  and  $|A_i - \beta^\ell \text{frac}(a_i/v)| < 1$ , and the line holds  $B_i = P(i) \bmod \beta^\ell$  for  $i < k$ ;
4. **(H\_T):** for  $0 \leq j \leq n$ ,

$$|\exp(x_0 + ju)/v - (a_0 + a_1j + \dots + a_{k-1}j^{k-1})/v| \leq \rho, \quad \rho = \exp(x_1) \frac{(nu)^k}{k!v};$$

5. **(H\_E):**  $E \geq \beta^\ell(2^{-m} + \rho) + (1 + n + \dots + n^{k-1})$ ;
6. **the window is less than half the modulus:**  $2E < \beta^\ell$ .

Conditions 3 to 6 are the hypotheses of `hscan_exp` in `code/APaul/rocq/TaylorLink.v` (there  $M = \beta^\ell$ , and its  $a_i$  is  $a_i/v$  here). Conditions 1 and 2 make  $u$  and  $v$  single numbers on the line, which the other four take for granted. Condition 6 is on the search, not on a line: it is checked once.

In Rocq, the six conditions are `line_ok` and `table_ok` in `ExpCheck.v` (annex A).  $\ell$  appears as `l`, and  $x_0 = M_0u$  with  $M_0$  the integer significand of  $x_0$ .

## 5 The parameters

They are the first definitions of `ExpCheck.v`, and nothing else in the files is a number about the table:

```
Definition beta : Z := 2 ^ 64.      (* the machine word basis          *)
Definition l : Z := 5.              (* words of an A_i or a B_i          *)
Definition k : nat := 8.            (* terms of the Taylor polynomial    *)
Definition m : Z := 43.             (* identical bits after the round bit *)
Definition E : Z := 2 ^ 278.        (* the window of the search (a guess) *)
Definition xbin : Z := 9.           (* x ranges over [2^xbin, 2^(xbin+1)) *)
Definition guard : Z := 64.         (* extra bits in the exp enclosure    *)
```

$E = 2^{278}$  is our choice, not a value read from the search: `doc/htr.md` asks  $E \geq \beta^\ell(2^{-43} + 2^{-43.7} + 2^{-91})$ , which is below  $2^{278}$ , and line 1 needs  $E \geq 2^{277.59}$ . The value the search uses must be put here. `guard` is the number of bits beyond  $\beta^\ell$  and  $v$  at which `exp` is enclosed; it changes the cost, not the result.

## 6 How one line is checked: `check_line`

`check_line` takes  $M_0$ ,  $n$  and  $B_0, \dots, B_{k-1}$  and computes with integers only, except for one call to the certified `exp` of the Interval library.

1. **Condition 1** is three integer tests:  $0 \leq n$ ,  $2^{52} \leq M_0$  and  $M_0 + n < 2^{53}$ .
2. **Enclosures of exp.** `encl` builds the point  $M_0u$  as a float of Interval and calls its `exp` at precision  $\ell \cdot 64 + 53 + \text{guard}$  bits. The answer is two floats  $L_0 \leq \exp x_0 \leq U_0$ . The same is done at  $x_1$ :  $L_1 \leq \exp x_1 \leq U_1$ .
3. **Condition 2.**  $e$  is the exponent of  $L_0$ , so  $2^e \leq L_0 \leq \exp x_0$ ; the test is  $U_1 < 2^{e+1}$ .
4. **Condition 3.** For each  $i < k$ ,  $T = \beta^\ell a_i/v$  is  $\exp(x_0)$  times the power of two  $\beta^\ell u^i/v$ , divided by  $i!$ . The checker computes, at both ends  $L_0$  and  $U_0$ , the nearest integer  $R$  of  $T$  and the integer part  $q$  of  $T/\beta^\ell$ , and requires the same  $R$  and the same  $q$  at both ends. Then they are those of the exact  $T$ , and  $A_i = R - q\beta^\ell$  satisfies  $0 \leq A_i < \beta^\ell$  and  $|A_i - \beta^\ell \text{frac}(a_i/v)| = |R - T| \leq \frac{1}{2}$ . Last, it computes  $P(i) \bmod \beta^\ell$  from these  $A_i$  and compares with  $B_i$ .
5. **Condition 4** needs no test: it is a theorem of analysis (the Taylor remainder of `exp`, `ExpTaylor.v`).
6. **Condition 5** is one integer inequality, with  $\exp x_1$  replaced by its upper bound  $U_1$ , which only makes  $\rho$  larger.

The  $A_i$  are not in the table and cannot be read back from it: going from the  $B_i$  to the  $A_i$  divides by  $i!$ , which has no inverse modulo  $\beta^\ell$ . So the checker recomputes them from  $\exp x_0$  and compares the  $B_i$ .

`check_table` tests condition 6, then `check_line` on every line.

## 7 Line 1, step by step

The first line of `in_lt` is (the  $B_i$  are shown by their most significant word only; each has five):

$$x_0 = 0x1.4678ea18f304cp+9 \approx 652.94464, \quad n = 7412951889,$$

|                                  |                                  |
|----------------------------------|----------------------------------|
| $B_0 = 0x3be38424e0f19a8a \dots$ | $B_1 = 0x3be384255a1916fa \dots$ |
| $B_2 = 0x3be384265340936b \dots$ | $B_3 = 0x3be38427cc680fdb \dots$ |
| $B_4 = 0x3be38429c58f8c4c \dots$ | $B_5 = 0x3be3842c3eb708bc \dots$ |
| $B_6 = 0x3be3842f37de852d \dots$ | $B_7 = 0x3be38432b106019d \dots$ |

The numbers below are the checker's own values when it says so; the others are computed with `check_line.py` (a Python computation with exact integers, not a proof), and give the orders of magnitude.

**Condition 1:  $u$  is constant.** The significand of  $x_0$  is  $M_0 = 0x14678ea18f304c = 5743361827745868$ , so  $x_0 = M_0 u$  with  $u = 2^{-43}$ . Then  $x_1 = x_0 + nu$  has significand  $M_0 + n = 5743369240697757$ , that is  $x_1 = 0x1.467905b67db9dp+9 \approx 652.94549$ . Both significands are between  $2^{52}$  and  $2^{53}$ , so  $x_0$  and  $x_1$  are in  $[2^9, 2^{10})$ , where  $\text{ulp}(x) = 2^{-43}$ .

**Enclosures of  $\exp$  (checker's values).** Interval's `exp` at 437 bits returns, for  $x_0$ , two numbers  $L_0 \leq \exp(x_0) \leq U_0$  of the form  $L_0 = p \cdot 2^{505}$  with  $p$  an integer of 438 bits, and  $U_0 = L_0 + 2^{505}$ : an enclosure of relative width about  $2^{-437}$ . The same holds at  $x_1$ .

**Condition 2:  $v$  is constant.**  $L_0$  lies in  $[2^{942}, 2^{943})$ , so  $2^{942} \leq \exp(x_0)$  and  $e = 942$ ; the upper end  $U_1$  at  $x_1$  is below  $2^{943}$ . So all of  $\exp(x_0), \dots, \exp(x_1)$  are in  $[2^{942}, 2^{943})$  and  $v = 2^{942-53} = 2^{889}$ . (Here  $x_0 \approx 942 \ln 2$ : this line starts exactly where `exp` enters that binade,  $\exp(x_0) \approx 2^{942.000000}$ , and  $\exp(x_1) \approx 2^{942.0012}$ .)

**Condition 3: the  $A_i$ , then the  $B_i$ .** For each  $i$ , the checker forms  $T = \beta^\ell a_i / v$  at both ends of the enclosure and finds the same integer part of  $T/\beta^\ell$  ( $q$  below) and the same nearest integer  $R$  of  $T$ ; then  $A_i = R - q\beta^\ell$ . The distance  $|R - T|$  is at most  $1/2$ , so (H\_A) holds.

| $i$ | $a_i/v$                     | $q$              | $A_i$ , top word   |
|-----|-----------------------------|------------------|--------------------|
| 0   | $9.007199255 \cdot 10^{15}$ | 9007199254741449 | 0x3be38424e0f19a8a |
| 1   | 1024.0000                   | 1024             | 0x39277c70         |
| 2   | $5.82 \cdot 10^{-11}$       | 0                | 0x40000000         |
| 3   | $2.21 \cdot 10^{-24}$       | 0                | 0x0                |
| 4   | $6.27 \cdot 10^{-38}$       | 0                | 0x0                |
| 5   | $1.43 \cdot 10^{-51}$       | 0                | 0x0                |
| 6   | $2.70 \cdot 10^{-65}$       | 0                | 0x0                |
| 7   | $4.39 \cdot 10^{-79}$       | 0                | 0x0                |

From the fourth on,  $a_i/v$  is below  $2^{-64}$ , so the top word of  $A_i$  is 0 and only the lower words are nonzero. The checker then computes  $P(0), \dots, P(7)$  modulo  $\beta^\ell$  from these  $A_i$  and finds exactly the eight  $B_i$  of the line. Only  $B_0 = P(0) = A_0$ . The other  $A_i$  are small next to  $A_0$  (the top word of  $A_1$  is below  $2^{30}$ , that of  $A_2$  is  $2^{30}$ , the others are 0), so  $P(i) = A_0 + A_1 i + \dots$  changes only the low half of the top word: this is why the eight top words look alike.

**Condition 4: (H\_T).** Nothing to compute: the Taylor theorem gives the bound, with

$$\rho = \exp(x_1) \frac{(nu)^k}{k!v} \approx 2^{-44.00}.$$

**Condition 5: (H\_E).** The three terms of the window are  $\beta^\ell 2^{-m} = 2^{277}$ ,  $\beta^\ell \rho \approx 2^{276.00}$  and  $1 + n + \dots + n^7 \approx 2^{229.51}$ , a total of about  $2^{277.59}$ . The checker bounds  $\rho$  from above with  $U_1$  and verifies that the total is at most  $E = 2^{278}$ .

**Condition 6** is on the whole table:  $2E = 2^{279} < \beta^\ell = 2^{320}$ .

On this line `check_line` answers `true`; the line then satisfies the six conditions, by the theorem.

## 8 The theorem

Theorem `check_tableP t : check_table t = true -> table_ok t`.

It is proved once, in `ExpProof.v` (annex B), from four files:

- `ExpEncl.v`: what `encl` returns does enclose `exp`, from the correctness theorem `I.exp_correct` of `Interval`;
- `ExpArith.v`: each integer test of the checker, read in the real numbers;
- `ExpTaylor.v`: the Taylor remainder, condition 4.

No lemma is admitted. The theorem rests on the axioms of Rocq’s real numbers (`sig_forall_dec`, `sig_not_dec`), functional extensionality and the excluded middle (`classic`), which the libraries bring in, and on the declarations of the primitive 63-bit integers that the `Interval` library computes with.

A table is then checked by one computation: `ExpRun.v` proves `table_ok table` by apply `check_tableP` and evaluating `check_table table` to `true`.

## 9 The result: the whole table

All 67 486 lines of `in_lt` pass. The Rocq file `ExpAll.v` proves, for each of the 15 slices `NN = 00, ..., 14`:

Lemma `lines_okNN : forall s, In s ExpDataNN.lines -> exists M0 n B, parse s = Some (M0, n, B) /\ line_ok M0 n B`.

In words: **every line of the table, read by `parse`, is a subrange  $[x_0, x_1]$  with its  $n$  and its  $B_0, \dots, B_7$  that satisfies the six conditions of section 4**, for the parameters of section 5 ( $E = 2^{278}$ ). Conditions 3 to 6 are the hypotheses of `hscan_exp` in `TaylorLink.v`, which says that the search then misses no  $x_0 + ju$  with  $\exp(x_0 + ju)/v$  within  $2^{-m}$  of an integer; the two are not yet joined in one Rocq theorem.

The run was made on `roquableu` (an Intel Xeon E5-2667 server, 24 threads), with `native_compute`; all times are measured:

|                             | wall time  | per slice    |
|-----------------------------|------------|--------------|
| slice 00 alone              | 3 min 36 s | 209 s        |
| slices 01 to 14, 14 at once | 4 min 37 s | 226 to 274 s |
| <b>ExpAll.v</b>             | 7.5 s      |              |

A slice of 4 500 lines takes 209 s alone, 0.046 s a line, and each worker uses about 605 MB. Run 14 at once, a slice takes up to 30% longer, the cores being shared. The whole table is about one hour of processor time (57 minutes for slices 01 to 14, plus 3.5 for slice 00).

## 10 Running it

`gen.py in_lt FIRST COUNT K L ExpData.v` writes lines `FIRST + 1` to `FIRST + COUNT` of `in_lt` as the Rocq list `table` (it only parses;  $K$  and  $L$  must be `k` and `l`). `make` builds the files and `ExpRun.v`.

The table is in the repository as `code/exptable/in_lt.xz`; `xz -dk in_lt.xz` gives `in_lt`, and `sha256sum -c in_lt.sha256` checks it.

The whole table is checked in slices. `mkslices.sh in_lt 15` cuts it into 15 slices of 4 500 lines. `ExpData00.v` to `ExpData14.v` hold the lines **verbatim**, as primitive strings (`genraw.py`); the Rocq function `parse` (`ExpParse.v`) reads each one into  $(M_0, n, B)$  during the evaluation. For each slice, `ExpRunNN.v` proves that `check_raw`, which parses every line and runs `check_line` on it, answers `true`, with `native_compute`. These files use `ExpCheck.v` and `ExpParse.v` only, so the proofs can change without running them again. `make -j15 slices` runs them in parallel; `make all-slices` then builds `ExpAll.v`: every line of every slice reads as a line that satisfies the six conditions (`check_rawP`).

The text form matters for the cost. Measured on 300 lines on the desktop, Rocq reads the lines as strings in 0.5 s (168 MB), but the same numbers written as decimal integers in 55 s (1.1 GB), and in hexadecimal in 28 s: building each 320-bit number as a Rocq term is what is slow. The check of the 300 lines then takes 21.5 s with `native_compute`.

Measured on the first 10 lines, on the desktop: `check_table` evaluates to `true` in 2.48 s with `vm_compute`, and in 0.75 s with `native_compute` once the code is compiled (1.50 s the first time). That is 0.25 s and 0.075 s a line. At 0.075 s a line, the 67 486 lines would take about 1.4 h on one core (scaled, not measured). Changing one bit of a  $B_i$ , moving  $x_0$  by one ulp, or doubling  $n$  makes `check_line` answer `false` on line 1.

`check_line.py` computes the same six conditions for one line in Python, with its own integer exp at 1200 bits. It is a reference, not a proof; it agrees with the Rocq checker on the first 10 lines.

## 11 What is not checked

- That the lines cover the whole range: each line is checked alone, and nothing relates  $x_0$  of a line to  $x_1$  of the previous one.
- The value of  $E$  that the search actually uses: the run is for  $E = 2^{278}$  (see the parameters). A different  $E$  is a change to `ExpCheck.v`, and the run must be made again (about 5 minutes on roquableu).
- The parser: that `parse` reads a line as the text says. It agrees with `gen.py` on the first 10 lines, but it is not proved.
- The search itself: that is `TaylorLink.v`, which this check feeds.

## A ExpCheck.v

```
(** * Checking a table for the hard-to-round search of exp, by reflection

The search is the one of [doc/htr.md] (Paul Zimmermann), whose
notation we keep. The input range is cut into subranges
[[x0, x1]] with [x1 = x0 + n u], [u = ulp x] and [v = ulp(exp x) / 2]
constant on each. With [a_i = exp x0 u^i / i!], each [A_i] is an
integer with [0 <= A_i < beta^l] and [|A_i - beta^l frac(a_i/v)| < 1],
and [P(j) = A_0 + A_1 j + ... + A_(k-1) j^(k-1)].

A line of the table is [(x0, n, B)] with [B_i = P(i) mod beta^l] for
[i < k], the output of step 3 of the search. [line_ok] states the
six conditions under which the search on that line misses no hard
case; [check_table] tests them all with one boolean function. This
file holds the definitions only; [ExpProof.check_tableP] proves that
a [true] answer gives [table_ok]. *)

From Stdlib Require Import ZArith Reals Lia Lra List.
From Flocq Require Import Core.
From Bignums Require Import BigZ.
From Interval Require Import Xreal Basic Specific_bigint Specific_ops.
From Interval Require Import Float_full.
Import ListNotations.

(** ** Parameters

The table and the search are described here and nowhere else, in the
notation of [doc/htr.md]. *)

Open Scope Z_scope.

Definition beta : Z := 2 ^ 64.      (* the machine word basis *)
Definition l : Z := 5.             (* words of an A_i or a B_i *)
Definition k : nat := 8.           (* terms of the Taylor polynomial *)
Definition m : Z := 43.            (* identical bits after the round bit *)
Definition E : Z := 2 ^ 278.       (* the window of the search (a guess) *)
Definition xbin : Z := 9.          (* x ranges over [2^xbin, 2^(xbin+1)) *)
Definition guard : Z := 64.        (* extra bits in the exp enclosure *)

(** ** Derived constants

[beta^l = 2^lbits], [u = 2^uexp], [v = 2^(e - vsh)] for [exp x] in
[[2^e, 2^(e+1))], and the precision at which [exp] is enclosed. *)

Module SFBI2 := SpecificFloat BigIntRadix2.
Module I := FloatIntervalFull SFBI2.

Definition beta_l : Z := beta ^ l.
Definition lbits : Z := Z.log2 beta * l.
Definition uexp : Z := xbin - 52.
Definition vsh : Z := 53.
Definition prec : SFBI2.precision :=
  SFBI2.PtoP (Z.to_pos (lbits + vsh + guard)).

(** ** The conditions *)
```

```

Open Scope R_scope.

Definition bp (e : Z) : R := bpow radix2 e.
Definition u : R := bp uexp.
Definition fracR (r : R) : R := r - IZR (Zfloor r).

(** [a_i = exp x0 u^i / i!]. *)
Definition a (x0 : R) (i : nat) : R := exp x0 * u ^ i / INR (fact i).

(** [f 0 + ... + f (N-1)]. *)
Fixpoint sumR (f : nat -> R) (N : nat) : R :=
  match N with 0 => 0 | S N' => sumR f N' + f N' end.

(** [P(j) = A_0 + A_1 j + ... + A_(k-1) j^(k-1)], in integers. *)
Definition Pz (A : list Z) (j : Z) : Z :=
  fold_right Z.add 0%Z (map (fun i => (nth i A 0 * j ^ Z.of_nat i)%Z) (seq 0 k)).

(** The six conditions on a line [(x0, n, B)], [x0 = M0 u]. *)
Definition line_ok (M0 n : Z) (B : list Z) : Prop :=
  let x0 := IZR M0 * u in
  let x1 := IZR (M0 + n) * u in
  exists e : Z,
  let v := bp (e - vsh) in
  let rho := exp x1 * (IZR n * u) ^ k / (INR (fact k) * v) in
  (* 1. u is constant on [x0, x1] *)
  (0 <= n)%Z /\ bp xbin <= x0 /\ x1 < bp (xbin + 1) /\
  (* 2. v is constant on [x0, x1] *)
  bp e <= exp x0 /\ exp x1 < bp (e + 1) /\
  (* 3. (H_A), and the table holds P(0) .. P(k-1) *)
  (exists A : list Z, length A = k /\ length B = k /\
    (forall i, (i < k)%nat ->
      (0 <= nth i A 0%Z < beta_l)%Z /\
      Rabs (IZR (nth i A 0%Z) - IZR beta_l * fracR (a x0 i / v)) < 1) /\
    (forall i, (i < k)%nat ->
      nth i B 0%Z = (Pz A (Z.of_nat i) mod beta_l)%Z)) /\
  (* 4. (H_T), the Taylor remainder *)
  (forall j, (0 <= j <= n)%Z ->
    Rabs (exp (x0 + IZR j * u) / v - sumR (fun i => a x0 i / v * IZR j ^ i) k)
      <= rho) /\
  (* 5. (H_E), the window *)
  IZR beta_l * (bp (- m) + rho) + sumR (fun i => IZR n ^ i) k <= IZR E.

(** Condition 6, [2 E < beta^l], is on the search, not on a line. *)
Definition table_ok (t : list (Z * Z * list Z)) : Prop :=
  (2 * E < beta_l)%Z /\
  forall M0 n B, In (M0, n, B) t -> line_ok M0 n B.

Close Scope R_scope.

(** ** The checker **)

Open Scope bool_scope.

(** The float [N u]. *)
Definition xpt (N : Z) : SFBI2.type :=

```

```

Specific_ops.Float (BigZ.of_Z N) (BigZ.of_Z uexp).

(** A positive float as its significand and exponent. *)
Definition getF (f : SFBI2.type) : option (positive * Z) :=
  match SFBI2.toF f with Basic.Float false p e => Some (p, e) | _ => None end.

(** An enclosure  $[[mL \cdot 2^{fL}, mU \cdot 2^{fU}]]$  of  $[\exp(N \cdot u)]$ . *)
Definition encl (N : Z) : option (Z * Z * Z * Z) :=
  if SFBI2.valid_lb (xpt N) && SFBI2.valid_ub (xpt N) &&
    match getF (xpt N) with
    | Some (p, e) => Z.eqb (Z.pos p) N && Z.eqb e uexp
    | None => false
  end
then
  match I.exp prec (Float.Ibnd (xpt N) (xpt N)) with
  | Float.Ibnd lo up =>
    if SFBI2.valid_lb lo && SFBI2.valid_ub up then
      match getF lo, getF up with
      | Some (pL, fL), Some (pU, fU) => Some (Z.pos pL, fL, Z.pos pU, fU)
      | _, _ => None
    end
  else None
  | Float.Inan => None
end
else None.

(**  $\lfloor p \cdot 2^g / fk + h / 2 \rfloor$ , in integers. *)
Definition flr (p g fk h : Z) : Z :=
  if Z.leb 0 g then (2 * p * 2 ^ g + h * fk) / (2 * fk)
  else (2 * p + h * fk * 2 ^ (- g)) / (2 * fk * 2 ^ (- g)).

(**  $[p \cdot 2^f < 2^g]$ , for  $[p \geq 1]$ . *)
Definition lt2 (p f g : Z) : bool :=
  if Z.leb g f then false else Z.ltb p (2 ^ (g - f)).

(**  $[A_i]$ , from the enclosure of  $[\exp x_0]$ :  $[\beta^l a_i / v]$  is
 $[p \cdot 2^{(f + g_i) / i!}]$ , its nearest integer  $[R]$  and its integer part
 $[q]$  (in units of  $[\beta^l]$ ) must be the same at both ends. *)
Definition coefA (mL fL mU fU e : Z) (i : nat) (fk : Z) : option Z :=
  let gi := lbits + uexp * Z.of_nat i - (e - vsh) in
  let R := flr mL (fL + gi) fk 1 in
  let q := flr mL (fL + gi - lbits) fk 0 in
  let Ai := R - q * beta_l in
  if Z.eqb R (flr mU (fU + gi) fk 1) &&
    Z.eqb q (flr mU (fU + gi - lbits) fk 0) &&
    Z.leb 0 Ai && Z.ltb Ai beta_l
  then Some Ai else None.

(**  $[A_i \dots A_{(i+c-1)}]$ ,  $[fk]$  being  $[i!]$ . *)
Fixpoint coefs (mL fL mU fU e : Z) (i : nat) (fk : Z) (c : nat)
  : option (list Z) :=
  match c with
  | 0 => Some nil
  | S c' =>
    match coefA mL fL mU fU e i fk,
    coefs mL fL mU fU e (S i) (fk * Z.of_nat (S i)) c' with

```

```

    | Some Ai, Some As => Some (Ai :: As)
    | _, _ => None
  end
end.

(** [1 + n + ... + n^(k-1)]. *)
Definition sumn (n : Z) : Z :=
  fold_right Z.add 0 (map (fun i => n ^ Z.of_nat i) (seq 0 k)).

(** (H_E) with [exp x1 <= mU 2^fU]:
    [beta^l (2^-m + mU 2^fU (n u)^k / (k! v)) + sumn n <= E]. *)
Definition window_ok (mU fU e n : Z) : bool :=
  let X := mU * n ^ Z.of_nat k in
  let g := fU + lbits + uexp * Z.of_nat k - (e - vsh) in
  let C := 2 ^ (lbits - m) + sumn n in
  let kf := Z.of_nat (fact k) in
  if Z.leb 0 g then Z.leb (X * 2 ^ g + C * kf) (E * kf)
  else Z.leb (X + C * kf * 2 ^ (- g)) (E * kf * 2 ^ (- g)).

Definition check_line (M0 n : Z) (B : list Z) : bool :=
  Z.leb 0 n && Z.leb (2 ^ 52) M0 && Z.ltb (M0 + n) (2 ^ 53) &&
  Nat.eqb (length B) k &&
  match encl M0, encl (M0 + n) with
  | Some (mL0, fL0, mU0, fU0), Some (mL1, fL1, mU1, fU1) =>
    let e := Z.log2 mL0 + fL0 in
    lt2 mU1 fU1 (e + 1) && window_ok mU1 fU1 e n &&
    match coefs mL0 fL0 mU0 fU0 e 0 1 k with
    | Some A =>
      forallb (fun i => Z.eqb (nth i B 0) (Pz A (Z.of_nat i) mod beta_l))
        (seq 0 k)
    | None => false
    end
  | _, _ => false
  end.

Definition check_table (t : list (Z * Z * list Z)) : bool :=
  Z.ltb (2 * E) beta_l && Z.leb m lbits &&
  forallb (fun r => match r with (M0, n, B) => check_line M0 n B end) t.

```

## B ExpProof.v

```

(** * A [true] answer of the checker gives the six conditions *)

From Stdlib Require Import ZArith Reals Lia Lra List Bool.
From Flocq Require Import Core.
From ExpTable Require Import ExpCheck ExpParse ExpTaylor ExpArith ExpEncl.

Open Scope R_scope.

(** The parameters leave room for the [2^-m] term of the window. *)
Lemma m_le_lbits : (m <= lbits)%Z.
Proof. apply Z.leb_le; vm_compute; reflexivity. Qed.

(** [N u] is in [[2^xbin, 2^(xbin+1)]] when [N] has 53 bits. *)
Lemma x_lo N : (2 ^ 52 <= N)%Z -> bp xbin <= IZR N * u.

```

```

Proof.
intros hN; unfold u, uexp, bp.
replace xbin with (52 + (xbin - 52))%Z at 1 by ring.
rewrite bpow_plus; apply Rmult_le_compat_r; [apply bpow_ge_0|].
rewrite <- IZR_Zpower by lia; apply IZR_le; exact hN.
Qed.

Lemma x_hi N : (N < 2 ^ 53)%Z -> IZR N * u < bp (xbin + 1).
Proof.
intros hN; unfold u, uexp, bp.
replace (xbin + 1)%Z with (53 + (xbin - 52))%Z by ring.
rewrite bpow_plus; apply Rmult_lt_compat_r; [apply bpow_gt_0|].
rewrite <- IZR_Zpower by lia; apply IZR_lt; exact hN.
Qed.

Theorem check_lineP M0 n B : check_line M0 n B = true -> line_ok M0 n B.
Proof.
unfold check_line.
destruct (encl M0) as [[[[mL0 fL0] mU0] fU0]] eqn:h0;
  [|rewrite !andb_false_r; discriminate].
destruct (encl (M0 + n)) as [[[[mL1 fL1] mU1] fU1]] eqn:h1;
  [|rewrite !andb_false_r; discriminate].
set (e := (Z.log2 mL0 + fL0)%Z).
destruct (coefs mL0 fL0 mU0 fU0 e 0 1 k) as [A] eqn:hc;
  [|rewrite !andb_false_r; discriminate].
intros h.
apply andb_prop in h as [h hm].
apply andb_prop in hm as [hm hB].
apply andb_prop in hm as [hlt hw].
apply andb_prop in h as [h hlen].
apply andb_prop in h as [h h53].
apply andb_prop in h as [hn h52].
apply Z.leb_le in hn; apply Z.leb_le in h52; apply Z.ltb_lt in h53.
apply Nat.eqb_eq in hlen.
destruct (encl_ok _ _ _ _ h0) as [pL0 [pU0 [lo0 up0]]].
destruct (encl_ok _ _ _ _ h1) as [pL1 [pU1 [lo1 up1]]].
exists e; cbv zeta.
assert (hx1 : IZR (M0 + n) * u = IZR M0 * u + IZR n * u)
  by (rewrite plus_IZR; ring).
repeat split.
- (* 1. u is constant *)
  exact hn.
- apply x_lo; exact h52.
- apply x_hi; exact h53.
- (* 2. v is constant *)
  apply Rle_trans with (IZR mL0 * bp fL0); [apply log2_le; exact pL0|].
  exact lo0.
- apply Rle_lt_trans with (IZR mU1 * bp fU1); [exact up1|].
  apply lt2_ok; [lia|exact hlt].
- (* 3. (H_A), and the table holds P(0) .. P(k-1) *)
  exists A.
  destruct (coefs_ok _ _ _ _ _ _ _ _ _ _ eq_refl (conj lo0 up0) hc)
    as [h1A hA].
  split; [exact h1A|]; split; [exact hlen|]; split.
+ intros i hi; destruct (hA i hi) as [hA1 hA2]; split; [exact hA1|].
  exact hA2.

```

```

+ intros i hi.
  rewrite forallb_forall in hB.
  apply Z.eqb_eq, hB, in_seq; lia.
- (* 4. (H_T) *)
  intros j hj; rewrite hx1.
  apply HT_ok; [apply bpow_gt_0|lia].
- (* 5. (H_E) *)
  apply window_okP with (mU := mU1) (fU := fU1);
    [exact m_le_lbits|exact hn| |exact hw].
  split; [apply Rlt_le, exp_pos|exact up1].
Qed.

Theorem check_tableP t : check_table t = true -> table_ok t.
Proof.
unfold check_table; intros h.
apply andb_prop in h as [h hall].
apply andb_prop in h as [h2E _].
split; [apply Z.ltb_lt; exact h2E|].
intros M0 n B hin.
rewrite forallb_forall in hall.
apply check_lineP; exact (hall _ hin).
Qed.

(** The same on the text of the lines: each one reads as a line that
    satisfies the six conditions. *)
Theorem check_rawP ls : check_raw ls = true ->
  (2 * E < beta_l)%Z /\
  forall s, In s ls -> exists M0 n B,
    parse s = Some (M0, n, B) /\ line_ok M0 n B.
Proof.
unfold check_raw; intros h.
apply andb_prop in h as [h hall].
apply andb_prop in h as [h2E _].
split; [apply Z.ltb_lt; exact h2E|].
intros s hin.
rewrite forallb_forall in hall.
specialize (hall _ hin).
destruct (parse s) as [[[M0 n] B]]; [|discriminate].
exists M0, n, B; split; [reflexivity|].
apply check_lineP; exact hall.
Qed.

```

## C ExpEncl.v

```

(** * The enclosure of exp given by Interval *)

From Stdlib Require Import ZArith Reals Lia Lra.
From Flocq Require Import Core.
From Interval Require Import Xreal Basic Specific_bigint Specific_ops.
From ExpTable Require Import ExpCheck.

Open Scope R_scope.

(* A positive float with a radix-2 exponent is p 2^e. *)

```

```

Lemma FtoR_pos p e : FtoR radix2 false p e = IZR (Z.pos p) * bp e.
Proof.
unfold bp; destruct e as [|q|q]; cbv beta iota zeta delta [FtoR bpow].
- lra.
- rewrite mult_IZR; reflexivity.
- reflexivity.
Qed.

(* The value of a float read by getF. *)
Lemma getF_val f p e : getF f = Some (p, e) ->
  SFBI2.toX f = Xreal (IZR (Z.pos p) * bp e).
Proof.
unfold getF, SFBI2.toX.
destruct (SFBI2.toF f) as [| [|] p' e']; try discriminate.
intros H; injection H; intros <- <-; simpl FtoX; rewrite <- FtoR_pos.
reflexivity.
Qed.

Lemma encl_ok N mL fL mU fU : encl N = Some (mL, fL, mU, fU) ->
  (0 < mL)%Z /\ (0 < mU)%Z /\
  IZR mL * bp fL <= exp (IZR N * u) <= IZR mU * bp fU.
Proof.
unfold encl.
destruct (SFBI2.valid_lb (xpt N)) eqn:VL; [|discriminate|.
destruct (SFBI2.valid_ub (xpt N)) eqn:VU; [|discriminate|.
destruct (getF (xpt N)) as [|p e|] eqn:GX; [|discriminate|.
destruct (Z.eqb_spec (Z.pos p) N) as [HN|]; [|discriminate|.
destruct (Z.eqb_spec e uexp) as [He|]; [|discriminate|.
simpl andb; cbv iota.
(* The point interval contains N u. *)
assert (Hc : Interval.contains
  (I.convert (Float.Ibnd (xpt N) (xpt N))) (Xreal (IZR N * u))).
{ unfold I.convert; change I.F.valid_lb with SFBI2.valid_lb.
  change I.F.valid_ub with SFBI2.valid_ub; rewrite VL, VU.
  change I.F.toX with SFBI2.toX; rewrite (getF_val _ _ GX), HN, He.
  unfold u; simpl; lra. }
generalize (I.exp_correct prec _ _ Hc).
destruct (I.exp prec (Float.Ibnd (xpt N) (xpt N))) as [|lo up|];
[discriminate|].
unfold I.convert.
change I.F.valid_lb with SFBI2.valid_lb.
change I.F.valid_ub with SFBI2.valid_ub.
change (SFBI2.valid_lb lo) with true; rewrite Bool.andb_true_l.
destruct (SFBI2.valid_ub up); [|intros _ H; discriminate H|.
destruct (getF lo) as [|pL fL'|] eqn:GL; [|intros _ H; discriminate H|.
destruct (getF up) as [|pU fU'|] eqn:GU; [|intros _ H; discriminate H|.
change I.F.toX with SFBI2.toX.
rewrite (getF_val _ _ GL), (getF_val _ _ GU).
intros [H1 H2] H; injection H; intros <- <- <- <-.
split; [lia|split; [lia|]].
split; assumption.
Qed.

```

## D ExpArith.v

```
(** * The integer tests of the checker, read in the reals *)

From Stdlib Require Import ZArith Reals Lia Lra List.
From Flocq Require Import Core.
From ExpTable Require Import ExpCheck.

Open Scope R_scope.

(** [flr] is the floor it is named after. *)
Lemma flrE p g fk h : (0 < fk)%Z -> (0 <= h)%Z ->
  flr p g fk h = Zfloor (IZR p * bp g / IZR fk + IZR h / 2).
Proof.
  intros Hfk Hh; unfold flr, bp.
  assert (Hfk' : IZR fk <> 0) by (apply not_0_IZR; lia).
  destruct (Z.leb_spec 0 g) as [Hg | Hg].
- rewrite <- Zfloor_div by lia; f_equal.
  rewrite <- (IZR_Zpower radix2 g) by lia; simpl radix_val.
  rewrite !mult_IZR, plus_IZR, !mult_IZR; field; auto.
- rewrite <- Zfloor_div.
  2: { apply Z.neq_mul_0; split; [lia]; apply Z.pow_nonzero; lia. }
  f_equal.
  (* a negative power of two is the inverse of an integer *)
  assert (Hq : bpow radix2 g = / IZR (2 ^ (- g))).
  { rewrite (IZR_Zpower radix2) by lia; rewrite bpow_opp, Rinv_inv; easy. }
  assert (H2 : IZR (2 ^ (- g)) <> 0).
  { apply not_0_IZR; apply Z.pow_nonzero; lia. }
  rewrite Hq, !mult_IZR, plus_IZR, !mult_IZR; field; auto.
Qed.

Lemma lt2_ok p f g : (1 <= p)%Z -> lt2 p f g = true -> IZR p * bp f < bp g.
Proof.
  intros Hp; unfold lt2, bp.
  destruct (Z.leb_spec g f) as [Hgf | Hgf]; [discriminate].
  intros Hlt; apply Z.ltb_lt in Hlt.
  replace (bpow radix2 g) with (bpow radix2 ((g - f) + f)) by (f_equal; ring).
  rewrite bpow_plus; apply Rmult_lt_compat_r; [apply bpow_gt_0].
  rewrite <- (IZR_Zpower radix2) by lia; apply IZR_lt; exact Hlt.
Qed.

Lemma log2_le p f : (0 < p)%Z -> bp (Z.log2 p + f) <= IZR p * bp f.
Proof.
  intros Hp; unfold bp; rewrite bpow_plus.
  apply Rmult_le_compat_r; [apply Rlt_le, bpow_gt_0].
  rewrite <- (IZR_Zpower radix2) by (apply Z.log2_nonneg).
  apply IZR_le; destruct (Z.log2_spec p Hp) as [H _]; exact H.
Qed.

(** [beta^l] is the power of two of exponent [lbits]. *)
Lemma beta_lE : beta_l = (2 ^ lbits)%Z.
Proof. vm_compute; reflexivity. Qed.

Lemma lbits_ge0 : (0 <= lbits)%Z.
Proof. vm_compute; discriminate. Qed.
```

```

Lemma beta_lR : IZR beta_l = bp lbits.
Proof.
rewrite beta_lE; unfold bp; rewrite (IZR_Zpower radix2); [easy|].
exact lbits_ge0.
Qed.

(** A power of a power of two. *)
Lemma bp_pow a i : bp a ^ i = bp (a * Z.of_nat i).
Proof.
induction i as [|i IH]; [now rewrite Z.mul_0_r|].
rewrite Nat2Z.inj_succ, <- Z.add_1_r, Z.mul_add_distr_l, Z.mul_1_r.
unfold bp in *; rewrite bpow_plus, <- IH; simpl; ring.
Qed.

(** Moving the start of an integer sum. *)
Lemma fold_addE (s : list Z) a :
  fold_right Z.add a s = (fold_right Z.add 0 s + a)%Z.
Proof. induction s as [|x s IH]; simpl; lia. Qed.

(** [sumR] of powers of an integer, in integers. *)
Lemma sumR_powE n N : sumR (fun i => IZR n ^ i) N =
  IZR (fold_right Z.add 0 (map (fun i => n ^ Z.of_nat i) (seq 0 N)))%Z.
Proof.
induction N as [|N IH]; [easy|].
rewrite seq_S, map_app, fold_right_app; simpl.
rewrite fold_addE, plus_IZR, <- IH, Z.add_0_r, pow_IZR; easy.
Qed.

(** A power of two, as an integer. *)
Lemma bp_IZR g : (0 <= g)%Z -> bp g = IZR (2 ^ g).
Proof.
intros Hg; unfold bp; rewrite <- (IZR_Zpower radix2) by exact Hg; easy.
Qed.

(** A negative power of two, as the inverse of an integer. *)
Lemma bp_IZRN g : (g < 0)%Z -> bp g = / IZR (2 ^ (- g)).
Proof.
intros Hg; unfold bp; rewrite (IZR_Zpower radix2) by lia.
rewrite bpow_opp, Rinv_inv; easy.
Qed.

(** [window_ok] in the reals, before the bound on [exp x1]. *)
Lemma window_okR mU fU e n : window_ok mU fU e n = true ->
  IZR (2 ^ (lbits - m) + sumn n) + IZR (mU * n ^ Z.of_nat k) *
  bp (fU + lbits + uexp * Z.of_nat k - (e - vsh)) / IZR (Z.of_nat (fact k))
  <= IZR E.
Proof.
unfold window_ok; cbv zeta.
set (X := (mU * n ^ Z.of_nat k)%Z).
set (g := (fU + lbits + uexp * Z.of_nat k - (e - vsh))%Z).
set (C := (2 ^ (lbits - m) + sumn n)%Z).
set (kf := Z.of_nat (fact k)).
assert (Hkf : (0 < kf)%Z) by (pose proof (lt_0_fact k); lia).
assert (HkfR : 0 < IZR kf) by (apply IZR_lt; exact Hkf).
clearbody X g C kf; generalize E; intros EE.
destruct (Z.leb_spec 0 g) as [Hg | Hg]; intros H; apply Z.leb_le, IZR_le in H;

```

```

rewrite ?plus_IZR, ?mult_IZR, ?plus_IZR, ?mult_IZR in H.
- rewrite bp_IZR by exact Hg.
  (* field and lra only see real variables, or the kernel check is slow *)
  generalize (IZR X) (IZR C) (IZR (2 ^ g)) (IZR EE) H.
  generalize (IZR kf) HkfR; clear; intros kr Hk xr cr pr er H.
  apply Rmult_le_reg_r with (1 := Hk).
  replace ((cr + xr * pr / kr) * kr) with (xr * pr + cr * kr) by (field; lra).
  exact H.
- rewrite bp_IZRN by exact Hg.
  assert (HP : 0 < IZR (2 ^ (- g))).
  { apply IZR_lt; apply Z.pow_pos_nonneg; lia. }
  generalize (IZR X) (IZR C) (IZR (2 ^ (- g))) (IZR EE) H HP.
  generalize (IZR kf) HkfR; clear; intros kr Hk xr cr pr er H Hp.
  apply Rmult_le_reg_r with (r := kr * pr); [now apply Rmult_lt_0_compat|].
  replace ((cr + xr * / pr / kr) * (kr * pr))
    with (xr + cr * kr * pr) by (field; lra).
  lra.
Qed.

(** (H_E), from an upper bound [mU 2^fU] of [y = exp x1]. *)
Lemma window_okP mU fU e n y :
  (m <= lbits)%Z -> (0 <= n)%Z -> 0 <= y <= IZR mU * bp fU ->
  window_ok mU fU e n = true ->
  IZR beta_l * (bp (- m) + y * (IZR n * u) ^ k / (INR (fact k) * bp (e - vsh)))
    + sumR (fun i => IZR n ^ i) k <= IZR E.
Proof.
intros Hm Hn Hy Hw.
eapply Rle_trans; [| exact (window_okR _ _ _ Hw)].
rewrite sumR_powE; fold (sumn n).
rewrite plus_IZR, mult_IZR, <- pow_IZR, <- INR_IZR_INZ.
rewrite <- bp_IZR by lia.
rewrite beta_lR.
unfold u; rewrite Rpow_mult_distr, bp_pow.
replace (bp (lbits - m)) with (bp lbits * bp (- m))
  by (unfold bp; rewrite <- bpow_plus; f_equal; ring).
replace (bp (fU + lbits + uexp * Z.of_nat k - (e - vsh)))
  with (bp fU * bp lbits * bp (uexp * Z.of_nat k) / bp (e - vsh))
  by (unfold bp, Rdiv; rewrite <- bpow_opp, <- !bpow_plus; f_equal; ring).
assert (HB : 0 < bp lbits) by apply bpow_gt_0.
assert (HU : 0 < bp (uexp * Z.of_nat k)) by apply bpow_gt_0.
assert (HV : 0 < bp (e - vsh)) by apply bpow_gt_0.
assert (HK : 0 < INR (fact k)) by apply INR_fact_lt_0.
assert (HN : 0 <= IZR n ^ k) by (apply pow_le, IZR_le; exact Hn).
(* only real variables are left *)
revert Hy HB HU HV HK HN.
generalize (bp lbits) (bp (- m)) (bp (uexp * Z.of_nat k)) (bp (e - vsh)).
generalize (INR (fact k)) (IZR n ^ k) (IZR (sumn n)) (IZR mU) (bp fU).
clear; intros K N S F1 F2 B M U V Hy HB HU HV HK HN.
assert (Hc : 0 <= N * U * B / (K * V)).
{ unfold Rdiv; apply Rmult_le_pos.
  - apply Rmult_le_pos; [apply Rmult_le_pos|]; lra.
  - apply Rlt_le, Rinv_0_lt_compat, Rmult_lt_0_compat; easy. }
replace (B * (M + y * (N * U) / (K * V)) + S)
  with (B * M + S + y * (N * U * B / (K * V))) by (field; lra).
replace (B * M + S + F1 * N * (F2 * B * U / V) / K)
  with (B * M + S + (F1 * F2) * (N * U * B / (K * V))) by (field; lra).

```

```

apply Rplus_le_compat_l, Rmult_le_compat_r; [exact Hc | apply Hy].
Qed.

(** A floor that is the same at both ends is the same in between. *)
Lemma Zfloor_mid a b d : a <= b <= d -> Zfloor a = Zfloor d ->
  Zfloor b = Zfloor a.
Proof.
intros [Hab Hbd] Had.
apply Zfloor_le in Hab; apply Zfloor_le in Hbd; lia.
Qed.

(** (H_A) for one coefficient, from an enclosure of [y = exp x0]. *)
Lemma coefA_ok mL fL mU fU e i fk Ai y :
  fk = Z.of_nat (fact i) ->
  IZR mL * bp fL <= y <= IZR mU * bp fU ->
  coefA mL fL mU fU e i fk = Some Ai ->
  (0 <= Ai < beta_l)%Z /\
  Rabs (IZR Ai - IZR beta_l * fracR (y * u ^ i / INR (fact i) / bp (e - vsh)))
  < 1.
Proof.
intros Hfk Hy H.
assert (Hfk0 : (0 < fk)%Z) by (pose proof (lt_0_fact i); lia).
unfold coefA in H; cbv zeta in H.
set (gi := (lbits + uexp * Z.of_nat i - (e - vsh))%Z) in H.
set (r := flr mL (fL + gi) fk 1) in H.
set (q := flr mL (fL + gi - lbits) fk 0) in H.
destruct (&&_) eqn:Hb; [|discriminate].
injection H as <-.
rewrite !Bool.andb_true_iff, Z.eqb_eq, Z.eqb_eq, Z.leb_le, Z.ltb_lt in Hb.
destruct Hb as [[H1 H2] H3] H4].
split; [lia|].
unfold r, q in *.
rewrite !flrE in H1, H2 by lia.
rewrite !flrE by lia.
clear H3 H4.
assert (HfkR : 0 < IZR fk) by (apply IZR_lt; exact Hfk0).
assert (HB : 0 < bp lbits) by apply bpow_gt_0.
(* the argument of fracR is y (2^gi / i!) / beta^l *)
assert (Hc : y * u ^ i / INR (fact i) / bp (e - vsh) =
  y * (bp gi / IZR fk) / bp lbits).
{ rewrite INR_IZR_INZ, <- Hfk; unfold u; rewrite bp_pow.
  unfold gi; replace (lbits + uexp * Z.of_nat i - (e - vsh))%Z
    with (lbits + uexp * Z.of_nat i + - (e - vsh))%Z by ring.
  assert (HV : 0 < bp (e - vsh)) by apply bpow_gt_0.
  unfold bp in *; rewrite !bpow_plus, bpow_opp; field; lra. }
rewrite Hc; clear Hc; clearbody gi.
assert (Ha : forall z f, IZR z * bp (f + gi) / IZR fk =
  IZR z * bp f * (bp gi / IZR fk)).
{ intros z f; unfold bp; rewrite bpow_plus; field; lra. }
assert (Hb : forall z f, IZR z * bp (f + gi - lbits) / IZR fk + 0 / 2 =
  IZR z * bp f * (bp gi / IZR fk) / bp lbits).
{ intros z f; replace (f + gi - lbits)%Z with (f + gi + - lbits)%Z by ring.
  unfold bp; rewrite !bpow_plus, bpow_opp.
  unfold bp in HB; field; lra. }
rewrite !Ha, !Hb in *; clear Ha Hb.
assert (Hc : 0 < bp gi / IZR fk).

```

```

{ apply Rdiv_lt_0_compat; [apply bpow_gt_0 | exact HfkR]. }
rewrite minus_IZR, mult_IZR, beta_lR.
unfold fracR.
(* only real variables are left *)
revert Hy H1 H2 HB Hc.
generalize (IZR mL * bp fL) (IZR mU * bp fU) (bp gi / IZR fk) (bp lbits).
clear; intros lo hi c B Hy H1 H2 HB Hc.
assert (Hlo : lo * c <= y * c) by (apply Rmult_le_compat_r; lra).
assert (Hhi : y * c <= hi * c) by (apply Rmult_le_compat_r; lra).
rewrite <- (Zfloor_mid (lo * c / B) (y * c / B) (hi * c / B));
[| | exact H2].
2: { unfold Rdiv; split; apply Rmult_le_compat_r; try lra;
    apply Rlt_le, Rinv_0_lt_compat; exact HB. }
rewrite <- (Zfloor_mid (lo * c + 1 / 2) (y * c + 1 / 2) (hi * c + 1 / 2));
[| lra | exact H1].
pose proof (Zfloor_lb (y * c + 1 / 2)).
pose proof (Zfloor_ub (y * c + 1 / 2)).
replace (B * (y * c / B - IZR (Zfloor (y * c / B))))
  with (y * c - IZR (Zfloor (y * c / B)) * B) by (field; lra).
apply Rabs_def1; lra.
Qed.

(** (H_A) for the [c] coefficients from the [i]-th on. *)
Lemma coefs_ok mL fL mU fU e y c i fk As :
  fk = Z.of_nat (fact i) ->
  IZR mL * bp fL <= y <= IZR mU * bp fU ->
  coefs mL fL mU fU e i fk c = Some As ->
  length As = c /\
  forall j, (j < c)%nat ->
    (0 <= nth j As 0%Z < beta_l)%Z /\
    Rabs (IZR (nth j As 0%Z) - IZR beta_l *
      fracR (y * u ^ (i + j) / INR (fact (i + j)) / bp (e - vsh))) < 1.
Proof.
intros Hfk Hy; revert i fk As Hfk.
induction c as [|c IH]; intros i fk As Hfk H; cbn [coefs] in H.
- injection H as <-; split; [easy | intros j Hj; lia].
- destruct (coefA mL fL mU fU e i fk) as [Ai] eqn:HA; [|discriminate].
  destruct (coefs mL fL mU fU e (S i) (fk * Z.of_nat (S i)) c) as [As']
    eqn:HAs; [|discriminate].
  injection H as <-.
  (* the next factorial *)
  assert (Hfk' : (fk * Z.of_nat (S i))%Z = Z.of_nat (fact (S i))).
  { change (fact (S i)) with (S i * fact i)%nat.
    rewrite Nat2Z.inj_mul, Hfk; ring. }
  destruct (IH _ _ Hfk' HAs) as [Hl HAs'].
  split; [simpl; lia].
  intros [|j] Hj.
  + rewrite Nat.add_0_r; exact (coefA_ok _ _ _ _ _ _ _ Hfk Hy HA).
  + replace (i + S j)%nat with (S i + j)%nat by lia.
    apply HAs'; lia.
Qed.

```

## E ExpTaylor.v

```
(** * The Taylor remainder of exp: condition 4, (H_T) *)

From Stdlib Require Import ZArith Reals Lia Lra.
From Coquelicot Require Import Coquelicot.
From ExpTable Require Import ExpCheck.

Open Scope R_scope.

(* Every derivative of exp is exp. *)
Lemma Derive_n_exp (m : nat) (t : R) : Derive_n exp m t = exp t.
Proof.
  revert t; induction m as [|m IH]; intros t; [reflexivity|].
  simpl; rewrite (Derive_ext _ _ _ IH).
  now apply is_derive_unique, is_derive_exp.
Qed.

(* exp is differentiable [m] times everywhere. *)
Lemma ex_derive_n_exp (m : nat) (t : R) : ex_derive_n exp m t.
Proof.
  destruct m as [|m]; [exact I|simpl].
  apply (ex_derive_ext exp); [intros s; now rewrite Derive_n_exp|].
  eexists; apply is_derive_exp.
Qed.

(* [sumR] with [N + 1] terms is the Stdlib [sum_f_R0] up to [N]. *)
Lemma sumR_sum_f (f : nat -> R) (N : nat) : sumR f (S N) = sum_f_R0 f N.
Proof.
  induction N as [|N IH]; [simpl; ring|].
  change (sumR f (S N) + f (S N) = sum_f_R0 f N + f (S N)); now rewrite IH.
Qed.

(** For [h >= 0], the Taylor polynomial of degree [N-1] of [exp] at [x0]
  is below [exp (x0 + h)] by at most [exp (x0 + h) h^N / N!]. *)
Lemma taylor_exp (x0 h : R) (N : nat) : 0 <= h ->
  Rabs (exp (x0 + h) - sumR (fun i => exp x0 * h ^ i / INR (fact i)) N)
  <= exp (x0 + h) * h ^ N / INR (fact N).
Proof.
  intros Hh.
  destruct N as [|N].
  simpl; rewrite Rminus_0_r, Rabs_right by (left; apply exp_pos); lra.
  destruct Hh as [Hh|<-].
  2:{ (* At [h = 0] the sum is [exp x0] and the bound is [0]. *)
    rewrite Rplus_0_r, sumR_sum_f, pow_i by lia.
    replace (sum_f_R0 _ N) with (exp x0).
    rewrite Rminus_diag, Rabs_R0, Rmult_0_r; unfold Rdiv; lra.
    induction N as [|N IH]; [simpl; field|].
    rewrite tech5, <- IH, pow_i by lia; unfold Rdiv; ring. }
  (* Lagrange: the remainder is [h^(N+1) / (N+1)! exp z], [z] in the range. *)
  destruct (Taylor_Lagrange exp N x0 (x0 + h)) as [z [Hz Hz']]; [lra|].
  intros t _ m _; apply ex_derive_n_exp.
  rewrite sumR_sum_f.
  replace (sum_f_R0 _ N) with
    (sum_f_R0 (fun m => (x0 + h - x0) ^ m / INR (fact m) * Derive_n exp m x0)
      N).
```

```

2:{ apply sum_eq; intros i _; rewrite Derive_n_exp.
  replace (x0 + h - x0) with h by ring; unfold Rdiv; ring. }
rewrite Hz' at 1; rewrite Derive_n_exp.
replace (x0 + h - x0) with h by ring.
assert (0 < INR (fact (S N))) by apply INR_fact_lt_0.
assert (0 < h ^ S N) by (apply pow_lt; lra).
rewrite Rplus_minus_l, Rabs_right.
2:{ apply Rle_ge; unfold Rdiv; apply Rmult_le_pos; [|left; apply exp_pos|.
  apply Rmult_le_pos; [lra|left; apply Rinv_0_lt_compat; lra]. }
rewrite (Rmult_comm (exp _)); unfold Rdiv.
assert (exp z < exp (x0 + h)) by (apply exp_increasing; lra).
assert (0 < / INR (fact (S N))) by (apply Rinv_0_lt_compat; lra).
assert (0 < h ^ S N * / INR (fact (S N))) by (apply Rmult_lt_0_compat; lra).
nra.
Qed.

(* Two sums with equal terms are equal. *)
Lemma sumR_ext (f g : nat -> R) (N : nat) :
  (forall i, f i = g i) -> sumR f N = sumR g N.
Proof.
intros Hfg; induction N as [|N IH]; simpl; [easy|now rewrite IH, Hfg].
Qed.

(* A common divisor comes out of the sum. *)
Lemma sumR_div (f : nat -> R) (v : R) (N : nat) :
  sumR (fun i => f i / v) N = sumR f N / v.
Proof.
induction N as [|N IH]; simpl; [|rewrite IH]; unfold Rdiv; ring.
Qed.

(** Condition 4 of [line_ok], for [j] in [[0, n]]. *)
Lemma HT_ok (x0 v : R) (n j : Z) : 0 < v -> (0 <= j <= n)%Z ->
  Rabs (exp (x0 + IZR j * u) / v - sumR (fun i => a x0 i / v * IZR j ^ i) k)
  <= exp (x0 + IZR n * u) * (IZR n * u) ^ k / (INR (fact k) * v).
Proof.
intros Hv [Hj HjN].
assert (Hu : 0 < u) by apply Flocq.Core.Raux.bpow_gt_0.
apply IZR_le in Hj; apply IZR_le in HjN.
assert (Hh : 0 <= IZR j * u) by (apply Rmult_le_pos; lra).
(* The sum is the Taylor sum at [h = j u], divided by [v]. *)
rewrite (sumR_ext _ (fun i => exp x0 * (IZR j * u) ^ i / INR (fact i) / v)).
2:{ intros i; unfold a; rewrite Rpow_mult_distr; field.
  split; [apply not_0_INR, fact_neq_0|lra]. }
rewrite (sumR_div (fun i => exp x0 * (IZR j * u) ^ i / INR (fact i))).
set (Sj := sumR _ k).
replace (exp (x0 + IZR j * u) / v - Sj / v) with
  ((exp (x0 + IZR j * u) - Sj) / v) by (field; lra).
rewrite Rabs_div, (Rabs_right v) by lra.
assert (0 < INR (fact k)) by apply INR_fact_lt_0.
replace (_ / (INR (fact k) * v)) with
  (exp (x0 + IZR n * u) * (IZR n * u) ^ k / INR (fact k) / v)
  by (field; lra).
apply Rmult_le_compat_r; [left; apply Rinv_0_lt_compat; lra|].
eapply Rle_trans; [apply taylor_exp; lra|].
(* The bound grows with [j], so [j = n] is the worst case. *)
unfold Rdiv; apply Rmult_le_compat_r; [left; apply Rinv_0_lt_compat; lra|].

```

```
apply Rmult_le_compat.  
- left; apply exp_pos.  
- now apply pow_le.  
- destruct (Rle_lt_or_eq_dec _ _ Hjn) as [Hlt|Heq]; [|rewrite Heq; lra].  
  left; apply exp_increasing; nra.  
- apply pow_incr; split; [lra|]; nra.  
Qed.
```