

socialReview

My project / Production / review-scaper-service

Search K + New ⌂ Upgrade ⌂

Environment

review-scaper-service

Events

**Settings**

MONITOR

Logs

Metrics

MANAGE

Environment

Shell \*

Scaling \*

Previews

Disk \*

Jobs \*

Changelog

Invite a friend

Contact support

Render Status

WEB SERVICE

## review-scaper-service

Docker Free Upgrade your instance →

Service ID: srv-d4lvn0euk2gs738kvkg ↗ main  
thesagor / review-scaper-service https://review-scaper-service.onrender.com ↗

Connect Manual Deploy

### Settings

**General**

**Name**  
A unique name for your Web Service.  
review-scaper-service ⌂ Edit

**Region**  
Your services in the same **region** can communicate over a **private network**.  
Oregon (US West) ⌂ Edit

**Instance Type**  
Free 0.1 CPU 512 MB ⌂ Update  
Please enter your payment information to select an instance type with higher limits.

See remaining free usage, or learn about free service limits.

**Build & Deploy**

**Repository**  
The repository used for your Web Service.  
https://github.com/thesagor/review-scaper-service ⌂ Edit

**Branch**  
The Git branch to build and deploy.  
main ⌂ Edit

**Git Credentials**  
User providing the credentials to pull the repository.  
shagor.bp3@gmail.com (you) ⌂ Use My Credentials

**Root Directory** Optional  
If set, Render runs commands from this directory instead of the repository root. Additionally, code changes outside of this directory do not trigger an auto-deploy. Most commonly used with a **monorepo**.

**Build Filters**  
Include or ignore specific paths in your repo when determining whether to trigger an auto-deploy. Paths are relative to your repo's root directory. [Learn more](#).

**Included Paths**  
Changes that match these paths will trigger a new build.  
+ Add Included Path

**Ignored Paths**  
Changes that match these paths will not trigger a new build.  
+ Add Ignored Path

**Registry Credential**  
If your service pulls private Docker images from a registry, specify a credential that can access those images. Manage your credentials in [Settings](#).

**Dockerfile Path**  
The path to your service's Dockerfile, relative to the repo root. Defaults to `./Dockerfile`.

**Docker Build Context Directory**  
The path to your service's **Docker build context**, relative to the repo root. Defaults to the root.

**Docker Command**  
Optionally override your Dockerfile's `CMD` and `ENTRYPOINT` instructions with a different command to start your service.

**Pre-Deploy Command** Optional  
Render runs this command before the start command. Useful for database migrations and static asset uploads.

General

Build & Deploy

Custom Domains

PR Previews

Edge Caching

Notifications

Health Checks

Maintenance Mode

Delete or suspend

**Auto-Deploy**  
By default, Render automatically deploys your service whenever you update its code or configuration. Disable to handle deploys manually. [Learn more.](#)

**Deploy Hook**  
Your private URL to trigger a deploy for this server. Remember to keep this a secret.

On Commit

.....

[Edit](#) [Regenerate hook](#)

### Custom Domains

You can point [custom domains](#) you own to this service. See [DNS configuration instructions](#).

+ Add Custom Domain

**Render Subdomain**  
If enabled, your service remains reachable at its `onrender.com` subdomain in addition to all custom domains. Disable to serve exclusively from custom domains.

Enabled

Your service is reachable at <https://review-scraping-service.onrender.com>.

### PR Previews

**Pull Request Previews**  
Spin up temporary instances to test pull requests opened against the `main` branch of `thesagor/review-scraping-service`. Choose `Automatic` to preview all PRs, or `Manual` for only PRs with `[render preview]` in their title. **Pull Request Previews** create a new instance for just this service. Use [Preview Environments](#) to clone a group of services for every PR.

Off

[Edit](#)

### Edge Caching

Serve static content at the edge to improve performance and reduce service load.

[Learn more.](#)

**Cacheable File Types**  
Specify which file types Render is allowed to cache for your service. You can fine-tune this behavior with `Cache-Control` headers.

None

[Edit](#)

**PAID** Edge Caching is only available for paid instances. [Upgrade](#)

### Notifications

**Service Notifications**  
Set notifications to receive for your service. This setting will override your workspace's default settings.

Use workspace default (Only failure notifications)

[Edit](#)

**Preview Environment Notifications**  
Configure notifications for [preview environments](#) and [service previews](#).

Use account default (Disabled)

[Edit](#)

### Health Checks

**Health Check Path**  
Provide an HTTP endpoint path that Render messages periodically to monitor your service. [Learn More](#).

/healthz

[Edit](#)

### Maintenance Mode

**Maintenance Mode**  
Temporarily disable public access to your service. While enabled, Render serves a static maintenance page for all incoming requests. [Learn more.](#)

Maintenance Mode Disabled

**Custom Maintenance Page** Optional  
If provided, Render uses the specified URL for your maintenance page instead of serving the [default page](#).

[Edit](#)

**PAID** Maintenance mode is only available for paid instances. [Upgrade](#)

 Delete Web Service

 Suspend Web Service