

Leetcode Problem 1. (Easy)

Roman to Integer

Roman numerals are represented by seven different symbols: I, V, X, L, C, D and M.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two ones added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

- I can be placed before V (5) and X (10) to make 4 and 9.
- X can be placed before L (50) and C (100) to make 40 and 90.
- C can be placed before D (500) and M (1000) to make 400 and 900.

Given a roman numeral, convert it to an integer.

Example 1:

Input: s = "III"

Output: 3

Explanation: III = 3.

Example 2:

Input: s = "LVIII"

Output: 58

Explanation: L = 50, V = 5, III = 3.

Example 3:

Input: s = "MCMXCIV"

Output: 1994

Explanation: M = 1000, CM = 900, XC = 90 and IV = 4.

Constraints:

- 1 <= s.length <= 15

- s contains only the characters ('I', 'V', 'X', 'L', 'C', 'D', 'M').
- It is **guaranteed** that s is a valid roman numeral in the range [1, 3999].

Link : <https://leetcode.com/problems/roman-to-integer/>

```
int result = 0;
int prevValue = 0;

for (int i = s.length() - 1; i >= 0; i--) {
    int currValue = getRomanValue(s.charAt(i));
    if (currValue < prevValue) {

        result -= currValue;
    } else {
        result += currValue;
    }
    prevValue = currValue;
}

return result;
}

private int getRomanValue(char c) {

    switch (c) {
        case 'I':
            return 1;
        case 'V':
            return 5;
        case 'X':
            return 10;
        case 'L':
            return 50;
        case 'C':
            return 100;
        case 'D':
            return 500;
    }
}
```

```
        case 'M':  
            return 1000;  
        default:  
            return 0;  
    }  
}  
}
```

LeetCode

< Problem List >

Premium

🕒 0 👤

Description Editorial Solutions (14.2K) Submissions

Accepted

Next question

14. Longest Common Prefix

More challenges

12. Integer to Roman

All statuses All languages

Accepted a few seconds ago Java

Close

Sakib Rahman Apr 13, 2023 00:01

Details + Solution

Java

Runtime 4 ms Beats 93.38% Memory 42.4 MB Beats 91.34%

Click the distribution chart to view more details

Notes

Write your notes here

Related Tags

Select tags 0/5

```
class Solution {  
    public int romanToInt(String s)  
    {  
  
        int result = 0;  
        int prevValue = 0;  
  
        for (int i = s.length() - 1; i >= 0; i--)  
        {  
            int currValue = getRomanValue(s.charAt(i));  
            if (currValue < prevValue)  
            {  
                result -= currValue;  
            }  
        }  
    }  
}
```

Console ^

Run Submit