

Analysis of Linux kernel as a complex network



Yichao Gao, Zheng Zheng*, Fangyun Qin

School of Automation Science and Electrical Engineering, Beihang University, Beijing 100191, China

ARTICLE INFO

Article history:

Received 17 June 2014

Accepted 14 October 2014

Available online 9 November 2014

ABSTRACT

Operating system (OS) acts as an intermediary between software and hardware in computer-based systems. In this paper, we analyze the core of the typical Linux OS, Linux kernel, as a complex network to investigate its underlying design principles. It is found that the Linux Kernel Network (LKN) is a directed network and its out-degree follows an exponential distribution while the in-degree follows a power-law distribution. The correlation between topology and functions is also explored, by which we find that LKN is a highly modularized network with 12 key communities. Moreover, we investigate the robustness of LKN under random failures and intentional attacks. The result shows that the failure of the large in-degree nodes providing basic services will do more damage on the whole system. Our work may shed some light on the design of complex software systems.

© 2014 Elsevier Ltd. All rights reserved.

1. Introduction

Many natural and technological systems, such as the Internet [1–3], social networks [4–6], biological networks [7–9], and airline networks [10–12], can be represented as complex networks. These networks consist of a set of nodes representing entities of the systems connected by edges indicating relationships between entities. In 1950s, Erdős and Rényi introduced the famous ER random network model [13], which has guided the research on complex networks for decades. Since the small-world network model [14] and scale-free network model [15] were proposed at the end of last century, it is found that many real-world networks are actually complex networks associated with small-world properties and power-law degree distributions. In recent years, the study of complex networks has attracted various scientific communities, such as network modeling [16–18], synchronization [19,20], cascading failures [21,22], evolutionary games [23–25], optimization [26], network traffic [27,28] and epidemic spreading [29,30]. One interesting research direction is to

explore software systems in the framework of complex network theory [31–33].

As the centerpiece of information world, software systems play more and more important roles in our daily life. How to build high quality software systems is one of our major concerns. In the last decades, the software engineering, whose objective is to provide methodologies and tools to efficiently design and build software systems [34], has been widely introduced. However, it remains a challenge to model software system due to its high complexity. Software systems are typical man-made systems which can be represented as networks. Valverde et al. [35] presented the first evidence for the emergence of scale-free and small-world structure in software networks. Cai and Yin [36] proposed the software mirror graph to record the runtime information of a software system under given environments. Gorshenev and Pis'mak [37] investigated the evolution of software systems and proposed a model representing the natural selection principle behind software evolution. The studies of software using graph methods are helpful to predict defects of software systems and to develop large software systems with well-designed structures.

Among various software systems, operating system (OS) is the foundation of other kind of software systems.

* Corresponding author.

E-mail address: zhengz@buaa.edu.cn (Z. Zheng).




Fig. 1. An illustration of function calls.

It provides interfaces to software and hardware, allowing users to communicate with computers. There are a lot of popular OSs such as Microsoft Windows, Linux, OS X, and UNIX, in which Linux is a well-known open source OS.¹ Thus, ever since it was first released by Linus Torvalds in 1991, Linux has been arousing millions of volunteers' interests to add, change and improve the system. Nowadays, it is a matured OS widely utilized, ranging from cell phones to supercomputers. In this paper, we will study the Linux system from the network point of view. For the high complexity of Linux, we focus on the kernel, which is the innermost part of Linux.

The rest of this paper is organized as follows. Section 2 presents LKN's topological properties to investigate the underlying design principles, followed by the analysis of LKN's community structures and its relationship with kernel's functional modules in Section 3. In Section 4, the robustness of LKN is discussed. Section 5 concludes this study.

2. Topological properties of LKN

Linux kernel consists of thousands of functions which collaborate with each other through function calls. For example, Fig. 1 illustrates the function call relationship among 5 functions: *foo1* calls *foo2* and *foo3*, *foo2* calls *foo4*, and *foo3* calls *foo5*. With functions as nodes and function calls as edges, the relationship among the 5 functions can be represented as a directed network. Note that, Linux is updated almost every 2 months and there have been hundreds of releases until now. In this research, we select the latest version (v3.12.6) as our object. We build up the LKN as a directed complex network and focus on its largest weakly connected component, which consist of 9334 nodes.

In LKN, the in-degree k_{in} of a node indicates the number of functions calling it, while the out-degree k_{out} represents the number of functions it calls. Table 1 shows some basic features of the LKN. To comparatively illustrate the features of the LKN, a randomized network with the same number of nodes and edges is constructed. During the process of randomization, self-connections and duplicated edges are avoided. From Table 1, it is clear to see that the LKN consists of 9334 nodes and 26841 edges and it is a sparse network with $k_{in} = k_{out} = 2.8756$. In Table 1, C is

Table 1

Comparisons between LKN and a randomized network. n : number of nodes; m : number of edges; $k_{in,max}$: maximum in-degree; $k_{out,max}$: maximum out-degree; $\langle k_{in} \rangle$: average in-degree; $\langle k_{out} \rangle$: average out-degree; C : clustering coefficient; R : reciprocity parameter; E : the efficiency. The data of randomized network are averaged by 10 realizations.

	LKN	Randomized network
n	9334	9334
m	26841	26841
$k_{in,max}$	415	11
$k_{out,max}$	92	11
$\langle k_{in} \rangle$	2.8756	2.8756
$\langle k_{out} \rangle$	2.8756	2.8756
C	0.0253	0.0003
R	−0.0003	−0.0001
E	0.0017	0.1071

the clustering coefficient, which is used to qualify a network's cluster tendency. It evaluates the extent to which the nodes in the neighborhood of a certain node are connected. Fagiolo [38] extended the clustering coefficient in a directed network as:

$$C = \frac{1}{2n} \sum_{i=1}^n \frac{\sum_j \sum_k (a_{ij} + a_{ji})(a_{ik} + a_{ki})(a_{jk} + a_{kj})}{(k_i^{in} + k_i^{out})(k_i^{in} + k_i^{out} - 1) - 2 \sum_j a_{ij} a_{ji}} \quad (1)$$

where k_i^{in} and k_i^{out} are the in-degree and out-degree of node i respectively, and $a_{ij} = 1$ if there exists an edge from i to j , otherwise $a_{ij} = 0$. We can find that the clustering coefficient of LKN is $C = 0.0253$, which is 84 times larger than the value ($C = 0.0003$) of the randomized network. Fig. 2 exhibits the correlation between clustering coefficient C and degrees (both k_{in} and k_{out}), we can find that the clustering coefficients are negatively correlated with k_{in} and k_{out} . It implies that the neighborhoods of the nodes with small degrees tend to cluster together.

In Table 1, R is a reciprocity parameter, which is used to qualify the symmetry of a network [39]. It can be formulated as follows:

$$R = \frac{\sum_{i \neq j}^n (a_{ij} - \bar{a})(a_{ji} - \bar{a})}{\sum_{i \neq j}^n (a_{ij} - \bar{a})^2} \quad (2)$$

where

$$\bar{a} = \frac{\sum_{i \neq j}^n a_{ij}}{n(n-1)} \quad (3)$$

Here, $a_{ij} = 1$ if and only if there exists an edge from i to j , otherwise $a_{ij} = 0$. The maximum of R is 1, implying that each edge in the network has a reverse mate. A small R indicates the high asymmetry of the network. Table 1 shows that the reciprocity parameter of LKN is $R = -0.0003$, which is smaller than the value ($R = -0.0001$) of a randomized network. Actually, LKN is an extremely asymmetric network without edge reversing each other, because there is no mutual function call between two functions in the kernel. As a result, it is hard to find a path back in LKN even though there are some loops. In the table, E evaluates the efficiency of information translation [40]. It is defined as

$$E = \frac{1}{n(n-1)} \sum_{i \neq j} \frac{1}{d_{ij}} \quad (4)$$

¹ Linux is open source software with GNU General Public License which provides users the freedom to run, copy, distribute, study, change and improve the software. Its source codes are available on www.kernel.org.




Fig. 2. (a) Correlation between k_{in} and C ; (b) correlation between k_{out} and clustering C .

where, d_{ij} is the length of shortest path between node i and j . If there is no path in the network between i and j , $d_{ij} = +\infty$. We can find that the efficiency of LKN is $E = 0.0017$, which is 63 times less than the value ($E = 0.1071$) of the randomized network. Obviously, the low efficiency of LKN is caused by its high asymmetry.

Fig. 3(a) and (b) exhibit the in-degree distribution and out-degree distribution, respectively. Degree distribution $P(k)$ gives the probability of randomly selected nodes having exactly k degrees. It reflects the basic information about a network's organization. From Fig. 3, we can find that both the in-degree and out-degree are quite heterogeneous: numerous nodes have small degrees (23.42% nodes with $k_{in} = 0$ and 32.12% nodes with $k_{out} = 0$), while only a few of nodes are densely connected (There are only 0.64% nodes with $k_{in} > 50$ and 0.02% nodes with $k_{out} > 50$). As shown in Table 1, the maximum in-degree and maximum out-degree in LKN are $k_{in,max} = 415$ and $k_{out,max} = 92$ respectively. They are much larger than those in a randomized network with same nodes and edges.

Although both the in-degree and out-degree are quite heterogeneous, they follow different distributions. The

in-degree follows a power-law distribution while the out-degree follows an exponential distribution. Compared with a randomized network, the maximum of k_{in} is much greater than the maximum of k_{out} in LKN. Its out-degree is more homogeneous than in-degree. The difference between the distributions mainly comes from the following reasons:

- (1) Small k_{out} : The complex functions with too many calls are less reliable and difficult to be maintained. Therefore, in the software development process, developers are less likely to use a complex function, but usually use several simpler functions instead. This principle limits the value of k_{out} .
- (2) Large k_{in} : In Linux kernel, lots of basic functions (e.g., system status checking) are widely called by various functions, resulting in large k_{in} values. This is determined by the design principles of operating systems.

Fig. 3(c) shows the relationship between k_{out} and k_{in} . We can see that k_{out} and k_{in} are negatively correlated, especially for large degree nodes. The maximal out-degree of




Fig. 3. (a) In-degree distribution of directed LKN; (b) out-degree distribution of directed LKN; (c) the correlation between k_{out} and k_{in} .

nodes with $k_{in} > 30$ (denoted by red circle) is only 5, while the maximal in-degree of nodes with $k_{out} > 30$ (denoted by blue triangle) is only 11. As discussed above, the large in-degree nodes represent the basic service functions and these functions rarely call other functions, resulting in the small value of k_{out} . In contrast, nodes with large k_{out} are actually related to high level functions, which directly exposed to users, thus they are rarely called by other functions.

3. Community characteristics of LKN

For a real networked system, its structure is usually closely related to its functions [41]. Linux is a typical modularized software system, each module of which performs a certain task. In this part, we will identify the modules and in further investigate their characteristics.

Community detection is widely adopted to identify the modules of networks. Newman et al. [42] defined *modularity* to evaluate the quality of a particular division of a network with the expectation that a random network does not have community structure. For a directed network, the modularity can be formulated as follows [43]:

$$Q = \frac{1}{m} \sum_{vw} \left[A_{vw} - \frac{k_v^{in} k_w^{out}}{m} \right] \delta(C_v, C_w) \quad (5)$$

where, m is the total number of edges in the network, A_{vw} is the adjacent matrix, k_v^{in} and k_w^{out} are the node v 's in-degree and node w 's out-degree respectively. $\delta(C_v, C_w) = 1$ if v and w are in the same community ($C_v = C_w$). To simplify the definition, let e_{ij} be the fraction of edges in the network connecting nodes in community i to those in community j , which can be formulated as:

$$e_{ij} = \frac{1}{m} \sum_{vw} A_{vw} \delta(C_v, i) \delta(C_w, j) \quad (6)$$

Thus, e_{ij} represents the edges that fall in the community i . Let a_i^{in} be the fraction of edges in the network that target to

the nodes in the community i , and a_j^{out} be the fraction of edges in the network that originate from the nodes in the community j respectively. They can be formulated as:

$$a_i^{in} = \frac{1}{m} \sum_v k_v^{in} \delta(C_v, i) \quad (7)$$

$$a_j^{out} = \frac{1}{m} \sum_w k_w^{out} \delta(C_w, j) \quad (8)$$

According to these, the modularity can be simplified as:

$$Q = \sum_i (e_{ii} - a_i^{in} a_i^{out}) \quad (9)$$

Based on the idea that a well division of a network should have large modularity, Newman proposed a greedy algorithm [44] to maximize the modularity so that one can achieve a suitable division. The inputs of the algorithm are n communities, each of which only has a single node. The algorithm recursively merges communities to get the maximal increase of Q at each step. The increase can be calculated as follows:

$$\Delta Q = e_{ij} + e_{ji} - (a_i^{in} a_j^{out} + a_i^{out} a_j^{in}) \quad (10)$$

By using sophisticated data structures, Clauset et al. [45] proposed a more efficient community detection algorithm for sparse graphs, called the fast modularity algorithm. In this section, we adopt the algorithm to investigate the module characteristics of LKN.

After executing the algorithm, we can identify 85 communities in LKN. Among them, there are 12 communities with more than 100 nodes, occupying 91.15% nodes of LKN, which we call key communities (Fig. 4). The key communities (C1 to C12) can be classified into 7 groups according to their functions. Table 2 lists the characteristics of the 12 communities. The different color is used to distinguish the 7 groups. We find that there are only two largest communities C1 and C2 with $l_{i,out} < l_{i,in}$. $l_{i,out}$ represents the ratio




Fig. 4. Connections among 12 key communities. The width of the edge represents the density of the connection between two communities.

Table 2

Key communities of LKN. $l_{i,in}$ is the ratio of edges target to community i and $l_{i,out}$ represents the ratio of edges originate from community i .

Community	Size	$l_{i,in}$	$l_{i,out}$	Related function
C1	2008	30.44%	23.09%	Basic services
C2	1817	28.01%	19.82%	
C3	1636	16.91%	19.23%	Process scheduler
C5	449	2.70%	5.15%	
C4	950	6.87%	8.89%	Trace system
C6	444	3.40%	3.71%	
C7	304	2.01%	2.79%	
C10	185	0.74%	2.12%	
C11	154	1.00%	2.28%	Runtime locking correctness validator
C12	115	0.88%	1.16%	Time functions
C8	226	1.13%	2.76%	Device management
C9	220	2.25%	2.49%	Interrupt mechanism

of edges originate from community i and $l_{i,in}$ is the ratio of edges target to community i . They are formulated as:

$$l_{i,out} = \frac{\sum_{j \neq i} e_{ij}}{\sum_i \sum_{j \neq i} e_{ij}} \quad (11)$$

$$l_{i,in} = \frac{\sum_{j \neq i} e_{ji}}{\sum_i \sum_{j \neq i} e_{ij}} \quad (12)$$

The functions in a community with $l_{i,out} < l_{i,in}$ are more likely to be called in the system than to call other functions. By analyzing source codes, we find that most functions in C1 and C2 provide basic services widely used in the kernel. So we can infer that C1 and C2 are the foundation of the LKN. The functions in C3 and C5 perform the main task of the kernel which is to schedule the processes. The functions in C4, C6, C7 and C10 are assistant functions to trace system status. With the help of the useful information, developers can trace the system and find out the system defects conveniently and efficiently. The functions in C8, C9, C11 and C12 are also necessary for the operation of kernel. C8 refers to the runtime locking correctness validator which is used to guarantee the security of system resources. C9 is related to the time functions and C11 manages system devices. C12 refers to the interrupt mechanism which is used to communicate with the devices.

4. Robustness of LKN

In this section, we will investigate the robustness of LKN according to the mechanism of software failures. Robustness of a network refers to the ability to avoid crash when a fraction of its nodes or edges fail. It is an important property of many real and complicate systems such as Internet [46] and power grids [47].

For a complex software system, Voas [48] proposed the PIE model to examine the mechanism of software failures. When a program fails, it is certain to say that at least one fault exists. However, the existence of a fault does not guarantee the failure of the program. To turn a fault into an observable failure, firstly the faulty statements must

be executed. After that, the system should show some unexpected behaviors. Furthermore, the abnormal states need to be propagated in the system till the users notice them. Considering these, the *Execution* of faults, *Infection* of system and *Propagation* of abnormal states are necessary conditions to cause the failure of a program. For i -th function in a program, let P_i denote the propagation probability of its abnormal states, I_i the probability that it is infected and E_i the probability that at least one fault in the function has been executed. Thus, we have:

$$P_i = p I_i \quad (13)$$

$$I_i = E_i + \bar{E}_i \left(1 - \prod_{h \neq i} a_{ji} \bar{P}_h \right) \quad (14)$$

$$\bar{P}_i = 1 - P_i \quad (15)$$

$$\bar{E}_i = 1 - E_i \quad (16)$$

where $p \in [0, 1]$ is a parameter to specify the propagation probability of abnormal states, and $a_{ji} = 1$ if and only if function j is called by i (otherwise $a_{ji} = 0$). Obviously, once a node of LKN fails, it may lead to cascading effect. Fig. 5 shows a mini illustration of the process. At first, the system works well (Fig. 5 (a)). Then node f failed due to error or attack factor (Fig. 5 (b)), resulting in the cascading failure of node e and d (Fig. 5 (c)). Finally, node a is infected (Fig. 5 (d)).




Fig. 5. An illustration of function failure propagation. (a): original network. (b) Some faults in the function f were executed. (c) The abnormal behaviors of f are propagated with probability p . e and d are infected (d) function a is infected further.




Fig. 6. The impacts of three cases. f is the initial fraction of failed nodes; p is the propagation probability of abnormal states; $G = n'/n$ is the relative size of largest weakly connected component, where n and n' are the number of nodes in largest weakly connected components before and after removing failed nodes respectively; $I = 1/n \sum_i I_i$ is the infection probability of the nodes in LKN. Each data is averaged over 10 independent experiments. (a) The relationship of I and f , $p = 0.2$; (b) the relationship of I and p , $f = 0.1$; (c) the relationship of G and f , $p = 0.2$; (d) the relationship of G and p , $f = 0.1$.

The infection probability I is the evaluation standard of system reliability. The larger the value of I is, the higher risk the system will have. From Fig. 6(a), we can see that the value of I grows as the initial fraction of failure nodes f increases under the three failure strategies: random failure, k_{out} and k_{in} based intentional attacks. Among the three cases, the k_{in} based intentional attack brings the network highest risk. As discussed above, the nodes with large k_{in} usually relate to the functions providing basic services. The failure of these nodes will induce more severe propagation in the system. On the contrary, the nodes with large k_{out} usually relate to high level functions which are rarely called, and thus the k_{out} based intentional attack can hardly induce cascading failures. Fig. 6(b) shows the infection probability I as the function of p . It is clear that the value of I also monotonously increases with the increment of p for all the three cases. Besides, the nodes are most likely to fail under the k_{in} based intentional attack, while they are least likely to fail under the k_{out} based intentional attack. From the discussion of f and p , we can infer that the faults in basic functions can bring the whole system high risk to fail.

We further investigate the network robustness of LKN. Fig. 6(c) shows the relative size G as the function of f . We can find that the network is robust against random failure, but is vulnerable when facing intentional attacks. Specifically, the network soon breakdown as f increase under the k_{in} based intentional attack. Fig. 6(d) shows the relationship of G and p . It is obvious that the network becomes more and more vulnerable as p increase. Again, the network is most fragile when facing the k_{in} based intentional attack. These

phenomena indicate that the network is extremely vulnerable under the k_{in} based intentional attack.

5. Conclusion

In this paper, we study the Linux kernel from the network point of view to investigate the underlying principles of operating system. It is found that the LKN's out-degree is more homogeneous than its in-degree. Community detection shows that LKN is a highly modularized network with 12 key communities. They can be classified into 7 groups, and each group refers to a particular mechanism of the Linux kernel. Moreover, the robustness of LKN is examined according to PIE model. We find that the failure of the nodes with large in-degree do more damage on the whole system. This work is helpful in understanding complex software systems.

Acknowledgements

The authors would like to thank Dr. Wen-Bo Du from Beihang University for kindly providing valuable technical advices to this manuscript.

References

- [1] Albert R, Jeong H, Barabási A-L. Internet: diameter of the world-wide web. *Nature* 1999;401:130.
- [2] Pastor-Satorras R, Vázquez A, Vespignani A. Dynamical and correlation properties of the internet. *Phys Rev Lett* 2001;87:258701.
- [3] Vázquez A, Pastor-Satorras R, Vespignani A. Large-scale topological and dynamical properties of the Internet. *Phys Rev E* 2002;65:066130.

- [4] Newman MEJ. Scientific collaboration networks I Network construction and fundamental results. *Phys Rev E* 2001;64:016131.
- [5] Borgatti SP, Mehra A, Brass DJ, Labianca G. Network analysis in the social sciences. *Science* 2009;323:892.
- [6] Schweitzer F, Fagiolo G, Sornette D, Vega-Redondo F, Vespignani A, White DR. Economic networks: the new challenges. *Science* 2009;325:422.
- [7] Spirin V, Mirny LA. Protein complexes and functional modules in molecular networks. *Proc Nat Acad Sci USA* 2003;100:12123.
- [8] Barabási A-L, Oltvai ZN. Network biology: understanding the cell's functional organization. *Nat Rev Genet* 2004;5:101.
- [9] Bullmore E, Sporns O. Complex brain networks: graph theoretical analysis of structural and functional systems. *Nat Rev Neurosci* 2009;10:186.
- [10] Barrat A, Barthélemy M, Pastor-Satorras R, Vespignani A. The architecture of complex weighted networks. *Proc Nat Acad Sci USA* 2004;101:3747.
- [11] Guimerà R, Mossa S, Turtschi A, Amaral LAN. The worldwide air transportation network: Anomalous centrality, community structure, and cities' global roles. *Proc Natl Acad Sci USA* 2005;102:7794.
- [12] Zhang J, Cao X-B, Du W-B, Cai K-Q. Evolution of chinese airport network. *Physica A* 2010;389:3922.
- [13] Erdős P, Rényi A. On random graphs I. *Pub Math Debrecen* 1959;6:290.
- [14] Watts DJ, Strogatz SH. Collective dynamics of 'small-world' networks. *Nature* 1998;393:440.
- [15] Barabási A-L, Albert R. Emergence of scaling in random networks. *Science* 1999;286:509.
- [16] Wang W-X, Wang B-H, Hu B, Yan G, Ou Q. General dynamics of topology and traffic on weighted technological networks. *Phys Rev Lett* 2005;94:188702.
- [17] Barrat A, Barthélemy M, Vespignani A. Weighted evolving networks: coupling topology and weight dynamics. *Phys Rev Lett* 2004;92:228701.
- [18] Zhou T, Yan G, Wang B-H. Maximal planar networks with large clustering coefficient and power-law degree distribution. *Phys Rev E* 2005;71:046141.
- [19] Arenas A, Díaz-Guilera A, Kurths J, Moreno Y, Zhou C-S. Synchronization in complex networks. *Phys Rep* 2008;469:93.
- [20] Yan G, Chen G-R, Lu J-H, Fu Z-Q. Synchronization performance of complex oscillator networks. *Phys Rev E* 2009;80:056116.
- [21] Wang W-X, Lai Y-C. Abnormal cascading on complex networks. *Phys Rev E* 2009;80:036109.
- [22] Cao X-B, Hong C, Du W-B, Zhang J. Improving the network robustness against cascading failures by adding links. *Chaos Solitons Fractals* 2013;57:35.
- [23] Szabó G, Fáth G. Evolutionary games on graphs. *Phys Rep* 2007;446:97.
- [24] Du W-B, Cao X-B, Hu M-B, Wang W-X. Asymmetric cost in snowdrift game on scale-free networks. *Europhys Lett* 2009;87:60004.
- [25] Wang Z, Szolnoki A, Perc M. Optimal interdependence between networks for the evolution of cooperation. *Sci Rep* 2013;3:2470.
- [26] Liu C, Du W-B, Wang W-X. Particle swarm optimization with scale-free Interactions. *PLoS One* 2014;9:e97822.
- [27] Yan G, Zhou T, Hu B, Fu Z-Q, Wang B-H. Efficient routing on complex networks. *Phys Rev E* 2006;73:046108.
- [28] Du W-B, Wu Z-X, Cai K-Q. Effective usage of shortest paths promotes transportation efficiency on scale-free networks. *Physica A* 2013;392:3505.
- [29] Pastor-Satorras R, Vespignani A. Epidemic spreading in scale-free networks. *Phys Rev Lett* 2001;86:3200.
- [30] Yang H-X, Wang W-X, Lai Y-C, Xie Y-B, Wang B-H. Control of epidemic spreading on complex networks by local traffic dynamics. *Phys Rev E* 2011;84:045101.
- [31] Myers CR. Software systems as complex networks: Structure, function, and evolvability of software collaboration graphs. *Phys Rev E* 2003;68:046116.
- [32] Concas G, Marchesi M, Pinna S, Serra N. Power-laws in a large object-oriented software system. *IEEE Trans Softw Eng* 2007;33:687.
- [33] Louridas P, Spinellis D, Vlachos V. Power laws in software. *ACM Trans Softw Eng Method* 2008;18:2.
- [34] Pressman RS. *Software Engineering: A Practitioner's Approach*. seventh ed. New York: McGraw-Hill; 2010.
- [35] Valverde S, Cancho RF, Solé RV. Scale-free networks from optimal design. *Europhys Lett* 2002;60:512.
- [36] Cai K-Y, Yin B-B. Software execution processes as an evolving complex network. *Inf Sci* 2009;179:1903.
- [37] Gorshenev AA, Pis'mak YM. Punctuated equilibrium in software evolution. *Phys Rev E* 2004;70:067103.
- [38] Fagiolo G. Clustering in complex directed networks. *Phys Rev E* 2007;76:026107.
- [39] da Rocha LEC. Structural evolution of the Brazilian airport network. *J Stat Mech* 2009;04:P04020.
- [40] Latora V, Marchiori M. Efficient behavior of small-world networks. *Phys Rev Lett* 2001;87:198701.
- [41] Newman MEJ. The structure and function of complex networks. *SIAM Rev* 2003;45:167.
- [42] Newman MEJ, Girvan M. Finding and evaluating community structure in networks. *Phys Rev E* 2004;69:026113.
- [43] Leicht E, Newman MEJ. Community structure in directed networks. *Phys Rev Lett* 2008;100:118703.
- [44] Newman MEJ. Fast algorithm for detecting community structure in networks. *Phys Rev E* 2004;69:066133.
- [45] Clauset A, Newman MEJ, Moore C. Finding community structure in very large networks. *Phys Rev E* 2004;70:066111.
- [46] Albert R, Jeong H, Barabási A-L. Error and attack tolerance of complex networks. *Nature* 2000;406:378.
- [47] Motter AE, Lai Y-C. Cascade-based attacks on complex networks. *Phys Rev E* 2002;66:065102.
- [48] Voas JM. PIE: a dynamic failure-based technique. *IEEE Trans Softw Eng* 1992;18:717.