$$\frac{\partial L}{\partial w_{11}^1} = \frac{\partial L}{\partial \hat{y}}\left[\frac{\partial \hat{y}}{\partial o_{21}} \times \frac{\partial o_{21}}{\partial o_{11}} \times \frac{\partial o_{11}}{\partial w_{11}^1} + \frac{\partial \hat{y}}{\partial o_{22}} \times \frac{\partial o_{22}}{\partial o_{11}} \times \frac{\partial o_{11}}{\partial w_{11}^1}\right]$$

↳ Very complex with only 2 hidden layers

Backpropagatn → chain diff (rule) + Memorization

↓ Maths ↓ CS (OP)

↳ Store the derivatives while calculated one time.

Vanishing Gradient Problem

less in fewer layer networks
.VGD is affected mostly in deep layer networks

In ML, the vanishing gradient problem is encountered when training ANNs with GD and backpropagation. In such methods, during each iteration of train each of the NN's weights receives an update proportional to the partial derivative of the error function w.r.t. the current weight. In worst case, this may stop the training of NN.

gradient
layer4->0.5
layer 3->0.05
layer2->0.05
layer 1->0.0005

1) $0.1 \times 0.1 \times 0.1 \times 0.1 = 0.0001$ → VGP.

2) Deep NN →

early layers affected more as gradient needs to travel further during backpropagation

3) Sigmoid/tanh → Activatn fn →

Back prop. 

$\hat{y} - y = L$

$w_\eta = w_0 - \eta\left[\frac{\partial L}{\partial w_0}\right]$ → derivative of the L wrt w

$$\frac{\partial L}{\partial w_{11}^1} = \frac{\partial L}{\partial \hat{y}} \times \frac{\partial \hat{y}}{\partial z} \times \frac{\partial z}{\partial o_{11}} \times \frac{\partial o_{11}}{\partial w_{11}^1}$$

↑ $0<x<1$ ↑ $0<x<1$

$w_\eta = 1 - 0.01 \times 0.0001$ (η ↑)

$w_\eta = 0.99999$

↳ did not changed

0.0001



too many layers.

$\frac{\partial L}{\partial w_{11}^1} = 0.000000001$

↳ Stop training.

(Skips connection)
Bypassing one or more layers

How to recognize VGP?

1) Loss focus → epoch → no changes → VGP
2) weights → graph
3) Gradient ->graph

keras → loss after every epoch



How to handle Vanishing Gradient Problem?

1) Reduce model complexity

 → Problem cannot find complex patterns

2) Using ReLU Activation functions

max (0, z)





dying relu → derivative $w_\eta = w_0$

{Leaky relu}

3) Proper weight initialization → Glorot / Xavier.

4) Batch normalization → Layer. pg 25

normalizing ii/p of each layer with constant mean and variance

5) Residual Network → CNN → ResNET

↳ Building Block → ANN

Opposite of VGD

Exploding Gradient Problems. → RNN

$w \times 10 \times 10 \ldots \rightarrow w = 1000000 \ldots$ (very large)

↑ >1 ↑ >1 ↑ >1

Solution
-Gradient clipping
-lower learning rate
-weight regularization(l1,L2)
-Gradient Normalization

layer 4->2.0
layer 3->4.0
layer 2->8.0
layer 1->16.0

Scanned with OKEN Scanner
Scanned with OKEN Scanner