

Edge-AI Based Distributed Fleet Coordination for Autonomous Mobile Robots

PS ID: 26123 | Organization: Bharat Electronics Limited | Theme: Smart Automation

1. THE OFFICIAL PROBLEM STATEMENT

Modern smart warehouses heavily rely on autonomous mobile robots (AMRs) to move goods efficiently. Historically, the orchestration of these fleets has been dictated by a central "brain" or server. However, as the number of robots increases, this centralized approach creates critical bottlenecks.

THE CORE CHALLENGE

The objective is to shift from a **Centralized** to a **Decentralized (Edge-based)** architecture. Instead of a master server tracking and directing every robot, robots must communicate directly with one another, share intent, avoid collisions in real-time, and adapt their paths locally without waiting for cloud instructions.

KEY TERMINOLOGY

- **AMR (Autonomous Mobile Robot):** Modern robotics using onboard sensors (LiDAR, cameras) to dynamically navigate around obstacles, unlike older AGVs which follow fixed floor tracks.
- **Edge-AI:** Processing AI models physically close to where data is generated (e.g., on a Raspberry Pi onboard the robot) rather than sending data to a central cloud server.


2. THE STRUCTURAL FLAW: WHY IS THIS A PROBLEM?

In traditional warehouse systems, robots constantly ping a central Wi-Fi router to send their position and receive their next waypoint. At scale, this centralized architecture suffers from three fatal flaws:

- **Network Latency & Throughput Drops:** If hundreds of robots query the central server simultaneously at a busy intersection, server response times lag. Robots must temporarily stop to avoid collisions, drastically reducing operational speed.

- **Wi-Fi Dead-zones & Traffic Jams:** Metal racks in warehouses cause severe signal interference. When a robot enters a dead-zone and loses server connection, safety protocols force an emergency stop (E-stop), blocking aisles and causing traffic jams behind it.
- **Single Point of Failure:** If the central server crashes or the main router goes down, the entire warehouse ceases operation.

SYSTEM ARCHITECTURE: CENTRALIZED VS. DECENTRALIZED



3. HOW INDUSTRY LEADERS TACKLE THIS

Global logistics giants handle fleets of thousands of robots. Analyzing their software architecture gives profound insight into the scale of this problem.

A. Amazon Robotics

- **Software Architecture:** Amazon historically uses a centralized grid-based approach. The cloud server treats the floor like a giant chessboard and uses CBS (Conflict-Based Search) algorithms to reserve tiles for specific robots in future time-steps.
- **Communication:** Relies entirely on highly maintained, expensive, high-bandwidth industrial Wi-Fi.

B. Alibaba (Cainiao Network)

- **Software Architecture:** Cainiao utilizes a hybrid model. The central server assigns "macro-tasks" (e.g., "Go to Aisle 12"), but they increasingly rely on Edge-AI for "micro-navigation".
- **Sensor Fusion:** If a box blocks a path, the robot's local AI detects it, stops, and calculates a small detour without waiting for central server input.

MAPF (MULTI-AGENT PATH FINDING)

The mathematical problem of finding paths for multiple robots without colliding. As fleet sizes grow, calculating this centrally becomes exponentially more difficult (NP-hard). Edge computing distributes this math across the fleet.

4. INDUSTRY STRUGGLES & LIMITATIONS

Despite massive budgets, major corporations face severe challenges that directly validate the need for a decentralized approach:

Challenge Area	The Real-World Issue	Root Cause
Compute Bottlenecks	Re-routing thousands of robots takes massive centralized server power.	Because MAPF is NP-hard, a single blocked aisle forces the server to simultaneously recalculate overlapping paths for hundreds of robots.
The "Traffic Jam" Effect	One offline robot can halt an entire warehouse sector.	If a robot loses Wi-Fi, it stops. Other centrally-controlled robots cannot locally "negotiate" with the dead robot, resulting in cascading physical deadlocks.
Infrastructure Costs	Millions spent on private networking gear.	To prevent dead-zones in metal warehouses, companies must install dense, private 5G/Wi-Fi mesh networks—an unfeasible cost for medium-sized businesses.

Conclusion: To bypass these struggles, the industry is shifting computing power to the **Edge**. Empowering robots with local decision-making and direct peer-to-peer (P2P) communication allows fleets to operate fluidly, regardless of warehouse internet stability.