

TECHNISCHE UNIVERSITÄT DRESDEN

FAKULTÄT INFORMATIK

INSTITUT FÜR SOFTWARE- UND MULTIMEDIATECHNIK

PROFESSUR FÜR COMPUTERGRAPHIK UND VISUALISIERUNG

PROF. DR. STEFAN GUMHOLD

Diplomarbeit

zur Erlangung des akademischen Grades
Diplom-Informatiker

Validierung einer Gathering-Strategie zur Szenendiskretisierung für Partikeldaten im Kontext der Berechnung von ambienter Verdeckung

Maximilian Richter

(Geboren am 8. April 1993 in Schleiz, Mat.-Nr.: 3802290)

Betreuer: Dipl.-Medieninf. Joachim Staib

Dresden, 19. Dezember 2017

Aufgabenstellung

Selbstständigkeitserklärung

Hiermit erkläre ich, dass ich die von mir am heutigen Tag dem Prüfungsausschuss der Fakultät Informatik eingereichte Arbeit zum Thema:

*Validierung einer Gathering-Strategie zur Szenendiskretisierung für Partikeldaten im Kontext der
Berechnung von ambienter Verdeckung*

vollkommen selbstständig verfasst und keine anderen als die angegebenen Quellen und Hilfsmittel benutzt sowie Zitate kenntlich gemacht habe.

Dresden, den 19. Dezember 2017

Maximilian Richter

Kurzfassung

Abstract

Inhaltsverzeichnis

1	Introduction	2
1.1	Motivation	2
1.2	Task	2
1.3	Outline	2
2	Related Work	4
3	Gathering Voxelization	5
4	Ambient Occlusion	6
4.1	Voxel Cone Tracing	6
4.2	Ray Casting	6
5	Implementation	7
5.1	Gathering Voxelization	7
5.2	Ambient Occlusion	7
5.3	Voxel Cone Tracing	7
5.4	Ray Casting	7
6	Results	8
6.1	Evaluation	8
6.2	Discussion	8
7	Conclusion	9
	Literaturverzeichnis	10

1 Introduction

1.1 Motivation

Global illumination allows to visualize complex structures in particle data, that would otherwise remain unseen. Ambient occlusion mimics indirect diffuse light by calculating the level of occlusion for visible surfaces. The calculation of the ambient terms is costly, but several methods exist to approximate it. One of them, Voxel Cone Tracing, uses an discretized voxel representation of the geometry. This requires a method to transfer particles into a voxel grid. Scattering iterates all particles and adds their partial contributions to the intersected voxels. Parallel scattering processes the particles simultaneously, leading to race conditions whenever multiple spheres intersect the same voxel. Synchronization has to assure correct summation of the contributions. As synchronization increases, parallelism decreases. Therefore scattering performs the worse, the more dense the particle data is.

1.2 Task

To find a particle voxelization technique that better fits the parallel nature of graphics processing units a gathering approach is validated. Gathering determines for each voxel which particles it intersects with. For efficient particle search around voxels an acceleration data structure is required. Starting from an unordered list of particles an algorithm is designed to first build a hashed uniform grid and then use it to calculate the voxel densities. To compare the gathering approach against scattering the construction time is measured for multiple particle clouds of variable density. The created voxel data structure is used to calculate ambient occlusion using voxel cone tracing. To evaluate the quality of the proposed solution a ground truth renderer using ray-casting is implemented.

1.3 Outline

The work is organized as follows. In chapter 2 related works are discussed. First concerning acceleration data structures on particles, followed by voxelization techniques and finally ambient occlusion for

particle data.

Chapter 3 presents the proposed gathering based voxelization technique.

Chapter 4 details the techniques used to calculate ambient occlusion.

In chapter 5 implementation details are given.

Chapter 6 finally presents the results of the work.

2 Related Work

3 Gathering Voxelization

4 Ambient Occlusion

4.1 Voxel Cone Tracing

cone tracing idea + cone approximation with voxels construction of hierarchy

4.2 Ray Casting

idea + hemisphere sampling ray sphere intersection math

5 Implementation

5.1 Gathering Voxelization

5.2 Ambient Occlusion

5.3 Voxel Cone Tracing

-> hemisphere of n cones per frame -> variable cone size + variable voxel grid size for comparison

5.4 Ray Casting

-> GPU Pathtracer on spheres -> progressive pipeline -> also on voxels for comparison

6 Results

6.1 Evaluation

1. Qualitativ

VCT on standard resolution grid - ray tracing on particle data -> Fehlerquellen:

VCT on high resolution grid -> voxelization error

Ray casting/Fine cones on voxel grid -> cone tracing error

2. Quantitativ

Scattering vs Gathering Performance + Speicherverbrauch

6.2 Discussion

7 Conclusion

Literaturverzeichnis